



US009788751B2

(12) **United States Patent**
Li et al.

(10) **Patent No.:** **US 9,788,751 B2**
(45) **Date of Patent:** **Oct. 17, 2017**

(54) **METHODS AND SYSTEMS FOR
GENERATING INTEGRATED SUBSTRATE
MAPS FOR CARDIAC ARRHYTHMIAS**

(71) Applicant: **St. Jude Medical, Cardiology
Division, Inc.**, St. Paul, MN (US)

(72) Inventors: **Wenwen Li**, San Jose, CA (US); **Erhan
Erdemir**, Maplewood, MN (US);
Valtino Afonso, Oakdale, MN (US);
Carlo Pappone, Cernusco Lombardone
(IT); **Dennis Morgan**, Crystal, MN
(US)

(73) Assignee: **St. Jude Medical, Cardiology
Division, Inc.**, St. Paul, MN (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/884,545**

(22) Filed: **Oct. 15, 2015**

(65) **Prior Publication Data**

US 2016/0106336 A1 Apr. 21, 2016

Related U.S. Application Data

(60) Provisional application No. 62/063,989, filed on Oct.
15, 2014.

(51) **Int. Cl.**
A61B 5/05 (2006.01)
A61B 5/053 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 5/0536** (2013.01); **A61B 5/0422**
(2013.01); **A61B 5/0452** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61B 5/04; A61B 5/72; A61B 5/74; A61B
6/03; A61B 18/14; G06T 7/00; G06F
19/32

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,697,377 A 12/1997 Wittkampf
5,983,126 A 11/1999 Wittkampf
(Continued)

FOREIGN PATENT DOCUMENTS

EP 2638853 9/2013
WO 2007/024983 3/2007
(Continued)

OTHER PUBLICATIONS

Greenhut, SE et al., "Comparison of new template matching algo-
rithm, correlation, and area of difference methods for detection of
ventricular tachycardia", Computers in cardiology, pp. 371-374,
Oct. 1992.

(Continued)


Primary Examiner — Ankit D Tejani

(74) *Attorney, Agent, or Firm* — Wiley Rein LLP

(57) **ABSTRACT**

An electrophysiology map, for example a map of arrhythmic
substrate, can be generated by acquiring both geometry
information and electrophysiology information pertaining to
an anatomical region, and associating the acquired geometry
and electrophysiology information as a plurality of electro-
physiology data points. A user can select two (or more)
electrophysiological characteristics for display, and can fur-
ther elect to apply various filters to the selected electro-
physiological characteristics. The user can also define vari-
ous relationships (e.g., Boolean ANDs, ORs, and the like)
between the selected and/or filtered characteristics. The
user-selected filtering criteria can be applied to the electro-
physiology data points to output various subsets thereof.
These subsets can then be graphically rendered using vari-
ous combinations of colorscale, monochrome scale, and
iconography, for example as a three-dimensional cardiac
electrophysiology model.

12 Claims, 13 Drawing Sheets



- (51) **Int. Cl.**
A61B 5/042 (2006.01)
A61B 5/0452 (2006.01)
A61B 5/0408 (2006.01)
A61B 5/00 (2006.01)
- (52) **U.S. Cl.**
 CPC *A61B 5/04087* (2013.01); *A61B 5/0538*
 (2013.01); *A61B 5/7225* (2013.01); *A61B*
5/7485 (2013.01); *A61B 5/725* (2013.01);
A61B 5/743 (2013.01); *A61B 5/746* (2013.01);
A61B 2505/05 (2013.01)
- (56) **References Cited**
- U.S. PATENT DOCUMENTS
- | | | | |
|--------------|----|---------|-----------------|
| 6,301,496 | B1 | 10/2001 | Reisfeld |
| 6,368,285 | B1 | 4/2002 | Osadchy et al. |
| 6,640,119 | B1 | 10/2003 | Budd et al. |
| 6,728,562 | B1 | 4/2004 | Budd et al. |
| 6,939,309 | B1 | 9/2005 | Beatty et al. |
| 6,947,785 | B1 | 9/2005 | Beatty et al. |
| 6,978,168 | B2 | 12/2005 | Beatty et al. |
| 6,990,370 | B1 | 1/2006 | Beatty et al. |
| 7,263,397 | B2 | 8/2007 | Hauck et al. |
| 7,515,954 | B2 | 4/2009 | Harlev et al. |
| 7,885,707 | B2 | 2/2011 | Hauck |
| 7,937,136 | B2 | 5/2011 | Harlev et al. |
| 7,957,792 | B2 | 6/2011 | Harlev et al. |
| 8,103,338 | B2 | 1/2012 | Harlev et al. |
| 8,428,700 | B2 | 4/2013 | Harlev et al. |
| 9,220,435 | B2 | 12/2015 | Deno |
| 9,474,491 | B2 | 10/2016 | Li et al. |
| 2005/0192972 | A1 | 9/2005 | Daignault |
| 2007/0197929 | A1 | 8/2007 | Porath et al. |
| 2008/0085042 | A1 | 4/2008 | Trofimov et al. |
- | | | | |
|--------------|-----|---------|---------------------------------------|
| 2008/0221425 | A1 | 9/2008 | Olson et al. |
| 2009/0275826 | A1 | 11/2009 | Shachar et al. |
| 2010/0021031 | A1* | 1/2010 | Brockway G06K 9/3233
382/128 |
| 2010/0130882 | A1 | 5/2010 | Nakada et al. |
| 2011/0118590 | A1 | 5/2011 | Zhang |
| 2011/0144510 | A1 | 6/2011 | Ryu et al. |
| 2011/0184488 | A1 | 7/2011 | De Ridder |
| 2011/0206256 | A1 | 8/2011 | Ramanathan et al. |
| 2012/0108994 | A1 | 5/2012 | Patel et al. |
| 2012/0130267 | A1 | 5/2012 | Harlev et al. |
| 2012/0184858 | A1 | 7/2012 | Harlev et al. |
| 2012/0184863 | A1 | 7/2012 | Harlev et al. |
| 2012/0265054 | A1 | 10/2012 | Olson |
| 2013/0241929 | A1 | 9/2013 | Massarwa et al. |
| 2014/0200467 | A1 | 7/2014 | Strom et al. |
| 2014/0200874 | A1 | 7/2014 | Zeng et al. |
| 2015/0157267 | A1 | 6/2015 | Shushan et al. |
| 2015/0228254 | A1 | 8/2015 | Olson |
| 2016/0242667 | A1 | 8/2016 | Fay et al. |
- FOREIGN PATENT DOCUMENTS
- | | | |
|----|-------------|--------|
| WO | 2010/054320 | 5/2010 |
| WO | 2012/092016 | 7/2012 |
- OTHER PUBLICATIONS
- Kindlmann, G., Superquadric Tensor Glyphs, Joint Joint EUROGRAPHICS—IEEE TCVG Symposium on Visualization, 2004.
- Krasteva, Vessels et al., “QRS template matching for recognition of ventricular ectopic beats”, Annals of biomedical engineering, vol. 35, No. 12, pp. 2065-2076, Dec. 2007.
- * cited by examiner




FIG.1




FIG.2




FIG. 3




FIG. 4a




FIG. 4b




FIG. 4c




FIG. 4d




FIG.5a




FIG. 5b




FIG. 5c




FIG. 6a




FIG. 6b




FIG. 7a




FIG. 7b




FIG. 8a




FIG. 8b




FIG.9b




FIG.9a




FIG.10

1

METHODS AND SYSTEMS FOR GENERATING INTEGRATED SUBSTRATE MAPS FOR CARDIAC ARRHYTHMIAS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. provisional application No. 62/063,989, filed 15 Oct. 2014, which is hereby incorporated by reference as though fully set forth herein.

BACKGROUND

The instant disclosure relates to anatomical mapping. In particular, the instant disclosure relates to systems, apparatuses, and methods for creating electrophysiology maps, such as may be useful in cardiac diagnostic and therapeutic procedures.

Two mainstay hypotheses of arrhythmia maintenance mechanisms are single source focus and circus movement reentry. However, the mechanisms and substrates that maintain atrial fibrillation can vary from patient-to-patient. Thus, there is a need for apparatuses, systems, and methods that facilitate the identification, classification, and characterization of multiple arrhythmic mechanisms and substrates.

BRIEF SUMMARY

Disclosed herein is a method of generating an electrophysiology map, including: acquiring geometry information pertaining to an anatomical region, the geometry information including position information for a plurality of points in the anatomical region; acquiring electrophysiology information pertaining to the anatomical region, the electrophysiology information including a plurality of electrophysiological characteristics of the anatomical region; associating the geometry information with the electrophysiology information as a plurality of electrophysiology ("EP") data points; accepting user input to select a first electrophysiological characteristic of the plurality of electrophysiological characteristics and a first filtering criterion for the first electrophysiological characteristic; accepting user input to select a second electrophysiological characteristic of the plurality of electrophysiological characteristics and a second filtering criterion for the second electrophysiological characteristic; applying the first filtering criterion and the second filtering criterion to the plurality of EP data points; and outputting a subset of the plurality of EP data points satisfying both the first filtering criterion and the second filtering criterion. For example, the first electrophysiological characteristic can be cycle length mean and the second electrophysiological characteristic can be cycle length standard deviation. Similarly, the first filtering criterion can be a band pass filter with a pass band from 110 ms to 290 ms (e.g., between about 150 ms and about 250 ms), and the second filtering criterion can be a band pass filter with a pass band from 1 ms to 30 ms.

In other embodiments, the first and second electrophysiological characteristics and their respective filtering criteria can be selected from the following pairings of electrophysiological characteristics and filtering criteria: fractionation index and a high pass filter; peak-to-peak voltage and a low pass filter; electrogram sharpness and a high pass filter; conduction velocity consistency index and a high pass filter; and conduction velocity and a low pass filter.

It is also contemplated that a three-dimensional graphical representation of the subset of the plurality of EP data points

2

can be output. For example, a user can provide input to prioritize the first electrophysiological characteristic and the second electrophysiological characteristic, such that the graphical representation of the subset of the plurality of EP data points is rendered according to the prioritization of the first electrophysiological characteristic and the second electrophysiological characteristic (e.g., with higher priority electrophysiological characteristics drawn preferentially to lower priority electrophysiological characteristics at any given point on the graphical representation).

Also disclosed herein is a method of generating an electrophysiology map, including: acquiring geometry information pertaining to an anatomical region, the geometry information including position information for a plurality of points in the anatomical region; acquiring electrophysiology information pertaining to the anatomical region, the electrophysiology information including a plurality of electrophysiological characteristics of the anatomical region; associating the geometry information with the electrophysiology information as a plurality of electrophysiology ("EP") data points; accepting user input to select a first electrophysiological characteristic of the plurality of electrophysiological characteristics, a first filtering criterion for the first electrophysiological characteristic, and a first priority for the first electrophysiological characteristic; applying the first filtering criterion to the plurality of EP data points to output a first subset of the plurality of EP data points satisfying the first filtering criterion; accepting user input to select a second electrophysiological characteristic of the plurality of electrophysiological characteristics, a second filtering criterion for the second electrophysiological characteristic, and a second priority for the second electrophysiological characteristic; applying the second filtering criterion to the plurality of EP data points to output a second subset of the plurality of EP data points satisfying the second filtering criterion; outputting a three-dimensional graphical representation of the first and second subsets of the plurality of EP data points according to the first priority and the second priority. For example, outputting a three-dimensional graphical representation of the first and second subsets of the plurality of EP data points according to the first priority and the second priority can include: rendering the graphical representation of the first subset of the plurality of EP data points preferentially to the graphical representation of the second subset of the plurality of data points if the first priority is higher than the second priority; and rendering the graphical representation of the second subset of the plurality of EP data points preferentially to the graphical representation of the first subset of the plurality of data points if the second priority is higher than the first priority. The graphical representations of the first and second subsets of the plurality of EP data points can be rendered using various combinations of colorscale, monochrome scale, and iconography.

It should also be understood that the teachings herein are not limited to two subsets of the plurality of EP data points, and can be extended to any number of electrophysiological characteristics and/or filters. Thus, for example, according to certain aspects of the disclosure, the method can further include: accepting user input to select a third electrophysiological characteristic of the plurality of electrophysiological characteristics, a third filtering criterion for the third electrophysiological characteristic, and a third priority for the third electrophysiological characteristic; applying the third filtering criterion to the plurality of EP data points to output a third subset of the plurality of EP data points satisfying the third filtering criterion; and outputting a three-dimensional graphical representation of the third sub-

set of the plurality of EP data points according to the third priority. As with the first and second subsets of the plurality of EP data points, the third subset of the plurality of EP data points can likewise be output using various combinations of colorscale, monochrome scale, and iconography (e.g., one of the graphical representations of the first, second, and third subsets of the plurality of EP data points can be output in colorscale while the other two of the graphical representations of the first, second, and third subsets are output in monochrome scale).

According to yet another aspect disclosed herein, a system for generating an electrophysiology map includes: an electrophysiology data point processor configured to accept as input geometry information and electrophysiology information pertaining to an anatomical region and to associate the geometry information with the electrophysiology information as a plurality of electrophysiology data points; a filtering processor configured to accept as input a user's selection of *n* electrophysiological characteristics, wherein each of the *n* selected electrophysiological characteristics has an associated filtering criterion and an associated priority, and to apply the filtering criteria to their respective ones of the *n* selected electrophysiological characteristics; and a mapping processor configured to output a three-dimensional representation of the filtered *n* selected electrophysiological characteristics according to their respective priorities.

The foregoing and other aspects, features, details, utilities, and advantages of the present invention will be apparent from reading the following description and claims, and from reviewing the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic of an electrophysiology system, such as may be used in an electrophysiology study.

FIG. 2 depicts an exemplary multi-electrode catheter used in an electrophysiology study.

FIG. 3 is a flowchart of representative steps that can be followed to create an electrophysiology map.

FIGS. 4a through 4d illustrate the application of the EP data point filtering teachings herein to maps of cycle length mean and cycle length standard deviation.

FIGS. 5a through 5c illustrate the application of the EP data point filtering and electrophysiology map combination teachings herein with reference to cycle length mean and cycle length standard deviation.

FIGS. 6a and 6b illustrate the application of the EP data point filtering teachings herein to a map of fractionation index.

FIGS. 7a and 7b illustrate the application of the EP data point filtering teachings herein to a map of conduction velocity.

FIGS. 8a and 8b illustrate the application of the EP data point filtering and electrophysiology map combination teachings herein to a map of the magnitude, direction, and consistency of local conduction velocity.

FIGS. 9a and 9b illustrate the application of the display prioritization teachings herein to a map of cycle length mean, cycle length standard deviation, and peak-to-peak voltage.

FIG. 10 is another electrophysiology map that illustrates the display prioritization teachings herein.

DETAILED DESCRIPTION

The present disclosure relates to the collection and storage of data used to create anatomical maps and to the display of

anatomical maps from the data so collected and stored, and provides methods, apparatuses, and systems for the storage and display of anatomical maps. As used herein, the term "anatomical map" refers to a graphical representation of an anatomical region that includes both a geometric model of the anatomical region and biological information of the anatomical region. For example, the biological information can be superimposed upon the geometric model. As used herein, the term "superimposed" means that the biological information is displayed over the geometric model and can, in some embodiments, be incorporated into the geometric model. In other embodiments, the biological information is not part of the geometric model itself, but rather "hovers" as an overlay upon the geometric model.

Electrophysiology maps, such as those that can be created using system 8 described below, are one type of anatomical map. For purposes of illustration, several exemplary embodiments will be described in detail herein in the context of a cardiac electrophysiology procedure, including the creation of cardiac electrophysiology maps. It is contemplated, however, that the methods, apparatuses, and systems disclosed herein can be utilized in other contexts.

Electrophysiology maps are generally created from a plurality of electrophysiology ("EP") data points, each of which includes both electrophysiology data (e.g., endocardial and/or epicardial electrograms ("EGMs")) and location data (e.g., information regarding the location of the apparatus (e.g., catheter and/or catheter-mounted electrodes) collecting the electrophysiology data, allowing the electrophysiology information to be associated with a particular location in space (that is, allowing the electrophysiology information to be interpreted as indicative of electrical activity at a point on the patient's heart). Insofar as the ordinarily skilled artisan will be familiar with various modalities for the acquisition and processing of EP data points (including, for example, both contact and non-contact electrophysiological mapping), as well as with various techniques that can be used to generate a graphical representation from the plurality of EP data points, these aspects will only be described herein to the extent necessary to understand the present disclosure.

FIG. 1 shows a schematic diagram of an electrophysiology system 8 for conducting cardiac electrophysiology studies by navigating a cardiac catheter and measuring electrical activity occurring in a heart 10 of a patient 11 and three-dimensionally mapping the electrical activity and/or information related to or representative of the electrical activity so measured. System 8 can be used, for example, to create an anatomical model of the patient's heart 10 using one or more electrodes. System 8 can also be used to measure electrophysiology data, including various morphological characteristics, at a plurality of points along a cardiac surface and store the measured data in association with location information for each measurement point at which the electrophysiology data was measured, for example to create a diagnostic data map of the patient's heart 10.

As one of ordinary skill in the art will recognize, and as will be further described below, system 8 can determine the location, and in some aspects the orientation, of objects, typically within a three-dimensional space, and express those locations as position information determined relative to at least one reference.

For simplicity of illustration, the patient 11 is depicted schematically as an oval. In the embodiment shown in FIG. 1, three sets of surface electrodes (e.g., patch electrodes) are shown applied to a surface of the patient 11, defining three generally orthogonal axes, referred to herein as an x-axis, a

y-axis, and a z-axis. In other embodiments the electrodes could be positioned in other arrangements, for example multiple electrodes on a particular body surface. As a further alternative, the electrodes do not need to be on the body surface, but could be positioned internally to the body or on an external frame.

In FIG. 1, the x-axis surface electrodes **12, 14** are applied to the patient along a first axis, such as on the lateral sides of the thorax region of the patient (e.g., applied to the patient's skin underneath each arm) and may be referred to as the Left and Right electrodes. The y-axis electrodes **18, 19** are applied to the patient along a second axis generally orthogonal to the x-axis, such as along the inner thigh and neck regions of the patient, and may be referred to as the Left Leg and Neck electrodes. The z-axis electrodes **16, 22** are applied along a third axis generally orthogonal to both the x-axis and the y-axis, such as along the sternum and spine of the patient in the thorax region, and may be referred to as the Chest and Back electrodes. The heart **10** lies between these pairs of surface electrodes **12/14, 18/19, and 16/22**.

An additional surface reference electrode (e.g., a "belly patch") **21** provides a reference and/or ground electrode for the system **8**. The belly patch electrode **21** may be an alternative to a fixed intra-cardiac electrode **31**, described in further detail below. It should also be appreciated that, in addition, the patient **11** may have most or all of the conventional electrocardiogram ("ECG" or "EKG") system leads in place. In certain embodiments, for example, a standard set of 12 ECG leads may be utilized for sensing electrocardiograms on the patient's heart **10**. This ECG information is available to the system **8** (e.g., it can be provided as input to computer system **20**). Insofar as ECG leads are well understood, and for the sake of clarity in the figures, only one lead **6** and its connection to computer system **20** is illustrated in FIG. 1.

A representative catheter **13** having at least one electrode **17** (e.g., a distal electrode) is also depicted in schematic fashion in FIG. 1. This representative catheter electrode **17** can be referred to as a "measurement electrode" or a "roving electrode." Typically, multiple electrodes on catheter **13**, or on multiple such catheters, will be used. In one embodiment, for example, system **8** may utilize sixty-four electrodes on twelve catheters disposed within the heart and/or vasculature of the patient.

In other embodiments, system **8** may utilize a single catheter that includes multiple (e.g., eight) splines, each of which in turn includes multiple (e.g., eight) electrodes. Of course, these embodiments are merely exemplary, and any number of electrodes and catheters may be used. Indeed, in some embodiments, a high density mapping catheter, such as the EnSite™ Array™ non-contact mapping catheter of St. Jude Medical, Inc., can be utilized.

Likewise, it should be understood that catheter **13** (or multiple such catheters) are typically introduced into the heart and/or vasculature of the patient via one or more introducers and using familiar procedures. For purposes of this disclosure, a segment of an exemplary multi-electrode catheter **13** is shown in FIG. 2. In FIG. 2, catheter **13** extends into the left ventricle **50** of the patient's heart **10** through a transeptal sheath **35**. The use of a transeptal approach to the left ventricle is well known and will be familiar to those of ordinary skill in the art, and need not be further described herein. Of course, catheter **13** can also be introduced into the heart **10** in any other suitable manner.

Catheter **13** includes electrode **17** on its distal tip, as well as a plurality of additional measurement electrodes **52, 54,**

56 spaced along its length in the illustrated embodiment. Typically, the spacing between adjacent electrodes will be known, though it should be understood that the electrodes may not be evenly spaced along catheter **13** or of equal size to each other. Since each of these electrodes **17, 52, 54, 56** lies within the patient, location data may be collected simultaneously for each of the electrodes by system **8**. Similarly, each of electrodes **17, 52, 54,** and **56** can be used to gather electrophysiological data from the cardiac surface.

Returning now to FIG. 1, in some embodiments, a fixed reference electrode **31** (e.g., attached to a wall of the heart **10**) is shown on a second catheter **29**. For calibration purposes, this electrode **31** may be stationary (e.g., attached to or near the wall of the heart) or disposed in a fixed spatial relationship with the roving electrodes (e.g., electrodes **17, 52, 54, 56**), and thus may be referred to as a "navigational reference" or "local reference." The fixed reference electrode **31** may be used in addition or alternatively to the surface reference electrode **21** described above. In many instances, a coronary sinus electrode or other fixed electrode in the heart **10** can be used as a reference for measuring voltages and displacements; that is, as described below, fixed reference electrode **31** may define the origin of a coordinate system.

Each surface electrode is coupled to a multiplex switch **24**, and the pairs of surface electrodes are selected by software running on a computer **20**, which couples the surface electrodes to a signal generator **25**. Alternately, switch **24** may be eliminated and multiple (e.g., three) instances of signal generator **25** may be provided, one for each measurement axis (that is, each surface electrode pairing).

The computer **20**, for example, may comprise a conventional general-purpose computer, a special-purpose computer, a distributed computer, or any other type of computer. The computer **20** may comprise one or more processors **28**, such as a single central processing unit (CPU), or a plurality of processing units, commonly referred to as a parallel processing environment, which may execute instructions to practice the various aspects disclosed herein.

Generally, three nominally orthogonal electric fields are generated by a series of driven and sensed electric dipoles (e.g., surface electrode pairs **12/14, 18/19,** and **16/22**) in order to realize catheter navigation in a biological conductor. Alternatively, these orthogonal fields can be decomposed and any pairs of surface electrodes can be driven as dipoles to provide effective electrode triangulation. Likewise, the electrodes **12, 14, 18, 19, 16,** and **22** (or any other number of electrodes) could be positioned in any other effective arrangement for driving a current to or sensing a current from an electrode in the heart. For example, multiple electrodes could be placed on the back, sides, and/or belly of patient **11**. For any desired axis, the potentials measured across the roving electrodes resulting from a predetermined set of drive (source-sink) configurations may be combined algebraically to yield the same effective potential as would be obtained by simply driving a uniform current along the orthogonal axes.

Thus, any two of the surface electrodes **12, 14, 16, 18, 19, 22** may be selected as a dipole source and drain with respect to a ground reference, such as belly patch **21**, while the unexcited electrodes measure voltage with respect to the ground reference. The roving electrodes **17, 52, 54, 56** placed in the heart **10** are exposed to the field from a current pulse and are measured with respect to ground, such as belly patch **21**. In practice the catheters within the heart **10** may contain more or fewer electrodes than the four shown, and

each electrode potential may be measured. As previously noted, at least one electrode may be fixed to the interior surface of the heart to form a fixed reference electrode **31**, which is also measured with respect to ground, such as belly patch **21**, and which may be defined as the origin of the coordinate system relative to which localization system **8** measures positions. Data sets from each of the surface electrodes, the internal electrodes, and the virtual electrodes may all be used to determine the location of the roving electrodes **17**, **52**, **54**, **56** within heart **10**.

The measured voltages may be used by system **8** to determine the location in three-dimensional space of the electrodes inside the heart, such as roving electrodes **17**, **52**, **54**, **56**, relative to a reference location, such as reference electrode **31**. That is, the voltages measured at reference electrode **31** may be used to define the origin of a coordinate system, while the voltages measured at roving electrodes **17**, **52**, **54**, **56** may be used to express the location of roving electrodes **17**, **52**, **54**, **56** relative to the origin. In some embodiments, the coordinate system is a three-dimensional (x, y, z) Cartesian coordinate system, although other coordinate systems, such as polar, spherical, and cylindrical coordinate systems, are contemplated.

As should be clear from the foregoing discussion, the data used to determine the location of the electrode(s) within the heart is measured while the surface electrode pairs impress an electric field on the heart. The electrode data may also be used to create a respiration compensation value used to improve the raw location data for the electrode locations as described in U.S. Pat. No. 7,263,397, which is hereby incorporated herein by reference in its entirety. The electrode data may also be used to compensate for changes in the impedance of the body of the patient as described, for example, in U.S. Pat. No. 7,885,707, which is also incorporated herein by reference in its entirety.

In one representative embodiment, the system **8** first selects a set of surface electrodes and then drives them with current pulses. While the current pulses are being delivered, electrical activity, such as the voltages measured with at least one of the remaining surface electrodes and in vivo electrodes, is measured and stored. Compensation for artifacts, such as respiration and/or impedance shifting, may be performed as indicated above.

In some embodiments, system **8** is the EnSite™ Velocity™ cardiac mapping and visualization system of St. Jude Medical, Inc., which generates electrical fields as described above, or another such system that relies upon electrical fields. Other systems, however, may be used in connection with the present teachings, including for example, the CARTO navigation and location system of Biosense Webster, Inc., the AURORA® system of Northern Digital Inc., or Stereotaxis' NIOBE® Magnetic Navigation System, all of which utilize magnetic fields rather than electrical fields. The localization and mapping systems described in the following patents (all of which are hereby incorporated by reference in their entireties) can also be used with the present invention: U.S. Pat. Nos. 6,990,370; 6,978,168; 6,947,785; 6,939,309; 6,728,562; 6,640,119; 5,983,126; and 5,697,377.

FIG. **3** is a flowchart of representative steps that can be carried out to create an electrophysiology map. Advantageously, the electrophysiology maps disclosed herein can depict multiple variables (e.g., multiple cardiac electrophysiological characteristics) by location (e.g., according to their position on the surface of the heart). In some embodiments, the flowchart may represent several exemplary steps that can be carried out by the computer **20** of FIG. **1** (e.g., by one or more processors **28**) to generate an electrophysi-

ology map. It should be understood that the representative steps described below can be either hardware- or software-implemented. For the sake of explanation, the term "signal processor" is used herein to describe both hardware- and software-based implementations of the teachings herein.

In block **302**, geometry information pertaining to an anatomical region (e.g., a heart chamber) is acquired. The acquired geometry information includes position information (e.g., Cartesian coordinates) for a plurality of points in the anatomical region.

The geometry can be acquired in numerous ways, many of which will be familiar to the person of ordinary skill in the art. For example, in certain aspects, system **8** is used to gather a plurality of location points that define the geometry of the anatomical region; the plurality of location points can then be used to create a model of the anatomical region. In other aspects, an external imaging modality, such as magnetic resonance imaging ("MRI"), computed tomography ("CT"), positron emission tomography ("PET"), ultrasound imaging, single-photon emission computed tomography ("SPECT"), or the like is used. It is also contemplated that multiple geometries can be acquired from multiple imaging modalities. Where multiple geometries are acquired, they can be fused or registered to a common coordinate system, for example as disclosed in U.S. application Ser. No. 11/715,923, filed 9 Mar. 2007, and/or U.S. application Ser. No. 13/087,203, filed 14 Apr. 2011, both of which are hereby incorporated by reference as though fully set forth herein.

Further, the geometry information can be time-varying. For example, cardiac geometry will vary over time with the beating of the heart. Thus, rather than acquiring a single geometry at a single point in time (e.g., max systole or max diastole), a plurality of time-varying geometries can be captured, such as by segmenting multiple phases from volumetric images captured by an MRI or CT system. These time-varying geometries can be used to create an animated geometric model of the anatomical region.

In block **304**, electrophysiology information pertaining to the anatomical region is acquired. The electrophysiology information includes a plurality of electrophysiological characteristics of the anatomical region. Just as there are numerous ways to acquire the geometry information in block **302**, so too are there numerous ways to acquire the electrophysiology information in block **304**. For example, system **8** (e.g., electrodes **17**, **52**, **54**, and **56** on catheter **13**) can be used to measure electrical activity on the surface of the patient's heart **10**. The electrophysiology information can also be time-varying.

In block **306**, the geometry information acquired in block **302** is associated with the electrophysiology information acquired in block **304**. For example, electrophysiology measurements made by electrodes **17**, **52**, **54**, **56** can be associated with the position of catheter **13** at the time the measurements were made. As another example, electrophysiology measurements can be associated with locations within a CT model after the CT model has been registered to the coordinate frame of system **8**. This creates a plurality of electrophysiology data points that can then be stored, for example in the memory of computer system **20**, for use in the creation (and manipulation) of anatomical maps.

As mentioned above, the ordinarily skilled artisan will be familiar with numerous electrophysiology maps. For example, maps of conduction velocity and/or consistency index, such as disclosed in U.S. provisional application No. 62/063,987, filed 15 Oct. 2014, which is hereby incorporated by reference as though fully set forth herein, are both electrophysiology maps. Other electrophysiology maps

include, without limitation, complex fractionated electrogram ("CFE") maps (e.g., maps of cycle length mean and cycle length standard deviation), fractionation index maps, peak-to-peak voltage maps, lateness maps (e.g., Late-P and Late-A), local activation time ("LAT") maps, and electrogram ("EGM") sharpness maps.

It is known to show a single electrophysiological characteristic per electrophysiology map. However, with the proliferation of electrophysiological characteristics that may be of interest to a practitioner during an electrophysiology study, a one-characteristic-per-map approach can become cumbersome.

Likewise, it is known to display a full range of values for an electrophysiological characteristic on an electrophysiology map (e.g., displaying peak-to-peak voltages from the lowest value measured within the anatomical region to the highest value measured within the anatomical region). This requires the presentation scale (e.g., color scale, monochrome scale, or other graphical convention) to be spread over a relatively large range. A practitioner may, however, be interested only in a narrower range of values for the electrophysiological characteristic. For example, U.S. patent application Ser. No. 14/504,174, filed 1 Oct. 2014 and hereby incorporated by reference as though fully set forth herein, describes the use of upper and lower bounds on the use of a presentation scale for lateness attributes.

According to an aspect of the instant disclosure, multiple electrophysiology characteristics can be presented on a single electrophysiology map. According to another aspect of the instant disclosure, the user can set various filters (e.g., high-pass, low-pass, band-pass, band-reject) on the presentation of the electrophysiological characteristics, such that only certain ranges of values for given electrophysiological characteristics are displayed.

Thus, in steps 308a, 308b, respectively, a user can select a first electrophysiology characteristic (e.g., cycle length mean) and a second electrophysiology characteristic (e.g., cycle length standard deviation) to display in an electrophysiology map.

Similarly, in steps 310a, 310b, respectively, the user can set first and second filter criteria corresponding, respectively, to the selected first and second electrophysiology characteristics. For example, the user can choose to apply a band-pass filter of 150 ms to 250 ms to the CFE cycle length mean and a band-pass filter of 1 ms to 30 ms to the CFE cycle length standard deviation.

The selected filters are applied to the plurality of EP data points in block 312. In certain aspects, the output of the filters is a subset of the plurality of EP data points that meet both the filtering criteria set in blocks 310a, 310b. That is, the filters can be applied to the plurality of EP data points with a Boolean AND. In other aspects, the output of the filters is a subset of the plurality of EP data points that meet either of the filtering criteria set in blocks 310a, 310b. That is, the filters can be applied to the plurality of EP data points with a Boolean OR. It is also contemplated that the application of the filters can yield two subsets: a first subset that satisfies the first filtering criterion of block 310a and a second subset that satisfies the second filtering criterion of block 310b.

An electrophysiology map is rendered in block 314. The electrophysiology map is a graphical representation of the subset of the plurality of EP data points that results from the application of the first and second filters in block 312. Thus, for example, the acquired geometry (or geometries) can be rendered graphically (e.g., using techniques that are familiar

to those of ordinary skill in the art), and a map of the electrophysiology characteristics, post-filtering, can be superimposed thereon.

FIGS. 4a through 4d and 5a through 5c illustrate the foregoing teachings. FIG. 4a is a traditional cycle length mean map without a filter applied, while FIG. 4b applies a band-pass filter having a pass band of 170 ms to 250 ms to the map of FIG. 4a. Similarly, FIG. 4c is a traditional cycle length standard deviation map without a filter applied, while FIG. 4d applies a band-pass filter having a pass band of 1 ms to 40 ms to the map of FIG. 4c.

As can be seen by comparing FIGS. 4a and 4c, on the one hand, to FIGS. 4b and 4d, on the other hand, only the regions having values of interest are mapped in FIGS. 4b and 4d. The same range of colorscale values is thus applied over a narrower numerical range in FIGS. 4b and 4d than in FIGS. 4a and 4c, allowing a more refined presentation in FIGS. 4b and 4d relative to FIGS. 4a and 4c (that is, more subtle variations in the depicted electrophysiological characteristic can be depicted in FIGS. 4b and 4d than in FIGS. 4a and 4c).

Turning now to FIGS. 5a through 5c, suppose that a practitioner is interested in identifying regions of cardiac tissue that exhibit fast and regular activation. Such regions could, for example, be defined as regions that exhibit both a cycle length mean between 150 ms and 250 ms and a cycle length standard deviation between 1 ms and 30 ms. FIG. 5a, therefore, is an exemplary electrophysiology map that graphically presents only those EP data points meeting both criteria (i.e., EP data points having a cycle length mean between 150 ms and 250 ms and a cycle length standard deviation between 1 ms and 30 ms). The advantages of such a presentation are similar to those discussed above with respect to FIGS. 4a-4d. In particular, FIG. 5b illustrates the types of EP data points that are included in the map of FIG. 5a (that is, EP data points that exhibit electrophysiological characteristics of interest to the practitioner), while FIG. 5c illustrates the types of EP data points that are excluded in the map of FIG. 5c (that is, EP data points that do not exhibit electrophysiological characteristics of interest to the practitioner).

It should be understood that FIGS. 4a-4d and 5a-5c are merely exemplary of the present teachings. In other embodiments, a user might select the following electrophysiology characteristics and associated filters:

Using a high pass filter and a map of fractionation index to identify areas with high fractionation, which may be critical substrates for the perpetuation of atrial fibrillation, and thus desirable targets for ablation to treat the same (compare FIG. 6a with FIG. 6b);

Using a low pass filter and a map of peak-to-peak voltage to identify areas with low peak-to-peak voltage; areas of low voltage can indicate fibrosis or scarring, which can serve as a substrate for arrhythmia maintenance;

Using a high pass filter and a map of electrogram sharpness to identify areas with high sharpness, which might be indicative of an ectopic focus;

Using a high pass filter and a map of conduction velocity consistency index to identify regions where the direction of the propagating activation wavefront is highly consistent, which can highlight a wavefront circuit in an atrial arrhythmia; and/or

Using a low pass filter and a map of conduction velocity to identify regions of slow conduction; because slow conduction is a hallmark of maintaining a reentrant circuit, the regions identified by such a map can be

11

targeted for ablation therapy in the treatment of ventricular tachycardia ("VT") (compare FIG. 7a with FIG. 7b).

Of course, even this list of embodiments is non-exhaustive, and the person of ordinary skill in the art would readily appreciate how to extend the teachings herein to additional electrophysiology maps and combinations of electrophysiology maps.

Similarly, various conventions can be used to present the various combinations of electrophysiology maps discussed herein. For example, various combinations of full color and monochrome scales (e.g., grey scale, brown scale) can be used in the display of electrophysiology maps. Various iconography can also be used. For example, FIGS. 8a (unfiltered) and 8b (high pass filtered for consistency index) illustrate the use of arrowheads to depict activation direction (direction of arrow), local conduction velocity (length of arrow), and consistency index (width of arrow). In an alternative embodiment, a zig-zag line can be used instead of an arrowhead to represent conduction velocity, with a tighter zig-zag reflecting a lower conduction velocity. Still other methods of presenting electrophysiology maps are disclosed in U.S. provisional application No. 61/936,954, filed 7 Feb. 2014, which is hereby incorporated by reference as though fully set forth herein.

Where multiple different electrophysiology characteristics are to be displayed on a single electrophysiology map, the user can assign priorities to the various characteristics. Once the characteristics are prioritized, any regions of overlap can be rendered according to the relative priorities of the characteristics, with higher priority characteristics drawn preferentially to lower priority characteristics. Stated another way, if a particular EP data point includes data for multiple electrophysiology characteristics that satisfy the user-specified filters, the EP data point will be displayed with the highest priority electrophysiology characteristic.

For example, FIG. 9a is similar to FIG. 5a in that it depicts a map of EP data points that have been band pass filtered for cycle length mean and standard deviation. In FIG. 9b, a low pass filtered peak-to-peak map is added to the map of FIG. 9a, with the peak-to-peak map having a higher priority. Thus, where the two maps overlap (that is, where EP data points satisfy both the cycle length and peak-to-peak filters), the peak-to-peak map is drawn instead of the cycle length map (see region 900).

FIG. 10 is another exemplary prioritized electrophysiology map. The map of FIG. 10 includes as the highest priority a low pass filtered peak-to-peak map, as the next highest priority a high pass filtered fractionation index map, and as the lowest priority a band pass filtered map of cycle length mean and standard deviation as described above. FIG. 10 also includes conduction velocity arrows that have been high pass filtered for consistency index and star icons indicative of focal activity as identified using high pass filtered sharpness data.

Although several embodiments of this invention have been described above with a certain degree of particularity, those skilled in the art could make numerous alterations to the disclosed embodiments without departing from the spirit or scope of this invention.

For example, although the electrophysiology maps disclosed herein have been described in the context of a two-characteristic (and, similarly, two-filter) map, the ordinarily skilled artisan will appreciate how to extend the teachings herein to any n-characteristic and/or n-filter map, where n is an integer greater than 1.

12

As another example, although some of the filtering methods described above are applied with Boolean ANDs and Boolean ORs, the teachings herein could be adapted to other relationships between characteristics (e.g., filtered characteristic one AND NOT (filtered characteristic two OR filtered characteristic three)).

All directional references (e.g., upper, lower, upward, downward, left, right, leftward, rightward, top, bottom, above, below, vertical, horizontal, clockwise, and counterclockwise) are only used for identification purposes to aid the reader's understanding of the present invention, and do not create limitations, particularly as to the position, orientation, or use of the invention. Joinder references (e.g., attached, coupled, connected, and the like) are to be construed broadly and may include intermediate members between a connection of elements and relative movement between elements. As such, joinder references do not necessarily infer that two elements are directly connected and in fixed relation to each other.

It is intended that all matter contained in the above description or shown in the accompanying drawings shall be interpreted as illustrative only and not limiting. Changes in detail or structure may be made without departing from the spirit of the invention as defined in the appended claims.

What is claimed is:

1. A method of generating an electrophysiology map, comprising:

acquiring geometry information pertaining to an anatomical region, the geometry information comprising position information for a plurality of points in the anatomical region;

acquiring electrophysiology information pertaining to the anatomical region, the electrophysiology information comprising a plurality of electrophysiological characteristics of the anatomical region;

associating the geometry information with the electrophysiology information as a plurality of electrophysiology ("EP") data points;

accepting user input to select a first electrophysiological characteristic of the plurality of electrophysiological characteristics and a first filtering criterion for the first electrophysiological characteristic;

accepting user input to select a second electrophysiological characteristic of the plurality of electrophysiological characteristics and a second filtering criterion for the second electrophysiological characteristic;

applying the first filtering criterion and the second filtering criterion to the plurality of EP data points;

outputting a subset of the plurality of EP data points satisfying both the first filtering criterion and the second filtering criterion;

accepting user input prioritizing the first electrophysiological characteristic and the second electrophysiological characteristic; and

outputting a three-dimensional graphical representation of the subset of the plurality of EP data points,

wherein the three-dimensional graphical representation includes both the first electrophysiological characteristic and the second electrophysiological characteristic, and

wherein a higher priority electrophysiological characteristic of the first and second electrophysiological characteristics is rendered preferentially to and to the exclusion of a lower priority electrophysiological characteristic of the first and second electrophysiological characteristics in regions of overlap between the

first electrophysiological characteristic and the second electrophysiological characteristic.

2. The method according to claim 1, wherein the first electrophysiological characteristic comprises cycle length mean and the second electrophysiological characteristic comprises cycle length standard deviation.

3. The method according to claim 2, wherein the first filtering criterion comprises a band pass filter with a pass band from 110 ms to 290 ms and second filtering criterion comprises a band pass filter with a pass band from 1 ms to 30 ms.

4. The method according to claim 1, wherein the first electrophysiological characteristic and the first filtering criterion respectively comprise one of: fractionation index and a high pass filter; peak-to-peak voltage and a low pass filter; electrogram sharpness and a high pass filter; conduction velocity consistency index and a high pass filter; and conduction velocity and a low pass filter.

5. The method according to claim 4, wherein the second electrophysiological characteristic and the second filtering criterion respectively comprise one of: fractionation index and a high pass filter; peak-to-peak voltage and a low pass filter; electrogram sharpness and a high pass filter; conduction velocity consistency index and a high pass filter; and conduction velocity and a low pass filter, and wherein the second electrophysiological characteristic and the second filtering criterion differ, respectively, from the first electrophysiological characteristic and the first filtering criterion.

6. A method of generating an electrophysiology map, comprising:

acquiring geometry information pertaining to an anatomical region, the geometry information comprising position information for a plurality of points in the anatomical region;

acquiring electrophysiology information pertaining to the anatomical region, the electrophysiology information comprising a plurality of electrophysiological characteristics of the anatomical region;

associating the geometry information with the electrophysiology information as a plurality of electrophysiology ("EP") data points;

accepting user input to select a first electrophysiological characteristic of the plurality of electrophysiological characteristics, a first filtering criterion for the first electrophysiological characteristic, and a first priority for the first electrophysiological characteristic;

applying the first filtering criterion to the plurality of EP data points to output a first subset of the plurality of EP data points satisfying the first filtering criterion;

accepting user input to select a second electrophysiological characteristic of the plurality of electrophysiological characteristics, a second filtering criterion for the second electrophysiological characteristic, and a second priority for the second electrophysiological characteristic;

applying the second filtering criterion to the plurality of EP data points to output a second subset of the plurality of EP data points satisfying the second filtering criterion;

outputting a three-dimensional graphical representation of the first and second subsets of the plurality of EP data points according to the first priority and the second priority such that, in regions of overlap between the first and second subsets of the plurality of EP data points, a higher priority subset of the first and second subsets of the plurality of EP data points is rendered

preferentially to and to the exclusion of a lower priority subset of the plurality of EP data points.

7. The method according to claim 6, wherein outputting a three-dimensional graphical representation of the first and second subsets of the plurality of EP data points according to the first priority and the second priority comprises:

rendering the graphical representation of the first subset of the plurality of EP data points preferentially to the graphical representation of the second subset of the plurality of data points if the first priority is higher than the second priority; and

rendering the graphical representation of the second subset of the plurality of EP data points preferentially to the graphical representation of the first subset of the plurality of data points if the second priority is higher than the first priority.

8. The method according to claim 6, wherein outputting a three-dimensional graphical representation of the first and second subsets of the plurality of EP data points according to the first priority and the second priority comprises:

rendering the graphical representation of the first subset of the plurality of data points using a colorscale; and rendering the graphical representation of the second subset of the plurality of data points using a monochrome scale.

9. The method according to claim 6, wherein outputting a three-dimensional graphical representation of the first and second subsets of the plurality of EP data points according to the first priority and the second priority comprises:

rendering the graphical representation of the first subset of the plurality of data points using one of a colorscale and a monochrome scale; and

rendering the graphical representation of the second subset of the plurality of data points using iconography.

10. The method according to claim 6, further comprising: accepting user input to select a third electrophysiological characteristic of the plurality of electrophysiological characteristics, a third filtering criterion for the third electrophysiological characteristic, and a third priority for the third electrophysiological characteristic;

applying the third filtering criterion to the plurality of EP data points to output a third subset of the plurality of EP data points satisfying the third filtering criterion; and outputting a three-dimensional graphical representation of the third subset of the plurality of EP data points according to the third priority.

11. The method according to claim 10, wherein one of the graphical representations of the first, second, and third subsets of the plurality of EP data points is output in colorscale and two of the graphical representations of the first, second, and third subsets is output in monochrome scale.

12. A system for generating an electrophysiology map, comprising:

an electrophysiology data point processor configured to accept as input geometry information and electrophysiology information pertaining to an anatomical region and to associate the geometry information with the electrophysiology information as a plurality of electrophysiology data points;

a filtering processor configured to accept as input a user's selection of n electrophysiological characteristics, wherein each of the n selected electrophysiological characteristics has an associated filtering criterion and an associated priority, and to apply the filtering criteria to their respective ones of the n selected electrophysiological characteristics; and

15

a mapping processor configured to output a three-dimensional representation of the filtered n selected electrophysiological characteristics according to their respective priorities,
wherein the three-dimensional representation includes 5
each of the filtered n selected electrophysiological characteristics, and
wherein a highest priority electrophysiological characteristic of the filtered n selected electrophysiological characteristics is rendered preferentially to and to the exclusion 10
of lower priority electrophysiological characteristics of the filtered n selected electrophysiological characteristics in regions of overlap.

* * * * *

16

专利名称(译)	用于产生心律失常的集成衬底图的方法和系统		
公开(公告)号	US9788751	公开(公告)日	2017-10-17
申请号	US14/884545	申请日	2015-10-15
[标]申请(专利权)人(译)	圣犹达医疗用品心脏病学部门有限公司		
申请(专利权)人(译)	ST.犹达医疗用品，心脏病DIVISION，INC.		
当前申请(专利权)人(译)	ST.犹达医疗用品，心脏病DIVISION，INC.		
[标]发明人	LI WENWEN ERDEMIR ERHAN AFONSO VALTINO PAPPONE CARLO MORGAN DENNIS		
发明人	LI, WENWEN ERDEMIR, ERHAN AFONSO, VALTINO PAPPONE, CARLO MORGAN, DENNIS		
IPC分类号	A61B5/05 A61B5/042 A61B5/053 A61B5/0452 A61B5/0408 A61B5/00		
CPC分类号	A61B5/0536 A61B5/0422 A61B5/0452 A61B5/04087 A61B5/0538 A61B5/7225 A61B5/7485 A61B5/725 A61B5/743 A61B5/746 A61B2505/05		
优先权	62/063989 2014-10-15 US		
其他公开文献	US20160106336A1		
外部链接	Espacenet USPTO		

摘要(译)

通过获取关于解剖区域的几何信息和电生理学信息，并将获得的几何和电生理学信息关联为多个电生理学数据点，可以生成电生理学图，例如心律失常基质的图。用户可以选择两个（或更多个）电生理特征用于显示，并且可以进一步选择将各种滤波器应用于所选择的电生理特征。用户还可以定义所选和/或过滤的特征之间的各种关系（例如，布尔AND，OR等）。用户选择的过滤标准可以应用于电生理学数据点以输出其各种子集。然后可以使用色阶，单色比例和图像的各种组合以图形方式呈现这些子集，例如作为三维心脏电生理学模型。

