



US 20150148619A1

(19) **United States**  
(12) **Patent Application Publication**  
**Berg et al.**

(10) **Pub. No.: US 2015/0148619 A1**  
(43) **Pub. Date: May 28, 2015**

(54) **SYSTEM AND METHOD FOR MONITORING BIOMETRIC SIGNALS**

*A61B 5/04* (2006.01)  
*A61B 5/0496* (2006.01)  
*A61B 5/0492* (2006.01)  
*A61B 5/0408* (2006.01)

(71) Applicant: **Athos Works, Inc.**, Redwood City, CA (US)

(52) **U.S. Cl.**  
CPC ..... *A61B 5/6804* (2013.01); *A61B 5/0492* (2013.01); *A61B 5/0205* (2013.01); *A61B 5/0408* (2013.01); *A61B 5/0478* (2013.01); *A61B 5/04008* (2013.01); *A61B 5/0496* (2013.01); *A61B 5/1112* (2013.01); *A61B 5/7445* (2013.01); *A61B 5/0533* (2013.01)

(72) Inventors: **James Berg**, San Francisco, CA (US); **Hamid Butt**, Cupertino, CA (US); **Dhananja Jayalath**, Redwood City, CA (US); **Christopher Wiebe**, Burlingame, CA (US)

(21) Appl. No.: **14/541,446**

(57) **ABSTRACT**

(22) Filed: **Nov. 14, 2014**


**Related U.S. Application Data**

A system for monitoring biometric signals of a user comprising: a garment configured to be worn by the user and comprising a mounting module having an array of connection regions; a set of biometric sensors coupled to the garment and configured to communicate with the array of connection regions to receive and transmit biometric signals indicative of muscle activity of the user; and a portable control module configured to couple to the garment in a first configuration and to decouple from the garment in a second configuration and comprising: a housing comprising an array of openings; a set of contacts, each including a first region that hermetically seals at least one of the array of openings and couples to at least one of the array of connection regions in the first configuration, and an electronics subsystem coupled to the housing and in communication with a second region of each contact.

(60) Provisional application No. 61/908,077, filed on Nov. 23, 2013, provisional application No. 62/013,405, filed on Jun. 17, 2014, provisional application No. 62/016,373, filed on Jun. 24, 2014, provisional application No. 62/077,781, filed on Nov. 10, 2014.

**Publication Classification**

(51) **Int. Cl.**  
*A61B 5/00* (2006.01)  
*A61B 5/0205* (2006.01)  
*A61B 5/11* (2006.01)  
*A61B 5/0478* (2006.01)






FIGURE 1




FIGURE 2




FIGURE 3A

106




FIGURE 3B




FIGURE 3C




FIGURE 3D




FIGURE 4A




FIGURE 4B



150"

- Garment and Dock
- Other, Clothing Only
- Metal, Dock Only
- Garment Only




FIGURE 6




FIGURE 7A






FIGURE 7B







FIGURE 9A

FIGURE 9B




FIGURE 10

EXAMPLE IMAGES FROM AN EXERCISE-MONITORING APPLICATION

S260




FIGURE 11A

S260'




FIGURE 11B




FIGURE 12

## SYSTEM AND METHOD FOR MONITORING BIOMETRIC SIGNALS

### CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Application Ser. No. 61/908,077 filed 23 Nov. 2013, U.S. Provisional Application Ser. No. 62/013,405 filed 17 Jun. 2014, U.S. Provisional Application Ser. No. 62/016,373 filed 24 Jun. 2014, and U.S. Provisional Application Ser. No. 62/077,781 filed 10 Nov. 2014, which are each incorporated in its entirety herein by this reference.

### TECHNICAL FIELD

[0002] This invention relates generally to the biometric device field, and more specifically to a new and useful system and method for monitoring biometric signals.

### BACKGROUND

[0003] Tracking biometric parameters resulting from periods of physical activity can provide profound insights into improving one's performance and overall health. Historically, users have tracked their exercise behavior by manually maintaining records of aspects of their physical activity, including time points, durations, and/or other metrics (e.g., weight lifted, distance traveled, repetitions, sets, etc.) of their exercise behavior. Exercise tracking systems and software have been recently developed to provide some amount of assistance to a user interested in tracking his/her exercise behavior; however, such systems and methods still suffer from a number of drawbacks. In particular, many systems require a significant amount of effort from the user (e.g., systems rely upon user input prior to and/or after a period of physical activity), capture insufficient data (e.g., pedometers that estimate distance traveled, but provide little insight into an amount of physical exertion of the user), provide irrelevant information to a user, and are incapable of detecting body-responses to physical activity at a resolution sufficient to provide the user with a high degree of body awareness. Other limitations of conventional biometric monitoring devices include one or more of: involvement of single-use electrodes, involvement of a single electrode targeting a single body location, use of adhesives for electrode placement, contributions to user discomfort, and other deficiencies.

[0004] There is thus a need in the biometric device field to create a new and useful system and method for monitoring biometric signals. This invention provides such a new and useful system and method.

### BRIEF DESCRIPTION OF THE FIGURES

[0005] FIG. 1 depicts an embodiment of a system for monitoring biometric signals of a user;

[0006] FIG. 2 depicts an embodiment of a system for monitoring biometric signals of a user, in communication with an external electronic device;

[0007] FIG. 3A depicts a cross-section of a portion of an embodiment of a system for monitoring biometric signals of a user;

[0008] FIGS. 3B-3C depict different variations of garments in an embodiment of a system for monitoring biometric signals of a user;

[0009] FIG. 3D depicts a specific example of a biometric sensor configuration in an embodiment of a system for monitoring biometric signals of a user;

[0010] FIG. 4A depicts variations of a housing of a control module in an embodiment of a system for monitoring biometric signals of a user;

[0011] FIG. 4B depicts an example of a control module in an embodiment of a system for monitoring biometric signals of a user;

[0012] FIG. 5A depicts a first example configuration of contacts in an embodiment of a system for monitoring biometric signals of a user;

[0013] FIG. 5B depicts a cross-section of a portion of an embodiment of a system for monitoring biometric signals of a user;

[0014] FIG. 6 depicts a second example configuration of contacts in an embodiment of a system for monitoring biometric signals of a user;

[0015] FIGS. 7A-7B depict a first configurations and a second configuration, respectively, of coupling between a control module and an array of connection regions in an embodiment of a system for monitoring biometric signals of a user;

[0016] FIG. 8A depicts an example of a mounting module in an embodiment of a system for monitoring biometric signals of a user;

[0017] FIG. 8B depicts a cross section of a portion of an embodiment of a system for monitoring biometric signals of a user;

[0018] FIG. 8C depicts a variation of a configuration between portions of a system for monitoring biometric signals of a user;

[0019] FIGS. 9A-9B depict configurations of charging modules in an example of a system for monitoring biometric signals of a user;

[0020] FIG. 10 depicts a flow chart of an embodiment of a method for monitoring biometric signals of a user;

[0021] FIGS. 11A-11B depict examples of portions of an exercise-monitoring application in a method and/or system for monitoring biometric signals of a user; and

[0022] FIG. 12 depicts an embodiment of a portion of a system for monitoring biometric signals of a user.

### DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0023] The following description of the preferred embodiments of the invention is not intended to limit the invention to these preferred embodiments, but rather to enable any person skilled in the art to make and use this invention.

#### 1. System

[0024] As shown in FIGS. 1 and 2, an embodiment of a system 100 for monitoring biometric signals of a user comprises: a garment 105; a set of biometric sensors 120 coupled to the garment and configured to receive biometric signals indicative of muscle activity of the user; and a control module 130 comprising a housing 140, a set of contacts 150 configured to couple to an array of connection regions 115 that enable signal transmission from the set of biometric sensors, and an electronics subsystem 160 in communication with the set of contacts. In some embodiments, the system 100 can further comprise one or more of: a mounting module no coupled to the garment and providing the array of connection

regions; and a processing subsystem **170** configured to communicate with the electronics subsystem **160** and generate analyses based upon biometric signals detected by way of the set of biometric sensors.

**[0025]** The system **100** functions to position a set of biometric sensors at desired regions of a user's body, in order to detect biometric signals generated during physical activity of the user. The system **100** also functions to process detected biometric signals and to provide information derived from the processed biometric signals to the user performing a physical activity in substantially near real time, such that the user can gain insights into how to maintain or improve performance of the physical activity in a beneficial manner. In variations, the system **100** is configured to detect and process bioelectrical signals generated at a set of regions of the body of a user who is exercising (e.g., performing aerobic exercise, performing anaerobic exercise), and to present analyses in a visual manner (e.g., graphic manner, textual manner) by way of an application executing at an electronic device having a display. As such, bioelectrical signals detectable, processable, and/or analyzable by the system **100** can include any one or more of: electromyograph (EMG) signals, electrocardiography (ECG) signals, electroencephalograph (EEG) signals, magnetoencephalograph (MEG) signals, galvanic skin response (GSR) signals, electrooculograph (EOG) signals, and any other suitable bioelectrical signal of the user. The system **100** can, however, be configured to detect, process, and/or analyze any other suitable biosignal data of the user, including one or more of: heart rate data, movement data, respiration data, location data, environmental data (e.g., temperature data, light data, etc.), and any other suitable data.

**[0026]** In one embodiment, the system **100** can be configured to aggregate a combination of one or more of the biometric factors described above, and to determine and output a variety of metrics associated with the user's exercise activity. These metrics can provide the user with insights pertaining to his/her muscle exertion, muscle balance, exercise form, potential to incur injuries (e.g., acute injuries, chronic injuries), muscle fatigue, activity levels, muscle recovery behavior, exercise regimen parameters (e.g., types of exercise, sets of an exercise, repetitions of an exercise, etc.), and/or any other suitable exercise- or health-related factor.

**[0027]** The system **100** is preferably configured to be used by a user who is away from a research or clinical setting, such that the user is interfacing with a portion of the system **100** while he or she undergoes periods of activity in a natural setting (e.g., at a gym, outdoors, etc.). The system **100** can additionally or alternatively be configured to be operated by a user who is in a research setting, a clinical setting, or any other suitable setting. The system **100** is preferably configured to perform at least a portion of the method **200** described in Section 2 below; however, the system **100** can additionally or alternatively be configured to perform any other suitable method.

**[0028]** The garment **105** functions to position a set of biometric sensors proximal a set of body regions of the user, in order to enable detection of biometric signals from specific body regions of the user as the user is performing a form of physical exercise. The garment **105** can thus provide a means for providing close coupling and/or consistent placement of the set of biometric sensors at the body of the user. As such, the garment can be a form-fitting garment that provides a biasing force on the set of biometric sensors **120** described below, in order to promote close coupling between the set of

biometric sensors **120** and desired portions of the body of the user. The garment can thus include a stretchable and/or compressive fabric comprising natural and/or synthetic fibers (e.g., nylon, lycra, polyester, spandex, etc.) to promote coupling (i.e., electrical coupling, mechanical coupling) and/or reduce motion artifacts that could otherwise result from relative motion between the skin of the user and the sensors of the set of biometric sensors **120**. In examples, the garment **105** can include any one or more of: a top (e.g., shirt, jacket, tank top, etc.), bottom (e.g., shorts, pants, etc.), elbow pad, knee pad, arm sleeve, leg sleeve, socks, undergarment, neck wrap, glove, and any other suitable wearable garment. In some embodiments, the system **100** can comprise an embodiment of the garment described in U.S. application Ser. No. 14/079,629 entitled "Wearable Architecture and Methods for Performance Monitoring, Analysis, and Feedback" and filed on 13 Nov. 2013, which is herein incorporated in its entirety by this reference. However, the system **100** can alternatively comprise any other suitable garment.

**[0029]** In providing close coupling between the set of biometric sensors, as described below, and the body of the user, the garment **105** preferably comprises a plurality of conductive regions **106**, as shown in FIG. 3A, configured to contact the set of body regions of the user from which biometric signal detection is desired, when the garment is worn by the user. As such, the plurality of conductive regions **106** can facilitate biometric signal transduction to the set of biometric sensors **120** described below. Preferably, the plurality of conductive regions **106** includes volumes of a conductive material that is integrated into the garment, wherein the conductive material is flexible, has good fatigue resistance, and is biocompatible (e.g., does not induce an allergic response, does not promote harboring of bacteria, etc.). The plurality of conductive regions **106** preferably also provide direct interfaces with the skin of the user when the garment is worn by the user, in order to facilitate electrical coupling with low impedance. However, in alternative variations, the plurality of conductive regions **106** can alternatively not directly contact skin of the user, but be configured to electrically couple to the user by way of an electrical coupling medium (e.g., saline, sweat, electrolyte medium, etc.) transmitted by way of the garment **105** or the user. In variations, the plurality of conductive regions **106** can include a conductive resin or silicone material formed directly onto a surface of the garment **105** facing the skin of the user, when the garment **105** is worn by the user, in order to facilitate signal transduction from the user to the set of biometric sensors **120** of the system **100**. However, the conductive material can alternatively comprise any other suitable material and/or be configured in any other suitable manner.

**[0030]** The set of biometric sensors **120** is preferably coupled to the garment and configured to receive biometric signals indicative of muscle activity of the user. As such, the set of biometric sensors **120** function to detect bioelectric potentials (i.e., biopotentials) from body regions of the user, which vary according to different states of activity of the user. The set of biometric sensors **120**, as described above, are preferably incorporated with or otherwise coupled to the plurality of conductive regions **106** of the garment **105**; however, the set of biometric sensors **120** can include one or more biometric sensors that are configured to couple to the user in any other suitable manner (e.g., without involvement of the garment **105**, without involvement of a plurality of conductive regions **106** of the garment **105**).

**[0031]** The set of biometric sensors **120** preferably include electromyography (EMG) electrodes configured to acquire biopotential signals resulting from muscle activity of the user. However, in some variations, the set of biometric sensors **120** can additionally or alternatively include any one or more of: respiration sensors (e.g., sensors that operate according to plethysmography), galvanic skin response (GSR) sensors, temperature sensors, accelerometers (e.g., single axis accelerometers, multi-axis accelerometers), gyroscopes (e.g., single axis gyroscopes, multi-axis gyroscopes) global positioning system (GPS) sensors, vibration sensors, bioimpedance sensors, bend-angle measurement sensors, electrocardiography (ECG) sensors, sensors indicative of other cardiovascular parameters (e.g., pulse oximetry sensors, blood pressure sensors), and any other suitable type of sensor. As such, the set of biometric sensors **120** can detect biosignals indicative of one or multiple types of biological/physiological responses to activity of a user, in providing information relevant to exercise behavior of the user.

**[0032]** Preferably, the type, number, and positioning of the set of biometric sensors is dependent upon the type(s) of garment(s) **105** included in the system **100**. Additionally, for anatomical regions having contralateral pairs, the set of biometric sensors **120** preferably includes pairs of sensors, each pair including a first sensor at a first body region and a second sensor at a second body region that is a contralateral region to the first body region. In one variation, as shown in FIG. 3B, for a garment **105** that has a form factor of a top (e.g., shirt, tank top, etc.), the set of biometric sensors **120** can include a set of EMG electrodes configured to be positioned at desired locations when the garment **105** is worn by the user, and can additionally or alternatively include one or more of a heart rate sensor and a respiratory sensor. In one example of this variation, the set of EMG electrodes include electrodes configured to be positioned proximal one or more of: the pectoralis muscles, the abdominal muscles, the oblique muscles, the trapezius muscles, the rhomboid muscles, the teres major muscles, the latissimus dorsi muscles, the deltoid muscles, the biceps muscles, and the triceps muscles when the garment **105** is worn by the user. In the example, the set of biometric sensors can further include a heart rate sensor configured to be positioned proximal the heart region of the user, and/or a respiratory sensor configured to encircle at least a portion of the torso of the user (i.e., to facilitate plethysmography) when the garment **105** is worn by the user. Variations of the example of the garment **105** configured as a top with biometric sensors can, however, be configured in any other suitable manner (e.g., a tank top garment can omit sensors positioned proximal the triceps and the biceps muscles).

**[0033]** In another variation, as shown in FIGS. 3C and 3D, for a garment **105** that has a form factor of a bottom (e.g., shorts, pants, etc.), the set of biometric sensors **120** can include a set of EMG electrodes configured to be positioned at desired locations when the garment **105** is worn by the user. In one example of this variation, the set of EMG electrodes include electrodes configured to be positioned proximal one or more of: the gluteus maximus muscles, the gluteus medius muscles, the vastus lateralis muscles, the gracilis muscles, the semimembranosus muscles, the semitendinosus muscles, the biceps femoris, the quadriceps muscles, the soleus muscles, the gastrocnemius muscles, the rectus femoris muscles, the sartorius muscles, the peroneus longus muscles, and the adductor longus muscles when the garment **105** is worn by the user. Variations of the example of the garment **105** configured

as a bottom with biometric sensors can, however, be configured in any other suitable manner.

**[0034]** In alternative embodiments, the set of biometric sensors **120** can be supplemented with a set of supplementary sensors **125** configured to detect one or more aspects associated with an environment of the user. In variations, the set of supplementary sensors **125** can include one or more of: environmental temperature sensors, altimeters, oxygen content sensors, air quality sensors, near field communication (NFC) sensors (e.g., configured to detect a nearby device or piece of exercise equipment having a corresponding NFC element), and any other suitable supplementary sensor that can enrich the data acquired from user and/or the environment of the user.

**[0035]** The control module **130** comprises a housing **140** and a set of contacts **150** configured to couple to an array of connection regions **115** in electrical communication with the set of biometric sensors **120**, which enable signal transmission from the set of biometric sensors to the control module **130**. The control module **130** preferably also includes an electronics subsystem **160** in communication with the set of contacts **150**, wherein the electronics subsystem **160** facilitates signal reception, signal conditioning, signal transmission, and power distribution for the system **100**. The control module **130** thus functions to control signal reception, pre-processing, and transmission to a processing subsystem, and to physically protect/isolate sensitive elements (e.g., electronics) of the system **100**. The control module **130** is preferably configured to be a portable control module that can removably couple to the garment **105** and set of biometric sensors **120** in cooperation with a mounting module **170** of the garment **105**, as described below. As such, the control module **130** can be configured to be uncoupled from the garment by the user (or another entity) when desired (e.g., during charging, during washing of the garment, during battery replacement, etc.). However, the control module **130** can alternatively be configured to semipermanently couple to the garment **105**, such that it is not desirable for the user to remove the control module **130** from the garment.

**[0036]** The housing **140** functions to house and protect the electronics subsystem **160** over the lifetime of use of the system **100** by a user, and can further function to enhance wearability of the system. The housing **140** is preferably composed of a rigid material (e.g., a rigid plastic material, a metal, etc.), such that the housing **140** does not deform in response to normal forces, shear stresses, bending stresses, or torsional stresses induced during use of the system **100**. Alternatively, the housing **140** can be flexible to facilitate maintenance of compliance with a user as the user performs a physical activity. In variations wherein the housing **170** is flexible, other elements of the system **100** can also be flexible (e.g., the electronics subsystem can comprise a flexible thin film battery, the electronics subsystem can comprise flexible electronics, etc.) to facilitate compliance with the body of a user. In a specific example, the housing is composed of a polycarbonate/acrylonitrile butadiene styrene (ABS) blend; however, variations of the specific example can alternatively be composed of only polycarbonate, only ABS, or any other suitable material.

**[0037]** The housing **140** preferably has a profile that does not protrude a significant distance from the body of the user when the garment **105** is worn by the user. As such, the housing **140** preferably has a low aspect ratio that contributes to a thin form factor of the control module **130**. However, the

housing 140 can alternatively define a volume with a high aspect ratio. Preferably, the external surface of the housing 140 is substantially smooth and has rounded edges, in order to avoid damaging the garment 105 during motion of the user. Furthermore, the housing 140 can define a substantially polygonal footprint (i.e., triangular footprint with rounded edges, a quadrilateral footprint with rounded edges, a pentagonal footprint with rounded edges, a hexagonal footprint with rounded edges, etc.), or can alternatively define one or more of a circular footprint, an ellipsoidal footprint, and an amorphous footprint. In one example, as shown in FIG. 4B, the housing 140 defines an ellipsoidal footprint and has a thickness substantially below 2 cm, a height below 10 cm, and a width below 6 cm, in order to produce a smooth form factor with a low aspect ratio. In a specific example, as shown in FIG. 4B, the housing 140' has an ellipsoidal footprint with an overall thickness of 11 mm, a shell thickness of 1.4 mm, a width of 34 mm, and a height of 62 mm. Variations of the example of the housing can, however, be configured in any other suitable manner, as shown in FIG. 4A.

[0038] The housing 140 preferably forms a shell about internal components of the control module 130, and preferably has a first housing surface 141 facing the body of the user when the control module 130 interfaces with the user and a second housing surface 142 facing away from the body of the user when the control module 130 interfaces with the user, an example of which is shown in FIG. 4B. The first housing surface 141 and/or the second housing surface 142 can comprise a concave surface or a convex surface, in interfacing with the garment or the body of the user. Furthermore, depending upon the intended position of the control module 130 relative to the garment 105 and/or the body of the user, the first housing surface 141 and/or the second housing surface 142 can define surfaces that are configured to conform to the body of the user upon coupling of the system 100 to the user. The first housing surface 141 and the second housing surface 142 can be coupled together using a hermetic sealing element, including one or more of: an adhesive, a compliant sealing material (e.g., putty), an o-ring, an x-ring, any other suitable ring, and/or any other suitable sealing element. As such, an interface between the first housing surface 141 and the second housing surface 142 can be configured to be waterproof and/or machine-washable in order to protect aspects of the control module 130. In the specific example shown in FIG. 4B, the first housing surface 141 has an articulated surface configured to promote tactility, and ports that allow light transmission (e.g., from indicator LEDs) to inform the user regarding one or more statuses of the system 100 (e.g., proper coupling relative to other elements of the system 100, an active configuration of the control module 130, an inactive configuration of the control module 130, a charging status of the system 100, a calibration status of the system 100, etc.).

[0039] The housing 140 preferably has an array of openings 143 defined at one or more of the first housing surface 141 and the second housing surface 142, wherein the array of openings 143 provides access for a set of contacts 150 configured between the electronics subsystem 160 and an array of connection regions 115, as described in further detail below. Preferably, the array of openings 143 is defined entirely at the first housing surface 141; however, in alternative variations, the array of openings 143 can be defined at both the first housing surface 141 and the second housing surface 142, or at only the second housing surface 142. The array of openings 143 can comprise a rectangular array of openings; however,

the array of openings 143 can alternatively be configured in any other suitable manner (e.g., as a circular array of openings, as an ellipsoidal array of openings, as a polygonal array of openings, as an amorphous array of openings, etc.). Each opening in the array of openings 143 can be a circular opening or can alternatively be a non-circular opening. Furthermore, each opening in the array of openings 143 is preferably identical to every other opening in the array of openings 143 in morphology; however, the array of openings 143 can alternatively comprise non-identical openings. In a specific example, as shown in FIG. 4B the array of openings 143 includes 42 identical circular openings arranged in a 7×6 rectangular array, each opening having a diameter of 3 mm and an inter-opening spacing of 1.5 mm; however, variations of the specific example of the array of openings 143 can be configured in any other suitable manner.

[0040] The set of contacts 150 functions to facilitate coupling between the electronics subsystem 160 of the control module 130 and an array of connection regions 115, by way of the array of openings 143 of the housing 140 described above. As such, the set of contacts 150 comprise electrically conductive contacts that facilitate reception of biosignals from the set of biometric sensors 120 of the system 100. Preferably, the set of contacts 150 comprises contacts composed of an electrically conductive, elastic, and compliant material (e.g., electrically conductive silicone, electrically conductive polymer, etc.) that facilitates maintenance of electrical communication between the set of biometric sensors 120 and the electronics subsystem 160 during motion of the user. In one example, the conductive polymer used in the set of contacts comprises an ether-based conductive thermoplastic polyurethane material; However, the set of contacts 150 can alternatively comprise one or more contacts composed of an electrically conductive, but non-elastic or non-compliant material (e.g., a metallic material).

[0041] As shown in FIG. 5B, each contact in the set of contacts 150 preferably includes a first region 151 that extends through at least one opening of the array of openings 143 of the housing 140, and a second region 152 that couples to a portion of the electronics subsystem 160 configured for signal reception/conditioning. The first region 151 of each contact in the set of contacts 150 preferably hermetically seals at least one opening in the array of openings 143 of the housing 140, in order to prevent fluids (e.g., water, sweat) from seeping into the housing and potentially damaging the electronics subsystem 160, which is otherwise accessible through the array of openings 143. As such, the housing 140 of the control module 130 is preferably configured to be waterproof and/or machine-washable, due to the configuration of the set of contacts 150 in relation to the housing 140. The first region 151 of each of the set of contacts 150 can thus be over-molded on the housing 140 at least at one opening of the array of openings 143, and the second region 152 can be over-molded onto or otherwise coupled to a desired region of the electronics subsystem 160, which is internal to the housing 140 of the control module 130. Each contact in the set of contacts 150 is preferably associated with an opening of the array of openings 150 in a one-to-one manner; however, the set of contacts 150 and the array of openings 143 can alternatively be configured in a less-than-one-to-one or a more-than-one-to-one manner.

[0042] In relation to the configuration of the set of contacts 150, the contacts can each be assigned to and facilitate signal reception from a corresponding biometric sensor of the set of

biometric sensors **120**. Additionally, in some configurations, each contact and biometric sensor can be associated with a companion contact and biometric sensor to facilitate detection of a signal differential (i.e., a biopotential difference) across two paired biometric sensors. As such, the control module **130** can utilize signals from paired sensors in measuring a biopotential difference, thereby enabling determination of one or more metrics associated with muscle/exercise activity. In a first variation, the set of contacts **150** can be arranged according to pins on corresponding circuitry of the electronics subsystem **160**. In the first variation, as shown in FIG. 5A, the set of contacts **150'** can be arranged in a symmetrically opposing arrangement about any suitable axis of symmetry (e.g., a diagonal axis of symmetry defined by the array of openings **143** of the housing, a horizontal axis of symmetry defined by the array of openings **143** of the housing, a vertical axis of symmetry defined by the array of openings **143** of the housing, etc.). In an example of the first variation, contact **1A**, as shown in the top left corner of the set of contacts shown in FIG. 5A, can be paired with contact **1B** in the bottom right corner of the set of contacts **150**, in facilitating detection of a first biopotential difference determined from two paired biometric sensors. In the example, the set of contacts **150** further comprises contacts associated with paired heart rate/respiratory signal detection sensors, ground pins of the electronics subsystem **160**, and identification pins of the electronics subsystem **160**.

[0043] In a second variation, as shown in FIG. 6, the set of contacts **150"** can be arranged such that associated pairs of contacts are positioned proximal to each other. In an example of the second variation, contact **1A**, as shown in the top left corner of the set of contacts shown in FIG. 6, can be paired with contact **1B** just below contact **1A** (in the orientation shown in FIG. 6), in facilitating detection of a first biopotential difference determined from two paired biometric sensors. In the example, the set of contacts **150** further comprises contacts associated with paired heart rate/respiratory signal detection sensors, ground pins of the electronics subsystem **160**, and identification pins of the electronics subsystem **160**.

[0044] Variations of the first and the second variations of contact configurations can comprise any other suitable combination of symmetrically opposing arrangements of paired contacts and proximal placement of paired contacts. For instance, a portion of paired contacts associated with biometric sensors can be proximally placed, while other contacts (e.g., contacts associated with identification pins, contacts associated with ground pins, etc.) can be arranged in a symmetrically opposing arrangement.

[0045] In any of the above contact configurations, and for control modules **130** with housings **140** that can be coupled with the garment **105** in multiple orientations (e.g., for a control module **130** that has a housing **140** with at least one axis of symmetry), the control module can be configured to utilize the contact configuration(s) and any other suitable data (e.g., accelerometer data, gyroscope data) in order to detect the orientation of the control module relative to the garment **105**, and to adapt signal reception and processing functions accordingly. As such, the control module **130** can be configured to operate properly regardless of how the control module is coupled with the garment **105**. Thus, a user would not need to ensure that the control module **130** is coupled with the garment **105** according to a specific orientation (e.g., based upon alignment marks on the control module, based upon asymmetry of the control module, etc.). Additionally, the

control module **130** and contact configurations can have associated firmware to facilitate correct mapping between the set of contacts **150** and the set of biometric sensors **120** in a desired manner. For example, using the contact configuration shown in FIG. 6, signals **X** and **Y** can be received by way of contacts **1A** and **1B** in a first orientation of the control module **130**, but if the control module is positioned "upside-down" in a second orientation, firmware can adapt signal reception and processing of the control module to receive signals **X** and **Y** by way of contacts **14B** and **14A**, respectively. As such, in the example, the control module **130** can be configured to dynamically modify the contact mapping in order to properly attribute signals **X** and **Y** to the correct muscle group or set of biometric sensors. Alternatively, the control module **130** and/or housing **140** can be configured to couple with the garment **105** in only a single orientation (e.g., based upon markings, based upon asymmetry in the control module **130** or housing, etc.), such that the control module **130** does not require firmware that enables adaptive coupling.

[0046] The electronics subsystem **160** is configured to be in electrical communication with the set of contacts **150**, and functions to facilitate signal reception, signal conditioning, signal transmission, and power distribution for the system **100**. The electronics subsystem **160** is preferably housed within an internal portion of the housing **140** of the control module **130**, in order to be isolated from mechanisms that could damage the electronics subsystem **160**; however, the electronics subsystem **160** can alternatively be configured in any other suitable manner. The electronics subsystem **160** preferably comprises a power module **161**, a supplementary sensing module **163**, a signal conditioning module **165**, a communication interface **167**, and memory **169**; however, the electronics subsystem **160** can additionally or alternatively include any other suitable element(s) that enrich acquired data and/or facilitate conditioning or processing of signals from the user as the user performs a physical activity.

[0047] The power module **161** of the electronics subsystem **160** functions to provide regulated and unregulated electrical power to the system **100** and to allow power storage for the system **100**. The power module **161** preferably comprises a rechargeable battery **162** (e.g., a lithium-ion battery, nickel-cadmium battery, metal halide battery, nickel metal hydride battery, lithium-ion polymer battery, etc.); however, the power module **161** can alternatively comprise a non-rechargeable battery (e.g., alkaline battery) that can be replaced to further enhance modularity in the system **100**. Preferably, the power module **161** is configured to have a profile with a low aspect ratio, contributing to a thin form factor of the control module **130**/housing **140**. However, the power module **161** can be configured to have any other suitable profile such that the power module **161** provides adequate power characteristics (e.g., cycle life, charging time, discharge time, etc.) for the system **100**.

[0048] In variations where the battery **162** of the power module **161** is rechargeable, the electronics subsystem **160** can also comprise a coil of wire and associated electronics that function to allow inductive coupling of power between an external charging element **62** and the power module **161**, as shown in FIGS. 1 and 9A-9B. The charging coil preferably converts energy from an alternating electromagnetic field (e.g., provided by a charging dock or other adapter), into electrical energy to charge the battery **162** and/or to power the system **100**. Inductive charging allows electrical isolation between the external charging element **62** and internal elec-

tronics of the electronics subsystem **160** to promote user safety and convenience in interfacing with the system **100**. Inductive charging provided by the charging coil thus also facilitates user mobility while the user interacts with the system **100**, such that the user can perform a wide range of physical activities while having his/her biometric signals monitored by the system **100**. In alternative variations, however, the charging coil can be altogether omitted (e.g., in variations without a rechargeable battery), or replaced or supplemented by a connection (e.g., USB connection) configured to provide wired charging of a rechargeable battery.

**[0049]** The supplementary sensing module **163** functions to facilitate acquisition of additional data from the user, which can be used to trigger control of aspects of signal acquisition and/or analysis generation by the control module **130**. As such, not all sensors of the system **100** may be separate from the control module **130**. The supplementary sensing module **163** preferably includes a set of supplementary sensors **164** configured to detect one or more aspects associated with motion of the user and/or an environment of the user. In variations, the set of supplementary sensors **125** can include one or more of: an accelerometer (e.g., a single axis accelerometer, a multi-axis accelerometer), a gyroscope (e.g., a single axis gyroscope, a multi-axis gyroscope), a GPS module, environmental temperature sensors, altimeters, oxygen content sensors, air quality sensors, near field communication (NFC) sensors (e.g., configured to detect a nearby device or piece of exercise equipment having a corresponding NFC element), and any other suitable supplementary sensor that can enrich the data acquired from user and/or the environment of the user. In one example, accelerometers of the supplementary sensing module **163** can be used to detect a type of physical activity (e.g., cardio exercise, weight training exercise, etc.) performed by the user, and/or can be used during signal processing to remove motion-produced artifacts from signals being processed. The supplementary sensing module **163** can, however, comprise any other suitable sensors and be configured relative to the electronics subsystem **160** in any other suitable manner.

**[0050]** The signal conditioning module **165** functions to preprocess signals detected and received using the set of biometric sensors and/or sensors of the supplementary sensing module **163**, thereby producing conditioned data prior to processing. In variations, the signal conditioning module **165** can comprise elements configured to perform any one or more of: filtering (e.g., using a low pass filter, a high pass filter, a band-pass filter, a notch filter, etc.), smoothing, clipping, deconvolving, detrending/offsetting, standardizing, resampling, hard-binding, predicting, windowing, and any other suitable data conditioning process upon any signals received from the set of biometric sensors **120**. The signal conditioning module can thus comprise one or more of: filters, amplifiers, analog-to-digital converters (ADCs), digital-to-analog converters (DACs), signal multiplexers, and any other suitable elements for conditioning signals received from biometric sensors and supplementary sensors.

**[0051]** The communication interface **167** preferably comprises hardware and/or software elements configured to facilitate communication of information between the set of biometric sensors **120** and the control module **130**, and/or communication of information between the control module **130** and one or more separate devices (e.g., a processing subsystem, a mobile computing device of the user, etc.). As such, the communication interface **167** can function as a data

link that provides a means for communications to and from the control module **130** over a network. The network can comprise any suitable network used for communication between electronic devices. The network can include a wireless and/or a wired connection between devices. In examples of wireless connections, the network associated with the communication interface **167** can include any one or more of: a local area network (LAN), a wireless LAN (WLAN), a Bluetooth network (e.g., a Bluetooth Low Energy network), a municipal area network (MAN), a wide area network (WAN), the internet, and any other suitable network. Furthermore, in some variations, the communication interface **167** can include features that provide security in information communication. For example, cryptographic protocols such as Diffie-Hellman key exchange, Wireless Transport Layer Security (WTLS), or any other suitable type of protocol may be used. The data encryption may also comply with standards such as the Data Encryption Standard (DES), Triple Data Encryption Standard (3-DES), or Advanced Encryption Standard (AES).

**[0052]** In wired variations of the communication interface **167**, the communication interface can implement any one or more of an audio jack connection (e.g., AUX cable), a USB connection, a parallel port, a serial port, an ethernet adapter, an IEEE 1394 bus interface, a small computer system interface (SCSI) bus interface, an infrared (IR) communication port, and any other suitable wired or hardware connection. In this variation, the communication interface **167** can communicate with other devices over a network using one or more of: inter-integrated circuit communication (I2C), one-wire, master-slave, or any other suitable communication protocol. However, the communication interface **167** can transmit data in any other way and can include any other type of wired connection that supports data transfer between the electronics subsystem **160**, external devices, and/or any other suitable computing element.

**[0053]** The memory **169** functions to retain data from signals received at the electronics subsystem **160**. As such, upon receiving signals from the set of biometric sensors **120**, the electronics subsystem **160** of the control module **130** can thus facilitate storage of biometric data (e.g., conditioned data from biopotential signals, unconditioned data from biopotential signals) within memory of the electronics subsystem **160**. The memory **169** can comprise processor-readable medium including any one or more of: random access memory (RAM), read-only memory (ROM), non-volatile random access memory (NVRAM), programmable read-only memory (PROM), erasable programmable read-only memory (EPROM), electrically erasable PROM (EEPROM), flash memory, magnetic or optical data storage, registers, and any other suitable storage element. Preferably, data from the memory **169** is automatically transmitted to any appropriate external device, over a network, substantially continuously (e.g., every second, every millisecond, etc.); however, data from the data storage unit **180** can alternatively be transmitted intermittently (e.g., every minute, hourly, daily, or weekly). In one example, data generated by any element of the system **100** may be stored in memory **169** when the communication interface **167** is not actively coupled to an element external to the electronics subsystem **160** over the network. However, in the example, when a link is established between the communication interface **167** and an external element, data may then be automatically transmitted from memory **169**. In other examples, the memory **169** can additionally or alternatively

be manually prompted to transmit stored data, when prompted by a user or other entity.

[0054] The control module 130 can, however, include any other suitable elements, including input devices (e.g., keyboard, mouse, microphone, remote control, button, joystick, trackball, touchpad, optical sensor), wherein the input device (s) can receive input from another device, and output devices (e.g., displays, projectors, speakers, tactile devices, network cards, wireless transmitters, infrared transmitters, lights, etc.) that convey information to a user, as shown in FIG. 12. For instance, an output device associated with the control module 130 can display a graphical user interface (GUI) that facilitates user interaction. Such a display can utilize any suitable image projection technology, such as a cathode ray tube (CRT), liquid crystal display (LCD), light-emitting diode (LED), gas plasma, electroluminescence, or any other suitable image projection technology.

[0055] In relation to coupling between the control module 130 and the garment 105, the system 100 can also include a mounting module no, as shown in FIGS. 7A and 7B, that receives the control module 130 in order to facilitate coupling of the control module 130 to the garment 105 in a reversible and repeatable manner. The mounting module 110 thus preferably provides an array of connection regions 115, which function to facilitate electrical coupling between the set of biometric sensors 120 and the set of contacts 150 of the control module 130 in a first configuration 101. As such, the garment 105 can also function to serve as a substrate for facilitating electrical coupling between the set of biometric sensors and the mounting module 115. In variations, the mounting module no and/or the garment 105 can include any one or more of: slots, pouches, ports, bases, pathways, channels, cradles, and any other suitable feature by which the set of biometric sensors and/or control module 130 can be permanently or removably coupled to each other and/or to the mounting module 110 or the garment 105. Furthermore, the garment 105 can include conductive leads (e.g., wires, conductive filaments) passing along and/or throughout the garment 106 to enable signal transmission between the mounting module no and the set of biometric sensors 120 (e.g., by way of the plurality of conductive regions 106 of the garment 105). Alternatively, the garment 105 or any other element of the system 100 can be configured to facilitate wireless communication between the set of biometric sensors 120 and the control module 130. In one such example, the garment 105 and other elements of the system 100 can be configured according to an embodiment, variation, or example described in U.S. Application No. 62/071,781, entitled "Biometric Monitoring Garment" and filed on 10 Nov. 2014.

[0056] The mounting module 110 thus functions to provide an electrical and mechanical interface between the control module 130 and the set of biometric sensors 120 of the garment 105, in facilitating signal transmission in a robust manner as the user performs a physical activity. In producing a robust electrical and mechanical interface, the mounting module no can comprise a set of layers 111 coupled to each other and/or to a surface of the garment 105, wherein the set of layers provide a biasing force that maintains contact between the set of contacts 150 of the control module and the array of connection regions 115 of the mounting module no. In generating the biasing force, the set of layers 111 can include one or more of elastic layers (e.g., elastic fabrics), compliant layers (e.g., foam layers), and substantially rigid layers (e.g., layers that are configured to accommodate the

control module 130 in a press-fit or snap-fit manner). As such, the mounting module 110 provides a robust electromechanical connection between the control module 130 and the array of connection regions 115 of the mounting module 110 in a first configuration 101, and enables decoupling of the control module 130 from the mounting module 110 in a second configuration.

[0057] In one example, as shown in FIG. 8A, the mounting module no comprises: a fabric layer 112 affixed to the garment 105 and defining a receiving pocket for the control module 130, wherein the fabric layer 112 has an elastic opening 113 that accommodates reception of the control module 130 and exposes one or more indicator LEDs of the control module 130; a cradle 114 deeper than the fabric layer 112 and comprising the array of connection regions 115 that couple to the set of biometric sensors 120; a foam ring 116 at least partially surrounding the cradle 114 and deeper than the fabric layer 112, wherein the foam ring 116 functions to provide stability to a control module 130 seated within the fabric layer 112 at the cradle 114, and can further function to protect the user from the rigidity of the cradle as well as shielding regions where sensor leads are coupled to the cradle 114; a first tape ring 117 surrounding at least a portion of the elastic opening 113 of the fabric layer 112; and a second tape ring 118 surround at least a portion of the periphery of the fabric layer 112, wherein the first tape ring 117 and the second tape ring 118 function to provide structural integrity to the fabric. The mounting module no can, however, comprise a configuration such as that described in U.S. Provisional Application Ser. No. 62/013,405 filed 17 Jun. 2014, and/or U.S. Provisional Application Ser. No. 62/016,373 filed 24 Jun. 2014, both entitled "Biometric Monitoring System". Additionally or alternatively, variations of the mounting module 110 can comprise combinations of any of the above variations and examples, or any other suitable configuration of a mounting module.

[0058] In the example, and with regard to the cradle 114, the cradle 114 is preferably composed of a rigid material (e.g., rigid plastic) having the array of connection regions 115 arranged in a configuration that is complementary to the set of contacts 150 of the control module no. As such, in the example, the array of connection regions 115 comprises a 7x6 array of circular connection regions configured to couple with the 7x6 array of circular contacts of the control module 130. In the example, each connection region of the array of connection regions 115 comprises a conductive silicone rubber; however, the connection regions can additionally or alternatively be composed of any other suitable material. Similar to the set of contacts 150, and as shown in FIG. 8B, each connection region in the array of connection regions can have a first region 16, exposed through a first cradle surface 17 configured to contact the first region 151 of at least one contact, and a second region 18 in communication with the first region 16 and configured to couple to a lead proximal a second cradle surface 19, wherein the lead enables electrical communication between a connection region of the array of connection regions 115 and at least one biometric sensor of the set of biometric sensors 120. As such, each connection region of the array of connection regions 115 of the mounting module no can be in communication (e.g., by way of one or more leads) to one or more corresponding biometric sensors 120, as described above.

[0059] Thus, the set of layers in of the example function bias the set of contacts 150 of the control module 130 into

electromechanical communication with the array of connection regions **115** of the mounting module **110**, to enable reception of biopotential signals from the set of biometric sensors **120** at the control module **130**.

**[0060]** The location of mounting module no is preferably dependent upon the type(s) of garment(s) included in the system **100**. For instance, for a garment **105** configured as a top, the mounting module **110** is preferably located at a position that does not interfere with physical activity (e.g., weight lifting activity) of the user, generate significant signal interference with one or more of the set of biometric sensors **120**, or interfere with the user/signal reception in any other suitable manner. In one example, the mounting module no can be positioned proximal the triceps or biceps muscle of the user, when the garment **105** is worn by the user. In another example, the mounting module **110** can be centrally located between the pectoralis muscles of the user and/or the abdominal muscles of the user, when the garment **105** is worn by the user. In another variation wherein the garment **105** is configured as a bottom, the mounting module **110** can be located proximal the vastus lateralis muscle(s) of the user when the garment **105** is worn by the user. Additionally or alternatively, the system **100** can comprise multiple mounting modules no, such that the control module can be repositioned when the user is performing different types of physical activity. For example, a first mounting module positioned at an anterior portion of the garment **105** can allow the user to comfortably perform sit-ups or other exercises where the user is lying face-up, and a second mounting module positioned at a posterior portion of the garment **105** can allow the user to comfortably perform exercise where the user is lying face-down.

**[0061]** As noted earlier with respect to embodiments of the control module **130** including indicator LEDs, the mounting module no preferably allows light from the indicator LEDs to be visualized by the user wearing the garment **105**. In one variation, upon insertion of the control module **130** into the mounting module no, exposed LED indicators can be activated (e.g., by the control module **130**) in order to indicate that the control module **130** has been properly seated within the mounting module **110** and is in a state to receive signals from the set of biometric sensors **120**. As such, in coupling with the mounting module no, the control module **130** can perform one or more of: detecting proper seating within the mounting module **110**, determining an orientation of the control module **130** within the mounting module no, determining, based upon the orientation of the control module, which indicator LED(s) are exposed to the user, activating the exposed indicator LED(s), not activating the unexposed indicator LED(s), and performing any other suitable function.

**[0062]** While the array of connection regions **115** is described in relation to the mounting module **110**, the array of connection regions **115** can alternatively be integrated with the garment **105**, in variations of the system **100** wherein the control module **130** is not configured to be removably coupleable to the garment **105** by way of a mounting module no. As such, variations of the system **100** can alternatively omit a mounting module **110** and instead provide direct coupling between the set of biometric sensors **120** and the control module **130** without an intermediate mounting module no. Variations of the system **100** can, however, be configured in any other suitable manner.

**[0063]** Additionally or alternatively, the mounting module **110** can comprise a first locking portion that is configured to interact with a second locking portion on the housing **140** of

the control module **130**, in order to facilitate maintenance of contact between the set of contacts **150** of the control module **130** and the array of connection regions **115** of the mounting module no. In one example, the housing **140** of the control module **130** can define a notch **401** configured to reversibly couple with a latch **402** of a portion of the mounting module **110**, as shown in FIG. 8C. However, the housing **140** of the control module **130** can be configured to reversibly or irreversibly lock with the mounting module no using any other suitable mechanism, including one or more of a snap fit mechanism, a press fit mechanism, a magnetic mechanism, and any other suitable mechanism.

**[0064]** In some variations, the system **100** can further include a processing subsystem **170** configured to communicate with the electronics subsystem **160** and generate analyses based upon biometric signals detected by way of the set of biometric sensors. The processing subsystem **170** is preferably configured to perform at least a portion of the method **200** described in section 2 below; however, the processing subsystem **170** can alternatively be configured to perform any other suitable method. As such, the processing subsystem **170** is configured to be in communication with the electronics subsystem **160** over the network associated with the communication interface, and can further be configured to be in communication with an electronic device **180** of the user over the network. As such, analyses generated using the processing subsystem **170** can be transmitted to the electronic device **180** of the user in order to inform the user regarding his/her exercise behavior.

**[0065]** The processing subsystem **170** can comprise any suitable general purpose processing subsystem, which can include any one or more of: a central processing unit (CPU), a microprocessor, a digital signal processor (DSP), a microcontroller, a cloud-based computing system, a remote server, a state machine, an application-specific integrated circuit (ASIC), a programmable logic device (PLD), a field programmable gate array (FPGA), any other suitable processing device, and any suitable combination of processing devices (e.g., a combination of a DSP and a microprocessor, a combination of multiple microprocessors, etc.). For instance, in some variations, the processing subsystem **170** can be implemented in multiple modules including one or more of a DSP module of the electronics subsystem **160** having embedded algorithms, a module executing on a remote server, a module executing in a cloud-based computing system, and any other suitable module.

**[0066]** One or more of the elements of the electronics subsystem **160** and the processing subsystem **170** can be implemented in coordination with an electronic device **180** of the user or in proximity to the user, as the user performs physical activities. For instance, a mobile device and/or a wearable computing device (e.g., head-mounted computing device, wrist-mounted computing device, etc.) can implement indication, processing, and/or analysis provisions of the system **100**, in cooperation with other elements of the system **100**.

**[0067]** Additionally or alternatively, the electronic device **180** of the user can facilitate execution of an exercise monitoring application, in cooperation with data processing, analysis generation, and information transmission from other elements of the system **100**. The exercise monitoring application can implement hardware and/or software components used for obtaining activity data from the system **100**, and for performing operations on and analyses of the activity data. In one variation, the exercise monitoring application can utilize

the activity data to determine one or more exercise-related metrics (e.g., total effort output, average heart rate throughout a workout, average heart rate throughout a portion of a workout, a breakdown of muscle exertion for different muscle groups, exercise progress-related metrics, etc.) representative of the user's exercise behavior, and can additionally or alternatively generate a report including the exercise-related metrics and present the report to the user within a graphical user interface (e.g., incorporating a display device, incorporating a touchscreen device). Thus, the exercise monitoring application can allow the user to monitor effectiveness of one or more exercise activities he/she performs, as well as progress in aspects of the user's performance of one or more exercise activities. In utilizing the GUI provided by the electronic device 180, the electronic device 180 can be configured to display a virtual representation of different muscle groups of the user, and/or a graphic that depicts near-real-time feedback of muscle activity of the user in association with the virtual representation of different muscle groups of the user. As such, exercise-monitoring application executing on the electronic device 180 can be used to provide near-real-time feedback to the user as the user is performing a workout regimen.

[0068] Similar to other elements of the system 100, the electronic device 180 can include a storage module configured to store activity data, performance data, and/or generated reports within a database. The storage module can be implemented at the electronic device 180 and/or on a remote computing device, and preferably facilitates documentation and provision of historical exercise information to the user. Similar to the control module 130, the electronic device 180 can further include a communication interface that allows the electronic device to communicate information over the network associated with the control module 130, or any other suitable network(s). As such, an application executing at the electronic device 180 can facilitate interaction between the user and an exercise community. In one example, the application can be configured to upload exercise-related metrics, through a network, to be shared with a community of individuals with similar fitness interests, goals, or any other suitable association with the user, and the user may be able to obtain exercise advice and/or exercise-related metrics from the community of individuals to motivate the user according to his/her goals.

[0069] In expanding upon configurations of an exercise-monitoring application being executed at the electronic device 180, the application can be configured to provide a virtual coaching environment that includes one or more of: training plans, recovery plans, information regarding competitions (e.g., training regimens configured to prepare the user for an upcoming competition), instructions for stretching, instructions for injury prevention, instructions regarding proper form for conducting an exercise, and any other suitable coaching functions. Additionally or alternatively, the application can be configured to provide alerts to the user based upon received and processed data. For instance, the application can be configured to notify the user or another entity if the user is focusing too much on a particular exercise or muscle group (e.g., by visually showing the muscle group(s) that are overemphasized and recommending other exercises to the user), or if the user is using a muscle group incorrectly during an exercise (e.g., if the user is demonstrating poor form). Additionally or alternatively, the application can provide comprehensive reports pertinent to the user's exercise behavior, including one or more of: a muscle breakdown of work

performed/output for specific muscles; a breakdown of a score given for a workout, wherein the score can be tracked over time to monitor progress of the user; a classification of exercise as cardio-based or strength-based; indications of muscle atrophy, indications of rehabilitation progress; indications of fatigue; indications of potential or actual injury; and any other suitable reported factor. In one example, a report can provide a percentage of a workout associated with strength-based exercise vs. a percentage of a workout associated with cardio-based exercise. In another example, the report can additionally or alternatively provide a detailed breakdown of any exercise metric associated with one or more muscle groups, provided within a virtual display of various muscle groups. In this example, the application can be configured to accept a user input of a selection of one or more muscle groups (e.g., by selecting a portion of the virtual display of various muscle groups), and to provide relevant metrics pertaining to the muscle group(s) selected by the user.

[0070] Additionally or alternatively, the application executing at the electronic device 180 can be configured to display information directly related to muscle groups the user is monitoring, and/or to display information associated with muscle groups that the user is not actively monitoring, according to information acquired from muscle groups that the user is monitoring. As such, information from monitored muscles can be indicative of a problem elsewhere in the user's body, and monitored muscle groups can be used to provide indications or alerts pertaining to other portions of the user's body. In one example, monitored muscle groups can generate an alert that the user is positioning his bicycle seat at too high of a position, which is adversely affecting non-monitored muscle groups; in another example, monitored muscle groups can generate an alert that the user is running in a pigeon-toed manner, which is adversely affecting non-monitored muscle groups. The application(s) of the electronic device 180 can, however, be configured in any other suitable manner.

[0071] Furthermore, the system 100 can include any other suitable element(s) configured to detect and process biosignals data. Furthermore, as a person skilled in the art will recognize from the previous detailed description and from the figures and claims, modifications and changes can be made to the system 100 without departing from the scope of the system 100.

## 2. Method

[0072] As shown in FIG. 10, an embodiment of a method 200 for monitoring biometric signals of a user comprises: at a garment configured to be worn by the user, providing a set of interfaces between the user and a set of biometric sensors at a set of body regions exhibiting muscle activity, upon coupling of the garment to the user S210; at a mounting module coupled to the garment, providing an array of connection regions in communication with the set of biometric sensors and configured to couple to a set of contacts of a portable control module in a first configuration S230; at the portable control module, receiving a stream of electrical signals indicative of muscle activity from a subset of muscles of the user, in the first configuration S230; at the portable control module, transmitting the stream of electrical signals to a processing subsystem S240; at the processing subsystem, transforming the stream of electrical signals into a set of exercise-related metrics indicative of exercise behavior of the user S250; and at an electronic device in communication with

the processing subsystem, providing a report derived from the set of exercise-related metrics to the user **S260**.

**[0073]** The method **200** functions to facilitate positioning of a set of biometric sensors at desired regions of a user's body, in order to detect biometric signals generated during physical activity of the user. The method **200** also functions to process detected biometric signals and to provide information derived from the processed biometric signals to the user performing a physical activity in substantially near real time, such that the user can gain insights into how to maintain or improve performance of the physical activity in a beneficial manner. In variations, the method **200** is configured to detect and process bioelectrical signals generated at a set of regions of the body of a user who is exercising (e.g., performing aerobic exercise, performing anaerobic exercise), and to present analyses in a visual manner (e.g., graphic manner, textual manner) by way of an application executing at an electronic device having a display. As such, bioelectrical signals detectable, processable, and/or analyzable according to the method **200** can include any one or more of: electromyograph (EMG) signals, electrocardiography (ECG) signals, electroencephalograph (EEG) signals, magnetoencephalograph (MEG) signals, galvanic skin response (GSR) signals, electrooculograph (EOG) signals, and any other suitable bioelectrical signal of the user. The method **200** can, however, be configured to detect, process, and/or analyze any other suitable biosignal data of the user, including one or more of: heart rate data, movement data, respiration data, location data, environmental data (e.g., temperature data, light data, etc.), and any other suitable data. The method **200** is preferably implemented at least in part at an embodiment of the system **100** described in Section 1 above; however, the method **200** can alternatively be implemented at any other suitable system for detection and processing of biometric signals from a user who is performing a physical activity.

**[0074]** Block **S210** recites: at a garment configured to be worn by the user, providing a set of interfaces between the user and a set of biometric sensors at a set of body regions exhibiting muscle activity, upon coupling of the garment to the user. Block **S210** is preferably implemented at embodiments, variations, and/or examples of the garment and the set of biometric sensors described in Section 1 above; however, Block **S210** can alternatively be implemented using any other suitable garment with coupled biometric sensors that are configured to detect biopotential signals indicative of muscle activity of the user. Providing the set of interfaces thus functions to provide and maintain tight coupling between sensing portions of a set of biometric sensors and desired body regions of the user as the user performs a physical activity. In providing the set of interfaces, Block **S210** preferably utilizes conductive materials coupled to the garment and configured to maintain contact with the skin of the user as the user exercises; however, Block **S210** can produce the set of interfaces in any other suitable manner.

**[0075]** In Block **S210**, providing the set of interfaces preferably includes generation of interfaces configured to adequately conduct one or more of: electromyography (EMG) signals, motion signals (e.g., from an accelerometer, from a gyroscope), respiration signals (e.g., respiration rate, depth of breath, thoracic variations, inspiratory flow characteristics, expiratory flow characteristics, etc.), galvanic skin response (GSR) signals, temperature-induced signals, vibration signals, bioimpedance signals, electrocardiography (ECG) signals, signals indicative of other cardiovascular

parameters (e.g., pulse oximetry signals, blood pressure signals), and any other suitable type of signal. As such, the set of biometric sensors provided in Block **S210** can facilitate detection of biosignals indicative of one or multiple types of biological/physiological responses to activity of a user, in providing information relevant to exercise behavior of the user.

**[0076]** Preferably, providing the set of interfaces in Block **S210** is dependent upon the type of garment (e.g., top or bottom) provided in Block **S210**. Additionally, for anatomical regions having contralateral pairs, providing the set of interfaces preferably includes providing pairs of interfaces, each pair including an associated first sensor at a first body region and an associated second sensor at a second body region that is a contralateral region to the first body region. In one variation, for a garment that has a form factor of a top (e.g., shirt, tank top, etc.), the set of interfaces provided in Block **S210** can include interfaces between a set of EMG electrodes and skin of the user proximal one or more of: the pectoralis muscles, the abdominal muscles, the oblique muscles, the trapezius muscles, the rhomboid muscles, the teres major muscles, the latissimus dorsi muscles, the deltoid muscles, the biceps muscles, and the triceps muscles when the garment is worn by the user. In another variation, for a garment that has a form factor of a bottom (e.g., shorts, pants, etc.), the set of interfaces provided in Block **S210** can include interfaces between a set of EMG electrodes and skin of the user proximal one or more of: the gluteus maximus muscles, the gluteus medius muscles, the vastus lateralis muscles, the gracilis muscles, the semimembranosus muscles, the semitendinosus muscles, the biceps femoris, the soleus muscles, the gastrocnemius muscles, the rectus femoris muscles, the sartorius muscles, the peroneus longus muscles, and the adductor longus muscles when the garment is worn by the user. Variations of the set of interfaces provided in Block **S210** can, however, be configured in any other suitable manner.

**[0077]** Block **S220** recites: at a mounting module coupled to the garment, providing an array of connection regions in communication with the set of biometric sensors, wherein the array of connection regions is configured to couple to a set of contacts of a control module in a first configuration. Block **S220** functions to enable transmission of biopotential signals generated from the body of the user, as the user exercises, from the set of sensor interfaces to a control module. Block **S220** is preferably implemented at embodiments, variations, and/or examples of the garment, the control module, the mounting module, and the set of biometric sensors described in Section 1 above. As such, providing the array of connection regions preferably comprises providing electrically conductive connection regions coupled between the set of biometric sensors and the mounting module in a set configuration, as described in Section 1 above, wherein a set of contacts of the control module can be coupled to the array of connection regions in a first configuration (e.g., wherein the control module is seated within the mounting module), and uncoupled from the array of connection regions in a second configuration **102** (e.g., wherein the control module is removed from the mounting module).

**[0078]** In variations, as discussed in relation to the control module of Section 1 above, the array of connection regions of the mounting module can be mapped to the set of contacts of the control module regardless of the orientation of the control module, such that Block **S220** includes providing a symmetric array of connection regions of the mounting module, and

providing a corresponding symmetric set of contacts of the control module. Furthermore, providing the array of connection regions for the control module can further include facilitating activation of indicator LEDs of the control module, wherein activation of the indicator LEDs can be triggered upon proper coupling between the array of connection regions of the mounting module and the set of contacts of the control module. While Block S220 is preferably described in relation to the system described in Section 1 above, Block S220 can alternatively be implemented using any other suitable garment with coupled biometric sensors configured to communicate with a control module.

[0079] Block S230 recites: in the first configuration of the control module, receiving a stream of electrical signals indicative of muscle activity from a subset of muscles of the user. Block S230 functions to acquire biosignal data from the user by way of the set of biometric sensors, when the control module is coupled with the garment in the first configuration. Block S230 preferably includes receiving signals from paired sensor channels (e.g., associated with paired biometric sensors of the set of biometric sensors). As such, paired biometric sensors and contacts of the set of contacts of the control module can facilitate reception of signals that can be used to determine a signal differential (i.e., a biopotential difference) across a pair of associated sensor channels.

[0080] Receiving the stream of electrical signals in Block S230 can include conditioning the stream of electrical signals S235 at a signal conditioning module, such as the signal conditioning module described in Section 1 above, in order to generate a conditioned signal stream. In conditioning the stream of electrical signals, Block S235 can include passing the stream of electrical signals through at least one of a low pass filter, a high pass filter, a band-pass filter, and a notch filter (i.e., a band-stop filter), in order to preprocess the datasets to remove a portion of any artifacts or interference (e.g., due to noise). In variations, the low pass filter can function to remove higher frequency noise and the high pass filter can function to remove lower frequency noise (e.g., due to waist movement/pressure artifacts). Any of the filters can further be supplemented with filters configured to remove or mitigate the frequency spectrum of any known noise components. Additionally or alternatively, Block S235 can include any one or more of: smoothing, clipping, deconvolving, detrending/offsetting, standardizing, resampling, hard-binding, predicting, windowing, and performing any other suitable data conditioning process upon any signals received in Block S230. In variations, S230 can further include storing conditioned or unconditioned signal data in memory, as describe in relation to the memory of the electronics subsystem in Section 1 above.

[0081] Block S240 recites: at the portable control module, transmitting the stream of electrical signals to a processing subsystem, which functions to transmit conditioned and/or unconditioned data derived from the stream of signals for additional processing. Block S240 is preferably implemented at an embodiment, variation, or example of the communication interface(s) described in relation to the electronics subsystem of the control module described in Section 1 above, whereby signal transmission is performed over a network associated with the control module and the processing subsystem. Transmitting the stream of electrical signals in Block S240 can be performed substantially continuously (e.g., every second, every millisecond, etc.) and/or in near-real-time, thereby facilitating near-real-time provision of compre-

hensive feedback to the user. Alternatively, transmitting the stream of electrical signals in Block S240 can be performed intermittently (e.g., only when the control module is coupled to the garment, at random time points, etc.) and/or in non-real-time. Furthermore, according to variations of the communication interface described in Section 1 above, transmitting the signals in Block S240 can involve wireless and/or wired transmission of data derived from the stream of electrical signals to the processing subsystem.

[0082] Block S250 recites: at the processing subsystem, transforming the stream of electrical signals into a set of exercise-related metrics indicative of exercise behavior of the user. Block S250 functions to generate an analysis derived from the stream of electrical signals received in Block S240, which can be used to provide feedback to the user regarding aspects of his/her exercise behavior. Block S250 can include determining metrics including one or more of: a metric related to effort output (e.g., total effort output as a ratio between an amount of work performed by a muscle group and a maximum amount of work that can be performed by the muscle group), a metric derived from an amount of cardio-activity performed by the user, a metric derived from an amount of strength-based activity performed by the user, a metric related to balance in utilization of all muscles of a muscle group; a metric related to a total number of muscles/muscle groups utilized during one or more exercises, a metric related to a number of repetitions of a performed exercise, a metric related to a number of sets of a performed exercise, a metric related to a distance conquered or time duration of an exercise, a metric associated with impropriety or properness of form in performing one or more exercises (e.g., as identified by signals of the signal stream indicative of muscles the user is using to perform an exercise, in relation to a desired group of muscles the user should use to perform the exercise with proper form), a metric related to target intensity level (e.g., as determined using a target intensity level desired by the user or another entity associated with the user, in relation to actual intensity level indicated by signals of the signal stream), a metric related to average heart rate throughout a workout, a metric related to average heart rate throughout a portion of a workout, a breakdown of muscle exertion for different muscle groups, exercise progress-related metrics, and any other suitable metrics. In generating any one or more of the above metrics, the processing system can be configured to utilize time information and signal feature information (e.g., amplitude, frequency, signal signatures, etc.) in determining metrics associated with individual muscles, groups of muscles, and overall assessments of activity of the user.

[0083] Block S260 recites: at an electronic device in communication with the processing subsystem, providing a report derived from the set of exercise-related metrics to the user. Block S260 preferably involves processing of the set of exercise-related metrics into a report that provides insights to the user, pertaining to the user's exercise behavior. Block S260 preferably implements an embodiment, variation, or example of the processing subsystem, electronic device, and network described in Section 1 above; however, Block S260 can additionally or alternatively be implemented using any other suitable processing and information provision elements. In providing the report(s), Block S260 preferably utilizes an exercise-monitoring application being executed at the electronic device, an example of which is shown in FIG. 11A. The report(s) can contribute to a virtual coaching environment that includes one or more of: training plans, recovery plans,

information regarding competitions (e.g., training regimens configured to prepare the user for an upcoming competition), instructions for stretching, instructions for injury prevention, instructions regarding proper form for conducting an exercise, and any other suitable coaching functions derived from metrics associated with the user's muscular activity.

**[0084]** Additionally or alternatively, the report(s) provided in Block S260 can be used to provide alerts to the user based upon received and processed data, an example of which is shown in FIG. 11B. For instance, Block S260 can include notifying the user or another entity if the user is focusing too much on a particular exercise or muscle group (e.g., by visually showing the muscle group(s) that are overemphasized and recommending other exercises to the user), or if the user is using a muscle group incorrectly during an exercise (e.g., if the user is demonstrating poor form). Additionally or alternatively, the reports can provide synopses pertaining to one or more of: a muscle breakdown of work performed/output for specific muscles; a breakdown of a score given for a workout, wherein the score can be tracked over time to monitor progress of the user; a classification of exercise as cardio-based or strength-based; indications of muscle atrophy, indications of rehabilitation progress; indications of fatigue; indications of potential or actual injury; and any other suitable reported factor. In one example, a report can provide a percentage of a workout associated with strength-based exercise vs. a percentage of a workout associated with cardio-based exercise. In another example, the report provided in Block S260 can additionally or alternatively provide a detailed breakdown of any exercise metric associated with one or more muscle groups, provided within a virtual display of various muscle groups.

**[0085]** The method 200 can further include Block S270, as shown in FIG. 10, which recites: detecting an orientation of the control module within the mounting module and adaptively adjusting a mapping between a set of contacts of the control module and an array of connection regions of the mounting module. Block S270 functions to enable proper signal reception and processing from a symmetric control module that can be coupled to the garment in multiple orientations. Block S270 can implement contact configuration(s) of the set of contacts of the control module and any other suitable data (e.g., accelerometer data, gyroscope data) in order to detect the orientation of the control module relative to the garment. Once the orientation of the control module is detected, Block S270 can include adapting signal reception and processing functions accordingly. As such, Block S270 can allow the control module to operate properly regardless of how the control module is coupled with the garment, in receiving and processing signals from the set of biometric sensors. For example, using the contact configuration shown in FIG. 6, signals X and Y can be received by way of contacts 1A and 1B in a first orientation of the control module, but if the control module is positioned "upside-down" in a second orientation, firmware implementing Block S270 can adapt signal reception and processing of the control module to receive signals X and Y by way of contacts 14B and 14A, respectively. As such, in the example, Block S270 can facilitate dynamic modification of the contact mapping in order to properly attribute signals X and Y to the correct muscle group or set of biometric sensors.

**[0086]** Additionally or alternatively, Block S270 can include post-processing of signals based upon supplementary data that can allow signatures associated with one or muscle

groups or types of activity to be identified. For instance, if accelerometer data indicates motion behavior associated with a first muscle group, but EMG signal data indicates muscle activity not associated with the first muscle group, Block S270 can involve reconfiguring a mapping between the set of contacts of the control module and the set of biometric sensors, post-reception of the signal stream from the set of biometric sensors, and generating metrics and reports according to the reconfigured mapping. Any other signatures derived from one or more of: gyroscope data, accelerometer data, GPS data, temperature data, location data, heart rate data, and any other suitable data can be used to identify the most probable muscle groups being used in an activity, and adjusting a mapping between the set of contacts of the control module accordingly. As such, identification of the configuration of the control module relative to the garment can be facilitated based upon cross-correlation between different types of data (e.g., accelerometer data, EMG sensor data), detection of identification contact configurations, and/or in any other suitable manner.

**[0087]** The method 200 can further include any one or more of: detecting misalignment of the control module, providing an indication of misalignment of the control module (e.g., using indicator LEDs), receiving a user input and providing a customized report based upon the user input (e.g., allowing the user to select a portion of a virtual display of various muscle groups and providing a report based upon the selection), allowing the user to receive information and feedback (e.g., training information, motivational feedback) from a community of associated users, and any other suitable steps or blocks that promote proper exercise behavior of the user.

**[0088]** Variations of the system 100 and method 200 include any combination or permutation of the described components and processes. Furthermore, various processes of the preferred method can be embodied and/or implemented at least in part as a machine configured to receive a computer-readable medium storing computer-readable instructions. The instructions are preferably executed by computer-executable components preferably integrated with a system and one or more portions of the control module 155 and/or a processor. The computer-readable medium can be stored on any suitable computer readable media such as RAMs, ROMs, flash memory, EEPROMs, optical devices (CD or DVD), hard drives, floppy drives, or any suitable device. The computer-executable component is preferably a general or application specific processor, but any suitable dedicated hardware device or hardware/firmware combination device can additionally or alternatively execute the instructions.

**[0089]** The FIGURES illustrate the architecture, functionality and operation of possible implementations of systems, methods and computer program products according to preferred embodiments, example configurations, and variations thereof. In this regard, each block in the flowchart or block diagrams may represent a module, segment, step, or portion of code, which comprises one or more executable instructions for implementing the specified logical function(s). It should also be noted that, in some alternative implementations, the functions noted in the block can occur out of the order noted in the FIGURES. For example, two blocks shown in succession may, in fact, be executed substantially concurrently, or the blocks may sometimes be executed in the reverse order, depending upon the functionality involved. It will also be noted that each block of the block diagrams and/or flowchart illustration, and combinations of blocks in the block diagrams

and/or flowchart illustration, can be implemented by special purpose hardware-based systems that perform the specified functions or acts, or combinations of special purpose hardware and computer instructions.

**[0090]** As a person skilled in the art will recognize from the previous detailed description and from the figures and claims, modifications and changes can be made to the preferred embodiments of the invention without departing from the scope of this invention defined in the following claims.

We claim:

**1.** A system for monitoring biometric signals of a user comprising:

a garment configured to be worn by the user and comprising a mounting module having an array of connection regions;

a set of biometric sensors coupled to the garment, the set of biometric sensors configured to communicate with the array of connection regions and configured to receive and transmit biometric signals indicative of muscle activity of the user by way of the array of connection regions; and

a portable control module configured to couple to the garment in a first configuration and to decouple from the garment in a second configuration and comprising:

a housing comprising an array of openings;

a set of contacts, each contact in the set of contacts including a first region that hermetically seals at least one of the array of openings and couples to at least one of the array of connection regions in the first configuration, and

an electronics subsystem coupled to the housing and in communication with a second region of each of the set of contacts.

**2.** The system of claim **1**, further comprising a processing subsystem configured to receive and process biometric signals from the portable control module, to determine a set of exercise-related metrics associated with muscle activity of the user based upon the biometric signals, and to provide a report to the user based upon at least a subset of the set of exercise-related metrics.

**3.** The system of claim **2**, wherein the set of biometric sensors comprises paired sensors configured to enable detection of a biopotential difference across two sensors, and wherein the processing subsystem is configured to determine at least one of the set of exercise-related metrics based upon the biopotential difference.

**4.** The system of claim **1**, wherein the set of contacts of the control module is configured in a symmetric array having a shared axis of symmetry with the housing of the control module.

**5.** The system of claim **4**, wherein the control module is configured to be coupled with the mounting module in a first orientation and a second orientation, and wherein the control module is configured to adaptively adjust a mapping between the set of contacts and the array of connection regions of the mounting module upon detection that the control module is in one of the first orientation and the second orientation.

**6.** The system of claim **5**, wherein the set of contacts of the control module is arranged in a symmetrically opposing arrangement, whereby paired sensors of the set of biometric sensors are configured to correspond to symmetrically opposing contacts of the set of contacts.

**7.** The system of claim **1**, wherein the mounting module includes a set of layers coupled to the garment and configured

to provide a biasing force that maintains contact between the set of contacts of the portable control module and the array of connection regions of the mounting module in the first configuration.

**8.** The system of claim **7**, wherein the set of layers of the mounting modules includes: a fabric layer affixed to the garment and defining a receiving pocket for the portable control module, wherein the fabric layer has an elastic opening that accommodates reception of the portable control module; a cradle deeper than the fabric layer and comprising the array of connection regions that couple to the set of biometric sensors; and a foam ring at least partially surrounding the cradle and deeper than the fabric layer.

**9.** The system of claim **8**, wherein each connection region in the array of connection regions has a first portion that is exposed through a first cradle surface, configured to provide a hermetic seal at the first cradle surface, and configured to contact the first region of at least one contact of the control module, and wherein each connection region in the array of connection regions has a second portion in communication with the first portion and configured to couple to a lead proximal a second cradle surface, wherein the lead enables electrical communication between a connection region of the array of connection regions and at least one biometric sensor of the set of biometric sensors.

**10.** The system of claim **1**, wherein the electronics subsystem is coupled to a set of indicator LEDs configured to indicate alignment of the control module with the mounting module in the first configuration.

**11.** A method for monitoring biometric signals of a user comprising:

at a garment configured to be worn by the user, providing a set of interfaces between the user and a set of biometric sensors at a set of body regions exhibiting muscle activity, upon coupling of the garment to the user;

at a mounting module coupled to the garment, providing an array of connection regions in communication with the set of biometric sensors and configured to couple to a set of contacts of a control module in a first configuration; in the first configuration of the control module, receiving a stream of electrical signals indicative of muscle activity from a subset of muscles of the user;

at the portable control module, transmitting the stream of electrical signals to a processing subsystem; and

at the processing system, transforming the stream of electrical signals into a set of exercise-related metrics indicative of exercise behavior of the user; and

at an electronic device in communication with the processing system, providing a report derived from the set of exercise-related metrics to the user.

**12.** The method of claim **11**, wherein providing the set of interfaces comprises providing interfaces between subsets of the set of biometric sensors and at least one of a first group of muscles comprising a the pectoralis muscles, the deltoid muscles, and the biceps muscles of the user, and a second group of muscles comprising the quadriceps muscles, the biceps femoris muscles, and the gluteus maximus muscles, upon coupling of the garment to the user.

**13.** The method of claim **12**, wherein providing the set of sensor interfaces comprises providing a first interface between a heart rate sensor and a first body region of the user, and providing a second interface between a respiration sensor and a second body region of the user.

**14.** The method of claim **13**, wherein transforming the stream of electrical signals into the set of exercise-related metrics comprises determining values of muscle exertion for a set of muscles selected by the user at an input device.

**15.** The method of claim **14**, wherein transforming the stream of electrical signals into the set of exercise-related metrics comprises determining values of effort output by a subset of muscles being used during an exercise activity of the user.

**16.** The method of claim **13**, wherein providing the report comprises providing a report including an indication of properness of form and target intensity level in performing an exercise, based upon the stream of electrical signals processed at the processing subsystem.

**17.** The method of claim **16**, wherein providing the report comprises providing a notification related to non-monitored muscle groups, based upon an analysis of activity of monitored muscle groups during an exercise activity.

**18.** The method of claim **11**, further comprising: at least at one of an electronics subsystem of the portable control module and the processing system, detecting an orientation of the

control module within the mounting module, and adaptively adjusting a mapping between the set of contacts of the control module and the array of connection regions of the mounting module, based upon the orientation of the control module.

**19.** The method of claim **12**, wherein detecting the orientation of the control module within the mounting module is based upon at least one of a configuration of identification pins associated with the set of contacts, and supplementary sensor data indicative of muscle activity signatures associated with muscle groups that have a high probability of being active during performance of an exercise.

**20.** The method of claim **11**, wherein providing the array of connection regions of the mounting module comprises providing a fabric layer affixed to the garment and defining a receiving pocket for the portable control module; providing a cradle deeper than the fabric layer and comprising the array of connection regions that couple to the set of biometric sensors; and providing a foam ring at least partially surrounding the cradle and configured deeper than the fabric layer.

\* \* \* \* \*

专利名称(译)	用于监测生物信号的系统和方法		
公开(公告)号	<a href="#">US20150148619A1</a>	公开(公告)日	2015-05-28
申请号	US14/541446	申请日	2014-11-14
[标]申请(专利权)人(译)	阿托斯WORKS		
申请(专利权)人(译)	ATHOS WORKS , INC.		
当前申请(专利权)人(译)	ATHOS WORKS , INC.		
[标]发明人	BERG JAMES BUTT HAMID JAYALATH DHANANJA WIEBE CHRISTOPHER		
发明人	BERG, JAMES BUTT, HAMID JAYALATH, DHANANJA WIEBE, CHRISTOPHER		
IPC分类号	A61B5/00 A61B5/0205 A61B5/11 A61B5/0478 A61B5/04 A61B5/0496 A61B5/0492 A61B5/0408		
CPC分类号	A61B5/6804 A61B5/0492 A61B5/0205 A61B5/0408 A61B5/0478 A61B5/08 A61B5/0496 A61B5/1112 A61B5/7445 A61B5/0533 A61B5/024 A61B5/04008 A61B5/0024 A61B5/1118 A61B2505/09		
优先权	62/013405 2014-06-17 US 62/077781 2014-11-10 US 62/016373 2014-06-24 US 61/908077 2013-11-23 US		
其他公开文献	US10292652		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

一种用于监控用户的生物信号的系统，包括：服装，被配置为由用户佩戴并且包括具有连接区域阵列的安装模块；一组生物识别传感器，其耦合到衣服并且被配置为与连接区域阵列通信以接收和发送指示用户的肌肉活动的生物信号；便携式控制模块，被配置为以第一配置连接到衣服并且以第二配置与衣服分离，并且包括：壳体，包括开口阵列；一组触头，每个触头包括第一区域和电子子系统，所述第一区域气密地密封所述开口阵列中的至少一个并且连接到所述第一配置中的所述连接区域阵列中的至少一个，所述电子子系统连接到所述壳体并与所述壳体连通。每个联系人的第二个区域。

