



US009636905B2

(12) **United States Patent**
Miller et al.

(10) **Patent No.:** **US 9,636,905 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **DEVICE AND METHOD FOR IDENTIFYING
A CHANGE IN A PREDETERMINED
CONDITION**

B41M 5/282; G01D 21/00; B41F 31/00;
B41F 31/002; A63H 3/36; B44F 1/14;
A63F 2250/1031; Y10S 428/913

USPC 116/200, 201, 206, 207, 216; 2/69, 82,
2/455; 250/472.1

See application file for complete search history.

(71) Applicant: **PROTECT ME ALERT SERIES,**
Mount Royal (CA)

(72) Inventors: **Lorne Miller,** Montreal (CA); **Neil
Miller,** Montreal (CA)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **8372683 Canada, Inc.,** St-Laurent (CA)

2,949,880 A * 8/1960 Fromer G01J 1/50
250/474.1
3,903,423 A * 9/1975 Zweig A61B 5/0059
250/473.1

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 97 days.

(Continued)

(21) Appl. No.: **14/444,628**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Jul. 28, 2014**

WO WO 2010003222 A2 * 1/2010 C09D 131/04

(65) **Prior Publication Data**

US 2016/0023455 A1 Jan. 28, 2016

Primary Examiner — R. A. Smith

Assistant Examiner — Tania Courson

(74) *Attorney, Agent, or Firm* — Cesari and McKenna,
LLP

(51) **Int. Cl.**

B41F 31/00 (2006.01)

A61B 5/01 (2006.01)

(Continued)

(57) **ABSTRACT**

In an embodiment, a device and method for identifying a change in a predetermined condition. The device is a patch injected with ink that transforms in response to a change in the predetermined condition, such as, a change in temperature or change in the ultraviolet (UV) index level. The ink includes thermochromic ink that transforms or identifiably changes based on a change in a temperature condition, and/or photochromic ink that transforms or identifiably changes based on a change in an UV index level condition. When temperature increases or decreases to reach one or more threshold temperature values, the thermochromic ink transforms in an identifiable manner to indicate a condition has be met. When the UV index level increase or decrease to reach one or more threshold UV index levels, the photochromic ink transforms in an identifiable manner to indicate that a condition has be met.

(52) **U.S. Cl.**


CPC **B41F 31/002** (2013.01); **A41D 1/00**
(2013.01); **A41D 11/00** (2013.01); **A41D 27/08**
(2013.01); **A61B 5/015** (2013.01); **A61B**
5/6814 (2013.01); **A63F 2250/1031** (2013.01);
A63H 3/36 (2013.01); **B41F 31/00** (2013.01);
B41M 5/282 (2013.01); **B41M 5/287**
(2013.01); **B44F 1/14** (2013.01); **G01D 21/00**
(2013.01);

(Continued)

(58) **Field of Classification Search**

CPC A61B 5/015; A61B 5/6814; G01J 1/419;
G01K 1/14; G01K 11/12; A41D 27/08;
A41D 1/00; A41D 11/00; B41M 5/287;

20 Claims, 3 Drawing Sheets



- (51) **Int. Cl.**
A61B 5/00 (2006.01)
G01J 1/42 (2006.01)
G01K 11/12 (2006.01)
A41D 27/08 (2006.01)
B41M 5/28 (2006.01)
G01D 21/00 (2006.01)
A41D 1/00 (2006.01)
A41D 11/00 (2006.01)
A63H 3/36 (2006.01)
B44F 1/14 (2006.01)
- (52) **U.S. Cl.**
 CPC *G01J* 1/429 (2013.01); *G01K* 11/12 (2013.01); *Y10S* 428/913 (2013.01)
- (56) **References Cited**
- U.S. PATENT DOCUMENTS
- | | | | | | | | | | |
|----------------|--------|------------|-------|-------------|-------------------|---------|-------------|-------|-------------|
| 4,028,118 A * | 6/1977 | Nakasuji | | C08K 5/0041 | 6,228,804 B1 * | 5/2001 | Nakashima | | C09K 9/02 |
| | | | | 106/31.19 | | | | | 503/201 |
| 4,681,791 A * | 7/1987 | Shibahashi | | B41M 5/287 | 6,416,853 B1 * | 7/2002 | Nakashima | | A63H 33/22 |
| | | | | 374/E11.021 | | | | | 428/29 |
| 4,725,462 A * | 2/1988 | Kimura | | A63H 3/02 | 6,594,927 B2 * | 7/2003 | Witkowski | | G09F 3/0288 |
| | | | | 283/97 | | | | | 40/306 |
| 4,767,647 A * | 8/1988 | Bree | | B05D 1/30 | 6,604,854 B1 * | 8/2003 | Limburg | | G01K 11/165 |
| | | | | 40/1.5 | | | | | 116/207 |
| 5,085,607 A * | 2/1992 | Shibahashi | | A63H 33/22 | 6,808,804 B2 * | 10/2004 | Hotaka | | B32B 27/08 |
| | | | | 106/31.16 | | | | | 428/156 |
| 5,219,625 A * | 6/1993 | Matsunami | | A63H 3/36 | 7,280,441 B2 * | 10/2007 | MacDonald | | A61F 13/42 |
| | | | | 349/199 | | | | | 116/206 |
| 5,389,093 A * | 2/1995 | Howell | | A61F 13/42 | 7,370,689 B2 * | 5/2008 | Wang | | A61F 7/03 |
| | | | | 604/361 | | | | | 165/10 |
| 5,503,583 A * | 4/1996 | Hippely | | A63H 33/22 | 7,458,670 B2 * | 12/2008 | Kuki | | B41J 3/28 |
| | | | | 446/14 | | | | | 347/101 |
| 6,060,157 A * | 5/2000 | LaPerre | | B44C 1/16 | 7,674,747 B1 * | 3/2010 | Long | | D06P 1/004 |
| | | | | 428/212 | | | | | 503/201 |
| 6,060,321 A * | 5/2000 | Hovorka | | G01N 31/22 | 7,738,175 B2 * | 6/2010 | Steenblik | | B44F 1/10 |
| | | | | 422/421 | | | | | 359/619 |
| 6,196,241 B1 * | 3/2001 | Doolan | | A45B 25/18 | RE42,628 E * | 8/2011 | Aperfine | | A41D 13/00 |
| | | | | 135/16 | | | | | 2/82 |
| | | | | | 8,029,190 B2 * | 10/2011 | MacDonald | | A41D 13/002 |
| | | | | | | | | | 116/216 |
| | | | | | 8,827,315 B2 * | 9/2014 | Waumans | | B42D 25/00 |
| | | | | | | | | | 235/489 |
| | | | | | 9,427,048 B2 * | 8/2016 | James | | B29D 35/12 |
| | | | | | 2004/0158156 A1 * | 8/2004 | Schneemeyer | | A61B 5/01 |
| | | | | | | | | | 600/474 |
| | | | | | 2005/0285050 A1 * | 12/2005 | Bruce | | G01J 1/50 |
| | | | | | | | | | 250/474.1 |
| | | | | | 2008/0289535 A1 * | 11/2008 | Spector | | D06P 1/004 |
| | | | | | | | | | 106/31.13 |
| | | | | | 2010/0012017 A1 * | 1/2010 | Miller | | A61B 5/015 |
| | | | | | | | | | 116/201 |
| | | | | | 2010/0313325 A1 * | 12/2010 | Ebejer | | A41B 13/005 |
| | | | | | | | | | 2/80 |
| | | | | | 2015/0330843 A1 * | 11/2015 | Bodley | | G01K 11/12 |
| | | | | | | | | | 116/201 |

* cited by examiner




FIG. 1A




FIG. 1B





FIG. 1C

**FIG. 2**

1

DEVICE AND METHOD FOR IDENTIFYING A CHANGE IN A PREDETERMINED CONDITION

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention pertains to the field of identification devices and in particular to a device configured to identify a change in a predetermined condition.

Background Information

There are a number of different devices that provide for the evaluation of a condition. For example a thermometer can be used to identify a particular outside temperature or body temperature. This manner in identification can be cumbersome, because, if one thinks there is an elevated body temperature, one must subsequently obtain and utilize a thermometer to determine if there is any concern. Additionally, the current status of other conditions may also be required, for example, sun exposure, moisture level or other conditions. Likewise similar to the use of a thermometer, typically cumbersome identification devices may be required for the evaluation of these other conditions.

SUMMARY OF THE INVENTION

An embodiment of the present invention provides a device and method for identifying a change in a predetermined condition. Illustratively, the device comprises a patch (e.g., made of silicon) and injected with ink. The ink is illustratively configured to transform in response to a change in the predetermined condition, such as, e.g., a change in temperature or a change in the ultraviolet (UV) index level. Illustratively, the ink includes thermochromic ink that transforms or otherwise identifiably changes based on a change in a temperature condition (e.g., cold and heat), and/or photochromic ink that transforms or otherwise identifiably changes based on a change in an UV index level condition. The patch may be attached to an article of clothing, for example, a child's garment. Specifically, when temperature increases or decreases to reach one or more threshold temperature values, the thermochromic ink in the patch transforms in an identifiable manner, such as by changing color, to indicate that a condition has been met (e.g., an environmental condition of "too" hot or "too" cold). Similarly, when the UV index level increases or decreases to reach one or more threshold UV index levels, the photochromic ink in the patch transforms in an identifiable manner, such as by changing color, to indicate that a condition has been met (e.g., an environmental condition of "too" much UV radiation). As such, and based on the condition being met as indicated by the transformation of the ink in the patch, actions can be taken, such as, for example, moving the wearer of the garment that includes the patch out of the environment that caused the condition to be met.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention description below refers to the accompanying drawings, of which:

FIG. 1A is an environment that include the patch for identifying a change in a predetermined condition;

FIG. 1B is an environment that include the patch for identifying a change in a predetermined condition;

FIG. 1C is an environment that include the patch for identifying a change in a predetermined condition; and

2

FIG. 2 is a flowchart detailing the steps of a procedure for identifying a change in a predetermined condition in accordance with an illustrative embodiment of the present invention.

DETAILED DESCRIPTION OF AN ILLUSTRATIVE EMBODIMENTS

FIG. 1A illustrates an environment **100A** that includes an exemplary patch **102** injected with thermochromic ink and/or photochromic ink. For example, the thermochromic ink may be a metamorphic ink and the photochromic ink may be Chomazone® ink available from Thermographic Measurements Ltd of Devon, UK. However, it is expressly contemplated that any thermochromic ink and/or photochromic ink may be utilized. Illustratively, the patch **102** is made of silicon and attached to an article of clothing, such as article **106**. Patch **102** is shown as a circle, and includes sun **104** that holds or stores the injectable ink. It should be noted that sun **104** is for illustrative purposes. In accordance with alternative embodiments, sun **104** may be depicted in other shapes and/or sizes. As such, the description of sun **104** should be taken as exemplary only. Although the patch is illustratively a circle, patch **102** may be any shape and/or size. More generally, patch **102** may comprise any size and/or shape that may be integrated with a design of article **106**. Illustratively, the patch **102** adheres to the article **106** in a known manner. The patch **102** may be adhered to the article **106** or, in alternative embodiments, may be integrated into the article **106**. As such, the description of patch **102** being adhered to article **106** should be taken as exemplary only. It should be noted that the description of a hat as an exemplary article **106** is for exemplary purposes and that the principles of the present invention may be utilized with any type of clothing. Illustratively, and as shown in FIG. 1A, the color of the sun **104**, that stores the ink, is clear.

When a threshold temperature (e.g., 94 degrees Fahrenheit) is reached, the thermochromic ink in the sun **104** of patch **102** transforms or changes color, for example, as shown in environment **100B** of FIG. 1B. Similarly, when a threshold UV index level (e.g., UV index reading of 4) is reached, the photochromic ink in sun **104** of patch **102** transforms or changes color, for example, as shown in environment **100B** of FIG. 1B. Illustratively, the threshold temperature and threshold UV index level are associated with the changing of "predetermined conditions" from an existing or initial value, with reference to an entity including but not limited to a living being or inanimate object, to a threshold value or limit. The existing state may also be with reference or regard to the environment proximate to the entity, including but not limited to the atmospheric state proximate to an entity or state of a second entity proximate to a first entity. Examples of existing states, include but are not limited to, temperature state, pressure state, moisture state, UV radiation state, or other state as would be readily understood by a worker skilled in the art.

The identifiable change of the ink can be detected by one or more unassisted human senses or with the assistance of instruments and the like. Illustratively, the identifiable change is a change in color of the inks. Specifically, the thermochromic ink and/or the photochromic ink are configured to visually transform upon a change in the predetermined condition from the initial value to the threshold value, for example the color of the ink can transform in response to changes in temperature, pressure, UV radiation or moisture. The type and reason of occurrence of the transformation of the ink can be directly dependent on the predeter-

mined condition changing from the initial value to the threshold value. For example, ink in the patch can be configured to visually transform upon reaching a particular temperature threshold value or a particular UV index threshold level (e.g., the predetermined condition being met or reached). It is noted that the thermochromic ink and/or photochromic ink are injected into the patch **102** while in a controlled environment. For example, the thermochromic ink and/or photochromic ink are injected into the patch **102** while the injector (e.g., person or machine) is operating in a dark room and the thermochromic ink and/or photochromic ink are not exposed to elevated temperatures and UV radiation.

As shown in environment **100B** of FIG. **1B**, the ink (e.g., thermochromic ink) in the sun **104** of the patch **102** attached to article **106** may transform or identifiably change from a first color (e.g., a “lighter” color) to a second color (e.g., a “darker” color), when the predetermined condition associated with temperature changes to reach the threshold value (e.g., 94 degrees Fahrenheit in the environment is reached). Similarly, and as shown in environment **100B** of FIG. **1B**, the ink (e.g., photochromic ink) in the sun **104** of the patch **102** attached to article **106** may transform or identifiably change from a first color (e.g., a lighter color) to a second color (e.g., a darker color), when the predetermined condition associated with UV index levels changes to reach the threshold value (e.g., UV index reading of 4 in the environment is reached).

FIG. **1C** depicts environment **100C** that shows the sun **104** of the patch **102** attached to article **106** that has transformed to a third color (e.g., an even darker color than the second color) based on a further threshold being reached. For example, when a further threshold temperature (e.g., 98 degrees Fahrenheit) is reached, the ink (e.g., thermochromic ink) in the sun **104** transforms from the second color (darker color) to a third color (even darker color), as seen in FIG. **1C**, to indicate a more “extreme” condition. Similarly, when a further threshold UV level (e.g., UV index reading of 7) is reached, the ink (e.g., photochromic ink) in sun **104** transforms from the second color to a third color (even darker color), as seen in FIG. **1C**, to indicate a more extreme condition.

This configuration of the patch **102** provide a means for determining if the wearer of the clothing is being exposed to an undesired level of heat and/or UV radiation. This can enable the prevention of sunburn for example and can provide a means for decreasing the chance of developing skin cancer as it relates to overexposure to sunlight. For example, wearer of the article **106** may be taking out of the sun or environment for a certain period of time. It is noted that when the patch **102** is no longer in the condition where the threshold value has been met, for a predetermined amount of time (e.g., 2 minutes), the ink in the patch **102** will go back to its initial value/first color (e.g., lighter color) as seen in FIG. **1A**. This configuration of the patch **102** can be particularly applied to infant or children’s clothing, for example T-shirts, shirts or hats. In this manner the patch **102** acts as a visual identifier for a parent can be given a visual identifier, for example the changing of the color of the patch **102** to red, when the infant or child is being exposed to an undesired level of heat and/or ultraviolet radiation.

FIG. **2** is a flowchart detailing the steps of a procedure for identifying a change in a predetermined condition in accordance with an illustrative embodiment of the present invention. The procedure starts at step **205** and continues to step **210** where a patch **102**, injected with thermochromic ink and/or photochromic ink, is placed or attached to an article

to be monitored. Specifically, the patch **102** may include a shape, such as sun **104**, that stores the ink(s). The article may be an infant’s hat, or a cooler intended to store food. At step **215**, the article, e.g., infant’s hat, with the attached the patch **102** (injected with the thermochromic ink and/or photochromic ink) is utilized in a particular environment having particular conditions. For example, an infant wearing the article **106** with the attached patch **102** may be outside in the sun and exposed to an outside temperature and a particular UV light radiations.

The procedure continues to step **220** where the conditions of the environment change (e.g., change in a predetermined condition) to reach a threshold value causing the ink of patch **102** to transform and identifiably change. Illustratively, the conditions of the environment may cause the thermochromic ink and/or photochromic ink of patch **102** to change visually, and specifically, to change color. Specifically, the thermochromic ink in the patch **102** attached to article **106** transforms or identifiably changes from a first color to a second color, when the conditions of the environment meet or reach a temperature threshold value. More specifically, when temperature increases or decreases to reach one or more threshold temperature values, the thermochromic ink in the patch **102** transforms in an identifiable manner, such as changing color, to indicate that a condition has been met (e.g., an environmental condition of too hot or too cold). For example, a temperature threshold value may be 94 degrees Fahrenheit and initial temperature of the environment may be 88 degrees Fahrenheit. Thus, when the temperature of the environment changes (e.g., change in the predetermined condition) and increases to reach 94 degrees Fahrenheit, the thermochromic ink changes from a first color to a second color, as seen in environment **100B** of FIG. **1B**.

Similarly, when the UV index level increase or decrease to reach one or more threshold UV index levels, the photochromic ink in the patch **102** transforms in an identifiable manner, such as changing color, to indicate that a condition has been met (e.g., an environmental condition of “too” much UV radiation). For example, a threshold UV index level may be 4 and the initial UV index value may be 2. Thus, when the UV index level of the environment changes and increases to reach the UV index level of 4, the thermochromic ink changes from a first color to a second color, as seen in environment **100B** of FIG. **1B**.

The procedure continues to step **225**, where the procedure ends. It is noted that although the procedure of FIG. **2** describe a single threshold value being reached, it is expressly contemplated that the procedure **200** can utilize one or more additional predetermined conditions. For example, an additional temperature threshold value may be 98 degrees Fahrenheit. Thus, when the conditions of the environment change and reach 98 degrees Fahrenheit, the thermochromic ink changes from a second color to a third color as seen in environment **100C** of FIG. **1C**.

It is noted that when the patch **102** is no longer in the condition where the change in the predetermined condition has reached the threshold value, for a predetermined amount of time (e.g., 2 minutes), the ink in the patch **102** will go back to the first color (e.g., lighter color), as shown in FIG. **1A**. Further, although reference is made to a rise or increase in temperature or UV index level causing the threshold value to be met, a drop or decrease in temperature or UV index level can also cause threshold value to be met. For example, the predetermined condition may be 32 degrees Fahrenheit. As such, when the temperature drops to 32 degrees Fahrenheit, the thermochromic ink changes from the first color to the second color as depicted in FIG. **1B**.

5

The foregoing description has been directed to specific subject matter. It will be apparent, however, that other variations and modifications may be made to the described subject matter, with the attainment of some or all of its advantages. It is expressly contemplated that the procedures, processes, and methods described herein may be implemented in alternative orders. For example, the patch is shaped in order to form a cover for an apparatus, for example a cover for furniture, chairs, stroller, car seats, bags, or other type of cover as would be readily understood by a worker skilled in the art. In alternative embodiments, the patch may be attached to or adhere to, for example a towel, bed sheet, wash cloth, blanket, curtain, bandage, artwork, or other type of sheet-like product as would be readily understood by those skilled in the art. Additionally, the color of the patch is neutral. In another embodiment, the patch is colored. The selection of the color of the patch may be chosen based on the color of the ink being utilized. For example, the color of the patch can be chosen to be the same as that of the ink before it has changed and to contrast with the color of the ink after it has changed in response to stimulus (e.g., temperature UV index level). Moreover, although reference is made to the patch being injected with both thermochromic ink and/or photochromic ink, it is expressly contemplated that the patch could be injected with either thermochromic ink or photochromic ink, individually. Accordingly, this description is to be taken only by way of example and not to otherwise limit the scope of the subject matter described herein. Therefore, it is the object of the appended claims to cover all such variations and modifications as come within the true spirit and scope of the subject matter.

What is claimed is:

1. A device, comprising:
a silicon patch configured in a particular shape and further configured to be attached to an article, the silicon patch having an area configured to store and hold injectable ink; and
the injectable ink configured to be injected and stored within the area of the silicon patch, the injectable ink configured to identifiably change based on a change of a predetermined condition from an initial value to a threshold value,
where the silicon patch visually changes its appearance based on the injectable ink identifiably changing when the predetermined condition changes from the initial value to the threshold value.
2. The device of claim 1, wherein the injectable ink identifiably changes from a first color to a second color when the predetermined condition changes from the initial value to the threshold value.
3. The device of claim 1, wherein the injectable ink includes at least one of thermochromic ink and photochromic ink.
4. The device of claim 1, wherein the injectable ink is configured to identifiably changes in response a changing of a temperature from an initial temperature value to a temperature threshold value.
5. The device of claim 1, wherein the injectable ink is configured to identifiably changes in response to a changing of an ultraviolet (UV) index level value from an initial UV index level value to a threshold UV index level value.

6

6. The device of claim 1, wherein the injectable ink identifiably changes from a first color to a second color when the injectable ink identifiably changes.

7. The device of claim 6, wherein the injectable ink identifiably changes from the second color to a third color when a further threshold value is reached based on a further change of the predetermined condition.

8. The device of claim 1, wherein the predetermined condition is related to at least one of ultraviolet, temperature level, moisture level, or pressure level.

9. The device of claim 6, wherein the injectable ink identifiably changes from the second color to the first color after a predetermined amount of time and when the threshold value is no longer reached.

10. The device of claim 1, wherein the article is one of an article of clothing, a cooler, and a cover for furniture.

11. A method, comprising:

providing a patch, attached to an article, the patch injected with at least one type of injectable ink and storing the at least one type of injectable ink, wherein the injectable ink has a first color; and

transforming of the injectable ink from the first color to a second color based on a change in a predetermined condition from an initial value to a threshold value, wherein the transforming of the injectable ink causes the patch to visually change.

12. The method of claim 11, wherein the injectable ink includes at least one of thermochromic ink and photochromic ink.

13. The method of claim 11, further comprising detecting a change in temperature from an initial temperature value to a threshold temperature value to determine the predetermined condition changed from the initial value to the threshold value, and in response, the injectable ink transforming from the first color to the second color.

14. The method of claim 11, wherein detecting a change in ultraviolet (UV) index level from an initial UV index level value to a threshold UV index level to determine the predetermined condition changed from the initial value to the threshold value, and in response, the injectable ink transforming from the first color to the second color.

15. The method of claim 11, wherein the second color is darker than the first color.

16. The method of claim 11, wherein the injectable ink changes from the second color to a third color when a further threshold value is reached based on a further change of the predetermined condition.

17. The method of claim 16, wherein third color is darker than the second color.

18. The method of claim 11, wherein the predetermined condition is related to at least one of ultraviolet, temperature level, moisture level, or pressure level.

19. The method of claim 11, wherein the injectable ink changes from the second color to the first color after a predetermined amount of time and when the threshold value is no longer reached.

20. The method of claim 11, wherein the change in the predetermined condition is associated with one of an increase in temperature or a decrease in temperature.

* * * * *

专利名称(译)	用于识别预定条件的变化的装置和方法		
公开(公告)号	US9636905	公开(公告)日	2017-05-02
申请号	US14/444628	申请日	2014-07-28
[标]申请(专利权)人(译)	保护我ALERT系列		
申请(专利权)人(译)	保护我ALERT系列		
当前申请(专利权)人(译)	8372683加拿大公司		
[标]发明人	MILLER LORNE MILLER NEIL		
发明人	MILLER, LORNE MILLER, NEIL		
IPC分类号	B41F31/00 G01J1/42 G01K11/12 A41D27/08 B41M5/28 G01D21/00 A61B5/00 A61B5/01 A41D1/00 B44F1/14 A63H3/36 A41D11/00		
CPC分类号	B41F31/002 A41D1/00 A41D11/00 A41D27/08 A61B5/015 A61B5/6814 A63F2250/1031 A63H3/36 B41F31/00 B41M5/282 B41M5/287 B44F1/14 G01D21/00 G01J1/429 G01K11/12 Y10S428/913 G01J1/50 G01J5/48		
审查员(译)	史密斯		
其他公开文献	US20160023455A1		
外部链接	Espacenet USPTO		

摘要(译)

在一个实施例中，一种用于识别预定条件的变化的装置和方法。该装置是注入墨水的贴片，其响应于预定条件的变化而变换，例如温度变化或紫外（UV）指数水平的变化。油墨包括基于温度条件的变化而变换或可识别地变化的热致变色油墨，和/或基于UV指数水平条件的变化而变换或可识别地变化的光致变色油墨。当温度升高或降低以达到一个或多个阈值温度值时，热致变色墨水以可识别的方式变换以指示已满足条件。当UV指数水平增加或减少以达到一个或多个阈值UV指数水平时，光致变色油墨以可识别的方式变换以指示已满足条件。

