



US010010721B2

(12) **United States Patent**
Slayton et al.

(10) **Patent No.:** **US 10,010,721 B2**
(45) **Date of Patent:** ***Jul. 3, 2018**

- (54) **ENERGY BASED FAT REDUCTION**
- (71) Applicant: **Guided Therapy Systems, LLC**, Mesa, AZ (US)
- (72) Inventors: **Michael H. Slayton**, Tempe, AZ (US); **Peter G. Barthe**, Phoenix, AZ (US)
- (73) Assignee: **Guided Therapy Systems, L.L.C.**, Mesa, AZ (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
This patent is subject to a terminal disclaimer.

(58) **Field of Classification Search**
CPC A61N 7/00; A61N 2007/0008; A61N 2007/0052; A61N 2007/027;
(Continued)

(56) **References Cited**
U.S. PATENT DOCUMENTS

2,427,348 A 9/1947 Bond et al.
2,792,829 A 2/1952 Calosi
(Continued)

FOREIGN PATENT DOCUMENTS

CN 104027893 9/2014
DE 4029175 3/1992
(Continued)

- (21) Appl. No.: **15/829,175**
- (22) Filed: **Dec. 1, 2017**

OTHER PUBLICATIONS

Ulthera Exhibit 1025, Ulthera Oral Proceeding Demonstrative Slides (filed Oct. 2, 2017 in re IPR2016-01459).
(Continued)

- (65) **Prior Publication Data**
US 2018/0104515 A1 Apr. 19, 2018

Primary Examiner — Bo J Peng
(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear LLP


Related U.S. Application Data

- (63) Continuation of application No. 15/650,525, filed on Jul. 14, 2017, now Pat. No. 9,833,639, which is a
(Continued)

(57) **ABSTRACT**
Methods for non-invasive fat reduction can include targeting a region of interest below a surface of skin, which contains fat and delivering ultrasound energy to the region of interest. The ultrasound energy generates a thermal lesion with said ultrasound energy on a fat cell. The lesion can create an opening in the surface of the fat cell, which allows the draining of a fluid out of the fat cell and through the opening. In addition, by applying ultrasound energy to fat cells to increase the temperature to between 43 degrees and 49 degrees, cell apoptosis can be realized, thereby resulting in reduction of fat.

- (51) **Int. Cl.**
A61N 7/00 (2006.01)
G01S 7/52 (2006.01)
(Continued)
- (52) **U.S. Cl.**
CPC *A61N 7/00* (2013.01); *A61B 5/4869* (2013.01); *A61B 8/0858* (2013.01);
(Continued)

20 Claims, 27 Drawing Sheets



Related U.S. Application Data					
	continuation of application No. 15/380,267, filed on Dec. 15, 2016, now Pat. No. 9,713,731, which is a continuation of application No. 15/041,804, filed on Feb. 11, 2016, now Pat. No. 9,533,175, which is a continuation of application No. 14/550,772, filed on Nov. 21, 2014, now Pat. No. 9,283,409, which is a continuation of application No. 14/192,520, filed on Feb. 27, 2014, now Pat. No. 8,920,324, which is a continuation of application No. 12/646,609, filed on Dec. 23, 2009, now Pat. No. 8,663,112, which is a continuation-in-part of application No. 11/163,154, filed on Oct. 6, 2005, now Pat. No. 8,133,180.	4,534,221 A	8/1985	Fife et al.	
		4,566,459 A	1/1986	Umemura et al.	
		4,567,895 A	2/1986	Putzke	
		4,586,512 A	5/1986	Do-Huu	
		4,601,296 A	7/1986	Yerushalmi	
		4,620,546 A	11/1986	Aida et al.	
		4,637,256 A	1/1987	Sugiyama et al.	
		4,646,756 A	3/1987	Waimough	
		4,663,358 A	5/1987	Hyon	
		4,668,516 A	5/1987	Duraffourd et al.	
		4,672,591 A	6/1987	Breimesser et al.	
		4,680,499 A	7/1987	Umemura et al.	
		4,697,588 A	10/1987	Reichenberger	
		4,754,760 A	7/1988	Fukukita et al.	
		4,757,820 A	7/1988	Itoh	
		4,771,205 A	9/1988	Mequio	
		4,801,459 A	1/1989	Liburdy	
		4,803,625 A	2/1989	Fu et al.	
		4,807,633 A	2/1989	Fry	
		4,817,615 A	4/1989	Fukukita et al.	
		4,858,613 A	8/1989	Fry	
		4,860,732 A	8/1989	Hasegawa et al.	
		4,865,041 A	9/1989	Hassler	
		4,865,042 A	9/1989	Umemura	
		4,867,169 A	9/1989	Machida	
		4,874,562 A	10/1989	Hyon	
		4,875,487 A	10/1989	Seppi	
		4,881,212 A	11/1989	Takeuchi	
		4,891,043 A	1/1990	Zeimer et al.	
		4,893,624 A	1/1990	Lele	
		4,896,673 A	1/1990	Rose	
		4,900,540 A	2/1990	Ryan et al.	
		4,901,729 A	2/1990	Saitoh	
		4,917,096 A	4/1990	Englehart	
		4,932,414 A	6/1990	Coleman et al.	
		4,938,216 A	7/1990	Lele	
		4,938,217 A	7/1990	Lele	
		4,947,046 A	8/1990	Kawabata et al.	
		4,951,653 A	8/1990	Fry	
		4,955,365 A	9/1990	Fry	
		4,958,626 A	9/1990	Nambu	
		4,976,709 A	12/1990	Sand	
		4,979,501 A	12/1990	Valchanov	
		4,992,989 A	2/1991	Watanabe et al.	
		5,012,797 A	5/1991	Liang	
		5,018,508 A	5/1991	Fry et al.	
		5,030,874 A	7/1991	Saito et al.	
		5,036,855 A	8/1991	Fry	
		5,040,537 A	8/1991	Katakura	
		5,054,310 A	10/1991	Flynn	
		5,054,470 A	10/1991	Fry	
		5,054,491 A	10/1991	Saito et al.	
		5,070,879 A	12/1991	Herres	
		5,088,495 A	2/1992	Miyagawa	
		5,115,814 A	5/1992	Griffith	
		5,117,832 A	6/1992	Sanghvi	
		5,123,418 A	6/1992	Saurel	
		5,142,511 A	8/1992	Kanai et al.	
		5,143,063 A	9/1992	Fellner	
		5,143,074 A	9/1992	Dory	
		5,149,319 A	9/1992	Unger	
		5,150,711 A	9/1992	Dory	
		5,150,714 A	9/1992	Green	
		5,152,294 A	10/1992	Mochizuki et al.	
		5,156,144 A	10/1992	Iwasaki	
		5,158,536 A	10/1992	Sekins	
		5,159,931 A	11/1992	Pini	
		5,163,421 A	11/1992	Bernstein	
		5,163,436 A	11/1992	Saitoh et al.	
		5,178,135 A	1/1993	Uchiyama et al.	
		5,190,518 A	3/1993	Takasu	
		5,190,766 A	3/1993	Ishihara	
		5,191,880 A	3/1993	McLeod	
		5,205,287 A	4/1993	Erbel et al.	
		5,209,720 A	5/1993	Unger	
		5,212,671 A	5/1993	Fujii et al.	
		5,215,680 A	6/1993	D'Arrigo	
		5,224,467 A	7/1993	Oku	
		5,230,334 A	7/1993	Klopotek	
(60)	Provisional application No. 61/140,725, filed on Dec. 24, 2008, provisional application No. 60/616,753, filed on Oct. 6, 2004.				
(51)	Int. Cl.				
	<i>A61B 5/00</i> (2006.01)				
	<i>A61B 8/08</i> (2006.01)				
	<i>B06B 1/06</i> (2006.01)				
	<i>G01S 15/89</i> (2006.01)				
	<i>A61N 7/02</i> (2006.01)				
	<i>A61B 90/00</i> (2016.01)				
(52)	U.S. Cl.				
	CPC <i>B06B 1/0607</i> (2013.01); <i>G01S 7/5208</i> (2013.01); <i>G01S 15/899</i> (2013.01); <i>A61B 2090/378</i> (2016.02); <i>A61N 2007/0008</i> (2013.01); <i>A61N 2007/0052</i> (2013.01); <i>A61N 2007/027</i> (2013.01)				
(58)	Field of Classification Search				
	CPC ... A61B 5/4869; A61B 8/0858; A61B 1/0607; A61B 2090/378; B06B 1/0607; G01S 7/5208; G01S 15/899				
	See application file for complete search history.				
(56)	References Cited				
	U.S. PATENT DOCUMENTS				
	3,913,386 A 10/1975 Saglio				
	3,965,455 A 6/1976 Hurwitz				
	3,992,925 A 11/1976 Perilhou				
	4,039,312 A 8/1977 Patru				
	4,059,098 A 11/1977 Murdock				
	4,101,795 A 7/1978 Fukumoto				
	4,151,834 A 5/1979 Sato et al.				
	4,166,967 A 9/1979 Benes et al.				
	4,211,948 A 7/1980 Smith et al.				
	4,211,949 A 7/1980 Brisken et al.				
	4,213,344 A 7/1980 Rose				
	4,276,491 A 6/1981 Daniel				
	4,315,514 A 2/1982 Drewes et al.				
	4,325,381 A 4/1982 Glenn				
	4,343,301 A 8/1982 Indech				
	4,372,296 A 2/1983 Fahim				
	4,379,145 A 4/1983 Masuho et al.				
	4,381,007 A 4/1983 Doss				
	4,381,787 A 5/1983 Hottinger				
	4,397,314 A 8/1983 Vaguine				
	4,409,839 A 10/1983 Taenzer				
	4,431,008 A 2/1984 Wanner et al.				
	4,441,486 A 4/1984 Pounds				
	4,452,084 A 6/1984 Taenzer				
	4,484,569 A 11/1984 Driller				
	4,507,582 A 3/1985 Glenn				
	4,513,749 A 4/1985 Kino				
	4,513,750 A 4/1985 Heyman et al.				
	4,527,550 A 7/1985 Ruggera et al.				
	4,528,979 A 7/1985 Marchenko				

(56)		References Cited					
				5,577,507	A	11/1996	Snyder et al.
				5,577,991	A	11/1996	Akui et al.
				5,580,575	A	12/1996	Unger et al.
				5,601,526	A *	2/1997	Chapelon A61N 7/02 601/2
				5,603,323	A	2/1997	Pflugrath et al.
				5,605,154	A *	2/1997	Ries G01S 7/52046 600/444
5,230,338	A	7/1993	Allen et al.	5,609,562	A	3/1997	Kaali
5,247,924	A	9/1993	Suzuki et al.	5,615,091	A	3/1997	Palatnik
5,255,681	A	10/1993	Ishimura et al.	5,618,275	A	4/1997	Bock
5,257,970	A	11/1993	Dougherty	5,620,479	A	4/1997	Diederich
5,265,614	A	11/1993	Hayakawa	5,622,175	A	4/1997	Sudol et al.
5,267,985	A	12/1993	Shimada	5,617,858	A	5/1997	Taverna et al.
5,269,297	A	12/1993	Weng	5,638,819	A	6/1997	Manwaring et al.
5,282,797	A	2/1994	Chess	5,643,179	A *	7/1997	Fujimoto A61N 7/02 601/2
5,295,484	A	3/1994	Marcus	5,644,085	A	7/1997	Lorraine et al.
5,295,486	A	3/1994	Wollschlager et al.	5,647,373	A	7/1997	Paltieli
5,304,169	A	4/1994	Sand	5,655,535	A	8/1997	Frlmel et al.
5,305,756	A	4/1994	Entrekin et al.	5,655,538	A	8/1997	Lorraine
5,321,520	A	6/1994	Inga et al.	5,657,760	A	8/1997	Ying
5,323,779	A	6/1994	Hardy et al.	5,658,328	A	8/1997	Johnson
5,327,895	A	7/1994	Hashimoto et al.	5,660,836	A *	8/1997	Knowlton A61B 18/12 128/898
5,329,202	A	7/1994	Garlick et al.	5,662,116	A	9/1997	Kondo
5,348,016	A	9/1994	Unger et al.	5,665,053	A	9/1997	Jacobs
5,358,466	A *	10/1994	Aida A61B 17/2256 600/439	5,665,141	A	9/1997	Vago
5,360,268	A	11/1994	Hayashi	5,671,746	A	9/1997	Dreschel et al.
5,370,121	A	12/1994	Reichenberger	5,673,699	A	10/1997	Trahey et al.
5,370,122	A	12/1994	Kunig et al.	5,676,692	A	10/1997	Sanghvi
5,371,483	A	12/1994	Bhardwaj	5,685,820	A	11/1997	Riek et al.
5,375,602	A	12/1994	Lancee et al.	5,690,608	A	11/1997	Watanabe
5,379,773	A	1/1995	Hornsby	5,694,936	A	12/1997	Fujimoto
5,380,280	A	1/1995	Peterson	5,697,897	A	12/1997	Buchholtz
5,380,519	A	1/1995	Schneider et al.	5,701,900	A	12/1997	Shehada et al.
5,383,917	A	1/1995	Desai et al.	5,704,361	A	1/1998	Seward et al.
5,391,140	A	2/1995	Schaetzle et al.	5,706,252	A	1/1998	Le Verrier et al.
5,391,197	A	2/1995	Burdette et al.	5,706,564	A	1/1998	Rhyne
5,392,259	A	2/1995	Bolorforosh	5,715,823	A	2/1998	Wood et al.
5,396,143	A	3/1995	Seyed-Bolorforosh et al.	5,720,287	A	2/1998	Chapelon et al.
5,398,689	A	3/1995	Connor et al.	5,722,411	A	3/1998	Suzuki
5,406,503	A	4/1995	Williams	5,727,554	A	3/1998	Kalend et al.
5,413,550	A *	5/1995	Castel A61H 23/0245 601/2	5,735,280	A	4/1998	Sherman et al.
5,417,216	A	5/1995	Tanaka	5,743,863	A	4/1998	Chapelon
5,419,327	A	5/1995	Rohwedder	5,746,005	A	5/1998	Steinberg
5,423,220	A	6/1995	Finsterwald et al.	5,746,762	A	5/1998	Bass
5,435,311	A	7/1995	Umamura	5,748,767	A	5/1998	Raab
5,438,998	A	8/1995	Hanafy	5,749,364	A	5/1998	Sliwa et al.
5,443,068	A *	8/1995	Cline A61B 5/0555 600/411	5,755,228	A	5/1998	Wilson et al.
5,445,611	A	8/1995	Eppstein et al.	5,755,753	A	5/1998	Knowlton
5,458,596	A	10/1995	Lax	5,762,066	A	6/1998	Law
5,460,179	A	10/1995	Okunuki et al.	5,763,886	A	6/1998	Schulte
5,460,595	A	10/1995	Hall et al.	5,769,790	A	6/1998	Watkins
5,469,854	A	11/1995	Unger et al.	5,779,644	A	7/1998	Eberle et al.
5,471,488	A	12/1995	Fujio	5,792,058	A	8/1998	Lee
5,472,405	A	12/1995	Buchholtz et al.	5,795,297	A	8/1998	Daigle
5,487,388	A	1/1996	Rello et al.	5,795,311	A	8/1998	Wess
5,492,126	A	2/1996	Hennige	5,810,009	A	9/1998	Mine et al.
5,496,256	A	3/1996	Bock	5,810,888	A	9/1998	Fenn
5,501,655	A	3/1996	Rolt	5,814,599	A	9/1998	Mitragotri et al.
5,503,152	A	4/1996	Oakley et al.	5,817,013	A	10/1998	Ginn et al.
5,503,320	A	4/1996	Webster et al.	5,817,021	A	10/1998	Reichenberger
5,507,790	A	4/1996	Weiss	5,820,564	A	10/1998	Slayton
5,511,296	A	4/1996	Dias et al.	5,823,962	A	10/1998	Schaetzle
5,520,188	A	5/1996	Hennige	5,827,204	A	10/1998	Grandia et al.
5,522,869	A	6/1996	Burdette	5,840,032	A	11/1998	Hatfield et al.
5,523,058	A	6/1996	Umamura et al.	5,844,140	A	12/1998	Seale
5,524,620	A	6/1996	Rosenchein	5,853,367	A	12/1998	Chalek et al.
5,524,624	A	6/1996	Tepper	5,869,751	A	2/1999	Bonin
5,524,625	A	6/1996	Okazaki	5,871,524	A	2/1999	Knowlton
5,526,624	A	6/1996	Berg	5,873,902	A	2/1999	Sanghvi
5,526,812	A	6/1996	Dumoulin et al.	5,876,341	A	3/1999	Wang et al.
5,526,814	A	6/1996	Cline et al.	5,879,303	A	3/1999	Averkiou et al.
5,526,815	A	6/1996	Granz	5,882,557	A	3/1999	Hayakawa
5,529,070	A	6/1996	Augustine et al.	5,891,034	A	4/1999	Bucholz
5,540,235	A	7/1996	Wilson	5,895,356	A	4/1999	Andrus et al.
5,558,092	A	9/1996	Unger	5,899,861	A	5/1999	Friemel et al.
5,560,362	A	10/1996	Sliwa et al.	5,904,659	A	5/1999	Duarte
5,575,291	A	11/1996	Hayakawa				
5,575,807	A	11/1996	Faller				
5,577,502	A	11/1996	Darrow et al.				

(56)

References Cited

U.S. PATENT DOCUMENTS

5,919,219 A	7/1999	Knowlton	6,246,898 B1	6/2001	Vesely et al.
5,923,099 A	7/1999	Bilir	6,251,074 B1	6/2001	Averkiou et al.
5,924,989 A	7/1999	Polz	6,251,088 B1	6/2001	Kaufman et al.
5,928,169 A	7/1999	Schatzle et al.	6,268,405 B1	7/2001	Yao
5,931,805 A	8/1999	Brisken	6,273,864 B1	8/2001	Duarte
5,938,606 A	8/1999	Bonnefous	6,280,402 B1	8/2001	Ishibashi et al.
5,938,612 A	8/1999	Kline-Schoder	6,287,257 B1	9/2001	Maticchuk
5,948,011 A	9/1999	Knowlton	6,287,304 B1	9/2001	Eggers et al.
5,957,844 A	9/1999	Dekel	6,296,619 B1	10/2001	Brisken
5,957,882 A	9/1999	Nita et al.	6,301,989 B1	10/2001	Brown et al.
5,957,941 A	9/1999	Ream	6,307,302 B1	10/2001	Toda
5,964,707 A	10/1999	Fenster et al.	6,309,355 B1	10/2001	Cain et al.
5,967,980 A	10/1999	Ferre et al.	6,311,090 B1	10/2001	Knowlton
5,968,034 A	10/1999	Fullmer	6,315,741 B1 *	11/2001	Martin A61B 8/4254
5,971,949 A	10/1999	Levin			601/3
5,977,538 A	11/1999	Unger et al.	6,322,509 B1	11/2001	Pan et al.
5,984,881 A *	11/1999	Ishibashi A61B 17/2256	6,322,532 B1	11/2001	D'Sa
		601/2	6,325,540 B1	12/2001	Lounsberry et al.
5,984,882 A	11/1999	Rosenchein	6,325,758 B1	12/2001	Carol et al.
5,990,598 A	11/1999	Sudol et al.	6,325,769 B1	12/2001	Klopotek
5,997,471 A	12/1999	Gumb et al.	6,325,798 B1	12/2001	Edwards et al.
5,997,497 A	12/1999	Nita et al.	6,350,276 B1	2/2002	Knowlton
5,999,843 A	12/1999	Anbar	6,356,780 B1	3/2002	Licato et al.
6,004,262 A	12/1999	Putz et al.	6,361,531 B1	3/2002	Hissong
6,007,499 A	12/1999	Martin et al.	6,370,411 B1	4/2002	Osadchy et al.
6,013,032 A	1/2000	Savord	6,375,672 B1	4/2002	Aksan
6,014,473 A	1/2000	Hossack et al.	6,377,854 B1	4/2002	Knowlton
6,016,255 A	1/2000	Bolan et al.	6,377,855 B1	4/2002	Knowlton
6,019,724 A	2/2000	Gronningsaeter et al.	6,381,497 B1	4/2002	Knowlton
6,022,308 A	2/2000	Williams	6,381,498 B1	4/2002	Knowlton
6,022,327 A	2/2000	Chang	6,387,380 B1	5/2002	Knowlton
6,030,374 A	2/2000	McDaniel	6,390,982 B1	5/2002	Bova et al.
6,036,646 A	3/2000	Barthe	6,405,090 B1	6/2002	Knowlton
6,039,048 A	3/2000	Silberg	6,409,720 B1	6/2002	Hissong
6,039,689 A	3/2000	Lizzi	6,413,216 B1	7/2002	Cain et al.
6,042,556 A *	3/2000	Beach A61N 7/02	6,413,253 B1	7/2002	Koop
		600/437	6,413,254 B1	7/2002	Hissong
6,049,159 A	4/2000	Barthe	6,419,648 B1	7/2002	Vitek
6,050,943 A	4/2000	Slayton	6,423,007 B2	7/2002	Lizzi et al.
6,059,727 A	5/2000	Fowlkes	6,425,865 B1	7/2002	Salcudean
6,071,239 A	6/2000	Cribbs	6,425,867 B1	7/2002	Vaezy
6,080,108 A	6/2000	Dunham	6,425,912 B1	7/2002	Knowlton
6,083,148 A	7/2000	Williams	6,428,477 B1	8/2002	Mason
6,086,535 A	7/2000	Ishibashi	6,428,532 B1	8/2002	Doukas
6,086,580 A	7/2000	Mordon et al.	6,430,446 B1	8/2002	Knowlton
6,090,054 A	7/2000	Tagishi	6,432,057 B1	8/2002	Mazess et al.
6,093,148 A *	7/2000	Fujimoto A61N 7/00	6,432,067 B1	8/2002	Martin
		600/438	6,432,101 B1	8/2002	Weber
6,093,883 A	7/2000	Sanghvi	6,436,061 B1	8/2002	Costantino
6,101,407 A	8/2000	Groezinger	6,438,424 B1	8/2002	Knowlton
6,106,469 A	8/2000	Suzuki et al.	6,440,071 B1	8/2002	Slayton
6,113,558 A	9/2000	Rosenchein	6,440,121 B1	8/2002	Weber
6,113,559 A	9/2000	Klopotek	6,443,914 B1	9/2002	Costantino
6,120,452 A	9/2000	Barthe	6,447,443 B1	9/2002	Keogh et al.
6,123,081 A	9/2000	Durette	6,451,013 B1	9/2002	Bays et al.
6,126,619 A	10/2000	Peterson et al.	6,453,202 B1	9/2002	Knowlton
6,135,971 A	10/2000	Hutchinson	6,461,304 B1	10/2002	Tanaka et al.
6,139,499 A	10/2000	Wilk	6,461,378 B1	10/2002	Knowlton
6,159,150 A	12/2000	Yale et al.	6,470,216 B1	10/2002	Knowlton
6,171,244 B1	1/2001	Finger et al.	6,338,716 B1	11/2002	Hossack et al.
6,176,840 B1	1/2001	Nishimura	6,488,626 B1	12/2002	Lizzi
6,183,426 B1	2/2001	Akisada	6,491,657 B2	12/2002	Rowe
6,183,502 B1	2/2001	Takeuchi	6,500,121 B1	12/2002	Slayton
6,183,773 B1	2/2001	Anderson	6,500,141 B1	12/2002	Irion
6,190,323 B1	2/2001	Dias	6,506,171 B1	1/2003	Vitek et al.
6,190,336 B1	2/2001	Duarte	6,508,774 B1	1/2003	Acker
6,193,658 B1	2/2001	Wendelken	6,511,427 B1	1/2003	Sliwa, Jr. et al.
6,198,956 B1	3/2001	Dunne	6,511,428 B1	1/2003	Azuma
6,210,327 B1	4/2001	Brackett et al.	6,514,244 B2	2/2003	Pope
6,213,948 B1	4/2001	Barthe	6,517,484 B1	2/2003	Wilk
6,216,029 B1	4/2001	Paltieli	6,524,250 B1	2/2003	Weber
6,233,476 B1	5/2001	Strommer et al.	6,666,835 B2	3/2003	Martin
6,234,990 B1	5/2001	Rowe et al.	6,540,679 B2	4/2003	Slayton
6,241,753 B1 *	6/2001	Knowlton A61B 18/12	6,540,685 B1	4/2003	Rhoads et al.
		128/898	6,540,700 B1	4/2003	Fujimoto et al.
			6,547,788 B1	4/2003	Maguire et al.
			6,554,771 B1	4/2003	Buil et al.
			6,569,099 B1	5/2003	Babaev
			6,569,108 B2	5/2003	Sarvazyan et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,572,552 B2	6/2003	Fukukita	7,258,674 B2	8/2007	Cribbs
6,575,956 B1	6/2003	Brisken et al.	7,273,459 B2	9/2007	Desilets
6,595,934 B1	7/2003	Hissong	7,294,125 B2	11/2007	Phalen et al.
6,599,256 B1	7/2003	Acker	7,297,117 B2	11/2007	Trucco
6,605,080 B1	8/2003	Altshuler et al.	7,303,555 B2	12/2007	Makin et al.
6,607,498 B2	8/2003	Eshel	7,311,679 B2	12/2007	Desilets et al.
6,618,620 B1	9/2003	Freundlich et al.	7,327,071 B2	2/2008	Nishiyama et al.
6,623,430 B1	9/2003	Slayton	7,331,951 B2	2/2008	Eshel et al.
6,626,854 B2	9/2003	Friedman	7,332,985 B2	2/2008	Larson et al.
6,626,855 B1	9/2003	Weng	7,338,434 B1	3/2008	Haarstad et al.
6,638,226 B2	10/2003	He et al.	7,347,855 B2	3/2008	Eshel
6,645,150 B2	11/2003	Angelsen et al.	RE40,403 E	6/2008	Cho et al.
6,645,162 B2	11/2003	Friedman	7,393,325 B2	7/2008	Barthe
6,662,054 B2	12/2003	Kreindel	7,398,116 B2	7/2008	Edwards
6,663,627 B2	12/2003	Francischelli	7,399,279 B2	7/2008	Abend et al.
6,665,806 B1	12/2003	Shimizu	7,491,171 B2	2/2009	Barthe et al.
6,669,638 B1	12/2003	Miller	7,507,235 B2	3/2009	Keogh et al.
6,685,639 B1	2/2004	Wang et al.	7,510,536 B2	3/2009	Foley et al.
6,685,640 B1	2/2004	Fry	7,517,315 B2	4/2009	Willis
6,692,450 B1	2/2004	Coleman	7,530,356 B2	5/2009	Slayton
6,699,237 B2	3/2004	Weber	7,530,958 B2	5/2009	Slayton
6,716,184 B2	4/2004	Vaezy et al.	7,532,201 B2	5/2009	Quistgaard et al.
6,719,449 B1	4/2004	Laughlin	7,571,336 B2	8/2009	Barthe
6,719,694 B2	4/2004	Weng	7,601,120 B2	10/2009	Moilanen et al.
6,726,627 B1	4/2004	Lizzi et al.	7,615,015 B2	11/2009	Coleman
6,733,449 B1	5/2004	Krishnamurthy et al.	7,615,016 B2	11/2009	Barthe
6,749,624 B2	6/2004	Knowlton	7,631,611 B1	12/2009	Dick et al.
6,772,490 B2	8/2004	Toda	7,652,411 B2	1/2010	Crunkilton et al.
6,773,409 B2	8/2004	Truckai et al.	7,662,114 B2	2/2010	Seip et al.
6,775,404 B1	8/2004	Pagoulatos et al.	7,674,257 B2	3/2010	Pless et al.
6,790,187 B2	9/2004	Thompson et al.	7,686,763 B2	3/2010	Vaezy et al.
6,824,516 B2	11/2004	Batten et al.	7,713,203 B2	3/2010	Lacoste et al.
6,825,176 B2	11/2004	White et al.	7,694,406 B2	4/2010	Wildes et al.
6,835,940 B2	12/2004	Morikawa et al.	7,695,437 B2	4/2010	Quistgaard et al.
6,846,290 B2	1/2005	Lizzi et al.	7,727,156 B2	6/2010	Angelsen et al.
6,875,176 B2	4/2005	Mourad et al.	7,758,524 B2	7/2010	Barthe
6,882,884 B1	4/2005	Mosk et al.	7,766,848 B2	8/2010	Desilets et al.
6,887,239 B2	5/2005	Elstrom	7,789,841 B2	9/2010	Huckle et al.
6,889,089 B2	5/2005	Behl	7,806,839 B2	10/2010	Mast et al.
6,896,657 B2	5/2005	Willis	7,815,570 B2	10/2010	Eshel et al.
6,902,536 B2	6/2005	Manna	7,819,826 B2	10/2010	Diederich et al.
6,905,466 B2	6/2005	Salgo	7,828,734 B2	10/2010	Azhari et al.
6,918,907 B2	7/2005	Kelly	7,824,348 B2	11/2010	Barthe
6,920,883 B2	7/2005	Bessette	7,833,162 B2	11/2010	Hasegawa et al.
6,921,371 B2	7/2005	Wilson	7,841,984 B2	11/2010	Cribbs et al.
6,932,771 B2	8/2005	Whitmore	7,846,096 B2	12/2010	Mast et al.
6,932,814 B2	8/2005	Wood	7,857,773 B2	12/2010	Desilets et al.
6,936,044 B2	8/2005	McDaniel	7,875,023 B2	1/2011	Eshel et al.
6,936,046 B2	8/2005	Hissong	7,901,359 B2	3/2011	Mandrusov et al.
6,945,937 B2	9/2005	Culp et al.	7,905,007 B2	3/2011	Calisti et al.
6,948,843 B2	9/2005	Laugharn et al.	7,905,844 B2	3/2011	Desilets et al.
6,953,941 B2	10/2005	Nakano et al.	7,914,453 B2	3/2011	Slayton et al.
6,958,043 B2	10/2005	Hissong	7,914,469 B2	3/2011	Torbati
6,971,994 B1	12/2005	Young et al.	7,955,281 B2	6/2011	Pedersen et al.
6,974,417 B2	12/2005	Lockwood	7,967,764 B2	6/2011	Lidgren et al.
6,976,492 B2	12/2005	Ingle	7,967,839 B2	6/2011	Flock et al.
6,992,305 B2	1/2006	Maezawa et al.	7,955,262 B2	7/2011	Rosenberg
6,997,923 B2	2/2006	Anderson	7,993,289 B2	8/2011	Quistgaard et al.
7,006,874 B2	2/2006	Knowlton	8,057,465 B2	9/2011	Sliwa, Jr. et al.
7,020,528 B2	3/2006	Neev	8,057,389 B2	11/2011	Barthe et al.
7,022,089 B2	4/2006	Ooba	8,066,641 B2	11/2011	Barthe et al.
7,058,440 B2	6/2006	Heuscher et al.	8,123,707 B2	2/2012	Huckle et al.
7,063,666 B2	6/2006	Weng	8,128,618 B2	3/2012	Gliklich et al.
7,070,565 B2	7/2006	Vaezy et al.	8,133,180 B2	3/2012	Slayton et al.
7,074,218 B2	7/2006	Washington et al.	8,133,191 B2	3/2012	Rosenberg et al.
7,094,252 B2	8/2006	Koop	8,142,200 B2	3/2012	Crunkilton et al.
7,108,663 B2	9/2006	Talish et al.	8,152,904 B2	4/2012	Slobodzian et al.
7,115,123 B2	10/2006	Knowlton	8,162,858 B2	4/2012	Manna et al.
7,122,029 B2	10/2006	Koop et al.	8,166,332 B2	4/2012	Barthe et al.
7,142,905 B2	11/2006	Slayton	8,182,428 B2	5/2012	Angelsen et al.
7,165,451 B1	1/2007	Brooks et al.	8,197,409 B2	6/2012	Foley et al.
7,179,238 B2	2/2007	Hissong	8,206,299 B2	6/2012	Foley et al.
7,189,230 B2	3/2007	Knowlton	8,208,346 B2	6/2012	Crunkilton
7,229,411 B2	6/2007	Slayton	8,211,017 B2	7/2012	Foley et al.
7,235,592 B2	6/2007	Muratoglu	8,262,591 B2	9/2012	Pedersen et al.
			8,262,650 B2	9/2012	Zanelli et al.
			8,264,126 B2	9/2012	Toda et al.
			8,273,037 B2	9/2012	Kreindel et al.
			8,282,554 B2	10/2012	Makin et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

			9,833,639	B2	12/2017	Slayton et al.	
			9,833,640	B2	12/2017	Barthe et al.	
			2001/0009997	A1	7/2001	Pope	
			2001/0009999	A1	7/2001	Kaufman et al.	
			2001/0014780	A1	8/2001	Martin	
			2001/0014819	A1	8/2001	Ingle	
			2001/0031922	A1*	10/2001	Weng	A61B 17/0057 600/439
8,292,835	B1	10/2012	Cimino				
8,298,163	B1	10/2012	Cimino				
8,333,700	B1	12/2012	Barthe et al.				
8,334,637	B2	12/2012	Crunkilton et al.				
8,337,407	B2	12/2012	Quistgaard et al.				
8,343,051	B2	1/2013	Desilets et al.				
8,454,540	B2	1/2013	Eshel et al.				
8,366,622	B2	2/2013	Slayton et al.				
8,398,549	B2	3/2013	Palmeri et al.				
8,409,097	B2	4/2013	Slayton et al.				
8,425,435	B2	4/2013	Wing et al.				
8,388,535	B2	5/2013	Weng et al.				
8,444,562	B2	5/2013	Barthe et al.				
8,460,193	B2	6/2013	Barthe et al.				
8,480,585	B2	7/2013	Slayton et al.				
8,506,486	B2	8/2013	Slayton et al.				
8,512,250	B2	8/2013	Quistgaard et al.				
8,523,775	B2	9/2013	Barthe et al.				
8,535,228	B2	9/2013	Slayton et al.				
8,570,837	B2	10/2013	Toda et al.				
8,573,392	B2	11/2013	Bennett et al.				
8,583,211	B2	11/2013	Salomir et al.				
8,585,618	B2	11/2013	Hunziker et al.				
8,604,672	B2	12/2013	Toda et al.				
8,622,937	B2	1/2014	Weng et al.				
8,636,665	B2	1/2014	Slayton et al.				
8,640,193	B2	1/2014	Shigeeda				
8,641,622	B2	2/2014	Barthe et al.				
8,663,112	B2	3/2014	Slayton et al.				
8,672,848	B2	3/2014	Slayton et al.				
8,690,778	B2	4/2014	Slayton et al.				
8,690,779	B2	4/2014	Slayton et al.				
8,690,780	B2	4/2014	Slayton et al.				
8,708,935	B2	4/2014	Barthe et al.				
8,715,186	B2	5/2014	Slayton et al.				
8,726,781	B2	5/2014	Eckhoff et al.				
8,728,071	B2	5/2014	Lischinsky et al.				
8,753,295	B2	6/2014	Thierman				
8,758,253	B2	6/2014	Sano et al.				
8,836,203	B2	9/2014	Nobles et al.				
8,857,438	B2	10/2014	Barthe et al.				
8,858,471	B2	10/2014	Barthe et al.				
8,915,853	B2	12/2014	Barthe et al.				
8,915,854	B2	12/2014	Slayton et al.				
8,915,870	B2	12/2014	Barthe et al.				
8,920,320	B2	12/2014	Stecco et al.				
8,920,324	B2	12/2014	Slayton et al.				
8,926,533	B2	1/2015	Bockenstedt et al.				
8,932,224	B2	1/2015	Barthe et al.				
8,932,238	B2	1/2015	Wing et al.				
8,968,205	B2	3/2015	Zeng et al.				
9,011,336	B2	4/2015	Slayton et al.				
9,039,617	B2	5/2015	Slayton et al.				
9,039,619	B2	5/2015	Barthe et al.				
9,095,697	B2	8/2015	Barthe et al.				
9,114,247	B2	8/2015	Barthe et al.				
9,216,276	B2	12/2015	Slayton et al.				
9,272,162	B2	3/2016	Slayton et al.				
9,283,409	B2	3/2016	Slayton et al.				
9,283,410	B2	3/2016	Slayton et al.				
9,320,537	B2	4/2016	Slayton et al.				
9,421,029	B2	8/2016	Barthe et al.				
9,427,600	B2	8/2016	Barthe et al.				
9,427,601	B2	8/2016	Barthe et al.				
9,440,096	B2	9/2016	Barthe et al.				
9,510,802	B2	12/2016	Barthe et al.				
9,522,290	B2	12/2016	Slayton et al.				
9,533,175	B2	1/2017	Slayton et al.				
9,694,211	B2	7/2017	Barthe et al.				
9,694,212	B2	7/2017	Barthe et al.				
9,707,412	B2	7/2017	Slayton et al.				
9,713,731	B2	7/2017	Slayton et al.				
9,802,063	B2	10/2017	Barthe et al.				
9,827,449	B2	11/2017	Barthe et al.				
9,827,450	B2	11/2017	Slayton et al.				
			2001/0039380	A1	11/2001	Larson et al.	
			2001/0041880	A1	11/2001	Brisken	
			2002/0000763	A1	1/2002	Jones	
			2002/0002345	A1	1/2002	Marlinghaus	
			2002/0040199	A1	4/2002	Klopotek	
			2002/0040442	A1	4/2002	Ishidera	
			2002/0055702	A1	5/2002	Atala	
			2002/0062077	A1	5/2002	Emmenegger	
			2002/0062142	A1	5/2002	Knowlton	
			2002/0072691	A1	6/2002	Thompson et al.	
			2002/0082528	A1	6/2002	Friedman	
			2002/0082529	A1	6/2002	Suorsa et al.	
			2002/0082589	A1	6/2002	Friedman	
			2002/0087080	A1	7/2002	Slayton	
			2002/0095143	A1	7/2002	Key	
			2002/0099094	A1	7/2002	Anderson	
			2002/0115917	A1	8/2002	Honda et al.	
			2002/0128639	A1	8/2002	Pless et al.	
			2002/0128648	A1	9/2002	Weber	
			2002/0143252	A1	10/2002	Dunne et al.	
			2002/0156400	A1	10/2002	Babaev	
			2002/0161357	A1	10/2002	Anderson	
			2002/0165529	A1	11/2002	Danek	
			2002/0168049	A1	11/2002	Schriever	
			2002/0169394	A1	11/2002	Eppstein et al.	
			2002/0169442	A1	11/2002	Neev	
			2002/0173721	A1	11/2002	Grunwald et al.	
			2002/0193784	A1	12/2002	McHale et al.	
			2002/0193831	A1	12/2002	Smith	
			2003/0009153	A1	1/2003	Brisken et al.	
			2003/0014039	A1	1/2003	Barzell et al.	
			2003/0018255	A1	1/2003	Martin	
			2003/0018270	A1	1/2003	Makin et al.	
			2003/0023283	A1*	1/2003	McDaniel	A61K 8/02 607/88
			2003/0028111	A1	2/2003	Vaezy et al.	
			2003/0028113	A1	2/2003	Gilbert et al.	
			2003/0032900	A1	2/2003	Ella	
			2003/0036706	A1	2/2003	Slayton et al.	
			2003/0040739	A1	2/2003	Koop	
			2003/0050678	A1	3/2003	Sierra	
			2003/0055308	A1	3/2003	Friemel et al.	
			2003/0055417	A1	3/2003	Truckai et al.	
			2003/0060736	A1	3/2003	Martin et al.	
			2003/0065313	A1	4/2003	Koop	
			2003/0066708	A1	4/2003	Allison et al.	
			2003/0073907	A1	4/2003	Taylor	
			2003/0074023	A1	4/2003	Kaplan	
			2003/0083536	A1	5/2003	Eshel	
			2003/0092988	A1	5/2003	Makin	
			2003/0097071	A1	5/2003	Halmann et al.	
			2003/0099383	A1	5/2003	Lefebvre	
			2003/0125629	A1	7/2003	Ustuner	
			2003/0135135	A1	7/2003	Miwa et al.	
			2003/0139790	A1	7/2003	Ingle et al.	
			2003/0149366	A1	8/2003	Stringer et al.	
			2003/0153961	A1	8/2003	Babaev	
			2003/0171678	A1	9/2003	Batten et al.	
			2003/0171701	A1	9/2003	Babaev	
			2003/0176790	A1	9/2003	Slayton	
			2003/0191396	A1	10/2003	Sanghvi	
			2003/0199794	A1	10/2003	Sakurai et al.	
			2003/0200481	A1	10/2003	Stanley	
			2003/0212129	A1	11/2003	Liu et al.	
			2003/0212351	A1	11/2003	Hissong	
			2003/0212393	A1	11/2003	Knowlton	
			2003/0216648	A1	11/2003	Lizzi et al.	
			2003/0216795	A1	11/2003	Harth	
			2003/0220536	A1	11/2003	Hissong	
			2003/0220585	A1	11/2003	Hissong	
			2003/0229331	A1	12/2003	Brisken et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2003/0233085	A1	12/2003	Giammarusti	2005/0256406	A1	11/2005	Barthe
2003/0236487	A1	12/2003	Knowlton	2005/0261584	A1	11/2005	Eshel
2004/0000316	A1	1/2004	Knowlton	2005/0261585	A1	11/2005	Makin et al.
2004/0001809	A1	1/2004	Brisken	2005/0267454	A1	12/2005	Hissong
2004/0002658	A1	1/2004	Marian, Jr.	2005/0288748	A1	12/2005	Li et al.
2004/0002705	A1	1/2004	Knowlton	2006/0004306	A1	1/2006	Altshuler
2004/0010222	A1	1/2004	Nunomura et al.	2006/0020260	A1	1/2006	Dover et al.
2004/0015079	A1	1/2004	Berger et al.	2006/0025756	A1	2/2006	Francischelli
2004/0015106	A1	1/2004	Coleman	2006/0042201	A1	3/2006	Curry
2004/0030227	A1	2/2004	Littrup	2006/0058664	A1	3/2006	Barthe
2004/0039312	A1	2/2004	Hillstead	2006/0058671	A1	3/2006	Vitek et al.
2004/0039418	A1	2/2004	Elstrom	2006/0058707	A1	3/2006	Barthe
2004/0041563	A1	3/2004	Lewin et al.	2006/0058712	A1	3/2006	Altshuler et al.
2004/0041880	A1	3/2004	Ikeda et al.	2006/0074309	A1	4/2006	Bonnefous
2004/0042168	A1	3/2004	Yang et al.	2006/0074313	A1	4/2006	Slayton et al.
2004/0044375	A1	3/2004	Diederich et al.	2006/0074314	A1	4/2006	Slayton
2004/0049134	A1	3/2004	Tosaya et al.	2006/0074355	A1	4/2006	Slayton
2004/0049734	A1	3/2004	Tosaya et al.	2006/0079816	A1	4/2006	Barthe
2004/0059266	A1	3/2004	Fry	2006/0079868	A1	4/2006	Makin
2004/0068186	A1	4/2004	Ishida et al.	2006/0084891	A1	4/2006	Barthe
2004/0073079	A1	4/2004	Altshuler et al.	2006/0089632	A1	4/2006	Barthe
2004/0073113	A1	4/2004	Salgo	2006/0089688	A1	4/2006	Panesco
2004/0073115	A1	4/2004	Horzewski et al.	2006/0094988	A1	5/2006	Tosaya
2004/0073116	A1	4/2004	Smith	2006/0111744	A1	5/2006	Makin
2004/0073204	A1	4/2004	Ryan et al.	2006/0116583	A1	6/2006	Ogasawara et al.
2004/0077977	A1	4/2004	Ella et al.	2006/0116671	A1	6/2006	Slayton
2004/0082857	A1	4/2004	Schonenberger	2006/0122508	A1	6/2006	Slayton
2004/0082859	A1	4/2004	Schaer	2006/0122509	A1	6/2006	Desilets
2004/0102697	A1	5/2004	Evron	2006/0161062	A1	7/2006	Arditi et al.
2004/0105559	A1	6/2004	Aylward et al.	2006/0184069	A1	8/2006	Vaitekunas
2004/0106867	A1	6/2004	Eshel et al.	2006/0184071	A1	8/2006	Klopotek
2004/0122323	A1	6/2004	Vortman et al.	2006/0189972	A1	8/2006	Grossman
2004/0122493	A1	6/2004	Ishibashi et al.	2006/0206105	A1	9/2006	Chopra
2004/0143297	A1	7/2004	Ramsey	2006/0224090	A1	10/2006	Ostrovsky et al.
2004/0152982	A1	8/2004	Hwang et al.	2006/0229514	A1	10/2006	Wiener
2004/0158150	A1	8/2004	Rabiner et al.	2006/0241440	A1	10/2006	Eshel
2004/0186535	A1	9/2004	Knowlton	2006/0241442	A1	10/2006	Barthe
2004/0189155	A1	9/2004	Funakubo	2006/0241470	A1	10/2006	Novak et al.
2004/0206365	A1	10/2004	Knowlton	2006/0241576	A1	10/2006	Diederich et al.
2004/0210214	A1	10/2004	Knowlton	2006/0250046	A1	11/2006	Koizumi et al.
2004/0217675	A1	11/2004	Desilets	2006/0282691	A1	12/2006	Barthe
2004/0249318	A1	12/2004	Tanaka	2006/0291710	A1	12/2006	Wang et al.
2004/0254620	A1	12/2004	Lacoste	2007/0016039	A1	1/2007	Vortman et al.
2004/0267252	A1	12/2004	Washington et al.	2007/0032784	A1	2/2007	Gliklich et al.
2005/0033201	A1	2/2005	Takahashi	2007/0035201	A1	2/2007	Desilets
2005/0033316	A1	2/2005	Kertz	2007/0055154	A1	3/2007	Torbati
2005/0038340	A1	2/2005	Vaezy et al.	2007/0055155	A1	3/2007	Owen et al.
2005/0055018	A1	3/2005	Kreindel	2007/0055156	A1	3/2007	Desilets et al.
2005/0055073	A1	3/2005	Weber	2007/0065420	A1	3/2007	Johnson
2005/0061834	A1	3/2005	Garcia et al.	2007/0083120	A1	4/2007	Cain et al.
2005/0070961	A1	3/2005	Maki	2007/0087060	A1	4/2007	Dietrich
2005/0074407	A1	4/2005	Smith	2007/0088245	A1	4/2007	Babaev et al.
2005/0080469	A1	4/2005	Larson	2007/0088346	A1	4/2007	Mirizzi et al.
2005/0085731	A1	4/2005	Miller et al.	2007/0161902	A1	7/2007	Dan
2005/0091770	A1	5/2005	Mourad et al.	2007/0166357	A1	7/2007	Shaffer et al.
2005/0096542	A1	5/2005	Weng et al.	2007/0167709	A1	7/2007	Slayton
2005/0104690	A1	5/2005	Larson et al.	2007/0208253	A1	9/2007	Slayton
2005/0113689	A1	5/2005	Gritzky	2007/0219604	A1	9/2007	Yaroslaysky et al.
2005/0131302	A1	6/2005	Poland	2007/0219605	A1	9/2007	Yaroslaysky et al.
2005/0137656	A1	6/2005	Malak	2007/0238994	A1	10/2007	Stecco et al.
2005/0143677	A1	6/2005	Young et al.	2007/0239075	A1	10/2007	Rosenberg
2005/0154313	A1	7/2005	Desilets	2007/0239077	A1	10/2007	Azhari et al.
2005/0154314	A1	7/2005	Quistgaard	2007/0239079	A1	10/2007	Manstein et al.
2005/0154332	A1	7/2005	Zanelli	2007/0239142	A1	10/2007	Altshuler
2005/0154431	A1	7/2005	Quistgaard	2008/0015435	A1	1/2008	Cribbs et al.
2005/0187495	A1	8/2005	Quistgaard	2008/0027328	A1	1/2008	Klopotek
2005/0191252	A1	9/2005	Mitsui	2008/0039724	A1	2/2008	Seip et al.
2005/0193451	A1	9/2005	Quistgaard	2008/0071255	A1	3/2008	Barthe
2005/0193820	A1	9/2005	Sheljaskow et al.	2008/0086054	A1	4/2008	Slayton
2005/0197681	A1	9/2005	Barolet et al.	2008/0086056	A1	4/2008	Chang et al.
2005/0228281	A1	10/2005	Nefos	2008/0097214	A1	4/2008	Meyers et al.
2005/0240127	A1	10/2005	Seip et al.	2008/0097253	A1	4/2008	Pedersen et al.
2005/0240170	A1	10/2005	Zhang et al.	2008/0114251	A1	5/2008	Weymer et al.
2005/0251120	A1	11/2005	Anderson et al.	2008/0139974	A1	6/2008	Da Silva
2005/0251125	A1	11/2005	Pless et al.	2008/0146970	A1	6/2008	Litman et al.
				2008/0167556	A1	7/2008	Thompson
				2008/0183077	A1	7/2008	Moreau-Gobard et al.
				2008/0183110	A1	7/2008	Davenport et al.
				2008/0188745	A1	8/2008	Chen et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0194964 A1	8/2008	Randall et al.	2011/0190745 A1	8/2011	Uebelhoer et al.
2008/0195000 A1	8/2008	Spooner et al.	2011/0201976 A1	8/2011	Sanghvi et al.
2008/0200810 A1	8/2008	Buchalter	2011/0251524 A1	10/2011	Azhari et al.
2008/0200813 A1	8/2008	Quistgaard	2011/0251527 A1	10/2011	Kushculey et al.
2008/0214966 A1	9/2008	Slayton	2011/0270137 A1	11/2011	Goren et al.
2008/0214988 A1	9/2008	Altshuler et al.	2011/0319793 A1	12/2011	Henrik et al.
2008/0221491 A1	9/2008	Slayton	2011/0319794 A1	12/2011	Gertner
2008/0223379 A1	9/2008	Stuker et al.	2012/0004549 A1	1/2012	Barthe et al.
2008/0242991 A1	10/2008	Moon et al.	2012/0016239 A1	1/2012	Barthe et al.
2008/0243035 A1	10/2008	Crunkilton	2012/0029353 A1	2/2012	Slayton et al.
2008/0269608 A1	10/2008	Anderson et al.	2012/0035473 A1	2/2012	Sanghvi et al.
2008/0275342 A1	11/2008	Barthe	2012/0035475 A1	2/2012	Barthe et al.
2008/0281206 A1	11/2008	Bartlett et al.	2012/0035476 A1	2/2012	Barthe et al.
2008/0281236 A1	11/2008	Eshel et al.	2012/0046547 A1	2/2012	Barthe et al.
2008/0281237 A1	11/2008	Slayton	2012/0053458 A1	3/2012	Barthe et al.
2008/0281255 A1	11/2008	Slayton	2012/0059288 A1	3/2012	Barthe et al.
2008/0294073 A1	11/2008	Barthe	2012/0111339 A1	5/2012	Barthe et al.
2008/0319356 A1	12/2008	Cain	2012/0123304 A1	5/2012	Rybyanets et al.
2009/0005680 A1	1/2009	Jones et al.	2012/0136280 A1	5/2012	Rosenberg et al.
2009/0012394 A1	1/2009	Hobelsberger et al.	2012/0136282 A1	5/2012	Rosenberg et al.
2009/0043198 A1	2/2009	Milner et al.	2012/0143056 A1	6/2012	Slayton et al.
2009/0043293 A1	2/2009	Pankratov et al.	2012/0143100 A1	6/2012	Jeong et al.
2009/0048514 A1	2/2009	Azhari et al.	2012/0165668 A1	6/2012	Slayton et al.
2009/0069677 A1	3/2009	Chen et al.	2012/0165848 A1	6/2012	Slayton et al.
2009/0093737 A1	4/2009	Chomas et al.	2012/0191019 A1	7/2012	Desilets et al.
2009/0156969 A1	6/2009	Santangelo	2012/0191020 A1	7/2012	Vitek et al.
2009/0163807 A1	6/2009	Sliwa	2012/0197120 A1	8/2012	Makin et al.
2009/0171252 A1	7/2009	Bockenstedt et al.	2012/0197121 A1	8/2012	Slayton et al.
2009/0177122 A1	7/2009	Peterson	2012/0209150 A1	8/2012	Zeng et al.
2009/0177123 A1	7/2009	Peterson	2012/0215105 A1	8/2012	Slayton et al.
2009/0182231 A1	7/2009	Barthe et al.	2012/0271202 A1	10/2012	Wisdom
2009/0198157 A1	8/2009	Babaev et al.	2012/0271294 A1	10/2012	Barthe et al.
2009/0216159 A1	8/2009	Slayton et al.	2012/0296240 A1	11/2012	Azhari et al.
2009/0226424 A1	9/2009	Hsu	2012/0302883 A1	11/2012	Kong et al.
2009/0227910 A1	9/2009	Pedersen et al.	2012/0316426 A1	12/2012	Foley et al.
2009/0230823 A1	9/2009	Kushculey et al.	2012/0330197 A1	12/2012	Makin et al.
2009/0253988 A1	10/2009	Slayton et al.	2012/0330222 A1	12/2012	Makin et al.
2009/0281463 A1	11/2009	Chapelon et al.	2012/0330223 A1	12/2012	Makin et al.
2009/0312693 A1	12/2009	Thapliyal et al.	2012/0330283 A1	12/2012	Hyde et al.
2009/0318909 A1	12/2009	Debenedictis et al.	2012/0330284 A1	12/2012	Hyde et al.
2009/0326420 A1	12/2009	Mooney et al.	2013/0012755 A1	1/2013	Slayton
2010/0011236 A1	1/2010	Barthe et al.	2013/0012816 A1	1/2013	Slayton et al.
2010/0022919 A1	1/2010	Peterson	2013/0012838 A1	1/2013	Jaeger et al.
2010/0022921 A1	1/2010	Seip et al.	2013/0012842 A1	1/2013	Barthe
2010/0022922 A1	1/2010	Barthe et al.	2013/0018285 A1	1/2013	Park et al.
2010/0030076 A1	2/2010	Vortman et al.	2013/0018286 A1	1/2013	Slayton et al.
2010/0042020 A1	2/2010	Ben-Ezra	2013/0046209 A1	2/2013	Slayton et al.
2010/0049178 A1	2/2010	Deem et al.	2013/0051178 A1	2/2013	Rybyanets
2010/0056925 A1	3/2010	Zhang et al.	2013/0060170 A1	3/2013	Lee et al.
2010/0100014 A1	4/2010	Eshel et al.	2013/0066208 A1	3/2013	Barthe et al.
2010/0113983 A1	5/2010	Heckerman et al.	2013/0066237 A1	3/2013	Smotrich et al.
2010/0130891 A1	5/2010	Taggart et al.	2013/0072826 A1	3/2013	Slayton et al.
2010/0160782 A1	6/2010	Slayton et al.	2013/0096471 A1	4/2013	Slayton et al.
2010/0160837 A1	6/2010	Hunziker et al.	2013/0190659 A1	7/2013	Slayton et al.
2010/0168576 A1	7/2010	Poland et al.	2013/0211293 A1	8/2013	Auboiroux et al.
2010/0191120 A1	7/2010	Kraus et al.	2013/0225994 A1	8/2013	Hsu et al.
2010/0241035 A1	9/2010	Barthe et al.	2013/0268032 A1	10/2013	Neev
2010/0249602 A1	9/2010	Buckley et al.	2013/0274603 A1	10/2013	Barthe et al.
2010/0249669 A1	9/2010	Ulric et al.	2013/0281853 A1	10/2013	Slayton et al.
2010/0256489 A1	10/2010	Pedersen et al.	2013/0281891 A1	10/2013	Slayton et al.
2010/0274161 A1	10/2010	Azhari et al.	2013/0296697 A1	11/2013	Slayton et al.
2010/0280420 A1	11/2010	Barthe et al.	2013/0296700 A1	11/2013	Slayton et al.
2010/0286518 A1	11/2010	Lee et al.	2013/0296743 A1	11/2013	Lee et al.
2010/0312150 A1	12/2010	Douglas et al.	2013/0303904 A1	11/2013	Barthe et al.
2011/0040171 A1	2/2011	Foley et al.	2013/0303905 A1	11/2013	Barthe et al.
2011/0040190 A1	2/2011	Jahnke et al.	2013/0310714 A1	11/2013	Eshel et al.
2011/0040213 A1	2/2011	Dietz et al.	2013/0310863 A1	11/2013	Makin et al.
2011/0040214 A1	2/2011	Foley et al.	2013/0345562 A1	12/2013	Barthe et al.
2011/0066084 A1	3/2011	Desilets et al.	2014/0024974 A1	1/2014	Slayton et al.
2011/0087099 A1	4/2011	Eshel et al.	2014/0050054 A1	2/2014	Toda et al.
2011/0087255 A1	4/2011	McCormack et al.	2014/0081300 A1	3/2014	Melodelima et al.
2011/0112405 A1	5/2011	Barthe et al.	2014/0082907 A1	3/2014	Barthe et al.
2011/0144490 A1	6/2011	Davis et al.	2014/0117814 A1	5/2014	Toda et al.
2011/0178444 A1	7/2011	Slayton et al.	2014/0142430 A1	5/2014	Slayton et al.
2011/0178541 A1	7/2011	Azhari	2014/0148834 A1	5/2014	Barthe et al.
			2014/0180174 A1	6/2014	Slayton et al.
			2014/0187944 A1	7/2014	Slayton et al.
			2014/0188015 A1	7/2014	Slayton et al.
			2014/0188145 A1	7/2014	Slayton et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0194723 A1 7/2014 Herzog et al.
 2014/0208856 A1 7/2014 Schmid
 2014/0221823 A1 8/2014 Keogh et al.
 2014/0236049 A1 8/2014 Barthe et al.
 2014/0236061 A1 8/2014 Lee et al.
 2014/0243713 A1 8/2014 Slayton et al.
 2014/0257145 A1 9/2014 Emery
 2014/0276055 A1 9/2014 Barthe et al.
 2015/0000674 A1 1/2015 Barthe et al.
 2015/0080723 A1 3/2015 Barthe et al.
 2015/0080771 A1 3/2015 Barthe et al.
 2015/0080874 A1 3/2015 Slayton et al.
 2015/0088182 A1 3/2015 Slayton et al.
 2015/0164734 A1 6/2015 Slayton et al.
 2015/0165238 A1 6/2015 Slayton et al.
 2015/0165243 A1 6/2015 Slayton et al.
 2015/0174388 A1 6/2015 Slayton
 2015/0202468 A1 7/2015 Slayton et al.
 2015/0217141 A1 8/2015 Barthe et al.
 2015/0360058 A1 12/2015 Barthe et al.
 2015/0374333 A1 12/2015 Barthe et al.
 2015/0375014 A1 12/2015 Slayton et al.
 2016/0027994 A1 1/2016 Toda et al.
 2016/0151618 A1 6/2016 Powers et al.
 2016/0175619 A1 6/2016 Lee et al.
 2016/0206335 A1 7/2016 Slayton
 2016/0206341 A1 7/2016 Slayton
 2016/0256675 A1 9/2016 Slayton
 2016/0296769 A1 10/2016 Barthe et al.
 2016/0361572 A1 12/2016 Slayton
 2017/0028227 A1 2/2017 Emery et al.

FOREIGN PATENT DOCUMENTS

DE 10140064 3/2003
 DE 10219297 11/2003
 DE 10219217 12/2004
 DE 20314479 12/2004
 EP 0142215 5/1984
 EP 0344773 12/1989
 EP 1479412 11/1991
 EP 0473553 4/1992
 EP 670147 2/1995
 EP 0661029 7/1995
 EP 724894 2/1996
 EP 763371 11/1996
 EP 1044038 10/2000
 EP 1050322 11/2000
 EP 1234566 8/2002
 EP 1262160 12/2002
 EP 0659387 4/2003
 EP 1374944 1/2004
 EP 1028660 1/2008
 EP 1874241 1/2008
 EP 1362223 5/2008
 EP 1750804 7/2008
 EP 1283690 11/2008
 EP 1811901 4/2009
 EP 1785164 8/2009
 EP 2230904 9/2010
 EP 1501331 6/2011
 EP 2066405 11/2011
 EP 2474050 7/2012
 FR 2532851 9/1983
 FR 2685872 1/1992
 FR 2672486 8/1992
 FR 2703254 3/1994
 GB 2113099 8/1983
 IL 102516 1/1996
 IL 112369 8/1999
 IL 120079 3/2001
 JP 63036171 2/1988
 JP 03048299 3/1991
 JP 3123559 5/1991
 JP 03136642 6/1991

JP 4089058 3/1992
 JP 04150847 5/1992
 JP 7080087 3/1995
 JP 07505793 6/1995
 JP 7184907 7/1995
 JP 7222782 8/1995
 JP 09047458 2/1997
 JP 9108288 4/1997
 JP 9503926 4/1997
 JP 11123226 5/1999
 JP 11505440 5/1999
 JP 11506636 6/1999
 JP 10248850 9/1999
 JP 2000126310 5/2000
 JP 2000166940 6/2000
 JP 2000233009 8/2000
 JP 2001170068 6/2001
 JP 2002505596 2/2002
 JP 2002078764 3/2002
 JP 2002515786 5/2002
 JP 2002521118 7/2002
 JP 2002537939 11/2002
 JP 2003050298 7/2003
 JP 2003204982 7/2003
 JP 2004-504898 2/2004
 JP 2004-507280 3/2004
 JP 2004-509671 4/2004
 JP 2004-512856 4/2004
 JP 2004147719 5/2004
 JP 2005503388 2/2005
 JP 2005527336 9/2005
 JP 2005323213 11/2005
 JP 2006520247 9/2006
 JP 2008515559 5/2008
 JP 2009518126 5/2009
 JP 2010517695 5/2010
 KR 1020010024871 3/2001
 KR 100400870 10/2003
 KR 20060121267 11/2006
 KR 1020060113930 11/2006
 KR 1020070065332 6/2007
 KR 1020070070161 7/2007
 KR 1020070098856 10/2007
 KR 1020070104878 10/2007
 KR 1020070114105 11/2007
 KR 1020000059516 4/2012
 KR 10-2013-0124598 11/2013
 KR 10-1365946 2/2014
 TW 386883 9/2000
 TW 201208734 A 3/2012
 WO WO9312742 7/1993
 WO WO9524159 9/1995
 WO WO9625888 8/1996
 WO WO9634568 11/1996
 WO WO9639079 12/1996
 WO WO9735518 10/1997
 WO WO9832379 7/1998
 WO WO9852465 11/1998
 WO WO9933520 7/1999
 WO WO9949788 10/1999
 WO WO200006032 2/2000
 WO WO0015300 3/2000
 WO WO0021612 4/2000
 WO WO0053113 9/2000
 WO WO0128623 4/2001
 WO WO01045550 6/2001
 WO WO0182777 11/2001
 WO WO0182778 11/2001
 WO WO0187161 11/2001
 WO WO01080709 11/2001
 WO WO2001087161 11/2001
 WO WO 02/09812 2/2002
 WO WO0209813 2/2002
 WO WO02015768 2/2002
 WO WO0224050 3/2002
 WO WO2002054018 7/2002
 WO WO02092168 11/2002
 WO WO03053266 7/2003
 WO WO03065347 8/2003

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO03070105	8/2003
WO	WO03077833	9/2003
WO	WO03086215	10/2003
WO	WO03096883	11/2003
WO	WO03099177	12/2003
WO	WO03099382	12/2003
WO	WO03101530	12/2003
WO	WO2004000116	12/2003
WO	WO2004080147	9/2004
WO	WO2004110558	12/2004
WO	WO2005/011804	2/2005
WO	WO2005065408	7/2005
WO	WO2005065409	7/2005
WO	WO2005090978	9/2005
WO	WO2005113068	12/2005
WO	WO2006/042163	4/2006
WO	WO2006036870	4/2006
WO	WO2006042168	4/2006
WO	WO2006042201	4/2006
WO	WO2006065671	6/2006
WO	WO2006082573	8/2006
WO	WO2006104568	10/2006
WO	WO2007067563	6/2007
WO	WO2008036479	3/2008
WO	WO2008036622	3/2008
WO	WO2008144274	11/2008
WO	WO2009013729	1/2009
WO	WO2009149390	10/2009
WO	WO2012134645	10/2012
WO	WO2013048912	4/2013
WO	WO2014045216	3/2014
WO	WO2014055708	4/2014
WO	WO2014057388	4/2014
WO	WO2014127091	8/2014
WO	WO2015160708	10/2015
WO	WO2018035012	2/2018

OTHER PUBLICATIONS

DermaFocus Exhibit 2027, DermaFocus Oral Proceeding Demonstrative Slides (filed Oct. 2, 2017 in re IPR2016-01459).

PTAB Record of Oral Hearing held Oct. 4, 2017 in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 67 pages. (PTAB Document sent to Ulthera on Nov. 1, 2017).

A Validated Photonumeric Cellulite Severity Scale; Hessel et al; J Eur Acad Dermatol Venereol. May 2009;23(5):523-8, 6 pages.

Agren, Magnus S. et al., Collagenase in Wound Healing: Effect of Wound Age and Type. The Journal of Investigative Dermatology, vol. 99/No. 6, (Dec. 1992).

Alam, M., "The future of noninvasive procedural dermatology". Semin Cutan Med Surg. Mar. 2013; 32(1):59-61.

Alam, M., et al., "Ultrasound tightening of facial and neck skin: a rater-blinded prospective cohort study". J Am Acad Dermatol, 2010. 62(2): p. 262-269.

Alexiades-Armenakas, M., "Ultrasound Technologies for Dermatologic Techniques". J Drugs Derm. 2014. 12 (11): p. 1305.

Alster, T.S., et al., "Noninvasive lifting of arm, thigh, and knee skin with transcutaneous intense focused ultrasound". Dermatol Surg, 2012. 38(5): p. 754-9.

Alster, Tinas S., Tanzi, Elizabeth L., "Cellulite Treatment using a Novel Combination Radiofrequency, Infrared Light, and Mechanical Tissue Manipulation Device," Journal of Cosmetic & Laser Therapy, Jun. 2005, vol. 7, Issue 2, pp. 81-85.

Arosarena, O., "Options and Challenges for Facial Rejuvenation in Patients With Higher Fitzpatrick Skin Phototypes". JAMA Facial Plastic Surgery, 2015.

Arthur et al., "Non-invasive estimation of hyperthermia temperatures with ultrasound," Int. J. Hyperthermia, Sep. 2005, 21(6), pp. 589-600.

Barthe et al., "Ultrasound therapy system and ablation results utilizing miniature imaging/therapy arrays," Ultrasonics Symposium, 2004 IEEE, Aug. 23, 2004, pp. 1792-1795, vol. 3.

Bozec, Laurent et al., Thermal Denaturation Studies of Collagen by Microthermal Analysis and Atomic Force Microscopy, Biophysical Journal, vol. 101, pp. 228-236. (Jul. 2001).

Brobst, R.W., et al., "Noninvasive Treatment of the Neck". Facial Plast Surg Clin North Am, 2014. 22(2): p. 191-202.

Brobst, R.W., et al., "Ulthera: initial and six month results". Facial Plast Surg Clin North Am, 2012. 20(2): p. 163-76.

Calderhead et al., "One Mechanism Behind LED Photo-Therapy for Wound Healing and Skin Rejuvenation: Key Role of the Mast Cell" Laser Therapy 17.3: 141-148 (2008).

Casabona, G., et al., "Microfocused Ultrasound With Visualization and Fillers for Increased Neocollagenesis: Clinical and Histological Evaluation". Dermatol Surg 2014;40:S194-S198.

Chan, N.P., et al "Safety study of transcutaneous focused ultrasound for non-invasive skin tightening in Asians". Lasers Surg Med, 2011. 43(5): p. 366-75.

Chapelon et al., "Effects of Cavitation in the High Intensity Therapeutic Ultrasound", Ultrasonics Symposium—1357 (1991).

Chapelon, et al., "Thresholds for Tissue Ablation by Focused Ultrasound" (1990).

Chen, L. et al., "Effect of Blood Perfusion on the ablation of liver parenchyma with high intensity focused ultrasound," Phys. Med. Biol; 38:1661-1673; 1993b.

Coon, Joshua et al., "Protein identification using sequential ion/ion reactions and tandem mass spectrometry" Proceedings of the National Academy of Sciences of the USA, vol. 102, No. 27, Jul. 27, 2005, pp. 9463-9468.

Corry, Peter M., et al., "Human Cancer Treatment with Ultrasound", IEEE Transactions on Sonics and Ultrasonics, vol. SU-31, No. 5, Sep. 1984, pp. 444, 456.

Damianou et al., "Application of the Thermal Dose Concept for Predicting the Necrosed Tissue Volume During Ultrasound Surgery," 1993 IEEE Ultrasound Symposium, pp. 1199-1202.

Daum et al., Design and Evaluation of a Feedback Based Phased Array System for Ultrasound Surgery, IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control, vol. 45, No. 2, Mar. 1998, pp. 431-438.

Davis, Brian J., et al., "An Acoustic Phase Shift Technique for the Non-Invasive Measurement of Temperature Changes in Tissues", 1985 Ultrasonics Symposium, pp. 921-924.

Dayan, S.H., et al., "Prospective, Multi-Center, Pivotal Trial Evaluating the Safety and Effectiveness of Micro-Focused Ultrasound with Visualization (MFU-V) for Improvement in Lines and Wrinkles of the Decolletage". Plast Reconstr Surg. Oct. 2014; 134(4 Suppl 1):123-4.

Decision of the Korean Intellectual Property Tribunal dated Jun. 28, 2013 regarding Korean Patent No. 10-1142108, which is related to the pending application and/or an application identified in the Table on pp. 1-4 of the Information Disclosure Statement herein (English translation, English translation certification, and Korean decision included).

Delon Martin, C., et al, "Venous Thrombosis Generation by Means of High-Intensity Focused Ultrasound" Ultrasound in Med. & Biol., vol. 21, No. 1, pp. 113-119 (1995).

Dierickx, Christine C., "The Role of Deep Heating for Noninvasive Skin Rejuvenation" Lasers in Surgery and Medicine 38:799-807 (2006).

Dobke, M.K., et al., "Tissue restructuring by energy-based surgical tools". Clin Plast Surg, 2012. 39(4): p. 399-408.

Dong, Yuan-Lin et al., "Effect of Ibuprofen on the Inflammatory Response to Surgical Wounds" The Journal of Trauma, vol. 35, No. 3. (1993).

Dvivedi, Sanjay, et al. "Effect of Ibuprofen and diclofenac sodium on experimental wound healing" Indian Journal of Experimental Biology, vol. 35, pp. 1243-1245. (Nov. 1997).

Fabi, S.G., "Microfocused Ultrasound With Visualization for Skin Tightening and Lifting: My Experience and a Review of the Literature". Dermatol Surg. Dec. 2014; 40 Suppl 12:S164-7.

Fabi, S.G., "Noninvasive skin tightening: focus on new ultrasound techniques". Clin Cosmet Investig Dermatol. Feb. 5, 2015; 8:47-52.

(56)

References Cited

OTHER PUBLICATIONS

- Fabi, S.G., et. al., "A prospective multicenter pilot study of the safety and efficacy of microfocused ultrasound with visualization for improving lines and wrinkles of the décolleté". *Dermatol Surg.* Mar. 2015; 41(3):327-35.
- Fabi, S.G., et. al., "Evaluation of microfocused ultrasound with visualization for lifting, tightening, and wrinkle reduction of the décolletage". *J Am Acad Dermatol.* 2013. 69(6): p. 965-71.
- Fabi, S.G., et. al., "Future directions in cutaneous laser surgery". *Dermatol Clin.* 2014. 32(1): p. 61-9.
- Fabi, S.G., et al., "Retrospective Evaluation of Micro-focused Ultrasound for Lifting and Tightening the Face and Neck". *Dermatol Surg.* 2014.
- Friedmann D.P., "Comments on evaluation of microfocused ultrasound system for improving skin laxity and tightening in the lower face". *Aesthet Surg J.* Mar. 2015;35(3):NP81-2.
- Friedmann, D.P., et. al., "Combination of intense pulsed light, Sculptra, and Ultherapy for treatment of the aging face". *J Cosmet Dermatol.* 2014. 13(2): p. 109-18.
- Fry, W. J. et al., "Production of Focal Destructive Lesions in the Central Nervous System with Ultrasound," *J. Neurosurg.*, 11:471-478; 1954.
- Fujimoto, et al., "A New Cavitation Suppression Technique for Local Ablation Using High-Intensity Focused Ultrasound" *Ultrasonics Symposium—1629* (1995).
- Gliklich et al., Clinical Pilot Study of Intense Ultrasound therapy to Deep Dermal Facial Skin and Subcutaneous Tissues, *Arch Facial Plastic Surgery*, Mar. 1, 2007, vol. 9, No. 1.
- Gold, M.H., et. al., "Use of Micro-Focused Ultrasound with Visualization to Lift and Tighten Lax Knee Skin". *J Cosmet Laser Ther.* 2014: p. 1-15.
- Goldberg, D.J., et. al., "Safety and Efficacy of Microfocused Ultrasound to Lift, Tighten, and Smooth the Buttocks". *Dermatol Surg* 2014; 40:1113-1117.
- Greene, R.M., et al., "Skin tightening technologies". *Facial Plast Surg.* Feb. 2014; 30(1):62-7.
- Greenhalgh, David G., "Wound healing and diabetes mellitus" *Clinics in Plastic Surgery* 30; 37-45. (2003).
- Guo, S. S et al., "Factors Affecting Wound Healing" *Critical Reviews in Oral Biology & Medicine, J Dent Res* 89(3), pp. 219-229. (2010).
- Haar, G.R. et al., "Tissue Destruction with Focused Ultrasound in Vivo," *Eur. Urol.* 23 (suppl. 1):8-11; 1993.
- Hantash, Basil M. et al., "Bipolar Fractional Radiofrequency Treatment Induces Neocollagenesis and Neocollagenesis" *Lasers in Surgery and Medicine* 41:1-9 (2009).
- Hantash, Basil M. et al., "In Vivo Histological Evaluation of a Novel Ablative Fractional Resurfacing Device" *Lasers in Surgery and Medicine* 39:96-107 (2007).
- Harris, M.O., "Safety of Microfocused Ultrasound With Visualization in Patients With Fitzpatrick Skin Phototypes III to VI". *JAMA Facial Plast. Surg.* 2015.
- Hart, et. al., "Current Concepts in the Use of PLLA:Clinical Synergy Noted with Combined Use of Microfocused Ultrasound and Poly-L-Lactic Acid on the Face, Neck, and Décolletage". *Amer. Soc. Plast. Surg.* 2015. 136; 180-187S.
- Hassan et al., "Structure and Applications of Poly(vinyl alcohol) Hydrogels Produced by Conventional Crosslinking or by Freezing/Thawing Methods," *advanced in Polymer Science*, 2000, pp. 37-65, vol. 153.
- Hassan et al., "Structure and Morphology of Freeze/Thawed PVA Hydrogels," *Macromolecules*, Mar. 11, 2000, pp. 2472-2479, vol. 33, No. 7.
- Hitchcock, T. M. et al., "Review of the safety profile for microfocused ultrasound with Visualization". *Journal of Cosmetic Dermatology*, 13, 329-335. (2014).
- Husseini et al., "The Role of Cavitation in Acoustically Activated Drug Delivery," *J. Control Release*, Oct. 3, 2005, pp. 253-261, vol. 107(2).
- Husseini et al. "Investigating the mechanism of acoustically activated uptake of drugs from Pluronic micelles," *BMD Cancer* 2002, 2:20k, Aug. 30, 2002, pp. 1-6.
- Hynynen et al., *Temperature Distributions During Local Ultrasound Induced Hyperthermia in Vivo*, *Ultrasonics Symposium—745* (1982).
- Jeffers et al., "Evaluation of the Effect of Cavitation Activity on Drug-Ultrasound Synergisms," 1993 *IEEE Ultrasonics Symposium*, pp. 925-928.
- Jenne, J., et al., "Temperature Mapping for High Energy US-Therapy", 1994 *Ultrasonics Symposium*, pp. 1879-1882.
- Jeong, K.H., et al., "Neurologic complication associated with intense focused ultrasound". *J Cosmet Laser Ther.* 2013.
- Johnson, S.A., et al., "Non-Intrusive Measurement of Microwave and Ultrasound-Induced Hyperthermia by Acoustic Temperature Tomography", *Ultrasonics Symposium Proceedings*, pp. 977-982. (1977).
- Kim, H. J., et al., "Coagulation and ablation patterns of high-intensity focused ultrasound on a tissue mimicking phantom and cadaveric skin". *Laser Med Sci.* Sep. 4, 2015.
- Kornstein, A.N., "Ulthera for silicone lip correction". *Plast Reconstr Surg.* 2012. 129(6): p. 1014e-1015e.
- Kornstein, A.N., "Ultherapy shrinks nasal skin after rhinoplasty following failure of conservative measures". *Plast Reconstr Surg.* 2013. 131(4): p. 664e-6e.
- Krischak, G.D., et al., "The effects of non-steroidal anti-inflammatory drug application on incisional wound healing in rats" *Journal of Wound Care*, vol. 6, No. 2, (Feb. 2007).
- Laubach, H.J., et. al., "Confined Thermal Damage with Intense Ultrasound (IUS)" [abstr.] *American Society for Laser Medicine and Surgery Abstracts*, p. 15 #43 (Apr. 2006).
- Laubach, H.J., et. al., "Intense focused ultrasound: evaluation of a new treatment modality for precise microcoagulation within the skin". *Dermatol Surg.* 2008. 34(5): p. 727-734.
- Lee, H. J., et al., "The efficacy and safety of intense focused ultrasound in the treatment of enlarged facial pores in Asian skin". *J Dermatolog Treat.* 2014.
- Lee, H.S., et. al., "Multiple Pass Ultrasound Tightening of Skin Laxity of the Lower Face and Neck". *Dermatol Surg.* 2011.
- Lin, Sung-Jan, et al., "Monitoring the thermally induced structural transitions of collagen by use of second-harmonic generation microscopy" *Optics Letters*, vol. 30, No. 6, (Mar. 15, 2005).
- MacGregor J.L., et. al., "Microfocused Ultrasound for Skin Tightening". *Semin Cutan Med Surg* 32:18-25. (2013).
- Madersbacher, S. et al., "Tissue Ablation in Benign Prostatic Hyperplasia with High Intensity Focused Ultrasound," *Dur. Urol.*, 23 (suppl. 1):39-43; 1993.
- Makin et al, "B-Scan Imaging and Thermal Lesion Monitoring Using Miniaturized Dual-Functionality Ultrasound Arrays," *Ultrasonics Symposium*, 2004 *IEEE*, Aug. 23, 2004, pp. 1788-1791, vol. 3.
- Makin et al, "Confirmed Bulk Ablation and Therapy Monitoring Using Intracorporeal Image-Treat Ultrasound Arrays," 4th International Symposium on Therapeutic Ultrasound, Sep. 19, 2004.
- Makin et al., "Miniaturized Ultrasound Arrays for Interstitial Ablation and Imaging," *UltraSound Med. Biol.* 2005, Nov. 1, 2005, pp. 1539-1550, vol. 31(11).
- Manohar et al, "Photoacoustic mammography laboratory prototype: imaging of breast tissue phantoms." *Journal of Biomedical Optics*, Nov./Dec. 2004, pp. 1172-1181, vol. 9, No. 6.
- Mast et al, "Bulk Ablation of Soft Tissue with Intense Ultrasound; Modeling and Experiments," *J. Acoust. Soc. Am.*, Oct. 1, 2005, pp. 2715-2724, vol. 118(4).
- Meshkinpour, Azin, et al., "Treatment of Hypertrophic Scars and Keloids With a Radiofrequency Device: A Study of Collagen Effects" *Lasers in Surgery and Medicine* 37:343-349 (2005).
- Microfocused Ultrasound with Visualization and Calcium Hydroxylapatite for Improving Skin Laxity and Cellulite Appearance; Casabona et al.; *Plast Reconstr Surg Glob Open.* Jul. 25, 2017;5(7):e1388, 8 pages.

(56)

References Cited

OTHER PUBLICATIONS

Microfocused Ultrasound With Visualization and Fillers for Increased Neocollagenesis: Clinical and Histological Evaluation; Casabona et al.; *Dermatol Surg.* Dec. 2014; 40 Suppl 12:S194-8, 5 pages.

Minkis, K., et. al., "Ultrasound skin tightening". *Dermatol Clin*, 2014. 32(1): p. 71-7.

Mitragotri, S., "Healing sound: the use of ultrasound in drug delivery and other therapeutic applications," *Nature Reviews; Drug Delivery*, pp. 255-260, vol. 4 (Mar. 2005).

Mosser, David M. et al., "Exploring the full spectrum of macrophage activation" *Nat Rev Immunol*; 8(12): 958-969. (Dec. 2008).

Murota, Sei-Itsu, et al., "Stimulatory Effect of Prostaglandins on the Production of Hexosamine-Containing Substances by Cultured Fibroblasts (3) Induction of Hyaluronic Acid Synthetase by Prostaglandin" Department of Pharmacology, Tokyo Metropolitan Institute of Gerontology, Itabashiku, Tokyo-173, Japan. (Nov. 1977, vol. 14, No. 5).

Murota, Sei-Itsu, et al., "The Stimulatory Effect of Prostaglandins on Production of Hexosamine-Containing Substances by Cultured Fibroblasts" Department of Pharmacology, Tokyo Metropolitan Institute of Gerontology, Itabashiku, Tokyo-173, Japan. (Aug. 1976, vol. 12, No. 2).

Nestor, M.S. et. al., "Safety and Efficacy of Micro-focused Ultrasound Plus Visualization for the Treatment of Axillary Hyperhidrosis". *J Clin Aesthet Dermatol*, 2014. 7(4): p. 14-21.

Oni, G., et. al. "Response to 'comments on evaluation of microfocused ultrasound system for improving skin laxity and tightening in the lower face'". *Aesthet Surg J.* Mar. 2015;35(3):NP83-4.

Oni, G., et. al., "Evaluation of a Microfocused Ultrasound System for Improving Skin Laxity and Tightening in the Lower Face". *Aesthet Surg J*, 2014. 38:861-868.

Pak, C.S., et al., "Safety and Efficacy of Ulthera in the Rejuvenation of Aging Lower Eyelids: A Pivotal Clinical Trial". *Aesthetic Plast Surg*, 2014.

Paradossi et al., "Poly(vinyl alcohol) as versatile biomaterial for potential biomedical applications," *Journal of Materials Science: Materials in Medicine*, 2003, pp. 687-691, vol. 14.

Pritzker, R.N., et. al., "Updates in noninvasive and minimally invasive skin tightening". *Semin Cutan Med Surg.* Dec. 2014;33(4):182-7.

Pritzker, R.N., et. al., "Comparison of different technologies for noninvasive skin tightening". *Journal of Cosmetic Dermatology*, 13, 315-323. (2014).

Rappolee, Daniel A., et al., "Wound Macrophages Express TGF and Other Growth Factors in Vivo: Analysis by mRNA Phenotyping" *Science*, vol. 241, No. 4866 (Aug. 1988).

Reid, Gavin, et al., "Tandem Mass spectrometry of ribonuclease A and B: N-linked glycosylation site analysis of whole protein ions," *Analytical Chemistry*, Feb. 1, 2002, vol. 74, No. 3, pp. 577-583.

Righetti et al., "Elastographic Characterization of HIFU-Induced Lesions in Canine Livers," 1999, *Ultrasound in Med & Bio*, vol. 25, No. 7, pp. 1099-1113.

Rokhsar, C., et. al., "Safety and efficacy of microfocused ultrasound in tightening of lax elbow skin". *Dermatol Surg*, 2015; 41(7):821-6.

Rosenberg, Carol S. "Wound Healing in the Patient with Diabetes Mellitus" *Nursing Clinics of North America*, vol. 25, No. 1, (Mar. 1990).

Saad et al., "Ultrasound-Enhanced Effects of Adriamycin Against Murine Tumors," *Ultrasound in Med. & Biol.* vol. 18, No. 8, pp. 715-723 (1992).

Sabet-Peyman, E.J. et. al., "Complications Using Intense Ultrasound Therapy to Treat Deep Dermal Facial Skin and Subcutaneous Tissues". *Dermatol Surg* 2014; 40:1108-1112.

Sandulache, Vlad C. et al., "Prostaglandin E2 inhibition of keloid fibroblast migration, contraction, and transforming growth factor (TGF)-B1-induced collagen synthesis" *Wound Rep Reg* 15 122-133, 2007. (2007).

Sanghvi, N.T., et al., "Transrectal Ablation of Prostate Tissue Using Focused Ultrasound," 1993 *Ultrasonics Symposium*, IEEE, pp. 1207-1210.

Sasaki, G.H. et. al., "Clinical Efficacy and Safety of Focused-Image Ultrasonography: A 2-Year Experience". *Aesthet Surg J*, 2012.

Sasaki, G.H. et. al., "Microfocused Ultrasound for Nonablative Skin and Subdermal Tightening to the Periorbitum and Body Sites: Preliminary Report on Eighty-Two Patients". *Journal of Cosmetics, Dermatological Sciences and Applications*, 2012, 2, 108-116.

Sassen, Sander, "ATI's R520 architecture, the new king of the hill?" <http://www.hardwareanalysis.com/content/article/1813>, Sep. 16, 2005, 2 pages.

Seip, Ralf, et al., "Noninvasive Detection of Thermal Effects Due to Highly Focused Ultrasonic Fields," *IEEE Symposium*, pp. 1229-1232, vol. 2, Oct. 3-Nov. 1993.

Seip, Ralf, et al., "Noninvasive Estimation of Tissue Temperature Response to Heating Fields Using Diagnostic Ultrasound," *IEEE Transactions on Biomedical Engineering*, vol. 42, No. 8, Aug. 1995, pp. 828-839.

Simon et al., "Applications of Lipid-Coated Microbubble Ultrasonic Contrast to Tumor Therapy," *Ultrasound in Med. & Biol.* vol. 19, No. 2, pp. 123-125 (1993).

Sklar, L. R., et al., "Use of transcutaneous ultrasound for lipolysis and skin tightening: a review". *Aesthetic Plast Surg*, 2014. 38(2): p. 429-41.

Smith, Nadine Barrie, et al., "Non-invasive in Vivo Temperature Mapping of Ultrasound Heating Using Magnetic Resonance Techniques", 1994 *Ultrasonics Symposium*, pp. 1829-1832, vol. 3.

Suh, D.H., et. al., "A intense-focused ultrasound tightening for the treatment of infraorbital laxity". *J Cosmet Laser Ther*, 2012. 14(6): p. 290-5.

Suh, D.H., et. al., "Comparative histometric analysis of the effects of high-intensity focused ultrasound and radiofrequency on skin". *J Cosmet Laser Ther* Mar. 24, 2015:1-7.

Suh, D.H., et. al., "Intense Focused Ultrasound Tightening in Asian Skin: Clinical and Pathologic Results" *American Society for Dermatologic Surgery, Inc.*; 37:1595-1602. (2011).

Suh, D.H., et. al., "Intense focused ultrasound tightening in asian skin: clinical and pathologic results". *Dermatol Surg*, 2011. 37(11): p. 1595-602.

Surry et al., "Poly(vinyl alcohol) cryogel phantoms for use in ultrasound and MR imaging," *Phys. Med. Biol.*, Dec. 6, 2004, pp. 5529-5546, vol. 49.

Syka J. E. P. et al., "Peptide and Protein Sequence Analysis by Electron Transfer Dissociation Mass Spectrometry," *Proceedings of the National Academy of Sciences of USA*, National Academy of Science, Washington, DC, vol. 101, No. 26, Jun. 29, 2004, pp. 9528-9533.

Talbert, D. G., "An Add-On Modification for Linear Array Real-Time Ultrasound Scanners to Produce 3D Displays," *UTS Int'l 1977 Brighton, England* (Jun. 28-30, 1977) pp. 57-67.

Tata et al., "Interaction of Ultrasound and Model Membrane Systems: Analyses and Predictions," *American Chemical Society, Phys. Chem.* 1992, 96, pp. 3548-3555.

Ueno, S., et al., "Ultrasound Thermometry in Hyperthermia", 1990 *Ultrasonic Symposium*, pp. 1645-1652.

Verhofstad, Michiel H.J. et al., "Collagen Synthesis in rat skin and ileum fibroblasts is affected differently by diabetes-related factors" *Int. J. Exp. Path.* (1998), 79, 321-328.

Wang, H., et al., "Limits on Focused Ultrasound for Deep Hyperthermia", 1994 *Ultrasonic Symposium*, Nov. 1-4, 1994, pp. 1869-1872, vol. 3.

Wasson, Scott, "NVIDIA's GeForce 7800 GTX graphics processor Power MADD," <http://techreport.com/reviews/2005q2/geforce-7800gtx/index.x?pg=1>, Jun. 22, 2005, 4 pages.

Weiss, M., "Commentary: noninvasive skin tightening: ultrasound and other technologies: where are we in 2011?" *Dermatol Surg*, 2012. 38(1): p. 28-30.

White et al "Selective Creating of Thermal Injury Zones in the Superficial Musculoaponeurotic System Using Intense Ultrasound Therapy," *Arch Facial Plastic Surgery*, Jan./Feb. 2007, vol. 9, No. 1 (pp. 22-29).

(56)

References Cited

OTHER PUBLICATIONS

- White, W. M., et al., "Selective Transcutaneous Delivery of Energy to Facial Subdermal Tissues Using the Ultrasound Therapy System" [abstr]. American Society for Laser Medicine and Surgery Abstracts, p. 37 #113 (Apr. 2006).
- White, W. Matthew, et al., "Selective Transcutaneous Delivery of Energy to Porcine Soft Tissues Using Intense Ultrasound (IUS)" *Lasers in Surgery and Medicine* 40:67-75 (2008).
- Woodward, J.A., et al. "Safety and Efficacy of Combining Microfocused Ultrasound With Fractional CO₂ Laser Resurfacing for Lifting and Tightening the Face and Neck". *Dermatol Surg Dec. 2014* 40:S190-S193.
- Zelickson, Brian D. et al., "Histological and Ultrastructural Evaluation of the Effects of a Radiofrequency-Based Nonablative Dermal Remodeling Device, a Pilot Study" *Arch Dermatol*, vol. 140, (Feb. 2004).
- Ulthera, Inc., Petition for Inter Partes Review filed Jul. 19, 2016 in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 63 pages. (Filed Jul. 19, 2016).
- Ulthera Exhibit 1001, U.S. Pat. No. 6,113,559 to Klopotek, filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1002, Patent file history of U.S. Pat. No. 6,113,559 Klopotek filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1003, Declaration of Expert Witness Mark E. Schafer, Ph.D. filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1004, Curriculum Vitae of Mark E. Schafer, Ph.D. filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1005, International PCT Publication WO96/34568 Knowlton filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1006, French Patent No. 2,672,486, Technomed patent filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1007, English translation of French U.S. Pat. No. 2,672,486, Technomed filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1008, International PCT Publication WO93/12742, Technomed PCT filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1009, English translation of International PCT Publication WO93/12742, Technomed PCT filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1010, U.S. Pat. No. 5,601,526, which claims priority to Technomed PCT filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1011, Patent file history for European Patent Application No. 98964890.2, Klopotek filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1012, Translator Declaration filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1013, U.S. Pat. No. 5,230,334 to Klopotek filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1014, U.S. Pat. No. 5,755,753 to Knowlton filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1015, Excerpts from the American Medical Association Encyclopedia of Medicine (1989) filed Jul. 19, 2016 in re IPR2016-01459.
- Ulthera Exhibit 1016, the Simultaneous Study of Light Emissions and Shock Waves Produced by Cavitation Bubbles, G. Gimenez, J. Acoust. Soc. Am. 71(4), Apr. 1982, pp. 839-847 (filed Jul. 19, 2016 in re IPR2016-01459).
- Ulthera Exhibit 1017, Excerpts from Gray's Anatomy (1995) (filed Jul. 19, 2016 in re IPR2016-01459).
- Ulthera Exhibit 1018, Anatomy of the Superficial Venous System, Comjen G.M., *Dermatol. Surg.*, 1995; 21:35-45 (filed Jul. 19, 2016 in re IPR2016-01459).
- Ulthera Exhibit 1019, Section 2.6 from *Ultrasonics Theory and Application*, by G.L. Gooberman (Hart Publishing Co., 1969) (filed Jul. 19, 2016 in re IPR2016-01459).
- Ulthera Exhibit 1020, Deep Local Hyperthermia for Cancer Therapy: External Electromagnetic and Ultrasound Techniques, A.Y. Cheung and A. Neyzari, *Cancer Research (Suppl.)*, vol. 44, pp. 4736-4744 (1984) (filed Jul. 19, 2016 in re IPR2016-01459).
- Decision on Institution of Inter Partes Review in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 20 pages [011] (Dated Jan. 23, 2017).
- Dermafocus Response to Institution of Inter Partes Review in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 73 pages [018] (Dated Apr. 26, 2017).
- Dermafocus Exhibit List in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 5 pages [019] (Dated Apr. 26, 2017).
- Dermafocus Exhibit 2002, Declaration of Mark Palmeri, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 136 pages (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2003, Deposition of Dr. Mark Schafer, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 327 pages (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2004, Amendment No. 4 to Ulthera Form S-1, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 308 pages (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2005, Excerpt from Churchill Livingstone, Gray's Anatomy (38th ed. 1995), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 7 pages (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2006, Bo Eklof et al., "Revision of the CEAP Classification for Chronic Venous Disorders: Consensus Statement," ACTA FAC MED NAISS, vol. 25, No. 1 (2008), 3-10 in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 7 pages (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2007, WebMD, "Varicose Veins and Spider Veins" downloaded from <http://www.webmd.com/skin-problems-and-treatments/guide/varicose-spider-veins#1> in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 3 pages (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2008, John M. Porter et al., "Reporting Standards in Venous Disease: An Update," *Journal of Vascular Surgery*, vol. 21, No. 4 (1995), 635-645 in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 11 pages (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2009, Kullervo Hynynen, "Review of Ultrasound Therapy," 1997 Ultrasonics Symposium (1997), 1305-1313, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 9 pages (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2010, A.G. Visioli et al., "Preliminary Results of a Phase I Dose Escalation Clinical Trial Using Focused Ultrasound in the Treatment of Localised Tumours," *European Journal of Ultrasound*, vol. 9 (1999), 11-18, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 8 pages (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2011, U.S. Pat. No. 5,143,063, issued on Sep. 1, 1992, Fellner, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 6 pages (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2012, Hugh G. Beebe et al., "Consensus Statement: Classification and Grading of Chronic Venous Disease in the Lower Limbs," *European Journal of Vascular and Endovascular Surgery*, vol. 12 (1996), 487-492, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 6 pages (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2013, Excerpt from Mosby's Medical Dictionary (3rd ed. 1990), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 4 pages (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2014, Excerpt from Miller-Keane Encyclopedia & Dictionary of Medicine, Nursing, & Allied Health (5th ed. 1992), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 6 pages (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2015, David J. Tibbs et al, *Varicose Veins, Venous Disorders, and Lymphatic Problems in the Lower Limbs (1997)*, Chapter 4: Clinical Patterns of Venous Disorder I, 47-67, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 24 pages (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2016, Mitchel P. Goldman et al, *Varicose Veins and Telangiectasias (2nd ed. 1999)*, Chapter 22: Treatment of Leg Telangiectasias with Laser and High-Intensity Pulsed Light, 470-497, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 31 pages (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2017, Email from Anderson to Klopotek dated May 25, 2004, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 1 page (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2018, List of Klopotek Patents, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 411 pages (Filed Apr. 26, 2017).
- Dermafocus Exhibit 2019, Declaration of Peter Klopotek Civil Action 15-cv-654-SLR, dated Nov. 2, 2016, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 1 page (Filed Apr. 26, 2017).

(56) **References Cited**

OTHER PUBLICATIONS

Dermafocus Exhibit 2020, "Our Technology," downloaded from <http://jobs.ulthera.com/about> on Apr. 10, 2017, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 4 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2021, C. Damianou and K. Hynynen, "Focal Spacing and Near-Field Heating During Pulsed High Temperature Ultrasound Therapy," *Ultrasound in Medicine & Biology*, vol. 19, No. 9 (1993), 777-787, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 11 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2022, Excerpt from Mosby's Medical Dictionary (5th ed. 1997), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 5 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2023, Excerpt from Miller-Keane Encyclopedia & Dictionary of Medicine, Nursing, & Allied Health (6th ed. 1997), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 7 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2024, Excerpt from Stedman's Concise Medical Dictionary (3rd ed. 1997), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 4 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2025, Excerpt from Taber's Cyclopedic Medical Dictionary (18th ed. 1997), in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 9 pages (Filed Apr. 26, 2017).

Dermafocus Exhibit 2026, Bo Eklof et al., "Revision of the CEAP Classification for Chronic Venous Disorders: Consensus Statement," *Journal of Vascular Surgery*, vol. 40, No. 6 (2004), 1248-1252.e1, in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 6 pages (Filed Apr. 26, 2017).

Ulthera, Inc., Reply in Support of Petition for Inter Partes Review in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 33 pages (Filed Aug. 2, 2017).

Ulthera Exhibit 1022, Use of the Argon and Carbon Dioxide Lasers for Treatment of Superficial Venous Varicosities of the Lower Extremity, D. Apfelberg et al., *Lasers in Surgery and Medicine*, vol. 4.3, pp. 221-231 (1984) (filed Aug 2, 2017 in re IPR2016-01459).

Ulthera Exhibit 1023, 532-Nanometer Green Laser Beam Treatment of Superficial Varicosities of the Lower Extremities, T. Smith et al., *Lasers in Surgery and Medicine*, vol. 8.2, pp. 130-134 (1988) (filed Aug 2, 2017 in re IPR2016-01459).

Ulthera Exhibit 1024, Deposition Transcript of Dr. Mark Palmeri on Jul. 11, 2017 (filed Aug. 2, 2017 in re IPR2016-01459).

U.S. Appl. No. 12/996,616, filed Jan. 12, 2011, Hand Wand for Ultrasonic Cosmetic Treatment and Imaging.

U.S. Appl. No. 13/245,822, filed Sep. 26, 2011, System and Method for Cosmetic Treatment.

U.S. Appl. No. 13/245,852, filed Sep. 26, 2011, Systems for Cosmetic Treatment.

U.S. Appl. No. 13/245,864, filed Sep. 27, 2011, Methods for Non-Invasive Cosmetic Treatment of the Eye Region.

U.S. Appl. No. 13/246,117, filed Sep. 27, 2011, Methods for Non-Invasive Lifting and Tightening of the Lower Face and Neck.

U.S. Appl. No. 13/246,112, filed Sep. 27, 2011, Tissue Imaging and Treatment Method.

U.S. Appl. No. 14/193,234, filed Feb. 28, 2014, Devices and Methods for Multi-Focus Ultrasound Therapy.

U.S. Appl. No. 15/302,436, filed Oct. 6, 2016, Band Transducer Ultrasound Therapy.

U.S. Appl. No. 15/562,384, filed Oct. 27, 2017, Systems and Methods for Cosmetic Ultrasound Treatment of Skin.

U.S. Appl. No. 08/950,353, filed Oct. 14, 1997, Imaging, Therapy and Temperature Monitoring Ultrasonic System.

U.S. Appl. No. 09/502,174, filed Feb. 10, 2000, Imaging, Therapy and Temperature Monitoring Ultrasonic System.

U.S. Appl. No. 10/193,419, filed Jul. 10, 2002, Imaging, Therapy and Temperature Monitoring Ultrasonic System.

U.S. Appl. No. 10/944,499, filed Sep. 16, 2004, Method and System for Ultrasound Treatment With a Multi-Directional Transducer.

U.S. Appl. No. 11/163,177, filed Oct. 7, 2005, Method and System for Treating Acne and Sebaceous Glands.

U.S. Appl. No. 10/950,112, filed Sep. 24, 2004, Method and System for Combined Ultrasound Treatment.

U.S. Appl. No. 12/163,178, filed Oct. 7, 2005, Method and System for Treating Stretch Marks.

U.S. Appl. No. 11/245,999, filed Oct. 6, 2005, System and Method for Ultra-High Frequency Ultrasound Treatment.

U.S. Appl. No. 10/944,500, filed Sep. 16, 2004, System and Method for Variable Depth Ultrasound Treatment.

U.S. Appl. No. 11/744,655, filed May 4, 2007, Imaging, Therapy and Temperature Monitoring Ultrasonic System.

U.S. Appl. No. 13/937,190, filed Jul. 8, 2013, Imaging, Therapy and Temperature Monitoring Ultrasonic System.

U.S. Appl. No. 12/135,962, filed Jun. 9, 2008, Method and System for Ultrasound Treatment With a Multi-Directional Transducer.

U.S. Appl. No. 12/792,934, filed Jun. 3, 2010, System and Method for Ultra-High Frequency Ultrasound Treatment.

U.S. Appl. No. 13/914,945, filed Jun. 11, 2013, System and Method for Ultra-High Frequency Ultrasound Treatment.

U.S. Appl. No. 12/834,754, filed Jul. 12, 2010, System and Method for Variable Depth Ultrasound Treatment.

U.S. Appl. No. 14/264,732, filed Apr. 29, 2014, System and Method for Variable Depth Ultrasound Treatment.

U.S. Appl. No. 11/126,760, filed May 11, 2005, Method and System for Three-Dimensional Scanning and Imaging.

U.S. Appl. No. 13/564,552, filed Aug. 1, 2012, Method and System for Controlled Scanning, Imaging and/or Therapy.

U.S. Appl. No. 12/437,726, filed May 8, 2009, Method and System for Combined Ultrasound Treatment.

U.S. Appl. No. 11/163,148, filed Oct. 6, 2005, Method and System for Controlled Thermal Injury of Human Superficial Tissue.

U.S. Appl. No. 13/444,688, filed Apr. 11, 2012, Customized Cosmetic Treatment.

U.S. Appl. No. 11/163,152, filed Oct. 6, 2005, Method and System for Treatment of Sweat Glands.

U.S. Appl. No. 13/444,485, filed Apr. 11, 2012, Methods for Treatment of Sweat Glands.

U.S. Appl. No. 13/603,159, filed Sep. 4, 2012, Methods for Treatment of Hyperhidrosis.

U.S. Appl. No. 13/603,279, filed Sep. 4, 2012, Energy Based Hyperhidrosis Treatment.

U.S. Appl. No. 13/950,728, filed Jul. 25, 2013, Energy Based Hyperhidrosis Treatment.

U.S. Appl. No. 15/571,835, filed Dec. 16, 2014, Energy Based Hyperhidrosis Treatment.

U.S. Appl. No. 15/243,081, filed Aug. 22, 2016, Energy Based Hyperhidrosis Treatment.

U.S. Appl. No. 11/163,151, filed Oct. 6, 2005, Method and System for Noninvasive Face Lifts and Deep Tissue Tightening.

U.S. Appl. No. 13/444,336, filed Apr. 11, 2012, Treatment of Sub-Dermal Regions for Cosmetic Effects.

U.S. Appl. No. 13/679,430, filed Nov. 16, 2012, Ultrasound Treatment of Sub-Dermal Tissue for Cosmetic Effects.

U.S. Appl. No. 13/924,376, filed Jun. 21, 2013, Noninvasive Tissue Tightening for Cosmetic Effects.

U.S. Appl. No. 13/924,355, filed Jun. 21, 2013, Noninvasive Aesthetic Treatment for Tightening Tissue.

U.S. Appl. No. 13/924,323, filed Jun. 21, 2013, Energy-Based Tissue Tightening.

U.S. Appl. No. 14/200,852, filed Mar. 7, 2014, Noninvasive Tissue Tightening System.

U.S. Appl. No. 14/200,961, filed Mar. 7, 2014, Energy-Based Tissue Tightening System.

U.S. Appl. No. 12/028,636, filed Feb. 8, 2008, Method and System for Noninvasive Face Lifts and Deep Tissue Tightening.

U.S. Appl. No. 13/964,820, filed Aug. 12, 2013, Methods for Noninvasive Skin Tightening.

U.S. Appl. No. 14/201,256, filed Mar. 7, 2014, System for Noninvasive Skin Tightening.

U.S. Appl. No. 15/098,139, filed Apr. 13, 2016, System and Method for Noninvasive Skin Tightening.

U.S. Appl. No. 14/685,390, filed Apr. 13, 2015, Energy-Based Tissue Tightening System.

U.S. Appl. No. 11/163,150, filed Oct. 6, 2005, Method and System for Photoaged Tissue.

(56)

References Cited

OTHER PUBLICATIONS

- U.S. Appl. No. 13/230,498, filed Sep. 12, 2011, Method and System for Photoaged Tissue.
- U.S. Appl. No. 14/169,709, filed Jan. 31, 2014, Methods for Treating Skin Laxity.
- U.S. Appl. No. 14/692,114, filed Apr. 21, 2015, Systems for Treating Skin Laxity.
- U.S. Appl. No. 15/248,407, filed Aug. 26, 2016, Systems for Treating Skin Laxity.
- U.S. Appl. No. 15/625,700, filed Jun. 16, 2017, Systems for Treating Skin Laxity.
- U.S. Appl. No. 15/281,070, filed Nov. 22, 2017, Ultrasound Probe for Treating Skin Laxity.
- U.S. Appl. No. 11/163,176, filed Oct. 7, 2005, Method and System for Treating Blood Vessel Disorders.
- U.S. Appl. No. 13/601,742, filed Aug. 31, 2012, Method and System for Treating Blood Vessel Disorders.
- U.S. Appl. No. 12/574,512, filed Oct. 6, 2009, Method and System for Treating Stretch Marks.
- U.S. Appl. No. 14/554,668, filed Nov. 26, 2014, Method and System for Treating Stretch Marks.
- U.S. Appl. No. 15/260,825, filed Sep. 12, 2016, Method and System for Ultrasound Treatment of Skin.
- U.S. Appl. No. 15/625,818, filed Jun. 16, 2017, Method and System for Ultrasound Treatment of Skin.
- U.S. Appl. No. 11/857,989, filed Sep. 19, 2007, Method and System for Treating Muscle, Tendon, Ligament and Cartilage Tissue.
- U.S. Appl. No. 13/494,856, filed Jun. 12, 2012, Method and System for Treating Muscle, Tendon, Ligament and Cartilage Tissue.
- U.S. Appl. No. 13/835,635, filed Mar. 15, 2013, Methods for Face and Neck Lifts.
- U.S. Appl. No. 13/965,741, filed Aug. 13, 2013, Methods for Preheating Tissue for Cosmetic Treatment of the Face and Body.
- U.S. Appl. No. 14/740,092, filed Jun. 15, 2015, Methods for Rejuvenating Skin by Heating Tissue for Cosmetic Treatment of the Face and Body.
- U.S. Appl. No. 14/628,198, filed Feb. 20, 2015, System and Method for Treating Cartilage and Injuries to Joints and Connective Tissue.
- U.S. Appl. No. 14/554,571, filed Nov. 26, 2014, Methods for Face and Neck Lifts.
- U.S. Appl. No. 15/248,454, filed Aug. 26, 2016, Methods for Face and Neck Lifts.
- U.S. Appl. No. 12/654,484, filed Nov. 24, 2010, Methods and Systems for Generating Thermal Bubbles for Improved Ultrasound Imaging and Therapy.
- U.S. Appl. No. 12/350,383, filed Jan. 8, 2009, Method and System for Treating Acne and Sebaceous Glands.
- U.S. Appl. No. 11/116,845, filed May 7, 2008, Method and System for Combined Energy Profile.
- U.S. Appl. No. 14/643,749, filed Mar. 10, 2015, Method and System for Combined Energy Profile.
- U.S. Appl. No. 08/766,083, filed Dec. 16, 1996, Method and Apparatus for Surface Ultrasound Imaging.
- U.S. Appl. No. 09/113,227, filed Jul. 10, 1998, Method and Apparatus for Three Dimensional Ultrasound Imaging.
- U.S. Appl. No. 08/944,261, filed Oct. 6, 1997, Wideband Acoustic Transducer.
- U.S. Appl. No. 09/434,078, filed Nov. 5, 1999, Method and Apparatus for Three Dimensional Ultrasound Imaging.
- U.S. Appl. No. 09/523,890, filed Mar. 13, 2000, Method and Apparatus for Three Dimensional Ultrasound Imaging.
- U.S. Appl. No. 09/419,543, filed Oct. 18, 1999, Peripheral Ultrasound Imaging System.
- U.S. Appl. No. 09/750,816, filed Dec. 28, 2000, Visual Imaging System for Ultrasonic Probe.
- U.S. Appl. No. 10/358,110, filed Feb. 4, 2003, Visual Imaging System for Ultrasonic Probe.
- U.S. Appl. No. 11/380,161, filed Apr. 25, 2006, Method and System for Enhancing Computer Peripheral Safety.
- U.S. Appl. No. 11/554,272, filed Oct. 30, 2006, Visual Imaging System for Ultrasonic Probe.
- U.S. Appl. No. 13/071,298, filed Mar. 24, 2011, Visual Imaging System for Ultrasonic Probe.
- U.S. Appl. No. 13/854,936, filed Mar. 25, 2013, Visual Imaging System for Ultrasonic Probe.
- U.S. Appl. No. 12/509,254, filed Jul. 24, 2009, Method and System for Enhancing Computer Peripheral Safety.
- U.S. Appl. No. 13/453,847, filed Apr. 23, 2012, Method and System for Enhancing Computer Peripheral Safety.
- U.S. Appl. No. 11/538,794, filed Oct. 4, 2006, Ultrasound System and Method for Imaging and/or Measuring Displacement of Moving Tissue and Fluid.
- U.S. Appl. No. 09/502,175, filed Feb. 10, 2000, Method and Apparatus for Safely Delivering Medicants to a Region of Tissue, Using Imaging, Therapy and Temperature Monitoring.
- U.S. Appl. No. 08/943,728, filed Oct. 3, 1997, Method and Apparatus for Safely Delivering Medicants to a Region of Tissue Using Ultrasound.
- U.S. Appl. No. 12/415,945, filed Mar. 31, 2009, Method and System for Noninvasive Mastopexy.
- U.S. Appl. No. 11/163,155, filed Oct. 6, 2005, Method and System for Noninvasive Mastopexy.
- U.S. Appl. No. 11/163,154, filed Oct. 6, 2005, Method and System for Treatment of Cellulite.
- U.S. Appl. No. 13/356,405, filed Jan. 23, 2012, Method and System for Treatment of Cellulite.
- U.S. Appl. No. 13/789,562, filed Mar. 7, 2013, Method and System for Ultrasound Treatment of Fat.
- U.S. Appl. No. 14/164,598, filed Jan. 27, 2013, Method for Fat and Cellulite Reduction.
- U.S. Appl. No. 14/550,720, filed Nov. 21, 2014, System and Method for Fat and Cellulite Reduction.
- U.S. Appl. No. 15/041,829, filed Feb. 11, 2016, System and Method for Fat and Cellulite Reduction.
- U.S. Appl. No. 13/789,562, filed Dec. 9, 2016, System and Method for Fat and Cellulite Reduction.
- U.S. Appl. No. 15/650,246, filed Jul. 14, 2017, System and Method for Fat and Cellulite Reduction.
- U.S. Appl. No. 13/821,281, filed Nov. 22, 2017, Ultrasound Probe for Fat and Cellulite Reduction.
- U.S. Appl. No. 11/738,682, filed Apr. 23, 2007, Method and System for Non-Ablative Acne Treatment and Prevention.
- U.S. Appl. No. 12/116,810, filed May 7, 2008, Methods and Systems for Modulating Medicants Using Acoustic Energy.
- U.S. Appl. No. 12/116,828, filed May 7, 2008, Methods and Systems for Coupling and Focusing Acoustic Energy Using a Coupler Member.
- U.S. Appl. No. 12/646,609, filed Dec. 23, 2009, Methods and System for Fat Reduction and/or Cellulite Treatment.
- U.S. Appl. No. 14/192,520, filed Feb. 27, 2014, Energy Based Fat Reduction.
- U.S. Appl. No. 14/550,772, filed Nov. 21, 2014, Energy Based Fat Reduction.
- U.S. Appl. No. 15/401,804, filed Feb. 11, 2016, Energy Based Fat Reduction.
- U.S. Appl. No. 15/380,267, filed Dec. 15, 2016, Energy Based Fat Reduction.
- U.S. Appl. No. 15/650,525, filed Jul. 18, 2017, Energy Based Fat Reduction.
- U.S. Appl. No. 13/291,312, filed Nov. 11, 2011, Devices and Methods for Acoustic Shielding.
- U.S. Appl. No. 14/487,504, filed Sep. 16, 2014, Devices and Methods for Acoustic Shielding.
- U.S. Appl. No. 13/136,538, filed Aug. 2, 2011, Systems and Methods for Treating Acute and/or Chronic Injuries in Soft Tissue.
- U.S. Appl. No. 13/136,542, filed Aug. 2, 2011, System and Method for Treating Cartilage.
- U.S. Appl. No. 13/163,541, filed Aug. 2, 2011, Methods and Systems for Treating Plantar Fascia.
- U.S. Appl. No. 13/136,544, filed Aug. 2, 2011, Systems and Methods for Ultrasound Treatment.

(56)

References Cited

OTHER PUBLICATIONS

U.S. Appl. No. 13/547,023, filed Jul. 11, 2012, Systems and Methods for Coupling an Ultrasound Source to Tissue.

U.S. Appl. No. 13/545,931, filed Jul. 10, 2012, Methods and Systems for Controlling Acoustic Energy Deposition Into a Medium.

U.S. Appl. No. 13/545,953, filed Jul. 10, 2012, Systems and Methods for Accelerating Healing of Implanted Material and/or Native Tissue.

U.S. Appl. No. 13/547,011, filed Jul. 11, 2012, Systems and Methods for Monitoring and Controlling Ultrasound Power Output and Stability.

U.S. Appl. No. 13/545,954, filed Jul. 10, 2012, Systems and Methods for Improving an Outside Appearance of Skin Using Ultrasound as an Energy Source.

U.S. Appl. No. 13/545,945, filed Jul. 10, 2012, Systems and Methods for Treating Injuries to Joints and Connective Tissue.

U.S. Appl. No. 13/545,929, filed Jul. 10, 2012, Methods and Systems for Ultrasound Treatment.

U.S. Appl. No. 13/863,249, filed Apr. 15, 2013, Systems for Cosmetic Treatment.

U.S. Appl. No. 13/863,281, filed Apr. 15, 2013, Methods for Non-invasive Cosmetic Treatment.

U.S. Appl. No. 14/847,626, filed Sep. 8, 2015, Systems for Cosmetic Treatment.

U.S. Appl. No. 13/863,362, filed Apr. 15, 2013, Thick Film Transducer Arrays.

U.S. Appl. No. 14/217,110, filed Mar. 17, 2014, Ultrasound Treatment Device and Method of Use.

U.S. Appl. No. 14/217,382, filed Mar. 17, 2014, Ultrasound Treatment Device and Method of Use.

U.S. Appl. No. 14/225,189, filed Mar. 25, 2014, Reflective Ultrasound Technology for Dermatological Treatments.

U.S. Appl. No. 15/345,908, filed Nov. 8, 2016, Reflective Ultrasound Technology for Dermatological Treatments.

U.S. Appl. No. 15/719,377, filed Sep. 28, 2017, Reflective Ultrasound Technology for Dermatological Treatments.

U.S. Appl. No. 14/270,859, filed May 6, 2014, Methods and Systems for Generating Thermal Bubbles for Improved Ultrasound Imaging and Therapy.

U.S. Appl. No. 13/679,494, filed Apr. 6, 2015, Methods and Systems for Generating Thermal Bubbles for Improved Ultrasound Imaging and Therapy.

U.S. Appl. No. 14/405,368, filed Dec. 3, 2014, Devices and Methods for Ultrasound Focal Depth Control.

U.S. Appl. No. 14/568,954, filed Dec. 12, 2014, System and Method for Cosmetic Enhancement of Lips.

U.S. Appl. No. 14/569,001, filed Dec. 12, 2014, System and Method for Non-Invasive Treatment With Improved Efficiency.

U.S. Appl. No. 14/600,782, filed Jan. 20, 2015, Methods and Systems for Controlling and Acoustic Energy Deposition in Various Media.

U.S. Appl. No. 13/738,420, filed Jun. 12, 2015, Systems and Methods for Fast Ultrasound Treatment.

U.S. Appl. No. 14/751,349, filed Jun. 26, 2015, Methods and Systems for Tattoo Removal.

U.S. Appl. No. 15/001,712, filed Jan. 20, 2016, Methods and Systems for Removal of a Targeted Tissue from a Body.

U.S. Appl. No. 15/001,621, filed Jan. 20, 2016, Methods and Systems for Removal of a Foreign Object from Tissue.

U.S. Appl. No. 15/059,773, filed Mar. 3, 2016, Methods and Systems for Material Transport Across an Impermeable or Semi-Permeable Membrane Via Artificially Created Microchannels.

U.S. Appl. No. 15/094,774, filed Apr. 8, 2016, System and Method for Increased Control of Ultrasound Treatments.

Carruthers et al., "Consensus Recommendations for Combined Aesthetic Interventions in the Face Using Botulinum Toxin, Fillers, and Energy-Based Devices" *Dermatol Surg* 2016 (pp. 1-12). Final Written Decision of Inter Partes Review in Re U.S. Pat. No. 6,113,559; IPR2016-01459; 37 pages [030] (Entered Jan. 19, 2018).

* cited by examiner

100





FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4A

400 ↘




FIG. 4B




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 10D




FIG. 10E




FIG. 10F




FIG. 11




FIG. 12




FIG. 13




FIG. 14A




FIG. 14B




FIG. 15




FIG. 16A




FIG. 16B




FIG. 17




FIG. 18A




FIG. 18B

ENERGY BASED FAT REDUCTION**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. application Ser. No. 15/650,525, filed Jul. 14, 2017, now U.S. Pat. No. 9,833,639, which is a continuation of U.S. application Ser. No. 15/380,267, filed Dec. 15, 2016, now U.S. Pat. No. 9,713,731, which is a continuation of U.S. application Ser. No. 15/041,804, filed Feb. 11, 2016, now U.S. Pat. No. 9,533,175, which is a continuation of U.S. application Ser. No. 14/550,772, filed Nov. 21, 2014, now U.S. Pat. No. 9,283,409, which is a continuation of U.S. application Ser. No. 14/192,520 filed Feb. 27, 2014, now U.S. Pat. No. 8,920,324, which is a continuation of U.S. application Ser. No. 12/646,609 filed Dec. 23, 2009, now U.S. Pat. No. 8,663,112, which is a continuation-in-part of U.S. application Ser. No. 11/163,154 filed on Oct. 6, 2005, now U.S. Pat. No. 8,133,180, which claims the benefit of priority to U.S. Provisional No. 60/616,753 filed on Oct. 6, 2004, each of which are hereby incorporated by reference in their entirety herein. In addition, U.S. application Ser. No. 12/646,609, now U.S. Pat. No. 8,663,112, claims the benefit of priority from U.S. Provisional No. 61/140,725 filed on Dec. 24, 2008, which is hereby incorporated by reference in its entirety herein. Any and all priority claims identified in the Application Data Sheet, or any correction thereto, are hereby incorporated by reference under 37 CFR 1.57.

BACKGROUND**Field of the Invention**

The present invention relates to ultrasound therapy systems, and in particular to methods and systems for treating cellulite or reducing fat.

Description of the Related Art

In general, cellulite refers to a common skin disorder which is characterized by a dimple appearance in a person's skin that may be found on the hips, thighs, and/or buttocks. Underneath the dermis and epidermis layers of the skin there are multiple layers of fat. Cellulite tends to develop in the subcutaneous fat layers, which is unique as compared to other fat layers because the subcutaneous fat can be structured into specific chambers surrounded by strands of linked tissue, which are known as fat lobuli. This appearance is much more common in women than in men because of differences in the way fat, muscle, and connective tissue are distributed in men's and women's skin. The lumpiness of cellulite is caused by the fat lobuli that push and distort the connective tissues beneath the skin; resulting protrusions and depressions of connective tissue anchor points create the appearance of cellulite.

Invasive treatments for cellulite include Iontophoresis, liposuction, and electrolipophoresis, which can involve an application of a low-frequency electric current. Non-invasive treatments for cellulite can include laser and suction massage combination therapy, pneumatic pressure massage therapy, lymphatic drainage massage, and low-frequency ultrasound diathermy. Such invasive and non-invasive treatments have yielded marginal results. In addition, a number of drugs that act on fatty tissue have been tried as therapeutic agents for cellulite treatment. Such drugs can be administered orally, applied topically as ointments, or by transdermal injection. At this point, no drug has been reported in

the scientific literature as having a significant effect on cellulite. New developments for the treatment of cellulite are needed.

In addition, similar techniques have attempted to address the reduction of fat in humans, but such attempts have likewise had mixed results.

SUMMARY

In accordance with various aspects of the present invention, non-invasive methods and systems for fat reduction and/or treatment of cellulite are provided. In accordance with an exemplary embodiment, a non-invasive method for cellulite treatment can include targeting a region of interest below a surface of skin, which contains fat lobuli and delivering ultrasound energy to the region of interest. The ultrasound energy generates a conformal lesion with said ultrasound energy on a surface of a fat lobuli. The lesion creates an opening in the surface of the fat lobuli, which allows the draining of a fluid out of the fat lobuli and through the opening.

In accordance with an exemplary embodiment, a non-invasive method for cellulite treatment can include targeting fat cells in a subcutaneous fat layer and delivering ultrasound energy to raise the temperature of the fat cells, stimulating apoptosis of the fat cells and then allowing the targeted fat cells to die, thereby reducing a quantity of fat cells in the subcutaneous layer.

Further areas of applicability will become apparent from the description provided herein. It should be understood that the description and specific examples are intended for purposes of illustration only and are not intended to limit the scope of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

The drawings described herein are for illustration purposes only and are not intended to limit the scope of the present disclosure in any way. The present invention will become more fully understood from the detailed description and the accompanying drawings wherein:

FIG. 1 illustrates a block diagram of an ultrasound treatment system for treating cellulite in accordance with exemplary embodiments of the present invention;

FIG. 2 illustrates a cross-sectional diagram of a transducer system in accordance with exemplary embodiments of the present invention;

FIGS. 3A and 3B illustrate block diagrams of an exemplary control system in accordance with exemplary embodiments of the present invention;

FIGS. 4A and 4B illustrate block diagrams of an exemplary probe system in accordance with exemplary embodiments of the present invention;

FIG. 5 illustrates a cross-sectional diagram of an exemplary transducer in accordance with exemplary embodiments of the present invention;

FIGS. 6A and 6B illustrate cross-sectional diagrams of an exemplary transducer in accordance with exemplary embodiments of the present invention;

FIG. 7 illustrates exemplary transducer configurations for ultrasound treatment in accordance with exemplary embodiments of the present invention;

FIGS. 8A and 8B illustrate cross-sectional diagrams of an exemplary transducer in accordance with exemplary embodiments of the present invention;

FIG. 9 illustrates an exemplary transducer configured as a two-dimensional array for ultrasound treatment in accordance with exemplary embodiments of the present invention;

FIGS. 10A-10F illustrate cross-sectional diagrams of exemplary transducers in accordance with exemplary embodiments of the present invention;

FIG. 11 illustrates a schematic diagram of an acoustic coupling and cooling system in accordance with exemplary embodiments of the present invention;

FIG. 12 illustrates a block diagram of a treatment system comprising an ultrasound treatment subsystem combined with additional subsystems and methods of treatment monitoring and/or treatment imaging as well as a secondary treatment subsystem in accordance with exemplary embodiments of the present invention;

FIG. 13 is a cross-sectional diagram illustrating a method of treating cellulite in accordance with exemplary embodiments of the present invention;

FIGS. 14A and 14B are cross-sectional diagrams illustrating another method of treating cellulite in accordance with exemplary embodiments of the present invention;

FIG. 15 is a block diagram illustrating a method of treating cellulite in accordance with exemplary embodiments of the present invention;

FIGS. 16A and 16B are cross-sectional diagrams illustrating a method of reducing fat and treating cellulite in accordance with exemplary embodiments of the present invention;

FIG. 17 is a block diagram illustrating a method of fat reduction in accordance with exemplary embodiments of the present invention; and

FIGS. 18A and 18B are cross-sectional diagrams illustrating a method of reducing fat in accordance with exemplary embodiments of the present invention.

DETAILED DESCRIPTION

The following description is merely exemplary in nature and is not intended to limit the present invention or its teachings, applications, or uses thereof. It should be understood that throughout the drawings, corresponding reference numerals indicate like or corresponding parts and features. The description of specific examples indicated in various embodiments and aspects of the present invention are intended for purposes of illustration only and are not intended to limit the scope of the invention disclosed herein. Moreover, recitation of multiple embodiments having stated features is not intended to exclude other embodiments having additional features or other embodiments incorporating different combinations of the stated features.

The present invention may be described herein in terms of various functional components and processing steps. It should be appreciated that such components and steps may be realized by any number of hardware components configured to perform the specified functions. For example, the present invention may employ various medical treatment devices, visual imaging and display devices, input terminals and the like, which may carry out a variety of functions under the control of one or more control systems or other control devices. In addition, the present invention may be practiced in any number of medical or cosmetic contexts and the exemplary embodiments relating to a non-invasive methods and systems for fat reduction and/or cellulite treatment as described herein are merely indicative of exemplary applications for the invention. For example, various of the

principles, features and methods discussed herein may be applied to any medical or cosmetic application, or other related applications.

Various aspects of the present invention provide a method of non-invasive treatment of cellulite. The method includes targeting a region of interest below a surface of skin, which contains fat lobuli and delivering ultrasound energy to the region of interest. The ultrasound energy generates a conformal lesion within the ultrasound energy on a surface of a fat lobuli, such as, for example, by creating a sharp focal of ultrasound energy onto the fat lobuli. The lesion creates an opening in the surface of the fat lobuli, such as, for example, by piercing the fat lobuli, which allows the draining of a fluid out of the fat lobuli through the opening.

Various aspects of the present invention can also provide a method for fat reduction that can include heating a region of interest to a temperature in a range from about 43° C. to about 49° C., which can stimulate apoptosis of at least one fat cell in the fat lobuli. Still further, the method can include applying a physical treatment to said surface of skin and such physical treatment can include mesotherapy, iontophoresis, pressotherapy, pneumatic massage, lymphatic drainage, electrolipophoresis, roller massage, low frequency ultrasound, vacuum suction, laser energy, and application of RF energy. The physical treatment can be before, after, or concurrent with the delivery of the ultrasound energy. The method can include the use of a second energy, which can be used before, after, or concurrent with the delivery of the ultrasound energy. The method can reduce the appearance of cellulite on the surface of skin.

Various aspects of the present invention provide a method of non-invasively stimulating apoptosis of a fat cell located in a subcutaneous fat layer. The method include targeting at least one fat cell in a subcutaneous layer below a skin surface and delivering energy to the fat cell. The delivered energy raises a temperature of the fat cell into a range from about 43° C. to about 49° C., which stimulates apoptosis of the fat cell.

The method can further include imaging of the fat cell. Still further, the method can include generating a conformal lesion into said at least one fat cell, which can create an opening in the fat cell and allow the moving of a material out of the fat cell through the opening. The energy is typically ultrasound energy in the range of about 750 kHz to about 20 MHz or in a range from about 2 MHz to about 20 MHz, or other more specific ranges. Still further the method can include applying a physical treatment to said surface of skin and such physical treatment can include mesotherapy, iontophoresis, pressotherapy, pneumatic massage, lymphatic drainage, electrolipophoresis, roller massage, low-frequency ultrasound, vacuum suction, laser energy, and application of RF energy. The physical treatment can be before, after, or concurrent with the delivery of the energy. The method can include the use of a second energy, which can be used before, after, or concurrent with the delivery of the energy. The method can reduce the number of fat cells in the subcutaneous fat layer.

In addition, various aspects of the present invention provide a method that combines fat reduction and cellulite reduction. The method includes targeting a region of interest below a surface of skin, which contains fat lobuli, and delivering ultrasound energy to the region of interest. The ultrasound energy generates a conformal lesion with said ultrasound energy on a surface of a fat lobuli. The lesion creates an opening in the surface of the fat lobuli, which allows the draining of a fluid out of the fat lobuli through the opening. Additionally, the method can include targeting at

least one fat cell in a subcutaneous layer below a skin surface and delivering a second energy to the fat cell. The delivered second energy raises a temperature of the fat cell into a range from about 43° C. to about 49° C., which stimulates apoptosis of the fat cell.

The method can further include a physical treatment as described herein, as well as the use of a secondary energy source. The method can both reduce the number of fat cells in the subcutaneous fat layer and reduce the appearance of cellulite on a skin surface. The method can be effective in physically breaking fat cell clusters and stretching fibrous bonds of cellulite.

In accordance with an exemplary embodiment, a method of non-invasive treatment of cellulite can include targeting a region of interest below a skin surface, which contains fat lobuli, and delivering ultrasound energy at a specified depth below the skin surface. The method further includes moving a source of the energy along the skin surface and ablating a portion of the fat lobuli at the specified depth below the skin surface.

In accordance with the exemplary method, a specified depth is generally in the range of about 1 mm to about 35 mm below the skin surface. The method can include applying a physical treatment as described herein. The method can smooth the skin surface and may reduce the appearance of cellulite on the skin surface. The method can further include any of the additional method steps discussed herein.

In accordance with various aspects of the present invention, non-invasive methods and systems for the reduction of fat and/or the treating of cellulite are provided. For example, in accordance with an exemplary embodiment, with reference to FIG. 1, an exemplary treatment system 100 configured to treat a region of interest 106 comprises a control system 102, an imaging/therapy probe with acoustic coupling 104, and a display system 108.

Control system 102 and display system 108 can comprise various configurations for controlling probe 104 and overall system 100 functionality. In various embodiments, control system 102 can include, for example but not limited to any of the following, a microprocessor with software and a plurality of input/output devices, systems or devices for controlling electronic and/or mechanical scanning and/or multiplexing of transducers, systems for power delivery, systems for monitoring, systems for sensing the spatial position of the probe and/or transducers, and/or systems for handling user input and recording treatment results, among others. Imaging/therapy probe 104 can comprise various probe and/or transducer configurations. For example, probe 104 can be configured for a combined dual-mode imaging/therapy transducer, coupled or co-housed imaging/therapy transducers, or simply a separate therapy probe and an imaging probe.

In accordance with an exemplary embodiment, treatment system 100 is configured for treating a deep tissue region that contains a lower part of dermis and proximal protrusions of fat lobuli into the dermis by, first, imaging region of interest (“ROI”) 210 for localization of the treatment area and surrounding structures, second, delivering ultrasound energy at a depth, distribution, timing, and energy level to achieve the desired therapeutic effect, and third monitoring the treatment area before, during, and after therapy to plan and assess the results and/or provide feedback. As to the delivery of energy, control system 102 and transducer system 102 can be suitably configured to deliver conformal ultrasound therapeutic energy to ROI 210 creating a thermal injury and coagulating the proximal protrusions of fat lobuli,

thereby eliminating the fat protrusions into the dermis. As used herein, the term “dermis” refers to any part of the dermis and/or the epidermis.

Because the location and thickness of the fat lobuli varies from one patient to another (due to genetics, weight, age, etc.), imaging using a transducer can facilitate treatment within a patient, however imaging is not required to treat cellulite.

By planning a treatment protocol, the user may choose one or more spatial and/or temporal characteristics to provide conformal ultrasound energy to ROI 210. For example, the user may select one or more spatial characteristics to control, including, for example, the use of one or more transducers, one or more mechanical and/or electronic focusing mechanisms, one or more transduction elements, one or more placement locations of the transducer relative to ROI 210, one or more feedback systems, one or more mechanical arms, one or more orientations of the transducer, one or more temperatures of treatment, one or more coupling mechanisms and/or the like.

In addition, the user may choose one or more temporal characteristics to control in order to facilitate treatment of ROI 210. For example, the user may select and/or vary the treatment time, frequency, power, energy, amplitude and/or the like in order to facilitate temporal control. For more information on selecting and controlling ultrasound spatial and temporal characteristics, see U.S. application Ser. No. 11/163,148, entitled “Method and System for Controlled Thermal Injury”, filed Oct. 6, 2005, published on Jun. 1, 2006 as U.S. Patent Application Publication No. 20060116671, and incorporated herein by reference.

After planning of a treatment protocol is complete, the treatment protocol can be implemented. That is, a transducer system can be used to deliver ultrasound energy to a treatment region to ablate select tissue in order to facilitate cellulite treatment. By delivering energy, the transducer may be driven at a select frequency, a phased array may be driven with certain temporal and/or spatial distributions, a transducer may be configured with one or more transduction elements to provide focused, defocused and/or planar energy, and/or the transducer may be configured and/or driven in any other ways hereinafter devised.

For treatment of ROI 210, transducer system 102 may be configured to deliver one or more energy fields to promote one or more effects, for example, ablation of existing tissue, the breaking up of fat cell clusters, stretching of the fibrous bonds, enhancement of lymphatic drainage, stimulation of the evacuation of fat decay products, and/or enhanced cell permeability in order to treat cellulite. Additionally, for treatment of ROI 210, transducer system 102 may be configured to deliver one or more energy fields to promote one or more effects, for example cell apoptosis, piercing cells to promote drainage, and ablating a layer of fat cells to a specified distance below a skin surface, such as for example giving the fat cells a haircut. Of course transducer system may be configured to deliver one energy field as needed by any of the methods of treatment described herein. As described herein, imaging is not necessary for treatment methods or treatment plans but rather is an optional step. For example, the dimpled pattern of cellulite is typically visible on the surface of a patient’s skin and the system user can easily identify ROI 210 that will be treated.

Through operation of treatment system 100, a method for treatment of cellulite can be realized that can facilitate effective and efficient therapy without creating chronic injury to human tissue. For example, a user may first select one or more transducer probe configurations for treating

ROI 210. The user may select any probe configuration described herein. Because the treatment region ranges from about 0 mm to greater than about 5.5 cm or from about 1 mm to about 3.5 cm, exemplary transducer probes may include, for example, an annular array, a variable depth transducer, a mechanically moveable transducer, a cylindrical-shaped transducer, a linear or flat transducer and the like. As used herein, the term user may include a person, employee, doctor, nurse, and/or technician, utilizing any hardware and/or software of other control systems.

Once one or more transducers are selected, the user may then image ROI 210 in order to plan a treatment protocol. By imaging ROI 210, the user may use the same treatment transducer probe and/or one or more additional transducers to image ROI 210 at a high resolution. In one embodiment, the transducer may be configured to facilitate high speed imaging over a large ROI 210 to enable accurate imaging over a large ROI 210. In another embodiment, ultrasound imaging may include, individually or in combination, the use of Doppler flow monitoring and/or color flow monitoring. In addition, other means of imaging such as photography and other visual optical methods, MRI, X-Ray, PET, infrared or others can be utilized separately or in combination for imaging and feedback of the superficial tissue and the vascular tissue in ROI 210.

An exemplary ultrasound therapy system of FIG. 1 is further illustrated in an exemplary embodiment in FIG. 2. A therapy transducer system 200 includes a transducer probe 202 connected to control system 204, and display 206, in combination may provide therapy, imaging, and/or temperature or other tissue parameters monitoring to ROI 210. Exemplary transducer system 200 is configured for, first, imaging and display of ROI 210 for localization of the treatment area and surrounding structures, second, delivery of focused, unfocused, or defocused ultrasound energy at a depth, distribution, timing, and energy level to achieve the desired therapeutic effect of thermal ablation to treat cellulite, and, third, to monitor the treatment area and surrounding structures before, during, and after therapy to plan and assess the results and/or provide feedback to control system 204 and/or an operator.

Exemplary transducer probe 202 can be configured to be suitably controlled and/or operated in various manners. For example, transducer probe 202 may be configured for use within an ultrasound treatment system, an ultrasound imaging system and/or an ultrasound imaging, therapy, and/or treatment monitoring system, including motion control subsystems.

Control system 204 can be configured with one or more subsystems, processors, input devices, displays and/or the like. Display 206 may be configured to image and/or monitor ROI 210 and/or any particular sub-region within ROI 210. Display 206 can be configured for two-dimensional, three-dimensional, real-time, analog, digital and/or any other type of imaging. Exemplary embodiments of both control system 204 and display 206 are described in greater detail herein.

ROI 210, can be comprised of superficial layer (epidermis/dermis) subcutaneous fat, lobuli, and muscle. Exemplary transducer system 200 is configured to provide cross-sectional two-dimensional imaging of the region 207, displayed as an image 205, with a controlled thermal lesion 209, confined approximately to proximal portion of fat lobuli and lower portion of dermis.

Transducer system 200 can be configured with the ability to controllably produce conformal treatment areas in superficial human tissue within ROI 210 through precise spatial

and temporal control of acoustic energy deposition. In accordance with an exemplary embodiment, control system 204 and transducer probe 202 can be suitably configured for spatial control of the acoustic energy by controlling the manner of distribution of the acoustical energy. For example, spatial control may be realized through selection of the type of one or more transducer configurations insonifying ROI 210, selection of the placement and location of transducer probe 202 for delivery of acoustical energy relative to ROI 210, e.g., transducer probe 202 configured for scanning over part or whole of ROI 210 to deliver conformal ultrasound therapeutic energy to create a thermal injury, such as a lesion, and to coagulate the proximal protrusions of fat lobuli, thereby eliminating the fat protrusions into the dermis. Transducer probe 202 may also be configured for control of other environment parameters, e.g., the temperature at the acoustic coupling interface can be controlled. In addition to the spatial control, control system 204 and/or transducer probe 202 can also be configured for temporal control, such as through adjustment and optimization of drive amplitude levels, frequency/waveform selections, and timing sequences and other energy drive characteristics to control the treatment of tissue. The spatial and/or temporal control can also be facilitated through open-loop and closed-loop feedback arrangements, such as through the monitoring of various positional and temporal characteristics. For example, through such spatial and/or temporal control, an exemplary treatment system 200 can enable the regions of thermal injury to possess arbitrary shape and size and allow the tissue to be treated in a controlled manner.

Transducer system 200 may be used to provide a mechanical action of ultrasound to physically break fat cell clusters and stretch the fibrous bonds. This mechanical action will also enhance lymphatic drainage, stimulating the evacuation of fat decay products. That is, the ultrasound may facilitate movement of the muscles and soft tissues within ROI 210, thereby facilitating the loosening of fat deposits and/or the break up of fibrous tissue surrounding fat deposits.

In addition, transducer system 200 can be configured to deliver various therapeutic levels of ultrasound to increase the speed at which fat metabolizes, according to Arrhenius' Law: $K=Ae^{-B/T}$, where K is the kinetic rate of fat metabolism, A is a constant, B is the activation energy, and T is the temperature in degrees Kelvin. According to Arrhenius' Law, a metabolic reaction is a function of temperature. In exemplary embodiments, transducer system 200 is configured to provide various therapeutic levels of ultrasound to increase a temperature of fat cells in order to maximize the speed at which fat metabolizes. Moreover, transducer system 200 can be configured to deliver various therapeutic levels of ultrasound to increase the speed at which fat metabolizes. According to a modified equation of Arrhenius' Law, a metabolic reaction is a function of temperature and time, $T: K=At e^{-B/T}$, where K is the kinetic rate of fat metabolism, A is a constant, B is the activation energy, t is time, and T is the temperature in degrees Kelvin. In exemplary embodiments, transducer system 200 is configured to provide various therapeutic levels of ultrasound for a specified time period or for a pulsed delivery over time to increase a temperature of fat cells in order to maximize the speed at which fat metabolizes. Moreover, transducer system 200 can be configured to deliver various therapeutic levels of ultrasound for a specified time period or for a pulsed delivery over time to increase the speed at which fat metabolizes. Thus, ultrasound treatment from transducer system 200, ranging from approximately 750 kHz to 20

MHz, can increase the temperature in a treatment area, thereby increasing the metabolic reaction yield for that treatment area. As such, fat metabolism in the treatment area is increased which leads to fat cell reduction and decreases the appearance of cellulite above the treatment area. Ultra-

sound treatment from transducer **200** can be programmed to provide appropriate temperatures and optionally for appropriate time to ROI **210** to increase the spread of fat cell metabolism leading to fat cell destruction and optionally reducing the appearance of cellulite.

In some aspects of the present invention, a method of increasing metabolism of fat cells in a subcutaneous fat layer is provided. The method can include targeting a plurality of fat cells in a subcutaneous fat layer, heating the plurality of fat cells to a temperature as defined by Arrhenius' Law, increasing a metabolism of at least a portion of the plurality of fat cells, and reducing a portion of the plurality of fat cells. The method can also include any physical treatment described herein before, after, and/or concurrent with increasing the metabolism of the fat cells. In addition, the method can include the use a secondary energy as described herein.

As previously described, control systems **104** and **204** may be configured in a variety of manners with various subsystems and subcomponents. With reference to FIGS. **3A** and **3B**, in accordance with exemplary embodiments, an exemplary control system **300** can be configured for coordination and control of the entire therapeutic treatment process in accordance with the adjustable settings made by a therapeutic treatment system user. For example, control system **300** can suitably comprise power source components **302**, sensing and monitoring components **304**, cooling and coupling controls **306**, and/or processing and control logic components **308**. Control system **300** can be configured and optimized in a variety of ways with more or less subsystems and components to implement the therapeutic system for cellulite treatment, and the embodiment in FIGS. **3A** and **3B** are merely for illustration purposes.

For example, for power sourcing components **302**, control system **300** can comprise one or more direct current (DC) power supplies **303** configured to provide electrical energy for entire control system **300**, including power required by transducer electronic amplifier/driver **312**. DC current sense device **305** can also be provided to confirm the level of power going into amplifiers/drivers **312** for safety and monitoring purposes.

Amplifiers/drivers **312** can comprise multi-channel or single channel power amplifiers and/or drivers. In accordance with an exemplary embodiment for transducer array configurations, amplifiers/drivers **312** can also be configured with a beamformer to facilitate array focusing. An exemplary beamformer can be electrically excited by an oscillator/digitally controlled waveform synthesizer **310** with related switching logic.

Power sourcing components **302** can also include various filtering configurations **314**. For example, switchable harmonic filters and/or matching may be used at the output of amplifier/driver **312** to increase the drive efficiency and effectiveness. Power detection components **316** may also be included to confirm appropriate operation and calibration. For example, electric power and other energy detection components **316** may be used to monitor the amount of power going to an exemplary probe system.

Various sensing and monitoring components **304** may also be suitably implemented within control system **300**. For example, in accordance with an exemplary embodiment, monitoring, sensing and interface control components **324**

may be configured to operate with various motion detection systems implemented within transducer probe **104** to receive and process information such as acoustic or other spatial and temporal information from ROI **210**. Sensing and monitoring components can also include various controls, interfacing and switches **309** and/or power detectors **316**. Such sensing and monitoring components **304** can facilitate open-loop and/or closed-loop feedback systems within treatment system **100**.

For example, in such an open-loop system, a system user can suitably monitor the imaging and/or other spatial or temporal parameters and then adjust or modify the same to accomplish a particular treatment objective. Instead of, or in combination with, open-loop feedback configurations, an exemplary treatment system can comprise a closed-loop feedback system, wherein images and/or spatial/temporal parameters can be suitably monitored within monitoring components **304** to generate signals.

During operation of exemplary treatment system **100**, a lesion configuration of a selected size, shape, and orientation is determined. Based on that lesion configuration, one or more spatial parameters are selected, along with suitable temporal parameters, the combination of which yields the desired conformal lesion. Operation of the transducer can then be initiated to provide the conformal lesion or lesions. Open and/or closed-loop feedback systems can also be implemented to monitor the spatial and/or temporal characteristics, and/or other tissue parameter monitoring, to further control the conformal lesions.

Cooling/coupling control systems **306** may be provided to remove waste heat from exemplary probe **104**, provide a controlled temperature at the superficial tissue interface and deeper into tissue, and/or provide acoustic coupling from transducer probe **104** to ROI **210**. Such cooling/coupling control systems **306** can also be configured to operate in both open-loop and/or closed-loop feedback arrangements with various coupling and feedback components.

Processing and control logic components **308** can comprise various system processors and digital control logic **307**, such as one or more of microcontrollers, microprocessors, field-programmable gate arrays (FPGAs), computer boards, and associated components, including firmware and control software **326**, which interfaces to user controls and interfacing circuits as well as input/output circuits and systems for communications, displays, interfacing, storage, documentation, and other useful functions. System software and firmware **326** controls all initialization, timing, level setting, monitoring, safety monitoring, and all other system functions required to accomplish user-defined treatment objectives. Further, various control switches **308** can also be suitably configured to control operation.

An exemplary transducer probe **104** can also be configured in various manners and can comprise a number of reusable and/or disposable components and parts in various embodiments to facilitate its operation. For example, transducer probe **104** can be configured within any type of transducer probe housing or arrangement for facilitating the coupling of a transducer to a tissue interface, with such housing comprising various shapes, contours and configurations depending on the particular treatment application. For example, in accordance with an exemplary embodiment, transducer probe **104** can be depressed against a tissue interface whereby blood perfusion is partially or wholly cut-off, and tissue is flattened in superficial treatment ROI **210**. Transducer probe **104** can comprise any type of matching, such as for example, electric matching, which may be electrically switchable; multiplexer circuits and/or aperture/

element selection circuits; and/or probe identification devices, to certify probe handle, electric matching, transducer usage history and calibration, such as one or more serial EEPROM (memories).

Transducer probe **104** may also comprise cables and connectors; motion mechanisms, motion sensors and encoders; thermal monitoring sensors; and/or user control and status related switches, and indicators such as LEDs. For example, a motion mechanism in probe **104** may be used to controllably create multiple lesions, or sensing of probe motion itself may be used to controllably create multiple lesions and/or stop creation of lesions, e.g. for safety reasons if probe **104** is suddenly jerked or is dropped. In addition, an external motion encoder arm may be used to hold the probe during use, whereby the spatial position and attitude of probe **104** is sent to the control system to help controllably create lesions. Furthermore, other sensing functionality such as profilometers or other imaging modalities may be integrated into the probe in accordance with various exemplary embodiments.

With reference to FIGS. **4A** and **4B**, in accordance with an exemplary embodiment, transducer probe **400** can comprise control interface **402**, transducer **404**, coupling components **406**, and monitoring/sensing components **408**, and/or motion mechanism **410**. However, transducer probe **400** can be configured and optimized in a variety of ways with more or less parts and components to provide ultrasound energy for cellulite treatment and/or fat reduction, and the embodiments illustrated in FIGS. **4A** and **4B** are merely for illustration purposes. In some embodiments, transducer probe **104** is equivalent to transducer probe **400**. In some embodiments, transducer probe **104**, discussed above, can comprise control interface **402**, transducer **404**, coupling components **406**, and monitoring/sensing components **408**, and/or motion mechanism **410**.

In accordance with an exemplary embodiment of the present invention, transducer probe **400** is configured to deliver energy over varying temporal and/or spatial distributions in order to provide energy effects and initiate responses in ROI **210**. These effects can include, for example, thermal, cavitation, hydrodynamic, and resonance induced tissue effects. For example, exemplary transducer probe **400** can be operated under one or more frequency ranges to provide two or more energy effects and initiate one or more responses in ROI **210**. In addition, transducer probe **400** can also be configured to deliver planar, defocused and/or focused energy to ROI **210** to provide two or more energy effects and to initiate one or more reactions. These responses can include, for example, diathermy, hemostasis, revascularization, angiogenesis, growth of interconnective tissue, tissue reformation, ablation of existing tissue, protein synthesis, cell apoptosis, and/or enhanced cell permeability.

These and various other exemplary embodiments of systems and components for such combined ultrasound treatment, effects and responses are more fully set forth in U.S. patent application Ser. No. 10/950,112, entitled "Method and System for Combined Ultrasound Treatment", filed Sep. 24, 2004, published on Apr. 6, 2006 as U.S. Patent Application Publication No. 20060074355, and incorporated herein by reference.

In addition, these and various other exemplary embodiments of systems and components for such combined ultrasound treatment, effects and responses are more fully set forth in U.S. Pat. No. 6,050,943, entitled "Imaging, Therapy, and Temperature Monitoring Ultrasonic System", issued Apr. 18, 2000, and U.S. Pat. No. 6,500,121 entitled "Imag-

ing, Therapy, and temperature Monitoring Ultrasonic System," issued Dec. 31, 2002, both of which are incorporated herein by reference.

Control interface **402** is configured for interfacing with control system **300** to facilitate control of transducer probe **400**. Control interface components **402** can comprise multiplexer/aperture select **424**, switchable electric matching networks **426**, serial EEPROMs and/or other processing components and matching and probe usage information **430** and interface connectors **432**.

Coupling components **406** can comprise various devices to facilitate coupling of transducer probe **400** to ROI **210**. For example, coupling components **406** can comprise cooling and acoustic coupling system **420** configured for acoustic coupling of ultrasound energy and signals. Coupling system **420** with possible connections such as manifolds may be utilized to couple sound into ROI **210**, control temperature at the interface and deeper into tissue, provide liquid-filled lens focusing, and/or to remove transducer waste heat. Coupling system **420** may facilitate such coupling through use of various coupling mediums, including air and other gases, water and other fluids, gels, solids, and/or any combination thereof, or any other medium that allows for signals to be transmitted between transducer active elements **412** and ROI **210**. In addition to providing a coupling function, in accordance with an exemplary embodiment, coupling system **420** can also be configured for providing temperature control during the treatment application. For example, coupling system **420** can be configured for controlled cooling of an interface surface or region between transducer probe **400** and ROI **210** and beyond by suitably controlling the temperature of the coupling medium. The suitable temperature for such coupling medium can be achieved in various manners, and utilize various feedback systems, such as thermocouples, thermistors or any other device or system configured for temperature measurement of a coupling medium. Such controlled cooling can be configured to further facilitate spatial and/or thermal energy control of transducer probe **400**.

Monitoring and sensing components **408** can comprise various motion and/or position sensors **416**, temperature monitoring sensors **418**, user control and feedback switches **414** and other like components for facilitating control by control system **300**, e.g., to facilitate spatial and/or temporal control through open-loop and closed-loop feedback arrangements that monitor various spatial and temporal characteristics.

Motion mechanism **410** can comprise manual operation, mechanical arrangements, or some combination thereof. For example, motion mechanism **422** can be suitably controlled by control system **300**, such as through the use of accelerometers, encoders or other position/orientation devices **416** to determine and enable movement and positions of transducer probe **400**. Linear, rotational or variable movement can be facilitated, e.g., those depending on the treatment application and tissue contour surface.

Transducer **404** can comprise one or more transducers configured for producing conformal lesions of thermal injury in superficial human tissue within ROI **210** through precise spatial and temporal control of acoustic energy deposition. Transducer **404** can also comprise one or more transduction elements and/or lenses **412**. The transduction elements can comprise a piezoelectrically active material, such as lead zirconate titanate (PZT), or any other piezoelectrically active material, such as a piezoelectric ceramic, crystal, plastic, and/or composite materials, as well as lithium niobate, lead titanate, barium titanate, and/or lead

metaniobate. In addition to, or instead of, a piezoelectrically active material, transducer **404** can comprise any other materials configured for generating radiation and/or acoustic energy. Transducer **404** can also comprise one or more matching layers configured along with the transduction element such as coupled to the piezoelectrically active material. Acoustic matching layers and/or damping may be employed as necessary to achieve the desired electroacoustic response.

In accordance with an exemplary embodiment, the thickness of the transduction element of transducer **404** can be configured to be uniform. That is, transduction element **412** can be configured to have a thickness that is substantially the same throughout. In accordance with another exemplary embodiment, the thickness of transduction element **412** can also be configured to be variable. For example, transduction element(s) **412** of transducer **404** can be configured to have a first thickness selected to provide a center operating frequency of a lower range, for example from approximately 750 kHz to 5 MHz. Transduction element **404** can also be configured with a second thickness selected to provide a center operating frequency of a higher range, for example from approximately 5 MHz to 20 MHz or more. Transducer **404** can be configured as a single broadband transducer excited with at least two or more frequencies to provide an adequate output for generating a desired response. Transducer **404** can also be configured as two or more individual transducers, wherein each transducer comprises one or more transduction element. The thickness of the transduction elements can be configured to provide center-operating frequencies in a desired treatment range. For example, transducer **404** can comprise a first transducer configured with a first transduction element having a thickness corresponding to a center frequency range of approximately 750 kHz to 5 MHz, and a second transducer configured with a second transduction element having a thickness corresponding to a center frequency of approximately 5 MHz to 20 MHz or more.

Transducer **404** may be composed of one or more individual transducers in any combination of focused, planar, or unfocused single-element, multi-element, or array transducers, including 1-D, 2-D, and annular arrays; linear, curvilinear, sector, or spherical arrays; spherically, cylindrically, and/or electronically focused, defocused, and/or lensed sources.

In accordance with another exemplary embodiment, transducer probe **400** may be suitably configured to provide three-dimensional treatment. For example, to provide three-dimensional treatment of ROI **210**, with reference again to FIG. **4**, a three-dimensional system can comprise transducer probe **400** configured with an adaptive algorithm, such as, for example, one utilizing three-dimensional graphic software, contained in a control system, such as for example control system **300**. The adaptive algorithm is suitably configured to receive two-dimensional imaging, temperature monitoring and/or treatment information relating to ROI **210**, process the received information, and then provide corresponding three-dimensional imaging, temperature and/or treatment information.

In accordance with another aspect of the invention, transducer probe **400** may be configured to provide one, two or three-dimensional treatment applications for focusing acoustic energy to one or more regions of interest. For example, as discussed above, transducer probe **400** can be suitably diced to form a one-dimensional array, e.g., a transducer comprising a single array of sub-transduction elements.

For example, with reference to an exemplary embodiment depicted in FIG. **5**, exemplary transducer **500** can be configured as an acoustic array **502** to facilitate phase focusing. That is, transducer **500** can be configured as an array of electronic apertures that may be operated by a variety of phases via variable electronic time delays. By the term “operated,” the electronic apertures of transducer **500** may be manipulated, driven, used, and/or configured to produce and/or deliver an energy beam corresponding to the phase variation caused by the electronic time delay. For example, these phase variations can be used to deliver defocused beams **508**, planar beams **504**, and/or focused beams **506**, each of which may be used in combination to achieve different physiological effects in ROI **210**. Transducer **500** may additionally comprise any software and/or other hardware for generating, producing and or driving a phased aperture array with one or more electronic time delays.

Transducer **500** can also be configured to provide focused treatment to one or more regions of interest using various frequencies. In order to provide focused treatment, transducer **500** can be configured with one or more variable depth devices to facilitate treatment. For example, transducer **500** may be configured with variable depth devices disclosed in commonly assigned U.S. patent application Ser. No. 10/944,500, entitled “System and Method for Variable Depth Ultrasound”, filed on Sep. 16, 2004, published on Mar. 16, 2006, as U.S. Patent Application Publication No. 20060058664, and incorporated herein by reference. In some embodiments, transducer probe **104** or transducer probe **400** can comprise transducer **500**.

In addition, transducer **500** can also be configured to treat one or more additional ROI **210** through the enabling of sub-harmonics or pulse-echo imaging, as disclosed in commonly assigned U.S. patent application Ser. No. 10/944,499, entitled “Method and System for Ultrasound Treatment with a Multi-directional Transducer”, filed on Sep. 16, 2004, published on Mar. 16, 2006 as U.S. Patent Application Publication No. 20060058707, and incorporated herein by reference.

Moreover, any variety of mechanical lenses or variable focus lenses, e.g. liquid-filled lenses, may also be used to focus and/or defocus the sound field. For example, with reference to exemplary embodiments depicted in FIGS. **6A** and **6B**, transducer **600** may also be configured with an electronic focusing array **604** in combination with one or more transduction elements **606** to facilitate increased flexibility in treating ROI **210**. Array **604** may be configured in a manner similar to transducer **502**. That is, array **604** can be configured as an array of electronic apertures that may be operated by a variety of phases via variable electronic time delays, for example, $T_1, T_2 \dots T_j$. By the term “operated,” the electronic apertures of array **604** may be manipulated, driven, used, and/or configured to produce and/or deliver energy in a manner corresponding to the phase variation caused by the electronic time delay. For example, these phase variations can be used to deliver defocused beams, planar beams, and/or focused beams, each of which may be used in combination to achieve different physiological effects in ROI **210**.

Transduction elements **606** may be configured to be concave, convex, and/or planar. For example, in an exemplary embodiment depicted in FIG. **6A**, transduction elements **606** are configured to be concave in order to provide focused energy for treatment of ROI **210**. Additional embodiments of transducer **600** are disclosed in U.S. patent applications and U.S. patents that have been incorporated by reference herein.

In another exemplary embodiment, depicted in FIG. 6B, transduction elements **606** can be configured to be substantially flat in order to provide substantially uniform energy to ROI **210**. While FIGS. 6A and 6B depict exemplary embodiments with transduction elements **604** configured as concave and substantially flat, respectively, transduction elements **604** can be configured to be concave, convex, and/or substantially flat. In addition, transduction elements **604** can be configured to be any combination of concave, convex, and/or substantially flat structures. For example, a first transduction element can be configured to be concave, while a second transduction element can be configured to be substantially flat. In some embodiments, transducer probe **104** or transducer probe **400** can comprise transducer **600**.

To further illustrate the various structures for transducer **404**, with reference to FIG. 7, ultrasound therapy transducer **700** can be configured for a single focus, an array of foci, a locus of foci, a line focus, and/or diffraction patterns. Transducer **700** can also comprise single elements, multiple elements, annular arrays, one-, two-, or three-dimensional arrays, broadband transducers, and/or combinations thereof, with or without lenses, acoustic components, and mechanical and/or electronic focusing. Transducers configured as spherically focused single elements **702**, annular arrays **704**, annular arrays with damped regions **706**, line focused single elements **708**, 1-D linear arrays **710**, 1-D curvilinear arrays in concave or convex form, with or without elevation focusing, 2-D arrays, and 3-D spatial arrangements of transducers may be used to perform therapy and/or imaging and acoustic monitoring functions. For any transducer configuration, for example but not limited to including those employed in transducer probe **104** or transducer probe **400**, focusing and/or defocusing may be in one plane or two planes via mechanical focus **720**, convex lens **722**, concave lens **724**, compound or multiple lenses **726**, planar form **728**, or stepped form, such as illustrated in FIG. 10F. Any transducer or combination of transducers may be utilized for treatment. For example, an annular transducer may be used with an outer portion dedicated to therapy and the inner disk dedicated to broadband imaging wherein such imaging transducer and therapy transducer have different acoustic lenses and design, such as illustrated in FIGS. 10C-10F, as described below.

With reference to FIGS. 8A and 8B, transducer **404** can be configured as single-element arrays, wherein a single-element **802**, e.g., a transduction element of various structures and materials, can be configured with a plurality of masks **804**, such masks comprising ceramic, metal or any other material or structure for masking or altering energy distribution from element **802**, creating an array of energy distributions **808**. Masks **804** can be coupled directly to element **802** or separated by a standoff **806**, such as any suitably solid or liquid material.

In accordance with another exemplary embodiment, transducer probe **104** or transducer probe **400** may be suitably diced in two dimensions to form a two-dimensional array. For example, with reference to FIG. 9, an exemplary two-dimensional array **900** can be suitably diced into a plurality of two-dimensional portions **902**. Two-dimensional portions **902** can be suitably configured to focus on the treatment region at a certain depth, and thus provide respective slices **904**, **907** of the treatment region. As a result, the two-dimensional array **900** can provide a two-dimensional slicing of image planes of a treatment region, thus providing two-dimensional treatment.

In accordance with another exemplary embodiment, transducer probe **400** may be suitably configured to provide

three-dimensional treatment. For example, to provide three-dimensional treatment of ROI **210**, with reference again to FIG. 3, a three-dimensional system can comprise transducer probe **104** or transducer probe **400** configured with an adaptive algorithm, such as, for example, one utilizing three-dimensional graphic software, contained in a control system, such as for example control system **300**. The adaptive algorithm is suitably configured to receive two-dimensional imaging, temperature and/or treatment information relating to ROI **210**, process the received information, and then provide corresponding three-dimensional imaging, temperature and/or treatment information.

In accordance with an exemplary embodiment, with reference again to FIG. 9, an exemplary three-dimensional system can comprise a two-dimensional array **900** configured with an adaptive algorithm to suitably receive **904** slices from different image planes of the treatment region, process the received information, and then provide volumetric information **906**, e.g., three-dimensional imaging, temperature and/or treatment information. Moreover, after processing the received information with the adaptive algorithm, the two-dimensional array **900** may suitably provide therapeutic heating to the volumetric region **906** as desired.

Alternatively, rather than utilizing an adaptive algorithm, such as three-dimensional software, to provide three-dimensional imaging and/or temperature information, an exemplary three-dimensional system can comprise a single transducer **404** configured within a probe arrangement to operate from various rotational and/or translational positions relative to a target region.

An exemplary transducer **404** can also be configured as an annular array to provide planar, focused and/or defocused acoustical energy. For example, with reference to FIGS. 10A and 10B, in accordance with an exemplary embodiment, an annular array **1000** can comprise a plurality of rings **1012**, **1014**, **1016** to N. Rings **1012**, **1014**, **1016** to N can be mechanically and electrically isolated into a set of individual elements, and can create planar, focused, or defocused waves. For example, such waves can be centered on-axis, such as by methods of adjusting corresponding transmit and/or receive delays, $T_1, T_2, T_3, \dots, T_N$. An electronic focus can be suitably moved along various depth positions, and can enable variable strength or beam tightness, while an electronic defocus can have varying amounts of defocusing. In accordance with an exemplary embodiment, a lens and/or convex or concave shaped annular array **1000** can also be provided to aid focusing or defocusing such that at any time differential delays can be reduced. Movement of annular array **1000** in one, two or three-dimensions, or along any path, such as through use of probes and/or any conventional robotic arm mechanisms, may be implemented to scan and/or treat a volume or any corresponding space within ROI **210**.

Transducer **404** can also be configured in other annular or non-array configurations for imaging/therapy functions. For example, with reference to FIGS. 10C-10F, a transducer can comprise an imaging element **1012** configured with therapy element(s) **1014**. Elements **1012** and **1014** can comprise a single-transduction element, e.g., a combined imaging/transducer element, or separate elements, can be electrically isolated **1022** within the same transduction element or between separate imaging and therapy elements, and/or can comprise standoff **1024** or other matching layers, or any combination thereof. For example, with particular reference to FIG. 10F, a transducer can comprise an imaging element **1012** having a surface **1028** configured for focusing, defocusing or planar energy distribution, with therapy elements

1014 including a stepped-configuration lens configured for focusing, defocusing, or planar energy distribution.

Various shaped treatment lesions can be produced using the various acoustic lenses and designs in FIGS. 10A-10F. For example, mushroom-shaped lesions may be produced from a spherically-focused source, and/or planar lesions from a flat source. That is, as the application of ablative ultrasound energy continues, this causes thermal expansion to generate a growing lesion. Concave planar sources and arrays can produce a "V-shaped" or ellipsoidal lesion. Electronic arrays, such as a linear array, can produce defocused, planar, or focused acoustic beams that may be employed to form a wide variety of additional lesion shapes at various depths. An array may be employed alone or in conjunction with one or more planar or focused transducers. Such transducers and arrays in combination produce a very wide range of acoustic fields and their associated benefits. A fixed focus and/or variable focus lens or lenses may be used to further increase treatment flexibility. A convex-shaped lens, with acoustic velocity less than that of superficial tissue, may be utilized, such as a liquid-filled lens, gel-filled or solid gel lens, rubber or composite lens, with adequate power handling capacity; or a concave-shaped, low profile, lens may be utilized and composed of any material or composite with velocity greater than that of tissue. While the structure of transducer source and configuration can facilitate a particular shaped lesion as suggested above, such structures are not limited to those particular shapes as the other spatial parameters, as well as the temporal parameters, can facilitate additional shapes within any transducer structure and source.

In accordance with an exemplary embodiment, with additional reference to FIG. 11, acoustic coupling and cooling 1140 can be provided to acoustically couple energy and imaging signals from transducer probe 1104 to and from ROI 210, to provide thermal control at the probe to ROI 210 interface 1110, and to remove potential waste heat from the transducer probe at region 1144. Temperature monitoring can be provided at the coupling interface via thermal sensor 1146 to provide a mechanism of temperature measurement 1148 and control via control system 1106 and thermal control system 1142. Thermal control may consist of passive cooling such as via heat sinks or natural conduction and convection or via active cooling such as with peltier thermoelectric coolers, refrigerants, or fluid-based systems comprised of pump, fluid reservoir, bubble detection, flow sensor, flow channels/tubing 1144 and thermal control 1142. In some embodiments, transducer probe 1104 can be equivalent to transducer probe 104 or transducer probe 400.

In accordance with another exemplary embodiment, with reference to FIG. 12, an exemplary treatment system 200 can be configured with and/or combined with various auxiliary systems to provide additional functions. For example, an exemplary treatment system 1200 for treating ROI 210 can comprise a control system 1206, a probe 1204, and a display 1208. In some embodiments, probe 1204 can be equivalent to transducer probe 104 or transducer probe 400 or transducer probe 1104. Treatment system 1200 further comprises an auxiliary imaging modality 1274 and/or auxiliary monitoring modality 1272 may be based upon at least one of photography and other visual optical methods, magnetic resonance imaging (MRI), computed tomography (CT), optical coherence tomography (OCT), electromagnetic, microwave, or radio frequency (RF) methods, positron emission tomography (PET), infrared, ultrasound, acoustic, or any other suitable method of visualization, localization, or monitoring of cellulite within ROI 210, including imaging/

monitoring enhancements. Such imaging/monitoring enhancement for ultrasound imaging via probe 1204 and control system 1206 could comprise M-mode, persistence, filtering, color, Doppler, and harmonic imaging among others; furthermore an ultrasound treatment system 1270, as a primary source of treatment, may be combined with a secondary source of treatment 1276, including radio frequency (RF), intense pulsed light (IPL), laser, infrared laser, microwave, or any other suitable energy source.

An ultrasound treatment system as described herein, as a primary source of treatment, may be combined with a secondary source of treatment configured to deliver secondary treatment energy. Secondary treatment energy includes, but is not limited to, radio frequency (RF) energy, microwave energy, infrared light, visible light, ultraviolet light, and any other suitable electromagnetic energy. Secondary treatment energy may be coherent (as in a laser), incoherent, scattered, pulsed, refracted, focused, defocused, and/or delivered in any other form suitable for achieving a bio-effect.

In an exemplary embodiment, ultrasound treatment is combined with blue light treatment. As used herein, "blue light" means electromagnetic energy having a wavelength from about 400 nanometers to about 440 nanometers. Blue light is applied to the skin. Blue light may be applied as a pretreatment before therapeutic ultrasound energy is applied. Blue light may also be applied concurrently with therapeutic ultrasound energy. Furthermore, blue light may be applied before, during, or after therapeutic ultrasound treatment, or during any combination thereof.

In accordance with an exemplary embodiment, blue light is applied to ROI 210 for a period between 5 seconds and 20 minutes. Blue light may be applied to ROI 210 for any suitable amount of time in order to achieve a desired bio-effect.

In another exemplary embodiment, ultrasound treatment is combined with red light treatment. As used herein, "red light" means electromagnetic energy having a wavelength from about 600 nanometers to about 1350 nanometers. Red light is applied to ROI 210. Red light may be applied as a pretreatment before therapeutic ultrasound energy is applied. Red light may also be applied concurrently with therapeutic ultrasound energy. Furthermore, red light may be applied before, during, or after therapeutic ultrasound treatment, or during any combination thereof.

In accordance with an exemplary embodiment, red light is applied to the skin for a period between 5 seconds and 20 minutes. Red light may be applied to the skin for any suitable amount of time in order to achieve a desired bio-effect.

In accordance with an exemplary embodiment, secondary treatment energy can be delivered by the probe which contains an ultrasound energy source. In other exemplary embodiments, secondary treatment energy is delivered by a source external to the probe. Secondary treatment energy may be generated by a light emitting diode (LED), a laser, an incandescent bulb, a fluorescent tube, an antenna, an intense pulsed light source, or any other suitable electromagnetic energy generation mechanism.

In one exemplary embodiment, energy is delivered in relatively small ablative areas in order to minimize and/or prevent scar tissue from forming. That is, each ablative area of treatment can range from approximately 100 microns to 55 mm in diameter. In another exemplary embodiment, ultrasound energy is used in a "lawnmower" type fashion to evenly ablate a treatment region to provide a substantially

planar surface of lobuli. This “lawnmower”-type ablation in turn, helps to achieve a substantially smooth surface of the epidermis.

With reference to FIG. 13, another method of non-invasive treatment of cellulite is illustrated according to various other embodiments of the present invention. The cross-sectional diagram illustrates the layers of tissue below skin surface 1304 which is not to scale and is used for illustration purposes. Dermis layer 1302 includes skin surface 1304 and both the epidermis and dermis portions of the skin. Below the dermis layer 1302 is fat lobuli 1307. Fat lobuli 1307 causes protrusions in skin surface 1304, which gives skin surface 1304 a dimpled appearance 1311 or cellulite. Below fat lobuli 1307 is fascia layer 1315, subcutaneous fat layer 1317 and then muscle layer 1319.

In various aspects, probe 202 is coupled to skin surface 1304 and emits ultrasound energy to create conformal lesion 209 at specific depth 1305. Conformal lesion 209 ablates a portion of fat lobuli 1307. Probe movement 1303 along skin surface 1304 allows for ablation of a plurality of fat lobuli 1307 at specific depth 1305. This may be described as a lawnmower type ablation or a haircut of fat lobuli 1307. Probe movement 1303 leaves behind smoothed skin 1309. The treatment may need to be repeated in order to achieve a desired degree of smoothed skin 1309. This method may be combined with any other method steps described herein such as for example applying a physical treatment or applying a secondary energy source.

In accordance with an exemplary embodiment of the present invention, a method of non-invasive treatment of cellulite includes targeting ROI 210 below skin surface 1304, which contains fat lobuli 1307, and delivering ultrasound energy at specified depth 1305 below skin surface 1304. The method further includes moving a source of the energy along skin surface 1304 and ablating a portion of fat lobuli 1307 at specified depth 1305 below skin surface 1304.

Specified depth 1305 is generally in the range of about 1 mm to about 35 mm below skin surface 1304. The method can include applying a physical treatment as described herein. The method can smooth skin surface 1304 and may reduce the appearance of cellulite on skin surface 1304. The method can further include any of the additional method steps discussed herein.

With reference to FIG. 14, a method of non-invasive treatment of cellulite is illustrated according to another exemplary embodiment of the present invention. The cross-sectional diagram illustrates the layers of tissue below skin surface 1304 which is not to scale and is used for illustration purposes. Dermis layer 1302 includes skin surface 1304 and both the epidermis and dermis portions of the skin. Below dermis layer 1302 is fat lobuli 1307. Fat lobuli 1307 causes protrusions in skin surface 1304, which gives skin surface 1304 a dimpled appearance 1311 or cellulite. Below fat lobuli 1307 is fascia layer 1315, subcutaneous fat layer 1317 and then muscle layer 1319.

In the exemplary embodiment illustrated in FIG. 14A, probe 202 is coupled to skin surface 1304 and emits ultrasound energy to create conformal lesion 209 in the surface of fat lobuli 1307 to create opening 1321. A material that is housed in the punctured fat lobuli 1317 flows out of opening 1321. This material can be a fluid, a lipid, a lymphatic substance, fat, tissue, bodily materials, or any other material and mixtures thereof. The material can be any tissue, fluid, or the like that is typically housed in fat lobuli 1317. Moving to FIG. 14B, reduced fat lobuli 1325 has shriveled due to the loss of the material. The shrinking of reduced fat lobuli 1325 can cause smoothed skin 1309 above reduced fat lobuli 1325

which has been drained of the material, thereby reducing the appearance of cellulite on skin surface 1304.

In accordance with another exemplary embodiment, a method of non-invasive treatment of cellulite includes targeting ROI 210 below skin surface 1304, which contains fat lobuli 1307 and delivering ultrasound energy to ROI 210. The ultrasound energy generates conformal lesion 209 with the ultrasound energy on a surface of fat lobuli 1307. The lesion creates opening 1321 in the surface of fat lobuli 1307, which allows the draining of a fluid out of fat lobuli 1307 and through opening 1321.

The method can further include heating ROI 210 to a temperature in a range from about 43° C. to about 49° C., which can stimulate apoptosis of at least one fat cell in fat lobuli 1307. Still further the method can include applying a physical treatment to skin surface 1304 and such physical treatment can include mesotherapy, iontophoresis, pressotherapy, pneumatic massage, lymphatic drainage, electrolypophoresis, roller massage, low frequency ultrasound, vacuum suction, laser energy, and/or an application of RF energy. The physical treatment can be before, after, or concurrent with the delivery of the ultrasound energy. The method can include the use of a second energy, which can be used before, after, or concurrent with the delivery of the ultrasound energy. The method can reduce the appearance of cellulite on skin surface 1304.

With additional reference to FIG. 15, a block diagram illustrates an exemplary method for non-invasive treatment of cellulite according to various embodiments of the present invention. For example, method 1500 is a non-invasive treatment of cellulite. In step 1502, fat lobuli 1307 is targeted. Imaging the fat lobuli in a step 1503 may be useful in the targeting of fat lobuli 1307 but is optional or otherwise not required.

Targeting step 1502 is followed by energy delivery step 1504 which delivers ultrasound energy to form a conformal lesion 209 in the target which can be for example fat lobuli 1307. The ultrasound energy can be in the range from about 750 kHz to about 20 MHz and may be more useful in the range from about 2 MHz to about 10 MHz. The power of the ultrasound energy may be in a range from about 1 W to about 50 W and may be more useful in the range from about 2 W to about 20 W. The duration of the ultrasound energy may be in the range from about 10 milliseconds to about 20 minutes, or even more if desired. Energy delivery step 1504 may include applying secondary energy step 1505, which is optional. Applying a secondary energy step 1505 may be useful in heating the tissue around the target to an elevated temperature prior to or during delivery of ultrasound energy to the targeted region, and can comprise a variety of energy sources including those discussed previously herein.

Energy delivery step 1504 is followed by creating an opening in the target step 1506, which provides an opening 1321. In this step 1506, conformal lesion 209 creates opening 1321 in the target. Upon creating an opening in the target, step 1506 is followed by a release of contents step 1508, in which at least a portion of the contents of fat lobuli 1307 are released through opening 1321, e.g., by draining. An application of secondary energy step 1505 may be applied after the creation of opening 1321 but is optional. Such application of secondary energy step 1505 may be useful in smoothing skin surface 1304 and/or in facilitating movement of at least a portion of the contents of fat lobuli 1307 to facilitate their release. The contents of fat lobuli 1307 can be a fluid, a lipid, a lymphatic substance, fat, tissue, bodily materials, or any other material and mixtures thereof. An application of physical treatment step 1507, such

as, for example, by applying physical pressure or force to facilitate movement, may be useful in facilitating the releasing of at least a portion of the contents of fat lobuli 1307 through opening 1321, but this step 1507 is optional. An optional imaging step 1509 can be added for reviewing if the treatment was successful. If the treatment complete decision 1511 is yes, then the result is the final step 1510 wherein the skin is smoothed. If the treatment complete decision 1511 is no, then move to step 1504 for further treatment of the target until the treatment is successful within the treatment area, resulting in the smoothing of skin step 1510 which reduces the appearance of cellulite on skin surface 1304.

In accordance with another exemplary embodiment, a method of non-invasive treatment of cellulite includes identifying fat lobuli 1307 and creating a sharp focal of ultrasound energy onto fat lobuli 1307. The focal of energy pierces fat lobuli 1307 to create opening 1321, which then allows the flowing of a material out of fat lobuli 1307 through opening 1321. The method can further include any of the additional method steps discussed herein.

Now referring to FIG. 16, a method of non-invasive treatment for a reduction of fat is illustrated according to another exemplary embodiment of the present invention. In various embodiments, this method can be used as a non-invasive treatment of cellulite. The cross-sectional diagram illustrates the layers of tissue below skin surface 1304 which is not to scale and is used for illustration purposes. Dermis layer 1302 includes skin surface 1304 and both the epidermis and dermis portions of the skin. Below dermis layer 1302 is fat lobuli 1307. Fat lobuli 1307 causes protrusions in skin surface 1304, which gives skin surface 1304 a dimpled appearance 1311 or cellulite. Below fat lobuli 1307 is fascia layer 1315, subcutaneous fat layer 1317 and then muscle layer 1319.

In an exemplary embodiment, as illustrated in FIG. 16A, probe 202 is coupled to skin surface 1304 and emits ultrasound energy into adipose target area 1331. Adipose target area 1331 can include a portion of fat lobuli 1307. Adipose target area 1331 can include ROI 210. Fat lobuli 1307 can contain a plurality of adipose cells and a portion of the plurality of adipose cells can be located in adipose target area 1331. Adipose target area 1331 can include a plurality of other adipose cells 1329 that may be amongst fat lobuli 1307.

Probe 202 is targeted to deliver energy in adipose target area 1331. Adipose target area 1331 can be from about 1 mm to about 100 mm or greater below skin surface 1304. Height 1333 of adipose target area 1331 can be from about 1 mm to about 10 mm or greater. Probe 202 delivers energy to create at least one conformational lesion 209 in adipose target area 1331. Delivered energy raises a temperature of at least a portion of adipose cells in fat lobuli 1307 and/or other adipose cells 1329 located in adipose target area 1331 to a range from about 43° C. to about 49° C., which stimulates apoptosis of fat cells, which can include at least a portion of other adipose cells in fat lobuli 1307 and/or other adipose cells 1329.

As illustrated in FIG. 16B, over a period of time, the portion of the plurality of adipose cells fat lobuli 1307 that were located in adipose target zone 1331 begin cell apoptosis. As these adipose cells die, fat lobuli 1307 shrinks. This cell apoptosis of the adipose cells reduces the amount of fat in an area on a patient. The effect of the reduction in size of fat lobuli 1307 by the adipose cell apoptosis can create smoothed skin 1309. In addition, other adipose cells 1329 that were located in adipose target area 1331 can begin cell apoptosis. As these other adipose cells 1329 die, skin surface

1304 can relax, which can contribute to creating smoothed skin 1309. Probe 202 can be moved along skin surface 1304 to enlarge the treatment of adipose target area 1331 of a patient's body.

An exemplary method, such as that illustrated by FIG. 16, can include applying a physical treatment to skin surface 1304, and such physical treatment can include mesotherapy, iontophoresis, pressotherapy, pneumatic massage, lymphatic drainage, electrolipophoresis, roller massage, low frequency ultrasound, vacuum suction, laser energy, and application of RF energy. The physical treatment can be before, after, or concurrent with the delivery of the energy. The method can include the use of a second energy, which can be used before, after, or concurrent with the delivery of the energy.

With reference to FIG. 17, a block diagram illustrates a method 1600 of fat reduction according to an exemplary embodiment. For example, the method 1600 begins with step 1602 which is the targeting of a group of fat cells in adipose target area 1331. This targeting step 1602 may include the movement of probe 202 to include an enlarged target area. In targeting step 1602 a depth below skin surface 1304 that is appropriate for adipose target area 1331 is determined. Generally, a depth of greater than 1 mm but less than 100 mm is appropriate and this can vary from patient to patient depending on location on the body and level of patient's body fat.

Targeting step 1602 is followed by energy delivery step 1603 which is the delivering of ultrasound energy to the target fat cells. The ultrasound energy can be in the range from about 750 kHz to about 20 MHz and may be more useful in the range from about 2 MHz to about 10 MHz. The power of the ultrasound energy may be in a range from about 1 W to about 50 W and may be more useful in the range from about 2 W to about 20 W. The duration of the ultrasound energy may be in the range from about 10 milliseconds to about 20 minutes, or more if desired.

Energy delivery step 1603 is followed by raising temperature step 1604, which is the raising of the fat cell temperature from about 43.5° C. to about 49° C. Different combinations of parameters outlined in energy delivery step 1603 can be useful to raise the fat cell temperature to the desired range in step 1604. Raising temperature step 1604 creates or facilitates the stimulating apoptosis step 1605 which is the stimulating cell apoptosis of the fat cells in adipose target area 1331. If the fat cells are held in the desired temperature range for a sufficient amount of time, cell apoptosis will occur. Stimulating apoptosis step 1605 is followed by step 1606 which is the allowing of the targeted fat cells and/or targeted portions thereof to die. Upon allowing target portions to die in step 1606 results, a reduction of the total number of fat cells in adipose target area 1331 is achieved 1607. This reduction of the total number of fat cells can result in lowering the circumference of a patient's body, for example the circumference of thighs, buttocks, hips, waist, and the like. In addition, this reduction of adipose target area 1331 can reduce an appearance of cellulite on skin surface 1304. Alternatively, or simultaneously, method 1600 can target fat cells in the subcutaneous fat layers to provide similar results.

Now with reference to FIGS. 18A and 18B, a method of non-invasive treatment for a reduction of fat is illustrated according to various exemplary embodiments of the present invention. In various embodiments, this method can be used as a non-invasive treatment of subcutaneous fat layer 1317. The cross-sectional diagram illustrates the layers of tissue below skin surface 1304 which is not to scale and is used for

illustration purposes. The dermis layer **1302** includes skin surface **1304** and both the epidermis and dermis portions of the skin. Below dermis layer **1302** is fat lobuli **1307**. Fat lobuli **1307** causes protrusions in skin surface **1304**, which gives skin surface **1304** a dimpled appearance **1311** or cellulite. Below fat lobuli **1307** is fascia layer **1315**, subcutaneous fat layer **1317** and then muscle layer **1319**. Subcutaneous fat layer **1317** can have a selected depth **1337**.

In an exemplary embodiment as illustrated in FIG. **18A**, probe **202** is coupled to skin surface **1304** and emits ultrasound energy into adipose target area **1331**. Adipose target area **1331** can include a portion of subcutaneous fat layer **1317**. Subcutaneous fat layer **1317** can contain a plurality of adipose cells and a portion of the plurality of adipose cells can be located in adipose target area **1331**.

Probe **202** is targeted to deliver energy in adipose target area **1331**. Adipose target area **1331** can be from about 1 mm to about 100 mm or greater below the surface of the skin **1304**. Height **1333** of adipose target area **1331** can be from about 1 mm to about 10 mm or greater. Probe **202** delivers energy to create at least one conformal lesion **209** which is located in adipose target area **1331**. Delivered energy raises a temperature of at least a portion of the adipose cells located in adipose target area **1331** in to a range from about 43° C. to about 49° C., which stimulates apoptosis of the fat cells, which can include at least a portion of adipose cells in fat lobuli **1307** and/or other adipose cells **1399**.

Over a period of time, the portion of the plurality of adipose cells in subcutaneous fat layer **1317** that were located in adipose target area **1331** begin cell apoptosis. As these adipose cells die, subcutaneous fat layer **1317** shrinks. This cell apoptosis of the adipose cells reduces the amount of fat in an area on a patient. As illustrated in FIG. **18B**, the effect of the adipose cell apoptosis in subcutaneous fat layer **1317** can create smoothed skin **1309**.

In addition, the effect of the adipose cell apoptosis in subcutaneous fat layer **1317** can create a reduction **1335** in the total volume of tissue in the treatment area. In accordance with the method, probe **202** can be moved along skin surface **1304** to enlarge the treatment of adipose target area **1331** of a patient's body. For example, this reduction **1335** can cause a decrease in the circumference of a patient's thighs, buttocks, hips, waist, and the like. As the adipose cell apoptosis in subcutaneous fat layer **1317** continues, skin surface **1304** can relax and can contribute to creating smoothed skin **1309**. Subcutaneous fat layer **1317** can have a reduced depth **1339** after cell apoptosis. Reduced cell depth **1339** generally results from thickness of depth **1337** less the thickness **1333** of adipose target area **1331**, i.e., the portion shrunk from cell apoptosis.

Various exemplary methods as illustrated in FIG. **18** provide a method of non-invasively stimulating apoptosis of a fat cell located in subcutaneous fat layer **1317**. The method includes targeting at least one fat cell in subcutaneous fat layer **1317** below skin surface **1304** and delivering energy to the fat cell. The delivered energy raises a temperature of the fat cell into a range from about 43° C. to about 49° C., which stimulates apoptosis of the fat cell.

The method can further include imaging of a fat cell or fat lobuli **1307**. Still further, the method can include generating conformal lesion **209** into at least one fat cell, which can create opening **1321** in a fat cell or fat lobuli **1307** and allow the moving of a material out of a fat cell or fat lobuli **1307** and through opening **1321**. This material can be a fluid, a lipid, a lymphatic substance, fat, tissue, bodily materials, or any other material and mixtures thereof. The ultrasound energy can be in the range from about 750 kHz to about 20

MHz and may be more useful in the range from about 2 MHz to about 10 MHz. The power of the ultrasound energy may be in a range from about 1 W to about 50 W and may be more useful in the range from about 2 W to about 20 W. The duration of the ultrasound energy may be in the range from about 10 milliseconds to about 20 minutes. Still further, the method can include applying a physical treatment to skin surface **1304** and such physical treatment can include mesotherapy, Iontophoresis, pressotherapy, pneumatic massage, lymphatic drainage, electrolipophoresis, roller massage, low frequency ultrasound, vacuum suction, laser energy, and application of RF energy. The physical treatment can be before, after, or concurrent with the delivery of the energy. The method can include the use of a second energy, which can be used before, after, or concurrent with the delivery of the energy. The method can reduce the number of fat cells in subcutaneous fat layer **1317**.

In addition, various other exemplary embodiments of the present invention can include a method that combines fat reduction and cellulite reduction. The method includes targeting ROI **210** below skin surface **1304**, which contains fat lobuli **1307** and delivering ultrasound energy to ROI **210**. The ultrasound energy generates conformal lesion **209** with said ultrasound energy on a surface of fat lobuli **1307**. Conformal lesion **209** creates opening **1321** in the surface of fat lobuli **1307**, which allows the draining of a fluid out of fat lobuli **1307** and through opening **1321**. Additionally, the method can include targeting at least one fat cell in subcutaneous fat layer **1321** below skin surface **1304** and delivering a second energy to the fat cell. The delivered second energy raises a temperature of the fat cell into a range from about 43° C. to about 49° C., which stimulates apoptosis of the fat cell.

The method can further include a physical treatment as described herein, as well as the use of a secondary energy source. The method can both reduce the number of fat cells in subcutaneous fat layer **1317** and reduce the appearance of cellulite on skin surface **1304**. The method can be effective in the physically breaking fat cell clusters and stretching fibrous bonds of cellulite.

In accordance with another exemplary embodiment of the present invention, a method of non-invasive treatment of cellulite includes identifying fat lobuli **1307** and creating a sharp focal of ultrasound energy onto fat lobuli **1307**. The focal of energy pierces fat lobuli **1307** to create opening **1321**, which then allows the flowing of a material out of fat lobuli **1307** through opening **1321**. The method can further include any of the additional method steps discussed herein.

In various embodiments, the energy is delivered at a treatment depth from about 0 mm to about 50 mm or about 1 mm to about 35 mm. The ultrasound energy can be in the range from about 750 kHz to about 20 MHz and may be more useful in the range from about 2 MHz to about 10 MHz. The power of the ultrasound energy may be in a range from about 1 W to about 50 W and may be more useful in the range from about 2 W to about 20 W. The duration of the ultrasound energy may be in the range from about 10 milliseconds to about 20 minutes.

Once the treatment protocol, for any of the methods of treatment discussed herein or variations thereof, has been implemented, ROI **210** may have one or more reactions to the treatment. For example, in some embodiments, the tissue responds by enhancement of lymphatic drainage, evacuation of fat decay products, creation of a thermal injury and/or coagulation of proximal protrusions of fat lobuli **1307**.

In an exemplary embodiment, energy such as ultrasound energy is emitted from a treatment system at multiple depths

to target numerous areas within a specific ROI 210. Multiple layers of tissue within ROI 210 are treated from the surface down to the deepest point of ultrasound energy penetration and no intervening layers of tissue are spared in one embodiment of the present invention. In addition to ultrasound energy, other energy forms such as laser energy, radio frequency energy, and other energies can be used and fall within the scope of the present invention. Further, blue light at a wavelength of approximately 400 to 450 nm can be used to pre-treat ROI 210 before the application of ultrasound energy or blue light of this wavelength can be used with ultrasound to increase the efficacy of treatment. In another embodiment, visible light in the range of 600 to 1350 nm can be used with the ultrasound during treatment.

Upon treatment, the steps outlined herein can be repeated one or more additional times to provide for optimal treatment results. Different ablation sizes and shapes of conformational lesion 209 may affect the recovery time and time between treatments. For example, in general, the larger the surface area of conformational lesion 209, the faster the recovery. The series of treatments can also enable the user to tailor additional treatments in response to a patient's responses to the ultrasound treatment.

The methods of treatment described herein can employ various shaped conformational lesions 209 and can be produced using the various acoustic lenses and designs described herein. For example, mushroom shaped lesions may be produced from a spherically-focused source, and/or planar lesions from a flat source. That is, as the application of ablative ultrasound energy continues, this causes thermal expansion to generate a growing lesion. Concave planar sources and arrays can produce a "V-shaped" or ellipsoidal lesion. Electronic arrays, such as a linear array, can produce defocused, planar, or focused acoustic beams that may be employed to form a wide variety of additional lesion shapes at various depths. Other lesion shapes that may be useful with the treatment methods described herein include the lesion shapes and patterns described in the U.S. patents and U.S. patent application that are incorporated by reference herein.

The citation of references herein does not constitute admission that those references are prior art or have relevance to the patentability of the invention disclosed herein. All references cited in the Description section of the specification are hereby incorporated by reference in their entirety for all purposes. In the event that one or more of the incorporated references differs from or contradicts this application, including, but not limited to, defined terms, term usage, described techniques, or the like, this application controls.

The present invention has been described above with reference to various exemplary embodiments. However, those skilled in the art will recognize that changes and modifications may be made to the exemplary embodiments without departing from the scope of the present invention. For example, the various operational steps, as well as the components for carrying out the operational steps, may be implemented in alternate ways depending upon the particular application or in consideration of any number of cost functions associated with the operation of the system, e.g., various steps may be deleted, modified, or combined with other steps. These and other changes or modifications are intended to be included within the scope of the present invention, as set forth in the following claims.

What is claimed is:

1. An ultrasound treatment probe for treatment of fat, the probe comprising:

a motion mechanism and a piezoelectric ultrasound therapy element

wherein the piezoelectric ultrasound therapy element is spherically focused or cylindrically focused,

wherein the piezoelectric ultrasound therapy element delivers ultrasound energy at a frequency of between 2 MHz to 10 MHz,

wherein the piezoelectric ultrasound therapy element is configured for delivery of energy at a temperature sufficient to coagulate at least a portion of a plurality of fat lobuli at a depth under a skin surface,

wherein the piezoelectric ultrasound therapy element is connected to the motion mechanism,

wherein the piezoelectric ultrasound therapy element is configured for acoustic coupling to the skin surface,

wherein the motion mechanism is configured for connection to an encoder to determine movement and position of the piezoelectric ultrasound therapy element,

wherein the motion mechanism moves the piezoelectric ultrasound therapy element to form a plurality of thermal foci at the depth for coagulating the at least a portion of the plurality of fat lobuli.

2. The probe of claim 1, wherein the probe is disposable, wherein the ultrasound energy increases a speed at which fat metabolizes according to Arrhenius Law: $Y=A \cdot e^{-B/T}$, where Y is a yield of metabolic reaction, A and B are constants, and T is a temperature in degrees Kelvin.

3. The probe of claim 1, further comprising a control system, a user control switch to activate the piezoelectric ultrasound therapy element, and a monitoring system,

wherein the control system comprises a processor,

wherein the monitoring system is configured to monitor a treatment parameter, wherein the treatment parameter measured comprises a temperature of a tissue below the skin surface.

4. The probe of claim 1,

wherein the probe is disposable,

wherein the motion mechanism is configured to form a plurality of thermal lesions along a line at the depth in a region of interest by moving the piezoelectric ultrasound therapy element.

5. The probe of claim 1, further comprising further comprising a storage system comprising probe identification and probe usage history, and an acoustic coupler between the ultrasound probe and the skin surface,

wherein the motion mechanism is configured for any one of the group consisting of linear, rotational, and variable movement of the piezoelectric ultrasound therapy element within the ultrasound probe.

6. The probe of claim 1,

wherein the encoder is configured for monitoring a position of the piezoelectric ultrasound therapy element on the motion mechanism inside the ultrasound probe,

wherein the piezoelectric ultrasound therapy element is configured to deliver the energy at the depth below the skin surface.

7. The probe of claim 1, further comprising a monitoring system,

wherein the monitoring system is configured to monitor a treatment parameter, wherein the treatment parameter comprises a temperature of a tissue below the skin surface,

wherein the ultrasound probe further comprises a temperature monitoring sensor,

wherein the piezoelectric ultrasound therapy element is configured to increase the temperature of the tissue to a range of 43 to 49 degrees Celsius,

27

wherein the ultrasound energy is delivered with a treatment power of between 1 W and 50 W, wherein the probe is reusable.

8. The probe of claim 1, further comprising a piezoelectric ultrasound imaging element and an image display.

9. An ultrasound treatment probe for treatment of fat, the probe comprising a housing, a therapy component, and a motion mechanism,

wherein the therapy component comprises a cylindrically focused piezoelectric ultrasound therapy element,

wherein the cylindrically focused piezoelectric ultrasound therapy element delivers ultrasound energy at a frequency of between 750 kHz to 20 MHz,

wherein the cylindrically focused piezoelectric ultrasound therapy element is configured for delivery of ultrasound energy at a temperature sufficient to coagulate one or more fat lobuli at one or more depths under a skin surface,

wherein a portion of the housing is configured for acoustic coupling to the skin surface; and

wherein the cylindrically focused piezoelectric ultrasound therapy element is connected to the motion mechanism, wherein the motion mechanism is configured for connection to an encoder,

wherein the motion mechanism moves the cylindrically focused piezoelectric ultrasound therapy element to coagulate the fat lobuli.

10. The probe of claim 9, further comprising a storage system comprising probe identification and probe usage history,

wherein the housing further comprises a piezoelectric ultrasound imaging element,

wherein the piezoelectric ultrasound imaging element is configured for imaging a region of interest under the skin surface, wherein the region of interest comprises the fat lobuli.

11. The probe of claim 9, wherein the probe is disposable,

wherein the cylindrically focused piezoelectric ultrasound therapy element delivers ultrasound energy at a frequency of between 2 MHz to 10 MHz, and

wherein the ultrasound energy increases a speed at which fat metabolizes according to Arrhenius Law: $Y=A \cdot e^{-B/T}$, where Y is a yield of metabolic reaction, A and B are constants, and T is a temperature in degrees Kelvin.

12. The probe of claim 9, wherein the cylindrically focused piezoelectric ultrasound therapy element is configured to deliver the ultrasound energy up to 5.5 cm below the skin surface,

wherein the ultrasound energy is delivered with a treatment power of between 1 W and 50 W.

13. An ultrasound treatment probe for treatment of fat, the probe comprising:

a motion mechanism and a piezoelectric ultrasound therapy element,

wherein the ultrasound probe is configured for acoustic coupling to a skin surface;

28

wherein the piezoelectric ultrasound therapy element is configured for delivery of ultrasound energy to a region of interest under the skin surface,

wherein the piezoelectric ultrasound therapy element is configured to coagulate at least a portion of a plurality of fat lobuli at a depth under the skin surface,

wherein the piezoelectric ultrasound therapy element is connected to the motion mechanism,

wherein the motion mechanism is configured to operate with an encoder,

wherein the motion mechanism moves the piezoelectric ultrasound therapy element to form a plurality of thermal lesions at the portion of the plurality of fat lobuli at the depth for reducing an appearance of fat.

14. The probe of claim 13,

wherein the piezoelectric ultrasound therapy element delivers the ultrasound energy at a frequency of between 2 MHz to 10 MHz,

wherein the piezoelectric ultrasound therapy element is configured to deliver the ultrasound energy at the depth below the skin surface.

15. The probe of claim 13, wherein the ultrasound energy is configured for heating the plurality of fat lobuli to a temperature in a range of 43 to 49 degrees Celsius.

16. The probe of claim 13, further comprising a monitoring system,

wherein the monitoring system is configured to monitor a treatment parameter, wherein the treatment parameter measured comprises a temperature of the tissue below the skin surface,

wherein the ultrasound probe further comprises a temperature monitoring sensor,

wherein the ultrasound probe is configured for connection to a control system, wherein the control system comprises a spatial control and a temporal control, the spatial control and the temporal control controlling the delivery of energy to heat the plurality of fat lobuli at the depth under the skin surface.

17. The probe of claim 13, further comprising a storage system comprising probe identification and probe usage history, and a user switch to activate the piezoelectric ultrasound therapy element and wherein the ultrasound energy increases a speed at which fat metabolizes according to Arrhenius Law: $Y=A \cdot e^{-B/T}$, where Y is a yield of metabolic reaction, A and B are constants, and T is a temperature in degrees Kelvin.

18. The probe of claim 13, further comprising a storage system comprising probe identification and probe usage history, wherein the probe is reusable and is configured to connect to an input device and a power supply.

19. The probe of claim 13, wherein the piezoelectric therapy element is spherically focused.

20. The probe of claim 13, wherein the piezoelectric therapy element is cylindrically focused.

* * * * *

专利名称(译)	基于能量的脂肪减少		
公开(公告)号	US10010721	公开(公告)日	2018-07-03
申请号	US15/829175	申请日	2017-12-01
申请(专利权)人(译)	引导治疗系统公司		
当前申请(专利权)人(译)	引导治疗系统, L.L.C.		
[标]发明人	SLAYTON MICHAEL H BARTHE PETER G		
发明人	SLAYTON, MICHAEL H. BARTHE, PETER G.		
IPC分类号	A61N7/00 B06B1/06 A61B8/08 A61B5/00 G01S15/89 G01S7/52 A61B90/00 A61N7/02		
CPC分类号	A61N7/00 A61B5/4869 A61B8/0858 B06B1/0607 G01S15/899 G01S7/5208 A61N2007/027 A61B2090/378 A61N2007/0008 A61N2007/0052 A61B8/14 A61B8/429 A61B8/4455 A61B8/4483 A61B8/483 A61N7/02 B06B1/0622 G01S15/8906 G01S15/8993 H05K999/99		
优先权	15/380267 2017-07-25 US 15/041804 2017-01-03 US 14/192520 2014-12-30 US 61/140725 2008-12-24 US 60/616753 2004-10-06 US		
其他公开文献	US20180104515A1		
外部链接	Espacenet		

摘要(译)

用于非侵入性脂肪减少的方法可包括将目标区域靶向皮肤表面下方，所述皮肤表面含有脂肪并将超声能量传递到感兴趣的区域。超声能量在脂肪细胞上产生具有所述超声能量的热损伤。病变可在脂肪细胞的表面形成开口，这允许流体从脂肪细胞排出并通过开口。另外，通过向脂肪细胞施加超声能量以将温度升高到43度和49度之间，可以实现细胞凋亡，从而导致脂肪减少。

