



US010292657B2

(12) **United States Patent**
Abdul-Hafiz et al.

(10) **Patent No.:** **US 10,292,657 B2**
(45) **Date of Patent:** **May 21, 2019**

(54) **EAR SENSOR**

(71) Applicant: **MASIMO CORPORATION**, Irvine, CA (US)

(72) Inventors: **Yassir Abdul-Hafiz**, Irvine, CA (US); **Ammar Al-Ali**, San Juan Capistrano, CA (US); **Kevin Forrest**, Rancho Santa Margarita, CA (US); **Eugene Mason**, La Habra Heights, CA (US); **John Schmidt**, Lake Forest, CA (US); **Virginia Thanh Ta**, Santa Ana, CA (US)

(73) Assignee: **MASIMO CORPORATION**, Irvine, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 63 days.

(21) Appl. No.: **15/417,640**

(22) Filed: **Jan. 27, 2017**

(65) **Prior Publication Data**
US 2017/0258403 A1 Sep. 14, 2017

Related U.S. Application Data
(63) Continuation of application No. 14/218,328, filed on Mar. 18, 2014, now abandoned, which is a (Continued)

(51) **Int. Cl.**
A61B 5/1455 (2006.01)
A61B 5/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 5/6867** (2013.01); **A61B 5/0205** (2013.01); **A61B 5/0261** (2013.01);
(Continued)

(58) **Field of Classification Search**

None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,960,128 A 10/1990 Gordon et al.
4,964,408 A 10/1990 Hink et al.
(Continued)

FOREIGN PATENT DOCUMENTS

GB 191409166 7/1914
WO WO 2007/100959 9/2007
WO WO 2011/102846 8/2011

OTHER PUBLICATIONS


US 9,579,050 B2, 02/2017, Al-Ali (withdrawn)
(Continued)

Primary Examiner — Eric F Winakur
Assistant Examiner — Marjan Fardanesh
(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear LLP

(57) **ABSTRACT**

An ear sensor provides a sensor body having a base, legs extending from the base and an optical housing disposed at ends of the legs opposite the base. An optical assembly is disposed in the housing. The sensor body is flexed so as to position the housing over a concha site. The sensor body is unflexed so as to attach the housing to the concha site and position the optical assembly to illuminate the concha site. The optical assembly is configured to transmit optical radiation into concha site tissue and receive the optical radiation after attenuation by pulsatile blood flow within the tissue.

17 Claims, 31 Drawing Sheets



Related U.S. Application Data					
	continuation of application No. 13/975,008, filed on Aug. 23, 2013, now Pat. No. 9,259,185, which is a continuation of application No. 12/658,872, filed on Feb. 16, 2010, now Pat. No. 8,588,880.			6,011,986 A	1/2000 Diab et al.
				6,027,452 A	2/2000 Flaherty et al.
				6,036,642 A	3/2000 Diab et al.
				6,045,509 A	4/2000 Caro et al.
				6,067,462 A	5/2000 Diab et al.
				6,078,829 A	6/2000 Uchida
				6,080,110 A	6/2000 Thorgersen
				6,081,735 A	6/2000 Diab et al.
				6,088,607 A	7/2000 Diab et al.
(60)	Provisional application No. 61/152,964, filed on Feb. 16, 2009.			6,110,522 A	8/2000 Lepper, Jr. et al.
				6,124,597 A	9/2000 Shehada
(51)	Int. Cl.			6,128,521 A	10/2000 Marro et al.
	<i>A61B 5/0205</i> (2006.01)			6,129,675 A	10/2000 Jay
	<i>A61B 5/024</i> (2006.01)			6,144,868 A	11/2000 Parker
	<i>A61B 5/026</i> (2006.01)			6,151,516 A	11/2000 Kiani-Azarbayjany et al.
				6,152,754 A	11/2000 Gerhardt et al.
(52)	U.S. Cl.			6,157,850 A	12/2000 Diab et al.
	CPC <i>A61B 5/02427</i> (2013.01); <i>A61B 5/14552</i> (2013.01); <i>A61B 5/6815</i> (2013.01); <i>A61B 5/6816</i> (2013.01); <i>A61B 5/6817</i> (2013.01); <i>A61B 5/6838</i> (2013.01)			6,165,005 A	12/2000 Mills et al.
				6,184,521 B1	2/2001 Coffin, IV et al.
				6,206,830 B1	3/2001 Diab et al.
				6,229,856 B1	5/2001 Diab et al.
				6,232,609 B1	5/2001 Snyder et al.
				6,236,872 B1	5/2001 Diab et al.
				6,241,683 B1	6/2001 Macklem et al.
(56)	References Cited			6,253,097 B1	6/2001 Aronow et al.
	U.S. PATENT DOCUMENTS			6,256,523 B1	7/2001 Diab et al.
				6,263,222 B1	7/2001 Diab et al.
				6,278,522 B1	8/2001 Lepper, Jr. et al.
	5,041,187 A	8/1991 Hink et al.		6,280,213 B1	8/2001 Tobler et al.
	5,069,213 A	12/1991 Polczynski		6,285,896 B1	9/2001 Tobler et al.
	5,163,438 A	11/1992 Gordon et al.		6,301,493 B1	10/2001 Marro et al.
	5,319,355 A	6/1994 Russek		6,317,627 B1	11/2001 Ennen et al.
	5,337,744 A	8/1994 Branigan		6,321,100 B1	11/2001 Parker
	5,341,805 A	8/1994 Stavridi et al.		6,325,761 B1	12/2001 Jay
	D353,195 S	12/1994 Savage et al.		6,334,065 B1	12/2001 Al-Ali et al.
	D353,196 S	12/1994 Savage et al.		6,343,224 B1	1/2002 Parker
	5,377,676 A	1/1995 Vari et al.		6,349,228 B1	2/2002 Kiani et al.
	D359,546 S	6/1995 Savage et al.		6,360,114 B1	3/2002 Diab et al.
	5,431,170 A	7/1995 Mathews		6,368,283 B1	4/2002 Xu et al.
	D361,840 S	8/1995 Savage et al.		6,371,921 B1	4/2002 Caro et al.
	D362,063 S	9/1995 Savage et al.		6,377,829 B1	4/2002 Al-Ali
	5,452,717 A	9/1995 Branigan et al.		6,388,240 B2	5/2002 Schulz et al.
	D363,120 S	10/1995 Savage et al.		6,397,091 B2	5/2002 Diab et al.
	5,456,252 A	10/1995 Vari et al.		6,430,437 B1	8/2002 Marro
	5,479,934 A	1/1996 Imran		6,430,525 B1	8/2002 Weber et al.
	5,482,036 A	1/1996 Diab et al.		6,463,311 B1	10/2002 Diab
	5,490,505 A	2/1996 Diab et al.		6,470,199 B1	10/2002 Kopotic et al.
	5,494,043 A	2/1996 O'Sullivan et al.		6,501,975 B2	12/2002 Diab et al.
	5,533,511 A	7/1996 Kaspari et al.		6,505,059 B1	1/2003 Kollias et al.
	5,534,851 A	7/1996 Russek		6,515,273 B2	2/2003 Al-Ali
	5,561,275 A	10/1996 Savage et al.		6,519,487 B1	2/2003 Parker
	5,562,002 A	10/1996 Lalin		6,525,386 B1	2/2003 Mills et al.
	5,590,649 A	1/1997 Caro et al.		6,526,300 B1	2/2003 Kiani et al.
	5,602,924 A	2/1997 Durand et al.		6,541,756 B2	4/2003 Schulz et al.
	5,632,272 A	5/1997 Diab et al.		6,542,764 B1	4/2003 Al-Ali et al.
	5,638,816 A	6/1997 Kiani-Azarbayjany et al.		6,556,852 B1	4/2003 Schulze et al.
	5,638,818 A	6/1997 Diab et al.		6,580,086 B1	6/2003 Schulz et al.
	5,645,440 A	7/1997 Tobler et al.		6,584,336 B1	6/2003 Ali et al.
	5,685,299 A	11/1997 Diab et al.		6,595,316 B2	7/2003 Cybulski et al.
	D393,830 S	4/1998 Tobler et al.		6,597,932 B2	7/2003 Tian et al.
	5,743,262 A	4/1998 Lepper, Jr. et al.		6,597,933 B2	7/2003 Kiani et al.
	5,758,644 A	6/1998 Diab et al.		6,606,511 B1	8/2003 Ali et al.
	5,760,910 A	6/1998 Lepper, Jr. et al.		6,632,181 B2	10/2003 Flaherty et al.
	5,769,785 A	6/1998 Diab et al.		6,639,668 B1	10/2003 Trepagnier
	5,782,757 A	7/1998 Diab et al.		6,640,116 B2	10/2003 Diab
	5,785,659 A	7/1998 Caro et al.		6,643,530 B2	11/2003 Diab et al.
	5,791,347 A	8/1998 Flaherty et al.		6,650,917 B2	11/2003 Diab et al.
	5,810,734 A	9/1998 Caro et al.		6,654,624 B2	11/2003 Diab et al.
	5,823,950 A	10/1998 Diab et al.		6,658,276 B2	12/2003 Kiani et al.
	5,830,131 A	11/1998 Caro et al.		6,661,161 B1	12/2003 Lanzo et al.
	5,833,618 A	11/1998 Caro et al.		6,671,531 B2	12/2003 Al-Ali et al.
	5,860,919 A	1/1999 Kiani-Azarbayjany et al.		6,678,543 B2	1/2004 Diab et al.
	5,890,929 A	4/1999 Mills et al.		6,684,090 B2	1/2004 Ali et al.
	5,904,654 A	5/1999 Wohltmann et al.		6,684,091 B2	1/2004 Parker
	5,919,134 A	7/1999 Diab		6,697,656 B1	2/2004 Al-Ali
	5,934,925 A	8/1999 Tobler et al.		6,697,657 B1	2/2004 Shehada et al.
	5,940,182 A	8/1999 Lepper, Jr. et al.		6,697,658 B2	2/2004 Al-Ali
	5,995,855 A	11/1999 Kiani et al.		RE38,476 E	3/2004 Diab et al.
	5,997,343 A	12/1999 Mills et al.		6,699,194 B1	3/2004 Diab et al.
	6,002,952 A	12/1999 Diab et al.			

(56)

References Cited

U.S. PATENT DOCUMENTS

6,714,804	B2	3/2004	Al-Ali et al.	7,343,186	B2	3/2008	Lamego et al.
RE38,492	E	4/2004	Diab et al.	D566,282	S	4/2008	Al-Ali et al.
6,721,582	B2	4/2004	Trepagnier et al.	7,355,512	B1	4/2008	Al-Ali
6,721,585	B1	4/2004	Parker	7,356,365	B2	4/2008	Schurman
6,725,075	B2	4/2004	Al-Ali	7,371,981	B2	5/2008	Abdul-Hafiz
6,728,560	B2	4/2004	Kollias et al.	7,373,193	B2	5/2008	Al-Ali et al.
6,735,459	B2	5/2004	Parker	7,373,194	B2	5/2008	Weber et al.
6,745,060	B2	6/2004	Diab et al.	7,376,453	B1	5/2008	Diab et al.
6,760,607	B2	7/2004	Al-Ali	7,377,794	B2	5/2008	Al-Ali et al.
6,770,028	B1	8/2004	Ali et al.	7,377,899	B2	5/2008	Weber et al.
6,771,994	B2	8/2004	Kiani et al.	7,383,070	B2	6/2008	Diab et al.
6,792,300	B1	9/2004	Diab et al.	7,412,272	B2	8/2008	Medina
6,813,511	B2	11/2004	Diab et al.	7,415,297	B2	8/2008	Al-Ali et al.
6,816,741	B2	11/2004	Diab	7,428,432	B2	9/2008	Ali et al.
6,822,564	B2	11/2004	Al-Ali	7,438,683	B2	10/2008	Al-Ali et al.
6,826,419	B2	11/2004	Diab et al.	7,440,787	B2	10/2008	Diab
6,830,711	B2	12/2004	Mills et al.	7,454,240	B2	11/2008	Diab et al.
6,850,787	B2	2/2005	Weber et al.	7,467,002	B2	12/2008	Weber et al.
6,850,788	B2	2/2005	Al-Ali	7,469,157	B2	12/2008	Diab et al.
6,852,083	B2	2/2005	Caro et al.	7,471,969	B2	12/2008	Diab et al.
6,861,639	B2	3/2005	Al-Ali	7,471,971	B2	12/2008	Diab et al.
6,898,452	B2	5/2005	Al-Ali et al.	7,483,729	B2	1/2009	Al-Ali et al.
6,920,345	B2	7/2005	Al-Ali et al.	7,483,730	B2	1/2009	Diab et al.
6,931,268	B1	8/2005	Kiani-Azarbayjany et al.	7,489,958	B2	2/2009	Diab et al.
6,934,570	B2	8/2005	Kiani et al.	7,496,391	B2	2/2009	Diab et al.
6,939,305	B2	9/2005	Flaherty et al.	7,496,393	B2	2/2009	Diab et al.
6,943,348	B1	9/2005	Coffin, IV	D587,657	S	3/2009	Al-Ali et al.
6,950,687	B2	9/2005	Al-Ali	7,499,741	B2	3/2009	Diab et al.
6,961,598	B2	11/2005	Diab	7,499,835	B2	3/2009	Weber et al.
6,970,792	B1	11/2005	Diab	7,500,950	B2	3/2009	Al-Ali et al.
6,979,812	B2	12/2005	Al-Ali	7,509,154	B2	3/2009	Diab et al.
6,985,764	B2	1/2006	Mason et al.	7,509,494	B2	3/2009	Al-Ali
6,993,371	B2	1/2006	Kiani et al.	7,510,849	B2	3/2009	Schurman et al.
6,996,427	B2	2/2006	Ali et al.	7,526,328	B2	4/2009	Diab et al.
6,999,904	B2	2/2006	Weber et al.	7,530,942	B1	5/2009	Diab
7,003,338	B2	2/2006	Weber et al.	7,530,949	B2	5/2009	Al-Ali et al.
7,003,339	B2	2/2006	Diab et al.	7,530,955	B2	5/2009	Diab et al.
7,015,451	B2	3/2006	Dalke et al.	7,563,110	B2	7/2009	Al-Ali et al.
7,024,233	B2	4/2006	Ali et al.	7,596,398	B2	9/2009	Al-Ali et al.
7,027,849	B2	4/2006	Al-Ali	7,618,375	B2	11/2009	Flaherty
7,030,749	B2	4/2006	Al-Ali	D606,659	S	12/2009	Kiani et al.
7,039,449	B2	5/2006	Al-Ali	7,647,083	B2	1/2010	Al-Ali et al.
7,041,060	B2	5/2006	Flaherty et al.	D609,193	S	2/2010	Al-Ali et al.
7,044,918	B2	5/2006	Diab	D614,305	S	4/2010	Al-Ali et al.
7,067,893	B2	6/2006	Mills et al.	RE41,317	E	5/2010	Parker
7,096,052	B2	8/2006	Mason et al.	7,729,733	B2	6/2010	Al-Ali et al.
7,096,054	B2	8/2006	Abdul-Hafiz et al.	7,734,320	B2	6/2010	Al-Ali
7,132,641	B2	11/2006	Schulz et al.	7,761,127	B2	7/2010	Al-Ali et al.
7,142,901	B2	11/2006	Kiani et al.	7,761,128	B2	7/2010	Al-Ali et al.
7,149,561	B2	12/2006	Diab	7,764,982	B2	7/2010	Dalke et al.
7,186,966	B2	3/2007	Al-Ali	D621,516	S	8/2010	Kiani et al.
7,190,261	B2	3/2007	Al-Ali	7,791,155	B2	9/2010	Diab
7,215,984	B2	5/2007	Diab	7,801,581	B2	9/2010	Diab
7,215,986	B2	5/2007	Diab	7,822,452	B2	10/2010	Schurman et al.
7,221,971	B2	5/2007	Diab	RE41,912	E	11/2010	Parker
7,225,006	B2	5/2007	Al-Ali et al.	7,844,313	B2	11/2010	Kiani et al.
7,225,007	B2	5/2007	Al-Ali	7,844,314	B2	11/2010	Al-Ali
RE39,672	E	6/2007	Shehada et al.	7,844,315	B2	11/2010	Al-Ali
7,239,905	B2	7/2007	Kiani-Azarbayjany et al.	7,865,222	B2	1/2011	Weber et al.
7,245,953	B1	7/2007	Parker	7,873,497	B2	1/2011	Weber et al.
7,254,429	B2	8/2007	Schurman et al.	7,880,606	B2	2/2011	Al-Ali
7,254,431	B2	8/2007	Al-Ali	7,880,626	B2	2/2011	Al-Ali et al.
7,254,433	B2	8/2007	Diab et al.	7,891,355	B2	2/2011	Al-Ali et al.
7,254,434	B2	8/2007	Schulz et al.	7,894,868	B2	2/2011	Al-Ali et al.
7,272,425	B2	9/2007	Al-Ali	7,899,507	B2	3/2011	Al-Ali et al.
7,274,955	B2	9/2007	Kiani et al.	7,899,518	B2	3/2011	Trepagnier et al.
D554,263	S	10/2007	Al-Ali	7,904,132	B2	3/2011	Weber et al.
7,280,858	B2	10/2007	Al-Ali et al.	7,909,772	B2	3/2011	Popov et al.
7,289,835	B2	10/2007	Mansfield et al.	7,910,875	B2	3/2011	Al-Ali
7,292,883	B2	11/2007	De Felice et al.	7,919,713	B2	4/2011	Al-Ali et al.
7,295,866	B2	11/2007	Al-Ali	7,937,128	B2	5/2011	Al-Ali
7,328,053	B1	2/2008	Diab et al.	7,937,129	B2	5/2011	Mason et al.
7,332,784	B2	2/2008	Mills et al.	7,937,130	B2	5/2011	Diab et al.
7,340,287	B2	3/2008	Mason et al.	7,941,199	B2	5/2011	Kiani
7,341,559	B2	3/2008	Schulz et al.	7,951,086	B2	5/2011	Flaherty et al.
				7,957,780	B2	6/2011	Lamego et al.
				7,962,188	B2	6/2011	Kiani et al.
				7,962,190	B1	6/2011	Diab et al.
				7,976,472	B2	7/2011	Kiani

(56)

References Cited

U.S. PATENT DOCUMENTS

7,988,637 B2	8/2011	Diab	8,471,713 B2	6/2013	Poeze et al.
7,990,382 B2	8/2011	Kiani	8,473,020 B2	6/2013	Kiani et al.
7,991,446 B2	8/2011	Al-Ali et al.	8,483,787 B2	7/2013	Al-Ali et al.
8,000,761 B2	8/2011	Al-Ali	8,489,364 B2	7/2013	Weber et al.
8,008,088 B2	8/2011	Bellott et al.	8,498,684 B2	7/2013	Weber et al.
RE42,753 E	9/2011	Kiani-Azarbayjany et al.	8,504,128 B2	8/2013	Blank et al.
8,019,400 B2	9/2011	Diab et al.	8,509,867 B2	8/2013	Workman et al.
8,028,701 B2	10/2011	Al-Ali et al.	8,515,509 B2	8/2013	Bruinsma et al.
8,029,765 B2	10/2011	Bellott et al.	8,523,781 B2	9/2013	Al-Ali
8,036,727 B2	10/2011	Schurman et al.	8,529,301 B2	9/2013	Al-Ali et al.
8,036,728 B2	10/2011	Diab et al.	8,532,727 B2	9/2013	Ali et al.
8,046,040 B2	10/2011	Ali et al.	8,532,728 B2	9/2013	Diab et al.
8,046,041 B2	10/2011	Diab et al.	D692,145 S	10/2013	Al-Ali et al.
8,046,042 B2	10/2011	Diab et al.	8,547,209 B2	10/2013	Kiani et al.
8,048,040 B2	11/2011	Kiani	8,548,548 B2	10/2013	Al-Ali
8,050,728 B2	11/2011	Al-Ali et al.	8,548,549 B2	10/2013	Schurman et al.
RE43,169 E	2/2012	Parker	8,548,550 B2	10/2013	Al-Ali et al.
8,118,620 B2	2/2012	Al-Ali et al.	8,560,032 B2	10/2013	Al-Ali et al.
8,126,528 B2	2/2012	Diab et al.	8,560,034 B1	10/2013	Diab et al.
8,128,572 B2	3/2012	Diab et al.	8,570,167 B2	10/2013	Al-Ali
8,130,105 B2	3/2012	Al-Ali et al.	8,570,503 B2	10/2013	Vo et al.
8,145,287 B2	3/2012	Diab et al.	8,571,617 B2	10/2013	Reichgott et al.
8,150,487 B2	4/2012	Diab et al.	8,571,618 B1	10/2013	Lamego et al.
8,175,672 B2	5/2012	Parker	8,571,619 B2	10/2013	Al-Ali et al.
8,180,420 B2	5/2012	Diab et al.	8,577,431 B2	11/2013	Lamego et al.
8,182,443 B1	5/2012	Kiani	8,581,732 B2	11/2013	Al-Ali et al.
8,185,180 B2	5/2012	Diab et al.	8,584,345 B2	11/2013	Al-Ali et al.
8,190,223 B2	5/2012	Al-Ali et al.	8,588,880 B2	11/2013	Abdul-Hafiz et al.
8,190,227 B2	5/2012	Diab et al.	8,600,467 B2	12/2013	Al-Ali et al.
8,203,438 B2	6/2012	Kiani et al.	8,606,342 B2	12/2013	Diab
8,203,704 B2	6/2012	Merritt et al.	8,626,255 B2	1/2014	Al-Ali et al.
8,204,566 B2	6/2012	Schurman et al.	8,630,691 B2	1/2014	Lamego et al.
8,219,172 B2	7/2012	Schurman et al.	8,634,889 B2	1/2014	Al-Ali et al.
8,224,411 B2	7/2012	Al-Ali et al.	8,641,631 B2	2/2014	Sierra et al.
8,228,181 B2	7/2012	Al-Ali	8,652,060 B2	2/2014	Al-Ali
8,229,532 B2	7/2012	Davis	8,663,107 B2	3/2014	Kiani
8,229,533 B2	7/2012	Diab et al.	8,666,468 B1	3/2014	Al-Ali
8,233,955 B2	7/2012	Al-Ali et al.	8,667,967 B2	3/2014	Al-Ali et al.
8,244,325 B2	8/2012	Al-Ali et al.	8,670,811 B2	3/2014	O'Reilly
8,255,026 B1	8/2012	Al-Ali	8,670,814 B2	3/2014	Diab et al.
8,255,027 B2	8/2012	Al-Ali et al.	8,676,286 B2	3/2014	Weber et al.
8,255,028 B2	8/2012	Al-Ali et al.	8,682,407 B2	3/2014	Al-Ali
8,260,577 B2	9/2012	Weber et al.	RE44,823 E	4/2014	Parker
8,265,723 B1	9/2012	McHale et al.	RE44,875 E	4/2014	Kiani et al.
8,274,360 B2	9/2012	Sampath et al.	8,690,799 B2	4/2014	Telfort et al.
8,301,217 B2	10/2012	Al-Ali et al.	8,700,112 B2	4/2014	Kiani
8,306,596 B2	11/2012	Schurman et al.	8,702,627 B2	4/2014	Telfort et al.
8,310,336 B2	11/2012	Muhsin et al.	8,706,179 B2	4/2014	Parker
8,315,683 B2	11/2012	Al-Ali et al.	8,712,494 B1	4/2014	MacNeish, III et al.
RE43,860 E	12/2012	Parker	8,715,206 B2	5/2014	Telfort et al.
8,337,403 B2	12/2012	Al-Ali et al.	8,718,735 B2	5/2014	Lamego et al.
8,346,330 B2	1/2013	Lamego	8,718,737 B2	5/2014	Diab et al.
8,353,842 B2	1/2013	Al-Ali et al.	8,718,738 B2	5/2014	Blank et al.
8,355,766 B2	1/2013	MacNeish, III et al.	8,720,249 B2	5/2014	Al-Ali
8,359,080 B2	1/2013	Diab et al.	8,721,541 B2	5/2014	Al-Ali et al.
8,364,223 B2	1/2013	Al-Ali et al.	8,721,542 B2	5/2014	Al-Ali et al.
8,364,226 B2	1/2013	Diab et al.	8,723,677 B1	5/2014	Kiani
8,374,665 B2	2/2013	Lamego	8,740,792 B1	6/2014	Kiani et al.
8,385,995 B2	2/2013	Al-Ali et al.	8,754,776 B2	6/2014	Poeze et al.
8,385,996 B2	2/2013	Smith et al.	8,755,535 B2	6/2014	Telfort et al.
8,388,353 B2	3/2013	Kiani et al.	8,755,856 B2	6/2014	Diab et al.
8,399,822 B2	3/2013	Al-Ali	8,755,872 B1	6/2014	Marinow
8,401,602 B2	3/2013	Kiani	8,761,850 B2	6/2014	Lamego
8,405,608 B2	3/2013	Al-Ali et al.	8,764,671 B2	7/2014	Kiani
8,414,499 B2	4/2013	Al-Ali et al.	8,768,423 B2	7/2014	Shakespeare et al.
8,418,524 B2	4/2013	Al-Ali	8,771,204 B2	7/2014	Telfort et al.
8,423,106 B2	4/2013	Lamego et al.	8,777,634 B2	7/2014	Kiani et al.
8,428,967 B2	4/2013	Olsen et al.	8,781,543 B2	7/2014	Diab et al.
8,430,817 B1	4/2013	Al-Ali et al.	8,781,544 B2	7/2014	Al-Ali et al.
8,437,825 B2	5/2013	Dalvi et al.	8,781,549 B2	7/2014	Al-Ali et al.
8,455,290 B2	6/2013	Siskavich	8,788,003 B2	7/2014	Schurman et al.
8,457,703 B2	6/2013	Al-Ali	8,790,268 B2	7/2014	Al-Ali
8,457,707 B2	6/2013	Kiani	8,801,613 B2	8/2014	Al-Ali et al.
8,463,349 B2	6/2013	Diab et al.	8,821,397 B2	9/2014	Al-Ali et al.
8,466,286 B2	6/2013	Bellot et al.	8,821,415 B2	9/2014	Al-Ali et al.
			8,830,449 B1	9/2014	Lamego et al.
			8,831,700 B2	9/2014	Schurman et al.
			8,840,549 B2	9/2014	Al-Ali et al.
			8,847,740 B2	9/2014	Kiani et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,849,365 B2	9/2014	Smith et al.	9,333,316 B2	5/2016	Kiani
8,852,094 B2	10/2014	Al-Ali et al.	9,339,220 B2	5/2016	Lamego et al.
8,852,994 B2	10/2014	Wojtczuk et al.	9,341,565 B2	5/2016	Lamego et al.
8,868,147 B2	10/2014	Stippick et al.	9,351,673 B2	5/2016	Diab et al.
8,868,150 B2	10/2014	Al-Ali et al.	9,351,675 B2	5/2016	Al-Ali et al.
8,870,792 B2	10/2014	Al-Ali et al.	9,364,181 B2	6/2016	Kiani et al.
8,886,271 B2	11/2014	Kiani et al.	9,368,671 B2	6/2016	Wojtczuk et al.
8,888,539 B2	11/2014	Al-Ali et al.	9,370,325 B2	6/2016	Al-Ali et al.
8,888,708 B2	11/2014	Diab et al.	9,370,326 B2	6/2016	McHale et al.
8,892,180 B2	11/2014	Weber et al.	9,370,335 B2	6/2016	Al-Ali et al.
8,897,847 B2	11/2014	Al-Ali	9,375,185 B2	6/2016	Ali et al.
8,909,310 B2	12/2014	Lamego et al.	9,386,953 B2	7/2016	Al-Ali
8,911,377 B2	12/2014	Al-Ali	9,386,961 B2	7/2016	Al-Ali et al.
8,912,909 B2	12/2014	Al-Ali et al.	9,392,945 B2	7/2016	Al-Ali et al.
8,920,317 B2	12/2014	Al-Ali et al.	9,397,448 B2	7/2016	Al-Ali et al.
8,921,699 B2	12/2014	Al-Ali et al.	9,408,542 B1	8/2016	Kinast et al.
8,922,382 B2	12/2014	Al-Ali et al.	9,436,645 B2	9/2016	Al-Ali et al.
8,929,964 B2	1/2015	Al-Ali et al.	9,445,759 B1	9/2016	Lamego et al.
8,942,777 B2	1/2015	Diab et al.	9,466,919 B2	10/2016	Kiani et al.
8,948,834 B2	2/2015	Diab et al.	9,474,474 B2	10/2016	Lamego et al.
8,948,835 B2	2/2015	Diab	9,480,422 B2	11/2016	Al-Ali
8,965,471 B2	2/2015	Lamego	9,480,435 B2	11/2016	Olsen
8,983,564 B2	3/2015	Al-Ali	9,492,110 B2	11/2016	Al-Ali et al.
8,989,831 B2	3/2015	Al-Ali et al.	9,510,779 B2	12/2016	Poeze et al.
8,996,085 B2	3/2015	Kiani et al.	9,517,024 B2	12/2016	Kiani et al.
8,998,809 B2	4/2015	Kiani	9,532,722 B2	1/2017	Lamego et al.
9,028,429 B2	5/2015	Telfort et al.	9,538,949 B2	1/2017	Al-Ali et al.
9,037,207 B2	5/2015	Al-Ali et al.	9,538,980 B2	1/2017	Telfort et al.
9,060,721 B2	6/2015	Reichgott et al.	9,549,696 B2	1/2017	Lamego et al.
9,066,666 B2	6/2015	Kiani	9,554,737 B2	1/2017	Schurman et al.
9,066,680 B1	6/2015	Al-Ali et al.	9,560,996 B2	2/2017	Kiani
9,072,474 B2	7/2015	Al-Ali et al.	9,560,998 B2	2/2017	Al-Ali et al.
9,078,560 B2	7/2015	Schurman et al.	9,566,019 B2	2/2017	Al-Ali et al.
9,084,569 B2	7/2015	Weber et al.	9,579,039 B2	2/2017	Jansen et al.
9,095,316 B2	8/2015	Welch et al.	9,591,975 B2	3/2017	Dalvi et al.
9,106,038 B2	8/2015	Telfort et al.	9,622,693 B2	4/2017	Diab
9,107,625 B2	8/2015	Telfort et al.	2005/0033131 A1	2/2005	Chen et al.
9,107,626 B2	8/2015	Al-Ali et al.	2005/0209516 A1	9/2005	Fraden
9,113,831 B2	8/2015	Al-Ali	2007/0032715 A1	2/2007	Eghbal et al.
9,113,832 B2	8/2015	Al-Ali	2007/0078315 A1	4/2007	Kling et al.
9,119,595 B2	9/2015	Lamego	2007/0282478 A1	12/2007	Al-Ali et al.
9,131,881 B2	9/2015	Diab et al.	2009/0010461 A1	1/2009	Klinghult
9,131,882 B2	9/2015	Al-Ali et al.	2009/0247984 A1	10/2009	Lamego et al.
9,131,883 B2	9/2015	Al-Ali	2009/0275813 A1	11/2009	Davis
9,131,917 B2	9/2015	Telfort et al.	2009/0275844 A1	11/2009	Al-Ali
9,138,180 B1	9/2015	Coverston et al.	2010/0004518 A1	1/2010	Vo et al.
9,138,182 B2	9/2015	Al-Ali et al.	2010/0030040 A1	2/2010	Poeze et al.
9,138,192 B2	9/2015	Weber et al.	2011/0082711 A1	4/2011	Poeze et al.
9,142,117 B2	9/2015	Muhsin et al.	2011/0105854 A1	5/2011	Kiani et al.
9,153,112 B1	10/2015	Kiani et al.	2011/0125060 A1	5/2011	Telfort et al.
9,153,121 B2	10/2015	Kiani et al.	2011/0208015 A1	8/2011	Welch et al.
9,161,696 B2	10/2015	Al-Ali et al.	2011/0213212 A1	9/2011	Al-Ali
9,161,713 B2	10/2015	Al-Ali et al.	2011/0230733 A1	9/2011	Al-Ali
9,167,995 B2	10/2015	Lamego et al.	2011/0237969 A1	9/2011	Eckerbom et al.
9,176,141 B2	11/2015	Al-Ali et al.	2011/0288383 A1	11/2011	Diab
9,186,102 B2	11/2015	Bruinsma et al.	2012/0041316 A1	2/2012	Al-Ali et al.
9,192,312 B2	11/2015	Al-Ali	2012/0046557 A1	2/2012	Kiani
9,192,329 B2	11/2015	Al-Ali	2012/0059267 A1	3/2012	Lamego et al.
9,192,351 B1	11/2015	Telfort et al.	2012/0088984 A1	4/2012	Al-Ali et al.
9,195,385 B2	11/2015	Al-Ali et al.	2012/0165629 A1	6/2012	Merritt et al.
9,211,072 B2	12/2015	Kiani	2012/0209082 A1	8/2012	Al-Ali
9,211,095 B1	12/2015	Al-Ali	2012/0209084 A1	8/2012	Olsen et al.
9,218,454 B2	12/2015	Kiani et al.	2012/0283524 A1	11/2012	Kiani et al.
9,226,696 B2	1/2016	Kiani	2012/0296178 A1	11/2012	Lamego et al.
9,241,662 B2	1/2016	Al-Ali et al.	2012/0319816 A1	12/2012	Al-Ali
9,245,668 B1	1/2016	Vo et al.	2013/0023775 A1	1/2013	Lamego et al.
9,259,185 B2	2/2016	Abdul-Hafiz et al.	2013/0041591 A1	2/2013	Lamego
9,267,572 B2	2/2016	Barker et al.	2013/0046204 A1	2/2013	Lamego et al.
9,277,880 B2	3/2016	Poeze et al.	2013/0060147 A1	3/2013	Welch et al.
9,289,167 B2	3/2016	Diab et al.	2013/0096405 A1	4/2013	Garfio
9,295,421 B2	3/2016	Kiani et al.	2013/0096936 A1	4/2013	Sampath et al.
9,307,928 B1	4/2016	Al-Ali et al.	2013/0243021 A1	9/2013	Siskavich
9,323,894 B2	4/2016	Kiani	2013/0253334 A1	9/2013	Al-Ali et al.
D755,392 S	5/2016	Hwang et al.	2013/0267804 A1	10/2013	Al-Ali
9,326,712 B1	5/2016	Kiani	2013/0274572 A1	10/2013	Al-Ali et al.
			2013/0296672 A1	11/2013	O'Neil et al.
			2013/0296713 A1	11/2013	Al-Ali et al.
			2013/0324808 A1	12/2013	Al-Ali et al.
			2013/0331660 A1	12/2013	Al-Ali et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0331670	A1	12/2013	Kiani	2015/0238722	A1	8/2015	Al-Ali
2014/0012100	A1	1/2014	Al-Ali et al.	2015/0245773	A1	9/2015	Lamego et al.
2014/0034353	A1	2/2014	Al-Ali et al.	2015/0245794	A1	9/2015	Al-Ali
2014/0051953	A1	2/2014	Lamego et al.	2015/0257689	A1	9/2015	Al-Ali et al.
2014/0066783	A1	3/2014	Kiani et al.	2015/0272514	A1	10/2015	Kiani et al.
2014/0077956	A1	3/2014	Sampath et al.	2015/0351697	A1	12/2015	Weber et al.
2014/0081100	A1	3/2014	Muhsin et al.	2015/0351704	A1	12/2015	Kiani et al.
2014/0081175	A1	3/2014	Telfort	2015/0359429	A1	12/2015	Al-Ali et al.
2014/0100434	A1	4/2014	Diab et al.	2015/0366472	A1	12/2015	Kiani
2014/0114199	A1	4/2014	Lamego et al.	2015/0366507	A1	12/2015	Blank
2014/0120564	A1	5/2014	Workman et al.	2015/0374298	A1	12/2015	Al-Ali et al.
2014/0121482	A1	5/2014	Merritt et al.	2015/0380875	A1	12/2015	Coverston et al.
2014/0127137	A1	5/2014	Bellott et al.	2016/0000362	A1	1/2016	Diab et al.
2014/0129702	A1	5/2014	Lamego et al.	2016/0007930	A1	1/2016	Weber et al.
2014/0135588	A1	5/2014	Al-Ali et al.	2016/0029932	A1	2/2016	Al-Ali
2014/0142401	A1	5/2014	Al-Ali et al.	2016/0045118	A1	2/2016	Kiani
2014/0163344	A1	6/2014	Al-Ali	2016/0051205	A1	2/2016	Al-Ali et al.
2014/0163402	A1	6/2014	Lamego et al.	2016/0058338	A1	3/2016	Schurman et al.
2014/0166076	A1	6/2014	Kiani et al.	2016/0058347	A1	3/2016	Reichgott et al.
2014/0171763	A1	6/2014	Diab	2016/0066823	A1	3/2016	Kind et al.
2014/0180038	A1	6/2014	Kiani	2016/0066824	A1	3/2016	Al-Ali et al.
2014/0180154	A1	6/2014	Sierra et al.	2016/0066879	A1	3/2016	Telfort et al.
2014/0180160	A1	6/2014	Brown et al.	2016/0072429	A1	3/2016	Kiani et al.
2014/0187885	A1	7/2014	Kreuzer	2016/0081552	A1	3/2016	Wojtczuk et al.
2014/0187973	A1	7/2014	Brown et al.	2016/0095543	A1	4/2016	Telfort et al.
2014/0213864	A1	7/2014	Abdul-Hafiz et al.	2016/0095548	A1	4/2016	Al-Ali et al.
2014/0266790	A1	9/2014	Al-Ali et al.	2016/0103598	A1	4/2016	Al-Ali et al.
2014/0275808	A1	9/2014	Poeze et al.	2016/0113527	A1	4/2016	Al-Ali et al.
2014/0275835	A1	9/2014	Lamego et al.	2016/0143548	A1	5/2016	Al-Ali
2014/0275871	A1	9/2014	Lamego et al.	2016/0166182	A1	6/2016	Al-Ali et al.
2014/0275872	A1	9/2014	Merritt et al.	2016/0166183	A1	6/2016	Poeze et al.
2014/0276115	A1	9/2014	Dalvi et al.	2016/0166188	A1	6/2016	Bruinsma et al.
2014/0288400	A1	9/2014	Diab et al.	2016/0166210	A1	6/2016	Al-Ali
2014/0316217	A1	10/2014	Purdon et al.	2016/0192869	A1	7/2016	Kiani et al.
2014/0316218	A1	10/2014	Purdon et al.	2016/0196388	A1	7/2016	Lamego
2014/0316228	A1	10/2014	Blank et al.	2016/0197436	A1	7/2016	Barker et al.
2014/0323825	A1	10/2014	Al-Ali et al.	2016/0213281	A1	7/2016	Eckerbom et al.
2014/0323897	A1	10/2014	Brown et al.	2016/0228043	A1	8/2016	O'Neil et al.
2014/0323898	A1	10/2014	Purdon et al.	2016/0233632	A1	8/2016	Scruggs et al.
2014/0330092	A1	11/2014	Al-Ali et al.	2016/0234944	A1	8/2016	Schmidt et al.
2014/0330098	A1	11/2014	Merritt et al.	2016/0270735	A1	9/2016	Diab et al.
2014/0330099	A1	11/2014	Al-Ali et al.	2016/0283665	A1	9/2016	Sampath et al.
2014/0336481	A1	11/2014	Shakespeare et al.	2016/0287090	A1	10/2016	Al-Ali et al.
2014/0357966	A1	12/2014	Al-Ali et al.	2016/0287786	A1	10/2016	Kiani
2015/0005600	A1	1/2015	Blank et al.	2016/0296169	A1	10/2016	McHale et al.
2015/0011907	A1	1/2015	Purdon et al.	2016/0310052	A1	10/2016	Al-Ali et al.
2015/0012231	A1	1/2015	Poeze et al.	2016/0314260	A1	10/2016	Kiani
2015/0025406	A1	1/2015	Al-Ali	2016/0324486	A1	11/2016	Al-Ali et al.
2015/0032029	A1	1/2015	Al-Ali et al.	2016/0324488	A1	11/2016	Olsen
2015/0038859	A1	2/2015	Dalvi et al.	2016/0327984	A1	11/2016	Al-Ali et al.
2015/0045637	A1	2/2015	Dalvi	2016/0328528	A1	11/2016	Al-Ali et al.
2015/0051462	A1	2/2015	Olsen	2016/0331332	A1	11/2016	Al-Ali
2015/0080754	A1	3/2015	Purdon et al.	2016/0367173	A1	12/2016	Dalvi et al.
2015/0087936	A1	3/2015	Al-Ali et al.	2017/0007134	A1	1/2017	Al-Ali et al.
2015/0094546	A1	4/2015	Al-Ali	2017/0007190	A1	1/2017	Al-Ali et al.
2015/0097701	A1	4/2015	Al-Ali et al.	2017/0007198	A1	1/2017	Al-Ali et al.
2015/0099950	A1	4/2015	Al-Ali et al.	2017/0014084	A1	1/2017	Al-Ali et al.
2015/0099951	A1	4/2015	Al-Ali et al.	2017/0021099	A1	1/2017	Al-Ali et al.
2015/0099955	A1	4/2015	Al-Ali et al.	2017/0027456	A1	2/2017	Kinast et al.
2015/0101844	A1	4/2015	Al-Ali et al.	2017/0042488	A1	2/2017	Muhsin
2015/0106121	A1	4/2015	Muhsin et al.	2017/0055847	A1	3/2017	Kiani et al.
2015/0112151	A1	4/2015	Muhsin et al.	2017/0055851	A1	3/2017	Al-Ali
2015/0116076	A1	4/2015	Al-Ali et al.	2017/0055882	A1	3/2017	Al-Ali et al.
2015/0126830	A1	5/2015	Schurman et al.	2017/0055887	A1	3/2017	Al-Ali
2015/0133755	A1	5/2015	Smith et al.	2017/0055896	A1	3/2017	Al-Ali et al.
2015/0141781	A1	5/2015	Weber et al.	2017/0079594	A1	3/2017	Telfort et al.
2015/0165312	A1	6/2015	Kiani	2017/0086723	A1	3/2017	Al-Ali et al.
2015/0196237	A1	7/2015	Lamego				
2015/0216459	A1	8/2015	Al-Ali et al.				
2015/0230755	A1	8/2015	Al-Ali et al.				

OTHER PUBLICATIONS

U.S. Appl. No. 14/218,328, Ear Sensor, filed Mar. 18, 2014.
PCT International Search Report; PCT/US2010/033796; dated Oct. 17, 2011; pp. 1-4.




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 4C






FIG. 4D






FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 12D




FIG. 12E




FIG. 12F




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 13D




FIG. 13E




FIG. 13F




FIG. 14A




FIG. 14B




FIG. 15A




FIG. 15B




FIG. 16




FIG. 17A

1700

1700




FIG. 17B

1720

1710




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 18D




FIG. 18E





FIG. 19



DETAIL A

FIG. 20B

FIG. 20A




FIG. 21A




FIG. 21B




FIG. 22A




FIG. 22B




FIG. 23A




FIG. 23B




FIG. 24A




FIG. 24B




FIG. 24C




FIG. 25A




FIG. 25B





FIG. 25C



SECTION A-A

FIG. 25D




FIG. 25E




FIG. 26A




FIG. 26B




FIG. 26C




FIG. 26D




FIG. 26E




FIG. 26F




FIG. 27B




FIG. 27A




FIG. 27C




FIG. 27D




FIG. 27E




FIG. 27F

EAR SENSOR

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 14/218,328, filed Mar. 18, 2014, titled "Ear Sensor," which is a continuation of U.S. patent application Ser. No. 13/975,008, filed Aug. 23, 2013, titled "Ear Sensor," which is a continuation of U.S. patent application Ser. No. 12/658,872, filed Feb. 16, 2010, titled "Ear Sensor," which claims priority benefit under 35 U.S.C. § 119(e) to U.S. Provisional Patent Application No. 61/152,964, filed Feb. 16, 2009, titled "Ear Sensor," each of which is hereby incorporated by reference herein in its entirety.

BACKGROUND OF THE INVENTION

Pulse oximetry systems for measuring constituents of circulating blood have gained rapid acceptance in a wide variety of medical applications, including surgical wards, intensive care and neonatal units, general wards, home care, physical training, and virtually all types of monitoring scenarios. A pulse oximetry system generally includes an optical sensor applied to a patient, a monitor for processing sensor signals and displaying results and a patient cable electrically interconnecting the sensor and the monitor. A pulse oximetry sensor has light emitting diodes (LEDs), typically one emitting a red wavelength and one emitting an infrared (IR) wavelength, and a photodiode detector. The emitters and detector are typically attached to a finger, and the patient cable transmits drive signals to these emitters from the monitor. The emitters respond to the drive signals to transmit light into the fleshy fingertip tissue. The detector generates a signal responsive to the emitted light after attenuation by pulsatile blood flow within the fingertip. The patient cable transmits the detector signal to the monitor, which processes the signal to provide a numerical readout of physiological parameters such as oxygen saturation (SpO₂) and pulse rate.

Pulse oximeters capable of reading through motion induced noise are disclosed in at least U.S. Pat. Nos. 6,770,028, 6,658,276, 6,650,917, 6,157,850, 6,002,952, 5,769,785, and 5,758,644; low noise pulse oximetry sensors are disclosed in at least U.S. Pat. Nos. 6,088,607 and 5,782,757; all of which are assigned to Masimo Corporation, Irvine, Calif. ("Masimo") and are incorporated by reference herein. An ear sensor is disclosed in U.S. Pat. No. 7,341,559 titled Pulse Oximetry Ear Sensor, also assigned to Masimo and also incorporated by reference herein.

Advanced physiological monitoring systems may incorporate pulse oximetry in addition to advanced features for the calculation and display of other blood parameters, such as carboxyhemoglobin (HbCO), methemoglobin (HbMet) and total hemoglobin (Hbt), as a few examples. Advanced physiological monitors and corresponding multiple wavelength optical sensors capable of measuring parameters in addition to SpO₂, such as HbCO, HbMet and Hbt are described in at least U.S. patent application Ser. No. 12/056,179, filed Mar. 26, 2008, titled Multiple Wavelength Optical Sensor and U.S. patent application Ser. No. 11/366,208, filed Mar. 1, 2006, titled Noninvasive Multi-Parameter Patient Monitor, both incorporated by reference herein. Further, noninvasive blood parameter monitors and corresponding multiple wavelength optical sensors, such as Rainbow™ adhesive and reusable sensors and RAD-57™ and Radical-7™ monitors for measuring SpO₂, pulse rate, perfusion

index (PI), signal quality (SIQ), pulse variability index (PVI), HbCO and HbMet among other parameters are also available from Masimo.

SUMMARY OF THE INVENTION

FIG. 1 illustrates various areas of the ear **100** that are amenable to blood parameter measurements, such as oxygen saturation (SpO₂). An ear site has the advantage of more quickly and more accurately reflecting oxygenation changes in the body's core as compared to peripheral site measurements, such as a fingertip. Conventional ear sensors utilize a sensor clip on the ear lobe **110**. However, significant variations in lobe size, shape and thickness and the general floppiness of the ear lobe render this site less suitable for central oxygen saturation measurements than the concha **120** and the ear canal **130**. Disclosed herein are various embodiments for obtaining noninvasive blood parameter measurements from concha **120** and ear canal **130** tissue sites.

One aspect of an ear sensor optically measures physiological parameters related to blood constituents by transmitting multiple wavelengths of light into a concha site and receiving the light after attenuation by pulsatile blood flow within the concha site. The ear sensor comprises a sensor body, a sensor connector and a sensor cable interconnecting the sensor body and the sensor connector. The sensor body comprises a base, legs and an optical assembly. The legs extend from the base to detector and emitter housings. An optical assembly has an emitter and a detector. The emitter is disposed in the emitter housing and the detector is disposed in the detector housing. The legs have an unflexed position with the emitter housing proximate the detector housing and a flexed position with the emitter housing distal the detector housing. The legs are moved to the flexed position so as to position the detector housing and emitter housing over opposite sides of a concha site. The legs are released to the unflexed position so that the concha site is grasped between the detector housing and emitter housing.

In various embodiments, the ear sensor has a resilient frame and a one piece molded skin disposed over the resilient frame. A cup is disposed proximate the detector housing and has a surface that generally conforms to the curvature of the concha site so as to couple the detector to the concha site and so as to block ambient light. A sensor cable has wires extending from one end of the sensor cable and disposed within channels defined by the resilient frame. The wires electrically and mechanically attach to the optical assembly. A connector is attached to the other end of the sensor cable, and the cable wires electrically and mechanically attach to the connector so as to provide communications between the connector and the optical assembly.

In other embodiments, a stabilizer maintains the position of the detector housing and the emitter housing on the concha site. The stabilizer may have a ring that encircles the legs. The ring has a hold position disposed against the legs and a release position spaced from the legs. A release, when pressed, moves the ring from the hold position to the release position, allowing the ring to slidably move along the legs in a direction away from the base so as to increase the force of the emitter housing and detector housing on the concha site in the hold position and in a direction toward the base so as to decrease the force of the emitter housing and the detector housing on the concha site in the hold position. The stabilizer may have an ear hanger that rests along the back of the ear and couples to at least one of the legs and the sensor cable.

Another aspect of an ear sensor comprises providing a sensor body having a base, legs extending from the base and an optical housing disposed at ends of the legs distal the base. An optical assembly is disposed in the housing. The sensor body is flexed so as to position the housing over a concha site. The sensor body is unflexed so as to attach the housing to the concha site and position the optical assembly to illuminate the concha site.

In various embodiments, an ear surface conforming member is molded to at least a portion of the housing so as to physically couple the housing to the concha site and block ambient light from the optical assembly accordingly. The force of the housing against the concha site is adjusted. The adjusting comprises positioning a force adjustment ring on the sensor body so as to encircle the legs. The positioning comprises squeezing a ring release so as to move ring grips away from the legs, moving the force adjustment ring along the legs and toward the housing so as to increase the force of the housing on the concha site, and moving the force adjustment ring along the legs and away from the housing so as to decrease the force of the housing on the concha site.

In other embodiments, an aspect of the ear sensor comprises supporting at least a portion of the weight of the sensor body and corresponding sensor cable so as to reduce the force needed to attach the housing to the concha site. The supporting comprises attaching at least one of the sensor body and sensor cable to an ear hook placed over the ear.

A further aspect of an ear sensor comprising a clip means having a flexed position and an unflexed position. An optical means transmits multiple wavelength light into a tissue site when activated and receives the light after attenuation by pulsatile blood flow within the tissue site. The optical means is disposed on the clip means so that the optical means can be positioned on a concha site in the flexed position and pinched against the concha site in the unflexed position. A connector means mechanically attaches to and electrically communicates with a monitor. A cable means interconnects the connector means with the optical means. In various embodiments, the clip means comprises a resilient frame means for securing the optical means in a fixed position relative to the tissue site. A housing means encloses the resilient frame means and the optical means. A cup means physically couples at least a portion of the optical means to the concha site and blocks ambient light from the optical means. An adjustable force means holds the clip means to the concha site. Alternatively, or in addition to, a support means holds the clip means to the concha site.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an illustration of the pinna or external ear structure, including the concha;

FIGS. 2A-B and 3A-B illustrate various ear sensor embodiments;

FIGS. 2A-B are a side view and a perspective view of an ear bud embodiment of an ear sensor;

FIGS. 3A-B are perspective views of a flexible ear pad embodiment of an ear sensor;

FIGS. 4A-D, 5A-B, 6A-B, and 7A-C illustrate various ear bud/pad attachment embodiments for a concha site;

FIGS. 4A-D are side views of "C"-clip embodiments for attaching an ear sensor to a concha site;

FIGS. 5A-B are perspective views of alligator clip embodiments for attaching an ear sensor to a concha site;

FIGS. 6A-B are perspective views of a clear adhesive disk embodiment for attaching an ear sensor to a concha site;

FIGS. 7A-C are perspective views of a flexible magnet disk embodiment for attaching an ear sensor to a concha site;

FIGS. 8A-B, 9A-B, and 10A-B illustrate various "hearing aid" style ear sensor embodiments that integrate the ear sensor with an attachment mechanism;

FIGS. 8A-B illustrate a concha-placed reflective sensor embodiment;

FIGS. 9A-B illustrate an "in-the-canal" reflective sensor embodiment;

FIGS. 10A-B illustrate "behind-the-ear" transmissive and/or reflective sensor embodiments;

FIGS. 11A-B and 12A-F illustrate additional integrated ear sensor and attachment embodiments;

FIGS. 11A-B illustrate an integrated ear lobe attachment and concha-placed sensor embodiment;

FIGS. 12A-F illustrate a "Y"-clip sensor embodiment for concha-placement;

FIGS. 13A-F, 14A-B, 15A-B, and 16 illustrate various ear sensor attachment support embodiments;

FIGS. 13A-F are side views of ear-hook support embodiments;

FIGS. 14A-B are perspective views of headband support embodiments;

FIGS. 15A-B are front and perspective views of a "stethoscope" support embodiment;

FIG. 16 is a perspective view of a "headphone" support embodiment;

FIGS. 17A-B, 18A-E, 19, 20A-B, 21A-B, 22A-B, 23A-B, 24A-C, 25A-E, 26A-F, and 27A-F illustrate a concha-clip sensor embodiment having an orthogonally-routed sensor cable;

FIGS. 17A-B are perspective views of a concha-clip sensor;

FIGS. 18A-E are top, perspective, front, detector-side and emitter-side views, respectively, of a concha-clip sensor body;

FIG. 19 is an exploded view of an concha-clip sensor;

FIGS. 20A-B are assembly and detailed assembly views of a concha-clip sensor;

FIG. 21A-B are a mechanical representation and a corresponding electrical (schematic) representation of a concha-clip sensor having a DB9 connector;

FIG. 22A-B are a mechanical representation and a corresponding electrical (schematic) representation of a concha-clip sensor having a MC8 connector;

FIG. 23A-B are a mechanical representation and a corresponding electrical (schematic) representation of a concha-clip sensor having a M15 connector;

FIGS. 24A-C are assembly step representations for installing an optical assembly into a resilient frame and installing the resilient frame into a sensor housing;

FIGS. 25A-E are top, perspective, front, side cross-section, and side views, respectively, of a force adjustment ring;

FIGS. 26A-F are top, disassembled perspective, assembled perspective, front, detector-side and emitter-side views of a concha-clip sensor body and corresponding force adjustment ring; and

FIGS. 27A-F are top, bottom, perspective, detector-side, front, emitter side and perspective views, respectively of an concha-clip sensor body having a parallel-routed sensor cable.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIGS. 2A-B illustrate an ear bud embodiment of an ear sensor **200** having an emitter ear bud **210**, a detector ear bud

220 and connecting cables 230. The emitter ear bud 210 has a generally concave surface for attachment to the back of an ear. The detector ear bud 220 has a generally convex surface 222 for attachment inside the ear at a concha site opposite the emitter ear bud 210. Sensor cables 230 are attached at the back of each ear bud having wires for electrical communications with a physiological monitor, such as a pulse oximeter. In particular, the emitter ear bud 210 includes wires for receiving emitter drive current from a monitor and the detector ear bud 220 includes wires for transmitting photo-diode current to the monitor.

FIGS. 3A-B illustrate a flexible ear pad embodiment of an ear sensor 300 having an emitter pad 310, a detector pad 320 and corresponding cables 330. The sensor pads 310, 320 advantageously include a housing for each of the emitter pad 310 and the detector pad 320, minimizing the number of unique parts for the ear sensor. The detector pad 320 houses a shielded detector assembly (not shown). The emitter pad houses 310 an emitter (not shown). Both the detector pad 320 and the emitter pad 310 are connected to a sensor cable 330. The pads 310, 320 have an integrated bend relief 304 providing a finger grip. The pad face 306 provides a generally planar, pliant contact surface that can adapt to the curved front and back surfaces of a concha site. The pad face 306 has a relatively large area to minimize contact force. The housing 302 is injection molded of a pliant material. In one embodiment, the material is a medical grade thermoplastic elastomer.

FIGS. 2A-B and 3A-B, above, illustrate various ear sensor embodiments. Although described with respect to ear bud and flexible ear pad enclosures, the sensor emitter and detector may be enclosed in any number of housings having various sizes and shapes of ear tissue contact surfaces, may use various types of electrical interconnect and use various materials so as to noninvasively measure blood parameters from the concha area of the ear. As an example, the detector and emitter may both be mounted at one end of a "Y"-shaped flex circuit that has a connector at the opposite end. Although described above with respect to a detector placed inside the ear and an emitter placed outside the ear, a suitable alternative is the emitter inside and the detector outside the ear. Detector and emitter assemblies are described with respect to FIGS. 19-20, below.

FIGS. 4A-D illustrate "C"-clip embodiments 400 for attaching an ear sensor 410 to a concha site. The clip 400 is adapted for use with either the ear bud or the ear pad embodiments described above. The clip 400 has sensor mounts 420 fixedly attached to each end of a flexible "C"-shaped body 422. The body 422 is made of a suitable material having an appropriate stiffness so as to provide a comfortable yet secure attachment to ear tissue. The sensor mounts 420 have mounting apertures sized for the ear buds or ear pads described above. The ear buds or pads are secured within the apertures with a friction fit or adhesive. In an alternative embodiment, the sensor housings are molded or otherwise integrated with the sensor mounts.

As shown in FIGS. 4A-B, in one embodiment 401 the unflexed clip 400 (FIG. 4A) is compressed between fingertips so that the clip ends 424 are crossed (FIG. 4B) and the contact surfaces of the ear sensor 412 are facing each other. The clip 400 is placed over the ear so that the detector and emitter ear buds are on opposite sides of the ear. Finger pressure on the clip 400 is then released so that the clip tension holds the sensor contact surfaces 412 against the concha tissue. As shown in FIGS. 4C-D, in another embodiment 403 the clip ends 424 are crossed in both the flexed position (FIG. 4C) and the unflexed position (FIG. 4D).

Otherwise, sensor attachment is as described above. Although described above as a "C"-shape, the clip body can be constructed of any of various springy, pre-formed materials having a variety of shapes and sizes so as to attach to ear tissue via compression and release between finger and thumb.

FIGS. 5A-B illustrate an alligator clip embodiment for attaching an ear sensor to a concha site. The alligator clip 500 has opposing heads 510, each with a thru-hole 512 sized to accommodate either an ear pad sensor 300 (FIG. 5A) or an ear bud sensor 200 (FIG. 5B). The alligator clip 500 also has finger grips 520 each with a channel 530 for routing the sensor cabling 540. The alligator clip is compressed and released to position and then attach the corresponding ear sensor to a concha site.

FIGS. 6A-B illustrate an adhesive disk embodiment for attaching an ear sensor to a concha site. Clear disks 600 have an adhesive on both surfaces. The adhesive is bio-compatible on at least the tissue-facing surface. The disks 600 are first attached to the sensor 200 or to a concha site 10. Then the ear sensor 200 is attached on opposite sides of the concha tissue 10. The disks 600 are sized to accommodate either an ear bud sensor 200, as shown, or an ear pad sensor 300 (FIGS. 3A-B).

FIGS. 7A-C illustrate a flexible magnet disk embodiment for attaching an ear sensor to a concha site. Flexible magnetic disks 700, such as made from a mixture of a ferrite powder and a rubber polymer resin, are permanently or temporarily attached to an ear sensor 200. The attachment may be by friction fit or a removable or permanent adhesive. The ear sensor 200 is then placed on opposite sides of the concha site 10 and held in place by the magnetic force of the disks. One or both disks may be permanently magnetized during manufacture. The disks 700 are sized to accommodate either the ear bud sensor 200, as shown, or the ear pad sensor 300 (FIGS. 3A-B). In an alternative embodiment, each of the ear sensor housings is at least partially composed of a high magnetic permeable material. One or both of the housings are magnetized. In another embodiment, one or more rare earth magnets are embedded in one or both housings.

FIGS. 4A-D, 5A-B, 6A-B, and 7A-C, described above, illustrate various ear sensor attachment embodiments. Although described with respect to clips and adhesive or magnetic disks, the sensor emitter and detector may be attached to an ear tissue site using various other materials and mechanisms. For example, ear buds or pads may attach via suction cups or disks. Also, an emitter and detector may be integrated with disposable adhesive pads configured with snaps or other mechanical connectors for attaching and removing sensor leads from the disposable pads. In another embodiment, a sensor may be mounted in the concha or the ear canal using an expanding foam material that is first squeezed and then released after sensor placement within the ear.

FIGS. 8A-B illustrate a concha-placed reflective sensor embodiment. In one embodiment the sensor 800 has an ear canal extension 810 (FIG. 8B). In an embodiment, the ear canal extension has at least one emitter and at least one detector disposed proximate the extension surface so as to transmit light into ear canal tissue and to detect the transmitted light after attenuation by pulsatile blood flow within the ear canal tissue. In an embodiment, the emitter and detector are axially spaced on the extension. In an embodiment, the emitter and detector are radially spaced on the extension at a fixed angle, which may be, as examples, 30, 45, 90, 120, 135, 160 or 180 degrees.

In an embodiment, the concha-placed sensor body **820** has at least one emitter and at least one detector in lieu of an ear canal extension emitter and detector. The sensor body emitter and detector are disposed proximate the concha surface so as to transmit light into concha tissue and to detect the transmitted light after attenuation by pulsatile blood flow within the concha tissue. In an embodiment, the concha-placed sensor body **820** and the ear canal extension **810** both have at least one emitter and at least one detector, creating a multi-site (concha and ear canal) reflective sensor. Connected with the sensor body **820** is a sensor cable **830** providing electrical communications between sensor body/ear canal emitter(s) and detector(s) and a monitor. Detector and emitter assemblies are described with respect to FIGS. **19-20**, below.

FIGS. **9A-B** illustrate an “in-the-canal” ear sensor embodiment. The ear canal sensor **900** has a base **910**, an ear canal extension **920** and a sensor cable **930**. Similar to the embodiment described above, the ear canal extension **920** has at least one emitter **922** and at least one detector **924** disposed proximate the extension surface so as to transmit light into ear canal tissue and to detect the transmitted light after attenuation by pulsatile blood flow within the ear canal tissue. The emitter **922** and detector **924** may be axially-spaced on the ear canal extension a fixed distance. Alternatively, the emitter and detector may be radially-spaced on the ear canal extension at any of various angles, such as 30, 45, 90, 120, 135, 160 or 180 degrees, to name a few. A sensor cable **930** is attached to the sensor so as to extend from the ear canal to a corresponding monitor.

FIGS. **10A-B** illustrate “behind-the-ear” transmissive and/or reflective sensor embodiments. The ear sensor **1000** has a concha-placed body **1010**, an ear piece **1020**, a connecting piece **1030** attaching the concha body **1010** and the ear piece **1020** and a sensor cable **1040**. In one embodiment, a concha-placed body **1010** houses a detector and the ear piece **1020** houses an emitter opposite the detector so as to configure a transmissive concha sensor. In an embodiment, the concha-placed body **1010** or the ear piece **1020** has both an emitter and a detector so as to configure a reflective concha sensor. In an embodiment, the concha body **1010** and the ear piece **1020** are configured for multi-site transmissive and/or reflective concha tissue measurements. In an embodiment, the concha body **1010** also has an ear canal extension (see, e.g. **810** FIG. **8B**), which may also have an emitter and detector for multi-site concha and ear canal measurements. A sensor cable **1040** extends from the ear piece **1020** as shown. Alternatively, a sensor cable extends from the concha body, such as shown in FIG. **8B**, above.

FIGS. **11A-B** illustrate a concha sensor **1100** having an alligator clip **1110**, a concha piece **1120**, an ear back piece **1130**, a lobe attachment **1140** and a sensor cable **1150**. In an embodiment, the alligator clip **1110** attaches to the ear lobe **20** so as to provide the physical support for a concha sensor **1100**. A convex body **1122** extends from the concha piece **1120**. A detector disposed at the convex body **1122** surface is disposed against the concha tissue **10**. A concave surface **1132** is defined on the back piece **1130** and positioned behind the ear. An emitter disposed at the concave surface **1132** is disposed against the ear wall opposite the concha detector. The concha piece **1120** and ear back piece **1130** are “springy” so as to securely contact the concha tissue **10** under the force of the alligator clip **1110**, but without undue discomfort. In an embodiment, the lobe attachment **1140** also has an emitter and detector so as to provide multi-site ear tissue measurements at the ear lobe **20** and the concha **10**.

FIGS. **12A-F** illustrate a “Y”-clip ear sensor **1200** having a base **1210**, a pair of curved clips **1220** extending from the base, an emitter assembly **1230** extending from one clip end and a detector assembly **1240** extending from another clip end. The clips **1220** are tubular so as to accommodate wires from the emitter/detector assemblies, which extend from apertures **1212** in the base. Each assembly has a pad **1232**, a molded lens **1234** and a lid **1236**, which accommodate either an emitter subassembly or a detector subassembly. The Y-“clips” flex so as to slide over the ear periphery and onto either side of the concha. The integrated emitter and detector, so placed, can then transmit multiple wavelength light into the concha tissue and detect that light after attenuation by pulsatile blood flow within the concha tissue.

FIGS. **13A-F** illustrate ear hook sensor support embodiments having an ear hook **1300** with cable **1310**, fixed **1320** or sliding **1330** support for either an alligator clip or a “Y”-clip sensor. These embodiments are also applicable to “C”-clip sensors and alligator clip sensors, among others.

FIGS. **14A-B** illustrate headband sensor support embodiments. In one embodiment, the headband **1400** secures a concha body (FIGS. **8A-B**) or an ear canal sensor (FIGS. **9A-B**) by placement over the ear. In another embodiment, the headband **1400** provides a cable support for an ear clip sensor.

FIGS. **15A-B** illustrate a “stethoscope” **1500** sensor support embodiment. In this embodiment, one ear piece **1510** is integrated with an ear canal sensor **1520**, such as described above with respect to FIGS. **9A-B**. In another embodiment, both stethoscope ear pieces **1510** are integrated with ear canal sensors for multi-site (both ears) blood parameter measurements.

FIG. **16** illustrates a “headphone” **1600** support embodiment. In one embodiment (not shown), a headphone ear piece secures a concha body (FIGS. **8A-B**) or an ear canal sensor (FIGS. **9A-B**) by placement over the ear, in a similar manner as described with respect to FIGS. **14A-B**. In another embodiment, the headphone **1600** provides a “ring-shaped” earpiece **1610** that provides a cable support **1612** for an ear clip sensor **1200**, as shown.

FIGS. **17A-B** illustrate a concha-clip ear sensor **1700** embodiment having a sensor body **1800**, a connector **1710** and a sensor cable **1720** providing communications between the sensor body **1800** and the connector **1710**. As described in further detail with respect to FIGS. **18A-E**, the sensor body **1800** has resilient legs that are manually flexed so as to slide over an ear periphery and onto either side of a concha site. As described in further detail with respect to FIG. **19**, the sensor body **1800** incorporates an optical assembly **1910** (FIG. **19**) configured to transmit multiple wavelength light into the concha tissue and detect that light after attenuation by pulsatile blood flow within the concha tissue. In a particular embodiment, the sensor body **1800** has an emitter housing **1840** (FIGS. **18A-E**) configured to fit inside the ear and a detector housing **1850** (FIGS. **18A-E**) configured to fit outside the ear. In other embodiments, the sensor body is configured so as to place an emitter outside the ear and a detector inside the ear. In an embodiment, the sensor body **1800** is configured so that the sensor cable **1720** extends generally perpendicular to the sensor body **1800**, as shown and described with respect to FIGS. **17-26**. In another sensor body embodiment **2700** (FIGS. **27A-F**) the sensor cable **1720** extends generally parallel to the sensor body, as described in further detail with respect to FIGS. **27A-E**, below. Although the sensor body **1800**, **2700** as described below has legs **1830** extending from a base **1810** so as to generally form a “U”-shape, the sensor body **1800**, **2700** can

be constructed of any of various resilient, pre-formed materials having a variety of shapes and sizes so as to attach to ear tissue, such as a concha site or ear lobe site.

FIGS. 18A-E further illustrate a sensor body **1800** having a base **1810**, a strain relief **1820** formed at a side of the base **1810** and a pair of resilient legs **1830** extending from the base **1810**. The strain relief **1820** has a cable aperture **1822** that accommodates the sensor cable **1720** (FIGS. 17A-B). An emitter housing **1840** extends from one leg **1830** and a detector housing **1850** extends from the other leg **1830**. The legs **1830** accommodate cable conductors extending between the connector **1710** (FIGS. 17A-B) and an optical assembly **1910** (FIG. 19) located in the housings **1840**, **1850**. Each housing **1840**, **1850** has an optical end **1842**, **1852** (FIG. 20B) having an aperture **1844**, **1854** (FIG. 20B) that passes light from the emitter housing **1840** to the detector housing **1850**. In an embodiment, the housings **1840**, **1850** fit on either side of a concha tissue site so that light is transmitted from an emitter **1916** (FIG. 19), through the concha tissue and received by a detector **1912** (FIG. 19), as described in detail below. In an embodiment, the emitter housing **1840** fits within the ear and the detector housing **1850** outside the ear. In an embodiment, a cup **1860** extends from the detector housing **1850**. The cup **1860** has a generally circular edge and a curvature that accommodates the surface behind the ear. Accordingly, the cup **1860** advantageously provides a more comfortable and secure fit of the detector housing **1850** to the ear and further functions as a light shield, blocking external light sources from the detector **1912**. The resilient legs **1830** are manually flexed so that the emitter housing **1840** is moved away from the detector housing **1850** so as to position the detector housing **1850** and emitter housing **1840** over opposite sides of a concha site. The legs are then released to an unflexed position so that the concha site is grasped between the detector housing **1850** and emitter housing **1840**.

FIGS. 19, 20A-B further illustrates a concha-clip ear sensor **1700** having a connector **1710** in communications with a sensor body **1800** via a sensor cable **1720**. The sensor body **1800** has an optical assembly **1910**, a resilient frame **1920**, a sensor housing **1930** and lenses **1940**. As shown in FIGS. 19-20, the optical assembly **1910** has a detector **1912**, a detector shield **1914**, a light barrier **1915**, an emitter **1916** and white electrical tape **1918**. The cable **1720** has emitter wires **1722** and detector wires **1724** that are soldered to the emitter **1916** and detector **1912**, respectively, and communicate emitter drive signals and detector response signals to/from the connector **1710**.

Also shown in FIGS. 19, 20A-B, the resilient frame **1920** has an emitter channel **1926** terminating at an emitter holder **1924**, a detector channel **1927** terminating at a detector holder **1925**, a strain relief **1928** and a frame hole **1929**. The optical assembly **1910** fits within the resilient frame **1920**. In particular, the emitter wires **1722** are disposed within the emitter channel **1926**, the detector wires **1724** are disposed in the detector channel **1927**, the emitter is disposed in the emitter holder **1924** and the detector **1912** and corresponding shield **1914** and light barrier **1915** are disposed in the detector holder **1925**. In an embodiment, the sensor housing **1930** is a one piece silicon skin disposed over the resilient frame **1920** and the optical assembly **1910**, as described with respect to FIGS. 24A-C, below. In an embodiment, the resilient frame **1920** is a polypropylene/santoprene blend. The lenses **1940** are disposed within housing apertures **1844**, **1854**. In an embodiment, the lenses **1940** are formed from a translucent silicone adhesive. In an alternative embodiment,

the lenses **1940** are separately formed from clear silicone and glued into place with a translucent silicone adhesive.

FIGS. 21A-B, 22A-B, 23A-B further illustrate concha-clip sensor embodiments **2100**, **2200**, **2300** having a DB9 connector **2130** (FIGS. 21A-B), a MC8 connector **2230** (FIGS. 22A-B) or a M15 connector **2330** (FIGS. 23A-B). The sensor bodies **2110**, **2220**, **2330** have red and IR emitters **2112**, **2212**, **2312** and detectors **2114**, **2214**, **2314** in communication with connectors **2130**, **2230**, **2330** via emitter wires **2152**, **2252**, **2352** and detector wires **2154**, **2254**, **2354**. Sensor ID resistors **2132**, **2232**, **2332** are mounted in parallel with the emitters, and can be read by a monitor generating currents below the emitter-on thresholds. Compatibility resistors **2134**, **2234** can be read by other monitor types. EEPROMs **2136**, **2236**, **2336** programmed with various sensor information can be read by more advanced monitors. Shield wires **2156**, **2256**, **2356** provide conductive paths via the connectors to a common shield ground. In an embodiment, ID resistors are 12.7 K Ω , compatibility resistors are 6.81 K Ω , and EEPROMs are 1-wire, 20 Kbit memories available from Maxim Integrated Products, Inc., Sunnyvale, Calif.

FIGS. 24A-C illustrate integration of the optical assembly **1910** disposed at the end of a sensor cable **1720**, the resilient frame **1920** and the sensor housing **1930**. As shown in FIG. 24A, the optical assembly **1910** is threaded into the sensor housing **1930**. In particular, in a couple steps **2401-2402**, the optical assembly **1910** is inserted into the sensor housing **1930** through the cable aperture **1822**. In a further couple steps **2403-2404**, the optical assembly **1910** and portions of the attached sensor cable **1720** are pulled through the cable aperture **1822** and out of a U-slot **1932** of the sensor housing **1930**.

As shown in FIG. 24B, in a step **2405**, the optical assembly **1910** is integrated with the resilient frame **1920** to form a frame assembly **2490**. In particular, the detector assembly **1919** is inserted into a detector holder **1925** to form a framed detector **2495**. Also, the emitter **1916** is inserted into an emitter holder **1924** to form a framed emitter **2495**.

As shown in FIG. 24C, the frame assembly **2490** is integrated with the sensor housing **1930** to form the sensor body **1800**. In several steps **2406-2408** the framed emitter **2494** is inserted into a pocket within the emitter housing **1840**. In a couple additional steps **2409-2410**, the framed detector **2495** is inserted into a pocket within the detector housing **1850**. In a step **2411**, a housing post **1934** is inserted into the frame hole **1929**. In several additional steps **2412-2414**, excess cable **1720** is removed from the sensor housing **1930** via the cable aperture **1822**, and the U-slot **1932** is closed and sealed with an adhesive. The resulting sensor body **1800** is described in detail with respect to FIGS. 18A-E, above.

FIGS. 25A-E, 26A-F illustrate a force adjustment ring **2500** that slidably attaches to the sensor body **1800** so as to adjust the force of the sensor housings **1840**, **1850** against concha tissue. The ring **2500** forms a generally oval opening **2526** having a pair of opposing sensor grips **2520** generally centered along a long axis of the opening **2526** and a pair of finger releases **2510** generally centered along a short axis of the opening **2526**. The sensor grips **2520** have toothed faces **2525** configured to contact the sensor body legs **1830**. The finger releases **2510** allow the ring to be squeezed between a finger and thumb, say, so as to compress the ring short axis, thereby lengthening the ring long axis and releasing the toothed faces **2525** from the legs **1830**. In this manner, the

ring 2500 can be positioned closer to or farther from the housings 1840, 1850 so as to increase or decrease the force on a concha tissue site.

FIGS. 27A-F illustrate a sensor body 2700 configured for a parallel-routed sensor cable, as compared with the sensor body 1800 (FIGS. 18A-E) configured for a perpendicular-routed sensor cable, as described above. The sensor body 2700 has a base 2710, a strain relief 2720 formed at a bottom end of the base 2710 and a pair of resilient legs 2730 extending from an opposite end of the base 2710. The strain relief 2720 has an aperture 2722 that accommodates the sensor cable 1720 (FIGS. 17A-B). An emitter housing 2740 extends from one leg 2730 and a detector housing 2750 extends from the other leg 2530. The legs 2730 accommodate cable conductors extending between a connector 1710 (FIGS. 17A-B) and an optical assembly 1910 (FIG. 19) located in the housings 2740, 2750. Each housing 2740, 2750 has an optical end having an aperture that passes light from the emitter housing 2740 to the detector housing 2750. In an embodiment, the housings 2740, 2750 fit on either side of a concha tissue site so that light is transmitted from an emitter of the optical assembly, through the concha tissue and received by a detector of the optical assembly. In an embodiment, the emitter housing 2740 fits within the ear and the detector housing outside the ear. In an embodiment, a cup 2760 extends from the optical end of the detector housing 2750. The cup 2760 has a generally circular edge and a curvature that accommodates the outside curvature of the ear. Accordingly, the cup 2760 advantageously provides a more comfortable and secure fit of the detector housing 2750 to the ear and further functions as a light shield, blocking external light sources from the detector assembly.

A sensor body 1800 (FIGS. 18A-E), 2700 (FIGS. 27A-F) is described above with respect to directly flexing resilient legs in order to space apart emitter and detector housings for placement on a concha site. In another embodiment, a pair of finger levers can extend from the legs to a position below the sensor body base opposite the resilient legs. The finger levers can be squeezed between finger and thumb so as to flex the resilient legs for concha site placement.

In a particular advantageous embodiment, a single finger lever can extend from one leg to a position below the base. This single finger lever can be squeezed using a sensor cable portion extending from the sensor body base for leverage. Such a single finger lever configuration eliminates potential discomfort from a second lever poking a patient's neck area.

An ear sensor has been disclosed in detail in connection with various embodiments. These embodiments are disclosed by way of examples only and are not to be construed as limiting the scope of the claims that follow. One of ordinary skill in art will appreciate many variations and modifications.

What is claimed is:

1. An in-ear physiological measurement device comprising:

a base portion;

an extension portion configured to extend at least partially into an ear of a user, the extension portion including:

an outer surface that extends substantially cylindrically around an axis of the extension portion and is configured to be positioned at least partially in the ear of the user, wherein the axis extends from the base portion to an end of the extension portion configured to be positioned in the ear of the user; and an end surface that joins the outer surface at the end of the extension portion;

at least one light emitter configured to emit light into an ear tissue site of the user; and

at least one light detector configured to output a signal responsive to at least a portion of the emitted light after attenuation by ear tissue of the ear tissue site, the signal indicative of at least one physiological parameter of the user,

wherein the at least one light emitter and at least one light detector are positioned on the outer surface of the substantially cylindrical extension portion and not on the end surface of the extension portion, and wherein the at least one light emitter and the at least one light detector are positioned spaced apart relative to each other along an axis parallel to the axis of the extension portion.

2. The in-ear physiological measurement device of claim 1, wherein the at least one of the base portion or the extension portion is configured to conform to a portion of the ear of the user including at least one of a portion of a concha or a portion of an ear canal of the ear of the user.

3. The in-ear physiological measurement device of claim 2, wherein the extension portion narrows toward the end of the extension portion.

4. The in-ear physiological measurement device of claim 3, wherein the base portion is wider than the extension portion so as to be configured to stay outside the ear of the user.

5. The in-ear physiological measurement device of claim 2 further comprising:

an expanding material portion, wherein the in-ear physiological measurement device is configured to be mounted in the ear of the user by first squeezing and then releasing the expanding material portion after placement of the in-ear physiological measurement device in the ear.

6. The in-ear physiological measurement device of claim 5, wherein the expanding material portion is configured to mount the in-ear physiological measurement device in the concha and/or ear canal of the ear of the user.

7. The in-ear physiological measurement device of claim 6, wherein the expanding material portion comprises a foam material.

8. The in-ear physiological measurement device of claim 7 further comprising:

a cable portion extending from the base portion and configured to communicate the signal to a receiver, the signal useable by the receiver to determine the at least one physiological parameter of the user.

9. The in-ear physiological measurement device of claim 8, wherein at least one of: the base portion, the extension portion, or a combination of the base portion and the extension portion comprises an ear bud.

10. The in-ear physiological measurement device of claim 7, wherein the ear tissue of the ear tissue site includes at least one of ear canal ear tissue or concha ear tissue.

11. The in-ear physiological measurement device of claim 10, wherein the portion of the emitted light is reflected by the ear tissue to the at least one light detector.

12. The in-ear physiological measurement device of claim 11, wherein the at least one physiological parameter comprises at least one of an oxygen saturation or a pulse rate of the user.

13. The in-ear physiological measurement device of claim 12, wherein the base portion is configured to conform to a concha of the ear of the user.

14. The in-ear physiological measurement device of claim 13 further comprising:

at least one additional light emitter and at least one additional light detector positioned on the base portion.

15. A multi-site in-ear physiological measurement system comprising:

two in-ear physiological measurement devices according 5
to claim 1, each in-ear physiological measurement device configured to be simultaneously placed in either a right or left ear of the user; and
a monitoring device configured to receive the signal from each of the two in-ear physiological measurement 10
devices, the signals useable by the monitoring device to determine the at least one physiological parameter of the user.

16. The multi-site in-ear physiological measurement system of claim 15, wherein both of the two in-ear physiological 15
measurement devices are coupled to a single flexible frame.

17. An in-ear physiological measurement system comprising:

an in-ear physiological measurement device according to 20
claim 1, the in-ear physiological measurement device configured to be placed in at least one of a right or left ear of the user; and
a monitoring device configured to receive the signal from the in-ear physiological measurement device, the signal 25
useable by the monitoring device to determine the at least one physiological parameter of the user.

* * * * *

专利名称(译)	耳朵传感器		
公开(公告)号	US10292657	公开(公告)日	2019-05-21
申请号	US15/417640	申请日	2017-01-27
[标]申请(专利权)人(译)	梅西莫股份有限公司		
申请(专利权)人(译)	Masimo公司		
当前申请(专利权)人(译)	Masimo公司		
[标]发明人	ABDUL HAFIZ YASSIR AL ALI AMMAR FORREST KEVIN MASON EUGENE SCHMIDT JOHN TA VIRGINIA THANH		
发明人	ABDUL-HAFIZ, YASSIR AL-ALI, AMMAR FORREST, KEVIN MASON, EUGENE SCHMIDT, JOHN TA, VIRGINIA THANH		
IPC分类号	A61B5/1455 A61B5/0205 A61B5/024 A61B5/026 A61B5/00		
CPC分类号	A61B5/6867 A61B5/0205 A61B5/0261 A61B5/02427 A61B5/6838 A61B5/6815 A61B5/6816 A61B5/6817 A61B5/14552		
优先权	61/152964 2009-02-16 US		
其他公开文献	US20170258403A1		
外部链接	Espacenet		

摘要(译)

耳朵传感器提供传感器主体，该传感器主体具有基部，从基部延伸的腿部和设置在与基部相对的腿部的端部处的光学壳体。光学组件设置在壳体中。传感器主体弯曲，以便将外壳定位在外耳上。传感器主体是未弯曲的，以便将外壳连接到外耳部位，并定位光学组件以照亮外耳部位。光学组件被配置成将光辐射传输到外耳部位组织并且在通过组织内的脉动血流衰减之后接收光辐射。

