



US010136857B2

(12) **United States Patent**
Nuovo et al.

(10) **Patent No.: US 10,136,857 B2**
(45) **Date of Patent: *Nov. 27, 2018**

(54) **ADJUSTABLE WEARABLE SYSTEM
HAVING A MODULAR SENSOR PLATFORM**

(71) Applicant: **Samsung Electronics Co., Ltd.**,
Suwon-si (KR)

(72) Inventors: **Frank Settemo Nuovo**, Los Angeles,
CA (US); **Sheldon George Phillips**,
Glendale, CA (US); **James Schuessler**,
San Jose, CA (US)

(73) Assignee: **Samsung Electronics Co., Ltd.** (KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 418 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **14/878,706**

(22) Filed: **Oct. 8, 2015**

(65) **Prior Publication Data**

US 2016/0022210 A1 Jan. 28, 2016

Related U.S. Application Data

(63) Continuation-in-part of application No. 14/719,043,
filed on May 21, 2015, now Pat. No. 9,592,007.
(Continued)

(51) **Int. Cl.**
A61B 5/00 (2006.01)
A61B 5/0402 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 5/681** (2013.01); **A61B 5/0059**
(2013.01); **A61B 5/0402** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61B 5/681; A61B 5/0059; A61B 5/0402;
A61B 5/6831; A61B 5/6843;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,595,929 B2 * 7/2003 Stivoric A61B 5/0008
600/549
6,619,835 B2 9/2003 Kita
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101330869 A 12/2008
EP 00330434 A1 8/1989
(Continued)

OTHER PUBLICATIONS

Notification of Transmittal of the International Search Report and
Written Opinion of the International Searching Authority Authority,
or the Declaration corresponding to International Patent Application
No. PCT/IB2014/003257, dated Jan. 11, 2016.

(Continued)


Primary Examiner — Catherine Voorhees

(74) *Attorney, Agent, or Firm* — McAndrews, Held &
Malloy, Ltd.

(57) **ABSTRACT**

A wearable system and methods for measuring physiological data from a device worn about a body part of a user is provided comprising a base module, a first sensor module, and a second sensor module. The base module comprises a display and a base computing unit. The first sensor module measures a gravitational force experienced by the device. The second sensor module is spatially positioned relative to the base module and over a portion of the body part for measuring one or more physiological characteristics calibrated based on the gravitational force measured with the first sensor module. The base module is adjustably positioned by the user relative to the second sensor module such that the sensor module maintains its positioning over the body part for sufficient contact with the body part for accurate measurements of physiological data regardless of the anthropometric size of the body part.

97 Claims, 17 Drawing Sheets



Related U.S. Application Data			2011/0257553 A1 *	10/2011	Banet	A61B 5/0809	600/536
(60)	Provisional application No. 62/061,290, filed on Oct. 8, 2014, provisional application No. 62/002,589, filed on May 23, 2014.			2011/0288382 A1	11/2011	Finburgh	
				2012/0030165 A1	2/2012	Guirguis	
				2012/0045303 A1	2/2012	Murray	
				2012/0059233 A1	3/2012	Huber	
(51)	Int. Cl.			2012/0065514 A1 *	3/2012	Naghavi	A61B 5/02055
	<i>A61B 5/01</i> (2006.01)						600/454
	<i>A61B 5/0205</i> (2006.01)			2012/0071731 A1	3/2012	Gottesman	
	<i>A61B 5/0408</i> (2006.01)			2012/0203076 A1	8/2012	Fatta et al.	
	<i>A61B 5/053</i> (2006.01)			2013/0014706 A1	1/2013	Menkes	
(52)	U.S. Cl.			2013/0261405 A1	3/2013	Lee et al.	
	CPC	<i>A61B 5/6831</i> (2013.01); <i>A61B 5/6843</i> (2013.01); <i>A61B 5/7264</i> (2013.01); <i>A61B 5/7445</i> (2013.01); <i>A61B 5/0022</i> (2013.01); <i>A61B 5/0024</i> (2013.01); <i>A61B 5/01</i> (2013.01); <i>A61B 5/02055</i> (2013.01); <i>A61B 5/0408</i> (2013.01); <i>A61B 5/0533</i> (2013.01); <i>A61B 5/742</i> (2013.01); <i>A61B 2560/0214</i> (2013.01); <i>A61B 2560/0223</i> (2013.01); <i>A61B 2560/0247</i> (2013.01); <i>A61B 2560/0443</i> (2013.01); <i>A61B 2560/0475</i> (2013.01); <i>A61B 2562/028</i> (2013.01); <i>A61B 2562/0219</i> (2013.01); <i>A61B 2562/0257</i> (2013.01); <i>A61B 2562/164</i> (2013.01)		2013/0141235 A1	6/2013	Utter, II	
				2013/0165817 A1	6/2013	Horst	
				2013/0192050 A1	8/2013	LeMieux	
				2013/0211204 A1	8/2013	Caduff et al.	
				2013/0282679 A1	10/2013	Khin	
				2013/0317333 A1	11/2013	Yang	
				2013/0318347 A1	11/2013	Moffat	
				2013/0324072 A1	12/2013	Fish et al.	
				2014/0142403 A1 *	5/2014	Brumback	A61B 5/02433
							600/324
				2014/0159640 A1	6/2014	Yoshikawa et al.	
FOREIGN PATENT DOCUMENTS							
	EP		1965697 A2	10/2008			
	JP		2009-519737 A	5/2009			
	KR		10-1038432 B1	1/2011			
	KR		10-2011-0012784 A	9/2011			
	KR		10-2012-0033526 A	4/2012			
	KR		20130024468 A	3/2013			
	KR		10-2013-0111713 A	11/2013			
	RU		2008-129670 A	1/2010			
	WO		90-00366 A1	1/1990			
	WO		2004107971 A2	12/2004			
	WO		2006-018833 A2	2/2006			
	WO		2006-018833 A3	3/2006			
	WO		2007-072239 A2	6/2007			
	WO		2007-072239 A3	10/2007			
	WO		2010/120945 A1	10/2010			
	WO		2010120945 A1	10/2010			
	WO		2011/109716 A2	9/2011			
	WO		2013/175314 A2	11/2013			
	WO		2013175314 A2	11/2013			
OTHER PUBLICATIONS							
International Search Report corresponding to International Patent Application No. PCT/IB2014/003257, dated Jan. 11, 2016.							
Written Opinion of the International Searching Authority corresponding to International Patent Application No. PCT/IB2014/003257, dated Jan. 11, 2016.							
Communication with extended European Search Report corresponding to European Application No. 14196858.6, dated Jun. 25, 2015 (11 pages).							
Communication with European Examination Report corresponding to European Application No. 14196858.6, dated Oct. 6, 2016, (5 pages).							
International Search Report corresponding to International Patent Application No. PCT/IB2014/003245, dated Jul. 29, 2015.							
Notification of Transmittal of The International Search Report and the Written Opinion of the International Searching Authority, or the Declaration corresponding to International Patent Application No. PCT/IB2014/003245, dated Jul. 29, 2015.							
Written Opinion of the International Searching Authority corresponding to International Patent Application No. PCT/IB2014/003245, dated Jul. 29, 2015.							
Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration corresponding to International Application No. PCT/IB2015/001997, dated Mar. 3, 2016.							
International Search Report corresponding to International Application No. PCT/IB2015/001997, dated Mar. 3, 2016.							
Written Opinion of the International Searching Authority, or the Declaration corresponding to International Application No. PCT/IB2015/001997, dated Mar. 3, 2016.							

(58)	Field of Classification Search		
	CPC ...	A61B 5/7264; A61B 5/7445; A61B 5/0022; A61B 5/0024; A61B 5/01; A61B 5/02055; A61B 5/0408; A61B 5/0533; A61B 5/742; A61B 2560/0214; A61B 2560/0223; A61B 2560/0247; A61B 2560/0443; A61B 2560/0475; A61B 2562/0219; A61B 2562/0257; A61B 2562/028; A61B 2562/164	
	See application file for complete search history.		
(56)	References Cited		
	U.S. PATENT DOCUMENTS		
	7,127,432 B2	10/2006	Rubin et al.
	7,512,985 B1	3/2009	Grabarnik et al.
	7,618,260 B2	11/2009	Daniel
	7,894,888 B2	2/2011	Chan et al.
	8,251,903 B2	8/2012	LeBoeuf
	8,504,145 B2	8/2013	Kuroda et al.
	8,618,930 B2	12/2013	Papadopoulos
	8,647,268 B2	2/2014	Tran
	8,965,498 B2 *	2/2015	Katra A61B 5/0537
			600/382
	9,592,007 B2 *	3/2017	Nuovo A61B 5/0022
	2003/0212336 A1	11/2003	Lee et al.
	2007/0040449 A1	2/2007	Spurlin et al.
	2007/0279852 A1 *	12/2007	Daniel A44C 5/0007
			361/679.03
	2008/0171945 A1	7/2008	Dotter
	2008/0294058 A1	11/2008	Shklarski
	2009/0018409 A1	1/2009	Banet
	2009/0048526 A1	2/2009	Aarts et al.
	2009/0163820 A1	6/2009	Eerden
	2009/0270743 A1	10/2009	Dugan et al.
	2009/0306485 A1	12/2009	Bell
	2009/0322513 A1	12/2009	Hwang et al.
	2010/0076331 A1	3/2010	Chan et al.
	2010/0210956 A1	8/2010	Im
	2010/0267361 A1	10/2010	Sullivan
	2010/0306854 A1	12/2010	Neergaard
	2011/0066049 A1 *	3/2011	Matsumoto A61B 5/02438
			600/500
	2011/0213255 A1	9/2011	Finburgh
	2011/0234160 A1	9/2011	Smith
	2011/0245630 A1	10/2011	St Pierre

(56)

References Cited

OTHER PUBLICATIONS

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration corresponding to International Application No. PCT/IB2015/001559, dated Jan. 20, 2016.

International Search Report corresponding to International Application No. PCT/IB2015/001559, dated Jan. 20, 2016.

Written Opinion of the International Searching Authority, or the Declaration corresponding to International Application No. PCT/IB2015/001559, dated Jan. 20, 2016.

Mare et al., Hide-n-sense: preserving privacy efficiently in wireless mhealth, *Mobile Networks and Applications* 19.3 (Jun. 2014): 331-344. DOI: <http://dx.doi.org/10.1007/s11036-013-0447-x> ProQuest document ID: 1540736834 Jun. 1, 2014.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration corresponding to International Application No. PCT/IB2015/001979, dated Mar. 3, 2016.

International Search Report corresponding to International Application No. PCT/IB2015/001979, dated Mar. 3, 2016.

Written Opinion of the International Searching Authority, or the Declaration corresponding to International Application No. PCT/IB2015/001979, dated Mar. 3, 2016.

Notification Concerning Transmittal of International Preliminary Report on Patentability dated Apr. 20, 2017 with International Preliminary Report on Patentability corresponding to International Application No. PCT/IB2015/001997.

Examination Report dated Jun. 9, 2017 corresponding to EP Application No. 14196858.6.

Notification Concerning Transmittal of International Preliminary Report on Patentability with International Preliminary Report on Patentability corresponding to PCT/IB2015/001559, dated Dec. 8, 2016 and Written Opinion of the International Searching Authority dated Jan. 20, 2016.

"Blocks modular smartwatch: Like Project Ara for your wrist," W.Shanklin, *Gizmag*, Mar. 6, 2014, <http://newatlas.com/blocks-modular-smartwatch/31113>.

"A Survey on Wearable Sensor-Based Systems for Health Monitoring and Prognosis," A. Pantelopoulous and N.G. Bourbakis, *IEEE Transactions on Systems, Man and Cybernetics*, vol. 40, No. 1, Jan 2010.

"Multisensor Fusion in Smartphones for Lifestyle Monitoring," R.K. Ganti, S. Srinivasan, and A. Gacic, *International Conference on Body Sensor Networks*, 2010.

"A 5.2mW Self-Configured Wearable Body Sensor Network Controller and a 12uW Wireless Powered Sensor for a Continuous Health Monitoring System," J.Yoo, L.Yan, S.Lee, Y.Kim, and H-J Yoo, *IEEE Journal of Solid-state Circuits*, vol. 45, No. 1, Jan. 2010.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3

Modular Wearable Sensor Platform 10





FIG. 4

**FIG. 5**




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18

ADJUSTABLE WEARABLE SYSTEM HAVING A MODULAR SENSOR PLATFORM

RELATED APPLICATIONS

This application claims priority to U.S. Provisional Patent Application No. 62/061,290, filed Oct. 8, 2014, and is Continuation-in-Part of U.S. Non-Provisional patent application Ser. No. 14/719,043, filed May 21, 2015, which claims priority to U.S. Provisional Patent Application No. 62/002,589, filed May 23, 2014. The above-identified applications are hereby incorporated herein by reference in their entirety.

BACKGROUND

The disclosure relates to a wearable device for monitoring and communicating physiological information of an individual, among other things and in particular, a wearable modular sensor platform that is adjustable about a body part.

Over the years many types of watch bands, jewelry bands, magnetic health bands, bracelets and necklaces have been marketed. Wearable devices equipped with sensors are known that may track in some fashion user data, such as activity data (duration, step count, calories burned), sleep statistics, and/or physiological data (e.g., heart rate, perspiration and skin temperature). These conventional devices, however, often are very delicate and/or too flimsy or too rigid, and do not hold up well to physical exercise, fitness activities and sports, let alone the rigors of reliable sensor measurements sufficient, for example, health care monitoring on long-term basis.

Additionally, existing wearable devices have a number of disadvantages. They are generally bulky, uncomfortable and poorly suited for long-term use on an outpatient or personal basis. Such devices are also not well suited for long-term wear by infants or uncooperative patients, such as a patient with schizophrenia who may unexpectedly remove existing sensors. Nor are such wearable devices well suited for animals that are ambulatory or that require monitoring for a long period. Aside from those disadvantages, the wearable devices to date have not been suitable as a lifestyle product that also is capable of sensitive physiological and environmental measurements, processing and communications.

Another disadvantage is that existing sensors have cumbersome electrodes. As a result, such devices are generally encased in relatively large plastic shell cases and are not comfortable or suitable for wearing for more than a few hours, and as such, lack certain advantages of more suitable locations for physiological measurements. In the case of a watch, the sensors are typically located on the top of the wrist with the display. In these devices, continuous and long term wear is not practical because, among other things, using rubberized electrodes, standard metal medical electrodes and the related adhesive pads are uncomfortable, particularly when used on older users and those with sensitive skin. Continuous wearing of these devices also tends to cause skin irritation if the portion of the skin contacted is not suitably exposed to air for days or weeks during use.

Certain sensor arrangements with a wearable device can be cumbersome for another reason. For example, some measurements (e.g. skin conductance) commonly require additional electrodes that are clamped on the fingertips or that use adhesive patches separate from the wearable devices. In these circumstances, severe limits are placed on the user's ability to perform other daily tasks.

Disadvantages with such sensor arrangements are compounded by the fact that given body parts (e.g. wrist, neck, ankle, chest, waist or head) are not the same size and shape for all users. Wearable devices to date adjust asymmetrically (e.g. belt buckle-type bands). Other bands to date that are one piece bands do not address pressure (too much or too little) applied on the skin as the size of the body part increases for a larger person relative to smaller person, or vice versa. That is, these approaches to adjustment of wearable also can make the device uncomfortable to wear due to tightness or looseness when sensors are involved. Additionally, movement of the device on a body part tends to reposition sensors and displays making the measurements and display of measurements less convenient or reliable. Discomfort may lead to movement of the device out of preferred position to reduce pain or irritation of the skin. In short, movement of the device may lead to less than accurate measurements, which can be disadvantageous to a device for long term use.

A further disadvantage is that existing systems with wireless connectivity, for example, generally exhibit a short battery life. They are not suitable for continuous or long term wireless transmission for more than a few hours. Continuous physiological data collection may be necessary, however, over days, weeks and months in cases, for example, where chronic conditions exist (e.g. sleep disorders, diabetes, etc.). Existing wireless devices have a further disadvantage of being generally limited to a single user and do not support robust data collection and analysis remote of the device. In addition, existing devices generally do not provide much more than rudimentary board data analysis.

In short, devices to date do not address the size and comfort issues (e.g. flexibility, airflow, smooth contact area, skin irritation) to allow wearing of the device for continuous or long-term use in a small, compact and lightweight form factor, that is also accurate, continuously usable, and non-invasive and/or that can also consistently maintain comfortable positioning under varying user physiology and environmental conditions. Those devices also do not employ a full array of sensor capabilities (e.g., ECG, glucose, blood pressure, hydration, etc.) in a singular modular sensor platform. These sensor capabilities do not deliver reliable medical-grade readings for the less than optimal environments that such devices can be used or for the rigors of dynamic use. These devices also do not harness the insight that daily data acquisition about the body can provide the user or a healthcare professional which require suitable processing power. Suitable processing power requires adequate battery life in a wearable 24/7 device, which wearable devices do not achieve. Moreover, these devices have not confronted the privacy and security issues associated with the communication of health-related data.

BRIEF SUMMARY

According to implementations of the present invention, a wearable system and methods for measuring physiological data from a device worn about a body part of a user is provided comprising a base module, a first sensor module, and a second sensor module. The base module comprises a display and a base computing unit. The first sensor module measures a gravitational force experienced by the device. The second sensor module is spatially positioned relative to the base module and over a portion of the body part for measuring one or more physiological characteristics calibrated based on the gravitational force measured with the first sensor module. The base module is adjustably posi-

tioned by the user relative to the second sensor module such that the sensor module maintains its positioning over the body part for sufficient contact with the body part for accurate measurements of physiological data regardless of the anthropometric size of the body part.

BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWINGS

The features and utilities described in the foregoing brief summary, as well as the following detailed description of certain embodiments of the present general inventive concept below, will be better understood when read in conjunction with the accompanying drawings of which:

The features and utilities described in the foregoing brief summary, as well as the following detailed description of certain embodiments of the present general inventive concept below, will be better understood when read in conjunction with the accompanying drawings of which:

FIG. 1 is a diagram illustrating an embodiment of a modular sensor platform.

FIG. 2 is an embodiment of the modular sensor platform of FIG. 1.

FIG. 3 is a diagram illustrating another embodiment of a modular sensor platform.

FIG. 4 is a block diagram illustrating one embodiment of the modular sensor platform, including a bandwidth sensor module in connection with components comprising the base computing unit and battery.

FIG. 5 is a cross-sectional illustration of the wrist with a band mounted sensor in contact for an embodiment used about the wrist.

FIG. 6 is a diagram illustrating another embodiment of a modular sensor platform with a self-aligning sensor array system in relation to use about the wrist.

FIG. 7 is a block diagram illustrating components of the modular sensor platform including example sensors and an optical electric unit self-aligning sensor array system in a further embodiment.

FIG. 8 illustrates an embodiment of a side view of the adjustable wearable system with a sensor module positioned on the band.

FIG. 9 illustrates a side view of the adjustable wearable system with a sensor module integral to the band.

FIG. 10 illustrates a side view of another embodiment of the adjustable wearable system with a sensor module where the band over straps the sensor module.

FIG. 11 illustrates a side view of another embodiment of the view of the adjustable wearable system with a modular sensor module with a segmented band connected by flex connections.

FIG. 12 illustrates another embodiment of view of the adjustable wearable system with a self-adhering sensor module symmetrically disposed from a self-adhering display unit.

FIG. 13 illustrates a perspective view of an embodiment of the view of the adjustable wearable system with a sensor module comprising a micro-adjustable sensor configuration in a first position.

FIG. 14 illustrates another embodiment of the adjustable wearable system with a sensor module comprising a micro-adjustable sensor configuration in a second position relative to that shown in FIG. 13.

FIG. 15 illustrates a perspective view of an embodiment of the view of the adjustable wearable system with a sensor module comprising a rotatable sensor unit configuration in a first position.

FIG. 16 illustrates another embodiment of the adjustable wearable system with a sensor module comprising a rotatable sensor unit configuration in a second position relative to that shown in FIG. 15.

FIG. 17 illustrates a perspective view of an embodiment of the view of the adjustable wearable system with a sensor module comprising a sliding sensor unit configuration in a first position.

FIG. 18 illustrates another embodiment of the adjustable wearable system with a sensor module comprising a sliding sensor unit configuration in a second position relative to that shown in FIG. 17.

For the purpose of illustrating the general inventive concept of the invention, certain embodiments are shown in the drawings. It should be understood, however, that the present invention is not limited to the arrangements and instrumentality shown in the attached drawings.

DETAILED DESCRIPTION

Reference will now be made in detail to the embodiments of the present general inventive concept, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to the like elements throughout. The embodiments are described below in order to explain the present general inventive concept while referring to the figures.

Before any embodiments of the invention are explained in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of components set forth in the following description or illustrated in the drawings.

Advantages and features of the present invention and methods of accomplishing the same may be understood more readily by reference to the following detailed description and the drawings. The present general inventive concept may, however, be embodied in many different forms of being practiced or of being carried out in various ways and should not be construed as being limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete and will fully convey the general inventive concept to those skilled in the art, and the present general inventive concept is defined by the appended claims. In the drawings, the thickness of layers and regions are exaggerated for visual clarity.

Also, the phraseology and terminology used in this document are for the purpose of description and should not be regarded as limiting. The use of the terms "a" and "an" and "the" and similar referents in the context of describing the invention (especially in the context of the following claims) are to be construed to cover both the singular and the plural, unless otherwise indicated herein or clearly contradicted by context. The terms "comprising," "having," "including," and "containing" are to be construed as open-ended terms (i.e., meaning "including, but not limited to,") unless otherwise noted.

As should also be apparent to one of ordinary skill in the art, the systems shown in the figures are models of what actual systems might be like. Some of the modules and logical structures described are capable of being implemented in software executed by a microprocessor or a similar device, or of being implemented in hardware using a variety of components including, for example, application specific integrated circuits ("ASICs"). A term like "processor" may include or refer to both hardware and/or software. No specific meaning is implied or should be inferred simply due to the use of capitalization.

Likewise, the term “component” or “module”, as used herein, means, but is not limited to, a software or hardware component, such as a field programmable gate array (FPGA) or ASIC, which performs certain tasks. A component or module may advantageously be configured to reside in the addressable storage medium and configured to execute on one or more processors. Thus, a component or module may include, by way of example, components, such as software components, object-oriented software components, class components and task components, processes, functions, attributes, procedures, subroutines, segments of program code, drivers, firmware, microcode, circuitry, data, databases, data structures, tables, arrays, and variables. The functionality provided for the components and components or modules may be combined into fewer components and components or modules or further separated into additional components and components or modules.

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. Further, unless defined otherwise, all terms defined in generally used dictionaries should have their ordinary meaning. It is noted that the use of any and all examples, or exemplary terms provided herein is intended merely to better illuminate the general inventive concept and is not a limitation on the scope of the invention unless otherwise specified.

Embodiments of the invention relate to a system for providing a wearable device for monitoring an electrocardiogram (ECG) through a wrist of a user.

FIGS. 1 and 2 are diagrams illustrating embodiments of a modular sensor platform or wearable sensor platform 10. FIGS. 1 and 2 depict a perspective view of embodiments of the wearable sensor platform 10, while FIG. 3 depicts an exploded side view of another embodiment of the wearable sensor platform 10. Although the components of the wearable sensor platform in FIGS. 1 and 2 may be substantially the same, the locations of modules and/or components may differ.

In the embodiment shown in FIG. 1, the wearable sensor platform 10 may be implemented as a smart watch or other wearable device that fits on part of a body, here a user's wrist.

The wearable sensor platform 10 may include a base module 18, a strap or a band 12, a clasp 34, a power source, a removable power source, or a battery 22, and a removable sensor module, a micro-adjustable sensor module, or a sensor module 16 coupled to the band 12. In some embodiments, the modules and/or components of the wearable sensor platform 10 may be removable by an end user (e.g., a consumer, a patient, a doctor, etc.). However, in other embodiments, the modules and/or components of the wearable sensor platform 10 are integrated into the wearable sensor platform 10 by the manufacturer and may not be intended to be removed by the end user. The wearable sensor platform 10 may be waterproof or water sealed.

The band 12 may be one-piece or modular. The band 12 may be made of a fabric. For example, a wide range of twistable and expandable elastic mesh/textiles are contemplated. The band 12 may also be configured as a multi-band or in modular links. The band 12 may include a latch or a clasp mechanism to retain the watch in place in certain implementations. In certain embodiments, the band 12 will contain wiring (not shown) connecting, among other things, the base module 18 and sensor module 16. Wireless communication, alone or in combination with wiring, between base module 18 and sensor module 16 is also contemplated.

The sensor module 16 may be removably attached on the band 12, such that the sensor module 16 is located at the bottom of the wearable sensor platform 10 or, said another way, on the opposite end of the base module 18. Positioning the sensor module 16 in such a way to place it in at least partial pressure contact with the skin on the underside of the user's wrist to allow the sensor units 28 to sense physiological data from the user. The contacting surface(s) of the sensor units 28 may be positioned above, at or below, or some combination such positioning, the surface of the sensor module 16.

The base module 18 attaches to the band 12 such that the base module 18 is positioned at top of the wearable sensor platform 10. Positioning the base module 18 in such a way to place it in at least partial contact with the top side of the wrist.

The base module 18 may include a base computing unit 20, and a graphical user interface (GUI) or a display 26 on which a graphical user interface (GUI) may be provided. The base module 18 performs functions including, for example, displaying time, performing calculations and/or displaying data, including sensor data collected from the sensor module 16. In addition to communication with the sensor module 16, the base module 18 may wirelessly communicate with other sensor module(s) (not shown) worn on different body parts of the user to form a body area network, or with other wirelessly accessible devices (not shown), like a smartphone, tablet, display or other computing device. As will be discussed more fully with respect to FIG. 4, the base computing unit 20 may include a processor 36, memory 38, input/output 40, a communication interface 42, a battery 22 and a set of sensors 44, such as an accelerometer/gyroscope 46 and thermometer 48. In other embodiments, the base module 18 can also be other sizes, cases, and/or form factors, such as, for example, oversized, in-line, round, rectangular, square, oval, Carre, Carage, Tonneau, asymmetrical, and the like.

The sensor module 16 collects data (e.g., physiological, activity data, sleep statistics and/or other data), from a user and is in communication with the base module 18. The sensor module 16 includes sensor units 28 housed in a sensor plate 30. For certain implementations, because a portable device, such as a wristwatch, has a very small volume and limited battery power, sensor units 28 of the type disclosed may be particularly suited for implementation of a sensor measurement in a wristwatch. In some embodiments, the sensor module 16 is adjustably attached to the band 12 such that the base module 18 is not fixedly positioned, but can be configured differently depending on the physiological make-up of the wrist.

The sensor units 28 may include an optical sensor array, a thermometer, a galvanic skin response (GSR) sensor array, a bioimpedance (BioZ) sensor array, an electrocardiogram or electrocardiography (ECG) sensor, or any combination thereof. The sensors units 28 may take information about the outside world and supply it to the wearable sensor platform 10. The sensor units 28 can also function with other components to provide user or environmental input and feedback to a user. For example, a MEMS accelerometer may be used to measure information such as position, motion, tilt, shock, and vibration for use by processor 36. Other sensor(s) may also be employed. The sensor module 16 may also include a sensor computing unit 32. The sensor units 28 may also include biological sensors (e.g., pulse, pulse oximetry, body temperature, blood pressure, body fat, etc.), proximity detec-

tors for detecting the proximity of objects, and environmental sensors (e.g., temperature, humidity, ambient light, pressure, altitude, compass, etc.).

In other embodiments, the clasp 34 also provides an ECG electrode. One or more sensor units 28 and the ECG electrode on the clasp 34 can form a complete ECG signal circuit when the clasp 34 is touched. The sensor computing unit 32 may analyze data, perform operations (e.g., calculations) on the data, communicate data and, in some embodiments, may store the data collected by the sensor units 28. In some embodiments, the sensor computing unit 32 receives (for example, data indicative of an ECG signal) from one or more of the sensors of the sensor units 28, and processes the received data to form a predefined representation of a signal (for example, an ECG signal).

The sensor computing unit 32 can also be configured to communicate the data and/or a processed form of the received data to one or more predefined recipients, for example, the base computing unit 20, for further processing, display, communication, and the like. For example, in certain implementations the base computing unit 20 and/or sensor computing unit determine whether data is reliable and determine an indication of confidence in the data to the user.

Because the sensor computing unit 32 may be integrated into the sensor plate 30, it is shown by dashed lines in FIG. 1. In other embodiments, the sensor computing unit 32 may be omitted or located elsewhere on the wearable sensor platform 10 or remotely from the wearable sensor platform 10. In an embodiment where the sensor computing unit 32 may be omitted, the base computing unit 20 may perform functions that would otherwise be performed by the sensor computing unit 32. Through the combination of the sensor module 16 and base module 18, data may be collected, transmitted, stored, analyzed, transmitted and presented to a user.

The wearable sensor platform 10 depicted in FIG. 1 is analogous to the wearable sensor platform 10 depicted in FIGS. 2 and 3. Thus, the wearable sensor platform 10 includes a band 12, a battery 22, a clasp 34, a base module 18 including a display 26, a base computing unit 20, and a sensor module 16 including sensor units 28, a sensor plate 30, and an optional sensor computing unit 32. However, as can be seen in FIG. 3, the locations of certain modules have been altered. For example, the clasp 34 is closer in FIG. 3 to the display/GUI 26 than clasp 34 is in FIG. 1. Similarly, in FIG. 3, the battery 22 is housed with the base module 18. In the embodiment shown in FIG. 1, the battery 22 is housed on the band 12, opposite to the display 26. However, it should be understood that, in some embodiments, the battery 22 charges the base module 18 and optionally an internal or permanent battery (not shown) of the base module 18. In this way, the wearable sensor platform 10 may be worn continuously. Thus, in various embodiments, the locations and/or functions of the modules and other components may be changed.

FIG. 3 is a diagram illustrating one embodiment of a modular sensor platform 10 and components comprising the base module 18. The wearable sensor platform 10 is analogous to the wearable sensor platform 10 in FIGS. 1 and 2 and thus includes analogous components having similar reference labels. In this embodiment, the wearable sensor platform 10 may include a band 12, and a sensor module 16 attached to band 12. The sensor module 16 may further include a sensor plate 30 attached to the band 12, and sensor units 28 attached to the sensor plate 30. The sensor module 16 may also include a sensor computing unit 32.

The wearable sensor platform 10 includes a base computing unit 20 in FIG. 3 analogous to the base computing unit 20 and one or more batteries 22 in FIG. 3. For example, permanent and/or removable batteries 22 that are analogous to the battery 22 in FIGS. 1 and 2 may be provided. In one embodiment, the base computing unit 20 may communicate with or control the sensor computing unit 32 through a communication interface 42. In one embodiment, the communication interface 42 may comprise a serial interface. The base computing unit 20 may include a processor 36, a memory 38, input/output (I/O) 40, a display 26, a communication interface 42, sensors 44, and a power management unit 88.

The processor 36, the memory 38, the I/O 40, the communication interface 42 and the sensors 44 may be coupled together via a system bus (not shown). The processor 36 may include a single processor having one or more cores, or multiple processors having one or more cores. The processor 36 may be configured with the I/O 40 to accept, receive, transduce and process verbal audio frequency command, given by the user. For example, an audio codec may be used. The processor 36 may execute instructions of an operating system (OS) and various applications 90. The processor 36 may control on command interactions among device components and communications over an I/O interface. Examples of the OS 90 may include, but not limited to, Linux Android™, Android Wear, and Tizen OS.

The memory 38 may comprise one or more memories comprising different memory types, including RAM (e.g., DRAM and SRAM) ROM, cache, virtual memory micro-drive, hard disks, microSD cards, and flash memory, for example. The I/O 40 may comprise a collection of components that input information and output information. Example components comprising the I/O 40 having the ability to accept inputted, outputted or other processed data include a microphone, messaging, camera and speaker. I/O 40 may also include an audio chip (not shown), a display controller (not shown), and a touchscreen controller (not shown). In the embodiment shown in FIG. 4, the memory 38 is external to the processor 36. In other embodiments, the memory 38 can be an internal memory embedded in the processor 36.

The communication interface 42 may include components for supporting one-way or two-way wireless communications and may include a wireless network interface controller (or similar component) for wireless communication over a network in some implementations, a wired interface in other implementations, or multiple interfaces. In one embodiment, the communication interface 42 is for primarily receiving data remotely, including streaming data, which is displayed and updated on the display 26. However, in an alternative embodiment, besides transmitting data, the communication interface 42 could also support voice transmission. In an exemplary embodiment, the communication interface 42 supports low and intermediate power radio frequency (RF) communications. In certain implementations, example types of wireless communication may include Bluetooth Low Energy (BLE), WLAN (wireless local area network), WiMAX, passive radio-frequency identification (RFID), network adapters and modems. However, in another embodiment, example types of wireless communication may include a WAN (Wide Area Network) interface, Wi-Fi, WPAN, multi-hop networks, or a cellular network such as 3G, 4G, 5G or LTE (Long Term Evolution). Other wireless options may include ultra-wide band (UWB) and infrared, for example. The communication interface 42 may also include other types of communications devices

(not shown) besides wireless, such as serial communications via contacts and/or USB communications. For example, a micro USB-type USB, flash drive, or other wired connection may be used with the communication interface 42.

In one embodiment, the display 26 may be integrated with the base computing unit 20; while in another embodiment, the display 26 may be external from the base computing unit 20. Display 26 may be flat or curved, e.g., curved to the approximate curvature of the body part on which the wearable sensor platform 10 is located (e.g., a wrist, an ankle, a head, etc.).

Display 26 may be a touch screen or gesture controlled. The display 26 may be an OLED (Organic Light Emitting Diode) display, TFT LCD (Thin-Film-Transistor Liquid Crystal Display), or other appropriate display technology. The display 26 may be active-matrix. An example of the display 26 may be an AMOLED display or SLCD. The display may be 3D or flexible. The sensors 44 may include any type of microelectromechanical systems (MEMS) sensor. Such sensors may include an accelerometer/gyroscope 46 and a thermometer 48, for instance.

The power management unit 88 may be coupled to the power source 22 and may comprise a microcontroller that communicates and/or controls power functions of at least the base computing unit 20. Power management unit 88 communicates with the processor 36 and coordinates power management. In some embodiments, the power management unit 88 determines if a power level falls below a certain threshold level. In other embodiments, the power management unit 88 determines if an amount of time has elapsed for secondary charging.

The power source 22 may be a permanent or removable battery, fuel cell or photo voltage cell, etc. The battery 22 may be disposable. In one embodiment, the power source 22 may comprise a rechargeable, lithium ion battery or the like may be used, for example. The power management unit 88 may include a voltage controller and a charging controller for recharging the battery 22. In some implementations, one or more solar cells may be used as a power source 22. The power source 22 may also be powered or charged by AC/DC power supply. The power source 22 may charge by non-contact or contact charging. In one embodiment, the power management unit 88 may also communicate and/or control the supply of battery power to the sensor module 16 via power interface 52. In some embodiments, the battery 22 is embedded in the base computing unit 20. In other embodiments, the battery 22 is external to the base computing unit 20.

Other wearable device configurations may also be used. For example, the wearable sensor system 10 can be worn on the upper arm, waist, finger, ankle, neck chest or foot for example. That is, the wearable sensor platform 10 can be implemented as a leg or arm band, a chest band, a wrist-watch, a head band, an article of clothing worn by the user such as a snug fitting shirt, or any other physical device or collection of devices worn by the user that is sufficient to ensure that the sensor units 28 are in contact with approximate positions on the user's skin to obtain accurate and reliable data.

FIG. 5 is a diagram of a cross section of a wrist 14. More specifically, by way of example, FIG. 6 is a diagram illustrating an implementation of the wearable sensor platform 10. The top portion of FIG. 6 illustrates the wearable sensor platform 10 wrapped around a cross-section of a user's wrist 14, while the bottom portion of FIG. 6 shows the band 12 in an flattened position.

According to this embodiment, the wearable sensor platform 10 includes at least an optical sensor array 54, and may also include optional sensors, such as a galvanic skin response (GSR) sensor array 56, a bioimpedance (BioZ) sensor array 58, and an electrocardiogram (ECG) sensor 60, or any combination of which may comprise a sensor array.

According to another embodiment, the sensor units 28 configured as a sensor array(s) comprising an array of discrete sensors that are arranged or laid out on the band 12, such that when the band 12 is worn on a body part, each sensor array may straddle or otherwise address a particular blood vessel (i.e., a vein, artery, or capillary), or an area with higher electrical response irrespective of the blood vessel.

More particularly, as can be seen in FIGS. 5 and 6, the sensor array may be laid out substantially perpendicular to a longitudinal axis of the blood vessel (e.g., radial artery 14R and/or ulnar artery 14U) and overlaps a width of the blood vessel to obtain an optimum signal. In one embodiment, the band 12 may be worn so that the sensor units 28 comprising the sensor array(s) contact the user's skin, but not so tightly that the band 12 is prevented from any movement over the body part, such as the user's wrist 14, or creates discomfort for the user at sensor contact points.

In another embodiment, the sensor units 28 may comprise an optical sensor array 54 that may comprise a photoplethysmograph (PPG) sensor array that may measures relative blood flow, pulse and/or blood oxygen level. In this embodiment, the optical sensor array 54 may be arranged on sensor module 16 so that the optical sensor array 54 is positioned in sufficient proximity to an artery, such as the radial or ulnar artery, to take adequate measurements with sufficient accuracy and reliability.

Further details of the optical sensor array 54 will now be discussed. In general, configuration and layout of each of the discrete optical sensors 55 may vary greatly depending on use cases. In one embodiment, the optical sensor array 54 may include an array of discrete optical sensors 55, where each discrete optical sensor 55 is a combination of at least one photodetector 62 and at least two matching light sources 64 located adjacent to the photodetector 62. In one embodiment, each of the discrete optical sensors 55 may be separated from its neighbor on the band 12 by a predetermined distance of approximately 0.5 to 2 mm.

In one embodiment, the light sources 64 may each comprise a light emitting diode (LED), where LEDs in each of the discrete optical sensors 55 emit light of a different wavelength. Example light colors emitted by the LEDs may include green, red, near infrared, and infrared wavelengths. Each of the photodetectors 62 convert received light energy into an electrical signal. In one embodiment, the signals may comprise reflective photoplethysmograph signals. In another embodiment, the signals may comprise transmittance photoplethysmograph signals. In one embodiment, the photodetectors 62 may comprise phototransistors. In alternative embodiment, the photodetectors 62 may comprise charge-coupled devices (CCD).

FIG. 7 is a block diagram illustrating another configuration for components of wearable sensor module in a further implementation. In this implementation, the ECG 60, the bioimpedance sensor array 58, the GSR array 56, the thermometer 48, and the optical sensor array 54 may be coupled to an optical-electric unit 66 that controls and receives data from the sensors on the band 12. In another implementation, the optical-electric unit 66 may be part of the band 12. In an alternative implementation, the optical-electric unit 66 may be separate from the band 12.

The optical-electric unit **66** may comprise an ECG and bioimpedance (BIOZ) analog front end (AFE) **76, 78**, a GSR AFE **70**, an optical sensor AFE **72**, a processor **36**, an analog-to-digital converter (ADC) **74**, a memory **38**, an accelerometer/gyroscope **46**, a pressure sensor **80** and a power source **22**.

As used herein, an AFE **68** may comprise an analog signal conditioning circuitry interface between corresponding sensors and the ADC **74** or the processor **36**. The ECG and BIOZ AFE **76, 78** exchange signals with the ECG **60** and the bioimpedance sensor array **58**. The GSR AFE **70** may exchange signals with the GSR array **56** and the optical sensor AFE **72** may exchange signals with the optical sensor array **54**. In one embodiment, the GSR AFE **70**, the optical sensor AFE **72**, the accelerometer/gyroscope **46**, and the pressure sensor **80** may be coupled to the ADC **74** via bus **86**. The ADC **74** may convert a physical quantity, such as voltage, to a digital number representing amplitude.

In one embodiment, the ECG and BIOZ AFE **76, 78**, memory **38**, the processor **36** and the ADC **74** may comprise components of a microcontroller **82**. In one embodiment, the GSR AFE **70** and the optical sensor AFE **72** may also be part of the microcontroller **82**. The processor **36** in one embodiment may comprise a reduced instruction set computer (RISC), such as a Cortex 32-bit RISC ARM processor core by ARM Holdings, for example. In the embodiment shown in FIG. 7, the memory **38** is an internal memory embedded in the microcontroller **82**. In other embodiments, the memory **38** can be external to the microcontroller **82**.

According to an exemplary embodiment, the processor **36** may execute a calibration and data acquisition component **84** that may perform sensor calibration and data acquisition functions. In one embodiment, the sensor calibration function may comprise a process for self-aligning one more sensor arrays to a blood vessel. In one embodiment, the sensor calibration may be performed at startup, prior to receiving data from the sensors, or at periodic intervals during operation.

In another embodiment, the sensor units **28** may also comprise a galvanic skin response (GSR) sensor array **56**, which may comprise four or more GSR sensors that may measure electrical conductance of the skin that varies with moisture level. Conventionally, two GSR sensors are necessary to measure resistance along the skin surface. According to one aspect of this embodiment, the GSR sensor array **56** is shown including four GSR sensors, where any two of the four may be selected for use. In one embodiment, the GSR sensors **56** may be spaced on the band 2 to 5 mm apart.

In another embodiment, the sensor units **28** may also comprise bioimpedance (BioZ) sensor array **58**, which may comprise four or more BioZ sensors **59** that measure bioelectrical impedance or opposition to a flow of electric current through the tissue. Conventionally, only two sets of electrodes are needed to measure bioimpedance, one set for the “I” current and the other set for the “V” voltage. However, according to an exemplary embodiment, a bioimpedance sensor array **58** may be provided that includes at least four to six bioimpedance sensors **59**, where any four of electrodes may be selected for “I” current pair and the “V” voltage pair. The selection could be made using a multiplexor. In the embodiment shown, the bioimpedance sensor array **58** is shown straddling an artery, such as the Radial or Ulnar artery. In one embodiment, the BioZ sensors **59** may be spaced on the band 5 to 13 mm apart. In one embodiment, one or more electrodes comprising the BioZ sensors **59** may be multiplexed with one or more of the GSR sensors **56**.

In yet another embodiment, the band **12** may include one or more electrocardiogram (ECG) sensors **60** that measure electrical activity of the user’s heart over a period of time. In addition, the band **12** may also comprise a thermometer **48** for measuring temperature or a temperature gradient.

According to an exemplary embodiment of an adjustable sensor support structure, a series of sensors supported by flexible bridge structures may be serially connected edge-to-edge along a band. Such a band with bridge supported sensors may be worn, for example, about the wrist **14**. When worn about a measurement site such as the wrist **14**, the varying topology of the wrist **14** may cause force(s) to simultaneously be exerted upon the bridges due to compliance of the band to the varying topology of the wrist **14**.

Other kinds of devices can be used to provide for interaction with a user as well; for example, feedback provided to the user can be any form of sensory feedback (e.g., visual feedback, auditory feedback, or tactile feedback); and input from the user can be received in any form, including acoustic, speech, or tactile input.

Gravity is a force. It generally describes how objects interact relative to one another. For example, the gravitational force that the Earth exerts on a person ensures the person remains on the ground. Earth’s gravitational force is sometimes referred to as Earth’s g-force.

Micro-gravity or hypo-gravity generally refers to a condition where the gravitational force is smaller than that of Earth g-force. For example, the gravitational force exerted by the moon is only a fraction of the gravitational force exerted by the Earth’s g-force. By way of another example, when no artificial gravity is present, a person in space flight or on a space station is subject to microgravity. Similarly, super-gravity or hyper-gravity refers to a condition where the gravitational force is larger than that of the Earth’s g-force. For example, a person subject to g-forces in a spaceship on takeoff may be subject to super-gravity.

Biological processes are affected by variations in gravitational force. Variations in this force can have an impact on an organism’s health and function. For example, the human heart has evolved to pump blood against gravity to the head and upper torso and accept the benefits that Earth’s gravity provides in returning the blood to the heart and lungs or pumping blood to the lower extremities. For example, under micro-gravity, the heart’s normal pumping function leads to a phenomena called “puffy face syndrome,” where the veins of the neck and face appear expanded, the eyes become swollen and red, and the legs grow thinner because the heart does not have the benefit of Earth’s gravity and has to pump harder to get blood to the lower extremities and has less help from leg muscles.

As such, human physiological parameters (such as blood flow, blood volume, blood cell production, muscle mass and bone mass, for example) change under depending on what gravitational forces are exerted on the body. It is also known that clocks generally run differently in space-time dilation, and that light may also travel differently.

For example, it is known that blood flow of a jet pilot changes when the fighter jet is flying under varying “g” conditions. Space travel, and the varying gravitational conditions, will affect how blood flows in arteries of human under those conditions, and how some sensors, such as MEMS, measure certain parameters. Additionally, measurements that may employ light, such as the ECG signal, blood pressure and/or blood flow, may depend on time and light array behavior under varying gravitational conditions; that is, the accuracy of those sensors may also be affected by

physiological changes and/or how time and light are measured in micro- or super-gravity conditions.

In some embodiments, therefore, the sensors are configured to account for and operate in differing gravitational conditions. For example, the accelerometer/gyroscope **46** may be configured to measure a gravitational force, for example, micro-gravity, experienced by the wearable sensor platform **10**. The gravitational force measurement or data indicative of the measurement will be fed to one or more of the processor **36**, the galvanic skin response (GSR) sensor array **56**, the bioimpedance (BioZ) sensor array **58**, the electrocardiogram (ECG) sensor **60**, and/or the sensor units **28**. The processor **36**, the galvanic skin response (GSR) sensor array **56**, the bioimpedance (BioZ) sensor array **58**, the electrocardiogram (ECG) sensor **60**, and/or the sensor units **28** may then be calibrated based on the gravitational force data and/or the measurement. Similarly, based on the gravitational force measurement or data indicative of the measurement, the processor **36** may also be configured to determine a time differential and a light speed differential, and send one or more such differentials to one or more of the galvanic skin response (GSR) sensor array **56**, the bioimpedance (BioZ) sensor array **58**, the electrocardiogram (ECG) sensor **60**, and/or the sensor units **28** for further calibration due to time and light measurement differences.

The systems and techniques described here can be implemented in a computing system that includes a back end component (e.g., as a data server), or that includes a middleware component (e.g., an application server), or that includes a front end component (e.g., a client computer having a graphical user interface or a Web browser through which a user can interact with an implementation of the systems and techniques described here), or any combination of such back end, middleware, or front end components. The components of the system can be interconnected by any form or medium of digital data communication (e.g., a communication network). Examples of communication networks include a local area network ("LAN"), a wide area network ("WAN"), and the Internet.

The computing system can include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other. Various cloud-based platforms and/or other database platforms may be employed in certain implementations of the modular sensor platform **10** to, for example, receive and send data to the modular sensor platform **10**. One such implementation is architecture for multi-modal interactions (not shown). Such architecture can be employed as a layer of artificial intelligence between wearable devices, like modular sensor platform **10**, and the larger cloud of other devices, websites, online services, and apps. Such an architecture also may serve to translate (for example by monitoring and comparing) data from the modular sensor platform **10** with archived data, which may be then be used to alert, for example, the user or healthcare professional about changes in condition. This architecture further may facilitate interaction between the modular sensor platform **10** and other information, such as social media, sports, music, movies, email, text messages, hospitals, prescriptions to name a few.

FIGS. **8-12** illustrate several implementations of a wearable sensor platform **10** showing a sensor module **16** mounted on a band **12**. The wearable sensor platforms or systems **800**, **900**, **1000**, **1100** and **1200** are analogous to the wearable sensor platforms **10** and thus include analogous

components having similar labels. Each of the implementations illustrated may incorporate a removable power source **22**, and may include a wireless (or wired) communication capability between the sensor module **16** and the base module **18** or between the sensor module **16** and remote device or system (not shown). Likewise, as would be understood by an artisan, one or more implementations illustrated in FIGS. **8-12** may be employed in the implementations shown in FIGS. **1-3** depending on the desired use.

FIGS. **8-12** illustrate various embodiments that employ configurations that position the sensor module **16** relative to the display **26**, such that, as the anthropometric size of the body part increases (or decreases), the sensor module **16** is maintained in its optimal or near optimal position for suitable physiological measurements and user comfort over the period of use, while the display **26** maintains its position in relation to the body part over a large range of anthropometric sizes. For example, when the wearable sensor platform **10** is worn over the wrist, sensor module **16** maintains an optimal or near optimal position and pressure on the soft, underside of the wrist, while the display **26** maintains a user expected position on the topside of the wrist, regardless range of wrist sizes.

More specifically, in the implementation shown in FIG. **8**, the sensor module **816** is selectively removable, and further includes a sensor module **816** attached to the band **812**, and sensor units (not shown fully) attached to a sensor plate **830**. The sensor module **816** also includes a processor or a sensor computing unit (not shown) that is similar to the sensor computing unit **32** of FIGS. **1-3**.

The wearable sensor platform or system **800** is illustrated as including an optional smart device or base module **818**, a strap or a band **812**, a base computing unit **820**, a display/GUI **826**, and a sensor module **816** attached to the band **812**. In some other embodiments, the wearable sensor platform **800** does not include the optional base module **818**. In some embodiments, the base module **818** includes an interface (not shown) similar to the communication interface. In some embodiments, the modular wearable sensor platform or system **800** is a smart watch or a smart phone.

In various implementations, the band **812** may be configured to comfortably fit a range of different body parts with varying sizes (e.g., a head, a chest, a wrist, an ankle, a ring) for each unique user. For example, for a wrist, the band **812** may be symmetrically adjustable over a wide range of sizes for band **812** lengths ranging from about 135 mm for a small wrist to about 210 mm for a large wrist, and at the same time maintaining sufficient sensor unit **828** contact with the body part for reliable measurements and user comfort over the period of use (e.g., continuous, short or long-term). Such a band **812** may also include a plurality of sub-bands (not shown) that allows for similar symmetric adjustability around the body part and may also allow for more circulation of air in and around the wrist, thereby providing additional comfort. These sub-bands may be positioned in layers horizontally or vertically. Band **812** may also be of varying elasticity. For example, band **812** may have a less elastic region in or near the base module **818** and/or near the sensor module **816** and a more elastic region in the remaining portions of band **812**. Other material properties for band **812** are contemplated and should be appreciated by the artisan.

For example, the band **812** generally consists of chemically inert material, medical-grade material, hypoallergenic silicone, rubber, Graphene, and the like. The band **812** may comprise a material selected from the group consisting of:

15

elastomeric material, non-metallic material, non-magnetic metal, molded plastic, impact-resistant plastic, flexible plastic, plastic, rubber, wood, fabric, cloth, elastomeric material, or combinations of any of the preceding. The band **812** could be also made of a skin graft, artificial skin or other like fabric to provide a continuous skin-like feel and comfort. In some embodiments, the band **812** may employ textile-based wearable form factors (e.g. wrist and palm) made of breathable materials and avoiding hard bulky plastic materials. A flexible fabric could be moved to multiple positions. Such movement could avoid covering the same area of skin for too long with any non-breathable component. As such, a fabric band **812** may further provide added breathability and minimize risks of infection in a system for wearing continuously (24/7 use) in either short-term or longer-term applications. Additionally, the band **812** has a textured interior surface to minimize slipping. Band **812** may also include overlapping or intertwining straps with similar symmetric adjustability.

In the embodiment shown in FIG. **8**, both the sensor module **816** and, if employed, the removable power interface **822** (not shown in FIG. **8**) are contoured to conform to a body part, here, a wrist of a user. When the system **800** is worn over the wrist, the sensor module **816** may be in contact with the skin of the wrist. In some embodiments, the sensor module **816** is a flexible plate. In some embodiments, the sensor units **828** can be arranged, for example, to be spring loaded or co-molded in a flexible gel, to allow the sensor units **828** to contact the body part without adjusting the band to improve comfort and/or measurement reliability and accuracy. Additionally, the sensor module **816** may be worn with one type of band **812** during the day and inserted into and worn with a different type of band **812** during sleep.

The system **900** of FIG. **9** is analogous to the wearable sensor platforms **10** and system **800** of FIG. **8**. Thus, system **900** includes analogous components having similar labels. In FIG. **9**, band **912** in this implementation is similar to band **812**. Band **912** employs a sensor module **816** that is co-molded or integral to the band **912**. The sensor module **816** can may further have the sensor units **828** arranged in a flexible gel or similar fluid.

The system **1000** of FIG. **10** is analogous to the wearable sensor platforms **10** and systems **800** of FIG. **8** and **900** of FIG. **9**. Thus, system **1000** includes analogous components having similar labels. In FIG. **10**, band **1012** is similar to band **812** and **912**. Band **1012** is configured in this implementation as an overstrap arrangement so as to overlap sensor module **1016**. Other strap attaching arrangements are contemplated. Band **1012** may be releasably attached to the sensor module **1016**, and may be adjustable to accommodate different size of the body parts, while retaining appropriate positioning of the sensor module **1016** relative to the base module **1018**. The adjustability of sensor module **1016** can be accomplished through a variety of attachment mechanisms, for example, magnets, ratcheting, grooves, snaps and other ways to hold the sensor module **1016** in position that should be apparent to the artisan.

In one implementation, each flex connection **1192** slides into and out of each link of the band **1112**. In another implementation, the flex connections **1190** may be integral to the links of the band **1112**, where the links of the band **1112**, in turn, could be connected by various mechanisms to connect such links, e.g. watch links. In implementations employing links, sizing of the system **1100** about a body part can be further refined by removal or addition of links by a user, for example. Additionally, in implementations including a wireless communication between the sensor module

16

1116 and the base module **1118**, no wiring is needed between the modules, or power-only wiring between the sensor module **1116** and the base module **1118** may be employed. In other implementations, wiring arrangements for power and data communication may be employed between the sensor module **1116** and the base module **1118**.

The system **1200** of FIG. **12** is analogous to the wearable sensor platforms **10** and systems **800** of FIG. **8**, **900** of FIG. **9** and **1000** of FIG. **10** and **1100** of FIG. **11**. Thus, system **1200** includes analogous components having similar labels. In FIG. **12**, the base module **1218** and sensor module **1216** are self-adhering to the body part. In some implementations, a partial band **1212** as shown in FIG. **12** may employed with either the base module **1218** or the sensor module **1216** to further increase the surface area for improved adhesion to the body part. In other implementations, band **1212** is not employed.

It should appreciated that, in some implementations of the wearable sensor platforms **10** and systems **800-1200**, the display **1226** may be oriented toward or away from the sensor module **1216**. For example, a sensor module **1216** may be applied to the forehead of the user and the display may be oriented toward the user, for example, in the form of glasses for eyewear (not shown) or a helmet face shield (not shown). In other implementations, the sensor module **1216** may be configured as a skin-like tattoo that would adhere the sensor module **1216** to the skin of the forehead (or other body part), while the display **1226** may be a thin, flexible screen applied to the skin of the wrist (or other body part), where both may include a power source.

FIGS. **13** and **14** illustrate an embodiment using the implementation of FIG. **1**, and both FIGS. **13** and **14** include analogous components having similar labels. The implementation of FIGS. **13** and **14** may be employed in other implementations of the wearable sensor platform **10**. This implementation may be employed with or without the ECG clasp **1334**. In FIG. **13**, the sensor module **1316** is arranged to be microadjustable. The micro-adjustable sensor module **1316** of this implementation is positioned in a track in the band **1312**. The band **1312** is adjustable, manually or automatically, along the track of the band **1312** via a sensor module flex lead **1394**. In this implementation, the sensor module flex lead **1394** is shown as an accordion-like lead that allows adjustment along the track. FIG. **13** illustrates the sensor module **1316** in a first position, while FIG. **14** illustrates sensor module **1416** in a second position relative to the first position in FIG. **13**. Various other positions of the sensor module **1316** are possible within the track to accommodate the positioning of the sensor module for a given user.

Additionally, it should be understood that other implementations of the micro-adjustable sensor module **1316** are contemplated. For example, as illustrated in FIGS. **15** and **16**, instead of or in addition to employing the flex lead **1394** in FIG. **13** or other configuration for a micro-adjustable sensor module **1316**, one or more of the sensor units **1528** may be rotatable, manually or automatically, in the same or opposite rotational directions and the sensor units **1528** may be in sync or out of sync relative to each other depending on the application. Rotation of the sensor units **1528** may occur either individually, in combination with other sensor units **1528** or the sensor module **1516**, as illustrated in FIG. **15**, sensor module **1616**, as illustrated in FIG. **16**, may be moved along the track of the band **1512** having a clasp **1534** as illustrated in FIG. **15**, and **1612** having a clasp **1634** as illustrated in FIG. **16**, and the sensor units **1628** rotated. Such rotation may facilitate refined positioning of the sensor

17

units **1628** for improved comfort or improved physiological measurements depending on the body part.

FIGS. **17** and **18** illustrate an embodiment using the implementation of FIG. **1**, and both FIGS. **17** and **18** include analogous components having similar labels. The implementation of FIGS. **17** and **18** may be employed in other implementations of the wearable platform **10** (of FIG. **1**). In FIG. **17**, the micro-adjustable sensor module **16** (of FIG. **1**) is arranged on a sensor slide positioned in or on track of band **1712** (**1812** of FIG. **18**). The micro-adjustable sensor module **16** (of FIG. **1**) is positioned adjustably in or on the band **1712** (**1812** of FIG. **18**) via a sensor slide **1796**. In this implementation, the sensor slide **1796** (**1897** of FIG. **18**) is adjusted, manually or automatically, to refine the position the sensor module **16** (of FIG. **1**) as desired. FIG. **17** illustrates the sensor slide **1796** in a first position, while FIG. **18** illustrates sensor slide **1897** in second position relative to the first position in FIG. **17**. Various other positions of the sensor slide **1796** are possible within the track to accommodate the positioning of the sensor module **16** (of FIG. **1**) for a given user as desired.

Additionally, it should be understood that other implementations of the micro-adjustability of the sensor module **1316** are contemplated. For example, instead of or in addition to employing the flex lead **1394** in FIG. **13**, one or more of the sensor units **1328** may be rotatable. Rotation of the sensor units **1328** may occur either individually, in combination with other sensor units **1328** or as the sensor module is moved along the track of the band **1312** in FIG. **13**. Such rotation may facilitate refined positioning of the sensor units **1328** for improved comfort or improved physiological measurements depending on the body part. As should be apparent, the various implementations for sensor module **16** may be employed alone or together depending on the user and application.

The present invention has been described in accordance with the embodiments shown, and there could be variations to the embodiments, and any variations would be within the spirit and scope of the present invention. For example, the exemplary embodiment can be implemented using hardware, software, a computer readable medium containing program instructions, or a combination thereof. Software written according to the present invention is to be either stored in some form of computer-readable medium such as a memory, a hard disk, or a CD/DVD-ROM and is to be executed by a processor.

While the invention has been described with reference to certain embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted without departing from the scope of the invention. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the invention without departing from its scope. Therefore, it is intended that the invention not be limited to the particular embodiment disclosed, but that the invention will include all embodiments falling within the scope of the appended claims.

Additionally, In addition, the logic flows depicted in the figures do not require the particular order shown, or sequential order, to achieve desirable results. In addition, other steps may be provided, or steps may be eliminated, from the described flows, and other components may be added to, or removed from, the described systems. Accordingly, other embodiments are within the scope of the following claims.

We claim:

1. A wearable system for measuring physiological data from a device worn about a body part of a user comprising:

18

a base module, the base module comprising a display and a base computing unit, and being positioned on a first side of the body part;

a first sensor module configured to measure a gravitational force experienced by the device;

a second sensor module spatially positioned relative to the base module on a second side opposite to the first side of the body part and over a portion of the body part for measuring one or more physiological characteristics calibrated based on the gravitational force measured with the first sensor module; and

the base module being adjustably positioned on the body part relative to the second sensor module so that the second sensor module maintains its positioning over the body part for sufficient contact with the body part regardless of an anthropometric size of the body part.

2. The wearable system of claim 1, wherein the second sensor module is positioned over an underside of a wrist of the user.

3. The wearable system of claim 1, where in the second sensor module further maintains a pressure contact with skin of the user to allow for continuous use by the user.

4. The wearable system of claim 1, wherein the second sensor module is removable.

5. The wearable system of claim 1, wherein the second sensor module is replaceable with a different type of sensor module.

6. The wearable system of claim 5, wherein sensor units are adapted to be removably coupled to a sensor plate of the second sensor module so that the sensor units may be individually replaced with different sensor units.

7. The wearable system of claim 1, wherein the second sensor module comprises a combination of electric and optical sensors.

8. The wearable system of claim 1, wherein the second sensor module comprises one or more of: biological sensors, proximity detectors for detecting a proximity of objects, and environmental sensors.

9. The wearable system of claim 1, wherein the second sensor module comprises sensor units that further comprises any combination of optical sensor array, a thermometer, a galvanic skin response (GSR) sensor array, a bioimpedance (BioZ) sensor array, and an electrocardiography (ECG) sensor.

10. The wearable system of claim 1, wherein the second sensor module comprises sensor units that further comprises an optical sensor array, and wherein the optical sensor array is arranged on a band so that the optical sensor array on the band is adapted to straddle a blood vessel.

11. The wearable system of claim 1, wherein the second sensor module comprises sensor units that further comprises a bioimpedance (BioZ) sensor array and optical sensor array, and wherein the bioimpedance (BioZ) sensor array is arranged on a band so that the optical sensor array on the band is adapted to straddle a blood vessel.

12. The wearable system of claim 1, wherein the base module further includes a base computing unit comprising a processor, memory, a communication interface and a set of sensors.

13. The wearable system of claim 1, wherein the second sensor module is adapted to be removably disposed on an interior surface of a strap.

14. The wearable system of claim 1, wherein a symmetrically adjustable band is adapted to connect the base module and the second sensor module.

15. The wearable system of claim 1, wherein a symmetrically adjustable band is adapted to connect the base module

and the second sensor module, wherein the symmetrically adjustable band is a one-piece.

16. The wearable system of claim 1, wherein at least two symmetrically adjustable sub-bands are adapted to connect the base module and the second sensor module.

17. The wearable system of claim 1, wherein at least two symmetrically adjustable bands are adapted to connect the base module and the second sensor module, wherein the symmetrically adjustable bands are one-piece bands.

18. The wearable system of claim 1, wherein a symmetrically adjustable band is adapted to connect the base module and the second sensor module, and the second sensor module is co-molded to the symmetrically adjustable band.

19. The wearable system of claim 1, wherein a symmetrically adjustable band is adapted to connect the base module and the second sensor module and the second sensor module is co-molded to the symmetrically adjustable band in a flexible gel.

20. The wearable system of claim 1, wherein at least two overlapping straps are adapted to connect the base module and the second sensor module.

21. The wearable system of claim 1, further comprising a band, and wherein the band comprises at least four links connected by a flex connection, and the band is adapted to connect the base module and the second sensor module.

22. The wearable system of claim 21, wherein the second sensor module comprises sensor units housed on a sensor plate that is adapted to be removably coupled to the band.

23. The wearable system of claim 1, wherein the second sensor module is adapted to adhere to skin of a body part.

24. The wearable system of claim 23, wherein the second sensor module is adapted to be positioned on an underside of a wrist.

25. The wearable system of claim 1, the base module comprises a thin, flexible display adapted to be adhered to skin of a body part.

26. The wearable system of claim 23, wherein the base module is adapted to be positioned on a top side of a wrist.

27. The wearable system of claim 1, wherein the body part is a wrist and sizes of the wrist can range from 125 mm to 210 mm.

28. The wearable system of claim 1, wherein the body part is an upper arm, waist, finger, ankle, neck, chest, foot or thigh.

29. The wearable system of claim 1, further comprising a wireless communications link and a wireless communication unit positioned in the second sensor module for transmitting physiological data via the wireless communications link to the base module.

30. The wearable system of claim 1, further comprising a wire, and wherein the second sensor module and the base module are connected via the wire for power and communicate data wirelessly.

31. The wearable system of claim 1, further comprising a wireless communications link and a wireless communication unit for transmitting physiological data via the wireless communications link to the base module and to a location remote from the wearable system.

32. The wearable system of claim 1, wherein the second sensor module and the base module each contain battery power sources and communicate wirelessly between each other.

33. The wearable system of claim 1, wherein the second sensor module and the base module each contain battery power sources and communicate wirelessly between each other and to a location remote from the wearable system.

34. The wearable system of claim 1, further comprising multiple sensor modules, and wherein the base module wirelessly communicates with the multiple sensor modules adapted to be worn on different body parts of the user.

35. The wearable system of claim 1, wherein the wearable system further transmits data to a remote architecture adapted to implement multi-modal interactions.

36. The wearable system of claim 35, wherein the remote architecture comprises a layer of artificial intelligence between the wearable system and one or more of: cloud devices, websites, online services, and applications.

37. The wearable system of claim 35, wherein the wearable system and the remote architecture communicate changes in user condition.

38. The wearable system of claim 35, wherein the remote architecture interacts with the wearable system to provide information related to social media, sports, music, movies, email, text messages, hospitals and prescriptions.

39. The wearable system of claim 1, wherein the second sensor module is a micro-adjustable sensor module.

40. The wearable system of claim 1, further comprising a power source, wherein the power source comprises a removable battery and a permanent battery.

41. The wearable system of claim 1, wherein the first sensor module comprises at least one of an accelerometer and a gyroscope.

42. The wearable system of claim 1, wherein the one or more physiological characteristics are calibrated based on a time differential from the gravitational force measured with the first sensor module.

43. The wearable system of claim 42, further comprising a timer configured to adjust a time duration used to measure the one or more physiological characteristics based on the gravitational force measured with the first sensor module, wherein the second sensor module is further configured to calibrate the measurements based on the time duration adjusted with the timer.

44. The wearable system of claim 1, wherein the one or more physiological characteristics are calibrated based on a light speed differential from the gravitational force measured with the first sensor module.

45. The wearable system of claim 44, further comprising a light calibrator configured to adjust light emission based on the gravitational force, wherein the second sensor module is further configured to calibrate the measurements based on the light emission adjusted with the light calibrator.

46. A wearable system for measuring physiological data from a device worn about a body part of a user comprising: a base module, the base module comprising a display and a base computing unit, and being positioned on a first side of the body part;

a first sensor module configured to measure a gravitational force experienced by the device; and

a micro-adjustable sensor module spatially positioned relative to the base module on a second side opposite to the first side of the body part and over a portion of the body part for measuring one or more physiological characteristics calibrated based on the gravitational force measured with the first sensor module; the micro-adjustable sensor module configured to adjustably position in a first position of the body part of the user, and being adjustably relocated to a second position of the body part, relative to the first position, for sufficient contact with the body part at the second position regardless of an anthropometric size of the body part.

47. The wearable system of claim 46, wherein the micro-adjustable sensor module is positioned over an underside of a wrist of the user.

48. The wearable system of claim 46, where in the micro-adjustable sensor module further maintains a pressure contact with skin of the user to allow for continuous use by the user.

49. The wearable system of claim 46, wherein the micro-adjustable sensor module is removable.

50. The wearable system of claim 46, wherein the micro-adjustable sensor module is replaceable with a different type of sensor module.

51. The wearable system of claim 50, wherein sensor units are adapted to be removably coupled to a sensor plate of the micro-adjustable sensor module so that the sensor units may be individually replaced with different sensor units.

52. The wearable system of claim 46, wherein the micro-adjustable sensor module comprises a combination of electric and optical sensors.

53. The wearable system of claim 46, wherein the micro-adjustable sensor module comprises one or more of: biological sensors, proximity detectors for detecting a proximity of objects, and environmental sensors.

54. The wearable system of claim 46, wherein the micro-adjustable sensor module comprises sensor units that further comprises any combination of optical sensor array, a thermometer, a galvanic skin response (GSR) sensor array, a bioimpedance (BioZ) sensor array, and an electrocardiography (ECG) sensor.

55. The wearable system of claim 46, wherein the micro-adjustable sensor module comprises sensor units that further comprises an optical sensor array, and wherein the optical sensor array is arranged on a band so that the optical sensor array on the band is adapted to straddle a blood vessel.

56. The wearable system of claim 46, wherein the micro-adjustable sensor module that further comprises a bioimpedance (BioZ) sensor array and an optical sensor array, and wherein the bioimpedance (BioZ) sensor array is arranged on a band so that the optical sensor array on the band is adapted to straddle a blood vessel.

57. The wearable system of claim 46, wherein the base module further includes a base computing unit comprising a processor, memory, a communication interface and a set of sensors.

58. The wearable system of claim 46, wherein the micro-adjustable sensor module is adapted to be removably disposed on an interior surface of a strap.

59. The wearable system of claim 46, wherein a symmetrically adjustable band is adapted to connect the base module and the micro-adjustable sensor module.

60. The wearable system of claim 46, wherein a symmetrically adjustable band is adapted to connect the base module and the micro-adjustable sensor module, wherein the symmetrically adjustable band is a one-piece.

61. The wearable system of claim 46, wherein at least two symmetrically adjustable sub-bands are adapted to connect the base module and the micro-adjustable sensor module.

62. The wearable system of claim 46, wherein at least two symmetrically adjustable bands are adapted to connect the base module and the micro-adjustable sensor module, wherein the symmetrically adjustable bands are one-piece bands.

63. The wearable system of claim 46, wherein a symmetrically adjustable band is adapted to connect the base module and the micro-adjustable sensor module, and the micro-adjustable sensor module is co-molded to the symmetrically adjustable band.

64. The wearable system of claim 46, wherein a symmetrically adjustable band is adapted to connect the base module and the micro-adjustable sensor module and the micro-adjustable sensor module is co-molded to the symmetrically adjustable band in a flexible gel.

65. The wearable system of claim 46, wherein at least two overlapping straps are adapted to connect the base module and the micro-adjustable sensor module.

66. The wearable system of claim 46, further comprising a band, and wherein the band comprises at least four links connected by a flex connection, and the band is adapted to connect the base module and the micro-adjustable sensor module.

67. The wearable system of claim 66, wherein the micro-adjustable sensor module comprises sensor units housed on a sensor plate that is adapted to be removably coupled to the band.

68. The wearable system of claim 46, wherein the micro-adjustable sensor module adapted to be adhered to skin of a body part.

69. The wearable system of claim 68, wherein the micro-adjustable sensor module is adapted to be positioned on an underside of a wrist.

70. The wearable system of claim 46, the base module comprises a thin, flexible display adapted to be adhered to skin of a body part.

71. The wearable system of claim 70, wherein the base module is adapted to be positioned on a top side of a wrist.

72. The wearable system of claim 46, wherein the body part is a wrist and sizes of the wrist can range from 125 mm to 210 mm.

73. The wearable system of claim 46, wherein the body part is an upper arm, waist, finger, ankle, neck, chest, foot or thigh.

74. The wearable system of claim 46, further comprising a wireless communications link and a wireless communication unit positioned in the micro-adjustable sensor module for transmitting physiological data via the wireless communications link to the base module.

75. The wearable system of claim 46, further comprising a wire, and wherein the micro-adjustable sensor module and the base module are connected via the wire for power and communicate data wirelessly.

76. The wearable system of claim 46, further comprising a wireless communications link and a wireless communication unit for transmitting physiological data via the wireless communications link to the base module and to a location remote from the wearable system.

77. The wearable system of claim 46, wherein the micro-adjustable sensor module and the base module each contain battery power sources and communicate wirelessly between each other.

78. The wearable system of claim 46, wherein the micro-adjustable sensor module and the base module each contains battery power sources and communicates wirelessly between each other and to a location remote from the wearable system.

79. The wearable system of claim 46, further comprising multiple sensor modules, and wherein the base module wirelessly communicates with multiple sensor modules adapted to be worn on different body parts of the user.

80. The wearable system of claim 46, wherein the wearable system further transmits data to a remote architecture adapted to implement multi-modal interactions.

81. The wearable system of claim 80, wherein the remote architecture comprises a layer of artificial intelligence

23

between the wearable system and one or more of: cloud devices, websites, online services, and applications.

82. The wearable system of claim 80, wherein the wearable system and the remote architecture communicate changes in user condition.

83. The wearable system of claim 80, wherein the remote architecture interacts with the wearable system to provide information related to social media, sports, music, movies, email, text messages, hospitals and prescriptions.

84. The wearable system of claim 46, further comprising a power source, wherein the power source comprises a removable battery and a permanent battery.

85. The wearable system of claim 46, wherein the first sensor module comprises at least one of an accelerometer and a gyroscope.

86. The wearable system of claim 46, wherein the one or more physiological characteristics are calibrated based on a time differential from the gravitational force measured with the first sensor module.

87. The wearable system of claim 86, further comprising a timer configured to adjust a time duration used to measure the one or more physiological characteristics based on the gravitational force measured with the first sensor module, wherein the micro-adjustable sensor module is further configured to calibrate the measurements based on the time duration adjusted with the timer.

88. The wearable system of claim 46, wherein the one or more physiological characteristics are calibrated based on a light speed differential from the gravitational force measured with the first sensor module.

89. The wearable system of claim 88, further comprising a light calibrator configured to adjust light emission based on the gravitational force, wherein the micro-adjustable sensor module is further configured to calibrate the measurements based on the light emission adjusted with the light calibrator.

90. A method for measuring physiological data from a wearable device worn about a body part of a user, the wearable device having a base module comprising a display being positioned on a first side of the body part and a base computing unit, a first sensor module, and a micro-adjustable sensor module on a second side opposite to the first side of the body part, the method comprising:

measuring with the first sensor module a gravitational force experienced by the wearable device;

spatially and adjustably positioning the micro-adjustable sensor module relative to the base module on the first side of the body part and over a portion of the body part

24

at a first position for measuring one or more physiological characteristics calibrated based on the gravitational force measured with the first sensor module; and

adjustably relocating the micro-adjustable sensor module from the first position to a second position of the body part, relative to the first position, for sufficient contact with the body part at the second position for accurate measurements of physiological data regardless of an anthropometric size of the body part.

91. The method of claim 90, wherein the micro-adjustable sensor module comprises a plurality of sensor units that are rotated to provide sufficient contact with the body part for accurate measurements of physiological data regardless of the anthropometric size of the body part.

92. The method of claim 91, comprising relocating the plurality of sensor units relative to each other to improve contact with the body part for accurate measurements of physiological data.

93. The method of claim 90, wherein the first sensor module comprises at least one of an accelerometer and a gyroscope.

94. The method of claim 90, further comprising calibrating the one or more physiological characteristics based on a time differential from the gravitational force measured with the first sensor module.

95. The method of claim 94, wherein calibrating the one or more physiological characteristic based on a time differential further comprises:

adjusting a time duration with a timer used to measure the one or more physiological characteristics based on the gravitational force measured with the first sensor module; and

calibrating the measurements based on the time duration adjusted with the timer.

96. The method of claim 90, further comprising calibrating the one or more physiological characteristics based on a light speed differential from the gravitational force measured with the first sensor module.

97. The method of claim 96, wherein calibrating the one or more physiological characteristic based on a light speed further comprises:

adjusting light emission with a light calibrator based on the gravitational force measured with the first sensor module; and

calibrating the measurements based on the light emission adjusted with the light calibrator.

* * * * *

专利名称(译)	可调节的可穿戴系统，具有模块化传感器平台		
公开(公告)号	US10136857	公开(公告)日	2018-11-27
申请号	US14/878706	申请日	2015-10-08
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
[标]发明人	NUOVO FRANK SETTEMO PHILLIPS SHELDON GEORGE SCHUESSLER JAMES		
发明人	NUOVO, FRANK SETTEMO PHILLIPS, SHELDON GEORGE SCHUESSLER, JAMES		
IPC分类号	A61B5/00 A61B5/0402 A61B5/01 A61B5/0205 A61B5/0408 A61B5/053		
CPC分类号	A61B5/681 A61B5/0402 A61B5/6831 A61B5/6843 A61B5/7264 A61B5/7445 A61B5/0059 A61B2562/164 A61B5/0022 A61B5/0024 A61B5/01 A61B5/02055 A61B5/0408 A61B5/0533 A61B5/742 A61B2560/0214 A61B2560/0223 A61B2560/0247 A61B2560/0443 A61B2560/0475 A61B2562/028 A61B2562/0219 A61B2562/0257		
优先权	62/061290 2014-10-08 US 62/002589 2014-05-23 US		
其他公开文献	US20160022210A1		
外部链接	Espacenet		

摘要(译)

提供了一种可穿戴系统和方法，用于测量来自佩戴在用户身体部位周围的装置的生理数据，包括基础模块，第一传感器模块和第二传感器模块。基础模块包括显示器和基础计算单元。第一传感器模块测量装置所经历的重力。第二传感器模块相对于基座模块在空间上定位并且在身体部分的一部分上方，用于测量基于利用第一传感器模块测量的重力校准的一个或多个生理特征。基部模块由使用者相对于第二传感器模块可调节地定位，使得传感器模块保持其在身体部分上的定位，以与身体部分充分接触，以准确测量生理数据，而不管身体部位的人体测量尺寸如何。

