



US009922253B2

(12) United States Patent
Asbun et al.**(10) Patent No.: US 9,922,253 B2**
(45) Date of Patent: Mar. 20, 2018**(54) GAZE-DRIVEN AUGMENTED REALITY****(71) Applicant: InterDigital Patent Holdings, Inc.,**
Wilmington, DE (US)**(72) Inventors: Eduardo Asbun, San Diego, CA (US);**
Yuriy Reznik, Seattle, WA (US); Ariela
Zeira, Huntington, NY (US); Gregory
S. Sternberg, Mt. Laurel, NJ (US);
Ralph Neff, San Diego, CA (US)**(73) Assignee: InterDigital Patent Holdings, Inc.,**
Wilmington, DE (US)**(*) Notice:** Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 19 days.**(21) Appl. No.: 15/028,233****(22) PCT Filed: Oct. 10, 2014****(86) PCT No.: PCT/US2014/060016**

§ 371 (c)(1),

(2) Date: Apr. 8, 2016**(87) PCT Pub. No.: WO2015/054562****PCT Pub. Date: Apr. 16, 2015****(65) Prior Publication Data**

US 2016/0259977 A1 Sep. 8, 2016

Related U.S. Application Data**(60) Provisional application No. 61/889,900, filed on Oct.**
11, 2013.**(51) Int. Cl.**
G09G 5/00 (2006.01)
G02B 27/01 (2006.01)
(Continued)**(52) U.S. Cl.**
CPC **G06K 9/00671** (2013.01); **A61B 5/0022**
(2013.01); **A61B 5/1112** (2013.01);
(Continued)**(58) Field of Classification Search**CPC G06K 9/00302; G06K 9/00604; G06K
9/00671; G06K 9/46; G06F 3/013;
(Continued)**(56) References Cited**

U.S. PATENT DOCUMENTS

2006/0009702 A1 1/2006 Iwaki et al.
2010/0226535 A1 9/2010 Kimchi et al.
(Continued)

FOREIGN PATENT DOCUMENTS

JP 2005-315802 A 11/2005
WO WO 2012/154418 11/2012


OTHER PUBLICATIONS

Wayback Machine copy of Google, "Google Glass", Product web
page: <http://www.google.com/glass>, dated May 1, 2013, 1 page.

(Continued)

Primary Examiner — Jin-Cheng Wang**(74) Attorney, Agent, or Firm** — Condo Roccia Koptiw
LLP**(57) ABSTRACT**

Augmented reality (AR) systems, methods, and instrument-
talities are disclosed. A user's gaze point may be estimated
and may be used to search for and present information, e.g.,
information relating to areas on which the user is focusing.
The user's gaze point may be used to facilitate or enable
modes of interactivity and/or user interfaces that may be
controlled by the direction of view of the user. Biometric
techniques may be used to estimate an emotional state of the
user. This estimated emotional state may be used to be the
information that is presented to the user.

21 Claims, 22 Drawing Sheets

- (51) **Int. Cl.**
G06F 3/01 (2006.01)
G06K 9/00 (2006.01)
A61B 5/16 (2006.01)
A61B 5/00 (2006.01)
A61B 5/11 (2006.01)
H04W 4/04 (2009.01)
A61B 5/0476 (2006.01)
A61B 5/053 (2006.01)
- (52) **U.S. Cl.**
CPC **A61B 5/165** (2013.01); **A61B 5/742** (2013.01); **G02B 27/017** (2013.01); **G06F 3/013** (2013.01); **G06K 9/00302** (2013.01); **G06K 9/00604** (2013.01); **H04W 4/04** (2013.01); **A61B 5/0476** (2013.01); **A61B 5/0533** (2013.01); **G06F 3/015** (2013.01)
- (58) **Field of Classification Search**
CPC G06F 3/015; G06F 3/017; G06F 2203/011; G02B 27/017; G02B 2027/0178; G02B 2027/0187; G02B 27/0093; A61B 5/164; A61B 5/742; A61B 3/112; A61B 3/113; A61B 5/165; A61B 5/6803; G06T 19/006
USPC 345/633, 156, 8, 441; 382/103
See application file for complete search history.
- (56) **References Cited**
U.S. PATENT DOCUMENTS
- | | | | | | | |
|--------------|------|--------|-------------|-------|--------------|---------|
| 2011/0085700 | A1 * | 4/2011 | Lee | | G06Q 30/02 | 382/103 |
| 2011/0134026 | A1 * | 6/2011 | Kang | | G06F 3/011 | 345/156 |
| 2011/0137137 | A1 | 6/2011 | Shin et al. | | | |
| 2012/0062595 | A1 * | 3/2012 | Oh | | G06K 9/00671 | 345/633 |
- 2012/0290401 A1 * 11/2012 Neven A61B 3/113 705/14.68
2013/0147838 A1 * 6/2013 Small G06F 3/013 345/633
2013/0204535 A1 * 8/2013 Kapoor G06F 19/3437 702/19
2014/0049546 A1 * 2/2014 Wang G06T 11/20 345/441
2014/0225918 A1 * 8/2014 Mittal G06F 3/017 345/633
- OTHER PUBLICATIONS**
- Girod et al., "Mobile Visual Search: Architectures, Technologies, and the Emerging MPEG Standard", IEEE MultiMedia, vol. 18, No. 3, Aug. 15, 2011, pp. 86-94.
Girod et al., "Mobile Visual Search", IEEE Signal Processing Magazine, vol. 28, No. 4, Jul. 2011, pp. 61-76.
Lemahieu et al., "Low Cost Eye Tracking for Human-Machine Interfacing", Journal of Eye Tracking, Visual Cognition and Emotion, vol. 1, No. 1, May 31, 2011, 12 pages.
Pérez et al., "A Precise Eye-Gaze Detection and Tracking System", The Proceedings of 11th International Conference in Central Europe on Computer Graphics, Visualization and Computer Vision, Feb. 3-7, 2003, pp. 105-108 (4 pages).
Takacs et al., "Outdoors Augmented Reality on Mobile Phone using Loxel-Based Visual Feature Organization", Proceedings of the 1st ACM International Conference on Multimedia Information Retrieval, Vancouver, British Columbia, Canada, Oct. 30-31, 2008, pp. 427-434 (8 pages).
Talmi et al., "Eye and Gaze Tracking for Visually Controlled Interactive Stereoscopic Displays", Signal Processing: Image Communication, vol. 14, No. 10, Aug. 1999, 9 pages.
Time Magazine, "Google Glass", Best Inventions of the Year 2012, Available at <<http://techland.time.com/2012/11/01/best-inventions-of-the-year-2012/slide/google-glass/>>, Oct. 31, 2012, 2 pages.
- * cited by examiner





FIG. 1

**FIG. 2A****FIG. 2B**




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11B




FIG. 11A




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17





FIG. 18A

**FIG. 18B**




FIG. 18C




FIG. 18D




FIG. 18E

GAZE-DRIVEN AUGMENTED REALITY

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is the National Stage Entry under 35 U.S.C. § 371 of Patent Cooperation Treaty Application No. PCT/US2014/060016, filed Oct. 10, 2014, which claims the benefit of U.S. Provisional Application No. 61/889,900, filed Oct. 11, 2013, the disclosure of which is incorporated herein by reference in its entirety.

BACKGROUND

In augmented reality (AR), a user's view of the real world may be digitally enhanced (or augmented) by adding a layer, or layers, of digital information on top of an image being viewed through a device (such as a smartphone, tablet, or wearable electronic device (such as the GOOGLE GLASS® system)). Some applications of AR may include sightseeing (e.g., providing information on nearby businesses or attractions), gaming (e.g., digital game play in a real world environment), navigation, and others.

Applications of AR may be suitable for wireless transmit/receive units (WTRUs), such as mobile devices, because mobile devices may be equipped with cameras, sensors, a global positioning system (GPS), and a gyroscope (such as to determine the direction of the camera view). A WTRU also has send/receive capabilities to interact with a server.

SUMMARY

Augmented reality (AR) systems, methods, and instrumentalities are disclosed. A user's gaze point may be estimated and may be used to search for and present information, e.g., only present information relating to areas to which the user is focusing his or her direction of view. The user's gaze point may be used to facilitate or enable modes of interactivity and/or user interfaces that may be controlled by the direction of view of the user.

Biometric techniques may be used to estimate an emotional state of the user. This estimated emotional state may be used to refine the information that is presented to the user.

A method of presenting information in an AR system may involve determining a gaze point of a user and a region of interest (ROI) as a function of the gaze point. Information pertaining to an object in the ROI may be presented. An emotional state of a user may be determined as a function of biometric data pertaining to the user. The search result may be filtered as a function of the determined emotional state.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram illustrating example elements of an augmented reality (AR) system.

FIG. 2A is a diagram illustrating example AR information superimposed on an image.

FIG. 2B is a diagram illustrating an example of incorrectness or inconsistency of AR information superimposed on an image.

FIG. 3 is a block diagram illustrating an example system for implementing an AR technique.

FIG. 4 is a block diagram illustrating another example system for implementing an AR technique.

FIG. 5 is a diagram illustrating an example AR search result.

FIG. 6 is a block diagram illustrating an example AR system that may use location-based and visual search techniques.

FIG. 7 is a diagram illustrating an example AR user interface.

FIG. 8 is a block diagram illustrating an example gaze-point detection system.

FIG. 9 illustrates an example eye tracking system.

FIG. 10 illustrates an example of using gaze-point detection to limit a search over a region of interest (ROI).

FIG. 11A is a diagram illustrating different results from a ROI resulting from differing distances to a target.

FIG. 11B is a diagram illustrating adjustment of a size of a ROI.

FIG. 12 depicts an example AR system comprising a gaze-driven user interface (UI).

FIG. 13 illustrates an example of use of gaze-point detection on a gaze-driven user interface (UI).

FIG. 14 is a block diagram illustrating an example module that may be used for estimating emotional state.

FIG. 15 is a block diagram illustrating an example gaze-driven AR system.

FIG. 16 is a diagram illustrating a gaze-driven AR user interface.

FIG. 17 depicts an example of adaptively adjusting a size of a ROI to reduce a number of objects of interest.

FIG. 18A is a system diagram of an example communications system in which one or more disclosed embodiments may be implemented.

FIG. 18B is a system diagram of an example wireless transmit/receive unit (WTRU) that may be used within the communications system illustrated in FIG. 18A.

FIG. 18C is a system diagram of an example radio access network and an example core network that may be used within the communications system illustrated in FIG. 18A.

FIG. 18D is a system diagram of another example radio access network and another example core network that may be used within the communications system illustrated in FIG. 18A.

FIG. 18E is a system diagram of another example radio access network and another example core network that may be used within the communications system illustrated in FIG. 18A.

DETAILED DESCRIPTION

A detailed description of illustrative embodiments will now be described with reference to the various Figures. Although this description provides a detailed example of possible implementations, it should be noted that the details are intended to be exemplary and in no way limit the scope of the application.

FIG. 1 illustrates example elements of an augmented reality (AR) system including a mobile device, such as a WTRU 100. User experience in an AR system may be enhanced by presenting information that may be relevant to the user. By estimating a user's direction of view, a search space may be characterized, e.g., limited. The quality of results may be improved, and the usage of processing and network resources may be reduced. A user's gaze point may be estimated and may be used to search for and present information, e.g., only present information relating to areas to which the user is focusing his or her direction of view. The user's gaze point may be used to facilitate or enable modes of interactivity and/or user interfaces that may be controlled by the direction of view of the user. Biometric techniques may be used to estimate an emotional state of the user. This

estimated emotional state may be used to refine the information that is presented to the user.

A camera may be used to capture an image **102** or video of a scene. GPS may be used to determine a geographical location, e.g., GPS coordinates **104**, of the mobile device, and a gyroscope may be used to determine a direction of the camera view **106**. This information may be sent to a server **108**, which may determine whether the WTRU **100** is located close to objects of interest and whether they are within the field of view of the camera. The results may be provided to an AR client **110**, and the AR client **110** may highlight these objects by superimposing text or images on the device's display.

In location-based AR, relevant information may be selected based on the user's geolocation (e.g., obtained using GPS or wireless networks) and/or orientation information (e.g., obtained using gyroscope or compass). This type of AR may be used with mapping or navigation applications, where users may want to find stores or services near their location.

FIG. 2A illustrates that results may be superimposed on preexisting images or video, or may be overlaid on images or video captured using a camera. An advantage of this technique is that relatively little information may be sent to and received from the server; therefore, the communication overhead may be reduced and the response time may be improved. However, the geolocation and/or orientation information may be inaccurate, the view of the camera may be blocked, and/or the camera may be pointing to an unrelated object. These conditions may result in incorrect or inconsistent information being shown to the user, as in FIG. 2B, in which the view of the camera may have little or no relation to the information overlaid on the screen.

FIG. 3 depicts an example system **300** that may implement an AR technique that may use an image or images captured by a camera **302**, e.g., in real-time to perform a visual search about objects in the user's visual proximity. A visual search may be performed by a server **304**, e.g., entirely by the server **304**. For example, an image or images may be sent by a client **306** to the server **304**, which may perform the search. Results may then be sent back to the client **306** for display by the client **306**. This approach may offload most of the processing to the server **304**, but may involve transmission of a possibly large amount of information over a network **308**, which may increase latency.

FIG. 4 depicts an example system **400** that may implement an AR technique in which part of the processing may be done by a client **402** (e.g., a "client-server" model). The client **402** may extract relevant features from the captured image(s) to obtain a set of descriptors that are used by a server **404** to perform the search. With this approach, the amount of information sent over a network **406** may be significantly reduced, improving the system response time. However, processing requirements at the client **402** may increase. If client capability is high, a subset of a database **408** may be cached at the client **402** to further improve system performance.

Users may capture image or video under a variety of conditions, e.g., lighting, occlusion, camera tilt, etc. Improving the robustness of the system may improve performance under these conditions. In addition, reducing search latency may improve real-time operation. To improve the performance of visual search, a visual search may be conducted on a subset of data available at the server. For example, irrelevant data may be limited, e.g., by considering locations that are close to the user's position.

Information presented to the user may correspond to the view being shown on the device's display, thus increasing its relevance. However, for client-server models, processing time may be spent on descriptor extraction for objects that are of no interest to the user. Further, for server-centric systems, query images may be sent from clients to a remote server. This may create a significant amount of network traffic.

Other issues may be related to the user interface. For example, a search may result in a large number of matching objects, potentially complicating on-screen annotations.

FIG. 5 illustrates an example screenshot **502**. The system may find it difficult or impossible to reduce the number of displayed objects if it has no way of knowing which of the displayed objects are important to the user. Some users may experience information overload as they may be presented with results that may not be relevant to them. In addition, with small screens or if annotations are overlapping, selecting a particular result from multiple results may be challenging.

FIG. 6 depicts an example AR system **600** that may use both location-based and visual search techniques. Location-based search may use input from sensors **602**, such as GPS and wireless networks, to estimate a user's location. The location may be provided to a server **604**, which may perform a search prior to presenting results to the user on the device's display **606**. A visual search may be performed by extracting features, e.g., descriptors, from images that may be captured, for example, by a camera **608**. This information may be sent as part of a request to the server **604**. One example feature extraction algorithm is known as Scale Invariant Feature Transform (SIFT) **610**, but other algorithms may be used. An image retrieval algorithm that may be used is known as "bag of features" **612**. These features may be used to create a retrieval request that may be sent to the server **604** to obtain more relevant results. Other input methods, such as voice recognition, may be used to create a retrieval request.

The example AR system **600** may comprise a client **614** that may have capabilities to implement visual search and that may maintain a local database **616** to speed up computation and reduce network traffic. The local database **616** may be built up by collecting requests and corresponding results as they are sent to and received from the server **604**. To maintain relevance of results and avoid providing stale results, the local database **616** may remove results after a period of time. The local database **616** may remove results using one or more location criteria, e.g., when the user changes location, some results may be removed from the cache because the results may be less likely to be needed again, or based on whether cached contents may still be viewable from the user's current location. For example, a content result may be removed from the cache based on a comparison of the user's current location to a location associated with the content result. As described herein, visual search may be implemented at the server, e.g., only at the server. In this case, local search may be omitted.

FIG. 7 depicts an example AR user interface **702** that may be presented by an AR system, such as the GOOGLE GLASS® system. The AR user interface **702** may be used to allow users to perform functions that may be performed by smartphones. As shown in FIG. 7, a variety of information (e.g., icons, alerts, directional arrows, and/or other visual cues) may be displayed on the AR user interface **702**, e.g., may be projected on the surface of a wearable electronic device. As AR becomes more closely integrated with wear-

able electronic devices, such as eyewear or contact lenses, visual search functionality will improve the functionality of such devices.

AR systems that have visual search functionality may enable retrieval of information about objects in the field of view of the camera. However, with some visual search techniques, at least some of the presented information may not be of interest to the user. Also, system and network resources may be used on searching results that the user is not interested in. Further, the user interface may be cumbersome to use.

According to the disclosed subject matter, the relevance of the information presented to the user of an AR system may be improved using a number of techniques individually or in combination. The gaze point of a user may be estimated, and information may be presented in the areas, (e.g., only in the areas) where the user is focusing his or her direction of view. The estimated gaze point of a user may be used to enable or facilitate modes of interactivity and/or user interfaces that may be controlled by the user's direction of view. Biometric techniques may be used to estimate the emotional state of a user to further refine the information that is presented to the user.

A gaze-driven visual search engine may be used to improve the relevance and/or quality of search results in an AR system. FIG. 8 depicts an example gaze-point detection system 800. It will be appreciated that architectures other than the particular architecture shown in FIG. 8 may be implemented. A camera or cameras 802 facing a user 804 may capture one or more images, which may be used to determine the presence of human body features (e.g., face, nose, ears) to facilitate the identification of human eyes. If the camera or cameras 802 are located close to the face of the user, they may capture images of sufficient resolution to facilitate estimation of gaze point. For wearable devices, a camera may be placed on the device itself facing the user's eyes, enabling gaze-point detection.

A gaze-point detection subsystem 806 may use one or more eye gaze point direction estimation and/or detection techniques to estimate and/or detect a direction of view. A region of interest (ROI) subsystem 808 may determine coordinates 810 of a ROI 812 on an image 814 being captured by the camera. The size of the ROI and confidence level of accurate detection may be determined by the technique or techniques used for gaze-point detection. Either or both of these parameters may be used by the system 800 to determine the size of the ROI in which to perform a search.

Gaze-point detection may be based on any of a variety of technologies and may use devices mounted on the user's head or less intrusive systems (e.g., remote or non-head mounted systems). For example, a gaze-point detection system may analyze an image of the eye and may determine the gaze direction by computing the vector defined by the pupil center and a set of glints generated in the eye by an infrared illuminator. To increase the resolution of the vector, a camera with a narrow field of view may be used. Maintaining the eyes centered in the image, the camera may move to follow the eyes and compensate for the head movements.

Another example gaze-point detection system may allow combined tracking of the user's eye positions and the gaze direction in near real-time. Such a system may use two video cameras mounted on the left and right side of a display and may use facial feature detection to determine the position of the pupil in the eyes. A cornea-reflex method may be used to determine the gaze direction. For example, a low-power infrared-light emitting diode (LED) array may illuminate the eye and may generate a highlight on the cornea surface. An

algorithm may identify and localize the center of both the pupil and the corneal surface reflection. The distance between the two centers and their orientation (e.g., gaze vector) may provide a measure of the gaze direction.

FIG. 9 illustrates an example eye tracking system 900 that may use components, for example, including a webcam and infrared lighting. FIG. 9 illustrates how such a system may determine the direction of gaze, for example, based on a determined pupil center 902 and a reflection 904 of a screen 906 in the user's eye.

FIG. 10 illustrates an example of using gaze-point detection to limit a search over a ROI. Features from the user's ROI may be sent to the server, where the search may take place. In a server-only approach, the server may perform feature extraction using the ROI information provided by the client. Communication with the server may be reduced by performing a local search first.

At 1002, a gaze-point may be determined. At 1004, the ROI may be identified, for example, by the client. After determining the user's ROI, the scope of the search may be further refined.

FIG. 11A illustrates that the same ROI may yield different results depending on the distance to the target. When the user is close to the target, only object A may be found in the search. If the user is far from the target, objects A-E may be found in the search. To address this situation, the size of the ROI may be adaptively adjusted when multiple objects of interest are found. This is illustrated in FIG. 11B, where the original ROI size is reduced in order to reduce the number of objects of interest. Adaptation of ROI size may be triggered by staring, by pushing a button, by voice command or automatically when the number of objects of interest is above a threshold.

Returning to FIG. 10, if the confidence of the determined gaze-point is greater than a minimum threshold, a ROI may be determined at 1004. The client may perform feature extraction in the ROI at 1006. The client may send the resulting features from the ROI to the server at 1008. The server may perform a search over the determined ROI and may return the results to the client at 1010. The client may display relevant information pertaining to features extracted from the ROI at 1012.

As a result of using gaze-point detection, a visual search may be focused in or around the ROI. Extracting relevant features from the ROI may reduce the processing requirements to conduct a search, reduce the amount of information that may be sent to the server, and/or improve the relevance of the results shown to the user.

A system may present results in the area where the user focuses his or her direction of view. A different use case may occur when the user is looking for particular objects and may not know where they are located. The user may provide input to the system (e.g., via voice command, keyboard or touch screen) to direct the search to the objects that the user is looking for. The input may be general (e.g., categories such as "museum" or "food") or specific (e.g., "Starbucks coffee"). The user may scan the field of view of the camera by directing his or her direction of view to different regions in the field of view of the camera. Results may be shown in the estimated ROI, allowing the user to determine whether the object is within the ROI. The user may temporarily disable the gaze-driven feature so that all results within the field of view of the camera are presented.

Gaze-point direction may be used to improve user interaction and/or facilitate or enable modes of interactivity in an AR system. For example, a user interface may be controlled by a user's direction of view. In this type of interface, a menu

or set of choices may be shown on the display. The user may make choices using his or her eyes. This mode of interactivity may be more natural and may be faster than using hands, e.g., keyboard, mouse, and/or touch screen. For some systems, e.g., wearable systems, gaze-driven interactive processing may be a natural method for interaction, as peripherals that may be used for interaction, such as mouse and keyboard, may not be available.

FIG. 12 depicts an example AR system 1200 comprising a gaze-driven user interface (UI) 1202. Gaze-point detection may be determined by a gaze-point detection subsystem 1204. This information may be passed to an interactive processing (e.g., UI) engine 1206, where the gaze-point direction and ROI 1208 may be combined with input from a camera 1210 and/or results from location-based or visual search. Interactive processing may be achieved by determining if the user's gaze point corresponds to the location of an object of interest in the field of view of the camera. If so, the system may respond by taking an action that corresponds to the object of interest, for example, showing additional information 1212 on the object of interest, as shown in the user interface 1202.

FIG. 13 illustrates an example of use of gaze-point detection on a gaze-driven user interface. At 1302, the client may determine the objects of interest in the field of view of the camera. To improve system performance, a coarse visual search may be conducted first or location-based search may be used. At 1304, the user's ROI may be determined.

The user may be looking at a distant target that may have many objects of interest associated with it (e.g., a distant building with many small shops). In this case, the client may adaptively adjust the size of the ROI at 1306 to present only a subset of the objects of interest. In addition, at 1308, the objects may be arranged and/or the image may be zoomed such that the user is able to 'gaze trigger' the objects accurately. If the device is not capable of zooming the image itself (e.g., the camera is not equipped with zoom or its capabilities are limited), additional imagery could be obtained from the server. The server may be able to provide a detailed picture that the device camera may not produce by camera zoom from the distance.

After the user's gaze has been focused on a ROI that contains an object of interest for a pre-determined number of seconds, the client may fetch information about the object either from the server or from a local database at 1310, and the information may be displayed to the user at 1312. To improve system performance, a limited amount of information may initially be fetched and shown to the user.

The user may obtain additional information about the object of interest by focusing on the information shown on the display. After the user's gaze has been focused on a ROI that contains the information for a pre-determined number of seconds, the client may fetch more information about the object at 1314 and display it to the user at 1316. The client may also call an external application (e.g., web browser or media player) instead of showing the additional information itself.

To increase the relevancy of search results in an AR system, the emotional state of the user may be inferred or estimated. Emotional state could include traditional emotional states, such as joy and anger, as well as physiological states (e.g., tiredness, alertness, and/or hunger) or psychological states (e.g., nervousness and/or anxiety) that may not traditionally be considered emotions. A variety of sensors, such as Galvanic Skin Response (GSR) and/or Electroencephalography (EEG), may be used to estimate the user's emotional state. Other methods (such as voice analysis,

advanced computer vision techniques for recognizing emotion from facial expressions, biometrics and/or others) may also be used to perform this estimation, for example, as a point in a Valence/Arousal (V/A) chart.

FIG. 14 illustrates an example module 1400 that may be used for estimating emotional state. The result may be used to filter and/or rank the search results that are presented to the user. For example, if the user is tired, choices related to food or beverages may rank higher than museums. As shown in FIG. 14, the module 1400 may receive as inputs data from GSR, EEG, and/or other sensors, camera data, voice data, and/or other biometric data. The module 1400 may output an estimated emotional state, which may have valence and arousal values and/or may map to descriptors such as angry, sad, joyful, and/or relaxed.

Estimating the emotional state of the user from various inputs may be done using one or more of the techniques described herein. Each of these techniques may yield a point in a V/A chart. Some or all of the inputs to the module may be available. The available points in the V/A chart may be combined to estimate the user's emotional state with some degree of confidence.

Galvanic skin response (GSR) may measure the electrical conductance of the skin. GSR may be highly sensitive to emotions (e.g., fear, anger, startle response) and sympathetic responses (e.g., aroused). GSR sensor data may be mapped to a user's emotional state. Electroencephalography (EEG) data may be used to detect user thoughts, feelings, and expressions and may have a high degree of temporal resolution.

Computer vision techniques may be used for recognizing emotion from the user's facial expressions and gestures. Age, gender, ethnicity, demographics, height, and weight may be estimated from camera input.

Speech analysis techniques (e.g., speech pattern recognition, machine learning, study of prosodic and acoustic features, vocal energy, speech rate, and pausing) may be used to estimate user's emotion.

Some smart headphones can measure biometric data such as heart rate, distance traveled, steps taken, respiration rate, speed, metabolic rate, energy expenditure, calories burned, recovery time, etc. Biometric data, such as respiration rate and heart rate, may be correlated to the emotional state of the user.

If multiple sensors are used in conjunction with one another, an emotional estimate may be computed using a mean operation to combine the output from the sensors. The mean operation may be performed in a weighted manner (for example, such that the output from sensors types that are more error prone may be weighted less than the output from sensors types that are more accurate). If a certain sensor does not produce an output, the weight for that output in a mean operation to determine an emotion estimate may be zero.

After obtaining an estimate of the user's emotional state, the result may be used to refine a retrieval request to the server or for local search, or to filter results that are presented to the user. For example, a user's emotional state may be used to restrict the search space by adding conditions in order to increase the relevance of the results. Points in the V/A chart may be mapped to categories of objects that may be used as qualifiers in the search terms. Therefore, search results may contain objects related to these search terms and may be more relevant to the user. For example, if the client estimates that the user is "Joyful", then terms such as "shopping" or "food" may be used. As another example, if the state is estimated to be "Relaxed", then terms such as "drink" or "art" may be used. Emotional state may also be

used to filter and/or rank results to increase their relevance. For example, if the client estimates that the user is “Sad”, then search results that are related to “health” or “music” may be ranked higher prior to presenting them to the user. As another example, if the state is estimated to be “Angry”, then results related to “travel” or “nature” may be ranked higher.

FIG. 15 illustrates an example gaze-driven AR system 1500. The gaze-driven AR system 1500 may comprise a gaze-point detection/estimation subsystem 1502 and/or an emotional state detection/estimation subsystem 1504. One or more eye-facing cameras 1506 may be used to enable gaze-point detection. This information may be used to determine a ROI 1508 on which search will be focused. Relevant features may be extracted from the ROI, (e.g., only from the ROI), potentially reducing the processing requirements to conduct a search and/or reducing the amount of information that may be sent to a server 1510.

A variety of sensors, such as Galvanic Skin Response (GSR) and Electroencephalography (EEG) sensors 1512, may be used to estimate the user’s emotional state. Other methods, such as voice analysis or advanced image analysis techniques, may be used to perform this estimation. The results may be used to further narrow the search, potentially improving the quality of the results shown to the user.

A gaze-driven rendering and interactive processing module 1514 may enable users to interact with the results and options presented on a display 1516.

Gaze/visual search history may be stored and/or maintained in a local database 1518, e.g., as part of a local search module 1520. Keeping track of this history may reduce the burden on the network, as it may reduce traffic between clients and server. This may facilitate scaling the system to a large number of clients.

Search results may be improved by maintaining a profile of the user. The user may be able to configure search parameters, for example, by entering biometric or demographic information. Alternatively, with the user’s permission, the system 1500 may infer this data by using sensors, cameras, and/or other methods. User profiles may be maintained locally at a client 1522 or at the server 1510.

Emotional responses may also be a useful guide in triggering visual search that is most relevant to the user. For example, if the system 1500 has detected on multiple occasions that a particular search result or a class of search results caused a reaction of disgust for the user, the search result or the class of search results may be lowered in priority in the future, or may be filtered out entirely. For example, the system 1500 may detect instances where the display of AR content for a particular sandwich shop (“Harry’s sandwiches”) causes a negative emotional response to the user, and as a result the system may give lower priority to the display of “Harry’s Sandwich Shop” when it would appear in search results in the future. If the system 1500 were to subsequently detect a pattern where the display of AR content for multiple different sandwich shops caused a negative emotional response for the user, the system 1500 may give a lower priority to the display of sandwich shops generally, or may give a higher priority to the display of classes of restaurants other than sandwich shops. If the system 1500 has detected on multiple occasions that a particular search result or a class of search results caused a reaction of joy for the user (e.g. evoking a happy expression or a smile), then the search result or the class of search results may be given higher priority in the future. A history of emotional responses (e.g. multiple records comprising emotional response, date and/or time of the emotional

response, and the AR content and/or real content which evoked the emotional response) may be kept locally or at the server 1510.

Gaze tracking may be used with wearable electronic devices, such as head-worn AR devices, e.g., the GOOGLE GLASS® system. Knowledge of user’s gaze point may be used to localize search and improve relevance and effectiveness of annotations. Gaze point detection can also be used to facilitate or enable interactivity with AR applications. For example, by using gaze-driven visual search enhanced AR, search results may appear in the vicinity, e.g., only in the vicinity, of his/her gaze point. By focusing on a specific annotation, the user may invoke the expansion of the annotation into more detailed annotations with information about the object of interest.

FIG. 16 illustrates a gaze-driven AR user interface 1600. In FIG. 16, an image 1602 represents the view seen by the user through the AR user interface. The user may focus his or her gaze, represented by a circle 1604, on signs placed next to recognized objects, e.g., a restaurant icon shown in a detailed image 1606. If the user focuses his or her view on a sign for a few seconds, extra information about the recognized object may be presented on the screen, shown in a detailed image 1608.

FIG. 17 depicts an example of adaptively adjusting a size of a ROI to reduce a number of objects of interest. An image 1702 represents the view seen by the user through an AR user interface. The user may focus his or her gaze on a ROI 1704. The client may determine an ROI. As shown in an image 1706, the ROI 1704 may contain a number of objects that may be of interest to the user. The client may adaptively adjust the ROI size to present a limited number of objects to the user in an overlapped window 1708. The user may focus his or her attention on an object within the new window 1708. The client may determine a new ROI 1710. As shown in an image 1712, the client may obtain additional imagery from server, as its zooming capabilities may be limited, and may present additional information to the user in a new window 1714 (e.g., “Store hours”). The user may focus his or her attention on the new window 1714, and the client may launch a new application (e.g., web browser).

The additional imagery from the server may include prerecorded images or video content. For example, the server may have a database of additional imagery previously recorded from locations of interest, from locations corresponding to businesses or landmarks, or from all locations visible from a street or from a set of streets. For example, the server may have a database of continuous street imagery indexed by geographical location, and such imagery may be used to display zoomed ROI images. For example, such imagery may be used to display more detailed images than those obtainable from a camera available on the user’s device. The server may correlate and/or match the location of the user’s gaze point in the physical world to the locations corresponding to the additional imagery, as indexed in the database, in order to identify suitable imagery to display for a given ROI.

The additional imagery from the server may include images or video content captured from a live camera. For example, the server may have access to one or more cameras which have views of locations of interest, of locations corresponding to businesses or landmarks, or of street views. Image and/or video content from a live camera may be available to the server via a fixed connection, or via a communication network. The server may correlate and/or match the location of the user’s gaze point in the physical world to the locations of the available cameras, and in this

way the server may locate a suitable camera and/or may determine whether a suitable camera is available. The server may communicate with a camera to obtain images and/or video content which correspond to a given ROI, and may transmit such images to the user device for display on the user device.

The additional imagery from the server displayed by the user device may be displayed together with information about objects of interest which are associated with the scope of the additional imagery. The user interface may allow the user to select objects of interest displayed in this way, or may allow the user to zoom further into the imagery using techniques disclosed herein.

The user interface may allow the user to pan within the additional imagery. For example, if the user device is a tablet computing device, the device may pan the imagery within the zoomed view shown in the image 1712 of FIG. 17 in response to the user moving the tablet computing device in a panning motion. As another example, if the user device is a wearable camera device with a head-mounted display, then the device may pan the imagery within the zoomed view shown in the image 1712 of FIG. 17 in response to panning head movements of the user. The user device may detect panning movements using orientation sensors on the user device, or may infer panning movements by detecting motion from a camera of the user device. The user device may send updated information to the server which describes the panning motion, the user device orientation, and/or the gaze point of the user. In response, the server may provide updated imagery that corresponds to the updated information, and the user device may display the updated imagery in order to pan within the additional imagery. In this way, the user may navigate within a magnified view of the physical world which may have more detail than could be captured using the camera available on the user's device.

FIG. 18A is a diagram of an example communications system 1800 in which one or more disclosed embodiments may be implemented. The communications system 1800 may be a multiple access system that provides content, such as voice, data, video, messaging, broadcast, etc., to multiple wireless users. The communications system 1800 may enable multiple wireless users to access such content through the sharing of system resources, including wireless bandwidth. For example, the communications systems 1800 may employ one or more channel access methods, such as code division multiple access (CDMA), time division multiple access (TDMA), frequency division multiple access (FDMA), orthogonal FDMA (OFDMA), single-carrier FDMA (SC-FDMA), and the like.

As shown in FIG. 18A, the communications system 1800 may include wireless transmit/receive units (WTRUs) 1802a, 1802b, 1802c, and/or 1802d (which generally or collectively may be referred to as WTRU 1802), a radio access network (RAN) 1803/1804/1805, a core network 1806/1807/1809, a public switched telephone network (PSTN) 1808, the Internet 1810, and other networks 1812, though it will be appreciated that the disclosed embodiments contemplate any number of WTRUs, base stations, networks, and/or network elements. Each of the WTRUs 1802a, 1802b, 1802c, 1802d may be any type of device configured to operate and/or communicate in a wireless environment. By way of example, the WTRUs 1802a, 1802b, 1802c, 1802d may be configured to transmit and/or receive wireless signals and may include user equipment (UE), a mobile station, a fixed or mobile subscriber unit, a pager, a cellular telephone, a personal digital assistant

(PDA), a smartphone, a laptop, a netbook, a personal computer, a wireless sensor, consumer electronics, and the like.

The communications systems 1800 may also include a base station 1814a and a base station 1814b. Each of the base stations 1814a, 1814b may be any type of device configured to wirelessly interface with at least one of the WTRUs 1802a, 1802b, 1802c, 1802d to facilitate access to one or more communication networks, such as the core network 1806/1807/1809, the Internet 1810, and/or the networks 1812. By way of example, the base stations 1814a, 1814b may be a base transceiver station (BTS), a Node-B, an eNode B, a Home Node B, a Home eNode B, a site controller, an access point (AP), a wireless router, and the like. While the base stations 1814a, 1814b are each depicted as a single element, it will be appreciated that the base stations 1814a, 1814b may include any number of interconnected base stations and/or network elements.

The base station 1814a may be part of the RAN 1803/1804/1805, which may also include other base stations and/or network elements (not shown), such as a base station controller (BSC), a radio network controller (RNC), relay nodes, etc. The base station 1814a and/or the base station 1814b may be configured to transmit and/or receive wireless signals within a particular geographic region, which may be referred to as a cell (not shown). The cell may further be divided into cell sectors. For example, the cell associated with the base station 1814a may be divided into three sectors. Thus, in one embodiment, the base station 1814a may include three transceivers, e.g., one for each sector of the cell. In another embodiment, the base station 1814a may employ multiple-input multiple output (MIMO) technology and, therefore, may utilize multiple transceivers for each sector of the cell.

The base stations 1814a, 1814b may communicate with one or more of the WTRUs 1802a, 1802b, 1802c, 1802d over an air interface 1815/1816/1817, which may be any suitable wireless communication link (e.g., radio frequency (RF), microwave, infrared (IR), ultraviolet (UV), visible light, etc.). The air interface 1815/1816/1817 may be established using any suitable radio access technology (RAT).

More specifically, as noted above, the communications system 1800 may be a multiple access system and may employ one or more channel access schemes, such as CDMA, TDMA, FDMA, OFDMA, SC-FDMA, and the like. For example, the base station 1814a in the RAN 1803/1804/1805 and the WTRUs 1802a, 1802b, 1802c may implement a radio technology such as Universal Mobile Telecommunications System (UMTS) Terrestrial Radio Access (UTRA), which may establish the air interface 1815/1816/1817 using wideband CDMA (WCDMA). WCDMA may include communication protocols such as High-Speed Packet Access (HSPA) and/or Evolved HSPA (HSPA+). HSPA may include High-Speed Downlink Packet Access (HSDPA) and/or High-Speed Uplink Packet Access (HSUPA).

In another embodiment, the base station 1814a and the WTRUs 1802a, 1802b, 1802c may implement a radio technology such as Evolved UMTS Terrestrial Radio Access (E-UTRA), which may establish the air interface 1815/1816/1817 using Long Term Evolution (LTE) and/or LTE-Advanced (LTE-A).

In other embodiments, the base station 1814a and the WTRUs 1802a, 1802b, 1802c may implement radio technologies such as IEEE 802.16 (e.g., Worldwide Interoperability for Microwave Access (WiMAX)), CDMA2000, CDMA2000 1x, CDMA2000 EV-DO, Interim Standard

2000 (IS-2000), Interim Standard 95 (IS-95), Interim Standard 856 (IS-856), Global System for Mobile communications (GSM), Enhanced Data rates for GSM Evolution (EDGE), GSM EDGE (GERAN), and the like.

The base station **1814b** in FIG. **18A** may be a wireless router, Home Node B, Home eNode B, or access point, for example, and may utilize any suitable RAT for facilitating wireless connectivity in a localized area, such as a place of business, a home, a vehicle, a campus, and the like. In one embodiment, the base station **1814b** and the WTRUs **1802c**, **1802d** may implement a radio technology such as IEEE 802.11 to establish a wireless local area network (WLAN). In another embodiment, the base station **1814b** and the WTRUs **1802c**, **1802d** may implement a radio technology such as IEEE 802.15 to establish a wireless personal area network (WPAN). In yet another embodiment, the base station **1814b** and the WTRUs **1802c**, **1802d** may utilize a cellular-based RAT (e.g., WCDMA, CDMA2000, GSM, LTE, LTE-A, etc.) to establish a picocell or femtocell. As shown in FIG. **18A**, the base station **1814b** may have a direct connection to the Internet **1810**. Thus, the base station **1814b** may not be required to access the Internet **1810** via the core network **1806/1807/1809**.

The RAN **1803/1804/1805** may be in communication with the core network **1806/1807/1809**, which may be any type of network configured to provide voice, data, applications, and/or voice over internet protocol (VoIP) services to one or more of the WTRUs **1802a**, **1802b**, **1802c**, **1802d**. For example, the core network **1806/1807/1809** may provide call control, billing services, mobile location-based services, pre-paid calling, Internet connectivity, video distribution, etc., and/or perform high-level security functions, such as user authentication. Although not shown in FIG. **18A**, it will be appreciated that the RAN **1803/1804/1805** and/or the core network **1806/1807/1809** may be in direct or indirect communication with other RANs that employ the same RAT as the RAN **1803/1804/1805** or a different RAT. For example, in addition to being connected to the RAN **1803/1804/1805**, which may be utilizing an E-UTRA radio technology, the core network **1806/1807/1809** may also be in communication with another RAN (not shown) employing a GSM radio technology.

The core network **1806/1807/1809** may also serve as a gateway for the WTRUs **1802a**, **1802b**, **1802c**, **1802d** to access the PSTN **1808**, the Internet **1810**, and/or other networks **1812**. The PSTN **1808** may include circuit-switched telephone networks that provide plain old telephone service (POTS). The Internet **1810** may include a global system of interconnected computer networks and devices that use common communication protocols, such as the transmission control protocol (TCP), user datagram protocol (UDP) and the internet protocol (IP) in the TCP/IP internet protocol suite. The networks **1812** may include wired or wireless communications networks owned and/or operated by other service providers. For example, the networks **1812** may include another core network connected to one or more RANs, which may employ the same RAT as the RAN **1803/1804/1805** or a different RAT.

Some or all of the WTRUs **1802a**, **1802b**, **1802c**, **1802d** in the communications system **1800** may include multi-mode capabilities, e.g., the WTRUs **1802a**, **1802b**, **1802c**, **1802d** may include multiple transceivers for communicating with different wireless networks over different wireless links. For example, the WTRU **1802c** shown in FIG. **18A** may be configured to communicate with the base station

1814a, which may employ a cellular-based radio technology, and with the base station **1814b**, which may employ an IEEE 802 radio technology.

FIG. **18B** is a system diagram of an example WTRU **1802**. As shown in FIG. **18B**, the WTRU **1802** may include a processor **1818**, a transceiver **1820**, a transmit/receive element **1822**, a speaker/microphone **1824**, a keypad **1826**, a display/touchpad **1828**, non-removable memory **1830**, removable memory **1832**, a power source **1834**, a global positioning system (GPS) chipset **1836**, and other peripherals **1838**. It will be appreciated that the WTRU **1802** may include any sub-combination of the foregoing elements while remaining consistent with an embodiment. Also, embodiments contemplate that the base stations **1814a** and **1814b**, and/or the nodes that base stations **1814a** and **1814b** may represent, such as but not limited to transceiver station (BTS), a Node-B, a site controller, an access point (AP), a home node-B, an evolved home node-B (eNodeB), a home evolved node-B (HeNB or HeNodeB), a home evolved node-B gateway, and proxy nodes, among others, may include some or all of the elements depicted in FIG. **18B** and described herein.

The processor **1818** may be a general purpose processor, a special purpose processor, a conventional processor, a digital signal processor (DSP), a plurality of microprocessors, one or more microprocessors in association with a DSP core, a controller, a microcontroller, Application Specific Integrated Circuits (ASICs), Field Programmable Gate Array (FPGAs) circuits, any other type of integrated circuit (IC), a state machine, and the like. The processor **1818** may perform signal coding, data processing, power control, input/output processing, and/or any other functionality that enables the WTRU **1802** to operate in a wireless environment. The processor **1818** may be coupled to the transceiver **1820**, which may be coupled to the transmit/receive element **1822**. While FIG. **18B** depicts the processor **1818** and the transceiver **1820** as separate components, it will be appreciated that the processor **1818** and the transceiver **1820** may be integrated together in an electronic package or chip.

The transmit/receive element **1822** may be configured to transmit signals to, or receive signals from, a base station (e.g., the base station **1814a**) over the air interface **1815/1816/1817**. For example, in one embodiment, the transmit/receive element **1822** may be an antenna configured to transmit and/or receive RF signals. In another embodiment, the transmit/receive element **1822** may be an emitter/detector configured to transmit and/or receive IR, UV, or visible light signals, for example. In yet another embodiment, the transmit/receive element **1822** may be configured to transmit and receive both RF and light signals. It will be appreciated that the transmit/receive element **1822** may be configured to transmit and/or receive any combination of wireless signals.

In addition, although the transmit/receive element **1822** is depicted in FIG. **18B** as a single element, the WTRU **1802** may include any number of transmit/receive elements **1822**. More specifically, the WTRU **1802** may employ MIMO technology. Thus, in one embodiment, the WTRU **1802** may include two or more transmit/receive elements **1822** (e.g., multiple antennas) for transmitting and receiving wireless signals over the air interface **1815/1816/1817**.

The transceiver **1820** may be configured to modulate the signals that are to be transmitted by the transmit/receive element **1822** and to demodulate the signals that are received by the transmit/receive element **1822**. As noted above, the WTRU **1802** may have multi-mode capabilities. Thus, the transceiver **1820** may include multiple transceivers for

enabling the WTRU **1802** to communicate via multiple RATs, such as UTRA and IEEE 802.11, for example.

The processor **1818** of the WTRU **1802** may be coupled to, and may receive user input data from, the speaker/microphone **1824**, the keypad **1826**, and/or the display/touchpad **1828** (e.g., a liquid crystal display (LCD) display unit or organic light-emitting diode (OLED) display unit). The processor **1818** may also output user data to the speaker/microphone **1824**, the keypad **1826**, and/or the display/touchpad **1828**. In addition, the processor **1818** may access information from, and store data in, any type of suitable memory, such as the non-removable memory **1830** and/or the removable memory **1832**. The non-removable memory **1830** may include random-access memory (RAM), read-only memory (ROM), a hard disk, or any other type of memory storage device. The removable memory **1832** may include a subscriber identity module (SIM) card, a memory stick, a secure digital (SD) memory card, and the like. In other embodiments, the processor **1818** may access information from, and store data in, memory that is not physically located on the WTRU **1802**, such as on a server or a home computer (not shown).

The processor **1818** may receive power from the power source **1834**, and may be configured to distribute and/or control the power to the other components in the WTRU **1802**. The power source **1834** may be any suitable device for powering the WTRU **1802**. For example, the power source **1834** may include one or more dry cell batteries (e.g., nickel-cadmium (NiCd), nickel-zinc (NiZn), nickel metal hydride (NiMH), lithium-ion (Li-ion), etc.), solar cells, fuel cells, and the like.

The processor **1818** may also be coupled to the GPS chipset **1836**, which may be configured to provide location information (e.g., longitude and latitude) regarding the current location of the WTRU **1802**. In addition to, or in lieu of, the information from the GPS chipset **1836**, the WTRU **1802** may receive location information over the air interface **1815/1816/1817** from a base station (e.g., base stations **1814a**, **1814b**) and/or determine its location based on the timing of the signals being received from two or more nearby base stations. It will be appreciated that the WTRU **1802** may acquire location information by way of any suitable location-determination implementation while remaining consistent with an embodiment.

The processor **1818** may further be coupled to other peripherals **1838**, which may include one or more software and/or hardware modules that provide additional features, functionality and/or wired or wireless connectivity. For example, the peripherals **1838** may include an accelerometer, an e-compass, a satellite transceiver, a digital camera (for photographs or video), a universal serial bus (USB) port, a vibration device, a television transceiver, a hands free headset, a Bluetooth® module, a frequency modulated (FM) radio unit, a digital music player, a media player, a video game player module, an Internet browser, and the like.

FIG. **18C** is a system diagram of the RAN **1803** and the core network **1806** according to an embodiment. As noted above, the RAN **1803** may employ a UTRA radio technology to communicate with the WTRUs **1802a**, **1802b**, **1802c** over the air interface **1815**. The RAN **1803** may also be in communication with the core network **1806**. As shown in FIG. **18C**, the RAN **1803** may include Node-Bs **1840a**, **1840b**, **1840c**, which may each include one or more transceivers for communicating with the WTRUs **1802a**, **1802b**, **1802c** over the air interface **1815**. The Node-Bs **1840a**, **1840b**, **1840c** may each be associated with a particular cell (not shown) within the RAN **1803**. The RAN **1803** may also

include RNCs **1842a**, **1842b**. It will be appreciated that the RAN **1803** may include any number of Node-Bs and RNCs while remaining consistent with an embodiment.

As shown in FIG. **18C**, the Node-Bs **1840a**, **1840b** may be in communication with the RNC **1842a**. Additionally, the Node-B **1840c** may be in communication with the RNC **1842b**. The Node-Bs **1840a**, **1840b**, **1840c** may communicate with the respective RNCs **1842a**, **1842b** via an Iub interface. The RNCs **1842a**, **1842b** may be in communication with one another via an Iur interface. Each of the RNCs **1842a**, **1842b** may be configured to control the respective Node-Bs **1840a**, **1840b**, **1840c** to which it is connected. In addition, each of the RNCs **1842a**, **1842b** may be configured to carry out or support other functionality, such as outer loop power control, load control, admission control, packet scheduling, handover control, macrodiversity, security functions, data encryption, and the like.

The core network **1806** shown in FIG. **18C** may include a media gateway (MGW) **1844**, a mobile switching center (MSC) **1846**, a serving GPRS support node (SGSN) **1848**, and/or a gateway GPRS support node (GGSN) **1850**. While each of the foregoing elements are depicted as part of the core network **1806**, it will be appreciated that any one of these elements may be owned and/or operated by an entity other than the core network operator.

The RNC **1842a** in the RAN **1803** may be connected to the MSC **1846** in the core network **1806** via an IuCS interface. The MSC **1846** may be connected to the MGW **1844**. The MSC **1846** and the MGW **1844** may provide the WTRUs **1802a**, **1802b**, **1802c** with access to circuit-switched networks, such as the PSTN **1808**, to facilitate communications between the WTRUs **1802a**, **1802b**, **1802c** and traditional land-line communications devices.

The RNC **1842a** in the RAN **1803** may also be connected to the SGSN **1848** in the core network **1806** via an IuPS interface. The SGSN **1848** may be connected to the GGSN **1850**. The SGSN **1848** and the GGSN **1850** may provide the WTRUs **1802a**, **1802b**, **1802c** with access to packet-switched networks, such as the Internet **1810**, to facilitate communications between and the WTRUs **1802a**, **1802b**, **1802c** and IP-enabled devices.

As noted above, the core network **1806** may also be connected to the networks **1812**, which may include other wired or wireless networks that are owned and/or operated by other service providers.

FIG. **18D** is a system diagram of the RAN **1804** and the core network **1807** according to an embodiment. As noted above, the RAN **1804** may employ an E-UTRA radio technology to communicate with the WTRUs **1802a**, **1802b**, **1802c** over the air interface **1816**. The RAN **1804** may also be in communication with the core network **1807**.

The RAN **1804** may include eNode-Bs **1860a**, **1860b**, **1860c**, though it will be appreciated that the RAN **1804** may include any number of eNode-Bs while remaining consistent with an embodiment. The eNode-Bs **1860a**, **1860b**, **1860c** may each include one or more transceivers for communicating with the WTRUs **1802a**, **1802b**, **1802c** over the air interface **1816**. In one embodiment, the eNode-Bs **1860a**, **1860b**, **1860c** may implement MIMO technology. Thus, the eNode-B **1860a**, for example, may use multiple antennas to transmit wireless signals to, and receive wireless signals from, the WTRU **1802a**.

Each of the eNode-Bs **1860a**, **1860b**, **1860c** may be associated with a particular cell (not shown) and may be configured to handle radio resource management decisions, handover decisions, scheduling of users in the uplink and/or

downlink, and the like. As shown in FIG. 18D, the eNode-Bs **1860a**, **1860b**, **1860c** may communicate with one another over an X2 interface.

The core network **1807** shown in FIG. 18D may include a mobility management gateway (MME) **1862**, a serving gateway **1864**, and a packet data network (PDN) gateway **1866**. While each of the foregoing elements are depicted as part of the core network **1807**, it will be appreciated that any one of these elements may be owned and/or operated by an entity other than the core network operator.

The MME **1862** may be connected to each of the eNode-Bs **1860a**, **1860b**, **1860c** in the RAN **1804** via an S1 interface and may serve as a control node. For example, the MME **1862** may be responsible for authenticating users of the WTRUs **1802a**, **1802b**, **1802c**, bearer activation/deactivation, selecting a particular serving gateway during an initial attach of the WTRUs **1802a**, **1802b**, **1802c**, and the like. The MME **1862** may also provide a control plane function for switching between the RAN **1804** and other RANs (not shown) that employ other radio technologies, such as GSM or WCDMA.

The serving gateway **1864** may be connected to each of the eNode-Bs **1860a**, **1860b**, **1860c** in the RAN **1804** via the S1 interface. The serving gateway **1864** may generally route and forward user data packets to/from the WTRUs **1802a**, **1802b**, **1802c**. The serving gateway **1864** may also perform other functions, such as anchoring user planes during inter-eNode B handovers, triggering paging when downlink data is available for the WTRUs **1802a**, **1802b**, **1802c**, managing and storing contexts of the WTRUs **1802a**, **1802b**, **1802c**, and the like.

The serving gateway **1864** may also be connected to the PDN gateway **1866**, which may provide the WTRUs **1802a**, **1802b**, **1802c** with access to packet-switched networks, such as the Internet **1810**, to facilitate communications between the WTRUs **1802a**, **1802b**, **1802c** and IP-enabled devices.

The core network **1807** may facilitate communications with other networks. For example, the core network **1807** may provide the WTRUs **1802a**, **1802b**, **1802c** with access to circuit-switched networks, such as the PSTN **1808**, to facilitate communications between the WTRUs **1802a**, **1802b**, **1802c** and traditional land-line communications devices. For example, the core network **1807** may include, or may communicate with, an IP gateway (e.g., an IP multimedia subsystem (IMS) server) that serves as an interface between the core network **1807** and the PSTN **1808**. In addition, the core network **1807** may provide the WTRUs **1802a**, **1802b**, **1802c** with access to the networks **1812**, which may include other wired or wireless networks that are owned and/or operated by other service providers.

FIG. 18E is a system diagram of the RAN **1805** and the core network **1809** according to an embodiment. The RAN **1805** may be an access service network (ASN) that employs IEEE 802.16 radio technology to communicate with the WTRUs **1802a**, **1802b**, **1802c** over the air interface **1817**. As will be further discussed below, the communication links between the different functional entities of the WTRUs **1802a**, **1802b**, **1802c**, the RAN **1805**, and the core network **1809** may be defined as reference points.

As shown in FIG. 18E, the RAN **1805** may include base stations **1880a**, **1880b**, **1880c**, and an ASN gateway **1882**, though it will be appreciated that the RAN **1805** may include any number of base stations and ASN gateways while remaining consistent with an embodiment. The base stations **1880a**, **1880b**, **1880c** may each be associated with a particular cell (not shown) in the RAN **1805** and may each include one or more transceivers for communicating with

the WTRUs **1802a**, **1802b**, **1802c** over the air interface **1817**. In one embodiment, the base stations **1880a**, **1880b**, **1880c** may implement MIMO technology. Thus, the base station **1880a**, for example, may use multiple antennas to transmit wireless signals to, and receive wireless signals from, the WTRU **1802a**. The base stations **1880a**, **1880b**, **1880c** may also provide mobility management functions, such as handoff triggering, tunnel establishment, radio resource management, traffic classification, quality of service (QoS) policy enforcement, and the like. The ASN gateway **1882** may serve as a traffic aggregation point and may be responsible for paging, caching of subscriber profiles, routing to the core network **1809**, and the like.

The air interface **1817** between the WTRUs **1802a**, **1802b**, **1802c** and the RAN **1805** may be defined as an R1 reference point that implements the IEEE 802.16 specification. In addition, each of the WTRUs **1802a**, **1802b**, **1802c** may establish a logical interface (not shown) with the core network **1809**. The logical interface between the WTRUs **1802a**, **1802b**, **1802c** and the core network **1809** may be defined as an R2 reference point, which may be used for authentication, authorization, IP host configuration management, and/or mobility management.

The communication link between each of the base stations **1880a**, **1880b**, **1880c** may be defined as an R8 reference point that includes protocols for facilitating WTRU handovers and the transfer of data between base stations. The communication link between the base stations **1880a**, **1880b**, **1880c** and the ASN gateway **1882** may be defined as an R6 reference point. The R6 reference point may include protocols for facilitating mobility management based on mobility events associated with each of the WTRUs **1802a**, **1802b**, **1802c**.

As shown in FIG. 18E, the RAN **1805** may be connected to the core network **1809**. The communication link between the RAN **1805** and the core network **1809** may be defined as an R3 reference point that includes protocols for facilitating data transfer and mobility management capabilities, for example. The core network **1809** may include a mobile IP home agent (MIP-HA) **1884**, an authentication, authorization, accounting (AAA) server **1886**, and a gateway **1888**. While each of the foregoing elements are depicted as part of the core network **1809**, it will be appreciated that any one of these elements may be owned and/or operated by an entity other than the core network operator.

The MIP-HA may be responsible for IP address management, and may enable the WTRUs **1802a**, **1802b**, **1802c** to roam between different ASNs and/or different core networks. The MIP-HA **1884** may provide the WTRUs **1802a**, **1802b**, **1802c** with access to packet-switched networks, such as the Internet **1810**, to facilitate communications between the WTRUs **1802a**, **1802b**, **1802c** and IP-enabled devices. The AAA server **1886** may be responsible for user authentication and for supporting user services. The gateway **1888** may facilitate interworking with other networks. For example, the gateway **1888** may provide the WTRUs **1802a**, **1802b**, **1802c** with access to circuit-switched networks, such as the PSTN **1808**, to facilitate communications between the WTRUs **1802a**, **1802b**, **1802c** and traditional land-line communications devices. In addition, the gateway **1888** may provide the WTRUs **1802a**, **1802b**, **1802c** with access to the networks **1812**, which may include other wired or wireless networks that are owned and/or operated by other service providers.

Although not shown in FIG. 18E, it will be appreciated that the RAN **1805** may be connected to other ASNs and the core network **1809** may be connected to other core networks.

The communication link between the RAN 1805 the other ASNs may be defined as an R4 reference point, which may include protocols for coordinating the mobility of the WTRUs 1802a, 1802b, 1802c between the RAN 1805 and the other ASNs. The communication link between the core network 1809 and the other core networks may be defined as an R5 reference, which may include protocols for facilitating interworking between home core networks and visited core networks.

The processes and instrumentalities described herein may apply in any combination, may apply to other wireless technology, and for other services (e.g., not limited for proximity services).

A WTRU may refer to an identity of the physical device, or to the user's identity such as subscription related identities, e.g., MSISDN, SIP URI, etc. WTRU may refer to application-based identities, e.g., user names that may be used per application.

The processes described above may be implemented in a computer program, software, and/or firmware incorporated in a computer-readable medium for execution by a computer and/or processor. Examples of computer-readable media include, but are not limited to, electronic signals (transmitted over wired and/or wireless connections) and/or computer-readable storage media include, but are not limited to, a read only memory (ROM), a random access memory (RAM), a register, cache memory, semiconductor memory devices, magnetic media such as, but not limited to, internal hard disks and removable disks, magneto-optical media, and/or optical media such as CD-ROM disks, and/or digital versatile disks (DVDs). A processor in association with software may be used to implement a radio frequency transceiver for use in a WTRU, UE, terminal, base station, RNC, and/or any host computer.

What is claimed is:

1. A method for providing augmented reality (AR) to a user, comprising:

estimating a gaze point of the user to define a region of interest (ROI), wherein the ROI contains at least one physical object;

adaptively adjusting a size of the ROI based upon one or more of an active command, a gaze focused for a time exceeding a threshold, a user activity, or a number of objects of interest in the first defined ROI exceeding a threshold;

estimating an emotional state of the user;

sending information associated with the adjusted ROI and the emotional state of the user to a server;

receiving information regarding one or more objects in the ROI from the server, wherein the information about the one or more objects in the ROI is filtered based on the emotional state of the user; and

displaying the information regarding the one or more objects in the ROI while the user is in proximity to the one or more objects in the ROI.

2. The method of claim 1, wherein the emotional state of the user is determined by estimating a point for the emotional state on a valence/arousal chart.

3. The method of claim 1, further comprising using voice recognition of an emotion of the user to determine the emotional state.

4. The method of claim 1, further comprising using facial recognition of an emotion of the user to determine the emotional state.

5. The method of claim 1, further comprising using electroencephalographic (EEG) data of the user to determine the emotional state.

6. The method of claim 1, further comprising extracting images from the ROI and creating a set of descriptors for features of the extracted images without input from the user.

7. The method of claim 6, wherein the descriptors are used to search for information about the one or more objects in the ROI.

8. The method of claim 6, wherein the descriptors include a determined location.

9. The method of claim 1, wherein the information regarding one or more objects in the ROI received from the server is less than the total information available for the one or more objects in the ROI.

10. The method of claim 1, further comprising:

determining a gaze point of the user toward the information regarding one or more physical objects in the ROI received from the server; and

if the gaze is focused on the information for a time exceeding the threshold, displaying additional information regarding the one or more objects in the ROI.

11. A device, comprising:

a processor adapted to:

estimate a gaze point of the user to define a region of interest (ROI), wherein the ROI contains at least one physical object;

adaptively adjust a size of the ROI based upon one or more of an active command, a gaze focused for a time exceeding a threshold, a user activity, or a number of objects of interest in the first defined ROI exceeding a threshold;

estimate an emotional state of the user;

send information associated with the ROI and the emotional state of the user to a server;

receive information regarding one or more objects in the ROI from the server, wherein the information about the one or more objects in the ROI is filtered based on the emotional state of the user; and

display the information regarding the one or more objects in the ROI while the user is in proximity to the one or more objects in the ROI.

12. The device of claim 11, wherein a size of the ROI is adjusted based upon a number of objects detected.

13. The device of claim 11, wherein a size of the ROI is based upon a user activity.

14. The device of claim 11, wherein the emotional state of the user is determined by estimating a point for the emotional state on a valence/arousal chart.

15. The device of claim 11, wherein the emotional state is estimated using at least one of voice recognition of an emotion of the user, facial recognition of an emotion of the user, or electroencephalographic (EEG) data of the user.

16. The device of claim 11, wherein images are extracted from the ROI, and a set of descriptors for features of the extracted images objects is created without input from the user.

17. The device of claim 11, wherein the information regarding one or more objects in the ROI received from the server is less than the total information available for the one or more objects in the ROI.

18. The device of claim 11, wherein the processor is further adapted to:

estimate a gaze point of the user toward the information regarding one or more physical objects in the ROI received from the server; and

21

if the gaze is focused on the information for a time exceeding the threshold, display additional information regarding the one or more objects in the ROI.

19. A device, comprising:

a processor adapted to:

estimate a device user's emotional state;

send information to a server about the user and one or more physical objects in a region of interest (ROI); and

receive filtered information about the one or more objects in the ROI based upon an estimate from the server of the emotional state of the user; and display the filtered information regarding the one or more objects in the ROI while the user is in proximity to the one or more objects in the ROI.

20. The device of claim **19**, wherein the processor is further adapted to adaptively adjust a size of the ROI based upon one or more of an active command, a gaze focused for a time exceeding a threshold, a user activity, or a number of objects of interest in the first defined ROI exceeding a threshold.

21. The device of claim **19**, wherein the processor is further adapted to:

estimate a gaze point of the user toward the information regarding one or more physical objects in the ROI received from the server; and

if the gaze is focused on the information for a time exceeding a threshold, display additional information regarding the one or more objects in the ROI.

* * * * *

22

30

专利名称(译)	凝视驱动的增强现实		
公开(公告)号	US9922253	公开(公告)日	2018-03-20
申请号	US15/028233	申请日	2014-10-10
[标]申请(专利权)人(译)	内数位专利控股公司		
申请(专利权)人(译)	INTERDIGITAL专利HOLDINGS , INC.		
当前申请(专利权)人(译)	INTERDIGITAL专利HOLDINGS , INC.		
[标]发明人	ASBUN EDUARDO REZNIK YURIY ZEIRA ARIELA STERNBERG GREGORY S NEFF RALPH		
发明人	ASBUN, EDUARDO REZNIK, YURIY ZEIRA, ARIELA STERNBERG, GREGORY S. NEFF, RALPH		
IPC分类号	G09G5/00 A61B5/00 G06K9/00 G06F3/01 G02B27/01 A61B5/11 A61B5/16 A61B5/053 A61B5/0476		
CPC分类号	H04W4/30 G06K9/00671 A61B5/0022 A61B5/1112 A61B5/165 A61B5/742 G06F3/013 G06K9/00302 G06K9/00604 G02B27/017 G06F3/015 A61B5/0476 A61B5/0533 A61B5/163 G16H40/67		
审查员(译)	王 , 金城		
优先权	61/889900 2013-10-11 US		
其他公开文献	US20160259977A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了增强现实 (AR) 系统, 方法和手段。可以估计用户的凝视点, 并且可以使用该凝视点来搜索和呈现信息, 例如, 与用户正在关注的区域有关的信息。用户的凝视点可以用于促进或启用可以由用户的视线方向控制的交互模式和/或用户界面。生物识别技术可用于估计用户的情绪状态。该估计的情绪状态可以用于呈现给用户的信息。

