




US 20180344249A1

(19) **United States**(12) **Patent Application Publication**  
**McKinney et al.**(10) **Pub. No.: US 2018/0344249 A1**(43) **Pub. Date: Dec. 6, 2018**(54) **CATHETER WITH CONNECTABLE HUB  
FOR MONITORING PRESSURE***A61M 25/10* (2006.01)*A61M 25/00* (2006.01)*A61B 5/01* (2006.01)(71) Applicant: **Sentinel Medical Technologies, LLC,**  
Boca Raton, FL (US)(52) **U.S. Cl.**CPC ..... *A61B 5/6853* (2013.01); *A61B 5/03*  
(2013.01); *A61M 25/1018* (2013.01); *A61B*  
*2018/00517* (2013.01); *A61M 25/0097*  
(2013.01); *A61B 5/01* (2013.01); *A61M*  
*2025/0002* (2013.01); *A61M 25/0026*  
(2013.01)(72) Inventors: **Timothy McKinney**, Boca Raton, FL  
(US); **Marc-Alan Levine**, Pottstown,  
PA (US)(73) Assignee: **Sentinel Medical Technologies, LLC,**  
Boca Raton, FL (US)(21) Appl. No.: **15/949,016**

(57)

**ABSTRACT**(22) Filed: **Apr. 9, 2018****Related U.S. Application Data**(60) Provisional application No. 62/514,793, filed on Jun.  
3, 2017, provisional application No. 62/544,680, filed  
on Aug. 11, 2017, provisional application No. 62/590,  
513, filed on Nov. 24, 2017, provisional application  
No. 62/622,871, filed on Jan. 27, 2018.**Publication Classification**(51) **Int. Cl.***A61B 5/00* (2006.01)*A61B 5/03* (2006.01)

A multi-lumen catheter with a connectable hub for monitoring intra-abdominal pressure including an expandable outer balloon and a first lumen communicating with the balloon. The balloon and first lumen are filled with gas to form a gas filled chamber to monitor pressure within the bladder to thereby monitor pressure within an abdomen of the patient. A second lumen communicates with the bladder to remove fluid from the bladder. The hub includes a pressure transducer for measuring bladder pressure based on gas compression and has an elongated member insertable into the first lumen to advance gas through first lumen to expand the balloon.






Figure 1A




Figure 1B




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8A




Figure 8B




Figure 9




Figure 10A







Figure 10B






Figure 13B




Figure 14A




Figure 14B




Figure 15




Figure 16




Figure 17A









Figure 17B












Figure 22B




Figure 22C




Figure 22A




Figure 23




Figure 24B




Figure 24A





Figure 25A







Figure 27

Figure 26







Figure 28B






Figure 28D




Figure 29A




Figure 29B




Figure 35.3

## CATHETER WITH CONNECTABLE HUB FOR MONITORING PRESSURE

[0001] This application claims the benefit of provisional application Ser. No. 62/514,793, filed Jun. 3, 2017, provisional application Ser. No. 62/544,680, filed Aug. 11, 2017, provisional application Ser. No. 62/590,513, filed Nov. 24, 2017 and provisional application 62/622,871, filed Jan. 27, 2018. The entire contents of each of these applications are incorporated herein by reference.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

[0002] This application relates to a catheter and connectable hub for monitoring intra-abdominal pressure through the urinary bladder.

#### 2. Background

[0003] Traditionally, physicians relied on visual cues or physical examination to detect increase in intra-abdominal pressure (IAP). More recently Dr. Kirkpatrick and colleagues, in an article "Is Clinical Examination an Accurate Indicator of Raised Intra-Abdominal Pressure in Critically Injured Patients," CJS, June 2000, 43, No. 3, 207-211, showed that IAP measured through the patient's bladder was significantly more accurate than physical examination. That is, it was demonstrated that the clinical abdominal examination was insensitive and inaccurate when compared with urinary bladder pressure measurements.

[0004] Various tools for measuring IAP have been developed over the years. Many researchers have documented IAP measurements through almost every natural or man-made orifice in the body. Earlier crude forms of measuring IAP used bladder catheters, nasogastric tubes, and rectal tubes attached to a manometer. The nasogastric or the rectal route was better suited in rare cases of bladder rupture or situations where bladder catheters were contraindicated. However, due to local interferences, the nasogastric and the rectal tube measurements were neither reproducible nor logical as were the bladder catheters.

[0005] Thus, measuring of IAP through the bladder became more suitable. In 1989 Iberti and colleagues in an article entitled, "Determination of Intra-abdominal Pressure Using a Transurethral Bladder Catheter: Clinical Validation of the Technique," Anesthesiology, January 1989, 70(1), 47-50, validated the correlation of IAP using a catheter inserted in the bladder. Their study was key in using bladder pressure as the gold standard for measuring IAP. In 1995, Kron and colleagues published a study in "The Measurement of Intra-Abdominal Pressure as a Criterion for Abdominal Re-exploration, 1984 Ann Surg., 199, 28-30, comparing catheters in various body locations for measuring IAP. They measured IAP from the stomach using a nasogastric tube, from the rectum using a modified rectal tube, from the bladder using a modified bladder catheter, and direct abdominal pressure using a laparoscopic insufflator needle. They found that the bladder catheter had the best measurement of IAP and that the gastric and the rectal catheter measurements were less reliable due to dependence on the position of the catheter. Thus, clinicians generally agreed that the urinary bladder is the best-suited location for measurement of IAP.

[0006] The need for measuring IAP has become more important as physicians increasingly realized that organ failure and death were directly related to increase in IAP in certain high-risk patients. High abdominal pressure has been found to cause a decrease in function of the intestines, liver and blood vessels resulting in adverse consequences for the patients. Consequently, accurate measurement of IAP can help decrease patient morbidity and mortality. It has also been more recently discovered that pediatric and neonate population may also have need for IAP measurement to determine specific conditions.

[0007] Currently, there are few products available on the market to measure the IAP through the bladder. One device, the Bard IAP device, has a "valve clamp" which diverts urine from the main catheter drainage channel to measure IAP via converting hydrostatic pressure to a readable pressure gauge. This mechanism of IAP measurements is archaic and does not provide continuous pressure measurement when used with the standard 2-channel bladder drainage catheter. Two other manufacturers, Holtech and ConvaTec, also use a column of urine by connecting their kit to an existing bladder catheter. Their systems are cumbersome and the IAP readings are also not continuous. Biometrix has developed an IAP monitoring device which like other manufacturers relies on tapping into the main bladder drainage catheter, using a valve to measure the hydrostatic pressure. In 2008 Sugrue and colleagues, in an article "Prospective Study of Intra-Abdominal Hypertension and Renal Function after Laparotomy, British Journal of Surgery, 1999, 82, 235-238, suggested the use of 3-channel bladder drainage catheter so that the smaller channel, which was used for bladder irrigation, could be used to attach a pressure-monitoring device. The use of an extra channel made it possible to have continuous bladder drainage while measuring the bladder pressure. However, this bladder catheter did not provide a continuous pressure read because intermittently the operator needed to add 50 ml of water or saline to the bladder to record the IAP pressure. Thus, the pressure reading at best was intermittent since pressure readings were not performed when fluid was being added to the bladder. Consequently, although this was a step toward increasing the amount of pressure readings/recordings, it still was unable to conduct continuous pressure monitoring. Furthermore, it was still the same cumbersome IAP device set up which required a skilled person to add water before each IAP reading. Control of the amount of water added is critical since adding too much water to the bladder can falsely increase the pressure readings and also increase infection risk, thus further complicating the use.

[0008] It has also been recognized that most patients that have a need for measurement of IAP also need to have continuous drainage of the urinary bladder and thus devices need to account for this process.

[0009] Consequently, current devices placed in the bladder for measuring pressure require a continuous water column to maintain pressure readings. Thus, they fail to measure IAP continuously but only measure pressure intermittently. They also all rely on tapping into an existing bladder drainage catheter, which adds complications. Furthermore, they do not reduce the complexity of the procedure since they require constant retrograde insertion of a relatively large amount of fluid into the bladder, e.g., 50 cc, which increases the ICU workload. Still further, these devices increase the risk of complications and infections associated with fluid

injection into the bladder. Fluid injection is also complicated since it needs to be closely monitored since too much fluid in the bladder can give false elevation of IAP readings, causing clinicians to take unnecessary steps in response to what is mistakenly believed is excess IAP.

**[0010]** It would therefore be advantageous to provide a device insertable into the bladder that accurately measures abdominal pressure without requiring adding water to the bladder to obtain such pressure readings. Such device would advantageously avoid the complications and risks associated with such fluid insertion. Furthermore, it would be advantageous if such device could continuously measure bladder pressure without interruption. This would advantageously enable a constant monitoring of IAP so critical time periods are not missed. It would further be advantageous to provide a device that improves the accuracy of the pressure reading in the bladder to more accurately determine IAP so necessary steps can be taken to address IAP only when warranted. Still further, it would be advantageous if such device could satisfy the foregoing needs and provide these enumerated advantages while being simple to use so that any of clinical staff with basic knowledge of bladder catheter insertion will be able to insert the device without relying on specially trained staff members.

#### SUMMARY

**[0011]** The present invention overcomes the deficiencies and disadvantages of the prior art. The present invention advantageously provides a multi-lumen catheter insertable into the bladder in the same manner as a regular bladder drainage catheter to determine intra-abdominal pressure without requiring insertion of water into the bladder. The catheters of the present invention utilize a gas-charged chamber to measure bladder pressure across a large surface area, and thus, accurately determine intra-abdominal pressure, and enable pressure to be measured continuously without interrupting urine flow and without interruptions to add water to the bladder.

**[0012]** Some embodiments of the catheter of the present invention utilize a stabilizing balloon to help retain the catheter in the bladder during the procedure.

**[0013]** In accordance with one aspect of the present invention, a multi-lumen catheter for monitoring pressure in a patient is provided comprising an expandable outer balloon at a distal portion of the catheter. An expandable inner balloon is positioned within the outer balloon. A first lumen communicates with the inner balloon and the inner balloon and first lumen form a gas filled chamber to monitor pressure within the bladder. The outer balloon has a circumferential area greater than a circumferential area of the inner balloon, wherein in response to pressure within the bladder exerted on the first outer wall of the expanded outer balloon, the outer balloon deforms and exerts a pressure on the second outer wall of the expanded inner balloon to deform the inner balloon and compress the gas within the inner balloon and the first lumen to provide a finer measurement. A second lumen communicates with the bladder to remove fluid from the bladder. A pressure transducer communicates with the gas filled chamber for measuring bladder pressure based on gas compression caused by deformation of the expanded inner balloon deformed by the expanded outer balloon.

**[0014]** In some embodiments, the gas filled chamber monitors pressure within the bladder to thereby monitor pressure within an abdomen of the patient.

**[0015]** In some embodiments, the pressure transducer measures average pressure continuously throughout insertion of the catheter within the urethra without requiring infusion of water into the bladder.

**[0016]** In some embodiments, the pressure transducer is an external transducer connectable to the catheter. In some embodiments, the pressure transducer is contained within a hub and the hub includes an elongated member extending distally therefrom, and connection of the pressure transducer to a first port of the catheter automatically inserts the elongated member into the first lumen to advance gas into the inner balloon to expand the inner balloon. In some embodiments, the first lumen is not vented to atmosphere when the pressure transducer is connected to the catheter and advances gas to expand the inner balloon.

**[0017]** In some embodiments, the gas within the inner balloon and/lumen is air to provide an air filled chamber.

**[0018]** In some embodiments, the second lumen has a side opening distal of the inner and outer balloons; in other embodiments the side opening is proximal of the inner and outer balloons. The catheter can include a third lumen communicating with the outer balloon to expand the outer balloon. In some embodiments, the hub includes a second elongated member insertable into the third lumen to automatically advance gas into the outer balloon to expand the outer balloon when the hub is connected to the catheter. In some embodiments, the outer balloon is in communication with the first lumen and gas advanced through the first lumen also expands the outer balloon.

**[0019]** In some embodiments, the catheter has a fourth lumen and a temperature sensor positioned within the fourth lumen to measure core body temperature. A wire can extend from the temperature sensor through the fourth lumen and external of the catheter into the hub connected to the catheter. The hub can have a first opening to receive a connector of the wire to automatically connect the temperature sensor to a cable extendable from the hub and connectable to an external temperature monitor.

**[0020]** In some embodiments, connection of the pressure transducer to the catheter a) automatically connects the temperature sensor to a temperature monitor cable; and b) automatically advances air through the first lumen to expand the inner balloon.

**[0021]** In some embodiments, the catheter includes a stabilizing balloon proximal of the outer balloon for stabilizing the catheter, and the catheter includes a fifth lumen communicating with the stabilizing balloon to expand the stabilizing balloon.

**[0022]** In some embodiments, the outer balloon has a circumference engageable with a wall of the bladder at multiple contact regions to provide multiple reference points for calculation of an average pressure of the bladder wall. In some embodiments, the outer balloon has a distal region having a larger transverse cross-section than a proximal region.

**[0023]** In accordance with another aspect of the present invention, a multi-lumen catheter for monitoring intra-abdominal pressure is provided comprising a distal balloon at a distal portion of the catheter and a first lumen communicating with the distal balloon. The distal balloon and first lumen form a gas filled chamber to monitor pressure within the bladder to thereby monitor pressure within an abdomen of the patient, wherein in response to pressure within the bladder the distal balloon deforms to compress the gas

within the distal balloon. The first lumen has a first proximal port communicating with the first lumen. A second lumen communicates with the bladder to remove fluid from the bladder and a temperature sensor is positioned in a third lumen of the catheter and has a wire extending through the third lumen. A hub is connectable to the first port of the catheter and includes a pressure transducer for measuring pressure based on gas compression within the first lumen, wherein connection of the hub to the first port automatically connects the wire to an electrical connector in the hub for connection to a temperature monitor.

**[0024]** In some embodiments, connection of the hub to the first port automatically advances gas into the distal balloon to expand the distal balloon, the first lumen remaining sealed to outside air during expansion of the distal balloon. The hub can include an elongated member extending distally therefrom and insertable into the first lumen to advance gas into the distal balloon upon connection of the hub to the first port. The hub can include a shroud over the elongated member and the shroud in some embodiments, snap fits over the first port. In some embodiments, the first port has a valve and the elongated member is insertable through the valve when the hub is connected to the catheter. The catheter in some embodiments includes a stabilizing balloon positioned proximal of the distal balloon for stabilizing the catheter.

**[0025]** In accordance with another aspect of the present invention, a multi-lumen catheter for monitoring intra-abdominal pressure is provided comprising a distal balloon at a distal portion of the catheter and a first lumen communicating with the distal balloon. The distal balloon and first lumen form a gas filled chamber to monitor pressure within the bladder to thereby monitor pressure within an abdomen of the patient, wherein in response to pressure within the bladder the distal balloon deforms to compress the gas within the distal balloon. The first lumen has a first proximal port communicating with the first lumen. A second lumen communicates with the bladder to remove fluid from the bladder. A hub is connectable to the first port of the catheter, the hub including a pressure transducer for measuring pressure based on gas compression with the first lumen. An elongated member extends distally from the hub, wherein connection of the hub to the first port automatically inserts the elongated member into the first lumen to advance gas through the first lumen to expand the distal balloon, the first lumen not vented to atmosphere when the hub is connected to the first port.

**[0026]** In some embodiments, a shroud is positioned over the elongated member and the shroud can be snap fit over the first port or attached in other ways. In some embodiments, the first port has a valve and the elongated member is insertable through the valve when the hub is connected to the catheter. The catheter can include a stabilizing balloon proximal of the distal balloon for stabilizing the catheter.

**[0027]** In accordance with another aspect of the present invention, a method for measuring intra-abdominal pressure is provided comprising the steps of:

**[0028]** providing a catheter having first and second lumens, an expandable first balloon and a temperature sensor;

**[0029]** inserting the catheter through the urethra into a bladder of a patient;

**[0030]** connecting a hub containing a pressure transducer to the first lumen to automatically advance air through the first lumen of the catheter to expand the first balloon from a

deflated condition to a more expanded condition and to automatically connect the temperature sensor to a connector within the hub;

**[0031]** obtaining a first pressure reading of the bladder based on deformation of the balloon without injecting fluid into the bladder;

**[0032]** transmitting the first pressure reading to an external monitor connected to the hub;

**[0033]** obtaining a second pressure reading of the bladder based on deformation of the balloon without injecting fluid into the bladder;

**[0034]** transmitting the second pressure reading to the external monitor connected to the hub; and

**[0035]** obtaining consecutive continuous pressure readings of the bladder without injecting fluid into the bladder.

**[0036]** The method can further include the step of draining the bladder through the second lumen of the catheter. In some embodiments, the step of obtaining pressure readings obtains average pressure.

**[0037]** In some embodiments, the catheter includes an outer balloon positioned over the first balloon and the outer balloon is expandable through a separate lumen of the catheter and deformable based on bladder pressure to deform the first balloon to provide finer measurements of bladder pressure. In some embodiments, the step of connecting a pressure transducer advances an elongated member extending from the hub into the first lumen to advance air into the first balloon. In some embodiments, the temperature sensor is positioned in a lumen of the catheter independent of the first lumen.

**[0038]** In accordance with another aspect of the present invention, a multi-lumen catheter for monitoring intra-abdominal pressure is provided. The catheter includes an elongated body configured and dimensioned for insertion into a bladder of a patient, a first lumen, a second lumen, and a first balloon at a distal portion. The first lumen communicates with the first balloon and the second lumen communicates with the bladder to remove fluid from the bladder. The first balloon is filled with a gas to form along with the first lumen a gas filled chamber to monitor pressure within the bladder to thereby monitor pressure within an abdomen of the patient. A sensor is positioned at the distal portion of the catheter to measure pressure about a circumferential area of the balloon.

**[0039]** In accordance with another aspect of the present invention, a multi-lumen catheter is provided for monitoring intra-abdominal pressure, the catheter comprising an elongated body configured and dimensioned for insertion into the bladder of a patient, a first lumen, a second lumen, and a first balloon at a distal portion. The first lumen communicates with the first balloon and the second lumen communicates with the bladder to remove fluid from the bladder. The first balloon is filled with a gas to form a gas filled chamber to monitor pressure within the bladder to thereby monitor pressure within an abdomen of the patient. A pressure sensor is positioned at the distal portion of the catheter for continuously measuring pressure of the bladder to provide continuous readings of bladder pressure.

**[0040]** In accordance with another aspect of the present invention, a multi-lumen catheter for monitoring intra-abdominal pressure is provided. The catheter includes an elongated body configured and dimensioned for insertion into a bladder of a patient, a first lumen, a second lumen, a third lumen, a first balloon at a distal portion and a second

balloon proximal of the first balloon. The first lumen communicates with the first balloon, the second lumen communicates with the bladder to remove fluid from the bladder, and the third lumen communicates with the second balloon to inflate the second balloon to stabilize the catheter. The first balloon is filled with a gas to form a gas filled chamber to monitor pressure within the bladder to thereby monitor pressure within an abdomen of the patient. A sensor measures pressure within the bladder as the first balloon changes shape in response to changes in pressure in the bladder.

**[0041]** In accordance with another aspect of the present invention, a multi-lumen catheter is provided for monitoring intra-abdominal pressure, the catheter comprising an elongated body configured and dimensioned for insertion into a bladder of a patient, a first lumen, a second lumen, and a first balloon at a distal portion. The first lumen communicates with the first balloon and the second lumen communicates with the bladder to remove fluid from the bladder, the first balloon filled with a gas to form a gas filled chamber to monitor pressure within the bladder to thereby monitor pressure within an abdomen of the patient. A pressure sensor measures pressure of the bladder and the first lumen extends distally of the first balloon.

**[0042]** In accordance with another aspect of the present invention, a multi-lumen catheter for monitoring intra-abdominal pressure is provided comprising an elongated body configured and dimensioned for insertion into a bladder of a patient, a first lumen, a second lumen and a first balloon at a distal portion. A first side port communicates with the first lumen and the first lumen communicates with the first balloon. The second lumen communicates with the bladder to remove fluid from the bladder. The first balloon is filled with a gas to form a gas filled chamber to monitor pressure within the bladder to thereby monitor pressure within the abdomen. A pressure sensor measures pressure of the bladder and is positioned distal of the first side port for measuring pressure within the bladder resulting in a change of shape of the first balloon in response to changes in pressure in the bladder.

**[0043]** In accordance with another aspect of the present invention, a multi-lumen catheter for monitoring intra-abdominal pressure is provided. The catheter includes an elongated body configured and dimensioned for insertion into a bladder of a patient, a first lumen, a second lumen, and a third lumen, the lumens being independent. A first balloon is positioned at a distal portion and the first lumen communicates with the first balloon. The second lumen communicates with the bladder to remove fluid from the bladder. The first balloon and first lumen are filled with a gas to form a gas filled fully closed chamber to monitor pressure within the bladder to thereby monitor pressure within an abdomen of the patient. A pressure sensor measures pressure within the bladder based on deformation of the first balloon in response to pressure within the bladder exerted on an outer wall of the balloon, the pressure sensor measuring bladder pressure continuously and communicating with an external monitor to visually display pressure readings, the sensor providing continuous pressure measurements throughout its duration of insertion without requiring infusion of water into the bladder.

**[0044]** In accordance with another aspect of the present invention, a multi-lumen catheter for monitoring intra-abdominal pressure is provided. The catheter includes an elongated body configured and dimensioned for insertion

into a bladder of a patient, a first lumen, a second lumen, an outer balloon at a distal portion and an inner balloon within the outer balloon. The first lumen communicates with the inner balloon and the second lumen communicates with the bladder to remove fluid from the bladder. The inner balloon and first lumen are filled with a gas to form a gas filled chamber to monitor pressure within the bladder to thereby monitor pressure within an abdomen of the patient. The outer balloon has a circumferential area greater than a circumferential area of the inner balloon and inflated with a fluid (liquid or a gas, e.g., air) wherein in response to pressure within the bladder exerted on an outer wall of the outer balloon, the outer balloon deforms and exerts a pressure on an outer wall of the inner balloon to deform the inner balloon and compress the gas, e.g., air, within the inner balloon and the first lumen. The pressure sensor measures bladder pressure based on gas compression caused by deformation of the inner balloon. As noted herein, the balloon(s) can be expanded by a gas such as air.

**[0045]** In accordance with another aspect of the present invention, a system for monitoring intra-abdominal pressure is provided comprising a catheter having an elongated body configured and dimensioned for insertion into the bladder of a patient, a first lumen, a second lumen, a third lumen, and a first balloon at a distal portion. The first lumen communicates with the first balloon and the second lumen communicates with the bladder to remove fluid from the bladder. The first balloon and first lumen are filled with a gas to form a gas filled fully closed chamber to monitor pressure within the bladder to thereby monitor pressure within an abdomen of the patient. A pressure sensor measures bladder pressure continuously and communicates with an external monitor to visually display pressure readings, the sensor providing continuous pressure measurements during its insertion without requiring infusion of water into the bladder. An indicator indicates if the measured pressure exceeds a threshold value.

**[0046]** The indicator can be a visual and/or audible indicator.

**[0047]** In accordance with another aspect, the present invention provides a method for measuring intra abdominal pressure comprising the steps of a) providing a catheter having first and second lumens and a balloon; b) inserting the catheter into a bladder of a patient; c) injecting gas into the first lumen of the catheter to expand the balloon from a deflated condition to a partially inflated condition; d) obtaining a first pressure reading of the bladder based on deformation of the balloon without injecting fluid into the bladder; e) transmitting the first pressure reading to an external monitor connected to the catheter; f) obtaining a second pressure reading of the bladder based on deformation of the balloon without injecting fluid into the bladder; g) transmitting the second pressure reading to the external monitor connected to the catheter; and h) obtaining consecutive continuous pressure readings of the bladder without injecting fluid into the bladder.

**[0048]** The method can include measuring the temperature of a body of a patient utilizing a temperature sensor within the first lumen.

#### BRIEF DESCRIPTION OF THE DRAWINGS

**[0049]** So that those having ordinary skill in the art to which the subject invention appertains will more readily understand how to make and use the surgical apparatus

disclosed herein, preferred embodiments thereof will be described in detail hereinbelow with reference to the drawings, wherein:

[0050] FIG. 1A is a side view of a first embodiment of the catheter of the present invention having a pressure balloon, a stabilizing balloon and a sensor positioned in the air lumen, both balloons shown in the deflated (collapsed) condition;

[0051] FIG. 1B is a side view similar to FIG. 1A showing the two balloons in the inflated (expanded) condition;

[0052] FIG. 2 is a schematic view of the system utilizing the catheter of FIG. 1A with an alarm system;

[0053] FIG. 3 is a close-up view of the tip of the catheter of FIG. 1A;

[0054] FIG. 4 is a close-up view of the sensor of FIG. 1A within the air lumen;

[0055] FIG. 5 is an enlarged transverse cross-sectional view of the catheter of FIG. 1;

[0056] FIG. 6 is an enlarged transverse cross-sectional view of an alternate embodiment of a catheter of the present invention having four lumens;

[0057] FIG. 7 is a side view of an alternate embodiment of the catheter of the present invention similar to FIG. 1A except having a single balloon, the balloon shown in the inflated condition,

[0058] FIGS. 8A and 8B are side views of an alternate embodiment of the catheter of the present invention having two balloons and a pressure sensor and a separate temperature sensor in the air lumen, the two balloons shown in the deflated condition, with FIG. 8A showing the distal end and FIG. 8B showing the proximal end of the catheter;

[0059] FIG. 9 is a side view similar to FIG. 8A showing the two balloons in the inflated condition;

[0060] FIG. 10A is a close up view of the distal portion of the catheter of FIG. 8A;

[0061] FIG. 10B is an enlarged transverse cross-sectional view of the catheter of FIG. 8A;

[0062] FIG. 11 is a side view of another alternate embodiment of the catheter of the present invention having two balloons, a sensor in the air lumen and an external transducer, the two balloons shown in the inflated condition;

[0063] FIG. 12 is a side view of another alternate embodiment of the catheter of the present invention having two balloons, a temperature sensor in the air lumen and the pressure sensor external of the catheter, the two balloons shown in the inflated condition;

[0064] FIG. 13A is a side view of another alternate embodiment of the catheter of the present invention having two balloons and a pressure sensor positioned within the pressure balloon, the two balloons shown in the inflated condition;

[0065] FIG. 13B is an enlarged view of the distal portion of the catheter of FIG. 13A;

[0066] FIG. 14A is a side view of another alternate embodiment of the catheter of the present invention having dual pressure sensors, the first sensor positioned within the air lumen and the second sensor positioned external of the catheter, the two balloons shown in the inflated condition;

[0067] FIG. 14B is an enlarged view of the distal portion of the catheter of FIG. 14A;

[0068] FIG. 15 is a side view of another alternate embodiment of the catheter of the present invention having an outer and inner pressure balloon and a stabilizing balloon, the balloons shown in the inflated condition;

[0069] FIG. 16 is a side view similar to FIG. 15 illustrating an alternate embodiment having a larger outer balloon;

[0070] FIG. 17A is a side view similar to FIG. 15 illustrating an alternate embodiment having a pear-shaped outer balloon;

[0071] FIG. 17B is a side view similar to FIG. 17A showing an alternate embodiment wherein the drainage opening is between the two balloons;

[0072] FIG. 18A is a side view of another alternate embodiment of the catheter of the present invention having a port for connection to an external pressure transducer and an outer and inner pressure balloon, the two balloons shown in the inflated condition;

[0073] FIG. 18B is close up view of the distal end of the catheter of FIG. 18A;

[0074] FIG. 19 is a perspective view of the catheter of FIG. 18A with a pressure transducer hub attached to the catheter;

[0075] FIGS. 20A, 20B and 20C are enlarged front, side and perspective views of the outer balloon of FIG. 18A in the expanded condition;

[0076] FIGS. 21A, 21B and 21C are enlarged front, side and perspective views of the stabilizing balloon of FIG. 18A in the expanded condition;

[0077] FIGS. 22A, 22B and 22C are enlarged front, side and perspective views of the inner balloon of FIG. 18A in the expanded condition;

[0078] FIG. 23 is a transverse cross-sectional view of the catheter of FIG. 18 illustrating the five lumens of the catheter;

[0079] FIG. 24A is a cutaway side view showing the pressure transducer hub prior to connection to the catheter of FIG. 18A, a portion of the hub wall and catheter connector removed to show internal components;

[0080] FIG. 24B is a side view similar to FIG. 24A showing the hub attached to the catheter;

[0081] FIG. 25A is a perspective view of the transducer hub of FIG. 24A;

[0082] FIG. 25B is a perspective view of the proximal end of the catheter showing a connector for the thermocouple wire;

[0083] FIG. 26 is a side view of alternate embodiment of the pressure transducer hub having a shroud over the elongated member for snap fitting onto the catheter;

[0084] FIG. 27 is a schematic view of an alternate embodiment of the pressure transducer hub extendable into two side ports of the catheter;

[0085] FIG. 28A is a perspective view of an alternate embodiment of the transducer hub and connector;

[0086] FIG. 28B is a cutaway side view of the hub and connector of FIG. 28A showing the pressure transducer prior to connection to the catheter of FIG. 18A, a portion of the hub wall and connector removed to show internal components;

[0087] FIG. 28C is a cutaway side view similar to FIG. 28B showing the hub attached to the catheter;

[0088] FIG. 28D is a cutaway side view similar to FIG. 28B from the other side;

[0089] FIG. 29A is a cutaway side view of the hub and connector of an alternate embodiment showing the pressure transducer prior to connection to the catheter of FIG. 18A, a portion of the hub wall and catheter connector removed to show internal components

[0090] FIG. 29B is a cutaway side view of the hub and connector of FIG. 29A; and

[0091] FIG. 29C is a cutaway view similar to FIG. 29B showing the hub attached to the connector of FIG. 29A when attached.

#### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0092] Increased abdominal pressure can cause many adverse conditions including diminishing the function of the intestines, liver, and blood vessels. Simply viewing or feeling the abdomen does not provide sufficient information or reading of health conditions.

[0093] It is recognized that urinary bladder pressure directly correlates to the intra-abdominal pressure. Although pressure readings can be determined by access to the esophagus or rectum, the bladder has been found to be the most accurate and the least invasive. In trauma or burn patients for example, time is critical and the less complicated the method for determining bladder pressure the better the clinical results.

[0094] The catheters of the present invention measure abdominal pressure via measurement of bladder pressure without filling the bladder with water. This avoids the risks associated with retrograde filling of the bladder with water as such retrograde filling not only increases the complications and workload for the intensive care (IC) staff and can create inaccuracies by providing false elevation of IAP readings, but can adversely affect the patient by increasing the risk of infection. Furthermore, by avoiding refilling of the bladder, bladder pressure can be measured continuously. This is because in devices requiring filling the bladder with water, water needs to be periodically added to the bladder to replace the water drained from the bladder and measurement readings are interrupted during water insertion. Due to these repeated interruptions, pressure cannot be read continuously. Note in some cases, as much as 50 cc of fluid needs to be repeatedly added to the bladder.

[0095] Thus, the catheters of the present invention efficiently and effectively measure bladder pressure without requiring filling the bladder with water. Also, as will become apparent from the discussion below, the catheters of the present invention provide a more accurate reading of pressure and enable continuous monitoring of the bladder pressure. This is all achieved in an easy to insert device.

[0096] It should be noted that the catheters of the present invention can be utilized for measuring other pressure in a patient and are not limited to intra-abdominal pressure.

[0097] Furthermore, in some embodiments, the catheter of the pressure invention provides a dual sensor to provide a backup pressure reading. In some embodiments, a dual pressure balloon arrangement is provided. This various embodiments are discussed in more detail below.

[0098] Referring now to the drawings and particular embodiments of the present invention wherein like reference numerals identify similar structural features of the devices disclosed herein, there is illustrated in FIGS. 1A-5 a catheter of a first embodiment of the present invention. The catheter (device) is designated generally by reference numeral 10 and is configured for insertion into and positioning within the bladder of the patient for measuring intra-abdominal pressure. This measurement is to check if the intra-abdominal pressure exceeds a specified threshold since if such threshold is exceeded, there is a risk to the patient as discussed

above and steps need to be taken to reduce the pressure such as draining additional fluid from the abdomen, opening the abdomen, etc.

[0099] The catheter 10 of the present invention can in some embodiments include an alarm or indicator to alert the user if pressure within the bladder, which correlates to pressure within the abdomen, rises to an unacceptable level, i.e., beyond a threshold or predetermined value (pressure). The indicator or alarm can be on the catheter or alternatively on an external device such as the monitor as discussed in more detail below. The alarm can also be connected via wireless connection to a phone or remote device to alert the appropriate personnel. The indicator or alarm can alternatively or in addition be activated if a change in pressure measurement exceeds a specified rate over a specified period of time.

[0100] Turning now to details of the catheter 10, which is also referred to herein as the device 10, and with initial reference to FIGS. 1A, 1B, 3 and 4 the catheter 10 of this embodiment has an elongated flexible shaft 12 having a lumen (channel) 14 extending within the shaft 12 and communicating at its distal region with balloon 16 to fluidly communicate with balloon 16 to inflate the balloon. Balloon 16 is utilized for monitoring pressure and is also referred to herein as the “pressure balloon.” A fluid port 15 is positioned at a proximal region 17 of the catheter 10 for communication with an infusion source for infusion of gas, e.g., air, through the lumen 14 and into the balloon 16. The catheter 10 is shown in FIG. 1A with balloon 16 in the deflated condition (position) and in FIG. 1B with the balloon 16 in the inflated condition (position). The shaft 12 also includes a second lumen (channel) 20 and third lumen (channel) 24 extending therein (see also FIG. 5). In a preferred embodiment, the second lumen 20 is the largest lumen and is configured for continuous drainage of bodily contents from the bladder and can be connected to a drainage bag for collection of urine. Second lumen 20 has a side opening 22 at a distal portion, best shown in FIG. 3, communicating with the bladder. The third lumen 24 terminates at its distal end within balloon 26 to fluidly communicate with balloon 26 to inflate the balloon 26. The balloon 26 is inflatable to stabilize the catheter 10 to limit movement of the catheter 10 to keep it in place within the bladder and is also referred to herein as “the stabilizing balloon 26.” A fluid port 28 is positioned at a proximal region 17 of the catheter 10 for communication with an infusion source for infusion of fluid through the lumen 24 and into the balloon 26. The balloon 26 can be filled with fluid, e.g., liquid such as water or saline, or a gas, e.g., air. In FIG. 1A, the balloon 26 is shown in the deflated condition and in FIG. 1B in the inflated condition.

[0101] Note FIG. 5 is a transverse cross-section of the catheter showing the three lumens of various shapes. These cross-sectional shapes of the lumens are provided by way of example as one or more of the lumens can be circular, oval or other symmetrical or asymmetrical shapes in transverse cross section. This also applies to the cross-sectional views of the other embodiments herein, e.g., FIGS. 6, 10B and 23 wherein the lumens can be shapes other than those shown. As noted above, preferably the drainage lumen is the largest lumen but in alternate embodiments one or more of the other lumens could be larger than the drainage lumen.

[0102] A sensor 30 is positioned within lumen 14 adjacent balloon 16. The wire(s) 32 are shown extending through lumen 14, the sensor 30 and wire(s) 32 being of sufficiently

small size so as not to interfere with air flow through lumen 14. The sensor 30 measures pressure of the bladder. The sensor 30 is part of a transducer for converting the variation in pressure to an electrical signal for transmission to an external monitor. The pressure sensor also includes a temperature sensor to measure core temperature of the body as seen inside the bladder. Transmission wire(s) 34 of the temperature sensor extend adjacent wire 32 through lumen 14 and terminate external of the catheter 10 for connection to an external monitor. The transducer can be wired directly to the monitor or alternatively wired to a converter external of the catheter for converting the signal received by the transducer and transmitting a signal to the monitor, e.g., a bedside monitor, to display the pressure readings. This is shown schematically in FIG. 2. The readings can be displayed in quantitative form, graphical form or other displays to provide an indicator to the clinician of the bladder pressure. The monitor, or a separate monitor, will also display the temperature readings from sensor 30. Alternatively, the sensor/transducer can be connected to the monitor via a Bluetooth wireless connection.

[0103] Wires 32 and 34 can extend through lumen 14 and exit side port 15 for connection to a converter or monitor or alternatively can be inserted through the lumen 14, piercing the wall to enter the lumen 14 distal of the side port.

[0104] An alarm system can also be provided wherein the system includes a comparator for comparing the measured pressure (and/or temperature) to a threshold (predetermined) value, and if such threshold is exceeded, an indicator, e.g., an alarm, is triggered to indicate to the hospital personnel the excessive pressure and/or temperature. An alarm system can alternatively or in addition be activated if a change in pressure measurement exceeds a specified rate over a specified period of time. This would alert the staff to an imminent risk of ACS prior to intra-abdominal pressure exceeding a certain value, e.g., 20 mm hg, since due to this link, the relationship between intra-abdominal pressure and abdominal cavity volume is believed to be linear up to an intra-abdominal pressure of 12-15 mm hg and increasing exponentially thereafter.

[0105] The alarm system can be part of the catheter (as shown in FIG. 2) or alternatively external to the catheter 10.

[0106] The lumen 14 and space 16a within balloon 16 together form a closed gas, e.g., air, chamber, i.e., the lumen 14 forming an air column. With the balloon 16 filled with air, pressure on the external wall of the balloon will force the balloon to deform inwardly, thereby compressing the air contained within the balloon space 16a and within the lumen 14. The pressure sensor 30 is located in a distal portion of the lumen 14 at the region of the balloon 16 and thus is positioned at the distal end of the air column. Therefore, the pressure is sensed at the distal region as the sensor 30 detects change in air pressure in lumen 14 due to balloon deformation. Placement of the sensor 30 at a distal location provides a pressure reading closer to the source which advantageously increases the accuracy because it reduces the risk of transmission issues by reducing the amount of interference which could occur due to water, air, clots, tissue, etc. if the transmission is down the air lumen (air column).

[0107] Additionally, the pressure measurement occurs about a more circumferential area of the balloon 16 providing a pressure reading of a region greater than a point pressure sensor reading. Also, average pressure over an area of the bladder wall can be computed. Thus, the area reading

gleans information on pressure over more of the bladder wall. Stated another way, the balloon has a relatively large surface area with multiple reference points to contribute to average pressure readings of the surface around it by the sensor.

[0108] The air column is charged by insertion of air through the side port 15 which communicates with lumen 14. The side port 15 includes a valve to provide a seal to prevent escape of air from a proximal end. The balloon 16 can be composed of impermeable material, or in alternative embodiments, a permeable or semi-permeable material with an impermeable coating. This seals the air column at the distal end to prevent escape of air through the distal end, i.e., through the wall of the balloon 16. Thus, with the lumen sealed at the proximal and distal ends, a closed air system is provided, and without the requirement for repeated water insertion, a fully closed unit is provided.

[0109] In some embodiments, when the lumen 14 is air charged, the balloon 16 is not fully inflated. This improves the accuracy of the balloon 16 transmitting pressure from external the balloon to the interior of the balloon and into the lumen, i.e., air column, by ensuring the balloon has sufficient compliancy to prevent the balloon from introducing artifact into the pressure reading which would diminish its accuracy.

[0110] In some embodiments, the pressure balloon 16 is of a size to receive at least about 3 cc (3 ml) of fluid. However, other sizes/volumes are also contemplated such as about 2 cc or about 1 cc. Additionally, these volumes represent the maximum volume of fluid for the balloon, however, as noted above, in preferred embodiments, the pressure balloon 16 is not fully inflated so it would receive less than the maximum volume. Thus, with a balloon of X volume, the fluid would receive X-Y fluid, with Y representing the amount of desired extra space to achieved desired compliancy of the balloon while still enable sufficient inflation of the balloon to achieve its pressure induced deformation function.

[0111] Note in this embodiment, the stabilizing balloon 26 is positioned proximal of the pressure balloon 16. Also, in this embodiment, the stabilizing balloon 26 is larger than the pressure balloon 16. By way of example, the stabilizing balloon 26 can have a fully expanded diameter of about 23 mm and the pressure balloon 16 can have a fully expanded diameter of about 15 mm, although other dimensions or diameters for these balloons are also contemplated. By way of example, the stabilizing balloon 26 can have a capacity of about 10 cc (10 ml) of air, although other sizes/volumes are also contemplated. Note these sizes/volumes for both balloons are provided by way of example and other sizes are also contemplated. Alternatively, the stabilizing balloon can be the same size or smaller than the pressure balloon. Various shapes of the balloons are also contemplated.

[0112] Additionally, although the balloon 26 is positioned proximal of the balloon 16, it is also contemplated that the balloon 26 be positioned distal of balloon 16. The axial spacing of the balloons 16, 26 enable the stabilizing balloon 26 to engage the bladder wall to provide a sufficient radial force thereon for securing/mounting the catheter within the bladder without interfering with the function of balloon 16.

[0113] It should be appreciated that although the stabilizing balloon is shown in the embodiment of FIG. 1, it is also contemplated as an alternative that the catheter and system of FIGS. 1 and 2 can be utilized without the stabilizing balloon 26 as shown for example in FIG. 7. Similarly, although the various embodiments (catheter) disclosed

herein utilize a stabilizing balloon, it is also contemplated that alternatively the catheter of these various embodiments not include a stabilizing balloon. In the embodiment of FIG. 7, catheter 50 has two lumens: 1) a lumen for drainage of the bladder which has a side opening at a distal end to communicate with the bladder (similar to lumen 20 of FIG. 1A); and 2) an air lumen filling pressure balloon 16 via insertion of air through side port 55. The sensor 30 is positioned within the air lumen in the same manner as sensor 30 is in lumen 14 or in the alternative positions disclosed herein. Thus, the pressure and temperature sensing described in conjunction with FIG. 1 is fully applicable to the embodiment of FIG. 7. Besides the elimination of the stabilizing balloon and its lumen and side port, catheter 50 is the same as catheter 10, [0114] Note that although only one sensor is shown in FIG. 3, it is also contemplated that multiple sensors can be provided. Also, note that the sensor 30 is positioned in lumen 14 at a mid-portion of the balloon, i.e., just proximal where the opening in lumen 14 communicates with the interior 16a of the balloon 16. It is also contemplated that the sensor can be placed at another portion within the lumen 14, e.g., a more proximal portion, with respect to the lumen opening. Also, the lumen opening need not be at the mid portion of the balloon and can be at other regions of the balloon to communicate with the interior space 16a. Note if multiple sensors are provided, they can be positioned at various locations within the lumen 14.

[0115] As shown, the sensor 30 and its transmission wires are located in the same lumen 14 also used for initial inflation gas, e.g., air, for balloon 16 and for the air charged column. This minimizes the overall transverse cross-section (e.g., diameter) of the catheter 10 by minimizing the number of lumens since additional lumens require additional wall space of the catheter. However, it is also contemplated in an alternate embodiment that the sensor is in a dedicated lumen separate from the inflation lumen 14. This can be useful if a larger sensor or additional wires are utilized which would restrict the air lumen if provided therein. This is also useful if a specific sized lumen for the sensor and wires is desired to be different than the sized lumen for the air column. Provision of a separate lumen is shown in the cross-sectional view of FIG. 6 wherein in this alternate embodiment catheter 40 has four lumens: 1) lumen 42 for drainage of the bladder which has a side opening at a distal end to communicate with the bladder (similar to lumen 20 of FIG. 1); 2) lumen 44 for filling pressure balloon 16; 3) lumen 46 for filling stabilizing balloon 26; and 4) lumen 50 in which sensor 30 and its transmission wires 32 and temperature sensor wires 34 are contained. In all other respects catheter 40 is identical to catheter 10 and its balloons, air channel, sensor, etc. would perform the same function as catheter 10. Therefore, for brevity, further details of catheter 40 are not discussed herein as the discussion of catheter 10 and its components and function are fully applicable to the catheter 40 of the embodiment of FIG. 6. As noted above, the cross-sectional shapes of the lumens can be circular, oval, etc. or other shapes.

[0116] Turning now to the use of the catheter 10, the catheter 10 is inserted into the bladder. Note catheter 50 would be used in the same manner. The balloon 26 is inflated to secure the catheter 10 in place during the procedure by insertion of a fluid (liquid or gas) through side port 28 which is in fluid communication with lumen 24. The system is charged by inflation of the balloon 16, i.e., preferably partial

inflation for the reasons discussed above, by insertion of air via a syringe through port 15 which is in fluid communication with lumen 14. As discussed above, the catheter 10 is a closed system with the balloon 16 sealed so that air inserted through lumen 14 and into balloon 16 cannot escape through balloon 16. Thus, a closed chamber is formed comprising the internal space 16a of the balloon 16 and the internal lumen 14 communicating with the internal space 16a of balloon 16. With the balloon 16 inflated, pressure monitoring can commence. When external pressure is applied to an outer surface 16b of the balloon 16, caused by outward abdominal pressure which applies pressure to the bladder wall and thus against the wall of balloon 16, the gas e.g., air, within the chamber is compressed. The sensor 30 at the distal end of lumen 14 provides continuous pressure readings, converted to an electrical signal by the transducer within the distal end of lumen 14, and then electrically communicates through wire(s) 32 extending through lumen 14, exiting through the proximal side port 15 and connected to an external monitor. Note the wire can terminate at the proximal end in a plug in connector which can be connected directly to the monitor or alternatively plugged into a converter to convert the signals from the transducer in the embodiments wherein the converter is interposed between the wires and monitor (see e.g., the system of FIG. 2) to provide the aforescribed graphic display. Although, the system is capable of continuous pressure and temperature monitoring, it can also be adapted if desired for periodic monitoring so the pressure and temperature readings can be taken at intervals or on demand by the clinician.

[0117] In the embodiments wherein an indicator is provided, if the measured pressure exceeds a threshold value, and/or a change in pressure measurement exceeds a specific rate over a specific time period, the indicator would alert the clinician, e.g., via a visual indication or an audible indication that the threshold is exceeded. The indicator in some embodiments can include an audible or visual alarm (shown schematically in FIG. 2). In the embodiments having an indicator, the indicator can be provided on a proximal end of the catheter which extends out of the patient or the indicator can be part of an external component such as the monitor or a separate alarm system. A visual, audible, or other indicator can likewise be provided in any of the other embodiments disclosed herein to indicate if the measured temperature exceeds a predetermined value, and such indicator can include an alarm and can be part of the catheter or a separate component.

[0118] In the embodiment of FIGS. 1-7, within the distal end of the air lumen 14 is a pressure transducer and pressure sensor 30 which also includes a temperature sensor. In the alternate embodiment of FIGS. 8A-10B, the temperature sensor is separate from the pressure sensor. More specifically, catheter 60 has an elongated flexible shaft 62 having a lumen (channel) 64 extending within the shaft 62 and fluidly communicating at a distal region with balloon 66 to inflate the balloon. Balloon 66 (also referred to as the pressure balloon) is utilized for monitoring pressure. A fluid side port 65 is positioned at a proximal region 67 of the catheter 60 for communication with an infusion source for infusion of gas e.g., air, through the lumen 64 and into the balloon 66. The catheter 60 is shown in FIG. 8A with balloon 66 in the deflated condition (position) and in FIG. 9 with the balloon 66 in the inflated condition (position). The shaft 62 also includes a second lumen (channel) 70 and third

lumen (channel) 74 extending therein. The second lumen 70 is preferably the largest lumen and is configured for drainage of the bladder. Second lumen 70 has a side opening 72 at a distal portion communicating with the bladder. The third lumen 74 communicates at a distal region with stabilizing balloon 76 to fluidly communicate with balloon 76 to inflate the balloon. The stabilizing balloon 76 is inflatable to stabilize the catheter 60 to limit movement of the catheter 60 to keep it in place within the bladder. A side fluid port 75 is positioned at a proximal region 67 of the catheter 60 for communication with an infusion source for infusion of fluid through the lumen 74 and into the balloon 76.

[0119] Sensor 80 is positioned in lumen 64 for sensing pressure in response to balloon deformation in the same manner as sensor 30. Sensor 82 is positioned in lumen 64 distal of sensor 80 for measuring core temperature. Temperature sensor 82 can be a thermocouple, a thermistor or other types of temperature sensors. As shown in FIG. 9, the temperature sensor is distal of the balloon 66 and its transmission wire(s) 83 extend proximally within lumen 64, exiting a proximal end (through side port 65) for communication with a monitor or alternatively a converter which communicates with the monitor. Wire(s) 81 of sensor 80 also extends through lumen 64, alongside wire 83, exiting through the side port 65 or a proximal end wall or a side wall of the lumen. It is also contemplated that alternatively one or both of sensors 80 and 82, and their associated wires 81, 83, can be positioned in a separate “fourth” lumen such as in the embodiment of FIG. 6 so that the “inflation lumen” and the “sensor lumen” are independent.

[0120] In use, catheter 60 is inserted into the bladder and stabilizing balloon 76 is inflated to secure the catheter 60 in place. The system is charged by inflation of the balloon 66, i.e., preferably partially inflated for the reasons discussed above, by insertion of gas, e.g., air, through port 65 which is in fluid communication with lumen 64 in a closed system formed by the internal space 66a of the balloon 66 and the internal lumen 64 communicating with the internal space 66a of balloon 66. With the balloon 66 inflated, pressure monitoring can commence as external pressure applied to an outer surface of the balloon 66 compresses the gas within the chamber. The sensor 80 at the distal end of lumen 64 provides continuous pressure readings, converted to an electrical signal by the transducer within the distal end of lumen, and then electrically communicates through wires 82 extending through lumen 64 to an external monitor either directly or via a converter. The sensor 82 at the distal end of lumen 64 provides continuous temperature readings via wires 83 communicating directly or indirectly with the monitor. Although, the system is capable of continuous pressure and continuous temperature monitoring, as with the other systems disclosed herein, it can also be adapted if desired for periodic monitoring so the pressure and/or temperature readings can be taken at intervals or on demand by the clinician.

[0121] In the alternative embodiment of FIG. 11, catheter 90 is identical to the catheter 60 of FIG. 8 except that the pressure transducer is positioned external of the catheter rather than in the air (or other gas) lumen. That is, instead of the pressure transducer including the sensor being positioned within the distal end of the air lumen, the pressure sensor 92 is positioned within lumen 94 at the distal end of the lumen and transmission wire(s) 93 connect the sensor 92 to the pressure transducer 96 positioned outside of the

patient at a proximal region of catheter 90. As shown, the pressure transducer 96 can be positioned in a side port of catheter 90. In alternate embodiments, it is positioned outside the catheter. The temperature sensor 95 is positioned within lumen 94 along with transmission wire 97 in the same manner as temperature 82 and wires 83 are positioned in catheter 60 described above. The temperature sensor 95 can be a separate sensor positioned distal of the pressure sensor 92 as shown or alternatively it can be part of sensor 92 as in the embodiment of FIG. 1. In all other respects, catheter 90 is identical to catheter 60 and therefore for brevity further discussion is not provided since the structure and function of the balloons, the lumens, the positioning of the sensors in the lumens, the continuous pressure monitoring, etc., as well as the aforescribed alternative arrangements of catheter 60, are fully applicable to the catheter 90.

[0122] In the alternative embodiment of FIG. 12, catheter 100 is identical to catheter 60 of FIG. 8 except that the pressure transducer and pressure sensor are positioned external of the patient at a proximal region of the catheter rather than in the air lumen. That is, instead of the pressure transducer sensor being positioned within and at the distal end of the air lumen, the transducer and pressure sensor 102 are positioned at a side port 103 of the catheter 100. In alternative embodiments, they are positioned outside the catheter. In yet other embodiments, the pressure sensor and/or pressure transducer can be positioned within the air (or other gas) lumen at a proximal end of the air lumen. The temperature sensor 107 is positioned within lumen 104 along with transmission wire(s) 108 in the same manner as temperature sensor 82 and wire 83 are positioned in catheter 60 described above. The system is charged by inflation of the balloon 106, i.e., preferably partially inflated for the reasons discussed above, by insertion of air via a syringe or other injection device through the side port 103 which is in fluid communication with lumen 104. The catheter 100 is a closed system with the balloon 106 sealed so that air inserted through lumen 104 and into balloon 106 cannot escape through balloon 106. Thus, a closed chamber is formed comprising the internal space of the balloon 106 and the internal lumen 104 communicating with the internal space of balloon 106. With the balloon 106 inflated, pressure monitoring can commence. When external pressure is applied to an outer surface of the balloon 106, caused by outward abdominal pressure which applies pressure to the bladder wall and thus against the wall of balloon 16, the gas (e.g., air) within the chamber of the balloon 106 is compressed. This compresses the air within the lumen 104 creating an air charged column along the lumen 104. The sensor 102 at the proximal end of catheter 100 measures pressure of the air column at its proximal end and can provide continuous pressure readings, converted to an electrical signal by the transducer at the proximal end or external of the catheter 100, and then electrically communicates through wire(s) to an external monitor. The balloon 106, like balloon 16, balloon 66 and the other pressure balloons described herein, is of sufficiently large size to provide a sufficient circumferential area for detection of pressure changes along several parts of the bladder wall, thereby providing an average pressure and enabling more accurate pressure readings. Balloon 109 is a stabilizing balloon like balloon 76 inflated through a separate lumen.

[0123] Note the wire(s) of the sensor 102 can terminate at the proximal end in a plug in connector which can be

connected directly to the monitor or alternatively plugged into a converter to convert the signals from the transducer in the embodiments where the converter is interposed between the wires and monitor (see e.g. the system of FIG. 2) to provide the aforescribed graphic display. Although, the system is capable of continuous pressure and temperature monitoring, it can also be adapted if desired for periodic monitoring so the pressure and/or temperature readings can be taken at intervals or on demand by the clinician. In all other respects, catheter 100 is identical to catheter 60 and therefore for brevity further discussion is not provided since the structure and function of the balloons, the continuous pressure monitoring, etc., as well as the aforescribed alternative arrangements of catheter 60, are fully applicable to the catheter 100.

[0124] FIGS. 13A and 13B illustrate an alternate embodiment wherein catheter 110 includes a pressure sensor within the balloon. More specifically, catheter 110 has an elongated flexible shaft 112 having a lumen (channel) 114 extending within the shaft 112 and communicating at its distal region with balloon 116 to fluidly communicate with balloon 116 to inflate the balloon. Balloon 116 (also referred to as the pressure balloon) is utilized for monitoring pressure. A fluid side port 115 is positioned at a proximal region 117 of the catheter 110 for communication with an infusion source for infusion of gas through the lumen 114 and into the balloon 116. The shaft 112 also includes a second lumen (channel) 120 and third lumen (channel) 122 extending therein. Second lumen 120 has a side opening 124 at a distal portion communicating with the bladder. The third lumen 122 communicates at a distal region with stabilizing balloon 126 to fluidly communicate with balloon 126 to inflate the balloon to limit movement of the catheter 110 to keep it in place within the bladder for drainage. A fluid port 113 is positioned at a proximal region 117 of the catheter 110 for communication with an infusion source for infusion of fluid through the lumen 122 and into the balloon 126.

[0125] The pressure sensor 130 is carried by catheter 110 and positioned within the balloon 116 to measure pressure in response to deformation of the balloon in response to pressure exerted on an outer wall of balloon 116. The pressure transducer can include the sensor 130 or can be a separate component positioned at a proximal end of the catheter external of the catheter 110. The temperature sensor 132 can be positioned within the balloon 116, can be part of sensor 130, or alternatively positioned within lumen 114 (as shown in FIG. 13B), with its transmission wire(s) 127 extending within the gas, e.g., air, lumen 114 along with the wires of sensor 130 in the same manner as in catheter 60 described above.

[0126] In all other respects, catheter 110 is identical to catheter 60 and therefore for brevity further discussion is not provided since the structure and function of the balloons, lumens, continuous pressure monitoring, etc. as well as the aforescribed alternative arrangements of catheter 60, are fully applicable to the catheter 110.

[0127] As discussed above, the pressure balloons disclosed herein have a large circumferential area (and large volume) to provide multiple reference points for pressure readings and to provide an average pressure to enable more accurate readings. Thus, the pressure balloon provides for gross measurement. In an alternate embodiment shown in FIG. 15, the pressure balloon for detecting pressure, designated by reference numeral 142, forms an outer balloon of

catheter 140. Contained within the outer balloon 142 is an inner balloon 143. The inner balloon 143 provides a smaller diameter balloon and a smaller circumference (and volume) than the outer balloon 14. The inner balloon 143 together with the lumen 144 forms a smaller gas, e.g., air, column than in the embodiments discussed above where the larger balloon internal space communicates directly with the air lumen. This provides finer measurements. Thus, the compliant outer balloon 142 compresses the compliant inner balloon 143 which compresses the air within air lumen 144. The closed system is thereby formed by the internal space of the inner balloon 143 and the lumen 144. In certain instances, the smaller balloon air column can provide a more accurate reading from the average pressure determined by the larger outer balloon 142.

[0128] The inner balloon 143 and outer balloon 142 can be separately/independently inflated and closed with respect to each other so there is no communication, e.g. passage of gas or liquid, between the inner and outer balloons 143, 142.

[0129] The pressure transducer and pressure sensor 150 can be positioned within the lumen 144 in the same manner as sensor 30 of FIG. 1 and can function in the same manner. Alternatively, the pressure transducer can be at a proximal end of the catheter 140 as in the embodiment of FIG. 12 or external of the catheter. A temperature sensor can be part of sensor 150 as in the embodiment of FIG. 1 or alternatively it can be a separate component which can be positioned for example distal of the pressure sensor within the gas, i.e., air, lumen as in the embodiment of FIG. 8A. The transmission wires of the pressure sensor 150 and the temperature sensor extend through lumen 144.

[0130] The catheter 140 can optionally include a stabilizing balloon 145 similar to balloon 76 of FIG. 8. The catheter 140 would have a lumen, e.g., lumen 146, to inflate the stabilizing balloon 145. Lumen 148 with side opening 149 provides for drainage of the bladder. Lumen 144 which is used to inflate the inner balloon 143 and create the gas column has an opening at a distal region to communicate with inner balloon 143. A separate lumen 147 has an opening at a distal region to communicate with the outer balloon 142 to fill the outer balloon 142.

[0131] In use, catheter 140 is inserted into the bladder and stabilizing balloon 145 is inflated to secure the catheter 140 in place. The system is charged by inflation of the inner balloon 143, i.e., preferably partially inflated for the reasons discussed above, by insertion of air through a side port which is in fluid communication with lumen 144 in a closed system formed by the internal space 143a of the inner balloon 143 and the internal lumen 144 communicating with the internal space of inner balloon 143. Outer balloon 142 is filled, i.e., preferably partially inflated for the reasons discussed above, via injection of air through a separate lumen. With the outer balloon 142 inflated, pressure monitoring can commence as external pressure applied to the larger circumferential outer surface of the outer balloon 142 compresses and deforms the outer balloon 142 which compresses the inner balloon 143. As the inner balloon 143 is compressed and deformed in response to compression/deformation of the outer balloon 142 based on changes to bladder pressure, the sensor 150 at the distal end of lumen 144 provides continuous pressure readings, converted to an electrical signal by the transducer within the distal end of lumen 144, and then electrically communicates through wires 152 extending through lumen 144 to an external monitor either directly or

via a converter. Although, the system is capable of continuous pressure and continuous temperature monitoring, as in the other embodiments disclosed herein it can also be adapted if desired for periodic monitoring so the pressure and/or temperature readings can be taken at intervals or on demand by the clinician.

[0132] Note that although separate lumens are provided for the inflation of inner balloon **143** and outer balloon **142**, in an alternate embodiment, a single lumen can be utilized to inflate both balloons **143** and **142**.

[0133] FIG. **16** illustrates an alternate embodiment of catheter **140**, designated by reference numeral **140'**. Catheter **140'** is identical to catheter **140** except a larger outer balloon **142'** is provided to cover more surface area for pressure readings. In all other respects, catheter **140'** is identical to catheter **140** and for brevity further discussion is not provided since the features and functions of catheter **140**, and its alternatives such as single or two lumens for inner and outer balloon inflation, are fully applicable to catheter **140'**. For ease of understanding, the components of catheter **140'** which are identical to catheter **140** are given the same reference numerals as catheter **140**.

[0134] Note that the larger balloon **142'** can be used with the catheters of any of the embodiments described herein. Thus, a pressure balloon of the larger size balloon **142'** can be used instead of the smaller pressure balloons illustrated in the drawings. Note the size of the balloons is provided by way of example and are not necessarily drawn to scale comparatively to the other components.

[0135] FIG. **17A** illustrates an alternate embodiment of catheter **140**, designated by reference numeral **140"**. Catheter **140"** is identical to catheter **140** except a pear shaped larger outer balloon **142"** is provided. The larger balloon **142"** covers more surface area for pressure readings. The pear shape could in certain applications decrease the risk of obstructing the ureter and provide more tactile continuity of the balloon to the bladder wall giving a better transmission of abdominal pressure to the internal sensor. In all other respects, catheter **140"** is identical to catheter **140** and for brevity further discussion is not provided since the features and functions of catheter **140**, and its alternatives such as single or two lumens for inner and outer balloon inflation, are fully applicable to catheter **140"**. For ease of understanding, the components of catheter **140"** which are identical to catheter **140** are given the same reference numerals as catheter **140**. FIG. **17B** illustrates a catheter identical to catheter **140"** with identical balloons, the only difference being that the side opening **149'** is positioned proximal of the balloon **143** rather than distal of the balloon as in FIG. **17A**. That is, opening **149'**, in communication with the catheter lumen **148'** for drainage of the bladder, is positioned between the stabilizing balloon **145** and the inner and outer pressure (and inner) pressure balloon **142"** (and **143**). Thus, it is distal of the stabilizing balloon **145** and proximal of the outer balloon **142"**.

[0136] Note that the positioning of the side opening for drainage of FIG. **17B**, which communicates with the drainage lumen of the catheter, can be utilized with any of the catheters disclosed herein. Thus, in the catheters disclosed in the various embodiments herein, instead of the drainage opening positioned distal of the pressure balloon(s), it can be proximal of the pressure balloon and distal of the stabilizing balloon so it is between the two balloons.

[0137] Note that the pear shaped balloon **142"** can be used with the catheters of any of the embodiments described herein. Thus, a pressure balloon of the pear shape of balloon **142"**, and of larger size if desirable, can be used instead of the pressure balloons illustrated in the drawings.

[0138] FIGS. **18-25B** illustrate an alternate embodiment of the catheter of the present invention. The pressure balloon for detecting pressure, designated by reference numeral **202**, forms an outer balloon of catheter **200**. Contained within the outer balloon **202** is an inner balloon **204**. The inner balloon **204** provides a smaller diameter balloon and a smaller circumference (and volume) than the outer balloon **202**. The inner balloon **204** together with the lumen **214**, which communicates with the inner balloon **204** for inflation thereof, forms a smaller gas, e.g., air, column as in the embodiments of FIGS. **15-17**. This provides finer measurements. Thus, the compliant outer balloon **202** compresses the outer wall **205** of the compliant inner balloon **204** which compresses the air (or other gas) within air lumen **214**. The closed system is thereby formed by the internal space **204a** of the inner balloon **204** and the lumen **214**. The smaller balloon air column can in certain instances provide a more accurate reading from the average pressure determined by the larger outer balloon **202**.

[0139] The pressure transducer and pressure sensor are external to catheter **200** and mounted to port **218** at the proximal end **201** of catheter **200**. More specifically, a transducer hub or housing, designated generally by reference numeral **240**, contains the pressure transducer and sensor and is mounted to the angled side port **218**. In the embodiment of FIG. **18A**, the hub **240** is mounted over the port **218** and can be locked or secured thereto such as by a friction fit, snap fit, threaded attachment, a latch, etc., maintaining an airtight seal so the air is contained within the lumen **214** and balloon **204**. The hub **240** has an elongated (rod-like) member or nose **242** extending distally therefrom (FIG. **24A**) dimensioned to be inserted through the proximal opening in port **218** and into air lumen **214**. (Note the air lumen **214** as in the other lumens extend into their respective angled side ports). The elongated member **242** also has a channel **244** extending therethrough to allow the pressure wave to travel through to the pressure sensor. Although in preferred embodiments no additional air needs to be injected into inner balloon **204** via lumen **214** after attachment of hub **240**, it is also contemplated that a port or opening can be provided in hub **240** to receive an injection device for injection of additional air. Such additional air can communicate with and flow through channel **244** of elongated member **242**, into lumen **214** and into inner balloon **204** for inflation, or alternatively, a side port or opening in angled port downstream of the elongated member **242** could be provided.

[0140] To charge the system, when the hub **240** is mounted to the side port **218**, the elongated member **242** extends into lumen **214** to advance air through the air lumen **214** into inner balloon **204** to expand inner balloon **204**. In some embodiments, 0.2 cc of air can be displaced/advanced by the member **242**, although other volumes are also contemplated. Thus, as can be appreciated, mounting of the hub **240** to the catheter **200** automatically pressurizes the air lumen/chamber and expands the inner balloon **204**. Note the inner balloon **204** can be partially or fully inflated (expanded), dependent on the amount of air advanced into the inner balloon **204**. Further note that the lumen **214** is not vented

to atmosphere when the transducer hub **240** is attached and air is advanced through the air lumen. The port **218** can include a closable seal through which the elongated member **242** is inserted but maintains the seal when the elongated member **242** remains in the lumen **214**.

[0141] Lumen **214** which is used to inflate the inner balloon **204** and create the air column has an opening at a distal region to communicate with the interior of inner balloon **204**. Lumen **212** of catheter has an opening at a distal region to communicate with the outer balloon **202** to fill the outer balloon **202**. Angled port (extension) **222** at the proximal end of catheter **200** receives an inflation device to inflate, either fully or partially, the outer balloon **202**.

[0142] Note as in the other embodiments disclosed herein, air is described as the preferred gas for creating the column and expanding the balloon, however, other gasses are also contemplated, for each of the embodiments herein.

[0143] The outer balloon **202** can be shaped such that a distal region **207a** (FIGS. 20A-20C) has an outer transverse cross-sectional dimension, e.g., diameter, greater than an outer transverse cross-sectional dimension, e.g., diameter, of the proximal region **207b**. A smooth transition (taper) can be provided between the distal region **207a** and proximal region **207b**. Note the balloon **202** can be pear shaped as shown in FIGS. 20B and 20C although other configurations are also contemplated. This pear shape in some applications is designed to conform to the shape of the bladder.

[0144] The inner and outer balloons **204**, **202** can by way of example be made of urethane, although other materials are also contemplated such as silicone or EVA.

[0145] A temperature sensor **230** (FIG. 18B), such as a thermocouple, is positioned within the catheter **200** at a distal end to measure core body temperature. The sensor **230** is shown positioned in a lumen **216** separate from the lumens **214** and **212**. One or more wires **232** extend from the sensor **230** through the lumen **216**, exiting the lumen **216** and catheter **200** at a proximal end between the angled extensions/ports of the catheter **200**, e.g., between the port **218** for the inner balloon **204** and the port **222** for the outer balloon **202**. A connector **234**, e.g., a male connector, is at the proximal terminal end of the wire **232** as shown in FIG. 25B. The transducer hub **240** includes a connector **247** with openings **249** (FIG. 25A) which receive the connector **234** of the wire **232**. When the hub **240** is mounted to port **218** of catheter **200**, the connector **234** of the wire is automatically connected to a connector carried by or within the hub **240** which is in communication with a temperature monitor. Note the connector, e.g., female connector, within or carried by the hub **240** can already be mounted to an external temperature monitor via a cable when the hub **240** is mounted to catheter **218** or alternatively the hub **240** can first be mounted to port **218** of the catheter **200** and then a cable is connected between the temperature monitor and catheter **200**. In the illustrated embodiment of FIG. 25A, the wire connector **234** can plug into the openings **249** of connector **247** positioned on the hub **240**. Note the connector **247** can also be internal of the hub **240** with an opening in the wall of the hub to enable access for the wire connector. Also note that alternatively the wire can include a female connector and the hub can have a male connector. Other types of connectors/connections are also contemplated.

[0146] As can be appreciated, connection of the transducer hub **240** to the catheter **200** (port **218**) a) automatically connects the temperature sensor **230** to a connector for

communication with a temperature monitor cable; and b) automatically advances air through the first lumen **214** to expand the inner balloon **204**.

[0147] The catheter **200** can optionally include a stabilizing balloon **206** similar to balloon **76** of FIG. 8A. The stabilizing balloon **206** can be made of silicone, although other materials are also contemplated. If provided, the catheter **200** would have a lumen, e.g., lumen **210**, to inflate the stabilizing balloon **206**. Angled side port **217** can be provided in communication with lumen **210** for injection of a liquid or gas to expand the stabilizing balloon **206**. The foregoing description of the stabilizing balloons in connection with other embodiments is fully applicable to balloon **206**. Catheter **200** also includes a lumen **211** with a distal side opening **211a** (FIG. 18B) to provide for drainage of the bladder as in the aforescribed embodiments. In the illustrated embodiment, the side opening **211a** is distal of outer balloon **202** and inner balloon **204** and distal of the stabilizing balloon **210** which as shown is proximal of outer balloon **202** and inner balloon **204**. In alternate embodiments, the stabilizing balloon **206** can be distal of the outer balloon **202**.

[0148] Thus, in the embodiment of FIG. 18A, catheter **200** has five lumens: 1) lumen **214** communicating with inner balloon **204** to inflate the inner balloon **204** and forming the air filled chamber; 2) lumen **212** communicating with outer balloon **202** for inflating outer balloon **202**; 3) lumen **210** communicating with the stabilizing balloon **206** to inflate stabilizing balloon **206**; 4) drainage lumen **211** having a side opening **211a** at a distal end for drainage of the bladder; and 5) lumen **216** for the temperature sensor wire(s) **232**. Catheter **200** also has three angled extensions/ports at its proximal end **201**: 1) port **218** for access to lumen **214** to inflate the inner balloon **204**; 2) port **222** for access to lumen **212** to inflate outer balloon **202**; and 3) port **217** for access to lumen **210** to inflate stabilizing balloon **206**. Drainage lumen **211** extends linearly terminating at region **223**. Lumen **216** terminates proximally at the region of the angled ports **218**, **222** through which wire **232** can exit from the catheter **200** for connection to a temperature monitor via hub **240**. Note the location of the ports can vary from that illustrated in FIG. 18. Also, location of the lumens and the cross-sectional dimension and size of the lumen can vary from that shown in FIG. 23 as FIG. 23 provides just one example of the location and size, e.g., diameter, of the lumens as well as the shape/cross-sectional configuration and location. The catheter **200**, as in the foregoing embodiments, can have an atraumatic tip **209**.

[0149] In use, catheter **200** is inserted into the bladder and stabilizing balloon **206** is inflated to secure the catheter **200** in place. The system is charged by inflation of the inner balloon **204**, i.e., preferably partially inflated for the reasons discussed above, by advancement of air through lumen **214** upon attachment of the pressure transducer **240** to the port **218** of catheter **200**. Such attachment moves elongated member **242** into lumen **214** to displace the air (or other gas) already in the lumen **214** to expand the inner balloon **204**. A closed system is formed by the internal space **204a** of the inner balloon **204** and the internal lumen **214** communicating with the internal space **204a** of inner balloon **204**. In a preferred embodiment, additional air does not need to be added to the balloon **204**/lumen **214**. Outer balloon **202** is filled, i.e., preferably partially inflated for the reasons discussed above, via injection of air through the separate port

**222** which communicates with lumen **212** of catheter **200**. With the outer balloon **202** inflated, pressure monitoring can commence as external pressure applied to the larger circumferential outer surface of the outer balloon **202** compresses and deforms the outer balloon **202** which exerts a force on the outer wall of inner balloon **204** and compresses the inner balloon **204**. As the inner balloon **204** is compressed and deformed in response to compression/deformation of the outer balloon **202** based on changes to bladder pressure, the pressure sensor within the external hub **240** attached at the proximal end of the catheter **200** provides continuous pressure readings, converted to an electrical signal by the transducer within the hub **240**, and then electrically communicates through a connector, e.g. cable **245**, to an external monitor either directly or via a converter to display pressure readings. Although, the system is capable of continuous pressure and continuous temperature monitoring, it can also be adapted if desired for periodic monitoring so the pressure and/or temperature readings can be taken at intervals or on demand by the clinician. Temperature readings are also taken during the procedure as temperature sensor **230** is connected to a temperature monitor via wire **232** connected to a connector of hub **240** which is connected to the temperature monitor to display temperatures. The temperature monitor can be separate from the pressure display monitor or alternatively integrated into one monitor. Cable **245** can connect to the temperature monitor as well (directly or via a converter) or a separate cable extending from the hub **240** could be provided for connection to the temperature monitor.

[**0150**] Note that although separate lumens are provided for the inflation of inner balloon **202** and outer balloon **204**, in an alternate embodiment, a single lumen can be utilized to inflate both balloons **202** and **204**. In such embodiment, catheter **200** can have one less angled port and one less lumen since inflation of the outer balloon **202** would be through port **218** and lumen **214**.

[**0151**] The proximal and distal end of the inner balloon **204** in the illustrated embodiment are within the confines of the outer balloon **202**, i.e., the proximal end of the inner balloon **204** is distal of the proximal end of the outer balloon **202** and the distal end of the inner balloon **204** is proximal of the distal end of the outer balloon **202**. Thus, in this illustrated embodiment, the inner balloon **204** is fully encapsulated within the outer balloon **202**.

[**0152**] With this inner/outer balloon arrangement, the larger outer surface of the outer balloon **202** takes gross measurements and then the forces are concentrated on the smaller inner balloon **204** to amplify/concentrate pressure on the small area of the inner balloon so small changes can be detected and waves transmitted to the pressure transducer (via the length of the lumen to a proximal transducer, e.g. an external pressure transducer).

[**0153**] As noted above, preferably no additional air needs to be added after mounting of hub **240**. However, it is also contemplated that in alternate embodiments a port can be provided in communication with hub **240** to enable subsequent injection of air through lumen **214** and into inner balloon **204**. Additionally, outer balloon **202** can in some embodiments receive additional fluid injection via port **222** during the procedure.

[**0154**] FIG. **26** illustrates an alternate embodiment of the pressure transducer hub. In this embodiment, hub **250** has a shroud **254** (shown schematically) positioned over elon-

gated member **252**. This helps protect/shield the elongated member **252**. When the transducer **240** is mounted to the port **260** of the catheter, the shroud **254** fits over cover **260** of port **218** and is retained by a snap fit or by other methods of securement.

[**0155**] In the aforescribed embodiments, mounting of the transducer hub a) automatically connects the temperature sensor to a connector for communication with a temperature monitor cable; and b) automatically advances air through the first lumen to expand the inner balloon. In the embodiment of FIG. **27**, the pressure transducer hub **270** has a second elongated member **274** extending therefrom. When transducer hub **270** is mounted to the catheter, e.g., port **218**, elongated member **272** enters the air lumen in the same manner as elongated member **242** of FIG. **24A**. Additionally, elongated member **274** automatically enters the lumen **210** at port **222** which communicates with the outer balloon **202**. Therefore, in this embodiment, mounting of the transducer hub **270** a) automatically connects the temperature sensor to a connector for communication with temperature monitor cable as in the embodiment of FIGS. **18-25B**; b) automatically advances air through the first lumen to expand the inner balloon as in the embodiment of FIGS. **18-25B**; and c) automatically advances air through lumen **210** communicating with the outer balloon **202** to inflate (expand) the outer balloon **202**. The catheter of FIG. **27** (and FIG. **26**) is otherwise identical to catheter **200** of FIG. **18A** so for brevity further discussion is not provided since the description of the function and elements of catheter **200** are fully applicable to the catheter of FIG. **27** (and to the catheter of FIG. **26**).

[**0156**] FIGS. **28A-28D** show an alternate embodiment of the hub/connector. The pressure transducer is external to catheter **280** and mounted to port **282** at the proximal end **281** of catheter **280** via connector (housing) **290**. Catheter **280** is identical to catheter **200** of FIG. **18A** except for the connector and transducer hub temperature sensor connection. More specifically, transducer hub or housing, designated generally by reference numeral **300**, contains the pressure transducer and sensor **309** and is mounted to the angled side port **282**. In the embodiment of FIG. **28A**, the hub **300** is mounted to the catheter **280** by connection to housing **290**. Housing **290** is connected to port **282** via a barbed fitting **295** providing an interference fit with the port **282**. The hub **300** is locked or secured to connector **290** such as by a snap fit provided by the latch arms discussed below, although other attachments are also contemplated such as a friction fit, threaded attachment, other form of latch, etc., as well as other types of snap fits to provide an attachment that maintains an airtight seal so the air is contained within the air lumen and balloon **202** of the catheter **280**. (As noted above catheter **280** is identical to catheter **200** except for its connector so catheter **280** includes (not shown) the inner and outer pressure balloons, stabilizing balloon, temperature sensor, etc. The catheter **280** can also have a single pressure balloon as in the aforementioned embodiments.

[**0157**] The housing **290** attached to catheter **280** has a proximal opening **294** and a channel (lumen) **296** to receive an elongated (rod-like) member or nose **302** extending distally from transducer hub **300**. As shown channel **296** has a first diameter region **296a** to match with the lumen **283** of the port **282**, a second larger diameter region **296b** proximal of region **296a** to receive the male rod **302** of the hub **300**, and a still larger diameter region **296c** proximal of region

296b to receive the valve 299 and valve 298 and allow expansion thereof. As shown, valve 298 is dome shaped and is distal of valve 299. Conical cap 293, proximal of valve 299, provides a lead in to the valve 299 for the rod 302. Thermistor pins 292 receive thermistor connectors 308. Note valves 288, 299 are one example of valves that can be provided as other valves to provide an airtight seal are also contemplated. A single valve is also contemplated.

[0158] Hub 300 is mounted to connector 290 and includes a housing 304 from which a pair of distally extending snap fit connector arms 306 extend. The latch arms 306 are sufficiently flexible to enable attachment and have an enlarged distal portion 307, illustratively shown as arrow shaped although other enlarged shapes could be provided. The elongated member 302 extends between the latch arms 306. When the hub 300 is mounted to the connector 290, the elongated member 302 extends into the channel 296 to advance air to inflate the inner balloon. The enlarged ends 307 of latch arms 306 enter recesses 291 and engage shoulders 291a to retain the hub 300. Note to release (disconnect) the hub 300, the ends 307 are pressed radially inwardly to disengage from shoulder 291a and the hub 300 is pulled proximally. Note that alternatively a different number of latch arms could be provided.

[0159] The housing (connector) 290 has a lumen 296 for communication with the lumen 283 in the side port 282 of catheter 280 which communicates with the air lumen and inner balloon of the catheter 280. As noted above, the lumen 296 is dimensioned to receive the elongated rod 302 of transducer hub 300. The wire for the sensor extends in housing 300.

[0160] When transducer hub 300 is attached to connector 290, such attachment inserts the elongated rod 302 into lumen 296 to advance air through the air lumen in the catheter and into the balloon 204. (Note the air lumen extends into its angled side port 282). The elongated member 302 also has a channel or lumen 305 extending there-through to allow the pressure wave to travel through to the pressure sensor. Although in preferred embodiments no additional air needs to be injected into balloon 204 after attachment of hub 300, it is also contemplated that a port or opening can be provided in hub 300 to receive an injection device for injection of additional air. Such additional air can communicate with and flow through channel 305 of elongated member 302, into the air lumen and balloon 204 for inflation, or alternatively, a side port or opening in the angled port downstream (distal) of the elongated member 302 could be provided. Attachment of hub 300 to housing 290 also automatically connects thermistor connectors 308 to thermistor pins 292 to automatically connect the temperature sensor to the hub 300 for communication via a cable to a temperature monitor.

[0161] To charge the system, when the hub 300 is mounted to the side port 282 via attachment to connector 290, the elongated member 302 extends into lumen 296 to advance air through the air lumen into balloon 204 (or the pressure balloon in the embodiments with a single pressure balloon) to expand the balloon 204. That is, connection of the transducer hub 300 to the catheter 280 (port 282) automatically advances air through the connector lumen 296, the port lumen 283 and the first lumen 214 to expand the balloon 204. (Such connection also automatically connects the temperature sensor to the hub 300). In some embodiments, 0.2 cc of air can be displaced/advanced by the member 102,

although other volumes are also contemplated. Thus, as can be appreciated, mounting of the hub 300 to the catheter 280 automatically pressurizes the air lumen/chamber and expands the balloon. Note the balloon can be partially or fully inflated (expanded), dependent on the amount of air advanced into the balloon. Further note that preferably the lumen is not vented to atmosphere when the transducer hub 300 is attached and air is advanced through the air lumen. The port 282 includes a closable seal, e.g., valves 298 and 299, through which the elongated member 302 is inserted but maintains the seal when the elongated member 302 remains in the lumen 296. Note that catheter 280 is identical in all other respects to catheter 200 so that the description of catheter 200 and its components and function (and alternatives) are fully applicable to catheter 280, the difference being the connector 290 of catheter 292 to receive transducer hub 300. The transducer hub is also different, e.g., has latch arms and a different configuration.

[0162] In the alternative embodiment of FIGS. 29A-29C, the latch arms are reversed so that they are located on the connector rather than on the transducer hub. More specifically, transducer hub (housing), designated by reference numeral 320, has an elongated member 322 with a channel 323 and is identical to elongated member 302 of FIG. 28A for advancing air through the lumen and into the pressure balloon. Pressure transducer 324 is contained within the housing 320. Recesses 325 are dimensioned to receive the latch arms 317 of the connector or housing 310 which is connected to the side port 282 of catheter 280. (Catheter 280 is the same as catheter 280 of FIG. 28A except for connector 310). Extending proximally from housing 310 are two latch arms 16 with enlarged region 317 which engage the shoulders 326 formed by recesses 325 in hub 320 in a similar manner as latch arms 306 of FIG. 28A engage in recesses 291 and shoulder 291a. Connectors 328 in hub 320 engage thermistor pins 312 of connector 310 for connection of the temperature sensor. Connection of the hub 320, like hub 300, automatically advances air to inflate the pressure balloon and automatically connects the temperature sensor.

[0163] To disconnect (release) the hub 320, ends 317 of latch arms 316 are pressed radially inwardly to disengage from shoulder 326 so hub 320 can be pulled proximally out of connector 310.

[0164] Note the lumen which is used to inflate the pressure balloon 20 and create the air column has an opening at a distal region to communicate with the interior of the pressure balloon. If an outer balloon is provided, an additional lumen can be provided in the catheter to communicate with the outer balloon to fill the outer balloon and an additional angled port (extension) at the proximal end of the catheter would receive an inflation device to inflate, either fully or partially, the outer balloon.

[0165] Note in each of the embodiments disclosed herein, air is described as the preferred gas for creating the column and expanding the balloon, however, other gasses are also contemplated for each of the embodiments.

[0166] The pressure balloons of the embodiments herein can be symmetrically shaped as shown or alternatively shaped such that a distal region has an outer transverse cross-sectional dimension, e.g., diameter, greater than an outer transverse cross-sectional dimension, e.g., diameter, of the proximal region. A smooth transition (taper) can be provided between the distal region and proximal region, although other configurations are also contemplated. The

inner (and outer) balloon can by way of example be made of urethane, although other materials are also contemplated.

[0167] The wire connector of the foregoing embodiments can plug into the openings of a connector positioned on or in the hub. The wire connector can be internal of the hub with an opening in the wall of the hub to enable access for the wire connector. Also note that alternatively the wire can include a female connector and the hub can have a male connector. Other types of connectors/connections are also contemplated.

[0168] In alternate embodiments, any of the catheters disclosed here can include a pulse oximetry sensor to measure oxygen saturation in the urethral or bladder tissue. The sensor can be located either proximal or distal to the pressure balloon and/or stabilizing balloon. It could also alternatively be mounted within one of the balloons.

[0169] It is also contemplated that in some embodiments a backup system be provided to determine pressure. The backup system can provide a double check of pressure readings to enhance accuracy. Such backup system can be used with any of the embodiments disclosed herein to provide a second pressure reading system. One example of such backup system is disclosed in FIGS. 14A and 14B. In this embodiment, catheter 160 has the pressure transducer/pressure sensor 162 like sensor 30 of FIG. 1 within the air (or other gas) lumen 164 communicating with pressure balloon 167, forming a “first system”, plus a pressure transducer/pressure sensor 169 at a proximal end of the catheter as in FIG. 12 or external of the catheter forming a “second system”. Thus, the pressure sensor 162 is at a distal end of the air charged lumen 164 and pressure sensor 169 is at proximal end of the air charged lumen 164. Both sensors 162 and 169 are electrically connected to a monitor which provides a graphic display of pressure readings. The catheter 160 also includes a temperature sensor either as part of the sensor 162 or a separate component that can be positioned for example in the lumen 164 distal of sensor 162 as in the embodiment of FIG. 8. A stabilizing balloon 168 and an inflation lumen to inflate balloon 168 can also be provided. Lumen 163, having a side opening 170 at its distal end, is configured to drain the bladder similar to lumen 20 and side opening 22 of the embodiment of FIG. 1.

[0170] In use, catheter 160 is inserted into the bladder and stabilizing balloon 168 is inflated to secure the catheter 160 in place. The system is charged by inflation of the balloon 167, i.e., preferably partially inflated for the reasons discussed above, by insertion of air through side port 172 which is in fluid communication with the air lumen in a closed system formed by the internal space of the balloon 167 and the internal lumen 164 communicating with the internal space of balloon 167. With the balloon 167 inflated, pressure monitoring can commence as external pressure applied to an outer surface of the balloon 167 compresses the air (or other gas) within the chamber. The sensor 162 at the distal end of lumen 64 provides continuous pressure readings, converted to an electrical signal by the transducer within the distal end of lumen, and then electrically communicates through its transmission wires extending through the air lumen to an external monitor either directly or via a converter. Additionally, pressure within the air charged column is measured at a proximal region by sensor 169 within side port 172 of catheter 160. The sensor 162 at the distal end of lumen 164 provides continuous pressure readings, and such pressure readings can be confirmed by the proximal sensor. Such

pressure readings can be performed continuously (along with continuous temperature monitoring) or alternatively can also be adapted if desired for periodic monitoring so the pressure and/or temperature readings can be taken at intervals or on demand by the clinician. Thus, air pressure readings at a proximal end plus microtip pressure readings at the distal end are provided. The sensors 162 and 169 can electrically communicate with an external monitor to display both pressure readings from sensors 162, 169, or alternatively, if the pressure readings are different, they can be averaged to display a single measurement. Clearly, other displays of information can be provided to display the information from the two sensors 162, 169.

[0171] The sensors disclosed herein can be microtip sensors within the air (or other gas) lumen or balloon. In alternative embodiments, fiber optic sensors within the air (or other gas) lumen or balloon can be utilized to transmit circumferential/area pressure. The pressure transducers can be housed within the catheter or alternatively external to the catheter. Additionally, core temperature sensors can be part of the pressure sensor or a separate axially spaced component.

[0172] The multi-lumen catheters disclosed herein provide an air (or other gas) charged balloon giving precise readings of intra-abdominal pressure and core temperature and the systems are charged via insertion of air through a side port. The multi-lumen catheters are easily inserted into the bladder in the same manner as standard bladder drainage catheters and enable continuous drainage of urine while continuously recording IAP without interrupting urine flow and without requiring retrograde filling of the bladder with water. Thus, these catheters provide a closed system. The catheters also have a balloon providing a large reservoir (large capacity) and large circumferential area/interface for obtaining more information from the bladder over multiple reference points (rather than a single point sensor) that provides an average pressure to provide a more accurate assessment of the surrounding environment as pressure measurement is not limited to one side of the bladder but can determine measurements on the opposing side as well.

[0173] As noted above the catheters in some embodiments can be connected to a bedside monitor through either a wire or blue-tooth wireless connection. The system can also in some embodiments include an indicator or alarm system to alert the staff at the site as well as remote staff through wired or wireless connections to external apparatus, e.g., hand held phones or remote monitors.

[0174] As noted above, an alarm or indicator can be provided in some embodiments to alert the staff. The indicator can be a visual indicator such as a light, LED, color change, etc. Alternatively, or additionally, the indicator can be an audible indicator which emits some type of sound or alarm to alert the staff. The indicator can be at the proximal region of the catheter or at other portions of the catheter, e.g., at a distal end portion, where known imaging techniques would enable the user to discern when the indicator is turned on. It is also contemplated that in addition to providing an alert to the user in some embodiments, the pressure monitoring system can be tied into a system to directly reduce abdominal pressure so that if the pressure exceeds a threshold level (value), the abdominal pressure can automatically be reduced. In such systems, an indicator can be provided on the proximal portion of the catheter, e.g., at a proximal end outside the patient's body, or separate from the catheter. The

sensor can be in communication with the indicator, either via connecting wires extending through a lumen of the catheter or a wireless connection. The sensor can be part of a system that includes a comparator so that a comparison of the measured pressure to a predetermined threshold pressure value is performed and a signal is sent to the indicator to activate (actuate) the indicator if the measured pressure exceeds the threshold pressure to alert the clinician or staff that pressure within the abdomen is too high and a signal is also sent to a device or system to automatically actuate the device or system to reduce the abdominal pressure. If the measured temperature is below the threshold, the indicator is not activated. A similar system can be used for temperature measurement and indication.

[0175] It is also contemplated that a micro-air charged sensor could be provided in the retention (stabilizing) balloon.

[0176] It is also contemplated that microtip sensors and/or fiber optic sensors can be utilized to measure pressure, and these sensors can be utilized instead of or in addition to the air pressure readings utilizing the aforescribed balloon(s) for measuring pressure.

[0177] Pulse oximeters for measuring oxygen levels (oxygen saturation) in the urethral and/or bladder tissue could also be provided. In some embodiments, the pulse oximetry sensors can be positioned on the catheter proximal to the retention balloon. Alternatively, the sensors can be positioned within the retention balloon, on the catheter distal to the pressure balloon or on other regions of the catheter. Another channel in the catheter can be provided for the sensor and its connector to external devices, e.g. readers.

[0178] The catheters disclosed herein are designed for insertion into the bladder. However, it is also contemplated that they can be adapted for insertion into the rectum, colostomy pouch, stomach, supra-pubic bladder drain, or other orifice directly connected with the abdominal cavity.

[0179] Although the apparatus and methods of the subject invention have been described with respect to preferred embodiments, those skilled in the art will readily appreciate that changes and modifications may be made thereto without departing from the spirit and scope of the present invention as defined by the appended claims.

What is claimed is:

1. A multi-lumen catheter for monitoring intra-abdominal pressure, the catheter comprising:

- a distal balloon at a distal portion of the catheter;
- a first lumen communicating with the distal balloon, the distal balloon and first lumen forming a gas filled chamber to monitor pressure within the bladder to thereby monitor pressure within an abdomen of the patient, wherein in response to pressure within the bladder the distal balloon deforms to compress the gas within the distal balloon and first lumen;
- a first proximal port communicating with the first lumen;
- a second lumen communicating with the bladder to remove fluid from the bladder; and
- a hub connectable to the first port of the catheter, the hub including a pressure transducer for measuring pressure based on gas compression with the first lumen, and an elongated member extending distally from the hub, wherein connection of the hub to the first port inserts the elongated member into the first lumen to advance gas through the first lumen to expand the distal balloon,

the first lumen not vented to atmosphere when the hub is connected to the first port.

2. The catheter of claim 1, wherein the first port has a valve and the elongated member is insertable through the valve when the hub is connected to the first part of the catheter.

3. The catheter of claim 1, further comprising a stabilizing balloon proximal of the distal balloon for stabilizing the catheter.

4. The catheter of claim 1, wherein the second lumen has a side opening distal of the distal balloon communicating with the bladder.

5. The catheter of claim 3, wherein the second lumen has a side opening positioned between the distal balloon and stabilizing balloon communicating with the bladder.

6. The catheter of claim 1, wherein the pressure transducer measures average pressure continuously throughout insertion of the catheter without requiring infusion of water into the bladder.

7. The catheter of claim 1, wherein the catheter has a temperature sensor to measure core body temperature and a pressure transducer is contained within the hub and a wire extends from the temperature sensor through another lumen and external of the catheter into the hub connected to the catheter.

8. The catheter of claim 1, wherein the catheter includes a temperature sensor at a distal portion and connection of the hub to the catheter automatically electrically connects the temperature sensor to a temperature monitor cable.

9. The catheter of claim 1, further comprising an outer balloon positioned over the distal balloon, the outer balloon having a circumferential area greater than a circumferential area of the distal balloon and filled with a fluid, wherein in response to pressure within the bladder exerted on an outer wall of the outer balloon, the outer balloon deforms and exerts a pressure on an outer wall of the distal balloon to deform the distal balloon and compress the gas within the distal balloon and the first lumen, and a pressure sensor carried by the hub for measuring bladder pressure based on gas compression caused by deformation of the distal balloon.

10. The catheter of claim 1, further comprising a third lumen communicating with the outer balloon to inflate the outer balloon.

11. A multi-lumen catheter for monitoring intra-abdominal pressure, the catheter comprising:

- a distal balloon at a distal portion of the catheter;
- a first lumen communicating with the distal balloon, the distal balloon and first lumen forming a gas filled chamber to monitor pressure within the bladder to thereby monitor pressure within an abdomen of the patient, wherein in response to pressure within the bladder the distal balloon deforms to compress the gas within the distal balloon;
- a first proximal port communicating with the first lumen;
- a second lumen communicating with the bladder to remove fluid from the bladder, a third lumen, a temperature sensor positioned in the third lumen and having a wire extending through the third lumen; and
- a hub connectable to the first port of the catheter, the hub including a pressure transducer for measuring pressure based on gas compression within the first lumen, wherein connection of the hub to the first port auto-

matically connects the wire to an electrical connector in the hub for connection to a temperature monitor.

**12.** The catheter of claim **11**, wherein connection of the hub to the first port automatically advances gas into the distal balloon to expand the distal balloon, the first lumen remaining sealed to outside air during expansion of the distal balloon.

**13.** The catheter of claim **12**, wherein the hub includes an elongated member extending distally therefrom and insertable into the first lumen to advance gas into the distal balloon upon connection of the hub to the first port.

**14.** The catheter of claim **13**, wherein the first port has a valve and the elongated member is insertable through the valve when the hub is connected to the catheter.

**15.** The catheter of claim **1**, further comprising an outer balloon positioned over the distal balloon, the outer balloon having a circumferential area greater than a circumferential area of the distal balloon and filled with a fluid, wherein in response to pressure within the bladder exerted on an outer wall of the outer balloon, the outer balloon deforms and exerts a pressure on an outer wall of the distal balloon to deform the distal balloon and compress the gas within the distal balloon and the first lumen.

**16.** The catheter of claim **11**, further comprising a stabilizing balloon positioned proximal of the distal balloon for stabilizing the catheter.

**17.** A method for measuring pressure comprising the steps of:

providing a catheter having first and second lumens, an expandable first balloon and a temperature sensor;  
inserting the catheter through the urethra into a bladder of a patient;

connecting a hub containing a pressure transducer to the first lumen to automatically advance gas through the first lumen of the catheter to expand the first balloon from a deflated condition to a more expanded condition and to automatically connect the temperature sensor to a connector within the hub;

obtaining a first pressure reading of the bladder based on deformation of the first balloon without injecting fluid into the bladder;

transmitting the first pressure reading to an external monitor connected to the hub;

obtaining a second pressure reading of the bladder based on deformation of the first balloon without injecting fluid into the bladder;

transmitting the second pressure reading to the external monitor connected to the hub; and

obtaining consecutive continuous pressure readings of the bladder without injecting fluid into the bladder.

**18.** The method of claim **17**, further comprising the step of draining the bladder through the second lumen of the catheter.

**19.** The method of claim **17**, wherein the catheter includes an outer balloon positioned over the first balloon, the outer balloon expandable through a separate lumen of the catheter and deformable based on bladder pressure to deform the first balloon to provide finer measurements of bladder pressure.

**20.** The method of claim **17**, wherein the step of connecting a pressure transducer advances an elongated member extending from the hub into the first lumen to advance air into the first balloon.

\* \* \* \* \*

专利名称(译)	带可连接集线器的导管，用于监测压力		
公开(公告)号	<a href="#">US20180344249A1</a>	公开(公告)日	2018-12-06
申请号	US15/949016	申请日	2018-04-09
[标]发明人	MCKINNEY TIMOTHY LEVINE MARC ALAN		
发明人	MCKINNEY, TIMOTHY LEVINE, MARC-ALAN		
IPC分类号	A61B5/00 A61B5/03 A61M25/10 A61M25/00 A61B5/01		
CPC分类号	A61B5/6853 A61B5/03 A61M25/1018 A61M25/0026 A61M25/0097 A61B5/01 A61M2025/0002 A61B2018/00517 A61M2205/3368 A61B2562/0247 A61B5/036 A61B5/205		
优先权	62/514793 2017-06-03 US 62/622871 2018-01-27 US 62/544680 2017-08-11 US 62/590513 2017-11-24 US		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

#### 摘要(译)

一种多腔导管，具有用于监测腹内压力的可连接鞘，包括可膨胀外球囊和与球囊连通的第一腔。球囊和第一内腔充满气体以形成充气室，以监测膀胱内的压力，从而监测患者腹部内的压力。第二腔与膀胱连通以从膀胱移除流体。鞘包括用于基于气体压缩测量囊压的压力传感器，并且具有可插入第一腔中的细长构件，以使气体前进通过第一腔以使球囊膨胀。

