



US010548788B2

(12) **United States Patent**
Lachenbruch et al.

(10) **Patent No.:** **US 10,548,788 B2**
(45) **Date of Patent:** **Feb. 4, 2020**

(54) **PERSON SUPPORT SYSTEMS WITH COOLING FEATURES**

(58) **Field of Classification Search**

CPC A61G 7/05

(Continued)

(71) Applicant: **Hill-Rom Services, Inc.**, Batesville, IN (US)

(56) **References Cited**

(72) Inventors: **Charles A. Lachenbruch**, Batesville, IN (US); **Varad Narayan Srivastava**, Loveland, OH (US); **David Lance Ribble**, Indianapolis, IN (US); **Rachel L. Williamson**, Batesville, IN (US); **David Lawrence Bedel**, Oldenburg, IN (US); **Andrew David Clark**, Waltham, MA (US); **Steven D. Baker**, Beaverton, OR (US); **John V. Harmeyer**, Cleves, OH (US); **Ben Hertz**, Acton, MA (US); **Todd P. O'Neal**, Fairfield, OH (US)

U.S. PATENT DOCUMENTS

4,057,861 A 11/1977 Howorth
5,837,002 A 11/1998 Augustine et al.

(Continued)

FOREIGN PATENT DOCUMENTS

TW 201407164 A 2/2014
WO 2012051628 A1 4/2012

(Continued)

OTHER PUBLICATIONS

Doty et al., "The Wearable Multimodal Monitoring System: A platform to study falls and near-falls in the real-world", Springer International Publishing, Switzerland, pp. 412-422, DOI: 10.1007/978-3-319-20913-5_38, 2015.

(Continued)

(73) Assignee: **HILL-ROM SERVICES, INC.**, Batesville, IN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 590 days.

(21) Appl. No.: **15/348,080**

(22) Filed: **Nov. 10, 2016**

Primary Examiner — Fredrick C Conley

(74) *Attorney, Agent, or Firm* — Dinsmore & Shohl LLP

(65) **Prior Publication Data**

US 2017/0135884 A1 May 18, 2017

Related U.S. Application Data

(60) Provisional application No. 62/255,147, filed on Nov. 13, 2015.

(51) **Int. Cl.**
A61G 7/05 (2006.01)
A61G 7/057 (2006.01)


(Continued)

(52) **U.S. Cl.**
CPC **A61G 7/057** (2013.01); **A61B 5/01** (2013.01); **A61B 5/6892** (2013.01);
(Continued)

(57) **ABSTRACT**

Embodiments provide a person support system including support pads having cooling features. According to one embodiment, a person support system may include a longitudinal frame comprising at least one side rail. A support pad may be positioned on the longitudinal frame. The support pad may comprise a thermally conductive core portion comprising a support matrix and at least one thermally conductive element. A cooling source may be thermally coupled to the thermally conductive core portion through the side rail with a connector comprising thermally conductive fibers. The cooling source may draw heat from the thermally conductive core portion through the at least one thermally conductive element and the thermally conductive fibers of

(Continued)



the connector thereby cooling at least the thermally conductive core portion of the support pad.

47 Claims, 28 Drawing Sheets

(51) Int. Cl.

A61B 5/00 (2006.01)
A61B 5/01 (2006.01)
A61G 13/12 (2006.01)
A61F 7/00 (2006.01)
A61G 13/00 (2006.01)
A61G 13/04 (2006.01)
A61G 13/06 (2006.01)
A61G 13/10 (2006.01)

(52) U.S. Cl.

CPC *A61F 7/0053* (2013.01); *A61F 7/0097* (2013.01); *A61G 13/0054* (2016.11); *A61G 13/04* (2013.01); *A61G 13/06* (2013.01); *A61G 13/104* (2013.01); *A61G 13/12* (2013.01); *A61G 13/126* (2013.01); *A61G 13/127* (2013.01); *A61B 5/4836* (2013.01); *A61F 2007/0056* (2013.01); *A61F 2007/0075* (2013.01); *A61F 2007/0086* (2013.01); *A61F 2007/0096* (2013.01); *A61G 2203/10* (2013.01); *A61G 2203/46* (2013.01); *A61G 2205/60* (2013.01); *A61G 2210/50* (2013.01); *A61G 2210/70* (2013.01)

(58) Field of Classification Search

USPC 5/724, 726, 652.1
 See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

6,210,427	B1	4/2001	Augustine et al.
6,840,955	B2	1/2005	Ein
7,273,490	B2	9/2007	Lachenbruch
7,727,267	B2	6/2010	Lachenbruch
7,784,126	B2	8/2010	Meissner et al.
7,857,507	B2	12/2010	Quinn et al.
7,942,825	B2	5/2011	Ranganathan et al.
8,087,254	B2	1/2012	Arnold
8,328,420	B2	12/2012	Abreu
8,475,368	B2	7/2013	Tran et al.
8,606,344	B2	12/2013	Dimaio et al.
8,620,625	B2	12/2013	Sing et al.
8,663,106	B2	3/2014	Stivorac et al.
8,716,629	B2	5/2014	Klewer et al.
8,800,078	B2	8/2014	Lachenbruch et al.
8,907,287	B2	12/2014	Vanderpohl
8,939,912	B2	1/2015	Turnquist et al.
9,089,462	B1	7/2015	Lafleche

9,132,031	B2	9/2015	Levinson et al.
9,596,944	B2	3/2017	Makansi et al.
2005/0149153	A1	7/2005	Nakase
2005/0168941	A1	8/2005	Sokol et al.
2006/0202816	A1	9/2006	Crump et al.
2007/0135878	A1 *	6/2007	Lachenbruch A61G 7/057 607/108
2008/0018480	A1	1/2008	Sham
2008/0077201	A1	3/2008	Levinson et al.
2009/0069642	A1	3/2009	Gao et al.
2010/0274331	A1 *	10/2010	Williamson A61G 7/05738 607/104
2010/0298658	A1	11/2010	Mccombie et al.
2011/0107514	A1 *	5/2011	Brykalski A47C 21/044 5/421
2013/0066237	A1	3/2013	Smotrich et al.
2013/0090571	A1	4/2013	Nourani et al.
2014/0237719	A1	8/2014	Brykalski et al.
2014/0260331	A1	9/2014	Lofy et al.
2014/0323816	A1	10/2014	Soderberg et al.
2015/0051673	A1	2/2015	Rivas Tapia
2015/0230974	A1	8/2015	Pistor et al.
2015/0290065	A1	10/2015	Augustine et al.
2015/0323388	A1	11/2015	Kostic et al.
2016/0338500	A1	11/2016	Malzl

FOREIGN PATENT DOCUMENTS

WO	2014047310	A1	3/2014
WO	2015074007	A1	5/2015
WO	20150148225	A2	10/2015
WO	20150164456	A2	10/2015

OTHER PUBLICATIONS

Jiang, "A Smart and Minimum-Intrusive Monitoring Framework Design for Health Assessment of the Elderly", Doctoral dissertation, University of Cincinnati, pp. 1-124, 2015.

Hill-Rom, "VersaCare® Med Surg Bed" <online: <http://www.hill-rom.com/usa/products/category/hospital-beds/versacare-med-surg-beds/>>.

Laird, "Penn Medicine tests continuous, wearable patient monitoring", <online: <http://www.summitdata.com/blog/penn-medicine-tests-wearable-patient-monitor-hospital/>>, 2015.

Appelboom G et al., "The Promise of Wearable Activity Sensors to Define Patient Recovery", Journal of Clinical Neuroscience, DOI: 10.1016/j.jocn.2013.12.003, 2014.


CSZ, Gelli-Roll®, "Reusable Warming and Cooling Gel Pad", <online: <http://www.cszmedical.com/gelli-roll/>>.

Bard Medical, "Arctic Sun® 5000 Temperature Management System", <online: <http://www.bardmedical.com/Prescriptive/?productID=5971&p=6564>>.

Lanata et al., "Complexity Index from a Personalized Wearable Monitoring System for Assessing Remission in Mental Health", Journal of Latex Class Files, vol. 11, No. 4, 2012.

Extended European Search Report dated Apr. 13, 2017 relating to EP Patent Application No. 16198283.0.

* cited by examiner









FIG. 2



மெட்டல்







FIG. 4C






FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 5F





FIG. 5G






FIG. 7B




FIG. 7A




FIG. 7C





FIG. 8








FIG. 10








FIG. 13




FIG. 14








FIG. 15







1
1
G
1
1






FIG. 19




FIG. 20




FIG. 21




FIG. 22

1

PERSON SUPPORT SYSTEMS WITH COOLING FEATURES

CROSS REFERENCE TO RELATED APPLICATIONS

The present application claims priority to U.S. Provisional Patent Application No. 62/255,147 filed Nov. 13, 2015 and entitled "Support Surfaces With Cooling Features," the entirety of which is incorporated by reference herein.

TECHNICAL FIELD

The present specification generally relates to person support systems, and more specifically, to person support systems having cooling features.

BACKGROUND

Conventionally, a subject may be positioned on a support surface during a medical procedure. The support surface is generally the upper surface of a surgical table, such as a spine table or standard operating room (OR) table, and may include a number of pads to provide support to the subject. The pads provide cushioning to the subject and may facilitate positioning the subject so as to provide access to a portion of the subject's anatomy that is to be operated on. For example, in the case of a spine table, the pads of the support surface may be used to position the subject on the spine table such that the subject's spine is curved or arched, thereby separating the vertebrae.

During a surgical operation the subject may be maintained in one position on the support surface for an extended period of time. As such, certain areas of the subject's anatomy in contact with the surface may be subject to relatively high, localized pressure. For example, when a subject is in a supine position on the surface, portions of the subject's posterior skin, such as the subject's sacral area, buttocks, scapular areas, and/or heels, may be subject to relatively high, localized pressure due to the subject's own body weight. These areas of localized pressure may be different depending on the orientation of the subject on the surface. For example, when the subject is in the prone position on the surface, the areas of localized pressure may be along the anterior skin of the subject. The areas of relatively high localized pressure may be prone to the development of pressure ulcers due to the localized increases in pressure. The development of pressure ulcers may be further exacerbated by heat and the presence of moisture, such as perspiration, trapped between the skin and the surface for extended periods of time.

Accordingly, a need exists for alternative support pads for support surfaces of person support systems, such as surgical tables or the like, which mitigate the development of pressure ulcers in subjects positioned on the support pads.

SUMMARY

According to one embodiment, a person support system may include a longitudinal frame comprising at least one side rail. A support pad may be positioned on the longitudinal frame. The support pad may comprise a thermally conductive core portion comprising a support matrix and at least one thermally conductive element. A cooling source may be thermally coupled to the thermally conductive core portion through the side rail with a connector comprising thermally conductive fibers. The cooling source may draw

2

heat from the thermally conductive core portion through the at least one thermally conductive element and the thermally conductive fibers of the connector thereby cooling at least the thermally conductive core portion of the support pad.

According to another embodiment, a subject cooling system may include a support pad comprising a core part and at least one recess formed in the core part. The recess may extend through a top surface of the support pad. The system may further include a foam plug having a shape and a size corresponding to the recess formed in the core part of the support pad. In addition, the system may include a set of thermally conductive core portions. Each thermally conductive core portion of the set of thermally conductive core portions may have a shape and a size corresponding to the recess formed in the core part of the support pad. Each thermally conductive core portion of the set of thermally conductive core portions may have different cooling characteristics than at least one other thermally conductive core portion in the set of thermally conductive core portions. The foam plug and each thermally conductive core portion of the set of thermally conductive core portions may be interchangeably insertable into the at least one recess formed in the core part of the support pad.

According to another embodiment, a support pad for a person support system may include a thermally conductive core portion that includes a support matrix and a plurality of thermally conductive elements formed from thermally conductive materials, such as thermally conductive particles or the like, disposed on or in the support matrix and arranged to conduct heat away from a top surface of the support matrix. The thermally conductive core portion may further include at least one thermal transport layer thermally coupled to the support matrix and configured to conduct heat from the support matrix. A cover material may envelope the thermally conductive core portion.

According to another embodiment, a support pad for a person support system may include a thermally conductive core portion comprising a support matrix. An array of thermally conductive fibers may be disposed in the support matrix and arranged to conduct heat away from a top surface of the support pad. At least a portion of the array of thermally conductive fibers extend from at least one of a side surface of the support matrix and a bottom surface of the support matrix.

According to another embodiment, a support pad for a person support system may include a thermally conductive core portion comprising a support matrix. A plurality of thermally conductive particles and/or thermally absorptive particles may be dispersed in the support matrix. The support pad may further include at least one thermal transport layer thermally coupled to the support matrix and configured to conduct heat from the support matrix.

Additional features and advantages will be set forth in the detailed description which follows, and in part will be readily apparent to those skilled in the art from that description or recognized by practicing the embodiments described herein, including the detailed description which follows, the claims, as well as the appended drawings.

It is to be understood that both the foregoing general description and the following detailed description describe various embodiments and are intended to provide an overview or framework for understanding the nature and character of the claimed subject matter. The accompanying drawings are included to provide a further understanding of the various embodiments, and are incorporated into and constitute a part of this specification. The drawings illustrate the various embodiments described herein, and together

with the description serve to explain the principles and operations of the claimed subject matter.

BRIEF DESCRIPTION OF THE DRAWINGS

Referring now to the illustrative examples in the drawings, wherein like numerals represent the same or similar elements throughout:

FIG. 1 is a perspective view of a person support system in accordance with one or more embodiments described herein;

FIG. 2 is a side view of the person support system of FIG. 1;

FIG. 3 schematically depicts a perspective view of a person support system in accordance with another embodiment described herein;

FIG. 4A schematically depicts a cross-section of a support pad for a person support system in accordance with one or more embodiments described herein;

FIG. 4B schematically depicts a cross-section of a support pad for a person support system in accordance with one or more embodiments described herein;

FIG. 4C schematically depicts a top view of a support pad depicting the location of thermally conductive core portions in accordance with one or more embodiments described herein;

FIG. 5A schematically depicts a cross-section of a thermally conductive core portion in accordance with one or more embodiments described herein;

FIG. 5B schematically depicts a cross-section of a thermally conductive core portion in accordance with one or more embodiments described herein;

FIG. 5C schematically depicts a cross-section of a thermally conductive core portion in accordance with one or more embodiments described herein;

FIG. 5D schematically depicts a cross-section of a thermally conductive core portion in accordance with one or more embodiments described herein;

FIG. 5E schematically depicts a cross-section of a thermally conductive core portion in accordance with one or more embodiments described herein;

FIG. 5F schematically depicts a cross-section of a thermally conductive core portion in accordance with one or more embodiments described herein;

FIG. 5G schematically depicts a cross-section of a thermally conductive core portion in accordance with one or more embodiments described herein;

FIG. 6 schematically depicts a cross-section of a support pad including a thermally conductive in accordance with one or more embodiments described herein;

FIG. 7A schematically depicts a cross-section of a magnetic coupler in accordance with one or more embodiments described herein;

FIG. 7B schematically depicts a cross-section of a magnetic coupler in accordance with one or more embodiments described herein;

FIG. 7C schematically depicts a cross-section of a magnetic coupler in accordance with one or more embodiments described herein;

FIG. 8 schematically depicts a cross-section of a coupler in accordance with one or more embodiments described herein;

FIG. 9 schematically depicts a cross-section of a side rail with a cooling source thermally coupled to the support pad, in accordance with one or more embodiments shown and described herein;

FIG. 10 schematically depicts a cross-section of a side rail with a cooling source thermally coupled to the support pad, in accordance with one or more embodiments shown and described herein;

FIG. 11 schematically depicts a cross-section of a side rail with a cooling source thermally coupled to the support pad, in accordance with one or more embodiments shown and described herein;

FIG. 12 schematically depicts a cross-section of a side rail with a cooling source thermally coupled to the support pad, in accordance with one or more embodiments shown and described herein;

FIG. 13 schematically depicts a cross-section of one of the support pads of the person support system of FIG. 1 along the line A-A in accordance with one or more embodiments described herein;

FIG. 14 schematically depicts a control unit of a person support system in accordance with one or more embodiments described herein;

FIG. 15 schematically depicts the interconnectivity of various components of the control unit of a person support system in accordance with one or more embodiments;

FIG. 16 schematically depicts one embodiment of a warming blanket for use with one or more embodiments of the person support systems described herein;

FIG. 17 schematically depicts an embodiment of a system for delivering warming fluid to the warming blanket of FIG. 16;

FIG. 18 schematically depicts another embodiment of a warming blanket for use with one or more embodiments of the person support systems described herein;

FIG. 19 schematically depicts an embodiment of a system for heating the warming blanket of FIG. 18;

FIG. 20 schematically depicts an alternative embodiment of a support pad with recesses for receiving foam plugs or thermally conductive core portions;

FIG. 21 schematically depicts the support pad of FIG. 20 with a thermally conductive core portion disposed in one recess and foam plugs positioned in other recesses; and

FIG. 22 schematically depicts a mobile person support system, such as a stretcher, having a support pad with a thermally conductive core portion in accordance with one or more embodiments described herein.

DETAILED DESCRIPTION

FIG. 1 generally depicts one embodiment of a person support system including support pads having cooling features. According to one embodiment, the person support system may include a longitudinal frame comprising at least one side rail. A support pad may be positioned on the longitudinal frame. The support pad may comprise a thermally conductive core portion comprising a support matrix and at least one thermally conductive element. A cooling source may be thermally coupled to the thermally conductive core portion through the side rail with a connector comprising thermally conductive fibers. The cooling source may draw heat from the thermally conductive core portion through the at least one thermally conductive element and the thermally conductive fibers of the connector thereby cooling at least the thermally conductive core portion of the support pad. Various embodiments of the support pads, person support systems with support pads, and methods of using the support pads will be described in more detail herein.

Referring to FIG. 1, one embodiment of a person support system 100 is schematically depicted. In this embodiment,

the person support system 100 may be, for example and without limitation, a two-column operating table such as the Allen® Advance Table manufactured by Allen Medical Systems, Inc. of Acton, Mass. The person support system 100 generally includes a base frame 110 and a primary support frame 120 that is supported by the base frame 110. The person support system 100 may further include a plurality of support pads 130 coupled to the primary support frame 120. In various embodiments, one or more of the support pads 130 may include cooling features, as will be described in greater detail herein.

The base frame 110 of the person support system 100 includes a head portion 114 positioned at a head end H of the person support system 100 and a foot portion 116 positioned at a foot end F of the person support system 100. The head portion 114 and the foot portion 116 are spaced apart from one another in a longitudinal direction (i.e., generally along the X axis of the coordinate axes depicted in the FIG. 1) and may be coupled to one another by a central portion 118 that extends between the head portion 114 and the foot portion 116 in the longitudinal direction. The central portion 118 may be extendable and retractable in the longitudinal direction, thereby increasing or decreasing the distance between the head portion 114 and the foot portion 116 in the longitudinal direction. In some embodiments, the head portion 114 and the foot portion 116 each have a plurality of casters 112 coupled thereto, such that the person support system 100 may be moved along a surface, such as a floor.

The primary support frame 120 extends upward in a vertical direction (i.e., generally along the Z axis of the coordinate axes depicted in FIG. 1) from the base frame 110 of the person support system 100. In the embodiment depicted in FIG. 1, the primary support frame 120 includes a head column 122 that extends upward from the head portion 114 of the base frame 110 in the vertical direction. The primary support frame 120 further includes a foot column 124 that extends upward from the foot portion 116 of the base frame 110 in the vertical direction. Accordingly, it should be understood that the head column 122 is generally positioned proximate the head end H of the person support system 100 and the foot column 124 is generally positioned proximate the foot end F of the person support system 100. The head column 122 is spaced apart from the foot column 124 in the longitudinal direction by the central portion 118. In some embodiments, the head column 122 and the foot column 124 are coupled to the head portion 114 and the foot portion 116 of the base frame 110, respectively. Alternatively, the head column 122 and the foot column 124 may be integrated with the head portion 114 and the foot portion 116 of the base frame 110, respectively. The head column 122 and the foot column 124 may be actuated to raise and lower the head column 122 and the foot column 124 in the +/-Z direction of the coordinate axes depicted in FIG. 1.

The primary support frame 120 includes a longitudinal frame 125 that is positioned above the base frame 110 in the vertical direction and that extends between the head column 122 and the foot column 124 in the longitudinal direction. The longitudinal frame 125 is coupled to the head column 122 and the foot column 124 such that the longitudinal frame 125 may be raised, lowered and/or tilted with respect to the base frame 110 upon actuation of the head column 122 and/or the foot column 124. In the embodiment depicted in FIG. 1, the longitudinal frame 125 generally extends in the horizontal plane (i.e., the X-Y plane as depicted). However, it should be understood that the longitudinal frame 125 may be tilted with respect to the X-Y plane (i.e., about an axis of

rotation generally parallel to the Y-axis in the coordinate axes depicted in FIG. 1) or rotated with respect to the X-Y plane (i.e., about an axis of rotation generally parallel to the X-axis in the coordinate axes depicted in FIG. 1). While FIG. 1 generally depicts the longitudinal frame as being substantially planar, in other embodiments, the longitudinal frame 125 may be contoured and may include portions that extend out of the horizontal plane. In some embodiments, the longitudinal frame 125 may include a first side rail 126 and a second side rail 127, where the first side rail 126 and the second side rail 127 extend substantially parallel to each other in the longitudinal direction between the head column 122 and the foot column 124. The first side rail 126 and the second side rail 127 may be coupled to the head column 122 and the foot column 124, respectively, by a head support piece 128 and a foot support piece 129. The head support piece 128 may be coupled between the head column 122 and the first and second side rails 126, 127. In embodiments, the head support piece 128 and the foot support piece 129 may be pivotable with respect to the head column 122 and the foot column 124 about an axis of rotation that is generally parallel to the X-axis in the coordinate axes depicted in FIG. 1. The foot support piece 129 may be coupled between the foot column 124 and the first and second side rails 126, 127.

As depicted in FIGS. 1 and 2, in embodiments, the longitudinal frame 125 supports and may be coupled to each of the plurality of support pads 130, each of which extends a distance in the longitudinal direction between the head column 122 and the foot column 124 and extends a distance in the lateral direction. Alternatively, the longitudinal frame 125 supports and may be coupled to a support deck (not shown), which extends a distance between the head column 122 and the foot column 124 in the longitudinal direction.

Referring again to FIG. 1, as noted above, the head column 122 and the foot column 124 may be adjustable in the vertical direction such that the head column 122 and the foot column 124 may raise or lower the longitudinal frame 125 with respect to the base frame 110 in the vertical direction. In some embodiments, at least one column actuator 121 is coupled to the head column 122 and/or the foot column 124. The at least one column actuator 121 moves the head column 122 and the foot column 124 upward and downward in the vertical direction with respect to the base frame 110. The column actuator 121 may be a powered actuator, such as an electric motor, linear actuator, or the like, or may be manually powered, such as by a system of gears actuated by a pedal, a crank, or the like, or even a hydraulic cylinder actuated by a pedal, crank, or the like. For example, the column actuator 121 may also include a linear actuator, a hydraulic actuator, a pneumatic actuator, an electro-mechanical actuator, or the like.

The head column 122 and the foot column 124 may be raised and lowered in the vertical direction independent of one another such that the longitudinal frame 125 may be tilted with respect to the horizontal plane (i.e., the X-Y plane), as described above. For example, the head column 122 may be raised with respect to the foot column 124 in the vertical direction such that the head end of the longitudinal frame 125 is positioned higher than the foot end of the longitudinal frame 125 in the vertical direction (i.e., a reverse Trendelenburg position). Conversely, the foot column 124 may be raised with respect to the head column 122 in the vertical direction, such that the foot end of the longitudinal frame 125 is positioned higher than the head end of the longitudinal frame 125 in the vertical direction (i.e., a Trendelenburg position). In some embodiments, both the head column 122 and the foot column 124 of the primary

support frame **120** may be raised or lowered in the vertical direction simultaneously and in conjunction with one another, thereby raising both the head end and the foot end of the longitudinal frame **125**.

Referring again to FIGS. **1** and **2**, each of the plurality of support pads **130** are coupled to the longitudinal frame **125** and are positioned between the head column **122** and the foot column **124**. In addition, each of the plurality of support pads **130** extends in the lateral direction (i.e., generally along the Y axis of the coordinate axes depicted in FIGS. **1** and **2**) by a width W from the first side rail **126** to the second side rail **127**. In some embodiments, each of the plurality of support pads **130** may extend beyond the side rails **123**, **127**, as depicted in FIG. **1**. In the embodiment depicted in FIG. **1**, the plurality of support pads **130** includes six support pads **130** positioned at various locations between the head column **122** and the foot column **124**. However, it should be understood that the number of support pads **130** coupled to the longitudinal frame **125** between the head column **122** and the foot column **124** is not limited by the present disclosure. In some embodiments, the person support system **100** may include a suitable number of support pads **130** sufficient to support a patient thereon.

While FIGS. **1** and **2** generally depict the person support system **100** as comprising a head column **122** and a foot column **124** supporting the longitudinal frame **125**, it should be understood that other embodiments are contemplated and possible.

For example, in an alternative embodiment, the longitudinal frame may be supported by a single support column located near the longitudinal center of the longitudinal frame. Examples of such person support systems include, without limitation, the TruSystem® 7000 series or 7500 series of operating room tables manufactured by TRUMPF Medizin Systeme GmbH+Co. KG of Saalfeld, Germany. Alternatively, the person support apparatus may be a MARSTTM OR Table or SATURN® OR Table, each of which is manufactured by TRUMPF Medizin Systeme GmbH+Co. KG of Saalfeld, Germany.

Referring to FIG. **3** by way of example, an alternative embodiment of a person support system **101** with a single support column is schematically depicted. In this embodiment, the person support system **101** includes a single support column **102**, a base **103**, and a table top assembly **104**. The base **103** may include a plurality of casters **112** such that the person support system **101** may be moved along a surface, such as a floor. The support column **102** is positioned on and supported by the base **103**. The table top assembly **104** is positioned on and supported by the support column **102**. In embodiments, the support column **102** may include an adjustment system (not shown) for raising and lowering the table top assembly **104** relative to the base **103** and/or tilting the table top assembly **104** relative to the base **103**. For example, in some embodiments the adjustment system may facilitate rotating the table top assembly **104** about an axis generally parallel with the Y axis depicted in FIG. **3** and/or rotating the table top assembly **104** about an axis generally parallel with the X axis depicted in FIG. **3**. In embodiments, the adjustment system may be a mechanical adjustment system, an electro-mechanical adjustment system, a hydraulic adjustment system or combinations thereof.

In embodiments, the table top assembly **104** generally includes a longitudinal frame **125**, a foot frame **107**, and a head frame **108**. The foot frame **107** may be pivotally and removably attached to the longitudinal frame **125**. Similarly, the head frame **108** may be pivotally and removably attached to the longitudinal frame **125** opposite the foot

frame **107**. Each of the longitudinal frame **125**, foot frame **107**, and head frame **108** may include a deck (not shown in FIG. **3**) on which a support pad **130** is removably positioned.

Similar to the embodiment of the person support system **100** depicted in FIG. **1**, the longitudinal frame **125** of the person support system **101** depicted in FIG. **3** may include a first side rail **126** and a second side rail **127** (not shown in FIG. **3**), where the first side rail **126** and the second side rail **127** extend substantially parallel to each other in the longitudinal direction (i.e., the +/-X direction of the coordinate axes depicted in the figures). In embodiments, the first side rail **126** and the second side rail **127** may be coupled to one another with cross rails and/or the deck. While the structure of the longitudinal frame **125** has been described herein, it should be understood that the foot frame **107** and the head frame **108** may have similar structures.

While reference has been made herein to specific embodiments of person support systems **100**, **101**, it should be understood that the embodiments of support pads with the cooling features of the person support systems described in further detail herein may also be used in conjunction with other person support systems including, without limitation, stretchers, gurneys, and the like.

Referring now to FIG. **1** and FIG. **3**, during a medical procedure, such as a surgical procedure or the like, a subject may be positioned on the person support system **100**, **101** such that the subject is in contact with the support pad **130**. The subject may be in a static position on the support pad for an extended period of time. As such, certain areas of the subject's anatomy in contact with the support pad(s) may be subject to relatively high, localized pressure. For example, when a subject is in a supine position on the support pad(s), portions of the subject's posterior skin, such as the subject's sacral area, buttocks, scapular areas, and heels, may be subject to relatively high, localized pressure due to the subject's own body weight. These areas of relatively high localized pressure, in conjunction with moisture trapped between the subject and the support pad and the local build-up of heat, may lead to the development of pressure ulcers in the tissue of the subject. The embodiments described herein provide person support systems and support pads for person support systems which may assist in mitigating the development of pressure ulcers.

Referring to FIG. **4A** by way of example, a cross section through the Y-Z plane of one embodiment of the longitudinal frame **125** and support pad **130** of the person support system **100** (FIG. **1**) and/or person support system **101** (FIG. **3**) is schematically depicted showing the side rails **126**, **127**, a deck **160** supported on the side rails **126**, **127**, and a support pad **130** supported on the deck **160**. In embodiments, at least a portion of the support pad **130** includes a thermally conductive core portion **200** which is constructed, at least in part, from thermally conductive material arranged to conduct heat away from an upper or top surface **131** of the support pad **130**, thereby providing at least localized, focal cooling of the top surface **131** of the support pad **130** which, in turn, may provide at least localized, focal cooling of a subject positioned on the top surface **131** of the support pad **130**. For example, the support pad **130** may include a cover material **136** which, in some embodiments, envelopes and encloses the support pad **130**. The cover material **136** may be, for example and without limitation, a woven or non-woven fabric which, in some embodiments, includes a coating, such as a urethane coating, polyurethane coating, or the like, which seals at least the top surface **131** of the support pad **130** from moisture permeation and facilitates cleaning of the support pad **130**. In embodiments where the

cover material **136** is formed from a woven or non-woven fabric material, the woven or non-woven fabric material may optionally include thermally conductive fibers, such as carbon fibers, metallic fibers or the like, to facilitate the conduction of heat into the thermally conductive core portion **200**. In some other embodiments, the cover material **136** may include a solid sheet of material which is impervious to fluids, such as a urethane material, vinyl, or the like. In embodiments where the cover material **136** is formed from a solid sheet material, the solid sheet material may optionally include thermally conductive fibers, such as carbon fibers, metallic fibers or the like, or thermally conductive particles, such as carbon particles, metallic particles or the like, embedded therein to facilitate the conduction of heat into the thermally conductive core portion **200**. In embodiments, the thermally conductive core portion **200** is positioned adjacent to the top surface **131** of the support pad **130** (i.e., adjacent to the top surface of the cover material **136**) to facilitate good thermal contact with a subject positioned on the top surface **131** of the support pad **130**.

While FIG. 4A schematically depicts a support pad **130** in which the thermally conductive core portion **200** extends through the cross section of the support pad **130** within the cover material **136**, it should be understood that other configurations of the thermally conductive core portion **200** are contemplated and possible. Referring to FIG. 4B by way of example, an alternative embodiment of a cross section through the Y-Z plane of the longitudinal frame **125** and support pad **130** is schematically depicted. As noted herein with respect to FIG. 4A, the support pad **130** includes a thermally conductive core portion **200** enclosed within a cover material **136**. In the embodiment depicted in FIG. 4A, the thermally conductive core portion **200** is disposed in only a portion of the support pad **130**. Specifically, the support pad **130** includes a core part **132** disposed within the cover material **136**. The core part **132** may be formed from, for example and without limitation, a foam such as urethane foam, polyurethane foam or the like. The core part **132** may also include a combination of different foam materials. For example, the core part **132** may include a urethane foam or a polyurethane foam with an additional layer of memory foam disposed over the urethane foam or the polyurethane foam. In these embodiments, the thermally conductive core portion **200** is disposed in a portion of the core part **132**. For example, the thermally conductive core portion **200** may be disposed in a recess **137** formed in the core part **132** and located adjacent to the top surface **131** of the support pad (i.e., adjacent to the cover material **136** forming the top surface **131** of the support pad **130**).

In embodiments, the thermally conductive core portion **200** need not extend through the entire thickness (i.e., the +/-Z direction of the coordinate axes depicted in FIG. 4B) of the core part **132**. That is, the thermally conductive core portion **200** may be positioned in the core part **132** and has a thickness that is less than the thickness of the core part **132**. In some embodiments, the thermally conductive core portion **200** may not extend across the entire width (i.e., the +/-Y direction of the coordinate axes depicted in FIG. 4B) of the core part **132**. That is, the thermally conductive core portion **200** is positioned in the core part **132** and has a width that is less than the width of the core part **132**. In some embodiments, the thermally conductive core portion **200** may not extend across the entire length (i.e., the +/-X direction of the coordinate axes depicted in FIG. 4B) of the core part **132**. That is, the thermally conductive core portion **200** is positioned in the core part **132** and has a length that is less than the length of the core part **132**. In some

embodiments, the thermally conductive core portion **200** has at least a width and a length that are less than the corresponding dimensions of the core part **132**.

Constructing the support pad **130** such that the thermally conductive core portion **200** has at least a width and a length that are less than the corresponding dimensions of the core part **132** allows for discrete, targeted cooling (i.e., focal cooling) of particular areas of a subject positioned on the support pad. For example, in some embodiments, the thermally conductive core portion **200** may be located within recesses **137** in the core part **132** beneath areas of the top surface **131** that contact a subject at locations most prone to the development of pressure ulcers, including, without limitation, the sacral area, buttocks, scapular areas, heels, and the like. Discrete, focal cooling of these areas with the thermally conductive core portion **200** may aid in mitigating the development of pressure ulcers.

For example, FIG. 4C is a top view of the support pad **130** depicted in FIG. 4B showing the relative positioning of three thermally conductive core portions **200a**, **200b**, **200c** in the core part beneath the cover material **136**. As depicted in FIG. 4C, thermally conductive core portions **200a**, **200b** are generally located beneath the areas of the top surface **131** that correspond to the scapular areas of a subject positioned on the top surface **131** of the support pad **130** while thermally conductive core portion **200c** is generally located beneath the area of the top surface **131** that corresponds to the sacral area of a subject positioned on the top surface **131** (assuming the head of the subject is positioned towards the end of the support pad **130** in the +X direction of the coordinate axes depicted and the pelvis of the subject is positioned towards the end of the support pad in the -X direction of the coordinate axes depicted). While FIG. 4C schematically depicts a support pad **130** that includes three thermally conductive core portions **200a**, **200b**, **200c**, it should be understood that the number of thermally conductive core portions within the support pad **130** may be greater than three or less than three. For example and without limitation, in embodiments, the support pad **130** may include the thermally conductive core portions **200a**, **200b** corresponding to the scapular areas or the thermally conductive core portion **200c** corresponding to the sacral area.

Referring again to FIG. 4B, in embodiments, the core part **132** of the support pad **130** may be formed with a channel **133** extending through the foam of the core part **132** from the recess **137** where the thermally conductive core portion **200** is located to the edge of the support pad **130**, as depicted in FIG. 4B. The channel **133** may facilitate removing and replacing the thermally conductive core portion **200** with, for example, a thermally conductive core portion constructed from different thermally conductive material having different cooling characteristics or a "fresh" thermally conductive core portion (such as when the thermally conductive core portion **200** has reached an equilibrium temperature with a subject positioned on the support pad **130** and the cooling capabilities of the thermally conductive core portion **200** are exhausted). In other embodiments, the channel **133** may facilitate removing and replacing the thermally conductive core portion **200** in the recess **137** with, for example, a plug of foam material similar or identical to the foam of the core part **132**. The thermally conductive core portion **200** may be replaced with a plug of foam material when, for example, focal cooling of a particular area is not needed or desired. The plug of foam material fills the recess **137** previously occupied by the thermally conductive core portion **200**, thereby maintaining the support provided by the support pad **130** in the absence of the thermally conductive

core portion **200**. In embodiments, access to the channel **133** in the core part **132** may be provided by, for example, a closure **138** formed in the cover material **136** enveloping the core part **132**. The closure **138** may be, for example and without limitation, a flap, a hook-and-loop closure, a zipper, or the like.

Still referring to FIGS. **4A** and **4B**, in embodiments, the side rails **126**, **127** may be formed from materials suitable for use in load bearing applications. Suitable materials may include, for example and without limitation, aluminum alloys, steel, titanium alloys, carbon fiber composites or the like. In embodiments where radiolucency is desired, the side rails **126**, **127** may be formed from, for example, carbon fiber composites. The deck **160** may also be formed from materials suitable for use in load bearing applications such as aluminum alloys, steel, titanium alloys, carbon fiber composites or the like. As with the side rails **126**, **127**, the deck **160** may be formed from carbon fiber composites when radiolucency is desired. More specifically, in various embodiments provided herein, the materials of various components of the person support systems **100**, **101** are radiolucent, or transparent to x-rays. Radiolucency, particularly in the area of the support pads **130** enables x-ray and fluoroscopic imaging to be performed during surgical procedures without interference from the person support system. X-ray or fluoroscopic images may be taken with a device having a C-arm that includes portions above and below the subject on the person support system. The use of non-radiolucent materials can cause shadows or even obstructions in the x-ray or fluoroscopic images. Accordingly, in some embodiments, portions of the person support systems described herein, such as the support pads **130** or the like, are formed from radiolucent materials.

In embodiments described herein, the thermally conductive core portion **200** of the support pad **130** may be utilized to provide focal cooling to a targeted area of a subject positioned on the support pad **130** including, without limitation, the scapular areas, the sacral areas, the buttocks, the heels, and the like. In embodiments, the targeted area may be cooled to a temperature that is from about 3° C. to about 20° C. less than body temperature. The focal cooling may be done either passively or actively, such as when the thermally conductive core portion is further coupled to a cooling source (i.e., a heat sink) as will be described in further detail herein. For example, in some embodiments, the thermally conductive core portion **200** of the support pad **130** may be thermally coupled to a cooling source (not shown) disposed within an interior channel **180** formed in at least one of the side rails **126**, **127**. The cooling source may be at a lower temperature than at least a portion of the thermally conductive core portion **200** such that the temperature gradient between the thermally conductive core portion **200** and the cooling source promotes the conduction of heat from the thermally conductive core portion **200** to the cooling source. That is, thermally coupling the thermally conductive core portion **200** of the support pad **130** to a cooling source (not shown) may assist in actively conducting heat away from the top surface **131** of the support pad **130**, enhancing the cooling provide by the thermally conductive core portion **200**. In embodiments, the thermally conductive core portion **200** may be thermally coupled to the cooling source with one or more thermally conductive elements formed from thermally conductive materials, as will be described in further detail herein.

Various embodiments of thermally conductive core portions **200** suitable for use with the support pads of FIGS. **4A** and **4B** will be described in further detail with specific reference to FIGS. **5A-5G**.

The thermally conductive core portions **200** of the support pads **130** may be formed from a variety of different materials in different arrangements. One embodiment of a thermally conductive core portion **200** is schematically depicted in FIG. **5A**. The thermally conductive core portion **200** of this embodiment includes a support matrix **204** enclosed within a compliant shell **202**. The compliant shell **202** may be formed from, for example, a fluid impermeable, elastomeric film. Suitable elastomeric films include, without limitation, urethane films, polyurethane films, and the like. The film generally has a thickness of less than 5 mils (127 micrometers) to facilitate conduction of heat into the support matrix **204**. In some embodiments, the compliant shell **202** has a thickness of less than 4 mils (101.6 micrometers) or even less than or equal to 3 mils (76.2 micrometers). In embodiments, the compliant shell **202** has a thickness greater than or equal to 1 mil (25.4 micrometers) and less than or equal to 3 mils (76.2 micrometers). In some embodiments, the compliant shell **202** has a thickness greater than or equal to 2 mils (50.8 micrometers) and less than or equal to 3 mils (76.2 micrometers).

In the embodiment depicted in FIG. **5A**, the support matrix **204** may be formed from thermally absorptive materials including, without limitation, oils with high heat capacity, fluids with high heat capacity, phase change materials (PCMs) and the like. Suitable phase change materials include, without limitation, alkanes having a melting temperature greater than or equal to about 5° C. and less than or equal to about 35° C. Examples of suitable alkanes include, without limitation, tetradecane, pentadecane, hexadecane, heptadecane, octadecane, and nonadecane. However, it should be understood that other suitable phase change materials may be used for the support matrix **204**. Suitable oils may include, without limitation, inorganic oils, silicone oils, mineral oils, and the like. Suitable fluids may include, without limitation, water, cooling fluids, or mixtures of water and cooling fluids. In embodiments where the support matrix **204** includes a fluid, an antimicrobial may be added to the fluid to mitigate microbial growth. In embodiments, the thermally conductive core portion **200** may be constructed from different phase change materials (or even different combinations of phase change materials) to achieve different degrees of cooling. In some embodiments, more or less phase change material may be incorporated into the support matrix **204** to achieve different degrees of cooling and/or the thickness of the thermally conductive core portion **200** may be increased or decreased to achieve different degrees of cooling.

Referring to FIGS. **4B** and **5A**, when the thermally conductive core portion **200** is positioned in the support pad **130** and a subject (not shown) is positioned on the top surface **131** of the support pad **130** over the thermally conductive core portion **200**, heat from the subject is absorbed into the thermally conductive core portion **200**. In embodiments where the support matrix comprises phase change materials, the absorbed heat causes the support matrix **204** to undergo a phase transformation from a solid into a pseudo-solid (i.e., a gel) or a liquid. The absorption of heat into the thermally conductive core portion **200** results in the localized cooling of the portion of the subject positioned over the thermally conductive core portion **200**.

Referring now to FIG. **5B**, in other embodiments, the thermally conductive core portion **200** may include a sup-

port matrix **204** enclosed within a compliant shell **202**. The compliant shell **202** may be formed from the same materials and have the same dimensions as described herein with respect to FIG. 5A. In the embodiment depicted in FIG. 5B, the support matrix **204** may be formed from, for example, elastomeric gels, foams, oils, or fluids. Suitable elastomeric gels may include, without limitation, silicone gels, urethane gels, polyurethane gels and the like. Suitable oils may include, without limitation, inorganic oils, silicone oils, mineral oils, and the like. Suitable foams may include, without limitation, urethane foam, polyurethane foam, and the like. Suitable fluids may include, without limitation, water, cooling fluids, or mixtures of water and cooling fluids. In embodiments where the support matrix **204** includes a fluid, the support matrix **204** may further include an anti-microbial agent to resist microbial growth.

In the embodiment depicted in FIG. 5B, the support matrix **204** may further include thermally conductive elements and/or thermally absorptive elements. For example, the support matrix **204** may include thermally conductive elements, such as thermally conductive particles **206**, suspended within the support matrix **204** to facilitate the conduction of heat through the support matrix **204** from the top surface **210** of the thermally conductive core portion **200** to the bottom surface **212** of the thermally conductive core portion **200**. The thermally conductive particles **206** may have a relatively high thermal conductivity (e.g., greater than about 40 W/m*K). Examples of thermally conductive particles **206** include, without limitation, metallic particles, carbon nanotubes, polymer particles, and combinations thereof. Suitable metallic particles include, without limitation, copper particles, copper alloy particles, silver particles, silver alloy particles, gold particles, gold alloy particles, and the like. Suitable polymer particles include, without limitation, ultra-high molecular weight polyethylene particles, polypropylene particles, liquid crystalline polymer particles, polyphthalamide particles, polycarbonate particles, and the like.

In some embodiments, the thermally conductive particles **206** are evenly dispersed throughout the support matrix **204**. In some other embodiments, the thermally conductive particles **206** are dispersed in the support matrix **204** such that the density of the thermally conductive particles **206** in the support matrix **204** (i.e., the number of thermally conductive particles **206** per unit volume of the support matrix **204**) is greatest proximate the top surface **210** of the thermally conductive core portion **200** and decreases with increasing distance from the top surface **210** of the thermally conductive core portion **200**. While not wishing to be bound by theory, it is believed that having a greater density of thermally conductive particles **206** proximate the top surface **210** of the thermally conductive core portion **200** may enhance the conduction of heat away from the top surface **210** of the thermally conductive core portion **200** and into the support matrix **204**.

Still referring to FIG. 5B, in some embodiments, the thermally conductive core portion **200** may further include a plurality of thermally absorptive elements **208** suspended within the support matrix **204**. The thermally absorptive elements **208** may be in addition to, or as an alternative to, the thermally conductive particles **206**. The thermally absorptive elements **208** facilitate the absorption and dissipation of heat from the top surface **210** of the thermally conductive core portion **200** into the support matrix **204**. In embodiments, the thermally absorptive elements **208** may be formed from phase change materials (PCMs). Suitable phase change materials include, without limitation, alkanes having

a melting temperature greater than or equal to about 5° C. and less than or equal to about 35° C. Suitable alkanes may include, without limitation, tetradecane, pentadecane, hexadecane, heptadecane, octadecane, and nonadecane. However, it should be understood that the thermally absorptive elements **208** may be formed from other suitable phase change materials.

In some embodiments, the thermally absorptive elements **208** are evenly dispersed throughout the support matrix **204**. In some other embodiments, the thermally absorptive elements **208** are dispersed in the support matrix **204** such that the density of the thermally absorptive elements **208** in the support matrix **204** (i.e., the number of thermally absorptive elements **208** per unit volume of the support matrix **204**) is greatest proximate the top surface **210** of the thermally conductive core portion **200** and decreases with increasing distance from the top surface **210** of the thermally conductive core portion **200**. While not wishing to be bound by theory, it is believed that having a greater density of thermally absorptive elements **208** proximate the top surface **210** of the thermally conductive core portion **200** may enhance the extraction and dissipation of heat from the top surface **210** of the thermally conductive core portion **200** and into the support matrix **204**.

In still other embodiments, the amount of thermally absorptive elements **208** in the support matrix **204** may be varied when constructing the thermally conductive core portion **200** to adjust the amount of cooling that can be achieved with the thermally conductive core portion **200**.

While FIG. 5B schematically depicts the thermally conductive core portion **200** as including both thermally conductive particles **206** and thermally absorptive elements **208** dispersed in the support matrix **204**, it should be understood that the thermally conductive core portion **200** may be formed without the thermally conductive particles **206** or without the thermally absorptive elements **208**. For example, in embodiments, the thermally conductive core portion **200** may be formed with only the thermally conductive particles **206** dispersed in the support matrix **204**. Alternatively, in embodiments, the thermally conductive core portion **200** may be formed with only the thermally absorptive elements **208** dispersed in the support matrix **204**.

In the embodiment depicted in FIG. 5B, the thermally conductive core portion **200** may further include a thermal transport layer **214** thermally coupled to the support matrix and configured to conduct heat from the support matrix. In some embodiments, the thermal transport layer **214** is disposed between the support matrix **204** and the compliant shell **202**, as depicted in FIG. 5B. In some other embodiments (not shown), the thermal transport layer **214** is embedded within the support matrix **204** such that a portion of the support matrix **204** is disposed between the thermal transport layer **214** and the bottom surface **212** of the compliant shell **202** and another portion of the support matrix **204** is disposed between the thermal transport layer **214** and the top surface **210** of the compliant shell **202**.

The thermal transport layer **214** may be constructed from thermally conductive materials such as, without limitation, metals, polymers, carbon fiber and/or combinations thereof. For example, in embodiments, the thermal transport layer **214** may be formed from a metal or alloy having relatively high thermal conductivity (e.g., greater than about 40 W/m*K) such as, for example and without limitation, copper, alloys of copper, and the like. In these embodiments, the thermal transport layer **214** may be in the form of a metal plate or, alternatively, a layer of woven or non-woven metallic fibers. Alternatively, the thermal transport layer **214**

may be formed from a polymer material having a relatively high thermal conductivity (e.g., greater than about 40 W/m²K) such as ultra-high molecular weight polyethylene, polypropylene, liquid crystalline polymer, polyphthalamide, polycarbonate, or the like. In these embodiments, the thermal transport layer **214** may be in the form of a polymer plate or, alternatively, a layer of woven or non-woven polymer fibers. As yet another alternative, the thermal transport layer **214** may be formed from a layer of woven or non-woven carbon fiber having a relatively high thermal conductivity (e.g., greater than about 40 W/m²K). Suitable carbon fibers include, without limitation, pitch-based carbon fibers. In these embodiments, the thermal transport layer **214** may be in the form of a carbon fiber plate or, alternatively, a layer of woven or non-woven carbon fibers.

In embodiments where radiolucency of the thermally conductive core portion **200** is desired, the thermally conductive particles **206** may be carbon nanotubes or thermally conductive polymers and the thermal transport layer **214** may be formed from carbon fiber or thermally conductive polymer(s).

In embodiments, the thermally conductive core portion **200** may further include a pigtail connector **216** thermally coupled to the thermal transport layer **214** and extending through the compliant shell **202**. The pigtail connector **216** may be used to couple the thermally conductive core portion **200** to a cooling source (described in further detail herein), thereby facilitating the extraction of heat from the interior of the thermally conductive core portion **200**. In embodiments, the pigtail connector **216** may be formed from, for example and without limitation, thermally conductive elements having a thermal conductivity of greater than about 40 W/m²K. For example, the thermally conductive elements of the pigtail connector **216** may have a thermal conductivity of from about 40 W/m²K to about 2000 W/m²K, from about 60 W/m²K to about 1000 W/m²K, from about 80 W/m²K to about 500 W/m²K, or from about 100 W/m²K to about 300 W/m²K. In one particular example, the thermally conductive elements may be carbon fibers, such as pitch-based carbon fibers. Alternatively, the thermally conductive elements may be polymer fibers or strips, such as polymer fibers or strips formed from ultra-high molecular weight polyethylene, polypropylene, liquid crystalline polymer, polyphthalamide, polycarbonate, or the like. In yet another alternative, the thermally conductive elements may be metallic fibers or wires, such as fibers or wires formed from copper or alloys of copper.

Referring to FIGS. 4B and 5B, when the thermally conductive core portion **200** is positioned in the support pad **130** and a subject (not shown) is positioned on the top surface **131** of the support pad **130** over the thermally conductive core portion **200**, heat from the subject is conducted into the support matrix **204** and through the support matrix **204** with the thermally conductive particles **206** to the thermal transport layer **214**. The thermal transport layer **214** conducts the heat laterally (i.e., in the X-Y plane) relative to the bottom surface **212** of the thermally conductive core portion **200**. Optionally, the heat may be conducted from the thermal transport layer **214** and through the pigtail connector **216** to a cooling source where the heat is dissipated. The conduction of heat into and through the thermally conductive core portion **200** results in the localized cooling of the portion of the subject positioned over the thermally conductive core portion **200**.

As noted herein, the thermally conductive particles **206** may be dispersed throughout the support matrix **204**. In embodiments, the thermal conductivity of the support matrix

204 may increase when the support matrix **204** is compressed, such as by the weight of a subject positioned on the support pad **130**. That is, as the support matrix **204** is compressed, the thermally conductive particles **206** are brought into closer proximity, thereby improving the thermal conductivity of the support matrix **204**.

In embodiments where the support matrix **204** comprises thermally absorptive elements **208**, the thermally absorptive elements **208** further assist in cooling an area of the subject positioned over the thermally conductive core portion **200**. Specifically, heat from the subject may be directly absorbed and dissipated by the thermally absorptive elements **208**. Similarly, heat being conducted through the support matrix **204** may be absorbed and dissipated by the thermally absorptive elements **208**. In either case, the absorption of heat causes the thermally absorptive elements **208** to undergo a phase transformation from a solid or pseudo-solid (i.e., a gel) to a liquid resulting in the dissipation of heat and the localized cooling of the portion of the subject positioned over the thermally conductive core portion **200**.

Referring now to FIG. 5C, an alternative embodiment of a thermally conductive core portion **200** is schematically depicted. In this embodiment, the thermally conductive core portion **200** includes a support matrix **204** enclosed within a compliant shell **202**, as described herein with respect to FIGS. 5A and 5B. In this embodiment, the support matrix **204** of the thermally conductive core portion **200** may be formed from one or more thermally absorptive materials, as described herein with respect to FIG. 5A. However, it should be understood that the support matrix **204** of the thermally conductive core portion **200** may be constructed as described with respect to FIG. 5B, that is, with a support matrix **204** formed from elastomeric gels, foams, oils, or fluids and which comprises thermally conductive particles **206** and/or thermally absorptive elements **208**.

In the embodiment depicted in FIG. 5C a top surface **210** of the compliant shell **202** may be formed with a cover flange **211** that extends around the support matrix **204** and is continuous with the top surface **210** of the compliant shell **202**. In this embodiment, at least the top surface **210** and the cover flange **211** of the compliant shell **202** may be formed from a thermally conductive material or, alternatively, from a material in which thermally conductive elements are incorporated. For example, in embodiments, at least the top surface **210** of the compliant shell **202** includes thermally conductive elements having a relatively high thermal conductivity (e.g., greater than about 40 W/m²K). The thermally conductive elements may include for example and without limitation, metal particles or metal fibers formed from copper, alloys of copper, silver, alloys of silver, gold, alloys of gold, and the like. For example, in embodiments, at least the top surface **210** of the compliant shell **202** may be in the form of an elastomeric film which includes metal particulates or a layer of woven or non-woven metallic fibers. Alternatively, at least the top surface **210** of the compliant shell **202** may be formed from or incorporate a polymer material having a relatively high thermal conductivity (e.g., greater than about 40 W/m²K) such as particles or fibers formed from ultra-high molecular weight polyethylene, polypropylene, liquid crystalline polymer, polyphthalamide, polycarbonate, or the like. For example, in embodiments, at least the top surface **210** of the compliant shell **202** may be in the form of an elastomeric film which includes thermally conductive polymer particles or a layer of woven or non-woven thermally conductive polymer fibers. As yet another alternative, at least the top surface **210** of the compliant shell **202** may be formed from or incorporate

carbon fiber or carbon nanotubes having a relatively high thermal conductivity (e.g., greater than about 40 W/m*K). For example, in embodiments, at least the top surface **210** of the compliant shell **202** may be in the form of an elastomeric film which includes thermally conductive carbon particulates or a layer of woven or non-woven thermally conductive carbon fibers.

In the embodiment of the thermally conductive core portion **200** depicted in FIG. 5C, the cover flange **211** of the compliant shell **202** assists in conducting heat into the support matrix **204**. For example, when the thermally conductive core portion **200** is positioned in the support pad and a subject (not shown) is positioned on the top surface of the support pad over and in contact with the cover flange **211**, heat from the subject is conducted through the cover flange **211** and into the support matrix **204** where the heat is dissipated. The conduction of heat into the thermally conductive core portion **200** through the cover flange **211** results in the localized cooling of the portion of the subject positioned over the thermally conductive core portion **200**.

Referring now to FIG. 5D, another alternative embodiment of a thermally conductive core portion **200** is schematically depicted. In this embodiment, the thermally conductive core portion **200** includes a support matrix enclosed within a compliant shell **202**. However, in this embodiment, the support matrix is formed from multiple parts. Specifically, the support matrix may include a first support matrix **204a** and a second support matrix **204b** enclosed within the compliant shell **202**. In this embodiment, each support matrix **204a**, **204b** is formed from elastomeric gels, foams, oils, or fluids which comprise thermally conductive particles **206** and/or thermally absorptive elements **208** dispersed therein, as described herein with respect to FIG. 5B. However, it should be understood that each support matrix **204a**, **204b** may be constructed as described with respect to FIG. 5A, that is, from thermally absorptive materials.

In the embodiment depicted in FIG. 5D, the first support matrix **204a** and the second support matrix **204b** may be separated and spaced apart by a third support matrix **204c** formed from different material than the first support matrix and the second support matrix. In the embodiment shown in FIG. 5D, the third support matrix **204c** is attached to, but not disposed in, the compliant shell **202**. However, in alternative embodiments (not shown) the third support matrix **204c** may be disposed in the compliant shell **202** between the first support matrix **204a** and the second support matrix **204b**. In these embodiments, the third support matrix **204c** may be formed from, for example and without limitation, foam such as urethane foam or polyurethane foam.

Still referring to FIG. 5D, in this embodiment of the thermally conductive core portion **200**, at least the top surface **210** of the compliant shell **202** is formed from a thermally conductive material or, alternatively, from a material in which thermally conductive elements are incorporated, such that heat from the top surface **210** of the compliant shell may be conducted into each of the first support matrix **204a** and the second support matrix **204b**. That is, in this embodiment, each of the first support matrix **204a** and the second support matrix **204b** serve as reservoirs in which heat from the top surface **210** of the compliant shell **202** may be absorbed and dissipated.

For example, in embodiments, at least the top surface **210** of the compliant shell **202** includes thermally conductive elements having a relatively high thermal conductivity (e.g., greater than about 40 W/m*K). The thermally conductive elements may include for example and without limitation, metal particles or metal fibers formed from copper, alloys of

copper, silver, alloys of silver, gold, alloys of gold, and the like. For example, in embodiments, at least the top surface **210** of the compliant shell **202** may be in the form of an elastomeric film which includes metal particulates or a layer of woven or non-woven metallic fibers. Alternatively, at least the top surface **210** of the compliant shell **202** may be formed from or incorporate a polymer material having a relatively high thermal conductivity (e.g., greater than about 40 W/m*K) such as particles or fibers formed from ultra-high molecular weight polyethylene, polypropylene, liquid crystalline polymer, polyphthalamide, polycarbonate, or the like. For example, in embodiments, at least the top surface **210** of the compliant shell **202** may be in the form of an elastomeric film which includes thermally conductive polymer particles or a layer of woven or non-woven thermally conductive polymer fibers. As yet another alternative, at least the top surface **210** of the compliant shell **202** may be formed from or incorporate carbon fiber or carbon nanotubes having a relatively high thermal conductivity (e.g., greater than about 40 W/m*K). For example, in embodiments, at least the top surface **210** of the compliant shell **202** may be in the form of an elastomeric film which includes thermally conductive carbon particulates or a layer of woven or non-woven thermally conductive carbon fibers.

In the embodiment of the thermally conductive core portion **200** depicted in FIG. 5D, at least the top surface **210** of the compliant shell **202** assists in conducting heat into the first support matrix **204a** and the second support matrix **204b**. For example, when the thermally conductive core portion **200** is positioned in the support pad and a subject (not shown) is positioned on the top surface of the support pad over and in contact with the top surface **210** of the compliant shell **202**, heat from the subject is conducted through and along the top surface **210** of the compliant cover and into support matrix **204a** and support matrix **204b** where the heat is dissipated. The conduction of heat into the support matrix **204a** and the support matrix **204b** of the thermally conductive core portion **200** results in the localized cooling of the portion of the subject positioned over the thermally conductive core portion **200**.

Referring now to FIGS. 5E-5G, alternative embodiments of thermally conductive core portions **200** are schematically depicted. These embodiments of the thermally conductive core portions **200** include a support matrix **204** enclosed within a compliant shell **202**, as described herein with respect to FIGS. 5A and 5B. The compliant shell **202** of the thermally conductive core portion **200** may be formed from the same materials and have the same dimensions as described hereinabove with respect to FIGS. 5A and 5B. Further, in the embodiments of the thermally conductive core portions **200** depicted in FIGS. 5E-5G, the support matrix **204** may be formed from, for example, phase change materials, elastomeric gels, foams, oils, or fluids as described herein with respect to FIG. 5B. In some embodiments, the support matrix may be formed from, for example, thermally absorptive materials including, without limitation, phase change materials, oils with high heat capacity, water, cooling fluids, and the like. Suitable phase change materials include, without limitation, alkanes having a melting temperature greater than or equal to about 5° C. and less than or equal to about 35° C. Examples of suitable alkanes include, without limitation, tetradecane, pentadecane, hexadecane, heptadecane, octadecane, and nonadecane. Suitable elastomeric gels may include, without limitation, silicone gels, urethane gels, polyurethane gels and the like. Suitable oils may include, without limitation, inorganic oils, silicone oils, mineral oils, and the like. Suitable foams may include,

without limitation, urethane foam, polyurethane foam, and the like. Suitable fluids may include, without limitation, water, cooling fluids, or mixtures of water and cooling fluids. In embodiments where the support matrix **204** includes a fluid, the support matrix **204** may further include an antimicrobial agent to resist microbial growth. Although not depicted in FIGS. 5E-5G, the thermally conductive core portions **200** may optionally include thermally conductive particles and/or thermally absorptive particles dispersed in the support matrix **204** as described herein with respect to FIG. 5B. However, it should be understood that the thermally conductive particles and/or thermally absorptive particles are optional and that the thermally conductive core portions **200** depicted in FIGS. 5E-5G may be formed without thermally conductive particles and/or thermally absorptive particles dispersed in the support matrix **204**.

In the embodiments of the thermally conductive core portion **200** depicted in FIGS. 5E-5G, the support matrix **204** may further include thermally conductive elements, such as an array of thermally conductive fibers **220**, suspended within the support matrix **204** to facilitate the conduction of heat through the support matrix **204** and away from the top surface **210** of the thermally conductive core portion **200**. In these embodiments, the thermally conductive fibers **220** may have a relatively high thermal conductivity (e.g., greater than about 40 W/m*K). For example, in embodiments, the thermally conductive fibers **220** may have a thermal conductivity of from about 40 W/m*K to about 2000 W/m*K, from about 60 W/m*K to about 1000 W/m*K, from about 80 W/m*K to about 500 W/m*K, or even from about 100 W/m*K to about 300 W/m*K. Examples of thermally conductive fibers **220** include, without limitation, metallic fibers, carbon fibers, polymer fibers and combinations thereof. Suitable metallic fibers include, without limitation, copper fibers, copper alloy fibers, silver fibers, silver alloy fibers, gold fibers, gold alloy fibers, and the like. Suitable polymer fibers include, without limitation, ultra-high molecular weight polyethylene fibers, polypropylene fibers, liquid crystalline polymer fibers, polyphthalamide fibers, polycarbonate fibers, and the like. Suitable carbon fibers include, without limitation, pitch-based carbon fibers.

In the embodiments of the thermally conductive core portions **200** depicted in FIGS. 5E-5G, the thermally conductive fibers **220** of the array of fibers may be arranged in various orientations within the support matrix **204**. In general, at least a portion of the array of thermally conductive fibers **220** extend from at least one of a side surface **222** of the thermally conductive core portion **200** and a bottom surface **212** of the thermally conductive core portion **200**. In embodiments, at least a portion of the array of thermally conductive fibers **220** extends towards a top surface **210** of the thermally conductive core portion **200**. In some embodiments, the thermally conductive fibers **220** extend to and contact the compliant shell **202**, as depicted in FIGS. 5E-5G. In some other embodiments, the thermally conductive fibers **220** extend towards the top surface **210** of the thermally conductive core portion **200** but are spaced apart from the compliant shell **202**. In embodiments, a portion of the support matrix **204** is disposed between the thermally conductive fibers **220** and the compliant shell **202**. In some other embodiments, an optional spacer layer (not shown) is disposed between the thermally conductive fibers **220** and the compliant shell **202**. In embodiments, the spacer layer may include a woven or non-woven batting or scrim formed from non-conductive fibers (such as polyester, cotton, or the like)

or a combination of non-conductive fibers and conductive fibers (such as carbon fiber, metallic fibers, and/or polymer fibers).

In the embodiment of the thermally conductive core portion **200** depicted in FIG. 5E, the array of thermally conductive fibers **220** includes a plurality of fibers which extend from the bottom surface **212** of the thermally conductive core portion **200** towards the top surface **210**. In this embodiment the thermally conductive fibers **220** in the array are generally parallel with one another and to the vertical direction (i.e., the +/-Z direction of the coordinate axes depicted in the figures). That is, the thermally conductive fibers are generally perpendicular to the top surface **210** of the thermally conductive core portion. The thermally conductive fibers **220** in this embodiment extend through the bottom surface **212** of the compliant shell **202** and may be bundled together to form a pigtail connector **216**. The pigtail connector **216** may be thermally coupled to a cooling source (not shown) as described in further detail herein.

Referring to FIGS. 4B and 5E, when the thermally conductive core portion **200** is positioned in the support pad **130** and a subject (not shown) is positioned on the top surface **131** of the support pad **130** over the thermally conductive core portion **200**, heat from the subject is conducted into the support matrix **204**, through the support matrix **204** with the thermally conductive fibers **220**, and through the pigtail connector **216** to a cooling source where the heat is dissipated. The conduction of heat into and through the thermally conductive core portion **200** results in the localized cooling of the portion of the subject positioned over the thermally conductive core portion **200**.

Referring now to FIG. 5F, in embodiments, the thermally conductive elements, specifically the array of thermally conductive fibers **220**, includes a first plurality of thermally conductive fibers **224** and a second plurality of thermally conductive fibers **226**. In the embodiment of the thermally conductive core portion **200** depicted in FIG. 5F, the first plurality of thermally conductive fibers **224** are the fibers **220** generally parallel to the +/-Z direction of the coordinate axes depicted in the figure and the second plurality of thermally conductive fibers **226** are the fibers generally parallel to the +/-Y direction of the coordinate axes depicted in the figure (i.e., generally parallel to the top surface **210** of the thermally conductive core portion). Accordingly, it should be understood that the first plurality of thermally conductive fibers **224** and the second plurality of thermally conductive fibers **226** are generally perpendicular with one another. In embodiments, the first plurality of thermally conductive fibers **224** intersect with and contact the second plurality of thermally conductive fibers **226** and, as such, the first and second pluralities of thermally conductive fibers **224**, **226** are directly thermally coupled to one another. In some other embodiments, the first plurality of thermally conductive fibers **224** do not contact the second plurality of thermally conductive fibers **226** and, as such, the first and second pluralities of thermally conductive fibers **224**, **226** are indirectly thermally coupled to one another. The first plurality of thermally conductive fibers **224** extend through the bottom surface **212** of the compliant shell **202** and may be bundled together to form a pigtail connector **216** while the second plurality of thermally conductive fibers **226** extend through the side surface **222** of the compliant shell **202** and may be bundled together to form a pigtail connector **216**. The pigtail connectors **216** may be thermally coupled to a cooling source (not shown) as described in further detail herein.

Referring to FIGS. 4B and 5F, when the thermally conductive core portion 200 is positioned in the support pad 130 and a subject (not shown) is positioned on the top surface 131 of the support pad 130 over the thermally conductive core portion 200, the first plurality of thermally conductive fibers 224 conducts heat from the top surface 210 of the thermally conductive core portion 200 through the support matrix 204 in a vertically downward direction (i.e., in the -Z direction of the coordinate axes depicted in the figure) towards and through the bottom surface 212 of the thermally conductive core portion 200, thereby expelling heat from the interior of the thermally conductive core portion 200 through the pigtail connector 216 formed from the first plurality of thermally conductive fibers 224. The second plurality of thermally conductive fibers 226 assists the first plurality of thermally conductive fibers 224 in expelling heat from the interior of the thermally conductive core portion. Specifically, as the first plurality of thermally conductive fibers 224 conducts heat away from the top surface 210, at least a portion of the heat is coupled into the second plurality of thermally conductive fibers 226 which conduct the heat laterally (i.e., in the +/-Y direction of the coordinate axes depicted in the figure) towards and through the side surface 222 of the thermally conductive core portion 200, thereby expelling heat from the interior of the thermally conductive core portion 200 through the pigtail connector 216 formed by the second plurality of thermally conductive fibers 226.

In embodiments, the fibers of the first plurality of thermally conductive fibers 224 may have substantially the same thermal conductivity as the second plurality of thermally conductive fibers 226. Alternatively, the fibers of the first plurality of thermally conductive fibers 224 may have greater thermal conductivity than the second plurality of thermally conductive fibers 226.

In embodiments, the second plurality of thermally conductive fibers 224 includes fibers having different thermal conductivities. In these embodiments, the fibers of the second plurality of thermally conductive fibers 224 are arranged in the support matrix 204 such that fibers having relatively greater thermal conductivities are positioned closer to the top surface 210 of the thermally conductive core portion 200 than fibers having a relatively lower thermal conductivity. While not wishing to be bound by theory, it is believed that having fibers with relatively greater thermal conductivities proximate the top surface 210 of the thermally conductive core portion 200 may enhance the extraction of heat away from the top surface 210 of the thermally conductive core portion 200 and into the support matrix 204.

In embodiments, the second plurality of thermally conductive fibers 226 are evenly distributed throughout the support matrix 204. In some other embodiments, the second plurality of thermally conductive fibers 226 are distributed in the support matrix 204 such that the density of the second plurality of thermally conductive fibers 226 in the support matrix 204 (i.e., the number of fibers 220 per unit volume of the support matrix 204) is greatest proximate the top surface 210 of the thermally conductive core portion 200 and decreases with increasing distance from the top surface 210 of the thermally conductive core portion 200. While not wishing to be bound by theory, it is believed that having a greater density of second plurality of thermally conductive fibers 226 proximate the top surface 210 of the thermally conductive core portion 200 may enhance the extraction of heat from the top surface 210 of the thermally conductive core portion 200 and into the support matrix 204.

While FIG. 5F schematically depicts the first plurality of thermally conductive fibers 224 as substantially perpendicular to the second plurality of fibers 226, it should be understood that other embodiments are contemplated and possible. For example, FIG. 5G depicts an alternative embodiment of the array of thermally conductive fibers 220. In this embodiment, the second plurality of fibers 226 are the fibers generally parallel to the +/-Y direction of the coordinate axes depicted in the figure. However, in this embodiment, the first plurality of thermally conductive fibers 224 are obliquely oriented with respect to the second plurality of thermally conductive fibers 226. Specifically, in this embodiment, the first plurality of thermally conductive fibers 224 are arranged at an angle with respect to the Z axis to conduct heat laterally, away from the mid-line 230 of the thermally conductive core portion 200. Arranging the first plurality of thermally conductive fibers 224 in this configuration may enhance the extraction of heat from the thermally conductive core portion 200.

Still referring to FIG. 5G, in embodiments, the fibers of the first plurality of thermally conductive fibers 224 may have substantially the same thermal conductivity as the second plurality of thermally conductive fibers 226. Alternatively, the fibers of the first plurality of thermally conductive fibers 224 may have greater thermal conductivity than the second plurality of thermally conductive fibers 226.

In embodiments, the second plurality of thermally conductive fibers 224 includes fibers having different thermal conductivities. In these embodiments, the fibers of the second plurality of thermally conductive fibers 224 are arranged in the support matrix 204 such that fibers having relatively greater thermal conductivities are positioned closer to the top surface 210 of the thermally conductive core portion 200 than fibers having a relatively lower thermal conductivity. While not wishing to be bound by theory, it is believed that having fibers with relatively greater thermal conductivities proximate the top surface 210 of the thermally conductive core portion 200 may enhance the extraction of heat away from the top surface 210 of the thermally conductive core portion 200 and into the support matrix 204.

In embodiments, the second plurality of thermally conductive fibers 226 are evenly distributed throughout the support matrix 204. In some other embodiments, the second plurality of thermally conductive fibers 226 are distributed in the support matrix 204 such that the density of the second plurality of thermally conductive fibers 226 in the support matrix 204 (i.e., the number of fibers 220 per unit volume of the support matrix 204) is greatest proximate the top surface 210 of the thermally conductive core portion 200 and decreases with increasing distance from the top surface 210 of the thermally conductive core portion 200. While not wishing to be bound by theory, it is believed that having a greater density of second plurality of thermally conductive fibers 226 proximate the top surface 210 of the thermally conductive core portion 200 may enhance the extraction of heat from the top surface 210 of the thermally conductive core portion 200 and into the support matrix 204.

Referring now to FIG. 6, an alternative embodiment of a portion of a support pad 130 is schematically depicted in cross section. In this embodiment, the support pad 130 may include a cover 304 (i.e., a cover material) with a cushioning material 306 (i.e., a support matrix), such as foam or the like, and a cooling feature in the form of a thermally conductive element 308 disposed between the substrate 302 and the cover 304. In embodiments, the support pad 130 may optionally include a rigid substrate 302 positioned beneath

the cushioning material **306**. In embodiments, the thermally conductive element **308** may include thermally conductive fibers, thermally conductive films, or the like. In some embodiments, the support pad **130** may include a contoured or a shaped surface to accommodate a specific portion of a patient. For example, a support pad **130** positioned to support a subject's head may be contoured to correspond to an approximate shape and size of a subject's head. Alternatively, a support pad **130** positioned to support a subject's head may include an aperture to accommodate a subject's facial features (i.e., eyes, nose, and/or mouth).

In the embodiment depicted in FIG. 6, the thermally conductive element **308** is positioned between the cover **304** and the cushioning material **306**. Alternatively, the thermally conductive element **308** may be embedded in and/or dispersed throughout the cushioning material, as described herein with respect to FIGS. 5B-5F. In embodiments, the thermally conductive element **308** and the cover **304** extend laterally (i.e., generally along the Y axis of the coordinate axes depicted in FIG. 6) beyond the cushioning material **306** and the optional substrate **302** in the embodiment of FIG. 6. For example, the cover **304** and the thermally conductive element **308** may wrap around the edges of the cushioning material **306** and the substrate **302**, enveloping the cushioning material **306**. In some embodiments, the cover **304** and/or the thermally conductive element **308** may be coupled to a bottom surface **312** of the optional substrate **302** of the cushioning material **306** such as by an adhesive, mechanical fasteners, or the like. In the embodiment of the support pad **130** depicted in FIG. 6, the cushioning material **306** and the thermally conductive element **308** are the thermally conductive core portion of the support pad **130**.

The optional substrate **302** may be a rigid material to provide structure and support for the support pad **130**. For example, the optional substrate **302** may be a rigid plastic or a composite that is radiolucent. In some embodiments, the optional substrate **302** may be a foam with an indentation load deflection (ILD) value that is suitable to provide support without producing unnecessarily high pressures on the subject supported by the support surface. It is contemplated that other materials may be used as a substrate **302**, provided that they do not degrade the radiolucency of the support pad **130**.

In the embodiments described herein, the cover **304** may be an elastomer, gel, or other protective material to protect the cushioning material **306** and the thermally conductive element **308** from fluids or biological materials. For example, in embodiments, the cover **304** may be fluid impermeable, such that water and/or biological fluids do not pass through the cover **304** and contaminate the cushioning material **306** and/or the thermally conductive element **308**. Suitable materials for the cover **304** may include, for example, urethane, nylon and/or Lycra material. In embodiments, the cover **304** may be formed from the same material as the cover material described herein with respect to FIGS. 4A and 4B. However, it is contemplated that other materials may be used as a cover **304**, provided that they do not degrade the radiolucency of the support pad **130**. In some embodiments, the cover **304** may be removable and/or washable, enabling it to be changed and/or washed.

As shown in FIG. 6, in some embodiments, the cover **304** may have a first thickness t_1 at a person support surface **310** and a second thickness t_2 at a portion of the support pad that does not form the person support surface **310**. For example, the cover **304** may have a first thickness t_1 over the cushioning material **306** and a second thickness t_2 over areas in which the thermally conductive element **308** extend beyond

the top of the cushioning material **306**, such as adjacent to the side of the cushioning material. In various embodiments, the first thickness t_1 is greater than the second thickness t_2 . In such embodiments, the increased thickness of the first thickness t_1 in relation to the second thickness t_2 provides insulation which prevents heat drawn away from the person support surface **310** from returning to that surface. Instead, the heat is transferred away from the person support surface **310**, thus providing a cooling effect. More specifically, the greater thickness of t_1 may reduce or eliminate the passage of heat from the thermally conductive element **308** back to the subject positioned on the person support surface **310**.

Alternatively, or in addition to the varying thickness of the cover **304**, an optional thermal shield may be positioned between the thermally conductive element **308** and the cover **304**. The thermal shield may be, for example, a polyethylene terephthalate, or polyester, film (e.g., Mylar®) or other thermally reflective material positioned to reflect heat toward the thermally conductive element **308**. It is contemplated that other materials may be used as a thermal shield, provided that they do not negatively impact the radiolucency of the support pad **130**. In such embodiments, as heat is transferred from the cover **304** at the person support surface **310** to the thermally conductive element **308**, the thermal shield reduces or eliminates the amount of heat that returns to the cover **304** at the person support surface **310**.

The cushioning material **306** may be any type of material suitable for providing support to the subject on the person support surface **310** without producing unnecessarily high pressures on the subject supported by the person support surface **310**. For example, the cushioning material **306** can be a foam, gel, other material, or combinations thereof. In some embodiments, the cushioning material **306** may be in the form of a fluid-filled bladder. The fluid may be, for example, a liquid or gas. In still other embodiments, multiple layers of cushioning material **306** may be included. The layers may include the same materials or different materials, depending on the particular embodiment. For example, a layer of foam and a layer of gel may be employed, or two layers of foam may be employed. As with the substrate **302** and the cover **304**, in various embodiments, the cushioning material **306** is made of a radiolucent material.

The cushioning material **306** may be planar or contoured, depending on the specific use of the support pad **130**. For example, the cushioning material **306** may have a uniform thickness, as depicted in FIG. 6, or it may have a thickness that varies along the length and/or width of the support pad **130**. In some embodiments, the variation in the thickness of the cushioning material **306** may be based on a portion of the anatomy of the subject supported by the support pad **130**. For example, a support pad intended for use in supporting a hip may have a first thickness profile, while a support pad intended for use in supporting a shoulder may have a second thickness profile. In addition to varying thicknesses of the cushioning material **306**, the shape of the cushioning material **306** may also vary depending on the particular use of the support pad **130**. For example, the cushioning material **306** may be rectangular, annular, hexagonal, or another suitable shape.

In various embodiments, the thermally conductive element **308** is positioned between the cover **304** and the cushioning material **306**. As noted herein, the thermally conductive element **308** and the cushioning material **306** together form the thermally conductive core portion of the support pad **130** depicted in FIG. 6. In embodiments, when the support pad **130** is positioned on the longitudinal frame **125** of a person support system **100**, **101** (FIGS. 1-3), the

thermally conductive element **308** is oriented across the support pad **130** in a direction perpendicular to the longitudinal direction of the longitudinal frame **125** (e.g., along the Y axis in FIG. 1) to facilitate coupling the thermally conductive element to a cooling fluid and/or cooling fluid source through the side rails **126**, **127**, as will be described in further detail herein.

As provided above, in various embodiments, the thermally conductive element **308** extends beyond the person support surface **310**. For example, the thermally conductive element **308** may extend to an area of the support pad **130** that is not contacted or covered by a subject supported by the support pad **130**, such as the sides of the support pad **130**. In various embodiments, the thermally conductive element **308** has an area that is not covered by the subject that is a minimum of about 25% of the area of the thermally conductive element **308**. The extension of the thermally conductive element **308** to an area of the support pad **130** that is not in contact with the subject supported by the support pad **130** enables formation of a temperature gradient along the thermally conductive element **308**, which in turn enables the thermally conductive element **308** to function as a cooling mechanism for the support pad **130**.

That is, the thermally conductive element **308** may include two areas, a source region and a sink region. The source region includes the portions of the thermally conductive element **308** that is covered by a subject supported by the support pad **130**. The sink region includes the portions of the thermally conductive element **308** that is not covered by a subject supported by the support pad **130**. The area of the sink region may be at least 25% of the area of the source region. In some embodiments, the area of the sink region may be from about 25% to about 200% of the area of the source region, from about 30% to about 100% of the area of the source region, or from about 40% to about 80% of the area of the source region. The sink region withdraws heat from the source region, thus removing heat from the person support surface **310** and directing it away from the interface between the subject supported by the support pad **130** and the cover **304** of the support pad **130**.

Still referring to FIG. 6, in various embodiments, the thermally conductive element **308** may include thermally conductive fibers, thermally conductive films, and the like. In embodiment, the thermally conductive fibers having a thermal conductivity of greater than about 40 W/m*K. For example, the thermally conductive fibers may have a thermal conductivity of from about 40 W/m*K to about 2000 W/m*K, from about 60 W/m*K to about 1000 W/m*K, from about 80 W/m*K to about 500 W/m*K, or from about 100 W/m*K to about 300 W/m*K. Suitable fibers may include, for example, carbon fibers and/or polymer fibers. In one particular example, the thermally conductive fibers may include pitch-based carbon fiber. Alternatively or additionally, the thermally conductive fibers may include polymer fibers formed from ultra-high molecular weight polyethylene fibers, polypropylene fibers, liquid crystalline polymer fibers, polyphthalamide fibers, polycarbonate fibers, and the like. Other materials having a suitable thermal conductivity are contemplated, including, without limitation, metallic fibers as described herein. In embodiments where the thermally conductive element **308** is formed from thermally conductive fibers, the fibers may be arrayed in a linear pattern (i.e., parallel with one another). Alternatively, the thermally conductive fibers may have a zig-zag or sinusoidal configuration. As yet another alternative, the thermally conductive fibers may be interwoven to form a thermally conductive fabric.

When the thermally conductive element **308** is a film, the film may be formed from, for example and without limitation, thermally conductive polymer materials. Suitable polymer films include polymer films having a thermal conductivity of greater than about 40 W/m*K. For example, the polymer film may have a thermal conductivity of from about 40 W/m*K to about 2000 W/m*K, from about 60 W/m*K to about 1000 W/m*K, from about 80 W/m*K to about 500 W/m*K, or from about 100 W/m*K to about 300 W/m*K. Suitable polymer materials for the film include, without limitation, ultra-high molecular weight polyethylene, polypropylene, liquid crystalline polymer, polyphthalamide, polycarbonate, and the like.

Furthermore, in the various embodiments of the support pads and thermally conductive core portions described herein (i.e., the thermally conductive core portions depicted in FIGS. 5A-5G and the support pad of FIG. 6), the thermally conductive elements (i.e., fibers, films, etc.) incorporated in the support pads may have a value of $k \times T$ of from about 0.006 W/K to about 12 W/K, from about 0.02 W/K to about 10 W/K, or from about 0.05 W/K to about 6 W/K. These values represent the mean directional thermal conductivity k (in Watts per meter degree Kelvin or W/m*K) and the total thickness T (in meters) of the thermally conductive element. The two values are specified together because there is an inverse relationship between the mean thermal conductivity k of the material and the thickness of the layer required to conduct sufficient heat to cool the skin under a set of typical thermal conditions for such applications. Table 1 reflects constraints on the conductivity (k) of the thermally conductive element and the thickness (T) of the element such that $k \times T$ is greater than or equal to about 0.006 W/K and less than about 12 W/K.

TABLE 1

Depth of Conductive Material for Given Conductivity Over Range of $k \times T$ from 0.006 W/K to 12 W/K				
Conductivity (W/m * K)	Minimum Depth		Maximum Depth	
	(m)	(cm)	(m)	(cm)
40	0.000150	0.015	0.300	30.00
60	0.000100	0.010	0.200	20.00
80	0.000075	0.008	0.150	15.00
100	0.000060	0.006	0.120	12.00
125	0.000048	0.005	0.06	9.60
150	0.000040	0.004	0.080	8.00
200	0.000030	0.0030	0.060	6.00
300	0.000020	0.0020	0.040	4.00
500	0.000012	0.0012	0.024	2.40
1000	0.000006	0.0006	0.012	1.20
2000	0.000003	0.0003	0.006	0.60

Referring again to FIG. 6, in embodiments, the support pad **130** may optionally further include a pigtail connector **216** thermally coupled to the thermally conductive element **308**. The pigtail connector **216** may be used to couple the thermally conductive element **308** to a cooling source (described in further detail herein), thereby facilitating the extraction of heat from the support pad **130**. In embodiments, the pigtail connector **216** may be formed from, for example and without limitation, thermally conductive material having a thermal conductivity of greater than about 40 W/m*K. For example, the thermally conductive material of the pigtail connector **216** may have a thermal conductivity of from about 40 W/m*K to about 2000 W/m*K, from about 60 W/m*K to about 1000 W/m*K, from about 80 W/m*K to

about 500 W/m²*K, or from about 100 W/m²*K to about 300 W/m²*K. In one particular example, the thermally conductive material may be carbon fiber, such as pitch-based carbon fibers. Alternatively, the thermally conductive elements may be polymer fibers or strips, such as polymer fibers or strips formed from ultra-high molecular weight polyethylene, polypropylene, liquid crystalline polymer, polyphthalamide, polycarbonate, or the like.

Referring now to FIGS. 5B-5G and FIG. 6, embodiments of the support pad 130 and/or the thermally conductive core portion 200 of the support pad 130 may include a pigtail connector 216, as described herein, to thermally couple the support pad 130 and/or the thermally conductive core portion 200 of the support pad 130 to a cooling source (i.e., a cooling source external to the thermally conductive core portion 200). The cooling source further aids in conducting and dissipating heat from the top surface of the support pad 130. In some embodiments, the pigtail connector 216 may further include a coupler to assist in thermally coupling the pigtail connector 216 to the cooling source and/or the side rails of a person support system.

Referring to FIG. 7A by way of example, one embodiment of a magnetic coupler 250 is schematically depicted. In this embodiment the magnetic coupler 250 includes a first coupler body 252a and a second coupler body 252b. The first coupler body 252a includes a magnet 254a positioned in a holder 256a. Similarly, the second coupler body 252b includes a magnet 254b positioned in a holder 256b. The magnets 254a, 254b may be, for example and without limitation, ferrite magnets, rare earth magnets, sintered AlNiCo magnets, and the like. The holders 256a, 256b may be formed from thermally conductive materials such as thermally conductive metals, thermally conductive polymers, and the like. For example, in some embodiments, the holders 256a, 256b are formed from copper or a copper alloy. Alternatively, the holders 256a, 256b are formed from thermally conductive polymers such as ultra-high molecular weight polyethylene, polypropylene, liquid crystalline polymer, polyphthalamide, polycarbonate, and the like.

The magnets 254a, 254b are arranged in their respective holders 256a, 256b such that the magnets 254a, 254b are mutually attracted, thereby coupling the first coupler body 252a and the second coupler body 252b to one another and, hence, thermally coupling holder 256a of the first coupler body 252a to holder 256b of the second coupler body 252b. That is, the magnets 254a, 254b are arranged such that the “+” pole piece of either magnet 254a or magnet 254b mates with the “-” pole piece of the other of magnet 254a and 254b.

Still referring to FIG. 7A, a pigtail connector 216 may be thermally coupled to the first coupler body 252a with a thermally conductive adhesive to facilitate good thermal conduction between the thermally conductive material of the pigtail connector 216 and the first coupler body 252a. Alternatively, the pigtail connector 216 may be embedded in or fused to the first coupler body 252a to facilitate good thermal conduction between the thermally conductive material of the pigtail connector 216 and the first coupler body 252a.

In the embodiment of the magnetic coupler 250 depicted in FIG. 7A, the second coupler body 252b may optionally comprise a second pigtail connector 218. The second pigtail connector 218 may be used to couple the magnetic coupler to, for example, a cooling source (not depicted). The second pigtail connector 218 may be thermally coupled to the second coupler body 252b with a thermally conductive adhesive to facilitate good thermal conduction between the

thermally conductive material of the second pigtail connector 218 and the second coupler body 252b. Alternatively, the second pigtail connector 218 may be embedded in or fused to the second coupler body 252b to facilitate good thermal conduction between the thermally conductive material of the second pigtail connector 218 and the second coupler body 252b.

Referring now to FIG. 7B, another embodiment of a magnetic coupler 250 is schematically depicted. In this embodiment the magnetic coupler 250 includes a magnet 254a and a magnet 254b. The magnets 254a, 254b may be, for example and without limitation, ferrite magnets, rare earth magnets, sintered AlNiCo magnets, and the like. The magnets 254a, 254b are arranged such that the magnets 254a, 254b are mutually attracted, thereby coupling the magnet 254a and magnet 254b to one another and, hence, thermally coupling magnet 254a to magnet 254b. That is, the magnets 254a, 254b are arranged such that the “+” pole piece of either magnet 254a or magnet 254b mates with the “-” pole piece of the other of magnet 254a and 254b.

In this embodiment, the pigtail connector 216 may be thermally coupled to the magnet 254a with a thermally conductive adhesive to facilitate good thermal conduction between the thermally conductive material of the pigtail connector 216 and the magnet 254a. Alternatively, the pigtail connector 216 may be embedded in or fused to the magnet 254a to facilitate good thermal conduction between the thermally conductive material of the pigtail connector 216 and the magnet 254a.

In the embodiment of the magnetic coupler 250 depicted in FIG. 7B, the magnet 254b may optionally comprise a second pigtail connector 218. The second pigtail connector 218 may be used to couple the magnetic coupler to, for example, a cooling source (not depicted). The second pigtail connector 218 may be thermally coupled to the magnet 254b with a thermally conductive adhesive to facilitate good thermal conduction between the thermally conductive material of the second pigtail connector 218 and the magnet 254b. Alternatively, the second pigtail connector 218 may be embedded in or fused to the magnet 254b to facilitate good thermal conduction between the thermally conductive material of the second pigtail connector 218 and the magnet 254b.

Referring now to FIG. 7C, another embodiment of a magnetic coupler 250 is schematically depicted. In this embodiment the magnetic coupler 250 includes a magnet 254a and a magnet 254b. The magnets 254a, 254b may be, for example and without limitation, ferrite magnets, rare earth magnets, sintered AlNiCo magnets, and the like. The magnets 254a, 254b are arranged such that the magnets 254a, 254b are mutually attracted, thereby coupling the magnet 254a and magnet 254b to one another and, hence, thermally coupling magnet 254a to magnet 254b. That is, the magnets 254a, 254b are arranged such that the “+” pole piece of either magnet 254a or magnet 254b mates with the “-” pole piece of the other of magnet 254a and 254b.

In this embodiment, the pigtail connector 216 may be mechanically connected to the magnet 254a. For example, the magnet 254a may include a plurality of channels 258 that extend through the thickness of the magnet 254a. Thermally conductive fibers 220 of the pigtail connector 216 may be positioned in the channels 258 such that the fibers extend through the thickness of the magnet 254a in the channels 258. The thermally conductive fibers 220 may be secured in the channels 258 with, for example, an adhesive, such as a thermally conductive adhesive.

In the embodiment of the magnetic coupler **250** depicted in FIG. 7C, the magnet **254b** may further comprise a second pigtail connector **218**. The second pigtail connector **218** may be used to couple the magnetic coupler to, for example, a cooling source (not depicted). The second pigtail connector **218** may be mechanically connected to the magnet **254b**. For example, the magnet **254b** may include a plurality of channels **258** that extend through the thickness of the magnet **254b**. Thermally conductive fibers **220** of the second pigtail connector **218** may be positioned in the channels **258** such that the fibers extend through the thickness of the magnet **254b** in the channels **258**. The thermally conductive fibers **220** may be secured in the channels **258** with, for example, an adhesive, such as a thermally conductive adhesive.

Still referring to FIG. 7C, when the magnet **254a** is mated with the magnet **254b**, the thermally conductive fibers **220** of the pigtail connector **216** are directly thermally coupled to the fibers **220** of the second pigtail connector **218**, thereby thermally coupling the pigtail connector **216** with the second pigtail connector **218**.

The embodiments of the magnetic coupler **250** depicted in FIGS. 7A-7C may provide a relatively large surface area between opposing halves of the coupler which, in turn, aids in good thermal conduction through the magnetic coupler. In addition, the embodiments of the magnetic coupler provide a connection that may be easily separated and reconnected without the use of tools.

Referring now to FIG. 8, an alternative embodiment of a coupler **260** for thermally coupling the pigtail connector **216** to a cooling source is schematically depicted. In this embodiment, the coupler **260** includes a pair of platens **262a**, **262b**. The platens **262a**, **262b** may be formed from thermally conductive metals such as, without limitation, copper and copper alloys. In this embodiment, the thermally conductive fibers **220** of the pigtail connector **216** may be sandwiched between platen **262a** and platen **262b** such that the thermally conductive fibers **220** are thermally coupled to the respective surfaces of the platens **262a**, **262b**. In embodiments, the platens **262a**, **262b**, with the thermally conductive fibers **220** sandwiched therebetween, may be joined using, for example and without limitation, mechanical fasteners, adhesives including thermally conductive adhesives, solder, or the like. For example, in the embodiment of the coupler **260** depicted in FIG. 8, the platen **262a** and **262b** are joined together with a layer of adhesive **263**. The thermally conductive platens **262a**, **262b** provide increased surface area by which heat conducted through the thermally conductive fibers **220** of the pigtail connector **216** may be diffused through conduction and/or convection.

While FIGS. 7A-7C and FIG. 8 depict various couplers for thermally coupling the pigtail connector **216** to, for example, a cooling source, it should be understood that other couplers are contemplated and possible. Moreover, it should be understood that, in some embodiments, the pigtail connector **216** may be thermally coupled to a cooling source without a coupler, such as when the thermally conductive fibers **220** of the pigtail connector **216** are proximity coupled to the cooling source or directly coupled to the cooling source.

As described herein, in embodiments, the thermally conductive core portion **200** (e.g., the thermally conductive core portions **200** depicted in FIGS. 5B-5F) of the support pads **130**, or the thermally conductive element **308** (e.g., the thermally conductive element **308** depicted in FIG. 6) of the support pads **130**, may be thermally coupled to a cooling source to further enhance the extraction of heat from the

surface of the support pad. Various embodiments of cooling sources will now be described in detail with specific reference to the figures.

Referring now to FIGS. 4A and 9, FIG. 9 schematically depicts one embodiment of a cross-section of the side rail **126** and support pad **130** of FIG. 4A in which the side rail **126** contains a cooling source. In this embodiment, the cooling source comprises a blower **400** disposed within the interior channel **180** of the side rail **126**. While FIG. 9 schematically depicts the blower **400** as a conventional bladed fan, it should be understood that other blowers are contemplated and possible including without limitation, centrifugal blowers and the like. Further, while FIG. 9 depicts the blower positioned within the interior channel **180**, it should be understood that other configurations are contemplated and possible, including configurations in which the blower **400** is located external to the side rail **126** and the output fluid **402** (e.g., air, schematically depicted with a block arrow) is coupled into the side rail **126** with a conduit.

In this embodiment, the support pad **130** includes a thermally conductive core portion **200** as depicted in FIG. 4A. However, it should be understood that, in an alternative embodiment, the thermally conductive core portion **200** may be similar to the thermally conductive core portion depicted in FIG. 4B. In this embodiment, the pigtail connector **216** of the support pad **130** is thermally coupled to a second pigtail connector **218** with magnetic coupler **250**, such as the magnetic couplers depicted in FIGS. 7A-7C. In this embodiment, the portion of the magnetic coupler **250** thermally coupled to the second pigtail connector **218** is affixed in an aperture in the side rail **126** and the portion of the magnetic coupler **250** thermally coupled to the pigtail connector **216** may be removably positioned in the aperture to facilitate coupling and decoupling the thermally conductive core portion **200** (and hence the support pad **130**) to and from the side rail **126**.

In the embodiment depicted in FIG. 9, the thermally conductive fibers **220** of the second pigtail connector **218** are loosely bundled and suspended within the interior channel **180** to facilitate the circulation of output fluid **402** from the blower **400** around and through the thermally conductive fibers **220**. In this regard, the thermally conductive fibers **220** are thermally coupled to a cooling source, specifically the blower **400**, with the output fluid **402** directed through the side rail **126**. Specifically, the blower **400** draws in feed fluid **404** (e.g., air, schematically depicted by a block arrow) and outputs output fluid **402** to create a flow of fluid through the side rail **126**. As the output fluid **402** passes around and through the thermally conductive fibers **220**, heat conducted from the thermally conductive core portion **200** through the pigtail connector **216** and magnetic coupler **250** to the second pigtail connector **218** is dissipated into the interior channel **180** of the side rail **126** by forced convection, thereby cooling at least a portion of the support pad **130**.

While the feed fluid **404** and the output fluid **402** are described as air in the embodiment depicted in FIG. 9, it should be understood that other fluids are possible and contemplated. For example, in some embodiments the feed fluid **404** may be, for example, an inert gas, such as nitrogen. Alternatively, the feed fluid **404** may be a combination of gases. In embodiments, the temperature of the feed fluid **404** may be reduced by conditioning to increase convection and hence, increase the extraction of heat from the support pad **130**. In such embodiments, the temperature of the feed fluid **404** may be conditioned by passing the input fluid over or through dry ice such that the feed fluid **404** is a mixture of,

for example, atmospheric air and CO₂ or nitrogen and CO₂. As another example, the feed fluid 404 may be conditioned by injecting liquid nitrogen into the feed fluid 404 such that the feed fluid 404 is a mixture of, for example, atmospheric air and N₂ vapor or nitrogen and N₂ vapor.

In still other embodiments, the temperature of the input air may be increased to reduce convection and, hence, reduce the extraction of heat from the support pad 130. For example, in embodiments, the feed fluid 404 may be passed over or through a heater, such as an electrical resistance heater or the like, which increases the temperature of the feed fluid 404 and reduces the convection of heat from the thermally conductive fibers 220.

In still other embodiments, the convection of heat from the thermally conductive fibers 220 may be controlled by controlling the volume of output fluid 402 flowing through the interior channel 180 of the side rail 126. For example, when more heat extraction from the thermally conductive fibers is desired (i.e., when more cooling of the support pad 130 is desired), the volume of output fluid 402 directed through the interior channel 180 of the side rail 126 may be increased, by, for example, increasing the rotational velocity of the blower 400. Conversely, when less heat extraction from the thermally conductive fibers is desired (i.e., when less cooling of the support pad 130 is desired), the volume of output fluid 402 directed through the interior channel 180 of the side rail 126 may be decreased, by, for example, decreasing the rotational velocity of the blower 400.

While FIG. 9 schematically depicts the thermally conductive fibers 220 being loosely bundled and suspended in the interior channel 180, it should be understood that other embodiments are contemplated and possible. For example, in embodiments, the thermally conductive fibers 220 may be thermally coupled to the output fluid 402 from the blower 400 using a coupler as depicted in FIG. 8. In this embodiment, the coupler provides increased surface area over which the output fluid 402 may be directed to facilitate forced convection of heat from the thermally conductive fibers 220.

While the feed fluid 404 has been described herein as being a gas directed through the interior channel 180 of the side rail 126, it should be understood that other embodiments are contemplated and possible. For example, in an alternative embodiment, the feed fluid may be a liquid, such as water, liquid nitrogen, or a coolant, directed through the interior channel 180 of the side rail 126 with a pump rather than a blower.

While FIG. 9 schematically depicts a support pad 130 with a thermally conductive core portion 200 as depicted in FIG. 4A, it should be understood that other configurations of the support pad 130 are also contemplated and possible including, without limitation, the configuration of the support pad 130 depicted in FIG. 6.

Referring now to FIGS. 4B and 10, FIG. 10 schematically depicts one embodiment of a cross-section of the side rail 126 and the support pad 130 of FIG. 4B in which the side rail 126 contains a cooling source. In this embodiment, the cooling source comprises a thermoelectric cooler 420, such as a Peltier cooler, disposed within the interior channel 180 of the side rail 126. While FIG. 9 depicts the thermoelectric cooler 420 positioned within the interior channel 180, it should be understood that other configurations are contemplated and possible, including configurations in which the thermoelectric cooler 420 is located external to the side rail 126, such as when the thermoelectric cooler 420 is mounted external to the side rail 126, such as at an opening of the interior channel 180 at an end of the side rail 126. Altern-

tively, the thermoelectric cooler 420 may be positioned within the support pad 130, specifically in areas of the support pad 130 outside of the thermally conductive core portion 200 and/or where radiolucency of the support pad 130 is not a consideration.

In this embodiment, the support pad 130 includes a thermally conductive core portion 200 as depicted in FIG. 4B. However, it should be understood that, in an alternative embodiment, the thermally conductive core portion 200 may be similar to the thermally conductive core portion depicted in FIG. 4A. In this embodiment, the pigtail connector 216 of the support pad 130 is thermally coupled to a second pigtail connector 218 with a magnetic coupler 250, such as the magnetic couplers depicted in FIGS. 7A-7C. In this embodiment, the portion of the magnetic coupler 250 thermally coupled to the second pigtail connector 218 is affixed in an aperture in the side rail 126 and the portion of the magnetic coupler 250 thermally coupled to the pigtail connector 216 may be removably positioned in the aperture to facilitate coupling and decoupling the thermally conductive core portion 200 (and hence the support pad 130) from the side rail 126.

In the embodiment depicted in FIG. 10, the thermally conductive fibers 220 of the second pigtail connector 218 are loosely bundled and directly coupled across the surface of the cooling plate 422 of the thermoelectric cooler 420 to facilitate conducting heat through the thermally conductive fibers 220 of the second pigtail connector 218. In this regard, the thermally conductive fibers 220 of the second pigtail connector 218 are thermally coupled to a cooling source, specifically the cooling plate 422 of the thermoelectric cooler 420. Specifically, when the thermoelectric cooler 420 is powered on, a temperature differential is created between the cooling plate 422 and the heating plate 424 of the thermoelectric cooler 420 resulting in heat input into the cooling plate 422 being pumped to the heating plate 424 where it may be dissipated. For example, in some embodiments, the heating plate 424 of the thermoelectric cooler 420 includes cooling fins 426 to aid in the dissipation of heat from the heating plate 424. The heat may be dissipated by, for example, radiation or a combination of radiation and convection, such as when a fan or blower is used to direct heat over the cooling fins 426. Accordingly, it should be understood that, in some embodiments, the thermoelectric cooler 420 may further include a fan or blower (not depicted) to assist with the dissipation of heat from the heating plate 424.

While FIG. 10 schematically depicts the thermally conductive fibers 220 of the second pigtail connector 218 directly coupled to the cooling plate 422 of the thermoelectric cooler 420, it should be understood that other embodiments are contemplated and possible. For example, a magnetic coupler, similar to the magnetic couplers depicted in FIGS. 7A-7C, may be utilized to couple the second pigtail connector 218 to the cooling plate 422 of the thermoelectric cooler 420. Alternatively, a coupler 260 as depicted in FIG. 8 may be utilized to couple the second pigtail connector 218 to the cooling plate 422 of the thermoelectric cooler 420. In this embodiment, the second pigtail connector 218 may be sandwiched between the platens 262a, 262b of the coupler 260 and one of the platens 262a, 262b may be attached to the cooling plate 422 of the thermoelectric cooler 420.

In operation, heat conducted from the thermally conductive core portion 200 of the support pad 130 is conducted through the pigtail connector 216 and magnetic coupler 250 to the second pigtail connector 218. This heat is then conducted through the thermally conductive fibers of the

second pigtail connector **218** into the cooling plate **422** of the thermoelectric cooler and pumped to the heating plate **424** of the thermoelectric cooler **420** and, thereafter, dissipated. The flow of heat from the thermally conductive core portion **200** of the support pad **130** to the heating plate **424** of the thermoelectric cooler **420** results in cooling of at least a portion of the support pad **130**.

In the embodiment depicted in FIG. **10**, the amount of heat extracted from the support pad **130** may be controlled by, for example, adjusting the input voltage and/or current into the thermoelectric cooler **420**.

While FIG. **10** schematically depicts a support pad **130** with a thermally conductive core portion **200** as depicted in FIG. **4B**, it should be understood that other configurations of the support pad **130** are also contemplated and possible including, without limitation, the configuration of the support pad **130** depicted in FIG. **6**.

Further, while FIG. **10** depicts a single thermoelectric cooler **420**, it should be understood that other embodiments are contemplated and possible. Referring to FIG. **11** and FIG. **8** by way of example, FIG. **11** schematically depicts one embodiment of a cross-section of the side rail **126** and support pad **130** similar to FIG. **10**. However, in this embodiment, the side rail **126** includes a first thermoelectric cooler **420a** and second thermoelectric cooler **420b** disposed within the interior channel **180** of the side rail **126**. In this embodiment, the pigtail connector **216** of the support pad **130** is thermally coupled to the first thermoelectric cooler **420a** and the second thermoelectric cooler **420b** with a coupler **260**, such as the coupler **260** depicted in FIG. **8**. Specifically, the thermally conductive fibers (not depicted) of the pigtail connector **216** are sandwiched between the platens **262a**, **262b** of the coupler **260**, as depicted in FIG. **8**, and the platens, **262a**, **262b** are, in turn, thermally coupled to the cooling plates **422a**, **422b** of the first thermoelectric cooler **420a** and the second thermoelectric cooler **420b**, respectively.

In operation, heat conducted from the thermally conductive core portion **200** of the support pad **130** is conducted through the pigtail connector **216** and to the platens **262a**, **262b** of the coupler **260**. The heat is then conducted through the platens **262a**, **262b** of the coupler **260** and into the cooling plates **422a**, **422b** of the first thermoelectric cooler **420a** and the second thermoelectric cooler **420b**, respectively. The heat is then and pumped to the heating plates **424a**, **424b** of the first thermoelectric cooler **420a** and the second thermoelectric cooler **420b**, respectively and, thereafter, dissipated. The flow of heat from the thermally conductive core portion **200** of the support pad **130** to the heating plates **424a**, **424b** of the first thermoelectric cooler **420a** and the second thermoelectric cooler **420b** results in cooling of at least a portion of the support pad **130**. Moreover, use of multiple thermoelectric coolers **420a**, **420b** increases the amount of heat that can be extracted from the thermally conductive core portion **200** and, thus, the amount of cooling provided by the support pad **130**.

While FIG. **11** schematically depicts a support pad **130** with a thermally conductive core portion **200** as depicted in FIG. **4B**, it should be understood that other configurations of the support pad **130** are also contemplated and possible including, without limitation, the configuration of the support pad **130** depicted in FIG. **6**.

Referring now to FIGS. **4B** and **12**, FIG. **12** schematically depicts one embodiment of a cross-section of the side rail **126** and support pad **130** of FIG. **4B** in which the side rail **126** contains a cooling source. In this embodiment, the cooling source comprises a canister **480** containing ther-

mally absorptive material **482**. The canister **480** is disposed within the interior channel **180** of the side rail **126**. In the embodiment depicted in FIG. **12**, the canister **480** may be constructed from a thermally conductive metal, such as, without limitation, copper or a copper alloy. The thermally absorptive material **482** contained in the canister **480** may include, without limitation, phase change materials, oils having relatively high heat capacities, dry ice, water ice, liquid nitrogen or the like. Suitable phase change materials include, without limitation, alkanes having a melting temperature greater than or equal to about 5° C. and less than or equal to about 35° C. Examples of suitable alkanes include, without limitation, tetradecane, pentadecane, hexadecane, heptadecane, octadecane, and nonadecane. Suitable high heat capacity oils include, without limitation, mineral oils, silicon oils, fluorocarbon oils, and the like. In embodiments, the canister **480** may be formed with a canister coupler **486** to enable the canister **480** and, more specifically, the thermally absorptive material **482** within the canister **480**, to be thermally coupled to the thermally conductive core portion **200** of the support pad **130**. In embodiments, the canister coupler **486** may be, for example, a slot configured to receive a corresponding connector, such as coupler **260** depicted in FIG. **8**.

While FIG. **12** depicts the canister **480** as being located within the side rail **126**, it should be understood that other embodiments are contemplated and possible, such as embodiments where the canister **480** is mounted external to the side rail **126**.

In the embodiment depicted in FIG. **12**, the support pad **130** includes a thermally conductive core portion **200** as depicted in FIG. **4B**. However, it should be understood that, in an alternative embodiment, the thermally conductive core portion **200** may be similar to the thermally conductive core portion depicted in FIG. **4A**. In this embodiment, the pigtail connector **216** of the support pad **130** is thermally coupled to a second pigtail connector **218** with magnetic coupler **250**, such as the magnetic couplers depicted in FIGS. **7A-7C**. In this embodiment, the portion of the magnetic coupler **250** thermally coupled to the second pigtail connector **218** is affixed in an aperture in the side rail **126** and the portion of the magnetic coupler **250** thermally coupled to the pigtail connector **216** may be removably positioned in the aperture to facilitate coupling and decoupling the thermally conductive core portion **200** (and hence the support pad **130**) from the side rail **126**.

A coupler **260**, such as the coupler **260** depicted in FIG. **8**, may be utilized to couple the second pigtail connector **218** to the canister coupler **486** of the canister **480**. Specifically, the second pigtail connector **218** may be sandwiched between the platens **262a**, **262b** of the coupler **260**. The coupler **260** is, itself, mechanically coupled to a bracket **484** disposed in the interior channel **180** of the side rail **126**. The canister **480** may be removably coupled to the coupler **260** by positioning the canister **480** in the interior channel **180** of the side rail such that the canister coupler **486** is engaged with the coupler **260** positioned in the side rail **126**.

In operation, heat conducted from the thermally conductive core portion **200** of the support pad **130** is conducted through the pigtail connector **216** and magnetic coupler **250** to the second pigtail connector **218**. This heat is then conducted through the thermally conductive fibers of the second pigtail connector **218** into the platens **262a**, **262b** (FIG. **8**) of the coupler **260**. The heat is conducted from the platens **262a**, **262b** of the coupler **260** into the thermally absorptive material **482** of the canister **480** where it is absorbed. The flow of heat from the thermally conductive

core portion **200** of the support pad **130** to the thermally absorptive material **482** of the canister results in cooling of at least a portion of the support pad **130**.

In embodiments, heat conduction from the support pad **130** to the thermally absorptive material **482** may continue until the heat capacity of the thermally absorptive material **482** is reached and/or an equilibrium temperature is reached between the thermally absorptive material **482** and the support pad **130**, more specifically, a subject positioned on the support pad **130**. When this occurs, and further cooling is desired, the canister **480** may be removed and replaced with a fresh canister of thermally absorptive material to continue the conduction of heat from the support pad **130**.

While FIG. **12** schematically depicts a support pad **130** with a thermally conductive core portion **200** as depicted in FIG. **4B**, it should be understood that other configurations of the support pad **130** are also contemplated and possible including, without limitation, the configuration of the support pad **130** depicted in FIG. **6**.

Referring again to FIGS. **1**, **2**, **6**, and **13** in some embodiments, the support pad **130** of FIG. **6** may be coupled to the longitudinal frame **125** with one or more clamps **135**. In some embodiments, each support pad **130** may be coupled to the longitudinal frame **125** via a plurality of clamps. More particularly, FIG. **13** depicts a cross-section along the line A-A of FIG. **1**. As shown in FIG. **13**, the support pad **130** includes a clamp **135** that is coupled to the first side rail **126** and a clamp **135** that is coupled to the second side rail **127**. The clamps **135** may be coupled such that they are slidably movable along a length of the respective side rails **126**, **127**. Accordingly, it should be understood that the clamps **135** (and the support pad **130** coupled thereto) are repositionable along the length of the longitudinal frame **125**. In addition, the clamps **135** may be coupled to respective side rails **126**, **127** such that the clamps **135** retain the support pad **130** on the respective side rails **126**, **127**. In some embodiments, the clamps **135** may be spaced in pairs such that a clamp **135** is positioned in a first location on the first side rail **126** and a second clamp **135** is positioned in a second location on the second side rail **127**, where the first and second locations are parallel and opposing each other at an equal distance from the head column **122** and the foot column **124**. In some embodiments, the clamps **135** may be positioned at a location on the respective side rail **126**, **127** that contains a quick disconnect slot **190** such that each of the clamps **135** are engaged and/or aligned with a corresponding quick disconnect slot **190**.

The clamps **135** are coupled to the respective side rails **126**, **127** via one or more clamping features. For example, as shown in FIG. **13**, the clamp **135** may be a "C" shaped clamp having an opening **155** and one or more lips **158** that extend towards the opening **155** in the "C" shape. As such, the clamp **135** receives the side rail **126**, **127** by allowing the side rail **126**, **127** to pass through the opening **155**. In addition, once the clamp **135** is arranged around the side rail **126**, **127**, the one or more lips **158** prevent the clamp **135** from slipping off of the side rail **126**, **127**. In this embodiment, the clamps may be formed from a material which is elastically deformable and recoverable, such as a polymeric material or the like, to facilitate attaching the clamp to a respective side rail.

Alternatively, the clamp **135** may have a first clamp portion and a second clamp portion that is separate from the first clamp portion. In such embodiments, the first clamp portion may be attachable to the second clamp portion with the side rail **126**, **127** enclosed within the clamp **135**. The first clamp portion may be secured to the second clamp

portion via one or more attachment devices, such as threaded fasteners, clips or the like. In other embodiments, the first clamp portion may be partially attached to the second clamp portion via a clamp hinge such that the first clamp portion and the second clamp portion can be brought together around the side rail by rotating the second clamp portion about a clamp hinge from an open position to a closed position. In some embodiments, the first clamp portion may be further secured to the second clamp portion via one or more attachment devices including, without limitation, threaded fasteners, clips, latches or the like.

Still referring to FIG. **13**, the longitudinal frame **125**, particularly the first side rail **126** and the second side rail **127**, may each include one or more quick disconnect slots **190**. In some embodiments, a plurality of the quick disconnect slots **190** may be spaced at particular locations along the length of each side rail **126**, **127**. In some embodiments, the quick disconnect slots **190** may be spaced in pairs such that a first quick disconnect slot **190** is positioned in a first location on the first side rail **126** and a second quick disconnect slot **190** is positioned in a second location on the second side rail **127**, where the first and second locations are parallel and opposing each other at an equal distance from the head column **122** and the foot column **124**.

The quick disconnect slots **190** facilitate inserting the pigtail connector **216** of the support pad **130** into the side rail **126**, **127** such that a cooling fluid may be directed over and through the thermally conductive fibers **220** of the pigtail connector **216**, in a similar manner as depicted and described herein with respect to FIG. **9**, thereby dissipating heat from the thermally conductive element **308** of the support pad **130**. For example, in various embodiments, in addition to the removal of heat from the person support surface **310** via convection through the thermally conductive element **308**, heat may be dissipated from the person support surface **310** by conducting the heat through the pigtail connector **216** into the side rail **127** where a cooling fluid (i.e., output fluid **402**), such as a gas or the like, is directed around and through the thermally conductive fibers **220** of the pigtail connector **216**. In such embodiments, the conduction may be coupled with convection enhance the removal of heat from the source region such as when the thermally conductive element **308** is thermally coupled to a cooling fluid. For example, as shown in FIG. **13**, the thermally conductive element **308** is coupled to the side rail **127** of the longitudinal frame **125** via the quick disconnect slot **190** and the pigtail connector **216**. More particularly, the pigtail connector **216** from the thermally conductive element **308** may be threaded through a slot in the clamp **135** and through the quick disconnect slot **190** such that the thermally conductive fibers **220** of the pigtail connector **216** are in communication with the inside of the side rail **127** and, more particularly, with a cooling fluid flowing through the side rail **127**.

In embodiments in which conduction is used in conjunction with convection to dissipate heat from the support pad **130**, the thermally conductive element **308** draws heat away from the source region and directs the heat into one or both of the side rails **126**, **127** with one or more pigtail connectors **216**. The side rails **126**, **127** are coupled to a cooling source **140** (shown in FIG. **1**) that provides a cooling fluid to the side rails **126**, **127**. The cooling source **140** may include, by way of example and not limitation, a pump or fan to direct cooling fluid through the side rails **126**, **127**, as shown and described herein with respect to FIG. **9**. The cooling fluid absorbs the heat from the thermally conductive fibers **220** of the pigtail connector **216** and carries the heat through the side rails **126**, **127**, away from the person support surface

310, where it may be dissipated in a heat exchanger and/or exhausted to the environment. In some embodiments, the cooling source 140 may provide the cooling fluid directly through the side rails 126, 127, although in other embodiments, the cooling fluid may be contained within a conduit, such as a tube or pipe running through the side rails 126, 127. A conduit may enable the quick disconnect slots 190 to provide cooling features in addition to one or more of electrical lines, pneumatic lines, and/or hydraulic lines via the longitudinal frame 125.

The cooling fluid may be any suitable gas or liquid, as described herein with respect to FIG. 9. For example and without limitation, in various embodiments, the cooling fluid may be air, water, or another fluid composition that has high thermal capacity. According to various embodiments, the cooling fluid is pumped into the side rail 126, 127 at a temperature from about 15.5° C. to about 32° C. The temperature of the cooling fluid may vary depending on the particular embodiment. For example, the temperature of the cooling fluid may be adjusted to achieve a particular temperature at the person support surface 310 of the support pad 130. As a result of the cooling fluid, the removal of heat from the thermally conductive element 308 may be enhanced, which in turn may increase the temperature gradient between the source region and the sink region and further enhance cooling of the person support surface 310 of the support pad 130.

Still referring to FIG. 13, when a subject is supported on the person support surface 310, the thermally conductive element 308 draws the heat from the person support surface 310 and directs the heat (via conduction) to the edges of the support pad 130. In the embodiment depicted in FIG. 13, the heat may be directed through the thermally conductive element 308 around the edges of the support pad 130. The pigtail connector 216 may conduct the heat from the thermally conductive element 308 through the slots in the clamps 135, and into the quick disconnect slots 190 positioned in the side rails 126, 127. Cooling fluid passing through the side rails 126, 127 then removes the heat via convection through the side rails 126, 127 and out to the environment or through an exhaust (not shown).

Referring now to FIGS. 1, 3, 14 and 15, in some embodiments described herein, the person support system 100, 101 may further include a control unit 500. FIG. 14 schematically depicts one embodiment of a control unit 500 and FIG. 15 schematically depicts the interconnectivity of various parts of the control unit 500 as well as components communicatively coupled to the control unit 500. In embodiments, the control unit 500 may be used to achieve a desired amount of cooling with a support pad comprising a thermally conductive core portion, including, without limitation, when the thermally conductive core portion is thermally coupled to a cooling source, as described with respect to FIGS. 9, 10, 11, and 13. However, it should be understood that the control unit 500 may also be used to assist in achieving a desired amount of cooling with support pads having thermally conductive core portions which are not thermally coupled to a cooling source.

The control unit 500 may be, by way of example and not limitation, a computing device that includes a microcontroller 501 communicatively coupled to a display device 504. The microcontroller 501 may include a processor 508 that is communicatively coupled to a non-transitory memory 510 storing computer-readable and executable instructions, which, when executed by the processor, facilitate cooling of a thermally conductive core portion of a support pad 130 of the person support system 100, 101. That is, in embodi-

ments, when the computer-readable and executable instructions are executed by the processor 508, the control unit 500 regulates the temperature of at least a portion of the top surface of a support pad 130 of the person support system 100, 101. In some embodiments, the control unit 500 may enable user, such as a caregiver, to manually adjust the cooling of the support pad 130, as will be described further herein.

In embodiments, the control unit 500 may include a temperature sensor 502 communicatively coupled to the microcontroller 501. The temperature sensor 502 outputs a signal (i.e., a temperature signal) indicative of the temperature of an object on which it is positioned. In embodiments, the temperature sensor 502 may be communicatively coupled to the microcontroller 501 with wires or, alternatively, wirelessly, such as when the temperature sensor 502 includes an RF transmitter (or transceiver) for transmitting the temperature signal from the temperature sensor 502 and the microcontroller 501 includes an RF receiver (or transceiver) for receiving the temperature signal from the temperature sensor 502.

In embodiments, the temperature sensor 502 may be positioned on the surface of a support pad 130 in an area corresponding to an area of a subject (e.g., the sacral area, the scapular areas, buttocks, heels or the like) to be cooled when the subject is positioned on the support pad 130. The temperature sensor 502 may be positioned to detect either the temperature of the skin of the subject or the temperature of the surface of the support pad 130, which may be similar to the temperature of the skin of the subject. Alternatively, the temperature sensor 502 may be embedded in the person support pad 130, such as in a thermally conductive core portion of the support pad 130, such that the temperature sensor 502 is positioned to detect a temperature of the thermally conductive core portion. In still other embodiments, the temperature sensor 502 may be positioned directly on the skin of the subject, such as in the sacral area, scapular area, buttocks, heels or the like, and held in place with, for example, adhesive or a dressing. In yet other embodiments, the temperature sensor 502 may be positioned in a garment worn by the subject, such as a hospital gown, undergarment, pants, or the like. In embodiments, the temperature signal provided by the temperature sensor 502 to the microcontroller 501 may be used, for example and without limitation, to control the cooling provided by the thermally conductive core portions of the support pad 130, determine proper positioning of the subject with respect to the thermally conductive core portions of the support pad 130, determine if a cooling device is functioning properly and/or providing sufficient cooling, determine if a thermally conductive core portion should be replaced to provide better cooling, and/or combinations thereof.

Still referring to FIGS. 1, 3, 14, and 15, in embodiments, the control unit 500 may optionally include an RFID reader 512 communicatively coupled to the microcontroller 501. In embodiments, the RFID reader 512 may be used to identify various accessories associated with the person support system 100, 101 and/or a subject positioned on the person support system 100, 101, which accessories may influence the cooling of the subject with the support pad(s) 130 of the person support system 100, 101. In embodiments, the RFID reader 512 outputs a signal (i.e., an accessory identification signal) indicative of an identity of an accessory being used in conjunction with the person support system 100, 101. For example, in embodiments, a sheet, pillow, or blanket (i.e., linens) being used on the person support system 100, 101 may include an RFID tag 514 encoded with the identity of

the sheet or blanket. Similarly, garments (e.g., the gown, pants, shirt, undergarment, socks, dressings, patches (i.e., a sacral patch) or the like) worn by the patient may include an RFID tag **514** encoded with the identity of the garment. As another example, any pads or cushions, such as incontinence pads or the like, used in conjunction with the support pads **130** of the person support system **100**, **101** and/or a subject positioned on the support pads **130**, may include an RFID tag **514** encoded with the identity of the pad or cushion. In the specific example, depicted in FIG. **15**, the accessory **590** is a hospital gown which includes an RFID tag **514** encoded with the identity of the hospital gown. The RFID reader detects the accessory **590** with RFID tag **514**, interrogates the RFID tag **514**, and outputs an accessory identification signal which, in this embodiment, indicates that the accessory **590** is a hospital gown. In embodiments, the RFID tag **514** may also be encoded with information related to the insulating properties of the accessories, which information may be encoded as a party of the identity of the accessory.

In embodiments, the RFID reader **512** may be communicatively coupled to the microcontroller **501** with wires or, alternatively, wirelessly, such as when the RFID reader **512** includes an RF transmitter (or transceiver) for transmitting the accessory identification signal and the microcontroller **501** includes an RF receiver (or transceiver) for receiving the accessory identification signal from the RFID reader **512**.

In embodiments, the control unit **500** may further include an input device **506** communicatively coupled to the microcontroller **501**. The input device **506** may be used to input data, operating parameters, and the like into the control unit **500**. In embodiments, the input device **506** may be a conventional input device such as a keyboard, mouse, track pad, stylus or the like. In embodiments, the input device **506** may be communicatively coupled to the microcontroller **501** with wires or, alternatively, wirelessly, such as when the input device **506** includes an RF transmitter (or transceiver) for transmitting an input signal and the microcontroller **501** includes an RF receiver (or transceiver) for receiving the input signal from the input device. In embodiments, the input device **506** may be used to, for example, input target cooling temperatures into the control unit **500**, input subject data into the control unit **500**, control the operation of one or more cooling sources operatively connected to the control unit **500**, and the like.

Still referring to FIGS. **14** and **15**, in embodiments, the display device **504** is communicatively coupled to the microcontroller **501** and may be used to display data associated with the person support system **100**, **101** and, more specifically, data related to the cooling of a subject position on the person support system **100**, **101**. In some embodiments, the display device **504** may be a touch screen and, as such, may also be used to input data, operating parameters, and the like, into the control unit **500**. For example, in the embodiment depicted in FIG. **15**, the display device **504** is a touch screen which includes various buttons including up/down arrow keys **520**, **521**, temperature check boxes **522**, **523**, and accessory check boxes **524**, **525**, **526**, **527**. The temperature check boxes **522**, **523** may be used to toggle between the actual temperature (i.e., the temperature measured and indicated by the temperature signal from the temperature sensor **502**) and the target temperature (i.e., the temperature input into the control unit by a user). With regard to the target temperature, up/down arrow keys **520**, **521** may be used to increase or decrease the target temperature and/or scroll to a different temperature setting. The accessory check boxes **524**, **525**, **526**, **527** may be used to

select and/or identify the accessories associated with the subject and/or the person support system **100**, **101**. In the embodiment shown in FIG. **15**, the accessory check boxes **524**, **525**, **526**, **527** are associated with subject-specific accessories (i.e., garments worn by the subject positioned on the person support system **100**, **101** and/or used in conjunction with the subject positioned on the person support system **100**, **101**).

In some embodiments described herein, the microcontroller **501** of the control unit **500** is communicatively coupled to a cooling source, such as the blower **400** (FIG. **9**) and/or a thermoelectric cooler **420** (FIGS. **10** and **11**). In these embodiments, the microcontroller **501** is programmed to output a control signal to operate the blower **400** and/or the thermoelectric cooler **420** based on input received from at least one of the temperature sensor **502**, the RFID reader **512**, the input device **506**, the display device **504**, or various combinations thereof.

For example, in embodiments, computer readable and executable instructions stored in the non-transitory memory cause the control unit to receive a temperature signal from the temperature sensor indicative of a measured temperature of the skin of a subject at a specific area or, alternatively, a measured temperature of a surface of the support pad. Thereafter, the control unit compares the measured temperature to a target temperature. If the measured temperature is not equal to the target temperature, the control unit outputs a control signal that adjusts an operating parameter of the cooling source, thereby increasing or decreasing cooling of the subject and/or support pad until the measured temperature is equal to the target temperature.

For example and without limitation, when the cooling source is a blower **400** as depicted in FIG. **9** and the microcontroller **501** of the control unit **500** determines that the temperature of a subject (i.e., the temperature of a specific portion of the skin of a subject or the temperature of the surface of the support pad on which the subject is positioned) measured with the temperature sensor **502** (i.e., the measured temperature or the actual temperature) is greater than a target temperature which may, in embodiments, be input in the control unit **500** through the display device **504** and/or the input device **506**, the microcontroller **501** sends a signal to the blower **400** to increase the rotational speed of the blower **400** thereby increasing the flow of output fluid through the side rail **126** and increasing the extraction of heat from the top surface of the support pad **130** through the thermally conductive core portion **200**.

Conversely, when the microcontroller **501** of the control unit **500** determines that the temperature of the subject (i.e., the temperature of a specific portion of the skin of a subject or the temperature of the surface of the support pad on which the subject is positioned) measured with the temperature sensor **502** (i.e., the measured temperature or the actual temperature) is less than the target temperature, the microcontroller **501** sends a signal to the blower **400** to decrease the rotational speed of the blower **400** thereby decreasing the flow of output fluid through the side rail **126** and decreasing the extraction of heat from the top surface of the support pad **130** through the thermally conductive core portion **200**.

Alternatively, when the cooling source is a thermoelectric cooler **420** as depicted in FIG. **10** and the microcontroller **501** of the control unit **500** determines that the temperature of the subject (i.e., the temperature of a specific portion of the skin of a subject or the temperature of the surface of the support pad on which the subject is positioned) measured with the temperature sensor **502** (i.e., the measured temperature or the actual temperature) is less than a target

temperature, the microcontroller **501** reduces the current and/or voltage supplied to the thermoelectric cooler **420** thereby decreasing the flow of heat through the thermoelectric cooler **420** from the cooling plate **422** to the heating plate **424** and decreasing the extraction of heat from the top surface of the support pad **130** through the thermally conductive core portion **200**.

Conversely, when the microcontroller **501** of the control unit **500** determines that the temperature of the subject (i.e., the temperature of a specific portion of the skin of a subject or the temperature of the surface of the support pad on which the subject is positioned) measured with the temperature sensor **502** (i.e., the measured temperature or the actual temperature) is greater than a target temperature, the microcontroller **501** increases the current and/or voltage supplied to the thermoelectric cooler **420** thereby increasing the flow of heat through the thermoelectric cooler **420** from the cooling plate **422** to the heating plate **424** and increasing the extraction of heat from the top surface of the support pad **130** through the thermally conductive core portion **200**.

In some embodiments, temperature measured with the temperature sensor **502** may be used to determine if a subject is appropriately positioned on the support pad **130** to facilitate effective cooling of a specific area of the subject. For example, in one embodiment, the actual temperature measured with the temperature sensor being relatively high when the temperature sensor **502** is applied directly to the skin of the subject may indicate that the subject is not properly positioned on the thermally conductive core portion of the support pad **130** (i.e., proper cooling is not taking place). Alternatively, the actual temperature measured with the temperature sensor **502** being at or above normal body temperature may indicate that insufficient cooling is occurring and that the cooling source should be adjusted (when present) or the thermally absorptive materials (i.e., PCMs or the like) exchanged or replaced (i.e., the cooling capacity of the materials is diminished or insufficient).

In embodiments where the thermally conductive core portion is thermally coupled to a passive cooling source such as the canister **480** containing thermally absorptive material **482** as depicted in FIG. 12, or the thermally conductive core portion **200** consists primarily of phase change material as depicted, for example, in FIG. 5A, the control unit **500** may be utilized to determine the proper thermally absorptive material for the canister **480** or thermally conductive core portion **200** for achieving the target temperature based on factors such as, for example and without limitation, the desired target temperature and the weight of the subject. For example, the non-transitory memory **510** of the control unit **500** may contain a look-up-table (LUT) of thermally absorptive materials (e.g., phase change materials, oils, coolant, etc.) that are indexed according to such factors as the target temperature and the weight of the subject. That is, the thermally absorptive materials may be indexed according to the target temperature which they are capable of achieving. In these embodiments, an operator may input the target temperature and the weight of the subject into the control unit **500** through the input device **506** or the display device **504**. The processor **508** of the microcontroller **501** compares the input factors to the LUT of thermally absorptive materials and outputs to the display device one or more materials that may be used to reach the desired target temperature. While target temperature and weight of the subject have been provided as examples of factors that may be used to determine the appropriate thermally absorptive materials, it should be understood that other factors are contemplated and possible including, without limitation, the location of cool-

ing (e.g., the sacral area, the scapular areas, buttocks, heels or the like), the ambient temperature, the length of the procedure, the material from which the support pad is formed, the type of accessories associated with the subject positioned on the person support system, and/or various combinations thereof.

For example, the control unit **500** may take into account variables that may adversely impact cooling, such as the presence of accessories **590** (e.g., linens, garments, and the like) in use with the person support system **100**, **101** and/or subject which may have an insulating effect. Specifically, any accessories **590** which may be positioned between the skin of the subject and the surface of the support pad(s) may have an insulating effect which diminishes cooling. In this embodiment, the control unit **500** may take into account any accessories **590** being used in conjunction with the person support system **100**, **101** and/or the subject positioned on the person support system **100**, **101** together with a desired target temperature input in the control unit by a user and adjust either the target temperature and/or the recommended thermally absorptive materials to account for the insulating effects of any accessories **590** that are present.

For example, in embodiments where the thermally conductive core portion is thermally coupled to a cooling source such as the canister **480** containing thermally absorptive material **482** as depicted in FIG. 12, or the thermally conductive core portion **200** consisting primarily of phase change material as depicted, for example, in FIG. 5A, the control unit **500** may be utilized to determine the proper thermally absorptive material for the canister **480** or the thermally conductive core portion **200** for achieving the desired target temperature based on the desired target temperature and any accessories **590** that may be present. Specifically, a user may input the desired target temperature into the control unit **500** with the input device **506** or the display device **504**. The target temperature may be displayed with the display device **504**. A user may then input the identity of any accessories **590** that are present using either the input device **506** or the display device **504**. Alternatively, the RFID reader **512** may be used to automatically detect the identity of any accessories **590** which include an RFID tag **514**. Regardless of the input method, a list of the accessories **590** present may be displayed with the display device **504**. In this embodiment the non-transitory memory **510** of the control unit **500** may contain a look-up-table (LUT) of thermally absorptive materials (e.g., phase change materials, oils, coolant, etc.) that are indexed according to the desired target temperature and the identity and insulating properties of various accessories. For example, the LUT may contain a list of thermally absorptive materials and each material may be associated with a combination of insulating properties of various accessories or combinations of accessories and correlated to a target temperature which may be achieved with the thermally absorptive material when the specified accessories are present. The processor **508** of the microcontroller **501** compares the input factors (i.e., the desired target temperature and the identified accessories) to the LUT of thermally absorptive materials and outputs one or more recommended thermally absorptive materials to the display device **504** that may be used to reach the desired target temperature at the surface of the skin in the presence of the identified accessories and/or provide a recommended time schedule for replacing the thermally absorptive material in order to achieve the desired target temperature. Alternatively, the non-transitory memory **510** of the microcontroller **501** may use an algorithm to identify one or more recommended thermally absorptive materials and/or recom-

mended time schedules for replacing the thermally absorptive materials in order to reach the desired target temperature based on the input target temperature and the insulating properties of the identified accessories **590**.

For example and without limitation, when the accessory **590** is an incontinence pad, the incontinence pad may provide thermal insulation to the skin of the subject thereby requiring additional cooling to reach the desired target temperature at the surface of the skin. Accordingly, a greater amount of heat withdrawal capacity may be necessary to reach the desired target temperature than in if the incontinence pad were not present. In this example, the control unit utilizes the identity of the accessory **590** in conjunction with the target temperature to determine a recommended thermally absorptive material and/or a recommended time schedule for replacing the thermally absorptive material in order to achieve the desired target temperature.

As another example, in embodiments where the thermally conductive core portion of the support pad **130** is thermally coupled to a cooling source, such as the blower **400** (FIG. 9) and/or a thermoelectric cooler **420** (FIGS. 10 and 11), and the microcontroller **501** is programmed to output a control signal to the cooling source to regulate cooling of the support pad **130**, the control unit **500** may be utilized to adjust the target temperature to account for the insulating effect of any accessories **590** that may be present. Specifically, a user may input the desired target temperature into the control unit **500** with the input device **506** or the display device **504**. The desired target temperature may be displayed with the display device **504**. A user may then input the identity of any accessories **590** that are present using either the input device **506** or the display device **504**. Alternatively, the RFID reader **512** may be used to automatically detect the identity of any accessories **590** which include an RFID tag **514**. Regardless of the input method, a list of the accessories **590** present may be displayed with the display device **504**. In this embodiment the non-transitory memory **510** of the control unit **500** may contain a look-up-table (LUT) of adjusted target temperatures that are indexed according to the desired target temperature and the identity and insulating properties of various combinations of accessories. For example, the LUT contains a list of adjusted target temperatures associated with one or more target temperatures and a corresponding accessory or combination of accessory. The adjusted target temperature is the actual temperature set point which may be utilized to obtain the desired target temperature at the surface of the skin in the presence of the identified accessories. The processor **508** of the microcontroller **501** compares the input factors (i.e., the desired target temperature and the identified accessories) to the LUT of adjusted target temperatures and outputs an adjusted target temperature to the display device **504** that may be used to reach the desired target temperature at the surface of the skin in the presence of the identified accessories. Alternatively, the non-transitory memory **510** of the microcontroller **501** may use an algorithm to identify an adjusted target temperature in order to reach the target temperature at the surface of the skin based on the input target temperature and the insulating properties of the identified accessories **590**. Thereafter, the microcontroller **501** provides control signals to the cooling source (i.e., the blower **400** and/or thermoelectric cooler **420**) to adjust an operating parameter of the cooling source and thereby achieve the adjusted target temperature at the surface of the accessory (i.e., at the top surface of the support pad) and, in turn, reach the desired target temperature at the surface of the skin. In this embodiment, the control unit **500** may further utilize the tempera-

ture signal from the temperature sensor **502** to control the cooling source in order to both achieve and maintain the adjusted target temperature at the surface of the accessory (i.e., at the top surface of the support pad) and, in turn, the desired target temperature at the surface of the subject's skin by controlled heat extraction through the thermally conductive core portion of the support pad **130**.

For example and without limitation, when the target temperature is 75° F. and the accessory **590** is an incontinence pad, the incontinence pad may provide thermal insulation to the skin of the subject thereby requiring additional cooling to reach the desired target temperature at the surface of the skin. Accordingly, a greater amount of heat withdrawal capacity may be necessary to reach the desired target temperature at the surface of the skin than if the incontinence pad were not present. In this example, the control unit **500** utilizes the identity of the accessory **590** in conjunction with the desired target temperature to determine an adjusted target temperature at the surface of the accessory (i.e., at the surface of the support pad) such that the desired target temperature is reached at the surface of the skin. The control unit **500** then operates the cooling source, in conjunction with the temperature signal from the temperature sensor **502**, to achieve and maintain the adjusted target temperature at the surface of the accessory (i.e., at the surface of the support pad) and, in turn, the desired target temperature at the surface of the subject's skin by controlled heat extraction through the thermally conductive core portion of the support pad **130**.

In embodiments where the target temperature is adjusted to account for the presence of insulating accessories and/or the type of thermally absorptive materials are selected to account for the presence of insulating accessories, the comfort of the patient may be improved by preventing over-cooling. Moreover, the workflow of a user (i.e., a caregiver) may be improved by minimizing the amount of cooling delivered to achieve a specific temperature, thereby decreasing the frequency of user intervention to monitor temperature and/or replace exhausted thermally absorptive materials. Further, by tailoring the operation of the cooling source to deliver only the minimal amount of cooling needed to obtain the desired target temperature may reduce the amount of energy expended on cooling.

Still referring to FIGS. 14 and 15, in embodiments, the control unit **500** may provide a visual indication of the temperature detected by the temperature sensors **502** on the display device **504**, as described herein. For example, the visual indication may be a number displayed on a display device **504** of the control unit **500**, or in the form of a graph. In some embodiments, a user may view the temperature and manually adjust the cooling source using the input device **506** communicatively coupled to the control unit **500**. An adjustment to the cooling source may result in a decrease in the temperature, such as when the adjustment causes an increase in the flow of the fluid through the side rail **126** with the blower **400**, or an increase in the temperature, such as when the adjustment causes a decrease in the flow of the fluid through the side rail **126** with the blower **400**. Similar manual adjustments may be made to increase or decrease the cooling when the cooling source is, for example, a thermoelectric cooler **420**.

In still other embodiments, temperature sensors **502** may be included in the side rails **126**, **127** or, in embodiments including a conduit for the cooling fluid, in the conduit. Accordingly, the control unit **500** may receive temperature readings from within the side rails **127**, **127** in addition to temperature readings from a temperature sensor associated

with the subject and/or the surface of the support pad 130. In such embodiments, the control unit 500 may determine a temperature gradient between the surface of the support pad and the side rails 126, 127. The flow of the cooling fluid may be increased or decreased in order to increase or decrease the temperature gradient and thus achieve a desired cooling rate. The control unit 500 may determine that an adjustment to the flow of the cooling fluid should be made by comparing the determined temperature gradient to a predetermined temperature gradient that is pre-set or set by a user and stored in the non-transitory memory 510.

In some embodiments, the cooling source may be positioned a distance away from the surface of the support pad(s). In some embodiments, the cooling source may be positioned from about 0.5 m to about 3 m from the support pads, from about 0.75 m to about 2 m from the support pads, or from about 1 m to about 1.5 m from the support pads in order to establish a suitable temperature gradient. In embodiments, the cooling source may be positioned proximate a head end of the person support system or the foot end of the person support system. The particular distance between the support pads and the cooling source and location of the cooling source may vary depending on the particular embodiment, provided that the cooling source 140 does not adversely impact the radiolucency of the support pad 130.

Based on the foregoing, it should be understood that the non-transitory memory 510 includes computer readable and executable instructions which, when executed by the processor 508, cause the microcontroller 501 to receive input signals from the temperature sensor 502, RFID reader 512, input device 506, and/or display device 504 and output signals to at least the display device 504 based on the input signals received. In some embodiments, the microcontroller 501 also outputs control signals to a cooling source such as a blower 400 or a thermoelectric cooler 420 to regulate cooling of a support pad 130.

In embodiments described herein, the targeted cooling of at least a portion of a support pad is achieved by conducting heat from the support pad and dissipating that heat with a heat sink, either by conduction, convection, radiation, or combinations thereof. The heat conducted away from the support pad is, effectively, waste heat. In some embodiments of the person support systems described herein, the heat conducted away from the support pad may be recycled and repurposed. For example, in embodiments, the heat conducted away from the support pad may be recycled to warm the subject positioned on the person support system.

Referring to FIG. 16 by way of example, a warming blanket 600 is schematically depicted for use in warming a subject 900 positioned on a support pad 130 of a person support system. In embodiments, the warming blanket 600 may include a sheet portion 602 which includes a flexible conduit 604. For example, the sheet portion 602 may include multiple plies and the flexible conduit 604 may be disposed between two of the plies. As shown in FIG. 16, the flexible conduit 604 may have a serpentine configuration within the sheet portion 602 of the warming blanket 600. In the embodiment of the flexible conduit 604 depicted in FIG. 16, the flexible conduit includes an inlet 606 for receiving a warming fluid 610 (schematically depicted by arrows) and an outlet 608 for expelling the warming fluid 610.

Referring now to FIGS. 16 and 17, the side rail 126 of the person support system may include a thermoelectric cooler 420 thermally coupled to a thermally conductive core portion 200 of the support pad 130, as described herein with respect to FIG. 10. However, in this embodiment, the side rail 126 may further include a frame conduit 622 extending

into the interior channel 180 of the side rail 126. The frame conduit 622 is positioned relative to the heating plate 424 of the thermoelectric cooler 420 and directs a flow of warming fluid 610 across the heating plate 424 and the cooling fins 426 extending from the heating plate 424. In the embodiment shown in FIG. 17, the frame conduit 622 is coupled to a pump 620 which circulates the warming fluid 610 through the frame conduit 622. The frame conduit 622 further includes a frame outlet 624 which is fluidly coupled to the inlet 606 of the warming blanket 600 and a frame inlet which is fluidly coupled to the outlet 608 of the warming blanket 600. Accordingly, it should be understood that, in this embodiment, the flexible conduit 604 of the warming blanket 600 and the frame conduit 622 form a closed loop system.

In embodiments, the warming fluid 610 directed through the flexible conduit 604 and the frame conduit 622 may be, for example, a gas such as, without limitation, air or nitrogen. Alternatively, the warming fluid 610 directed through the flexible conduit 604 and the frame conduit 622 may be, for example, a liquid such as, without limitation, water, mineral oil, or the like.

In operation, the thermoelectric cooler 420 conducts heat from the support pad 130 as described hereinabove with respect to FIG. 10. Simultaneously, the pump 620 pumps the warming fluid 610 through the frame conduit 622 such that the warming fluid 610 contacts the heating plate 424 and cooling fins 426 of the thermoelectric cooler 420, thereby heating the warming fluid 610. The heated warming fluid 610 exits the frame conduit 622 at frame outlet 624 and enters the inlet 606 of the flexible conduit 604 of the warming blanket 600. The warming fluid 610 is circulated through the flexible conduit 604 of the warming blanket 600 and the heat from the warming fluid 610 is transferred to a subject 900 positioned beneath the warming blanket 600 on the support pad 130, thereby warming the subject 900. The warming fluid 610 exits the flexible conduit 604 at the outlet 608 and is re-circulated into the frame inlet 626 of the frame conduit 622 and through the pump 620. In this embodiment, the flexible conduit 604 of the warming blanket receives the warming fluid 610 from the heating plate 424 of the thermoelectric cooler 420 by convection, specifically forced convection.

While a closed loop embodiment of the warming blanket has been described, it should be understood that an open loop embodiment is contemplated and possible. Referring again to FIGS. 16 and 17, in the open loop embodiment, the frame outlet 624 is coupled to the inlet 606 of the flexible conduit 604. However, the frame inlet 626 is coupled to atmosphere (i.e., open) as is the outlet 608 of the flexible conduit 604. In this embodiment the warming fluid 610 may be air.

In operation, the thermoelectric cooler 420 conducts heat from the support pad 130 as described hereinabove with respect to FIG. 10. Simultaneously, the pump 620 draws in warming fluid 610 (i.e., air) through the frame inlet 626 of the frame conduit 622 such that the warming fluid 610 contacts the heating plate 424 and cooling fins 426 of the thermoelectric cooler 420, thereby heating the warming fluid 610. The heated warming fluid 610 exits the frame conduit 622 at frame outlet 624 and enters the inlet 606 of the flexible conduit 604 of the warming blanket 600. The warming fluid 610 is circulated through the flexible conduit 604 of the warming blanket 600 and the heat from the warming fluid 610 is transferred to a subject 900 positioned beneath the warming blanket 600 on the support pad 130, thereby warming the subject 900. The warming fluid 610

exits the flexible conduit **604** at the outlet **608** and is expelled to atmosphere. In this embodiment, the flexible conduit **604** of the warming blanket receives the warming fluid **610** from the heating plate **424** of the thermoelectric cooler **420** by convection, specifically forced convection.

Still referring to FIGS. **16** and **17**, in another open loop embodiment, the frame outlet **624** is coupled to the inlet **606** of the flexible conduit **604**. However, the frame inlet **626** is coupled to atmosphere (i.e., open) and the outlet **608** of the flexible conduit **604** of the warming blanket **600** is plugged. In this embodiment the flexible conduit **604** is perforated along its length between the inlet **606** and the outlet **608**. In this embodiment the warming fluid **610** may be air.

In operation, the thermoelectric cooler **420** conducts heat from the support pad **130** as described hereinabove with respect to FIG. **10**. Simultaneously, the pump **620** draws in warming fluid **610** (i.e., air) through the frame inlet **626** of the frame conduit **622** such that the warming fluid **610** contacts the heating plate **424** and cooling fins **426** of the thermoelectric cooler **420**, thereby heating the warming fluid **610**. The heated warming fluid **610** exits the frame conduit **622** at frame outlet **624** and enters the inlet **606** of the flexible conduit **604** of the warming blanket **600**. The warming fluid **610** is circulated through the flexible conduit **604** of the warming blanket **600**. As the warming fluid **610** is circulated, the warming fluid **610** exits the flexible conduit **604** through the perforations along its length, thereby transferring heat from the warming fluid **610** to a subject **900** positioned beneath the warming blanket **600** on the support pad **130**. In this embodiment, the flexible conduit **604** of the warming blanket receives the warming fluid **610** from the heating plate **424** of the thermoelectric cooler **420** by convection, specifically forced convection.

Still referring to FIGS. **16** and **17**, in yet another open loop embodiment, natural convection is used to circulate the warming fluid **610** from the heating plate **424** of the thermoelectric cooler **420** through the flexible conduit **604** of the warming blanket. In this embodiment, the frame outlet **624** is coupled to the inlet **606** of the flexible conduit **604**. However, the frame inlet **626** is coupled to atmosphere (i.e., open) as is the outlet **608** of the flexible conduit **604** of the warming blanket **600**. In this embodiment the pump **620** is not coupled to the frame conduit **622**. In this embodiment the warming fluid **610** is air.

In operation, the thermoelectric cooler **420** conducts heat from the support pad **130** as described hereinabove with respect to FIG. **10**. Simultaneously, warming fluid **610** (i.e., air) in the frame conduit **622** contacts the heating plate **424** and cooling fins **426** of the thermoelectric cooler **420**, thereby heating the warming fluid **610** by convection. The heated warming fluid **610** rises and exits the frame conduit **622** at frame outlet **624** and enters the inlet **606** of the flexible conduit **604** of the warming blanket **600**. The warming fluid **610** circulates through the flexible conduit **604** of the warming blanket **600** and the heat from the warming fluid **610** is transferred to a subject **900** positioned beneath the warming blanket **600** on the support pad **130**, thereby warming the subject **900**. The warming fluid **610** exits the flexible conduit **604** at the outlet **608** and is expelled to atmosphere.

Referring to FIGS. **16** and **9**, in an alternative embodiment, the warming blanket **600** may be utilized in conjunction with side rail **126** and blower **400** as depicted in FIG. **9**. Specifically, the inlet **606** of the flexible conduit **604** of the warming blanket **600** may be fluidly coupled to the side rail **126** such that output fluid **402** is directed into and circulated through the flexible conduit **604** of the warming blanket **600**

after passing around and through the thermally conductive fibers **220** of the second pigtail connector **218**. In this manner, heat conducted from the top surface of the support pad **130** through the thermally conductive core portion **200**, the first pigtail connector **216**, and the magnetic coupler **250** is recycled into the warming blanket **600**.

Referring now to FIGS. **18** and **19**, in an alternative embodiment, the warming blanket **600** includes a thermally conductive element **630** disposed between two plies of the warming blanket or, alternatively, embedded in a single ply of the warming blanket **600**, such as when the thermally conductive element **630** is woven into the material of the ply. As shown in FIG. **18**, the thermally conductive element may have a serpentine configuration within the sheet portion **602** of the warming blanket **600**. In the embodiment depicted in FIG. **18**, the thermally conductive element **630** may be formed from, for example and without limitation, carbon fibers such as pitch-based carbon fibers, thermally conductive polymer fibers as described herein, or combinations thereof.

The side rail **126** of the person support system may include a thermoelectric cooler **420** thermally coupled to a thermally conductive core portion **200** of the support pad **130**, as described herein with respect to FIG. **10**. However, in this embodiment, the thermally conductive element **630** of the warming blanket **600** is thermally coupled to the heating plate **424** of the thermoelectric cooler **420**.

In operation, the thermoelectric cooler **420** conducts heat from the support pad **130** as described hereinabove with respect to FIG. **10**. After the heat is transferred from the cooling plate **422** of the thermoelectric cooler **420** to the heating plate **424** of the thermoelectric cooler **420**, the heat is conducted away from the heating plate **424** with the thermally conductive element **630**. As the heat is conducted along the length of the thermally conductive element **630** and through the warming blanket **600**, heat from the thermally conductive element **630** is transferred to a subject **900** positioned beneath the warming blanket **600** on the support pad **130**, thereby warming the subject **900**.

While various embodiments of support pads which include thermally conductive core portions that are actively cooled by thermally coupling the thermally conductive core portions to a cooling source which creates a temperature gradient between the top surface of the support pad and the cooling source have been described herein, it should be understood that alternative embodiments are contemplated and possible. For example, in some embodiments described here, the thermally conductive core portions may provide passive cooling by absorbing and dissipating heat without being thermally coupled to a cooling source.

Referring to FIGS. **20** and **21** by way of example, FIG. **20** schematically depicts a cross-section of one embodiment of a support pad **130**. In this embodiment, the support pad **130** is sized and shaped to extend from a head end **H** of a person support system to the foot end **F** of the person support system. However, it should be understood that, in alternative embodiments, the support pad **130** may be sized and shaped to extend only over a portion of the person support system. The support pad **130** may include a core part **132** enveloped in a cover material **136**, as described hereinabove with respect to FIG. **4B**. However, in this embodiment, the support pad **130** includes at least one recess **137** formed in the core part **132** and extending up through the top surface **131** of the support pad **130**. In embodiments, the recesses **137** may be located in the core part **132** in, for example and without limitation, areas that correspond to the sacral area, buttocks, scapular areas, and/or heels of a subject when the

subject is positioned on the top surface **131** of the support pad **130**. The recesses **137** are sized and shaped to removably receive a foam plug **170** that is formed from the same or similar material as the core part **132**. In embodiments, the foam plug **170** may be enveloped in a cover material that is the same as the cover material **136** of the support pad **130**. When the foam plugs **170** are inserted in the corresponding recesses **137**, the top of the foam plugs are flush with the top surface **131** of the support pad **130**.

In the embodiment of the support pad **130** shown in FIGS. **20** and **21**, the foam plug(s) **170** may be removed from the recesses **137** and replaced with thermally conductive core portions **200**, as depicted in FIG. **21**. Like the foam plugs **170**, the top surfaces of the thermally conductive core portions **200** are flush with the top surface **131** of the support pad **130** when inserted in the recesses **137**. The thermally conductive core portions **200** may be any one of the thermally conductive core portions described herein including, without limitation, the various embodiments of thermally conductive core portions depicted in FIGS. **5A-5G**. In embodiments where the thermally conductive core portions **200** depicted in FIG. **5B** are used, the thermally conductive core portions **200** may optionally include the thermal transport layer **214**. However, when the thermally conductive core portion of FIG. **5B** is used in conjunction with the support pad **130** depicted in FIGS. **20** and **21**, the thermally conductive core portion is formed without the pigtail connector **216**. Similarly, when the thermally conductive core portions **200** are as depicted in FIGS. **5E-5G**, the thermally conductive core portions are constructed without the pigtail connector **216**. That is, in the embodiments of the support pad **130** depicted in FIGS. **20** and **21**, heat from a subject positioned on the top surface **210** of the thermally conductive core portion **200** is conducted into the support matrix **204** of the thermally conducted core portion **200** and dissipated therein rather than further conducted out of the support matrix **204**.

Still referring to FIGS. **20** and **21**, a support pad **130** which includes recesses **137** in which foam plugs **170** and/or thermally conductive core portions **200** may be removably positioned facilitates tailoring the cooling capacity of the support pad **130** to specific situations and/or subjects. For example, in embodiments, where no cooling is desired, foam plugs **170** may be positioned in the recesses **137**. Where cooling is desired at a specific location, the foam plug **170** may be removed from the corresponding recess and replaced with a thermally conductive core portion **200**. The thermally conductive core portion **200** may be selected from a plurality of different thermally conductive core portions **200** to achieve a desired amount of cooling. For example and without limitation, a plurality of thermally conductive core portions **200** may be constructed as depicted in FIG. **5A** and/or FIG. **5B**. Each of the plurality of thermally conductive core portions **200** may be constructed from different materials (e.g., different phase change materials or the like) and, as a result, may have different cooling characteristics. The specific thermally conductive core portion **200** inserted in the recess **137** of the support pad **130** may be selected from the plurality of thermally conductive core portions based on cooling characteristics in order to achieve a desired amount of cooling.

Based on the foregoing it should be understood that, in one embodiment, the support pad of FIGS. **20** and/or **21** may form a component of a subject cooling system which includes the support pad **130** having at least one recess formed in the core part **132** of the support pad **130**; a foam plug sized and shaped to be received in the recess formed in

the core part of the support pad **130**; and a plurality of thermally conductive core portions **200** sized and shaped to be received in the recess formed in the core part. Each of the thermally conductive core portions **200** may have cooling characteristics different than the other thermally conductive core portions of the plurality. The thermally conductive core portions may be constructed as depicted in any one of FIGS. **5A-5G**.

The embodiment of the support pad **130** depicted in FIGS. **20** and **21** provides a customizable surface that can be tailored to specific cooling requirements by exchanging foam plugs for thermally conductive core portions and vice-versa. Because the thermally conductive core portions are recessed into the surface, the amount of cooling provided can be tailored up to a maximum cooling by, for example, adjusting the thickness of the thermally conductive core portions (i.e., using a combination of thermally conductive core portions and foam plug "spacers" inserted in the recesses with the thermally conductive core portions positioned on the spacers) or selecting thermally conductive core portions with different types of phase change materials with different melting temperatures or the like.

While specific reference has been made herein to use of the support pads with thermally conductive core portions in conjunction with subject support systems such as surgical tables and/or spine tables, it should be understood that use of the support pads with other types of subject support systems are contemplated and possible. For example, some embodiments of the support pads with thermally conductive core portions, such as the embodiment depicted in FIGS. **20** and **21**, may be used in conjunction with stretchers and or gurneys. Alternatively, a variation of the embodiment of the support pad **130** depicted in FIG. **4B** may be utilized in conjunction with a stretcher or gurney.

Referring to FIG. **22** by way of example, a stretcher **700** which includes a support pad **130** is schematically depicted. The support pad **130** is generally constructed as shown in FIG. **4B**. That is, the core part **132** of the support pad **130** may be formed with a channel **133** extending through the foam of the core part **132** from a recess where the thermally conductive core portion **200** is located to the edge of the support pad **130**, as depicted in FIG. **22**. The channel **133** may facilitate removing and replacing the thermally conductive core portion **200** with, for example, a thermally conductive core portion constructed from different thermally conductive material having different cooling characteristics or a "fresh" thermally conductive core portion (such as when the thermally conductive core portion **200** has reached an equilibrium temperature with a subject positioned on the support pad **130** and the cooling capabilities of the thermally conductive core portion **200** are exhausted). In other embodiments, the channel **133** may facilitate removing and replacing the thermally conductive core portion **200** in the recess with, for example, a plug of foam material similar or identical to the foam of the core part **132**. The thermally conductive core portion **200** may be replaced with a plug of foam material when, for example, focal cooling of a particular area is not needed or desired. The plug of foam material fills the recess previously occupied by the thermally conductive core portion **200**, thereby maintaining the support provided by the support pad **130** in the absence of the thermally conductive core portion **200**. In embodiments, access to the channel **133** in the core part **132** may be provided by, for example, a closure **138** formed in the cover material **136** enveloping the core part **132**. The closure **138** may be, for example and without limitation, a flap, a hook-and-loop closure, a zipper, or the like. In the embodi-

51

ment depicted in FIG. 22, the thermally conductive core portion 200 may be a thermally conductive core portion as shown and described in FIGS. 5A-5G.

The embodiment of the support pad 130 depicted in FIG. 22 allows focal cooling to be provided without modification of the structural components of the stretcher 700. That is, the support pad 130 may be retrofit to existing stretchers without modification of the stretcher frame.

While various embodiments of support pads with cooling features have been shown and described herein in conjunction with person support systems, it should be understood that other applications are contemplated and possible. For example, the support pads described herein may be used in conjunction with other medical equipment including, without limitation, wheelchairs, stretchers, gurneys, and the like or any other medical equipment which utilizes a support surface on which a subject may be positioned for extended periods of time.

Various embodiments described herein include cooling features in the form of thermally conductive elements in a support pad. The cooling features may reduce a temperature of the tissue in contact with the support pad, which may further reduce the likelihood of a pressure ulcer. In various embodiments, the support pad is made of radiolucent materials to enable the support pad to be used without interfering with imaging techniques utilized in conjunction with the person support systems on which the support pads are positioned.

It will be apparent to those skilled in the art that various modifications and variations can be made to the embodiments described herein without departing from the spirit and scope of the claimed subject matter. Thus it is intended that the specification cover the modifications and variations of the various embodiments described herein provided such modification and variations come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A person support system comprising:

a longitudinal frame comprising at least one side rail;
a support pad positioned on the longitudinal frame, the support pad comprising a thermally conductive core portion comprising a support matrix and at least one thermally conductive element; and

a cooling source thermally coupled to the thermally conductive core portion through the at least one side rail with a connector comprising thermally conductive fibers, wherein the cooling source draws heat from the thermally conductive core portion through the at least one thermally conductive element and the thermally conductive fibers of the connector thereby cooling at least the thermally conductive core portion of the support pad,

wherein the cooling source is thermally coupled to the thermally conductive core portion with a magnetic coupler.

2. The person support system of claim 1, wherein:

the person support system further comprises a control unit communicatively coupled to a temperature sensor, the control unit comprising a processor and a non-transitory memory storing computer readable and executable instructions which, when executed by the processor, cause the control unit to:

receive a temperature signal from the temperature sensor indicative of a measured temperature of skin of a subject or a surface of the support pad;
compare the measured temperature to a target temperature; and

52

adjust an operating parameter of the cooling source when the measured temperature is not equal to the target temperature, thereby increasing or decreasing cooling of the support pad until the measured temperature is equal to the target temperature.

3. The person support system of claim 1, wherein:

the person support system further comprises a control unit communicatively coupled to an input device and a temperature sensor, the control unit comprising a processor and a non-transitory memory storing computer readable and executable instructions which, when executed by the processor, cause the control unit to:
receive an input indicative of a target temperature;
receive an input indicative of an identity of an accessory;

determine an adjusted target temperature based on the target temperature and the identity of the accessory;
receive a temperature signal from the temperature sensor indicative of a measured temperature of a surface of the support pad; and
adjust an operating parameter of the cooling source thereby increasing or decreasing cooling of the support pad until the measured temperature is equal to the adjusted target temperature.

4. The person support system of claim 3 further comprising an RFID reader communicatively coupled to the control unit, wherein the computer readable and executable instructions, when executed by the processor, further cause the control unit to receive an accessory identification signal from the RFID reader indicative of the identity of the accessory, wherein the accessory identification signal is the input indicative of the identity of the accessory.

5. The person support system of claim 1, wherein:

the cooling source comprises thermally absorptive material; and

the person support system further comprises a control unit communicatively coupled to an input device, the control unit comprising a processor and a non-transitory memory storing computer readable and executable instructions which, when executed by the processor, cause the control unit to:

receive an input indicative of a target temperature;
receive an input indicative of an identity of an accessory; and

determine a recommended thermally absorptive material based on the target temperature and the identity of the accessory.

6. The person support system of claim 5 further comprising an RFID reader communicatively coupled to the control unit, wherein the computer readable and executable instructions, when executed by the processor, further cause the control unit to receive an accessory identification signal from the RFID reader indicative of the identity of the accessory, wherein the accessory identification signal is the input indicative of the identity of the accessory.

7. The person support system of claim 5, wherein the computer readable and executable instructions, when executed by the processor, further cause the control unit to determine a recommended time schedule for replacing the thermally absorptive material to achieve the target temperature.

8. The person support system of claim 1, wherein:

The cooling source comprises a thermally absorptive material disposed in a canister; and

the thermally conductive core portion of the support pad is thermally coupled to the canister with the thermally conductive fibers of the connector.

53

9. The person support system of claim 1, wherein the at least one thermally conductive element comprises:

thermally conductive particles suspended in the support matrix; and

at least one thermal transport layer thermally coupled to the support matrix and configured to conduct heat from the support matrix.

10. The person support system of claim 9, wherein a number of thermally conductive particles per unit volume of the support matrix is greatest proximate a top surface of the thermally conductive core portion and decreases with increasing distance from the top surface of the thermally conductive core portion.

11. The person support system of claim 9, wherein the thermally conductive core portion further comprises thermally absorptive particles suspended in the support matrix.

12. The person support system of claim 11, wherein a number of thermally absorptive particles per unit volume of the support matrix is greatest at a top surface of the thermally conductive core portion and decreases with increasing distance from the top surface of the thermally conductive core portion.

13. The person support system of claim 1, wherein the at least one thermally conductive element of the thermally conductive core portion comprises an array of thermally conductive fibers suspended in the support matrix and arranged to conduct heat away from a top surface of the thermally conductive core portion, wherein at least a portion of the array of thermally conductive fibers extend from at least one of a side surface of the support matrix and a bottom surface of the support matrix.

14. The person support system of claim 13, wherein the array of thermally conductive fibers comprises a first plurality of thermally conductive fibers and a second plurality of thermally conductive fibers, wherein the second plurality of thermally conductive fibers are arranged parallel to a top surface of the thermally conductive core portion.

15. The person support system of claim 14, wherein the first plurality of thermally conductive fibers are obliquely oriented with respect to the second plurality of thermally conductive fibers.

16. The person support system of claim 15, wherein the first plurality of thermally conductive fibers and the second plurality of thermally conductive fibers have different thermal conductivities and the thermal conductivity of the first plurality of thermally conductive fibers is greater than the thermal conductivity of the second plurality of thermally conductive fibers.

17. The person support system of claim 14, wherein the second plurality of thermally conductive fibers are arranged in the support matrix such that a density of the second plurality of thermally conductive fibers in the support matrix is greatest at a top surface of the thermally conductive core portion and decreases with increasing distance from the top surface of the thermally conductive core portion.

18. The person support system of claim 14, wherein: the second plurality of thermally conductive fibers comprises thermally conductive fibers having different thermal conductivities; and

the second plurality of thermally conductive fibers are arranged in the support matrix such that fibers having relatively greater thermal conductivity are positioned closer to a top surface of the thermally conductive core portion than thermally conductive fibers having relatively lower thermal conductivity.

54

19. The person support system of claim 1, wherein the at least one thermally conductive element envelops the support matrix.

20. The person support system of claim 1, wherein: the cooling source is a thermoelectric cooler and the thermally conductive core portion is thermally coupled to a cooling plate of the thermoelectric cooler; and the person support system further comprises a warming blanket thermally coupled to a heating plate of the thermoelectric cooler.

21. The person support system of claim 20, wherein the warming blanket comprises a flexible conduit receiving a warming fluid from the heating plate of the thermoelectric cooler by convection.

22. The person support system of claim 20, wherein the warming blanket comprises a thermally conductive element and the thermally conductive element of the warming blanket is thermally coupled to the heating plate of the thermoelectric cooler.

23. The person support system of claim 1, wherein: the cooling source is a thermoelectric cooler disposed in the at least one side rail of the longitudinal frame; and the thermally conductive core portion of the support pad is thermally coupled to a cooling plate of the thermoelectric cooler with the thermally conductive fibers of the connector.

24. The person support system of claim 1, wherein: the cooling source is a blower configured to direct a flow of fluid through an interior channel of the at least one side rail; and the thermally conductive core portion of the support pad is thermally coupled to the flow of fluid with the thermally conductive fibers of the connector.

25. The person support system of claim 1, wherein: the support pad comprises a core part; and the thermally conductive core portion is disposed in a recess formed in the core part.

26. The person support system of claim 25, wherein the core part comprises a channel extending from the recess to an edge of the support pad, the channel facilitating insertion and removal of the core part in the recess.

27. A person support system comprising: a longitudinal frame comprising at least one side rail; a support pad positioned on the longitudinal frame, the support pad comprising a thermally conductive core portion comprising a support matrix and at least one thermally conductive element;

a cooling source thermally coupled to the thermally conductive core portion through the at least one side rail with a connector comprising thermally conductive fibers, wherein the cooling source draws heat from the thermally conductive core portion through the at least one thermally conductive element and the thermally conductive fibers of the connector thereby cooling at least the thermally conductive core portion of the support pad;

a control unit communicatively coupled to an input device, an RFID reader, and a temperature sensor, the control unit comprising a processor and a non-transitory memory storing computer readable and executable instructions which, when executed by the processor, cause the control unit to:

receive an input indicative of a target temperature;

receive an accessory identification signal from the RFID reader indicative of an identity of an accessory;

55

determine an adjusted target temperature based on the target temperature and the identity of the accessory; receive a temperature signal from the temperature sensor indicative of a measured temperature of a surface of the support pad; and
 5 adjust an operating parameter of the cooling source thereby increasing or decreasing cooling of the support pad until the measured temperature is equal to the adjusted target temperature.

28. A subject cooling system comprising:

a support pad comprising a core part and at least one recess formed in the core part, the at least one recess extending through a top surface of the support pad;
 a foam plug comprising a shape and a size corresponding to the at least one recess formed in the core part of the support pad; and

a set of thermally conductive core portions, each thermally conductive core portion of the set of thermally conductive core portions comprising a shape and a size corresponding to the at least one recess formed in the core part of the support pad, wherein:

each thermally conductive core portion of the set of thermally conductive core portions has different cooling characteristics than at least one other thermally conductive core portion in the set of thermally conductive core portions; and

the foam plug and each thermally conductive core portion of the set of thermally conductive core portions are interchangeably insertable into the at least one recess formed in the core part of the support pad.

29. The subject cooling system of claim 28, wherein at least one thermally conductive core portion of the set of thermally conductive core portions comprises a support matrix and thermally absorptive particles suspended in the support matrix.

30. The subject cooling system of claim 28, wherein at least one thermally conductive core portion of the set of thermally conductive core portions comprises a support matrix and an array of thermally conductive fibers suspended in the support matrix and arranged to conduct heat away from a top surface of the thermally conductive core portion, wherein the support matrix comprises a thermally absorptive material and at least a portion of the array of thermally conductive fibers extend from at least one of a side surface of the support matrix and a bottom surface of the support matrix.

31. The subject cooling system of claim 28, wherein at least one thermally conductive core portion of the set of thermally conductive core portions comprises:

a compliant shell;

a support matrix comprising thermally adsorptive material enclosed within the compliant shell; and

a cover flange extending around the support matrix and continuous with a top surface of the compliant shell, wherein at least the top surface and the cover flange have a thermal conductivity greater than 40 W/m*K.

32. The subject cooling system of claim 28, wherein at least one thermally conductive core portion of the set of thermally conductive core portions comprises:

a first support matrix comprising thermally absorptive material;

a second support matrix comprising thermally absorptive material, wherein the first support matrix and the second support matrix are enclosed within a compliant shell comprising a top surface having a thermal con-

56

ductivity greater than 40 W/m*K, the compliant shell thermally coupling the first support matrix to the second support matrix; and

a third support matrix disposed between the first support matrix and the second support matrix, wherein the third support matrix is formed from a different material than the first support matrix and the second support matrix.

33. The subject cooling system of claim 32, wherein the third support matrix is positioned in the compliant shell.

34. The subject cooling system of claim 32, wherein the third support matrix comprises a foam.

35. A person support system comprising:

a longitudinal frame comprising at least one side rail;

a support pad positioned on the longitudinal frame, the support pad comprising a thermally conductive core portion comprising a support matrix and at least one thermally conductive element; and

a cooling source thermally coupled to the thermally conductive core portion through the at least one side rail with a connector comprising thermally conductive fibers, wherein the cooling source draws heat from the thermally conductive core portion through the at least one thermally conductive element and the thermally conductive fibers of the connector thereby cooling at least the thermally conductive core portion of the support pad, wherein:

the cooling source is a thermoelectric cooler and the thermally conductive core portion is thermally coupled to a cooling plate of the thermoelectric cooler; and

the person support system further comprises a warming blanket thermally coupled to a heating plate of the thermoelectric cooler.

36. The person support system of claim 35, wherein the warming blanket comprises a flexible conduit receiving a warming fluid from the heating plate of the thermoelectric cooler by convection.

37. The person support system of claim 35, wherein the warming blanket comprises a thermally conductive element and the thermally conductive element of the warming blanket is thermally coupled to the heating plate of the thermoelectric cooler.

38. A person support system comprising:

a longitudinal frame comprising at least one side rail;

a support pad positioned on the longitudinal frame, the support pad comprising a thermally conductive core portion comprising a support matrix and at least one thermally conductive element; and

a cooling source thermally coupled to the thermally conductive core portion through the at least one side rail with a connector comprising thermally conductive fibers, wherein the cooling source draws heat from the thermally conductive core portion through the at least one thermally conductive element and the thermally conductive fibers of the connector thereby cooling at least the thermally conductive core portion of the support pad, wherein:

the at least one thermally conductive element comprises thermally conductive particles suspended in the support matrix and at least one thermal transport layer thermally coupled to the support matrix and configured to conduct heat from the support matrix; and
 a number of thermally conductive particles per unit volume of the support matrix is greatest proximate a top surface of the thermally conductive core portion and decreases with increasing distance from the top surface of the thermally conductive core portion.

57

39. The person support system of claim 38, wherein the thermally conductive core portion further comprises thermally absorptive particles suspended in the support matrix.

40. The person support system of claim 39, wherein a number of thermally absorptive particles per unit volume of the support matrix is greatest at a top surface of the thermally conductive core portion and decreases with increasing distance from the top surface of the thermally conductive core portion.

41. A person support system comprising:

a longitudinal frame comprising at least one side rail;

a support pad positioned on the longitudinal frame, the support pad comprising a thermally conductive core portion comprising a support matrix and at least one thermally conductive element; and

a cooling source thermally coupled to the thermally conductive core portion through the at least one side rail with a connector comprising thermally conductive fibers, wherein the cooling source draws heat from the thermally conductive core portion through the at least one thermally conductive element and the thermally conductive fibers of the connector thereby cooling at least the thermally conductive core portion of the support pad, wherein:

the at least one thermally conductive element of the thermally conductive core portion comprises an array of thermally conductive fibers suspended in the support matrix and arranged to conduct heat away from a top surface of the thermally conductive core portion;

at least a portion of the array of thermally conductive fibers extend from at least one of a side surface of the support matrix and a bottom surface of the support matrix; and

the array of thermally conductive fibers comprises a first plurality of thermally conductive fibers and a second plurality of thermally conductive fibers, wherein the second plurality of thermally conductive fibers are arranged parallel to a top surface of the thermally conductive core portion.

42. The person support system of claim 41, wherein the first plurality of thermally conductive fibers are obliquely oriented with respect to the second plurality of thermally conductive fibers.

43. The person support system of claim 42, wherein the first plurality of thermally conductive fibers and the second plurality of thermally conductive fibers have different thermal conductivities and the thermal conductivity of the first plurality of thermally conductive fibers is greater than the thermal conductivity of the second plurality of thermally conductive fibers.

58

44. The person support system of claim 41, wherein the second plurality of thermally conductive fibers are arranged in the support matrix such that a density of the second plurality of thermally conductive fibers in the support matrix is greatest at a top surface of the thermally conductive core portion and decreases with increasing distance from the top surface of the thermally conductive core portion.

45. The person support system of claim 41, wherein:

the second plurality of thermally conductive fibers comprises thermally conductive fibers having different thermal conductivities; and

the second plurality of thermally conductive fibers are arranged in the support matrix such that fibers having relatively greater thermal conductivity are positioned closer to a top surface of the thermally conductive core portion than thermally conductive fibers having relatively lower thermal conductivity.

46. A person support system comprising:

a longitudinal frame comprising at least one side rail;

a support pad positioned on the longitudinal frame, the support pad comprising a thermally conductive core portion comprising a support matrix and at least one thermally conductive element;

a cooling source thermally coupled to the thermally conductive core portion through the at least one side rail with a connector comprising thermally conductive fibers, wherein the cooling source comprises thermally absorptive material and draws heat from the thermally conductive core portion through the at least one thermally conductive element and the thermally conductive fibers of the connector to the thermally absorptive material thereby cooling at least the thermally conductive core portion of the support pad; and

a control unit communicatively coupled to an input device and an RFID reader, the control unit comprising a processor and a non-transitory memory storing computer readable and executable instructions which, when executed by the processor, cause the control unit to: receive an input indicative of a target temperature; receive an accessory identification signal from the RFID reader indicative of an identity of an accessory; and

determine a recommended thermally absorptive material based on the target temperature and the identity of the accessory.

47. The person support system of claim 46, wherein the computer readable and executable instructions, when executed by the processor, further cause the control unit to determine a recommended time schedule for replacing the thermally absorptive material to achieve the target temperature.

* * * * *

专利名称(译)	具有冷却功能的人员支撑系统		
公开(公告)号	US10548788	公开(公告)日	2020-02-04
申请号	US15/348080	申请日	2016-11-10
[标]申请(专利权)人(译)	希尔 - 罗姆服务股份有限公司		
申请(专利权)人(译)	HILL-ROM SERVICES , INC.		
当前申请(专利权)人(译)	HILL-ROM SERVICES , INC.		
[标]发明人	LACHENBRUCH CHARLES A SRIVASTAVA VARAD NARAYAN RIBBLE DAVID LANCE WILLIAMSON RACHEL L BEDEL DAVID LAWRENCE CLARK ANDREW DAVID BAKER STEVEN D HARMEYER JOHN V HERTZ BEN ONEAL TODD P		
发明人	LACHENBRUCH, CHARLES A. SRIVASTAVA, VARAD NARAYAN RIBBLE, DAVID LANCE WILLIAMSON, RACHEL L. BEDEL, DAVID LAWRENCE CLARK, ANDREW DAVID BAKER, STEVEN D. HARMEYER, JOHN V. HERTZ, BEN O'NEAL, TODD P.		
IPC分类号	A61G7/05 A61G7/057 A61B5/00 A61B5/01 A61G13/12 A61G13/04 A61G13/06 A61G13/10 A61F7/00 A61G13/00		
CPC分类号	A61B5/01 A61G13/04 A61B5/6892 A61G13/06 A61G13/0054 A61G13/12 A61G13/127 A61F7/0053 A61G13/104 A61G7/057 A61G13/126 A61F7/0097 A61G2203/46 A61G2210/50 A61G2205/60 A61B5/4836 A61G2203/10 A61F2007/0056 A61F2007/0096 A61F2007/0075 A61G2210/70 A61F2007/0086		
优先权	62/255147 2015-11-13 US		
其他公开文献	US20170135884A1		
外部链接	Espacenet		

摘要(译)

实施例提供了一种人支撑系统，其包括具有冷却特征的支撑垫。 根据一个实施例，一种人支撑系统可以包括纵向框架，该纵向框架包括至少一个侧轨。 支撑垫可定位在纵向框架上。 支撑垫可以包括导热芯部，该导热芯部包括支撑矩阵和至少一个导热元件。 可以使用包括导热纤维的连接器通过侧轨将冷却源热耦合至导热芯部。 冷却源可通过至少一个导热元件和连接器的导热纤维从导热芯部吸收热量，从而至少冷却支撑垫的导热芯部。

