

(12) United States Patent

Barthe et al.

(10) Patent No.: US 9,694,211 B2

*Jul. 4, 2017 (45) Date of Patent:

(54) SYSTEMS FOR TREATING SKIN LAXITY

Applicant: Guided Therapy Systems, L.L.C.,

Mesa, AZ (US)

(72) Inventors: **Peter G. Barthe**, Phoenix, AZ (US);

Michael H. Slayton, Tempe, AZ (US); Inder Raj S. Makin, Mesa, AZ (US)

Assignee: Guided Therapy Systems, L.L.C.,

Mesa, AZ (US)

Subject to any disclaimer, the term of this (*) Notice:

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 15/248,407

(22)Filed: Aug. 26, 2016

(65)**Prior Publication Data**

> US 2016/0361573 A1 Dec. 15, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/692,114, filed on Apr. 21, 2015, now Pat. No. 9,427,600, which is a (Continued)

(51) Int. Cl.

A61N 7/02 (2006.01)A61B 5/00 (2006.01)

(Continued)

(52) U.S. Cl.

CPC A61N 7/02 (2013.01); A61B 5/682 (2013.01); A61B 5/6842 (2013.01); A61B 8/08 (2013.01);

(Continued)

(58) Field of Classification Search

CPC ... A61B 5/682; A61B 17/320068; A61B 8/08; A61B 8/0858; A61B 8/12; A61B 8/4483;

(Continued)

References Cited

(56)

U.S. PATENT DOCUMENTS

9/1947 Bond et al. 2,427,348 A 2,792,829 A 2/1952 Calosi (Continued)

FOREIGN PATENT DOCUMENTS

104027893 CN 9/2014 DE 4029175 3/1992 (Continued)

OTHER PUBLICATIONS

Delon Martin, C., et al, "Venous Thrombosis Generation By Means of High-Intensity Focused Ultrasound" Ultrasound in Med. & Biol., vol. 21, No. 1, pp. 113-119 (1995).

Agren, Magnus S. et al., Collagenase in Wound Healing: Effect of Wound Age and Type. The Journal of Investigative Dermatology, vol. 99/No. 6, (Dec. 1992).

Alster, Tinas S., Tanzi, Elizabeth L., "Cellulite Treatment using a Novel Combination Radiofrequency, Infrared Light, and Mechanical Tissue Manipulation Device," Journal of Cosmetic & Laser Therapy, Jun. 2005, vol. 7, Issue 2, pp. 81-85.


(Continued)

Primary Examiner — Bo J Peng (74) Attorney, Agent, or Firm — Knobbe, Martens, Olson & Bear, LLP

ABSTRACT (57)

A system and method for ultrasound treatment of skin laxity are provided. Systems and methods can include ultrasound imaging of the region of interest for localization of the treatment area, delivering ultrasound energy at a depth and pattern to achieve the desired therapeutic effects, and/or monitoring the treatment area to assess the results and/or provide feedback. In an embodiment, a treatment system and method can be configured for producing arrays of submillimeter and larger zones of thermal ablation to treat the epidermal, superficial dermal, mid-dermal and deep dermal components of tissue.

20 Claims, 22 Drawing Sheets



4,507,582 A 4,513,749 A Related U.S. Application Data 3/1985 Glenn 4/1985 Kino 4,513,750 A continuation of application No. 14/169,709, filed on 4/1985 Heyman et al. 4,527,550 A Jan. 31, 2014, now Pat. No. 9,039,619, which is a 7/1985 Ruggera et al. 4,528,979 A 7/1985 Marchenko continuation of application No. 13/230,498, filed on 4,534,221 A 8/1985 Fife et al. Sep. 12, 2011, now Pat. No. 8,641,622, which is a 4,566,459 A 1/1986 Umemura et al. continuation of application No. 11/163,150, filed on 4,567,895 A 2/1986 Putzke Oct. 6, 2005, now Pat. No. 8,066,641. 4,586,512 A 5/1986 Do-Huu 4.601.296 A 7/1986 Yerushalmi 4,620,546 A 11/1986 Aida et al. (60) Provisional application No. 60/617,295, filed on Oct. 4,637,256 A 1/1987 Sugiyama et al. 7, 2004. 4,646,756 A 3/1987 Watmough 4,663,358 A 5/1987 Hyon (51) Int. Cl. 4,668,516 A 5/1987 Duraffourd et al. 4,672,591 A 6/1987 A61B 8/08 (2006.01)Breimesser et al. 4,680,499 A 7/1987 Umemura et al. A61B 8/12 (2006.01)4,697,588 A 10/1987 Reichenberger A61H 23/02 (2006.01)4,754,760 A 4,757,820 A 7/1988 Fukukita et al. A61N 7/00 (2006.01)7/1988 Itoh G01S 15/89 (2006.01)4,771,205 A 9/1988 Mequio A61B 8/13 (2006.01)4,801,459 A 1/1989 Liburdy 4,803,625 A 2/1989 Fu et al. A61B 17/32 (2006.01)4,807,633 A 2/1989 Fry A61B 8/00 (2006.01)4,817,615 A 4/1989 Fukukita et al. (52)U.S. Cl. 4,858,613 A 8/1989 Fry 4,860,732 A 8/1989 Hasegawa et al. CPC 4,865,041 A 9/1989 Hassler (2013.01); A61B 8/13 (2013.01); A61B 8/4483 4,865,042 A 9/1989 Umemura (2013.01); A61B 8/461 (2013.01); A61B 8/483 4,867,169 A 9/1989 Machida (2013.01); A61B 8/546 (2013.01); A61B 4,874,562 A 10/1989 Hyon 17/320068 (2013.01); A61H 23/0245 4,875,487 A 10/1989 Seppi 4,881,212 A 11/1989 Takeuchi (2013.01); A61N 7/00 (2013.01); G01S 4,891,043 A 1/1990 Zeimer et al. 15/8909 (2013.01); A61B 8/4209 (2013.01); 1/1990 4,893,624 A Lele A61B 8/4281 (2013.01); A61B 8/4455 4,896,673 A 1/1990 Rose (2013.01); A61H 2201/5007 (2013.01); A61N 4,900,540 A 2/1990 Rvan et al. 2007/0008 (2013.01); A61N 2007/0034 4,901,729 A 2/1990 Saitoh 4,917,096 A 4,932,414 A 4/1990 (2013.01); A61N 2007/0052 (2013.01); A61N Englehart 6/1990 Coleman et al. 2007/027 (2013.01) 4,938,216 A 7/1990 Lele (58) Field of Classification Search 4,938,217 A 7/1990 CPC A61B 8/483; A61B 8/546; A61B 8/13; 4,947,046 A 8/1990 Kawabata et al. 4,951,653 A 8/1990 Fry A61B 8/461; A61B 5/6842; A61B 4.955,365 A 9/1990 Frv 8/4209; A61B 8/4281; A61B 8/4455; 4.958.626 A 9/1990 Nambu A61H 23/0245; A61H 2201/50; A61N 4,976,709 A 12/1990 Sand 7/00; A61N 7/02; G01S 15/8909 4,979,501 A 12/1990 Valchanov See application file for complete search history. 4.992.989 A 2/1991 Watanabe et al. 5,012,797 A 5/1991Liang 5,018,508 A 5/1991 Fry et al (56)**References Cited** 5,030,874 A 7/1991 Saito et al. 5,036,855 A 8/1991 Fry U.S. PATENT DOCUMENTS 5,040,537 A Katakura 8/1991 5.054,310 A 10/1991 Flynn 3,913,386 A 10/1975 Saglio 5.054.470 A 10/1991 Fry 3,965,455 A 3,992,925 A 6/1976 Hurwitz 5,054,491 A 10/1991 Saito et al. 11/1976 Perilhou 5,070,879 A 12/1991 Herres 4.039.312 A 8/1977 Patru 5,088,495 A 2/1992 Miyagawa 4,059,098 A 11/1977 Murdock 5,115,814 A 5/1992 Griffith 4,101,795 A 7/1978 Fukumoto et al. 5,117,832 A 6/1992 Sanghvi 4,151,834 A 5/1979 Sato et al 5,123,418 A 6/1992 Saurel 4,166,967 A 9/1979 Benes et al. 5,142,511 A 8/1992 Kanai et al. 4,211,948 A 7/1980 Smith et al. 5,143,063 A 9/1992 Fellner 4,211,949 A 7/1980 Brisken et al. 5.143.074 A 9/1992 Dorv 4,213,344 A 7/1980 Rose 9/1992 5,149,319 A Unger 4,276,491 A 4,315,514 A 6/1981 Daniel 5,150,711 A 9/1992 Dory 2/1982 Drewes et al. 5,150,714 A 9/1992 Green 4,325,381 A 4/1982 Glenn 5,152,294 A 10/1992 Mochizuki et al. 4,343,301 A 8/1982 Indech 5,156,144 A 10/1992 Iwasaki 4,372,296 A 2/1983 Fahim 5,158,536 A 10/1992 Sekins 4,379,145 A 4/1983 Masuho et al. 5.159,931 A 11/1992 Pini 4,381,007 A 4/1983 Doss 5,163,421 A 11/1992 Bernstein 4,381,787 A 5/1983 Hottinger 5,163,436 A 11/1992 Saitoh et al. 4,397,314 A 8/1983 Vaguine 5,178,135 A 1/1993 Uchiyama et al. 4,409,839 A 10/1983 Taenzer 5,190,518 A 3/1993 Takasu 4,431,008 A 2/1984 Wanner et al 5,190,766 A 3/1993 Ishihara 4,441,486 A 4/1984 Pounds 3/1993 5.191,880 A McLeod 4,452,084 A 6/1984 Taenzer

5,205,287 A

4/1993 Erbel et al.

4,484,569 A

11/1984 Driller

(56)	Referen	nces Cited	5,575,291 A		Hayakawa
II C	DATENIT	DOCER (ENTER	5,575,807 A	11/1996	
U.S.	PALENT	DOCUMENTS	5,577,502 A 5,577,507 A		Darrow et al. Snyder et al.
5 200 720 A	£/1002	TT	5,577,991 A		Akui et al.
5,209,720 A 5,212,671 A	5/1993	Unger Fujii et al.	5,580,575 A		Unger et al.
5,215,680 A		D'Arrigo	5,601,526 A *	2/1997	Chapelon A61N 7/02
5,224,467 A	7/1993				601/2
5,230,334 A		Klopotek	5,603,323 A	2/1997	Pflugrath et al.
5,230,338 A		Allen et al.	5,605,154 A *	2/1997	Ries G01S 7/52046
5,247,924 A		Suzuki et al.	5 (00 5(2 A	3/1997	600/444
5,255,681 A 5,257,970 A		Ishimura et al. Dougherty	5,609,562 A 5,615,091 A		Palatnik
5,265,614 A		Hayakawa	5,617,858 A		Taverna et al.
5,267,985 A		Shimada	5,618,275 A	4/1997	
5,269,297 A	12/1993		5,620,479 A		Diederich
5,282,797 A	2/1994		5,622,175 A		Sudol et al.
5,295,484 A		Marcus	5,638,819 A 5,643,179 A *		Manwaring et al. Fujimoto A61N 7/02
5,295,486 A 5,304,169 A	3/1994 4/1994	Wollschlager et al.	5,045,179 A	1/1997	601/2
5,305,756 A		Entrekin et al.	5,644,085 A	7/1997	Lorraine et al.
5,321,520 A		Inga et al.	5,647,373 A		Paltieli
5,323,779 A		Hardy et al.	5,655,535 A		FrIemel et al.
5,327,895 A		Hashimoto et al.	5,655,538 A		Lorraine
5,348,016 A		Unger et al.	5,657,760 A	8/1997	
5,558,400 A	10/1994	Aida A61B 17/2256 600/439	5,658,328 A 5,660,836 A *		Johnson Knowlton A61B 18/12
5,360,268 A	11/1994	Hayashi	5,000,830 A	0/1997	128/898
5,370,121 A		Reichenberger	5,662,116 A	9/1997	
5,371,483 A		Bhardwaj	5,665,053 A	9/1997	
5,375,602 A		Lancee et al.	5,665,141 A	9/1997	
5,379,773 A		Hornsby	5,671,746 A		Dreschel et al.
5,380,280 A		Peterson Schneider et al.	5,673,699 A 5,676,692 A		Trahey et al. Sanghvi
5,380,519 A 5,383,917 A		Desai et al.	5,685,820 A		Riek et al.
5,391,140 A		Schaetzle et al.	5,690,608 A		Watanabe
5,391,197 A	2/1995	Burdette et al.	5,694,936 A		Fujimoto
5,392,259 A		Bolorforosh	5,697,897 A		Buchholtz
5,396,143 A		Seyed-Bolorforosh et al.	5,701,900 A		Shehada et al.
5,398,689 A 5,406,503 A		Connor et al. Williams	5,704,361 A 5,706,252 A		Seward et al. Le Verrier et al.
5,413,550 A *		Castel A61H 23/0245	5,706,564 A	1/1998	
2,12,550 11	0,1330	601/2	5,715,823 A		Wood et al.
5,417,216 A	5/1995	Tanaka	5,720,287 A		Chapelon et al.
5,419,327 A		Rohwedder	5,722,411 A		Suzuki
5,423,220 A		Finsterwald et al.	5,727,554 A 5,735,280 A		Kalend et al. Sherman et al.
5,435,311 A 5,438,998 A		Umemura Hanafy	5,743,863 A		Chapelon
5,443,068 A *		Cline A61B 5/0555	5,746,005 A		Steinberg
-,,		600/411	5,746,762 A	5/1998	Bass
5,445,611 A	8/1995	Eppstein et al.	5,748,767 A	5/1998	
5,458,596 A	10/1995		5,749,364 A		Sliwa et al. Wilson et al.
5,460,179 A 5,460,595 A		Okunuki et al. Hall et al.	5,755,228 A 5,755,753 A		Knowlton
5,469,854 A		Unger et al.	5,762,066 A	6/1998	
5,471,988 A	12/1995		5,763,886 A	6/1998	Schulte
5,472,405 A	12/1995	Buchholtz et al.	5,769,790 A		Watkins
5,487,388 A		Rello et al.	5,779,644 A		Eberle et al.
5,492,126 A		Hennige	5,792,058 A 5,795,297 A	8/1998 8/1998	
5,496,256 A 5,501,655 A	3/1996 3/1996		5,795,311 A	8/1998	
5,503,152 A		Oakley et al.	5,810,009 A		Mine et al.
5,503,320 A		Webster et al.	5,810,888 A	9/1998	
5,507,790 A	4/1996		5,814,599 A		Mitragotri et al.
5,511,296 A		Dias et al.	5,817,013 A 5,817,021 A		Ginn et al. Reichenberger
5,520,188 A 5,522,869 A		Hennige Burdette	5,820,564 A	10/1998	
5,523,058 A		Umemura et al.	5,823,962 A		Schaetzle
5,524,620 A		Rosenschein	5,827,204 A	10/1998	Grandia et al.
5,524,624 A	6/1996	Tepper	5,840,032 A		Hatfield et al.
5,524,625 A		Okazaki	5,844,140 A	12/1998	
5,526,624 A	6/1996		5,853,367 A 5,869,751 A	2/1998	Chalek et al. Bonin
5,526,812 A 5,526,814 A		Dumoulin et al. Cline et al.	5,871,524 A		Knowlton
5,526,815 A		Granz	5,873,902 A		Sanghvi
5,529,070 A	6/1996	Augustine et al.	5,876,341 A		Wang et al.
5,540,235 A	7/1996	Wilson	5,879,303 A		Averkiou et al.
5,558,092 A	9/1996		5,882,557 A		Hayakawa
5,560,362 A	10/1996	Sliwa et al.	5,891,034 A	4/1999	Bucholz

(56)	References Cited	6,241,753 B1*	6/2001	Knowlton A61B 18/12 128/898
211	PATENT DOCUMENTS	6,246,898 B1	6/2001	Vesely et al.
0.5.	THE COME CO	6,251,074 B1		Averkiou et al.
5,895,356 A	4/1999 Andrus et al.	6,251,088 B1	6/2001	Kaufman et al.
5,899,861 A	5/1999 Friemel et al.	6,268,405 B1	7/2001	
5,904,659 A	5/1999 Duarte	6,273,864 B1	8/2001	
5,919,219 A	7/1999 Knowlton	6,280,402 B1 6,287,257 B1		Ishibashi et al. Matichuk
5,923,099 A	7/1999 Bilir	6,287,304 B1		Eggers et al.
5,924,989 A 5,928,169 A	7/1999 Polz 7/1999 Schatzle et al.	6,296,619 B1	10/2001	Brisken
5,931,805 A	8/1999 Brisken	6,301,989 B1		Brown et al.
5,938,606 A	8/1999 Bonnefous	6,307,302 B1	10/2001	
5,938,612 A	8/1999 Kline-Schoder	6,309,355 B1		Cain et al.
5,948,011 A	9/1999 Knowlton	6,311,090 B1		Knowlton Martin A61B 8/4254
5,957,844 A	9/1999 Dekel 9/1999 Nita et al.	0,313,741 D1	11/2001	601/3
5,957,882 A 5,957,941 A	9/1999 Nita et al. 9/1999 Ream	6,322,509 B1	11/2001	Pan et al.
5,964,707 A	10/1999 Fenster et al.	6,322,532 B1	11/2001	D'Sa
5,967,980 A	10/1999 Ferre et al.			Lounsberry et al.
5,968,034 A	10/1999 Fullmer			Carol et al.
5,971,949 A	10/1999 Levin			Klopotek Edwards et al.
5,977,538 A 5,984,881 A *	11/1999 Unger et al. 11/1999 Ishibashi A61B 17/2256	6,325,798 B1 6,338,716 B1		Hossack et al.
3,304,001 A	601/2	6,350,276 B1		Knowlton
5,984,882 A	11/1999 Rosenchein	6,356,780 B1	3/2002	Licato et al.
5,990,598 A	11/1999 Sudol et al.	6,361,531 B1		Hissong
5,997,471 A	12/1999 Gumb et al.	6,370,411 B1		Osadchy et al.
5,997,497 A	12/1999 Nita et al.	6,375,672 B1 6,377,854 B1	4/2002	Aksan Knowlton
5,999,843 A 6,004,262 A	12/1999 Anbar 12/1999 Putz et al.	6,377,855 B1		Knowlton
6,007,499 A	12/1999 Martin et al.	6,381,497 B1		Knowlton
6,013,032 A	1/2000 Savord	6,381,498 B1		Knowlton
6,014,473 A	1/2000 Hossack et al.	6,387,380 B1		Knowlton
6,016,255 A	1/2000 Bolan et al.	6,390,982 B1		Bova et al.
6,019,724 A	2/2000 Gronningsaeter et al. 2/2000 Williams	6,405,090 B1 6,409,720 B1		Knowlton Hissong
6,022,308 A 6,022,327 A	2/2000 Williams 2/2000 Chang	6,413,216 B1		Cain et al.
6,030,374 A	2/2000 McDaniel	6,413,253 B1	7/2002	Koop
6,036,646 A	3/2000 Barthe	6,413,254 B1		Hissong
6,039,048 A	3/2000 Silberg	6,419,648 B1	7/2002	
6,039,689 A	3/2000 Lizzi 3/2000 Beach A61N 7/02	6,423,007 B2 6,425,865 B1		Lizzi et al. Salcudean
6,042,556 A *	5/2000 Beach AoTN //02 600/437	6,425,867 B1	7/2002	
6,049,159 A	4/2000 Barthe	6,425,912 B1		Knowlton
6,050,943 A	4/2000 Slayton	6,428,477 B1	8/2002	
6,059,727 A	5/2000 Fowlkes	6,428,532 B1 6,430,446 B1		Doukas Knowlton
6,071,239 A	6/2000 Cribbs	6,432,057 B1		Mazess et al.
6,080,108 A 6,083,148 A	6/2000 Dunham 7/2000 Williams	6,432,067 B1	8/2002	
6,086,535 A	7/2000 Ishibashi	6,432,101 B1	8/2002	
6,086,580 A	7/2000 Mordon et al.	6,436,061 B1		Costantino
6,090,054 A	7/2000 Tagishi	6,438,424 B1 6,440,071 B1		Knowlton Slayton
6,093,148 A *	3	6,440,121 B1	8/2002	
6,093,883 A	600/438 7/2000 Sanghvi	6,443,914 B1		Costantino
6,101,407 A	8/2000 Groezinger	6,447,443 B1		Keogh et al.
6,106,469 A	8/2000 Suzuki et al.	6,451,013 B1	9/2002	Bays et al.
6,113,558 A	9/2000 Rosenchein	6,453,202 B1 6,461,304 B1		Knowlton Tanaka et al.
6,113,559 A	9/2000 Klopotek			Knowlton
6,120,452 A 6,123,081 A	9/2000 Barthe 9/2000 Durette	6,470,216 B1		Knowlton
6,126,619 A	10/2000 Peterson et al.		12/2002	
6,135,971 A	10/2000 Hutchinson		12/2002	
6,139,499 A	10/2000 Wilk		12/2002	
6,159,150 A	12/2000 Yale et al.	6,500,141 B1 6,506,171 B1	1/2002	Vitek et al.
6,171,244 B1 6,176,840 B1	1/2001 Finger et al. 1/2001 Nishimura	6,508,774 B1	1/2003	
6,183,426 B1	1/2001 Nishimura 2/2001 Akisada	6,511,427 B1	1/2003	Sliwa, Jr. et al.
6,183,502 B1	2/2001 Takeuchi	6,511,428 B1		Azuma
6,183,773 B1	2/2001 Anderson	6,514,244 B2	2/2003	
6,190,323 B1	2/2001 Dias	6,517,484 B1 6,524,250 B1	2/2003 2/2003	
6,190,336 B1 6,193,658 B1	2/2001 Duarte 2/2001 Wendelken	6,540,679 B2		Slayton
6,210,327 B1	4/2001 Wenderken 4/2001 Brackett et al.	6,540,685 B1		Rhoads et al.
6,213,948 B1	4/2001 Barthe	6,540,700 B1		Fujimoto et al.
6,216,029 B1	4/2001 Paltieli	6,547,788 B1		Maguire et al.
6,233,476 B1	5/2001 Strommer et al.	6,554,771 B1		Buil et al.
6,234,990 B1	5/2001 Rowe et al.	6,569,099 B1	3/2003	Babaev

(56)	Referen	ices Cited	7,235,592			Muratoglu
U	.S. PATENT	DOCUMENTS	7,258,674 7,273,459	B2		Desilets
6 560 100 T	5/2002	G 1	7,294,125 7,297,117		11/2007 11/2007	Phalen et al. Trucco
6,569,108 H 6,572,552 H		Sarvazyan et al. Fukukita	7,303,555		12/2007	Makin et al.
6,575,956 H	6/2003	Brisken et al.	7,311,679			Desilets et al.
6,595,934 H		Hissong	7,327,071 7,331,951			Nishiyama et al. Eshel et al.
6,599,256 E 6,605,080 E		Acker Altshuler et al.	7,332,985			Larson et al.
6,607,498 H	8/2003		7,338,434			Haarstad et al.
6,618,620 H		Freundlich et al.	7,347,855 RE40,403			Eshel Cho et al.
6,623,430 H 6,626,854 H		Slayton Friedman	7,393,325			Barthe
6,626,855 H			7,398,116			Edwards
6,638,226 H		He et al.	7,399,279 7,491,171			Abend et al. Barthe et al.
6,645,150 H 6,645,162 H		Angelsen et al. Friedman	7,507,235	B2		Keogh et al.
6,662,054 H	32 12/2003	Kreindel	7,510,536		3/2009 4/2009	
6,663,627 H 6,665,806 H	32 12/2003	Francischelli Shimizu	7,517,315 7,530,356		5/2009	
6,666,835 H			7,530,958	B2	5/2009	Slayton
6,669,638 H			7,532,201 7,571,336		5/2009 8/2009	Quistgaard et al. Barthe
6,685,639 H 6,685,640 H		Wang et al.	7,601,120		10/2009	Moilanen et al.
6,692,450 H		Coleman	7,615,015	B2	11/2009	Coleman
6,699,237 H	3/2004	Weber	7,615,016		11/2009	
6,716,184 H 6,719,449 H		Vaezy et al. Laugharn, Jr. et al.	7,652,411 7,662,114			Crunkilton et al. Seip et al.
6,719,694 H			7,674,257	B2	3/2010	Pless et al.
6,726,627 H	31 4/2004	Lizzi et al.	7,686,763 7,694,406			Vaezy et al. Wildes et al.
6,733,449 E 6,749,624 E		Krishnamurthy et al. Knowlton	7,695,437		4/2010	
6,772,490 H			7,713,203			Lacoste et al.
6,773,409 H		Truckai et al.	7,727,156 7,758,524		6/2010 7/2010	Angelsen et al.
6,775,404 E 6,790,187 E		Pagoulatos et al. Thompson et al.	7,766,848	B2		Desilets et al.
6,824,516 H		Batten et al.	7,789,841			Huckle et al.
6,835,940 H		Morikawa et al.	7,806,839 7,815,570			Mast et al. Eshel et al.
6,846,290 H 6,875,176 H		Lizzi et al. Mourad	7,819,826			Diederich et al.
6,882,884 H	31 4/2005	Mosk et al.	7,824,348		11/2010	
6,887,239 E 6,889,089 E		Elstrom Bohl	7,828,734 7,833,162		11/2010 11/2010	Azhari et al. Hasegawa et al.
6,896,657 H			7,841,984	B2	11/2010	Cribbs et al.
6,902,536 H		Manna	7,846,096 7,857,773		12/2010	Mast et al. Desilets et al.
6,905,466 H 6,918,907 H			7,875,023			Eshel et al.
6,920,883 H	32 7/2005	Bessette	7,901,359			Mandrusov et al.
6,921,371 H		Wilson	7,905,007 7,905,844			Calisti et al. Desilets et al.
6,932,771 H 6,932,814 H		Whitmore Wood	7,914,453	B2	3/2011	
6,936,044 H	8/2005	McDaniel	7,914,469		3/2011	Torbati
6,936,046 E 6,945,937 E		Hissong Culp et al.	7,931,611 7,955,262		6/2011	Novak et al. Rosenberg
6,948,843 H		Laugharn et al.	7,955,281	B2	6/2011	Pedersen et al.
6,953,941 H	32 10/2005	Nakano et al.	7,967,764 7,967,839	B2		Lidgren et al.
6,958,043 H 6,971,994 H		Hissong Young et al.	7,993,289		8/2011	Flock et al. Quistgaard et al.
6,974,417 H		Lockwood	8,057,389	B2		Barthe et al.
6,976,492 H			8,057,465 8,066,641		11/2011	Sliwa, Jr. et al. Barthe et al.
6,992,305 H 6,997,923 H		Maezawa et al. Anderson	8,123,707			Huckle et al.
7,006,874 H		Knowlton	8,128,618			Gliklich et al.
7,020,528 H			8,133,180 8,133,191		3/2012 3/2012	Slayton et al. Rosenberg et al.
7,022,089 H 7,058,440 H		Heuscher et al.	8,142,200		3/2012	Crunkilton et al.
7,063,666 H	32 6/2006	Weng	8,152,904		4/2012	Slobodzian et al.
7,070,565 H 7,074,218 H		Vaezy et al. Washington et al.	8,162,858 8,166,332			Manna et al. Barthe et al.
7,074,218 I 7,094,252 I			8,182,428	B2	5/2012	Angelsen et al.
7,108,663 H	9/2006	Talish et al.	8,197,409			Foley et al.
7,115,123 H 7,122,029 H		Knowlton Koop et al.	8,206,299 8,208,346			Foley et al. Crunkilton
7,122,029 F 7,142,905 F		Slayton	8,211,017		7/2012	
7,165,451 H	1/2007	Brooks et al.	8,262,591	B2	9/2012	Pedersen et al.
7,179,238 H 7,189,230 H		Hissong Knowlton	8,262,650 8,264,126			Zanelli et al. Toda et al.
7,189,230 F 7,229,411 F		Slayton	8,204,120			Kreindel et al.
,,			, ,			

(56)	Referen	ices Cited		2002/0002345			Marlinghaus	
U.S.	PATENT	DOCUMENTS		2002/0040199 2002/0040442	A1	4/2002	Klopotek Ishidera	
8,282,554 B2	10/2012	Makin et al.		2002/0055702 2002/0062077		5/2002 5/2002	Atala Emmenegger	
8,292,835 B1		Cimino		2002/0062142	A1	5/2002	Knowlton	
8,298,163 B1	10/2012			2002/0072691			Thompson et al. Friedman	
8,333,700 B1 8,334,637 B2		Barthe et al. Crunkilton et al.		2002/0082528 2002/0082529			Suorsa et al.	
8,337,407 B2		Quistgaard et al.		2002/0082589	A1		Friedman	
8,343,051 B2	1/2013	Desilets et al.		2002/0087080 2002/0095143		7/2002	Slayton	
8,366,622 B2 8,388,535 B2		Slayton et al. Weng et al.		2002/0093143		7/2002 7/2002	Anderson	
8,409,097 B2		Slayton et al.		2002/0115917	A1	8/2002	Honda et al.	
8,425,435 B2	4/2013	Wing et al.		2002/0128639 2002/0128648		9/2002 9/2002	Pless et al.	
8,444,562 B2 8,454,540 B2		Barthe et al. Eshel et al.		2002/0128048			Dunne et al.	
8,460,193 B2		Barthe et al.		2002/0156400	A1	10/2002		
8,480,585 B2		Slayton et al.		2002/0161357 2002/0165529		10/2002 11/2002	Anderson	
8,506,486 B2 8,512,250 B2		Slayton et al. Quistgaard et al.		2002/0103329			Schriever	
8,523,775 B2		Barthe et al.		2002/0169394			Eppstein et al.	
8,535,228 B2	9/2013	Slayton et al.		2002/0169442 2002/0173721		11/2002	Neev Grunwald et al.	
8,570,837 B2 8,573,392 B2		Toda et al. Bennett et al.		2002/01/3721			McHale et al.	
8,583,211 B2		Salomir et al.		2002/0193831		12/2002		
8,585,618 B2		Hunziker et al.		2003/0009153 2003/0014039			Brisken et al. Barzell et al.	
8,604,672 B2 8,622,937 B2		Toda et al. Weng et al.		2003/0014039		1/2003		
8,636,665 B2		Slayton et al.		2003/0018270			Makin et al.	
8,641,622 B2		Barthe et al.		2003/0023283	Al*	1/2003	McDaniel	. A61K 8/02 607/88
8,663,112 B2 8,672,848 B2		Slayton et al. Slayton et al.		2003/0028111	A1	2/2003	Vaezy et al.	007/00
8,690,778 B2	4/2014	Slayton et al.		2003/0028113			Gilbert et al.	
8,690,779 B2		Slayton et al.		2003/0032900 2003/0036706		2/2003	Ella Slayton et al.	
8,690,780 B2 8,708,935 B2		Slayton et al. Barthe et al.		2003/0040739		2/2003	Koop	
8,715,186 B2	5/2014	Slayton et al.		2003/0050678		3/2003		
8,726,781 B2 8,728,071 B2		Eckhoff et al. Lischinsky et al.		2003/0055417 2003/0060736			Truckai et al. Martin et al.	
8,753,295 B2		Thierman		2003/0065313	A1	4/2003	Koop	
8,758,253 B2		Sano et al.		2003/0066708 2003/0073907		4/2003 4/2003	Allison et al.	
8,836,203 B2 8,857,438 B2		Nobles et al. Barthe et al.		2003/0073907			Kaplan	
8,858,471 B2		Barthe et al.		2003/0083536		5/2003		
8,915,853 B2 8,915,854 B2		Barthe et al.		2003/0092988 2003/0097071		5/2003 5/2003	Makin Halmann et al.	
8,915,870 B2		Slayton et al. Barthe et al.		2003/0099383			Lefebvre	
8,920,320 B2		Stecco et al.		2003/0125629 2003/0135135			Ustuner Miwa et al.	
8,920,324 B2 8,926,533 B2	1/2014	Slayton et al. Bockenstedt et al.		2003/0133133			Ingle et al.	
8,932,224 B2		Barthe et al.		2003/0153961	A1	8/2003	Babaev	
8,932,238 B2		Wing et al.		2003/0171678 2003/0171701			Batten et al. Babaev	
8,968,205 B2 9,011,336 B2		Zeng et al. Slayton et al.		2003/0171701			Slayton	
9,039,617 B2		Slayton et al.		2003/0191396	A1	10/2003	Sanghvi	
9,039,619 B2		Barthe et al. Barthe et al.		2003/0200481 2003/0212129		10/2003	Stanley Liu et al.	
9,095,697 B2 9,114,247 B2		Barthe et al.		2003/0212123		11/2003		
9,272,162 B2	3/2016	Slayton et al.		2003/0212393			Knowlton	
9,283,409 B2 9,283,410 B2		Slayton et al. Slayton et al.		2003/0216648 2003/0216795		11/2003	Lizzi et al. Harth	
9,320,537 B2		Slayton et al.		2003/0220536	A1	11/2003	Hissong	
9,421,029 B2	8/2016	Barthe et al.		2003/0220585 2003/0229331			Hissong Brisken et al.	
9,427,600 B2 9,427,601 B2		Barthe et al. Barthe et al.		2003/0229331			Giammarusti	
9,440,096 B2	9/2016	Barthe et al.		2003/0236487	A1		Knowlton	
9,510,802 B2 9,522,290 B2		Barthe et al. Slayton et al.		2004/0000316 2004/0001809			Knowlton Brisken	
9,522,290 B2 9,533,175 B2		Slayton et al.		2004/0002658			Marian, Jr.	
2001/0009997 A1	7/2001	Pope		2004/0002705			Knowlton	
2001/0009999 A1 2001/0014780 A1		Kaufman et al. Martin		2004/0010222 2004/0015079			Nunomura et al. Berger et al.	
2001/0014819 A1	8/2001	Ingle		2004/0015106		1/2004	Coleman	
2001/0031922 A1*	10/2001	Weng		2004/0030227		2/2004	1	
2001/0039380 A1	11/2001	Larson et al.	600/439	2004/0039312 2004/0039418			Hillstead Elstrom	
2001/0041880 A1	11/2001	Brisken		2004/0041563			Lewin et al.	
2002/0000763 A1	1/2002	Jones		2004/0041880	A1	3/2004	Ikeda et al.	

(56)	Referen	ices Cited	2006/0074355		4/2006	
11.0	DATEDATE	DOCUMENTO	2006/0079816		4/2006	
U.S.	PATENT	DOCUMENTS	2006/0079868 2006/0084891		4/2006 4/2006	
2004/0042169 41	2/2004	37	2006/0089632		4/2006	
2004/0042168 A1 2004/0044375 A1		Yang et al. Diederich et al.	2006/0089688			Panescu
2004/0049134 A1		Tosaya et al.	2006/0094988	A1	5/2006	
2004/0059266 A1	3/2004		2006/0111744	A1	5/2006	
2004/0068186 A1		Ishida et al.	2006/0116583			Ogasawara et al.
2004/0073079 A1		Altshuler et al.	2006/0116671			Slayton
2004/0073113 A1	4/2004		2006/0122508 2006/0122509			Slayton Desilets
2004/0073115 A1		Horzewski et al.	2006/0122303			Arditi et al.
2004/0073116 A1 2004/0073204 A1	4/2004	Ryan et al.	2006/0184069			Vaitekunas
2004/0073204 A1 2004/0077977 A1		Ella et al.	2006/0184071	A1	8/2006	Klopotek
2004/0082857 A1		Schonenberger	2006/0189972			Grossman
2004/0082859 A1		Schaer	2006/0206105		9/2006	
2004/0102697 A1	5/2004		2006/0224090 2006/0229514		10/2006	Ostrovsky et al.
2004/0105559 A1		Aylward et al.	2006/0229314		10/2006	
2004/0106867 A1 2004/0122323 A1		Eshel et al. Vortman et al.	2006/0241442		10/2006	
2004/0122323 A1 2004/0122493 A1		Ishibashi et al.	2006/0241470			Novak et al.
2004/0143297 A1		Ramsey	2006/0241576			Diederich et al.
2004/0152982 A1	8/2004	Hwang et al.	2006/0250046			Koizumi et al.
2004/0158150 A1		Rabiner et al.	2006/0282691		12/2006	
2004/0186535 A1		Knowlton	2006/0291710 2007/0032784			Wang et al. Gliklich et al.
2004/0189155 A1		Funakubo	2007/0032784			Desilets
2004/0206365 A1 2004/0210214 A1		Knowlton Knowlton	2007/0055154		3/2007	
2004/0210214 A1 2004/0217675 A1		Desilets	2007/0055155	A1	3/2007	Owen et al.
2004/0249318 A1	12/2004		2007/0055156			Desilets et al.
2004/0254620 A1	12/2004	Lacoste	2007/0065420		3/2007	Johnson
2004/0267252 A1		Washington et al.	2007/0083120 2007/0087060			Cain et al. Dietrich
2005/0033201 A1		Takahashi	2007/0087000			Babaev et al.
2005/0033316 A1 2005/0038340 A1	2/2005	Vaezy et al.	2007/0088346			Mirizzi et al.
2005/0055018 A1		Kreindel	2007/0161902		7/2007	
2005/0055073 A1		Weber	2007/0166357	A1	7/2007	Shaffer et al.
2005/0061834 A1		Garcia et al.	2007/0167709			Slayton
2005/0070961 A1	3/2005		2007/0208253			Slayton
2005/0074407 A1	4/2005		2007/0219604 2007/0219605			Yaroslavsky et al. Yaroslavsky et al.
2005/0080469 A1 2005/0091770 A1		Larson Mourad et al.	2007/0238994		10/2007	
2005/0091770 A1 2005/0096542 A1		Weng et al.	2007/0239075			Rosenberg
2005/0104690 A1		Larson et al.	2007/0239077	A1	10/2007	Azhari et al.
2005/0113689 A1		Gritzky	2007/0239079			Manstein et al.
2005/0131302 A1		Poland	2007/0239142			Altshuler
2005/0137656 A1		Malak	2008/0015435 2008/0027328			Cribbs et al. Klopotek
2005/0143677 A1 2005/0154313 A1		Young et al. Desilets	2008/0039724			Seip et al.
2005/0154314 A1		Quistgaard	2008/0071255		3/2008	
2005/0154332 A1		Zanelli	2008/0086054			Slayton
2005/0154431 A1		Quistgaard	2008/0086056			Chang et al.
2005/0187495 A1		Quistgaard	2008/0097214			Meyers et al.
2005/0191252 A1		Mitsui	2008/0097253 2008/0114251			Pedersen et al. Weymer et al.
2005/0193451 A1 2005/0193820 A1		Quistgaard Sheljaskow et al.	2008/0139974			Da Silva
2005/0197681 A1		Barolet et al.	2008/0146970	A1	6/2008	Litman et al.
2005/0228281 A1	10/2005		2008/0167556			Thompson
2005/0240127 A1		Seip et al.	2008/0183077			Moreau-Gobard et al.
2005/0240170 A1		Zhang et al.	2008/0183110 2008/0188745			Davenport et al. Chen et al.
2005/0251120 A1		Anderson et al.	2008/0194964			Randall et al.
2005/0251125 A1 2005/0256406 A1	11/2005	Pless et al.	2008/0195000			Spooner et al.
2005/0261584 A1	11/2005		2008/0200810	A1		Buchalter
2005/0261585 A1		Makin et al.	2008/0200813			Quistgaard
2005/0267454 A1		Hissong	2008/0214966			•
2005/0288748 A1		Li et al.	2008/0221491 2008/0223379			Slayton Stuker et al.
2006/0004306 A1		Altshuler	2008/0242991			Moon et al.
2006/0020260 A1 2006/0025756 A1		Dover et al. Francischelli	2008/0243035			Crunkilton
2006/0023730 A1 2006/0042201 A1	3/2006		2008/0269608			Anderson et al.
2006/0058664 A1		Barthe	2008/0275342		11/2008	
2006/0058671 A1		Vitek et al.	2008/0281206	A1	11/2008	Bartlett et al.
2006/0058707 A1		Barthe	2008/0281236			Eshel et al.
2006/0058712 A1		Altshuler et al.	2008/0281237		11/2008	
2006/0074309 A1		Bonnefous	2008/0281255		11/2008	•
2006/0074313 A1		Slayton et al.	2008/0294073		11/2008	
2006/0074314 A1	4/2006	Slayton	2008/0319356	ΑI	12/2008	Cain

(56)	References Cited	2012/0165848 A1		Slayton et al.
11.9	S. PATENT DOCUMENTS	2012/0191020 A1 2012/0197120 A1	7/2012 8/2012	Vitek et al. Makin et al.
0.1	5. TATENT DOCUMENTS	2012/0197121 A1	8/2012	Slayton et al.
2009/0005680 A1	1/2009 Jones et al.	2012/0209150 A1		Zeng et al.
2009/0012394 A1		2012/0215105 A1 2012/0271202 A1	8/2012	Slayton et al. Wisdom
2009/0043198 A1 2009/0043293 A1		2012/0271294 A1	10/2012	
2009/0048514 A1		2012/0296240 A1	11/2012	Azhari et al.
2009/0069677 A1		2012/0302883 A1		Kong et al. Foley et al.
2009/0093737 A1 2009/0156969 A1		2012/0316426 A1 2012/0330197 A1	12/2012	
2009/0163807 A1	υ	2012/0330222 A1	12/2012	Makin et al.
2009/0171252 A1		2012/0330223 A1 2012/0330283 A1		Makin et al. Hyde et al.
2009/0177122 A1 2009/0177123 A1		2012/0330283 A1 2012/0330284 A1		Hyde et al.
2009/017/123 A1 2009/0182231 A1		2013/0012755 A1	1/2013	Slayton
2009/0198157 A1	8/2009 Babaev et al.	2013/0012816 A1	1/2013	
2009/0216159 A1	•	2013/0012838 A1 2013/0012842 A1	1/2013 1/2013	Jaeger et al. Barthe
2009/0226424 A1 2009/0227910 A1		2013/0018285 A1	1/2013	
2009/0230823 A1	9/2009 Kushculey et al.	2013/0018286 A1	1/2013	
2009/0253988 A1		2013/0046209 A1 2013/0051178 A1	2/2013 2/2013	Slayton et al. Rybyanets
2009/0281463 A1 2009/0312693 A1	1	2013/0060170 A1		Lee et al.
2009/0318909 A1		2013/0066208 A1	3/2013	Barthe et al.
2009/0326420 A1		2013/0066237 A1 2013/0072826 A1	3/2013 3/2013	
2010/0011236 A1 2010/0022919 A1		2013/0096471 A1	4/2013	,
2010/0022913 A1		2013/0190659 A1	7/2013	Slayton et al.
2010/0022922 A1		2013/0211293 A1 2013/0225994 A1	8/2013	Auboiroux et al. Hsu et al.
2010/0030076 A1 2010/0042020 A1		2013/0223994 A1 2013/0268032 A1	10/2013	
2010/0042020 A1 2010/0049178 A1		2013/0274603 A1		Barthe et al.
2010/0056925 A1		2013/0281853 A1	10/2013	
2010/0100014 A1		2013/0281891 A1 2013/0296697 A1	10/2013 11/2013	Slayton et al. Slayton et al.
2010/0113983 A1 2010/0130891 A1		2013/0296700 A1	11/2013	Slayton et al.
2010/0160782 A1	6/2010 Slayton et al.	2013/0303904 A1	11/2013	Barthe et al.
2010/0160837 A1 2010/0168576 A1		2013/0303905 A1 2013/0310714 A1		Barthe et al. Eshel et al.
2010/0108376 A1 2010/0191120 A1		2013/0310863 A1	11/2013	Makin et al.
2010/0241035 A1	9/2010 Barthe et al.	2013/0345562 A1		Barthe et al.
2010/0249602 A1	•	2014/0024974 A1 2014/0050054 A1	2/2014	Slayton et al. Toda et al.
2010/0249669 A1 2010/0256489 A1		2014/0081300 A1	3/2014	Melodelima et al.
2010/0274161 A1	10/2010 Azhari et al.	2014/0082907 A1		Barthe et al.
2010/0280420 A1		2014/0117814 A1 2014/0142430 A1	5/2014 5/2014	
2010/0286518 A1 2010/0312150 A1		2014/0148834 A1	5/2014	Barthe et al.
2011/0040171 A1	2/2011 Foley et al.	2014/0180174 A1	6/2014	Slayton et al.
2011/0040190 A1		2014/0187944 A1 2014/0188015 A1		Slayton et al. Slayton et al.
2011/0066084 A1 2011/0087099 A1		2014/0188145 A1	7/2014	
2011/0087255 A1		2014/0194723 A1		Herzog et al.
2011/0112405 A1		2014/0208856 A1 2014/0221823 A1		Schmid Keogh et al.
2011/0144490 A1 2011/0178444 A1		2014/0236049 A1		Barthe et al.
2011/0178541 A1	7/2011 Azȟari	2014/0236061 A1		Lee et al.
2011/0190745 A1		2014/0243713 A1 2014/0257145 A1	8/2014 9/2014	Slayton et al. Emery
2011/0251524 A1 2011/0251527 A1		2014/0276055 A1		Barthe et al.
2011/0270137 A1		2015/0000674 A1		Barthe et al.
2011/0319793 A1		2015/0080723 A1 2015/0080771 A1		Barthe et al. Barthe et al.
2012/0004549 A1 2012/0016239 A1		2015/0080874 A1	3/2015	
2012/0029353 A1		2015/0088182 A1	3/2015	
2012/0035473 A1		2015/0164734 A1 2015/0165238 A1	6/2015 6/2015	
2012/0035475 A1 2012/0035476 A1		2015/0105238 A1 2015/0165243 A1	6/2015	Slayton et al.
2012/0035476 A1 2012/0046547 A1		2015/0174388 A1	6/2015	Slayton
2012/0053458 A1	3/2012 Barthe et al.	2015/0202468 A1	7/2015	•
2012/0111339 A1 2012/0123304 A1		2015/0217141 A1 2015/0360058 A1	8/2015 12/2015	Barthe et al. Barthe et al.
2012/0123304 A1 2012/0136280 A1	• •	2015/0374333 A1		Barthe et al.
2012/0136282 A1	5/2012 Rosenberg et al.	2015/0375014 A1	12/2015	Slayton et al.
2012/0143056 A1		2016/0027994 A1	1/2016	Toda et al.
2012/0143100 A1		2016/0175619 A1 2016/0206335 A1		Lee et al. Slayton
2012/0165668 A1	6/2012 Slayton et al.	2010/0200333 AI	112010	Siayton

US 9,694,211 B2

Page 9

(56)	Referen	ices Cited	ĴΡ	2005503388	2/2005
	IIS PATENT	DOCUMENTS	JР JР	2005527336 2005323213	9/2005 11/2005
	O.S. TAILIN	DOCOMENTS	JP	2006520247	9/2006
		Slayton	JP	2008515559	5/2008
	256675 A1 9/2016		JP	2009518126	5/2009
2016/0	296769 A1 10/2016	Barthe et al.	JP KR	2010517695	5/2010
	FOREIGN PATE	NT DOCUMENT		1020010024871 100400870	3/2001 10/2003
	TOREIGN TATE	NI DOCUMENT	KR KR	1020060113930	11/2006
DE	10140064	3/2003	KR	1020070065332	6/2007
DE	10219297	11/2003	KR	1020070070161	7/2007
DE DE	10219217 20314479	12/2004 12/2004	KR KR	1020070098856 1020070104878	10/2007 10/2007
EP	0142215	5/1984	KR KR	1020070104878	11/2007
EP	0344773	12/1989	KR	1020000059516	4/2012
EP EP	1479412 0473553	11/1991 4/1992	WO	WO9312742	7/1993
EP	670147	2/1995	WO	WO9524159	9/1995
EP	0661029	7/1995	WO WO	WO9625888 WO9634568	8/1996 11/1996
EP EP	724894 762271	2/1996	WO	WO9639079	12/1996
EP EP	763371 1044038	11/1996 10/2000	WO	WO9735518	10/1997
EP	1050322	11/2000	WO	WO9832379	7/1998
EP	1234566	8/2002	WO	WO9852465	11/1998
EP EP	1262160 1283690	12/2002 2/2003	WO	WO9933520	7/1999
EP	0659387	4/2003	WO	WO9949788	10/1999
EP	1374944	1/2004	WO WO	WO0006032 WO0015300	2/2000 3/2000
EP EP	1028660 1874241	1/2008 1/2008	WO	WO0013300 WO0021612	4/2000
EP EP	1362223	5/2008	WO	WO0053113	9/2000
EP	1750804	7/2008	WO	WO0128623	4/2001
EP	1811901	4/2009	WO	WO0145550	6/2001
EP EP	1785164 2230904	8/2009 9/2010	WO	WO0180709	11/2001
EP	1501331	6/2011	WO WO	WO0182777 WO0182778	11/2001 11/2001
EP	2066405	11/2011	WO	WO0182778 WO0187161	11/2001
EP FR	2474050 2532851	7/2012 9/1983	WO	WO0209813	2/2002
FR	2685872	1/1992	WO	WO0215768	2/2002
FR	2672486	8/1992	WO	WO0224050	3/2002
FR GB	2703254 2113099	3/1994 8/1983	WO	WO02092168	11/2002
IL	102516	1/1996	WO WO	WO03053266 WO03065347	7/2003 8/2003
IL	112369	8/1999	WO	WO03070105	8/2003
IL JP	120079 63036171	3/2001 2/1988	WO	WO02054018	9/2003
JР	03048299	3/1991	WO	WO03077833	9/2003
JP	3123559	5/1991	WO	WO03086215	10/2003
JP JP	03136642 4089058	6/1991 3/1992	WO	WO03096883	11/2003
JP JP	04150847	5/1992	WO WO	WO03099177 WO03099382	12/2003 12/2003
JP	7080087	3/1995	WO	WO03101530	12/2003
JР	07505793	6/1995	WO	WO04000116	12/2003
JP JP	7184907 7222782	7/1995 8/1995	WO	WO2004080147	9/2004
JР	09047458	2/1997	WO	WO2004110558	12/2004
JР	9108288	4/1997	WO	WO2005/011804	2/2005
JP JP	9503926 11123226	4/1997 5/1999	WO WO	WO2005065408 WO2005090978	7/2005 9/2005
JР	11505440	5/1999	WO	WO2005030978	12/2005
JP	11506636	6/1999	WO	WO2006/042163	4/2006
JP JP	10248850 2000126310	9/1999 5/2000	WO	WO2006036870	4/2006
JР	2000120310	6/2000	WO	WO2006042168	4/2006
JP	2000233009	8/2000	WO	WO2006042201	4/2006
JP JP	2001170068 2002505596	6/2001 2/2002	WO WO	WO2006065671 WO2006082573	6/2006 8/2006
JP JP	2002505596 2002078764	2/2002 3/2002	WO	WO 2006104568	10/2006
JP	2002515786	5/2002	WO	WO2007067563	6/2007
JP	2002521118	7/2002	WO	WO2008036622	3/2008
JP JP	2002537939 2003050298	11/2002 7/2003	WO	WO2008036479	11/2008
JР	2003204982	7/2003	WO	WO2009013729	1/2009
JP	2004-507280	3/2004	WO WO	WO2009149390 WO2008144274	10/2009 1/2010
JP JP	2004-509671 2004-512856	4/2004 4/2004	WO WO	WO2008144274 WO2012134645	1/2010
JP JP	2004-312836	4/2004 5/2004	WO	WO2012134043 WO2014045216	3/2014

(56) References Cited

FOREIGN PATENT DOCUMENTS

WO WO2014055708 4/2014 WO WO2014057388 4/2014

OTHER PUBLICATIONS

Arthur et al., "Non-invasive estimation of hyperthermia temperatures with ultrasound," Int. J. Hyperthermia, Sep. 2005, 21(6), pp. 589-600

Barthe et al., "Ultrasound therapy system and ablation results utilizing miniature imaging/therapy arrays," Ultrasonics Symposium, 2004 IEEE, Aug. 23, 2004, pp. 1792-1795, vol. 3.

Bozec, Laurent et al., Thermal Denaturation Studies of Collagen by Microthermal Analysis and Atomic Force Microscopy, Biophysical Journal, vol. 101, pp. 228-236. (Jul. 2001).

Calderhead et al., "One Mechanism Behind LED Photo-Therapy for Wound Healing and Skin Rejuvenation: Key Role of the Mast Cell" Laser Therapy 17.3: 141-148 (2008).

Chen, L. et al., "Effect of Blood Perfusion on the ablation of liver parenchyma with high intensity focused ultrasound," Phys. Med. Biol; 38:1661-1673; 1993b.

Coon, Joshua et al., "Protein identification using sequential ion/ion reactions and tandem mass spectrometry" Proceedings of the National Academy of Sciences of the USA, vol. 102, No. 27, Jul. 27, 2005, pp. 9463-9468.

Corry, Peter M., et al., "Human Cancer Treatment with Ultrasound", IEEE Transactions on Sonics and Ultrasonics, vol. SU-31, No. 5, Sep. 1984, pp. 444, 456.

Damianou et al., "Application of the Thermal Dose Concept for Predicting the Necrosed Tissue Volume During Ultrasound Surgery," 1993 IEEE Ultrasound Symposium, pp. 1199-1202.

Daum et al., Design and Evaluation of a Feedback Based Phased Array System for Ultrasound Surgery, IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control, vol. 45, No. 2, Mar. 1998, pp. 431-438.

Davis, Brian J., et al., "An Acoustic Phase Shift Technique for the Non-Invasive Measurement of Temperature Changes in Tissues", 1985 Ultrasonics Symposium, pp. 921-924.

Decision of the Korean Intellectual Property Tribunal dated Jun. 28, 2013 regarding Korean Patent No. 10-1142108 (English translation, English translation certification, and Korean decision included).

Dierickx, Christine C., "The Role of Deep Heating for Noninvasive Skin Rejuvenation" Lasers in Surgery and Medicine 38:799-807 (2006).

Dong, Yuan-Lin et al., "Effect of Ibuprofen on the Inflammatory Response To Surgical Wounds" The Journal of Trauma, vol. 35, No. 3. (1993).

Dvivedi, Sanjay, et al. "Effect of Ibuprofen and diclofenac sodium on experimental wound healing" Indian Journal of Experimental Biology, vol. 35, pp. 1243-1245. (Nov. 1997).

Fry, W.J. et al., "Production of Focal Destructive Lesions in the Central Nervous System with Ultrasound," J. Neurosurg., 11:471-478; 1954.

Gliklich et al., Clinical Pilot Study of Intense Ultrasound therapy to Deep Dermal Facial Skin and Subcutaneous Tissues, Arch Facial Plastic Surgery, Mar. 1, 2007, vol. 9, No. 1.

Greenhalgh, David G., "Wound healing and diabetes mellitus" Clinics in Plastic Surgery 30; 37-45. (2003).

Guo, S. et al., "Factors Affecting Wound Healing" Critical Reviews in Oral Biology & Medicine, J Dent Res 89(3), pp. 219-229. (2010). Haar, G.R. et al., "Tissue Destruction with Focused Ultrasound in Vivo," Eur. Urol. 23 (suppl. 1):8-11; 1993.

Hantash, Basil M. et al., "Bipolar Fractional Radiofrequency Treatment Induces Neoelastogenesis and Neocollagenesis" Lasers in Surgery and Medicine 41:1-9 (2009).

Hantash, Basil M. et al., "In Vivo Histological Evaluation of a Novel Ablative Fractional Resurfacing Device" Lasers in Surgery and Medicine 39:96-107 (2007).

Hassan et al., "Structure and Applications of Poly(vinyl alcohol) Hydrogels Produced by Conventional Crosslinking or by Freezing/Thawing Methods," advanced in Polymer Science, 2000, pp. 37-65, vol. 153.

Hassan et al., "Structure and Morphology of Freeze/Thawed PVA Hydrogels," Macromolecules, Mar. 11, 2000, pp. 2472-2479, vol. 33, No. 7.

Husseini et al, "The Role of Cavitation in Acoustically Activated Drug Delivery," J. Control Release, Oct. 3, 2005, pp. 253-261, vol. 107(2).

Husseini et al. "Investigating the mechanism of acoustically activated uptake of drugs from Pluronic micelles," BMD Cancer 2002, 2:20k, Aug. 30, 2002, pp. 1-6.

Jeffers et al., "Evaluation of the Effect of Cavitation Activity on Drug-Ultrasound Synergisms," 1993 IEEE Ultrasonics Symposium, pp. 925-928.

Jenne, J., et al., "Temperature Mapping for High Energy US-Therapy", 1994 Ultrasonics Symposium, pp. 1879-1882.

Johnson, S.A., et al., "Non-Intrusive Measurement of Microwave and Ultrasound-Induced Hyperthermia by Acoustic Temperature Tomography", Ultrasonics Symposium Proceedings, pp. 977-982. (1977).

Krischak, G.D., et al., "The effects of non-steroidal anti-inflammatory drug application on incisional wound healing in rats" Journal of Wound Care, vol. 6, No. 2, (Feb. 2007).

Lin, Sung-Jan, et al., "Monitoring the thermally induced structural transitions of collagen by use of second-harmonic generation microscopy" Optics Letters, vol. 30, No. 6, (Mar. 15, 2005).

Madersbacher, S. et al., "Tissue Ablation in Benign Prostatic Hyperplasia with High Intensity Focused Ultrasound," Dur. Urol., 23 (suppl. 1):39-43; 1993.

Makin et al, "B-Scan Imaging and Thermal Lesion Monitoring Using Miniaturized Dual-Functionality Ultrasound Arrays," Ultrasonics Symposium, 2004 IEEE, Aug. 23, 2004, pp. 1788-1791, vol.

Makin et al, "Confirmed Bulk Ablation and Therapy Monitoring Using Intracorporeal Image-Treat Ultrasound Arrays," 4th International Symposium on Therapeutic Ultrasound, Sep. 19, 2004.

Makin et al., "Miniaturized Ultrasound Arrays for Interstitial Ablation and Imaging," UltraSound Med. Biol. 2005, Nov. 1, 2005, pp. 1539-1550, vol. 31(11).

Manohar et al, "Photoacoustic mammography laboratory prototype: imaging of breast tissue phantoms," Journal of Biomedical Optics, Nov./Dec. 2004, pp. 1172-1181, vol. 9, No. 6.

Mast et al, "Bulk Ablation of Soft Tissue with Intense Ultrasound; Modeling and Experiments," J. Acoust. Soc. Am., Oct. 1, 2005, pp. 2715-2724, vol. 118(4).

Meshkinpour, Azin, et al., "Treatment of Hypertrophic Scars and Keloids With a Radiofrequency Device: A Study of Collagen Effects" Lasers in Surgery and Medicine 37:343-349 (2005).

Mitragotri, S., "Healing sound: the use of ultrasound in drug delivery and other therapeutic applications," Nature Reviews; Drug Delivery, pp. 255-260, vol. 4 (Mar. 2005).

Mosser, David M. et al., "Exploring the full spectrum of macrophage activation" Nat Rev Immunol; 8(12): 958-969. (Dec. 2008). Murota, Sei-Itsu, et al., "Stimulatory Effect of Prostaglandins on the Production of Hexosamine-Containing Substances by Cultured Fibroblasts (3) Induction of Hyaluronic Acid Synthetase by Prostaglandin" Department of Pharmacology, Tokyo Metropolitan Institute of Gerontology, Itabashiku, Tokyo-173, Japan. (Nov. 1977, vol. 14, No. 5).

Murota, Sei-Itsu, et al., "The Stimulatory Effect of Prostaglandins on Production of Hexosamine-Containing Substances by Cultured Fibroblasts" Department of Pharmacology, Tokyo Metropolitan Institute of Gerontology, Itabashiku, Tokyo-173, Japan. (Aug. 1976, vol. 12, No. 2).

Paradossi et al., "Poly(vinyl alcohol) as versatile biomaterial for potential biomedical applications," Journal of Materials Science: Materials in Medicine, 2003, pp. 687-691, vol. 14.

Rappolee, Daniel A., et al., "Wound Macrophages Express TGF and Other Growth Factors in Vivo: Analysis by mRNA Phenotyping" Science, vol. 241, No. 4866 (Aug. 1988).

(56) References Cited

OTHER PUBLICATIONS

Reid, Gavin, et al., "Tandem Mass spectrometry of ribonuclease A and B: N-linked glycosylation site analysis of whole protein ions," Analytical Chemistry. Feb. 1, 2002, vol. 74, No. 3, pp. 577-583. Righetti et al, "Elastographic Characterization of HIFU-Induced Lesions in Canine Livers," 1999, Ultrasound in Med & Bio, vol. 25, No. 7, pp. 1099-1113.

Rosenberg, Carol S. "Wound Healing in the Patient with Diabetes Mellitus" Nursing Clinics of North America, vol. 25, No. 1, (Mar. 1990)

Saad et al., "Ultrasound-Enhanced Effects of Adriamycin Against Murine Tumors," Ultrasound in Med. & Biol. vol. 18, No. 8, pp. 715-723 (1992).

Sandulache, Vlad C. et al., "Prostaglandin E2 inhibition of keloid fibroblast migration, contraction, and transforming growth factor (TGF)—B1—induced collagen synthesis" Wound Rep Reg 15 122-133, 2007. (2007).

Sanghvi, N.T., et al., "Transrectal Ablation of Prostrate Tissue Using Focused Ultrasound," 1993 Ultrasonics Symposium, IEEE, pp. 1207-1210

Sassen, Sander, "ATI's R520 architecture, the new king of the hill?" http://www.hardwareanalysis.com/content/article/1813, Sep. 16, 2005, 2 pages.

Seip, Ralf, et al., "Noninvasive Detection of Thermal Effects Due to Highly Focused Ultrasonic Fields," IEEE Symposium, pp. 1229-1232, vol. 2, Oct. 3-Nov. 1993.

Seip, Ralf, et al., "Noninvasive Estimation of Tissue Temperature Response to Heating Fields Using Diagnostic Ultrasound," IEEE Transactions on Biomedical Engineering, vol. 42, No. 8, Aug. 1995, pp. 828-839.

Simon et al., "Applications of Lipid-Coated Microbubble Ultrasonic Contrast to Tumor Therapy," Ultrasound in Med. & Biol. vol. 19, No. 2, pp. 123-125 (1993).

Smith, Nadine Barrie, et al., "Non-invasive In Vivo Temperature Mapping of Ultrasound Heating Using Magnetic Resonance Techniques", 1994 Ultrasonics Symposium, pp. 1829-1832, vol. 3.

Suh, D.H., et. al., "Intense Focused Ultrasound Tightening in Asian Skin: Clinical and Pathologic Results" American Society for Dermatologic Surgery, Inc.; 37:1595-1602. (2011).

Surry et al., "Poly(vinyl alcohol) cryogel phantoms for use in ultrasound and MR imaging," Phys. Med. Biol., Dec. 6, 2004, pp. 5529-5546, vol. 49.

Syka J. E. P. et al., "Peptide and Protein Sequence Analysis by Electron Transfer Dissociation Mass Spectrometry," Proceedings of the National Academy of Sciences of USA, National Academy of Science, Washington, DC, vol. 101, No. 26, Jun. 29, 2004, pp. 9528-9533.

Talbert, D. G., "An Add-On Modification for Linear Array Real-Time Ultrasound Scanners to Produce 3D Displays," UTS Int'l 1977 Brighton, England (Jun. 28-30, 1977) pp. 57-67.

Tata et al., "Interaction of Ultrasound and Model Membrane Systems: Analyses and Predictions," American Chemical Society, Phys. Chem. 1992, 96, pp. 3548-3555.

Ueno, S., et al., "Ultrasound Thermometry in Hyperthermia", 1990 Ultrasonic Symposium, pp. 1645-1652.

Verhofstad, Michiel H.J. et al., "Collagen Synthesis in rat skin and ileum fibroblasts is affected differently by diabetes-related factors" Int. J. Exp. Path. (1998), 79, 321-328.

Wang, H., et al., "Limits on Focused Ultrasound for Deep Hyperthermia", 1994 Ultrasonic Symposium, Nov. 1-4, 1994, pp. 1869-1872, vol. 3.

Wasson, Scott, "NVIDIA's GeForce 7800 GTX graphics processor Power MADD," http://techreport.com/reviews/2005q2/geforce-7800gtx/index.x?pg=1, Jun. 22, 2005, 4 pages.

White et al "Selective Creating of Thermal Injury Zones in the Superficial Musculoaponeurotic System Using Intense Ultrasound Therapy," Arch Facial Plastic Surgery, Jan./Feb. 2007, vol. 9, No. 1 (pp. 22-29).

White, W. Matthew, et al., "Selective Transcutaneous Delivery of Energy to Porcine Soft Tissues Using Intense Ultrasound (IUS)" Lasers in Surgery and Medicine 40:67-75 (2008).

Zelickson, Brian D. et al., "Histological and Ultrastructural Evaluation of the Effects of a Radiofrequency-Based Nonablative Dermal Remodeling Device, A Pilot Study" Arch Dermatol, vol. 140, (Feb. 2004).

Alam, M., "The future of noninvasive procedural dermatology". Semin Cutan Med Surg. Mar. 2013; 32(1):59-61.

Alam, M., et al., "Ultrasound tightening of facial and neck skin: a rater-blinded prospective cohort study". J Am Acad Dermatol, 2010. 62(2): p. 262-9.

Alexiades-Armenakas, M., "Ultrasound Technologies for Dermatologic Techniques". J Drugs Derm. 2014. 12 (11): p. 1305. Alster, T.S., et. al., "Noninvasive lifting of arm, thigh, and knee skin with transcutaneousintense focused ultrasound". Dermatol Surg, 2012. 38(5): p. 754-9.

Arosarena, O., "Options and Challenges for Facial Rejuvenation in Patients With Higher Fitzpatrick Skin Phototypes". JAMA Facial Plastic Surgery, 2015.

Brobst, R.W., et. al., "Noninvasive Treatment of the Neck". Facial Plast Surg Clin North Am, 2014. 22(2): p. 191-202.

Brobst, R.W., et., al., "Ulthera: initial and six month results". Facial Plast Surg Clin North Am, 2012. 20(2): p. 163-76.

Casabona, G., et. al., "Microfocused Ultrasound With Visualization and Fillers for Increased Neocollagenesis: Clinical and Histological Evaluation". Dermatol Surg 2014;40:S194-S198.

Chan, N.P., et al., "Safety study of transcutaneous focused ultrasound for non-invasive skin tightening in Asians". Lasers Surg Med, 2011. 43(5): p. 366-75.

Chapelon et al., "Effects of Cavitation in the High Intensity Therapeutic Ultrasound", Ultrasonics Symposium—1357 (1991).

Chapelon, et al., "Thresholds for Tissue Ablation by Focused Ultrasound" (1990).

Dayan, S.H., et al., "Prospective, Multi-Center, Pivotal Trial Evaluating the Safety and Effectiveness of Micro-Focused Ultrasound with Visualization (MFU-V) for Improvement in Lines and Wrinkles of the Décolletage". Plast Reconstr Surg. Oct. 2014; 134(4 Suppl 1):123-4.

Dobke, M.K., et al., "Tissue restructuring by energy-based surgical tools". Clin Plast Surg, 2012. 39(4): p. 399-408.

Fabi, S.G., "Microfocused Ultrasound With Visualization for Skin Tightening and Lifting: My Experience and a Review of the Literature". Dermatol Surg. Dec. 2014; 40 Suppl 12: S164-7.

Fabi, S.G., "Noninvasive skin tightening: focus on new ultrasound techniques". Clin Cosmet Investig Dermatol. Feb. 5, 2015; 8:47-52. Fabi, S.G., et. al., "A prospective multicenter pilot study of the safety and efficacy of microfocused ultrasound with visualization for improving lines and wrinkles of the décolleté". Dermatol Surg. Mar. 2015; 41(3):327-35.

Fabi, S.G., et. al., "Evaluation of microfocused ultrasound with visualization for lifting, tightening, and wrinkle reduction of the decolletage". J Am Acad Dermatol, 2013. 69(6): p. 965-71.

Fabi, S.G., et. al., "Future directions in cutaneous laser surgery". Dermatol Clin, 2014. 32(1): p. 61-9.

Fabi, S.G., et. al., "Retrospective Evaluation of Micro-focused Ultrasound for Lifting and Tightening the Face and Neck". Dermatol Surg, 2014.

Friedmann D.P., "Comments on evaluation of microfocused ultrasound system for improving skin laxity and tightening in the lower face". Aesthet Surg J. Mar. 2015;35(3):NP81-2.

Friedmann, D.P., et. al., "Combination of intense pulsed light, Sculptra, and Ultherapy for treatment of the aging face". J Cosmet Dermatol, 2014. 13(2): p. 109-18.

Fujimoto, et al., "A New Cavitation Suppression Technique for Local Ablation Using High-Intensity Focused Ultrasound" Ultrasonics Symposium—1629 (1995).

Gold, M.H., et. al., "Use of Micro-Focused Ultrasound with Visualization to Lift and Tighten Lax Knee Skin". J Cosmet Laser Ther, 2014: p. 1-15.

Goldberg, D.J., et. al., "Safety and Efficacy of Microfocused Ultrasound to Lift, Tighten, and Smooth the Buttocks". Dermatol Surg 2014; 40:1113-1117.

(56) References Cited

OTHER PUBLICATIONS

Greene, R.M., et al., "Skin tightening technologies". Facial Plast Surg. Feb. 2014; 30(1):62-7.

Harris, M.O., "Safety of Microfocused Ultrasound With Visualization in Patients With Fitzpatrick Skin Phototypes III to VI". JAMA Facial Plast. Surg. 2015.

Hart, et. al., "Current Concepts in the Use of PLLA:Clinical Synergy Noted with Combined Use of Microfocused Ultrasound and Poly-I-Lactic Acid on the Face, Neck, and Décolletage". Amer. Soc. Plast. Surg. 2015. 136; 180-187S.

Hitchcock, T.M. et. al., "Review of the safety profile for microfocused ultrasound with Visualization". Journal of Cosmetic Dermatology, 13, 329-335. (2014).

Hynynen et al., Temperature Distributions During Local Ultrasound Induced Hyperthermia In Vivo, Ultrasonics Symposium—745 (1982).

Jeong, K.H., et al., "Neurologic complication associated with intense focused ultrasound". J Cosmet Laser Ther, 2013.

Kim, H.J., et al., "Coagulation and ablation patterns of high-intensity focused ultrasound on a tissue mimicking phantom and cadaveric skin". Laser Med Sci. Sep. 4, 2015.

Kornstein, A.N., "Ulthera for silicone lip correction". Plast Reconstr Surg, 2012. 129(6): p. 1014e-1015e.

Kornstein, A.N., "Ultherapy shrinks nasal skin after rhinoplasty following failure of conservative measures". Plast Reconstr Surg, 2013. 131(4): p. 664e-6e.

Laubach, H.J., et. al., "Confined Thermal Damage with Intense Ultrasound (IUS)" [abstr.] American Society for Laser Medicine and Surgery Abstracts, p. 15 #43 (Apr. 2006).

Laubach, H.J., et. al., "Intense focused ultrasound: evaluation of a new treatment modality for precise microcoagulation within the skin". Dermatol Surg, 2008. 34(5): p. 727-34.

Lee, H.J., et. al., "The efficacy and safety of intense focused ultrasound in the treatment of enlarged facial pores in Asian skin". J Dermatolog Treat, 2014.

Lee, H.S., et. al., "Multiple Pass Ultrasound Tightening of Skin Laxity of the Lower Face and Neck". Dermatol Surg, 2011. Macgregor J.L., et. al., "Microfocused Ultrasound for Skin Tight-

Macgregor J.L., et. al., "Microfocused Ultrasound for Skin Tight ening". Semin Cutan Med Surg 32:18-25. (2013).

Minkis, K., et. al., "Ultrasound skin tightening". Dermatol Clin, 2014. 32(1): p. 71-7.

Nestor, M.S. et. al., "Safety and Efficacy of Micro-focused Ultrasound Plus Visualization for the Treatment of Axillary Hyperhidrosis". J Clin Aesthet Dermatol, 2014. 7(4): p. 14-21.

Oni, G., et. al. "Response to 'comments on evaluation of microfocused ultrasound system for improving skin laxity and tightening in the lower face'". Aesthet Surg J. Mar. 2015;35(3):NP83-4.

Oni, G., et. al., "Evaluation of a Microfocused Ultrasound System for Improving Skin Laxity and Tightening in the Lower Face". Aesthet Surg J, 2014. 38:861-868.

Pak, C.S., et. al., "Safety and Efficacy of Ulthera in the Rejuvenation of Aging Lower Eyelids: A Pivotal Clinical Trial". Aesthetic Plast Surg, 2014.

Pritzker, R.N., et. al, "Updates in noninvasive and minimally invasive skin tightening". Semin Cutan Med Surg. Dec. 2014;33(4):182-7.

Pritzker, R.N., et. al., "Comparison of different technologies for noninvasive skin tightening". Journal of Cosmetic Dermatology, 13, 315-323. (2014).

Rokhsar, C., et. al., "Safety and efficacy of microfocused ultrasound in tightening of lax elbow skin". Dermatol Surg. 2015; 41(7):821-6. Sabet-Peyman, E.J. et. al., "Complications Using Intense Ultrasound Therapy to TreatDeep Dermal Facial Skin and Subcutaneous Tissues". Dermatol Surg 2014; 40:1108-1112.

Sasaki, G.H. et. al., "Clinical Efficacy and Safety of Focused-Image Ultrasonography: A 2-Year Experience". Aesthet Surg J, 2012.

Sasaki, G.H. et. al., "Microfocused Ultrasound for Nonablative Skin and Subdermal Tightening to the Periorbitum and Body Sites: Preliminary Report on Eighty-Two Patients". Journal of Cosmetics, Dermatological Sciences and Applications, 2012, 2, 108-116.

Sklar, L.R., et. al., "Use of transcutaneous ultrasound for lipolysis and skin tightening: a review". Aesthetic Plast Surg, 2014. 38(2): p. 429-41.

Suh, D.H., et. al., "A intense-focused ultrasound tightening for the treatment of infraorbital laxity". J Cosmet Laser Ther, 2012. 14(6): p. 290-5.

Suh, D.H., et. al., "Comparative histometric analysis of the effects of high-intensity focused ultrasound and radiofrequency on skin". J Cosmet Laser Ther. Mar. 24, 2015:1-7.

Suh, D.H., et. al., "Intense focused ultrasound tightening in asian skin: clinical and pathologic results". Dermatol Surg, 2011. 37(11): p. 1595-602.

Weiss, M., "Commentary: noninvasive skin tightening: ultrasound and other technologies: where are we in 2011?" Dermatol Surg, 2012. 38(1): p. 28-30.

White, W. M., et al., "Selective Transcutaneous Delivery of Energy to Facial Subdermal Tissues Using the Ultrasound Therapy System" [abstr]. American Society for Laser Medicine and Surgery Abstracts, p. 37 #113 (Apr. 2006).

Woodward, J.A., et. al. "Safety and Efficacy of Combining Microfocused Ultrasound With Fractional CO2 Laser Resurfacing for Lifting and Tightening the Face and Neck". Dermatol Surg, Dec. 2014 40:S190-S193.

Ulthera, Inc., Petition for Inter Partes Review filed Jul. 19, 2016 in Re U.S. Pat. No. 6,113,559; 1PR2016-01459; 63 pages.

Ulthera Exhibit 1001, U.S. Pat. No. 6,113,559 to Klopotek, filed Jul. 19, 2016 in re IPR2016-01459.

Ulthera Exhibit 1002, Patent file history of U.S. Pat. No. 6,113,559 Klopotek.

Ulthera Exhibit 1003, Declaration of Expert Witness Mark E. Schafer, Ph.D.

Ulthera Exhibit 1004, Curriculum Vitae of Mark E. Schafer, Ph.D. Ulthera Exhibit 1005, International PCT Publication WO96/34568 Knowlton.

Ulthera Exhibit 1006, French Patent No. 2,672,486, Technomed patent.

Ulthera Exhibit 1007, English translation of French Patent No. 2.672.486, Technomed.

Ulthera Exhibit 1008, International PCT Publication WO93/12742, Technomed PCT.

Ulthera Exhibit 1009, English translation of International PCT Publication WO93/12742, Technomed PCT.

Ulthera Exhibit 1010, U.S. Pat. No. 5,601,526, which claims priority to Technomed PCT.

Ulthera Exhibit 1011, Patent file history for European Patent Application No. 98964890.2, Klopotek.

Ulthera Exhibit 1012, Translator Declaration.

Ulthera Exhibit 1013, U.S. Pat. No. 5,230,334 to Klopotek.

Ulthera Exhibit 1014, U.S. Pat. No. 5,755,753 to Knowlton.

Ulthera Exhibit 1015, Excerpts from The American Medical Association Encyclopedia of Medicine (1989).

Ulthera Exhibit 1016, The Simultaneous Study of Light Emissions and Shock Waves Produced by Cavitation Bubbles, G. Gimenez, J. Acoust. Soc. Am. 71(4), Apr. 1982, pp. 839-847.

Ulthera Exhibit 1017, Excerpts from Gray's Anatomy (1995).

Ulthera Exhibit 1018, Anatomy of the Superficial Venous System, Comjen G.M., Dermatol. Surg., 1995; 21:35-45.

Ulthera Exhibit 1019, Section 2.6 from Ultrasonics Theory and Application, by G.L. Gooberman (Hart Publishing Co., 1969).

Ulthera Exhibit 1020, Deep Local Hyperthermia for Cancer Therapy: External Electromagnetic and Ultrasound Techniques, A.Y. Cheung and A. Neyzari, Cancer Research (Suppl.), vol. 44, pp. 4736-4744 (1984).

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3A

Jul. 4, 2017






FIG. 3B




FIG. 4A






FIG. 4B




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 10D




FIG. 10E




FIG. 10F




FIG. 11




FIG. 12




FIG. 13

SYSTEMS FOR TREATING SKIN LAXITY

INCORPORATION BY REFERENCE TO ANY PRIORITY APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 14/692,114, issued as U.S. Pat. No. 9,427,600, which is a continuation of U.S. patent application Ser. No. 14/169,709, issued as U.S. Pat. No. 9,039,619, which is a continuation of U.S. patent application Ser. No. 13/230,498, 10 issued as U.S. Pat. No. 8,641,622, which is a continuation of U.S. patent application Ser. No. 11/163,150, issued as U.S. Pat. No. 8,066,641, which claims the benefit of priority to U.S. Provisional Application No. 60/617,295, each of which is incorporated in its entirety by reference herein. Any and 15 all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference under 37 CFR 1.57.

BACKGROUND

The present invention relates to ultrasound therapy and imaging systems, and in particular to a method and system for treating photoaged tissue.

Photoaging of human skin is a complex response due to inflammation, oxidative injury, cellular and extracellular changes induced by decades of sunlight exposure. UV wavelengths are thought to be mainly responsible. Both of the primary skin layers, epidermis and dermis, are affected. 30 Epidermal photoaging includes pigmentary lesions called ephilides (freckles) and solar lentigines (larger pigmented spots), plus precancerous clonal lesions of keratinocytes called actinic keratoses. Thermal destruction of part or all of the epidermis, the outermost cellular layer of skin about 0.1 35 mm thick, is an effective treatment for epidermal photoaging. For example, lasers that vaporize epidermis are highly effective in a treatment called laser resurfacing. However laser resurfacing creates a significant skin wound with risk of infection, and prolonged healing. Dermal changes of 40 photoaging include solar elastosis (an accumulation of abnormally-formed elastin fibers in the upper reticular layer of the dermis), laxity, loss of elasticity, fine and coarse wrinkles. Laser resurfacing to a depth below the dermoepidermal junction can be highly effective for improving der- 45 mal photoaging, through a process of stimulated wound healing. Deep chemical peels, dermabrasion and other methods of destruction of epidermis and/or dermis are also effective, and also produce a significant open skin wound with risk of infection and delayed healing.

Patterns of stimulated thermal damage to epidermis and/ or dermis are also effective for treatment of photoaging. Recently, "fractional photothermolysis" using mid-infrared lasers to produce a microscopic array of thermal injury zones that include both epidermis and dermis was reported 55 to be effective and well-tolerated for treatment of photoaging (D. Manstein et al. "Fractional Photothermolysis: a new concept for cutaneous remodeling using microscopic patterns of thermal injury." Lasers Surg Med 34:426-438, 2004). A primary advantage of fractional photothermolysis 60 is that each zone of thermal injury is smaller than can be easily seen with the unaided eye, and surrounded by a zone of healthy tissue that initiates a rapid healing response. As described Manstein, the epidermis is stimulated to heal rapidly and without creating an open wound. The micro- 65 scopic zones of thermally injured epidermis slough harmlessly from the skin surface after several days to several

2

weeks, leaving a rejuvenated epidermis with less photoaging changes. Repeat treatments, which are well tolerated, can be performed until a desired result is obtained. The microscopic zones of thermal injury with fractional photothermolysis extend well into the dermis, as well. Dermis does not heal as rapidly as epidermis, in general. Over weeks to months following treatment, some of the abnormal dermis due to photoaging is remodeled, however, leading to improvement in laxity, wrinkles and skin texture.

Fractional photothermolysis (FP) is intrinsically limited to regions of approximately the upper 1-millimeter of skin. The basic concept of producing well-controlled arrays of thermal injury is therefore limited with fractional photothermolysis, to superficial aspects of photoaging. Aging, which also causes laxity of the skin, and photoaging involve deeper layers of the dermis. Solar elastosis can extend throughout the dermis, to approximately 3 mm deep or more. Laxity and loss of elasticity due to aging are bulk problems of the dermis.

A fundamental requirement for producing arrays of small thermal injury zones using a source of radiant energy that propagates and is absorbed within tissue, is that the source of radiant energy be capable of being adequately delivered to the tissue depth for which the array is desired. Near the skin surface, light can be used, as in fractional photothermolysis. However, light that propagates more than about 1 mm through skin has been multiplied scattered, and can no longer be focused or delivered.

SUMMARY

A method and system for ultrasound treatment of photoaged tissue are provided. An exemplary method and system are configured for first, ultrasound imaging of the region of interest for localization of the treatment area, second, delivery of ultrasound energy at a depth and pattern to achieve the desired therapeutic effects, and third to monitor the treatment area during and after therapy to assess the results and/or provide feedback. The exemplary treatment method and system can be configured for producing arrays of sub-millimeter and larger zones of thermal ablation to treat the epidermal, superficial dermal, mid-dermal and deep dermal components of photoaged tissue.

In accordance with an exemplary embodiment, the treatment method and system use focused, unfocused, and/or defocused ultrasound for treatment of epidermal, superficial dermal, dermal, mid-dermal, and/or deep dermal components of photoaged tissue by adjusting the strength, depth, and/or type of focusing, energy levels and timing cadence. For example, focused ultrasound can be used to create precise arrays of microscopic thermal damage much deeper into the skin or even into subcutaneous structures. Detection of changes in the reflection of ultrasound can be used for feedback control to detect a desired effect on the tissue and used to control the exposure intensity, time, and/or position.

In accordance with an exemplary embodiment, an exemplary treatment system comprises an imaging/therapy probe, a control system and display system. The imaging/therapy probe can comprise various probe and/or transducer configurations. For example, the probe can be configured for a combined dual-mode imaging/therapy transducer, coupled or co-housed imaging/therapy transducers, a separate therapy probe and imaging probe, or a single therapy probe. The control system and display system can also comprise various configurations for controlling probe and system functionality, including for example a microprocessor with software and a plurality of input/output and communication

devices, a system for controlling electronic and/or mechanical scanning and/or multiplexing of transducers, a system for power delivery, systems for monitoring, systems for sensing the spatial position of the probe and/or temporal parameters of the transducers, and systems for handling user input and recording treatment input and results, among others.

BRIEF DESCRIPTION OF THE DRAWINGS

The subject matter of the invention is particularly pointed out in the concluding portion of the specification. The invention, however, both as to organization and method of operation, may best be understood by reference to the following description taken in conjunction with the accompanying drawing figures, in which like parts may be referred to by like numerals:

FIG. 1 illustrates a block diagram of a treatment system in accordance with an exemplary embodiment of the present invention;

FIGS. 2A-2D illustrates a schematic diagram of an ultrasound treatment system including therapy, imaging and/or monitoring and treating photoaged tissue in accordance with various exemplary embodiments of the present invention;

FIGS. **3**A and **3**B illustrate block diagrams of an exemplary control system in accordance with exemplary embodiments of the present invention;

FIGS. 4A and 4B illustrate block diagrams of an exemplary probe system in accordance with exemplary embodiments of the present invention;

FIG. 5 illustrates a cross-sectional diagram of an exemplary transducer in accordance with an exemplary embodiment of the present invention;

FIGS. **6A** and **6B** illustrate cross-sectional diagrams of an exemplary transducer in accordance with exemplary ³⁵ embodiments of the present invention;

FIG. 7 illustrates exemplary transducer configurations for ultrasound treatment in accordance with various exemplary embodiments of the present invention;

FIGS. **8**A and **8**B illustrate cross-sectional diagrams of an ⁴⁰ exemplary transducer in accordance with another exemplary embodiment of the present invention;

FIG. **9** illustrates an exemplary transducer configured as a two-dimensional, array for ultrasound treatment in accordance with an exemplary embodiment of the present invention:

FIGS. 10A-10F illustrate cross-sectional diagrams of exemplary transducers in accordance with other exemplary embodiments of the present invention;

FIG. 11 illustrates a schematic diagram of an acoustic 50 coupling and cooling system in accordance with an exemplary embodiment of the present invention;

FIG. 12 illustrates a block diagram of an ultrasound treatment system combined with additional subsystems and methods of treatment monitoring and/or treatment imaging 55 as well as a secondary treatment subsystem in accordance with an exemplary embodiment of the present invention; and

FIG. 13 illustrates a schematic diagram with imaging, therapy, or monitoring being provided with one or more active or passive oral inserts in accordance with an exemplary embodiment of the present invention.

DETAILED DESCRIPTION

The present invention may be described herein in terms of 65 various functional components and processing steps. It should be appreciated that such components and steps may

4

be realized by any number of hardware components configured to perform the specified functions. For example, the present invention may employ various medical treatment devices, visual imaging and display devices, input terminals and the like, which may carry out a variety of functions under the control of one or more control systems or other control devices. In addition, the present invention may be practiced in any number of medical contexts and that the exemplary embodiments relating to a method and system for treating photoaged tissue as described herein are merely indicative of exemplary applications for the invention. For example, the principles, features and methods discussed may be applied to any medical application. Further, various aspects of the present invention may be suitably applied to other applications.

In accordance with various aspects of the present invention, a method and system for treating photoaged tissue are provided. For example, in accordance with an exemplary embodiment, with reference to FIG. 1, an exemplary treatment system 100 configured to treat a region of interest (ROI) 106 comprises a control system 102, an imaging/ therapy probe with acoustic coupling 104, and a display system 108. Control system 102 and display 108 can comprise various configurations for controlling functionality of probe 104 and system 100, including for example a microprocessor with software and a plurality of input/output and communication devices, a system for controlling electronic and/or mechanical scanning and/or multiplexing of transducers, a system for power delivery, systems for monitoring, systems for sensing the spatial position of the probe and/or temporal parameters of the transducers, and/or systems for handling user input and recording treatment input and results, among others. Imaging/therapy probe 104 can comprise various probe and/or transducer configurations. For example, probe 104 can be configured for a combined dual-mode imaging/therapy transducer, coupled or co-housed imaging/therapy transducers, a separate therapy probe and separate imaging probe, or a single therapy probe. In accordance with exemplary embodiments, imaging transducers may operate at frequencies from approximately 2 to 75 MHz or more, while therapy energy can be delivered at frequencies from approximately 2 to 50 MHz, with 2 MHz to 25 MHz being typical.

For the treatment of photoaged tissue, it is desirable to be able to produce well controlled arrays of microscopic zones of thermal injury not only near the surface of skin, but in the mid-dermis, and/or in the deep dermis. Thermal ablation of dermis at temperatures greater than about 60° C., capable of producing denaturation of tissue, is also desirable in such arrays of thermal lesions. Shrinkage of dermis due to thermal action results from tightening of the skin.

In contrast to optical or RF approaches, ultrasound energy propagates as a wave with relatively little scattering, over depths up to many centimeters in tissue depending on the ultrasound frequency. The focal spot size achievable with any propagating wave energy, depends on wavelength. Ultrasound wavelength is equal to the acoustic velocity divided by the ultrasound frequency. Attenuation (absorption, mainly) of ultrasound by tissue also depends on frequency.

In accordance with an exemplary embodiment, the use of focused, unfocused, or defocused ultrasound for treatment of epidermal, superficial dermal, dermal, middermal, and deep dermal components of photoaged tissue through adjustment of the strength, depth, and type of focusing, energy levels and timing cadence. For example, focused ultrasound can be used to create precise arrays of microscopic thermal ablation

-

zones which have several advantages over fractional photothermolysis (FP). At high frequency and with superficial focusing or diffraction pattern, ultrasound ablation can mimic FP but utilize a simpler ablation device. Unlike fractional photothermolysis, ultrasound can produce an array of ablation zones much deeper into the skin or even into subcutaneous structures. Detection of changes in the reflection of ultrasound can be used for feedback control to detect a desired effect on the tissue and used to control the exposure intensity, time, and/or position.

To further illustrate the use of ultrasound for the treatment of photoaged tissue, with reference to FIG. 2A, an exemplary method and system are configured for initially imaging a region 222 of a region of interest 206 and displaying that 15 region 224 during the localization of the treatment area and surrounding structures. After localization, delivery of ultrasound energy 220 at a depth, distribution, timing, and energy level to achieve the desired therapeutic effect of thermal ablation to treat an epidermis layer 212, superficial dermis 20 layer 214, mid-dermis layer 216, and/or deep dermis layer 218 can be provided. Before, during, and after therapy, i.e., before, during, and after the delivery of ultrasound energy 220, exemplary method and system 200 can suitably monitor the treatment area and surrounding structures to plan and 25 assess the results and/or provide feedback to control system 202 and/or a system user.

While an imaging function may be configured within control system **202** to facilitate imaging a region of interest, in accordance with another exemplary embodiment, an 30 exemplary treatment system **200** may also be configured for therapy only or therapy and monitoring, without imaging functions. In such a case prior known depth of the region of interest, approximately 0 to 5 mm or less, is employed to achieve treatment zones in photoaged skin.

Probe 204 and/or transducers within can be mechanically and/or electronically scanned in a direction 226 to place treatment zones 260 over an extended area, such as a line to generate a matrix of closely spaced treatment spots. Treatment depth 220 can be adjusted between a range of approximately 0 to 5 mm, or otherwise until the depth of the deep dermis. Treatment may be confined to a fixed depth or a few discrete depths, or can be adjustment limited to a fine range, e.g. from approximately between 0 to 5 mm or the greatest depth of the deep dermis, or can be dynamically adjusted 45 during treatment, to the treat region of interest 206 that lies above subcutaneous fat region 250.

In accordance with another exemplary embodiment of the present invention, with reference to FIG. 2B, a treated zone **260** may extend throughout regions of the dermis, and may 50 even extend to the epidermis, 262. In addition, as a treated zone increases in depth its cross section may increase from small size 264 (sub millimeter) in a shallow region near or at the epidermis, to medium size 266 (sub millimeter to millimeter sized) in a middle zone near or at the mid dermis, 55 to large size 268 (millimeter sized) in deep zones near or at the deep dermis. Furthermore a. single treated zone can have a shape expanding in cross section with depth, and/or be composed of the fusion of several smaller treatment zones. Spacing of treatment zones can be on the order of the 60 treatment zone size. The ultrasound beam can be spatially and/or temporally controlled by changing the position of the transducer, its frequency, treatment depth, drive amplitude, and timing via the control system. For example, the ultrasound beam can be controlled as set forth in U.S. patent 65 application Ser. No. 11/163,148, filed Oct. 6, 2005, and entitled METHOD AND SYSTEM FOR COTROLLED

6

THERMAL INJURY OF HUMAN SUPERFICIAL TISSUE, and hereby incorporated by reference.

In accordance with another exemplary embodiment of the present invention, with reference to FIG. 2C, an exemplary treatment method and system 200 may be configured to monitor the temperature profile or other tissue parameters of region of interest 206, such as attenuation or speed of sound of the treatment region and suitably adjust the spatial and/or temporal characteristics and energy levels of the ultrasound therapy transducer. The results of such monitoring techniques may be indicated on display 208, such as through display of one-, two-, or three-dimensional images of monitoring results 270, or may comprise an indicator 272, such as a success, fail and/or completed/done type of indication, or combinations thereof. Additional treatment monitoring methods may be based on one or more of temperature, video, profilometry, strain imaging and/or gauges or any other suitable sensing method.

In accordance with another exemplary embodiment, with reference to FIG. 20, an expanded region of interest 280 can suitably include a combination of tissues, such as subcutaneous fat/adipose tissue 250. A combination of such tissues includes at least one of epidermis 212, superficial dermis 214, mid dermis 216, or deep dermis 218, in combination with at least one of muscle tissue, adipose tissue, or other tissues useful for treatment. For example, treatment 260 of superficial dermis may be performed in combination with treatment 220 of subcutaneous fat 250 by suitable adjustment of the spatial and temporal parameters of transducers in probe 204.

An exemplary control system 202 and display system 208 may be configured in various manners for controlling probe and system functionality for providing the various exemplary treatment methods illustrated above. For example, with reference to FIGS. 3A and 3B, in accordance with exemplary embodiments, an exemplary control system 300 can be configured for coordination and control of the entire therapeutic treatment process for producing arrays of submillimeter and larger zones of thermal ablation to treat the epidermal, superficial dermal, mid-dermal and deep dermal components of photoaged tissue. For example, control system 300 can suitably comprise power source components 302, sensing and monitoring components 304, cooling and coupling controls 306, and/or processing and control logic components 308. Control system 300 can be configured and optimized in a variety of ways with more or less subsystems and components to implement the therapeutic system for controlled thermal injury of photoaged tissue, and the embodiments in FIGS. 3A and 3B are merely for illustration purposes.

For example, for power sourcing components 302, control system 300 can comprise one or more direct current (DC) power supplies 303 configured to provide electrical energy for entire control system 300, including power required by a transducer electronic amplifier/driver 312. A DC current sense device 305 can also be provided to confirm the level of power going into amplifiers/drivers 312 for safety and monitoring purposes.

Amplifiers/drivers 312 can comprise multi-channel or single channel power amplifiers and/or drivers. In accordance with an exemplary embodiment for transducer array configurations, amplifiers/drivers 312 can also be configured with a beamformer to facilitate array focusing. An exemplary beamformer can be electrically excited by an oscillator/digitally controlled waveform synthesizer 310 with related switching logic.

The power sourcing components can also include various filtering configurations 314. For example, switchable harmonic filters and/or matching may be used at the output of amplifier/driver 312 to increase the drive efficiency and effectiveness. Power detection components 316 may also be 5 included to confirm appropriate operation and calibration. For example, electric power and other energy detection components 316 may be used to monitor the amount of power going to an exemplary probe system.

Various sensing and monitoring components 304 may 10 also be suitably implemented within control system 300. For example, in accordance with an exemplary embodiment, monitoring, sensing and interface control components 324 may be configured to operate with various motion detection systems implemented within transducer probe 204 to receive 15 and process information such as acoustic or other spatial and temporal information from a region of interest. Sensing and monitoring components can also include various controls, interfacing and switches 309 and/or power detectors 316. Such sensing and monitoring components 304 can facilitate 20 open-loop and/or closed-loop feedback systems within treatment system 200.

Cooling/coupling control systems 306 may be provided to remove waste heat from an exemplary probe 204, provide a controlled temperature at the superficial tissue interface and 25 deeper into tissue, and/or provide acoustic coupling from transducer probe 204 to region-of-interest 206. Such cooling/coupling control systems 306 can also be configured to operate in both open-loop and/or closed-loop feedback arrangements with various coupling and feedback components.

Processing and control logic components 308 can comprise various system processors and digital control logic 307, such as one or more of microcontrollers, microprocessors, field-programmable gate arrays (FPGAs), computer 35 boards, and associated components, including firmware and control software 326, which interfaces to user controls and interfacing circuits as well as input/output circuits and systems for communications, displays, interfacing, storage, documentation, and other useful functions. System software 40 and firmware 326 controls all initialization, timing, level setting, monitoring, safety monitoring, and all other system functions required to accomplish user-defined treatment objectives. Further, various control switches 308 can also be suitably configured to control operation.

An exemplary transducer probe 204 can also be configured in various manners and comprise a number of reusable and/or disposable components and parts in various embodiments to facilitate its operation. For example, transducer probe 204 can be configured within any type of transducer 50 probe housing or arrangement for facilitating the coupling of transducer to a tissue interface, with such housing comprising various shapes, contours and configurations. Transducer probe 204 can comprise any type of matching, such as for example, electric matching, which may be electrically swit- 55 chable; multiplexer circuits and/or aperture/element selection circuits; and/or probe identification devices, to certify probe handle, electric matching, transducer usage history and calibration, such as one or more serial EEPROM (memories). Transducer probe 204 may also comprise cables 60 and connectors; motion mechanisms, motion sensors and encoders; thermal monitoring sensors; and/or user control and status related switches, and indicators such as LEDs. For example, a motion mechanism in probe 204 may be used to controllably create multiple lesions, or sensing of probe 65 motion itself may be used to controllably create multiple lesions and/or stop creation of lesions, e.g. for safety reasons

8

if probe 204 is suddenly jerked or is dropped. In addition, an external motion encoder arm may be used to hold the probe during use, whereby the spatial position and attitude of probe 104 is sent to the control system to help controllably create lesions. Furthermore, other sensing functionality such as profilometers or other imaging modalities may be integrated into the probe in accordance with various exemplary embodiments.

With reference to FIGS. 4A and 4B, in accordance with an exemplary embodiment, a transducer probe 400 can comprise a control interface 402, a transducer 404, coupling components 406, and monitoring/sensing components 408, and/or motion mechanism 410. However, transducer probe 400 can be configured and optimized in a variety of ways with more or less parts and components to provide ultrasound energy for controlled thermal injury of photoaged tissue, and the embodiments in FIGS. 4A and 4B are merely for illustration purposes.

Control interface 402 is configured for interfacing with control system 300 to facilitate control of transducer probe 400. Control interface components 402 can comprise multiplexer/aperture select 424, switchable electric matching networks 426, serial EEPROMs and/or other processing components and matching and probe usage information 430 and interface connectors 432.

Coupling components 406 can comprise various devices to facilitate coupling of transducer probe 400 to a region of interest. For example, coupling components 406 can comprise cooling and acoustic coupling system 420 configured for acoustic coupling of ultrasound energy and signals. Acoustic cooling/coupling system 420 with possible connections such as manifolds may be utilized to couple sound into the region-of-interest, control temperature at the interface and deeper into tissue, provide liquid-filled lens focusing, and/or to remove transducer waste heat. Coupling system 420 may facilitate such coupling through use of various coupling mediums, including air and other gases, water and other fluids, gels, solids, and/or any combination thereof, or any other medium that allows for signals to be transmitted between transducer active elements 412 and a region of interest. In addition to providing a coupling function, in accordance with an exemplary embodiment, coupling system 420 can also be configured for providing temperature control during the treatment application. For example, coupling system 420 can be configured for controlled cooling of an interface surface or deeper region between transducer probe 400 and a region of interest and beyond by suitably controlling the temperature of the coupling medium. The suitable temperature for such coupling medium can be achieved in various manners, and utilize various feedback systems, such as thermocouples, thermistors or any other device or system configured for temperature measurement of a coupling medium. Such controlled cooling can be configured to further facilitate spatial and/or thermal energy delivery control of transducer probe 400.

In accordance with an exemplary embodiment, with additional reference to FIG. 11, acoustic coupling and cooling 1140 can be provided to acoustically couple energy and imaging signals from transducer probe 1104 to and from the region of interest 1102, to provide thermal control at the probe to region-of-interest interface 1110 and deeper into tissue, and to remove potential waste heat from the transducer probe at region 1144. Temperature monitoring can be provided at the coupling interface via a thermal sensor 1146 to provide a mechanism of temperature measurement 1148 and control via control system 1106 and a thermal control system 1142. Thermal control may consist of passive cool-

ing such as via heat sinks or natural conduction and convection or via active cooling such as with peltier thermoelectric coolers, refrigerants, or fluid-based systems comprised of pump, fluid reservoir, bubble detection, flow sensor, flow channels/tubing 1144 and thermal control 1142. 5

With continued reference to FIG. 4, monitoring and sensing components 408 can comprise various motion and/or position sensors 416, temperature monitoring sensors 418, user control and feedback switches 414 and other like components for facilitating control by control system 300, 10 e.g., to facilitate spatial and/or temporal control through open-loop and closed-loop feedback arrangements that monitor various spatial and temporal characteristics.

Motion mechanism **410** can comprise manual operation, mechanical arrangements, or some combination thereof. For 15 example, a motion mechanism **422** can be suitably controlled by control system **300**, such as through the use of accelerometers, encoders or other position/orientation devices **416** to determine and enable movement and positions of transducer probe **400**. Linear, rotational or variable 20 movement can be facilitated, e.g., those depending on the treatment application and tissue contour surface.

Transducer 404 can comprise one or more transducers configured for treating of SMAS layers and targeted regions. Transducer 404 can also comprise one or more transduction 25 elements and/or lenses 412. The transduction elements can comprise a piezoelectrically active material, such as lead zirconante titanate (PZT), or any other piezoelectrically active material, such as a piezoelectric ceramic, crystal, plastic, and/or composite materials, as well as lithium nio- 30 bate, lead titanate, barium titanate, and/or lead metaniobate. In addition to, or instead of, a piezoelectrically active material, transducer 404 can comprise any other materials configured for generating radiation and/or acoustical energy. Transducer 404 can also comprise one or more matching 35 layers configured along with the transduction element such as coupled to the piezoelectrically active material. Acoustic matching layers and/or damping may be employed as necessary to achieve the desired electroacoustic response.

In accordance with an exemplary embodiment, the thick- 40 ness of the transduction element of transducer 404 can be configured to be uniform. That is, a transduction element 412 can be configured to have a thickness that is substantially the same throughout. In accordance with another exemplary embodiment, the thickness of a transduction 45 element 412 can also be configured to be variable. For example, transduction element(s) 412 of transducer 404 can be configured to have a first thickness selected to provide a center operating frequency of approximately 2 kHz to 75 MHz, such as for imaging applications. Transduction ele- 50 ment 412 can also be configured with a second thickness selected to provide a center operating frequency of approximately 2 to 50 MHz, and typically between 2 MHz and 25 MHz for therapy application. Transducer 404 can be configured as a single broadband transducer excited with at least 55 two or more frequencies to provide an adequate output for generating a desired response. Transducer 404 can also be configured as two or more individual transducers, wherein each transducer comprises one or more transduction element. The thickness of the transduction elements can be 60 configured to provide center-operating frequencies in a desired treatment range.

Transducer 404 may be composed of one or more individual transducers in any combination of focused, planar, or unfocused single-element, multi-element, or array transducers, including 1-D, 2-D, and annular arrays; linear, curvilinear, sector, or spherical arrays; spherically, cylindrically,

10

and/or electronically focused, defocused, and/or lensed sources. For example, with reference to an exemplary embodiment depicted in FIG. 5, transducer 500 can be configured as an acoustic array 502 to facilitate phase focusing. That is, transducer 500 can be configured as an array of electronic apertures that may be operated by a variety of phases via variable electronic time delays. By the term "operated," the electronic apertures of transducer 500 may be manipulated, driven, used, and/or configured to produce and/or deliver an energy beam corresponding to the phase variation caused by the electronic time delay. For example, these phase variations can be used to deliver defocused beams 508, planar beams 504, and/or focused beams 506, each of which may be used in combination to achieve different physiological effects in a region of interest 510. Transducer 500 may additionally comprise any software and/or other hardware for generating, producing and/or driving a phased aperture array with one or more electronic time delays.

Transducer 500 can also be configured to provide focused treatment to one or more regions of interest using various frequencies. In order to provide focused treatment, transducer 500 can be configured with one or more variable depth devices to facilitate treatment. For example, transducer 500 may be configured with variable depth devices disclosed in U.S. patent application Ser. No. 10/944,500, entitled "System and Method for Variable Depth Ultrasound", filed on Sep. 16, 2004, having at least one common inventor and a common Assignee as the present application, and incorporated herein by reference. In addition, transducer 500 can also be configured to treat one or more additional ROI 510 through the enabling of sub-harmonics or pulseecho imaging, as disclosed in U.S. patent application Ser. No. 10/944, 499, entitled "Method and System for Ultrasound Treatment with a Multi-directional Transducer," filed on Sep. 16, 2004, having at least one common inventor and a common Assignee as the present application, and also incorporated herein by reference.

Moreover, any variety of mechanical lenses or variable focus lenses, e.g. liquid-filled lenses, may also be used to focus and/or defocus the sound field. For example, with reference to exemplary embodiments depicted in FIGS. 6A and 6B, transducer 600 may also be configured with an electronic focusing array 604 in combination with one or more transduction elements 606 to facilitate increased flexibility in treating ROI 610. Array 604 may be configured in a manner similar to transducer 502. That is, array 604 can be configured as an array of electronic apertures that may be operated by a variety of phases via variable electronic time delays, for example, T1, T2 . . . Tj. By the term "operated," the electronic apertures of array 604 may be manipulated, driven, used, and/or configured to produce and/or deliver energy in a manner corresponding to the phase variation caused by the electronic time delay. For example, these phase variations can be used to deliver defocused beams, planar beams, and/or focused beams, each of which may be used in combination to achieve different physiological effects in ROI 610.

Transduction elements **606** may be configured to be concave, convex, and/or planar. For example, in an exemplary embodiment depicted in FIG. **6A**, transduction elements **606** are configured to be concave in order to provide focused energy for treatment of ROI **610**. Additional embodiments are disclosed in U.S. patent application Ser. No. 10/944,500, entitled "Variable Depth Transducer System and Method", and again incorporated herein by reference.

In another exemplary embodiment, depicted in FIG. **68**, transduction elements **606** can be configured to be substantially flat in order to provide substantially uniform energy to ROI **610**. While FIGS. **6A** and **68** depict exemplary embodiments with transduction elements **604** configured as concave and substantially flat, respectively, transduction elements **604** can be configured to be concave, convex, and/or substantially flat. In addition, transduction elements **604** can be configured to be any combination of concave, convex, and/or substantially flat structures. For example, a first transduction element can be configured to be concave, while a second transduction element can be configured to be substantially flat.

With reference to FIGS. 8A and 8B, transducer 404 can be configured as single-element arrays, wherein a single-element 802, e.g., a transduction element of various structures and materials, can be configured with a plurality of masks 804, such masks comprising ceramic, metal or any other material or structure for masking or altering energy distribution from element 802, creating an array of energy distributions 808. Masks 804 can be coupled directly to element 802 or separated by a standoff 806, such as any suitably solid or liquid material.

An exemplary transducer 404 can also be configured as an annular array to provide planar, focused and/or defocused 25 acoustical energy. For example, with reference to FIGS. 10A and 10B, in accordance with an exemplary embodiment, an annular array 1000 can comprise a plurality of rings 1012, 1014, 1016 to N. Rings 1012, 1014, 1016 to N can be mechanically and electrically isolated into a set of individual 30 elements, and can create planar, focused, or defocused waves. For example, such waves can be centered on-axis, such as by methods of adjusting corresponding transmit and/or receive delays, T1, T2, T3 . . . TN. An electronic focus can be suitably moved along various depth positions, 35 and can enable variable strength or beam tightness, while an electronic defocus can have varying amounts of defocusing. In accordance with an exemplary embodiment, a lens and/or convex or concave shaped annular array 1000 can also be provided to aid focusing or defocusing such that any time 40 differential delays can be reduced. Movement of annular array 800 in one, two or three-dimensions, or along any path, such as through use of probes and/or any conventional robotic arm mechanisms, may be implemented to scan and/or treat a volume or any corresponding space within a 45 region of interest.

Transducer 404 can also be configured in other annular or non-array configurations for imaging/therapy functions. For example, with reference to FIGS. 10C-10F, a transducer can comprise an imaging element 1012 configured with therapy 50 element(s) 1014. Elements 1012 and 1014 can comprise a single-transduction element, e.g., a combined imaging/transducer element, or separate elements, can be electrically isolated 1022 within the same transduction element or between separate imaging and therapy elements, and/or can 55 comprise standoff 1024 or other matching layers, or any combination thereof. For example, with particular reference to FIG. 10F, a transducer can comprise an imaging element 1012 having a surface 1028 configured for focusing, defocusing or planar energy distribution, with therapy elements 60 1014 including a stepped-configuration lens configured for focusing, defocusing, or planar energy distribution.

In accordance with various exemplary embodiments of the present invention, transducer 404 may be configured to provide one, two and/or three-dimensional treatment applications for focusing acoustic energy to one or more regions of interest. For example, as discussed above, transducer 404 12

can be suitably diced to form a one-dimensional array, e.g., transducer 602 comprising a single array of sub-transduction elements.

In accordance with another exemplary embodiment, transducer 404 may be suitably diced in two-dimensions to form a two-dimensional array. For example, with reference to FIG. 9, an exemplary two-dimensional array 900 can be suitably diced into a plurality of two-dimensional portions 902. Two-dimensional portions 902 can be suitably configured to focus on the treatment region at a certain depth, and thus provide respective slices 904, 907 of the treatment region. As a result, the two-dimensional array 900 can provide a two-dimensional slicing of the image place of a treatment region, thus providing two-dimensional treatment.

In accordance with another exemplary embodiment, transducer 404 may be suitably configured to provide three-dimensional treatment. For example, to provide three-dimensional treatment of a region of interest, with reference again to FIG. 1, a three-dimensional system can comprise a transducer within probe 104 configured with an adaptive algorithm, such as, for example, one utilizing three-dimensional graphic software, contained in a control system, such as control system 102. The adaptive algorithm is suitably configured to receive two-dimensional imaging, temperature and/or treatment or other tissue parameter information relating to the region of interest, process the received information, and then provide corresponding three-dimensional imaging, temperature and/or treatment information.

In accordance with an exemplary embodiment, with reference again to FIG. 9, an exemplary three-dimensional system can comprise a two-dimensional array 900 configured with an adaptive algorithm to suitably receive 904 slices from different image planes of the treatment region, process the received information, and then provide volumetric information 906, e.g., three-dimensional imaging, temperature and/or treatment information. Moreover, after processing the received information with the adaptive algorithm, the two-dimensional array 900 may suitably provide therapeutic heating to the volumetric region 906 as desired.

In accordance with other exemplary embodiments, rather than utilizing an adaptive algorithm, such as three-dimensional software, to provide three-dimensional imaging and/or temperature information, an exemplary three-dimensional system can comprise a single transducer **404** configured within a probe arrangement to operate from various rotational and/or translational positions relative to a target region.

To further illustrate the various structures for transducer **404**, with reference to FIG. 7, ultrasound therapy transducer 700 can be configured for a single focus, an array of foci, a locus of foci, a line focus, and/or diffraction patterns. Transducer 700 can also comprise single elements, multiple elements, annular arrays, one-, two-, or three-dimensional arrays, broadband transducers, and/or combinations thereof, with or without lenses, acoustic components, and mechanical and/or electronic focusing. Transducers configured as spherically focused single elements 702, annular arrays 704, annular arrays with damped regions 706, line focused single elements 708, 1-0 linear arrays 710, 1-0 curvilinear arrays in concave or convex form, with or without elevation focusing, 2-D arrays, and 3-D spatial arrangements of transducers may be used to perform therapy and/or imaging and acoustic monitoring functions. For any transducer configuration, focusing and/or defocusing may be in one plane or two planes via mechanical focus 720, convex lens 722, concave lens 724, compound or multiple lenses 726, planar form 728, or stepped form, such as illustrated in FIG. 10F. Any

transducer or combination of transducers may be utilized for treatment. For example, an annular transducer may be used with an outer portion dedicated to therapy and the inner disk dedicated to broadband imaging wherein such imaging transducer and therapy transducer have different acoustic ⁵ lenses and design, such as illustrated in FIG. 1 OC-1 OF.

Moreover, such transduction elements 700 may comprise a piezoelectrically active material, such as lead zirconante titanate (PZT), or any other piezoelectrically active material, such as a piezoelectric ceramic, crystal, plastic, and/or composite materials, as well as lithium niobate, lead titanate, barium titanate, and/or lead metaniobate. Transduction elements 700 may also comprise one or more matching layers configured along with the piezoelectrically active material. In addition to or instead of piezoelectrically active material, transduction elements 700 can comprise any other materials configured for generating radiation and/or acoustical energy. A means of transferring energy to and from the transducer to the region of interest is provided.

In accordance with another exemplary embodiment, with reference to FIG. 12, an exemplary treatment system 200 can be configured with and/or combined with various auxiliary systems to provide additional functions. For example, an exemplary treatment system 1200 for treating a region of 25 interest 1202 can comprise a control system 1206, a probe 1204, and a display 1208. Treatment system 1200 further comprises an auxiliary imaging modality 1272 and/or auxiliary monitoring modality 1274 may be based upon at least one of photography and other visual optical methods, mag- 30 netic resonance imaging (MRI), computed tomography (CT), optical coherence tomography (OCT), electromagnetic, microwave, or radio frequency (RF) methods, positron emission tomography (PET), infrared, ultrasound, acoustic, or any other suitable method of visualization, localization, or 35 monitoring of epidermal, superficial dermal, mid-dermal and deep dermal components within the region-of-interest 1202, including imaging/monitoring enhancements. Such imaging/monitoring enhancement for ultrasound imaging via probe 1204 and control system 1206 could comprise 40 M-mode, persistence, filtering, color, Doppler, and harmonic imaging among others; furthermore an ultrasound treatment system 1270, as a primary source of treatment, may be combined with a secondary source of treatment 1276, including radio frequency (RF), intense pulsed light (IPL), 45 laser, infrared laser, microwave, or any other suitable energy source.

In accordance with another exemplary embodiment, with reference to FIG. 13, treatment composed of imaging, monitoring, and/or therapy to a region of interest 1302 and/or 50 1308 may be aided, augmented, and/or delivered with passive or active devices 1304 and/or 1306 within the oral and/or nasal cavity, respectively. For example, if passive or active device 1304 and/or 1306 are second transducers or acoustic reflectors acoustically coupled to the mucous mem- 55 branes it is possible to obtain through transmission, tomographic, or round-trip acoustic waves which are useful for treatment monitoring, such as in measuring acoustic speed of sound and attenuation, which are temperature dependent; furthermore such transducers could be used to treat and/or 60 image. In addition an active, passive, or active/passive object 1304 and/or 1306 may be used to flatten the skin, and/or may be used as an imaging grid, marker, or beacon, to aid determination of position. A passive or active device 1304 and/or 1306 may also be used to aid cooling or 65 temperature control. Natural air in the oral cavity and/or nasal cavity may also be used as passive device 1304 and/or

14

1306 whereby it may be utilized to as an acoustic reflector to aid thickness measurement and monitoring function.

The present invention has been described above with reference to various exemplary embodiments. However, 5 those skilled in the art will recognize that changes and modifications may be made to the exemplary embodiments without departing from the scope of the present invention. For example, the various operational steps, as well as the components for carrying out the operational steps, may be implemented in alternate ways depending upon the particular application or in consideration of any number of cost functions associated with the operation of the system, e.g., various of the steps may be deleted, modified, or combined with other steps. These and other changes or modifications are intended to be included within the scope of the present invention, as set forth in the following claims.

What is claimed is:

- 1. An ultrasound system for treatment of skin laxity, the system comprising:
 - an ultrasound probe comprising a housing, wherein the housing comprises a motion mechanism and an ultrasound transducer.
 - wherein the ultrasound transducer comprises a therapy component,

wherein the therapy component consists of:

- a single active focused ultrasound therapy element, wherein the ultrasound therapy element is configured to provide a single mechanical focus,
- wherein the single mechanical focus is configured to provide ultrasound therapy energy in a form of a single thermal focus in a tissue at a depth below a skin surface.
- wherein the depth is a single, fixed depth in a range of up to 5 mm below the skin surface to treat the tissue,
- wherein the tissue comprises a combination of any of the group consisting of: an epidermal tissue, a superficial dermal tissue, a mid-dermal tissue, a deep dermal tissue, a muscle tissue, and an adipose tissue,
 - wherein the single thermal focus is formed without electronic focusing and without a lens,
- wherein a portion of the ultrasound probe is configured for acoustic coupling to the skin surface;
- a control system connected to the motion mechanism and the ultrasound therapy element;
- an input device connected to the control system; and a power supply connected to the control system;
- wherein the ultrasound therapy element is configured for delivery of energy at a temperature sufficient to tighten at least a portion of the tissue at the depth under the skin surface,
- wherein the ultrasound therapy element is connected to the motion mechanism.
- wherein the motion mechanism moves the ultrasound therapy element to form a plurality of thermal lesions at the depth for tighten at least a portion of the tissue for reducing an appearance of skin laxity.
- 2. The system of claim 1, wherein the ultrasound therapy element is configured to increase the temperature of the tissue in the region of interest to greater than 60° C.
- 3. The system of claim 1, further comprising a monitoring system.
 - wherein the monitoring system is configured to monitor a treatment parameter, wherein the treatment parameter measured comprises a temperature of the tissue below the skin surface,
 - wherein the housing further comprises a temperature monitoring sensor,

- wherein the therapy element is a single element that delivers ultrasound energy at a frequency of between 2 MHz to 25 MHz.
- 4. The system of claim 1, wherein the housing contains a temperature monitoring sensor,
 - wherein the control system comprises a processor, software, and a communication device,
 - wherein the ultrasound probe is connected to the control system via a cable,
 - wherein the processor relays data from the temperature $\,^{10}$ monitoring sensor via the communication device.
 - 5. The system of claim 1,
 - wherein the motion mechanism comprises an encoder and the ultrasound therapy energy is configured to deliver 15 an energy level for causing at least one of shrinking collagen and denaturing the tissue in the region of interest under a wrinkle,
 - wherein the therapy element delivers the ultrasound therapy energy at a frequency of between 2 MHz to 25 20
- 6. The system of claim 1, wherein the control system comprises a spatial control and a temporal control,
 - wherein the spatial control and the temporal control are configured for controlling the delivery of energy at a 25 temperature sufficient to cause denaturation of at least the portion of the tissue at the depth under the skin surface.
 - wherein the spatial control and the temporal control are configured for controlling the delivery of energy at a frequency of between 2 MHz to 25 MHz.
- 7. An ultrasound system for treatment of skin laxity, the system comprising:
 - an ultrasound probe configured for delivery of an ultrasound therapy energy at a temperature sufficient to heat at least a portion of a tissue at a depth under a skin surface,
 - wherein the tissue comprises a combination of any of the group consisting of: an epidermal tissue, a superficial 40 dermal tissue, a mid-dermal tissue, a deep dermal tissue, a muscle tissue, and an adipose tissue; and a control system;
 - wherein the ultrasound probe comprises a housing, wherein the housing comprises an ultrasound trans- 45
 - wherein the ultrasound transducer comprises a therapy component,
 - wherein the therapy component consists of:
 - a single active ultrasound therapy element,
 - wherein the single active ultrasound therapy element is configured to provide a single mechanical focus,
 - wherein the single mechanical focus is configured to provide ultrasound therapy energy in the form of a single thermal focus in the tissue at a depth below a 55 skin surface.
 - wherein the single thermal focus is formed without electronic focusing and without a lens,
 - wherein the ultrasound therapy element is in communication with the control system,
 - wherein the ultrasound therapy element is configured for delivery of the ultrasound therapy energy at the temperature sufficient to heat the at least a portion of the tissue at the depth under the skin surface,
 - wherein the ultrasound probe forms a plurality of thermal 65 lesions at the depth for reducing the appearance of skin

16

- 8. The system of claim 7, wherein the region of interest comprises the tissue, wherein the skin surface comprises a wrinkle, and wherein the plurality of thermal lesions tightens the tissue.
- 9. The system of claim 7, further comprising a monitoring
 - wherein the monitoring system is configured to monitor a treatment parameter, wherein the treatment parameter measured comprises a temperature of the tissue below the skin surface,
 - wherein the housing further comprises a temperature monitoring sensor, wherein the ultrasound therapy element delivers the ultrasound therapy energy at a frequency of between 2 MHz to 75 MHz.
- 10. The system of claim 7, wherein the ultrasound probe is connected to the control system via a cable, and wherein the control system comprises:
 - a communication device;
 - a processor, software, an input device, and a power supply.
 - 11. The system of claim 7,
 - wherein the ultrasound therapy element is a single element that delivers the ultrasound therapy energy at a frequency of between 2 MHz to 25 MHz, wherein the ultrasound therapy element is configured to increase the temperature of the tissue in the region of interest to greater than 60° C.
- 12. An ultrasound system for treatment of skin laxity, the system comprising:
 - an ultrasound probe comprising a housing, wherein the housing comprises an ultrasound transducer,
 - wherein the ultrasound transducer comprises a therapy component,
 - wherein the therapy component consists of:
 - a single active focused ultrasound therapy element, wherein the ultrasound therapy element is configured to provide a single mechanical focus,
 - wherein the single mechanical focus is configured to provide ultrasound therapy energy in the form of a single thermal focus in a tissue at a depth below a skin surface.
 - wherein the depth is up to 5 mm below the skin surface, wherein the tissue comprises a combination of any of the group consisting of: an epidermal tissue, a superficial dermal tissue, a mid-dermal tissue, a deep dermal tissue, an adipose tissue, and a muscle tissue,
 - wherein the single thermal focus is formed without electronic focusing and without a lens, and
 - a control system comprising a processor and power supply;
 - wherein the ultrasound therapy element is in communication with the control system,
 - wherein the ultrasound therapy element is configured for delivery of the ultrasound therapy energy at a temperature sufficient to denature at least a portion of the tissue in the region of interest at a depth under the skin surface.
 - wherein the ultrasound therapy element forms a plurality of thermal lesions at the depth for tightening the tissue for reducing skin laxity.
 - 13. The system of claim 12,
 - wherein the ultrasound probe is connected to the control system via a cable,
 - wherein the skin surface comprises a wrinkle.

- 14. The system of claim 12, further comprising an acoustic coupler between the ultrasound probe and the skin surface.
 - wherein the therapy element is a single element that delivers ultrasound energy at a frequency of between 2 5 MHz to 25 MHz,
 - wherein the housing further comprises a temperature monitoring sensor.
- 15. The system of claim 12, wherein the ultrasound therapy element is configured to increase the temperature of $_{10}$ the tissue in a region of interest to greater than 60° C.
- 16. The system of claim 12, further comprising an ultrasound imaging element co-housed with the ultrasound therapy element in the probe.
- 17. The system of claim 12, further comprising a moni- 15 toring system,
 - wherein the monitoring system is configured to monitor a treatment parameter, wherein the treatment parameter measured comprises a temperature of the tissue below the skin surface.

18

- 18. The system of claim 12,
- further comprising a motion mechanism for movement of the ultrasound therapy element to form a plurality of thermal lesions at the depth in the region of interest.
- 19. The system of claim 12,
- further comprising a motion mechanism configured for any one of the group consisting of linear, rotational, and variable movement of the ultrasound therapy element.
- 20. The system of claim 12,
- further comprising a motion mechanism with an encoder for monitoring a position of the ultrasound therapy element.
- wherein the therapy element is a single element that delivers the ultrasound therapy energy at a frequency of between 2 MHz to 25 MHz.
- wherein the ultrasound therapy element is configured to deliver the ultrasound therapy energy at the depth below the skin surface.

* * * * *



专利名称(译)	治疗皮肤松弛的系统		
公开(公告)号	<u>US9694211</u>	公开(公告)日	2017-07-04
申请号	US15/248407	申请日	2016-08-26
申请(专利权)人(译)	引导治疗系统,L.L.C.		
当前申请(专利权)人(译)	引导治疗系统,L.L.C.		
[标]发明人	BARTHE PETER G SLAYTON MICHAEL H MAKIN INDER RAJ S		
发明人	BARTHE, PETER G. SLAYTON, MICHAEL H. MAKIN, INDER RAJ S.		
IPC分类号	A61N7/02 A61B17/32 A6 A61B8/00	1B8/13 A61N7/00 G01S15/89 A61H	23/02 A61B8/12 A61B8/08 A61B5/00
CPC分类号	/461 A61B8/483 A61B8/5	46 A61B17/320068 A61H23/0245 A	61B8/12 A61B8/13 A61B8/4483 A61B8 61N7/00 G01S15/8909 A61H2201/5007 7/027 A61B8/4209 A61B8/4281 A61B8
优先权	14/169709 2015-05-26 US 13/230498 2014-02-04 US 11/163150 2011-11-29 US 60/617295 2004-10-07 US	S S	
其他公开文献	US20160361573A1		
外部链接	Espacenet USPTO		

摘要(译)

提供了一种用于皮肤松弛的超声治疗的系统和方法。系统和方法可以包括感兴趣区域的超声成像,用于治疗区域的定位,以深度和模式递送超声能量以实现期望的治疗效果,和/或监测治疗区域以评估结果和/或提供反馈。在一个实施例中,治疗系统和方法可以被配置用于产生亚毫米和更大的热消融区域的阵列,以治疗组织的表皮,浅表真皮,中真皮和深真皮组件。

