




US 20190201266A1

(19) **United States**(12) **Patent Application Publication**
Sayadi et al.(10) **Pub. No.: US 2019/0201266 A1**(43) **Pub. Date: Jul. 4, 2019**(54) **BED HAVING ROLLOVER IDENTIFYING
FEATURE**(71) Applicant: **Sleep Number Corporation,**
Minneapolis, MN (US)(72) Inventors: **Omid Sayadi, San Jose, CA (US); Carl
Hewitt, San Jose, CA (US); Steven Jay
Young, Los Gatos, CA (US)**(21) Appl. No.: **16/233,238**(22) Filed: **Dec. 27, 2018****Related U.S. Application Data**(60) Provisional application No. 62/611,084, filed on Dec.
28, 2017.**Publication Classification**(51) **Int. Cl.**
A61G 7/018 (2006.01)
A61B 5/00 (2006.01)
A47C 21/00 (2006.01)
A61G 7/015 (2006.01)(52) **U.S. Cl.**CPC **A61G 7/018** (2013.01); **A61B 5/4815**
(2013.01); **A47C 21/003** (2013.01); **A61B**
5/4809 (2013.01); **A61G 7/05769** (2013.01);
A61G 7/015 (2013.01); **A61B 5/4818**
(2013.01); **A61B 5/7267** (2013.01); **A61B**
5/4812 (2013.01)(57) **ABSTRACT**

A mattress has a first support portion configure to receive and support a first user and a second support portion configured to receive and support a second user. The first support portion and the second support portion are adjacent to each other such that the first user is capable of rolling over from the first support portion to the second support portion while sleeping on the first support portion. A sensor is configured to sense first pressure in the first support portion and sense second pressure in the second support portion. The sensor is further configured to transmit data of the first pressure and the second pressure. The controller is configured to receive the data and from the data of the first pressure and the second pressure, determine if the first user has rolled over from the first support portion to the second support portion.






FIG. 1





FIG. 2







FIG. 4A



402




FIG. 5

402 ↗




FIG. 6

404 ↗




FIG. 7

800 ↗




FIG. 8




FIG. 9




FIG. 10

412 ↗




FIG. 11

410a ↪




FIG. 12

410b ↪




FIG. 13

410c ↷




FIG. 14

1500 ↗




FIG. 15

1600 ↗




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20





FIG. 21



BED HAVING ROLLOVER IDENTIFYING FEATURE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to U.S. application Ser. No. 62/611,084, filed on Dec. 28, 2017. The disclosure of the prior application is considered part of the disclosure of this application, and is incorporated in its entirety into this application.

[0002] The present document relates to automation of a consumer device such as an airbed.

BACKGROUND

[0003] In general, a bed is a piece of furniture used as a location to sleep or relax. Many modern beds include a soft mattress on a bed frame. The mattress may include springs, foam material, and/or an air chamber to support the weight of one or more occupants.

SUMMARY

[0004] In one aspect, a system includes a mattress that includes a first support portion configured to receive and support a first user laying on the first portion. The mattress further includes a second support portion configured to receive and support a second user laying on the second portion. The first support portion and the second support portion are adjacent to each other such that the first user is capable of rolling over from the first support portion to the second support portion while sleeping on the first support portion. The system further includes a sensor configured to sense first pressure in the first support portion. The sensor is further configured to sense second pressure in the second support portion. The sensor is further configured to transmit, to a controller, data of the first pressure and the second pressure. The system further includes a controller configured to receive the data of the first pressure and the second pressure. The controller is further configured to, from the data of the first pressure and the second pressure, determine if the first user has rolled over from the first support portion to the second support portion. Other systems, devices, and methods may be used.

[0005] Implementations can include any, all, or none of the following features. Responsive to determining that the first user has rolled over from the first support portion to the second support portion, the controller is further configured to: transmit a control signal to a controllable device to engage the controllable device. The system including the controllable device, the controllable device configured to: receive the control signal to engage the controllable device; responsive to receiving the control signal to engage the controllable device, engage in order to alter the environment. The controllable device is a pressure controller and wherein engaging in order to alter the environment includes changing the pressure of the second support portion. The controllable device is a temperature controller and wherein engaging in order to alter the environment includes changing the temperature of the second support portion. The controllable device is an articulation controller and wherein engaging in order to alter the environment includes articulating the second support portion. The controller is further configured to: record in computer memory an amount of time that the first user has rolled onto the second support portion. The

controller is further configured to: record a degree of roll over. The controller is further configured to: determine if the roll over has negatively impacted the sleep quality of the second user. To determine if the first user has rolled over from the first support portion to the second support portion, the controller is configured to: generate a first parameter, from the data, that represents a measure of at least one from the group consisting of: the first user and the first support portion; using the first parameter, determine a movement value for the first user; if the determined movement value indicates movement for the first user, identify a rollover event using a covariation measure between the first support structure and the second support structure. The covariation measure between the first support structure and the second support structure represent measures of one of the group consisting of: amplitudes of pressure waves; rates of change of amplitudes of pressure waves; rates of motions of users; coherence measures; entropy of pressures; amplitude modulations of pressure waves; frequency modulations of pressure waves; phase differences of pressure waves; breathing rates; breathing amplitudes; heartbeat rates; heartbeat amplitudes. To determine if the first user has rolled over from the first support portion to the second support portion, the controller is configured to: detecting a decrease in the data of first pressure while also detecting an increase in the data of second pressure.

[0006] Implementations can include any, all, or none of the following features.

[0007] The technology of home automation can be improved. A bed that supports two users and tracks the two users can be configured to account for instances when one user rolls onto the support portion of another user. As such, the bed can account for pressure readings in which a single sensor signal contains information for more than one user. Home automation devices can be advantageously driven based on the existence of rollover events. In response to a rollover event, the home automation environment can advantageously engage to provide the users with their preferred experience.

[0008] Other features, aspects and potential advantages will be apparent from the accompanying description and figures.

[0009] DESCRIPTION OF DRAWINGS

[0010] FIG. 1 shows an example air bed system.

[0011] FIG. 2 is a block diagram of an example of various components of an air bed system.

[0012] FIG. 3 shows an example environment including a bed in communication with devices located in and around a home.

[0013] FIGS. 4A and 4B are block diagrams of example data processing systems that can be associated with a bed.

[0014] FIGS. 5 and 6 are block diagrams of examples of motherboards that can be used in a data processing system that can be associated with a bed.

[0015] FIG. 7 is a block diagram of an example of a daughterboard that can be used in a data processing system that can be associated with a bed.

[0016] FIG. 8 is a block diagram of an example of a motherboard with no daughterboard that can be used in a data processing system that can be associated with a bed.

[0017] FIG. 9 is a block diagram of an example of a sensory array that can be used in a data processing system that can be associated with a bed.

[0018] FIG. 10 is a block diagram of an example of a control array that can be used in a data processing system that can be associated with a bed

[0019] FIG. 11 is a block diagram of an example of a computing device that can be used in a data processing system that can be associated with a bed.

[0020] FIGS. 12-16 are block diagrams of example cloud services that can be used in a data processing system that can be associated with a bed.

[0021] FIG. 17 is a block diagram of an example of using a data processing system that can be associated with a bed to automate peripherals around the bed.

[0022] FIG. 18 is a schematic diagram that shows an example of a computing device and a mobile computing device.

[0023] FIGS. 19-21 are schematic diagrams of example beds supporting two users.

[0024] FIG. 22 is a swimlane diagram of an example process for identifying roll over events

[0025] Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION

[0026] A bed is designed with a left portion and a right portion to support a left user and a right user as they sleep. However, the users may roll over from their portion of the bed onto the other side of the bed. This can pose challenges to a bed system that is sensing information about the users based on their respective sides of the bed.

[0027] To account for user roll-over, the system can monitor the two sides of the bed and detect when a roll over happens. When detected, the system can disentangle readings from the bed in order to isolate the two users.

[0028] Example Airbed Hardware

[0029] FIG. 1 shows an example air bed system 100 that includes a bed 112. The bed 112 includes at least one air chamber 114 surrounded by a resilient border 116 and encapsulated by bed ticking 118. The resilient border 116 can comprise any suitable material, such as foam.

[0030] As illustrated in FIG. 1, the bed 112 can be a two chamber design having first and second fluid chambers, such as a first air chamber 114A and a second air chamber 114B. In alternative embodiments, the bed 112 can include chambers for use with fluids other than air that are suitable for the application. In some embodiments, such as single beds or kids' beds, the bed 112 can include a single air chamber 114A or 114B or multiple air chambers 114A and 114B. First and second air chambers 114A and 114B can be in fluid communication with a pump 120. The pump 120 can be in electrical communication with a remote control 122 via control box 124. The control box 124 can include a wired or wireless communications interface for communicating with one or more devices, including the remote control 122. The control box 124 can be configured to operate the pump 120 to cause increases and decreases in the fluid pressure of the first and second air chambers 114A and 114B based upon commands input by a user using the remote control 122. In some implementations, the control box 124 is integrated into a housing of the pump 120.

[0031] The remote control 122 can include a display 126, an output selecting mechanism 128, a pressure increase button 129, and a pressure decrease button 130. The output selecting mechanism 128 can allow the user to switch air flow generated by the pump 120 between the first and second

air chambers 114A and 114B, thus enabling control of multiple air chambers with a single remote control 122 and a single pump 120. For example, the output selecting mechanism 128 can be by a physical control (e.g., switch or button) or an input control displayed on display 126. Alternatively, separate remote control units can be provided for each air chamber and can each include the ability to control multiple air chambers. Pressure increase and decrease buttons 129 and 130 can allow a user to increase or decrease the pressure, respectively, in the air chamber selected with the output selecting mechanism 128. Adjusting the pressure within the selected air chamber can cause a corresponding adjustment to the firmness of the respective air chamber. In some embodiments, the remote control 122 can be omitted or modified as appropriate for an application. For example, in some embodiments the bed 112 can be controlled by a computer, tablet, smart phone, or other device in wired or wireless communication with the bed 112.

[0032] FIG. 2 is a block diagram of an example of various components of an air bed system. For example, these components can be used in the example air bed system 100. As shown in FIG. 2, the control box 124 can include a power supply 134, a processor 136, a memory 137, a switching mechanism 138, and an analog to digital (A/D) converter 140. The switching mechanism 138 can be, for example, a relay or a solid state switch. In some implementations, the switching mechanism 138 can be located in the pump 120 rather than the control box 124.

[0033] The pump 120 and the remote control 122 are in two-way communication with the control box 124. The pump 120 includes a motor 142, a pump manifold 143, a relief valve 144, a first control valve 145A, a second control valve 145B, and a pressure transducer 146. The pump 120 is fluidly connected with the first air chamber 114A and the second air chamber 114B via a first tube 148A and a second tube 148B, respectively. The first and second control valves 145A and 145B can be controlled by switching mechanism 138, and are operable to regulate the flow of fluid between the pump 120 and first and second air chambers 114A and 114B, respectively.

[0034] In some implementations, the pump 120 and the control box 124 can be provided and packaged as a single unit. In some alternative implementations, the pump 120 and the control box 124 can be provided as physically separate units. In some implementations, the control box 124, the pump 120, or both are integrated within or otherwise contained within a bed frame or bed support structure that supports the bed 112. In some implementations, the control box 124, the pump 120, or both are located outside of a bed frame or bed support structure (as shown in the example in FIG. 1).

[0035] The example air bed system 100 depicted in FIG. 2 includes the two air chambers 114A and 114B and the single pump 120. However, other implementations can include an air bed system having two or more air chambers and one or more pumps incorporated into the air bed system to control the air chambers. For example, a separate pump can be associated with each air chamber of the air bed system or a pump can be associated with multiple chambers of the air bed system. Separate pumps can allow each air chamber to be inflated or deflated independently and simultaneously. Furthermore, additional pressure transducers can

also be incorporated into the air bed system such that, for example, a separate pressure transducer can be associated with each air chamber.

[0036] In use, the processor 136 can, for example, send a decrease pressure command to one of air chambers 114A or 114B, and the switching mechanism 138 can be used to convert the low voltage command signals sent by the processor 136 to higher operating voltages sufficient to operate the relief valve 144 of the pump 120 and open the control valve 145A or 145B. Opening the relief valve 144 can allow air to escape from the air chamber 114A or 114B through the respective air tube 148A or 148B. During deflation, the pressure transducer 146 can send pressure readings to the processor 136 via the A/D converter 140. The A/D converter 140 can receive analog information from pressure transducer 146 and can convert the analog information to digital information useable by the processor 136. The processor 136 can send the digital signal to the remote control 122 to update the display 126 in order to convey the pressure information to the user.

[0037] As another example, the processor 136 can send an increase pressure command. The pump motor 142 can be energized in response to the increase pressure command and send air to the designated one of the air chambers 114A or 114B through the air tube 148A or 148B via electronically operating the corresponding valve 145A or 145B. While air is being delivered to the designated air chamber 114A or 114B in order to increase the firmness of the chamber, the pressure transducer 146 can sense pressure within the pump manifold 143. Again, the pressure transducer 146 can send pressure readings to the processor 136 via the A/D converter 140. The processor 136 can use the information received from the A/D converter 140 to determine the difference between the actual pressure in air chamber 114A or 114B and the desired pressure. The processor 136 can send the digital signal to the remote control 122 to update display 126 in order to convey the pressure information to the user.

[0038] Generally speaking, during an inflation or deflation process, the pressure sensed within the pump manifold 143 can provide an approximation of the pressure within the respective air chamber that is in fluid communication with the pump manifold 143. An example method of obtaining a pump manifold pressure reading that is substantially equivalent to the actual pressure within an air chamber includes turning off pump 120, allowing the pressure within the air chamber 114A or 114B and the pump manifold 143 to equalize, and then sensing the pressure within the pump manifold 143 with the pressure transducer 146. Thus, providing a sufficient amount of time to allow the pressures within the pump manifold 143 and chamber 114A or 114B to equalize can result in pressure readings that are accurate approximations of the actual pressure within air chamber 114A or 114B. In some implementations, the pressure of the air chambers 114A and/or 114B can be continuously monitored using multiple pressure sensors (not shown).

[0039] In some implementations, information collected by the pressure transducer 146 can be analyzed to determine various states of a person lying on the bed 112. For example, the processor 136 can use information collected by the pressure transducer 146 to determine a heart rate or a respiration rate for a person lying in the bed 112. For example, a user can be lying on a side of the bed 112 that includes the chamber 114A. The pressure transducer 146 can monitor fluctuations in pressure of the chamber 114A and

this information can be used to determine the user's heart rate and/or respiration rate. As another example, additional processing can be performed using the collected data to determine a sleep state of the person (e.g., awake, light sleep, deep sleep). For example, the processor 136 can determine when a person falls asleep and, while asleep, the various sleep states of the person.

[0040] Additional information associated with a user of the air bed system 100 that can be determined using information collected by the pressure transducer 146 includes motion of the user, presence of the user on a surface of the bed 112, weight of the user, heart arrhythmia of the user, and apnea. Taking user presence detection for example, the pressure transducer 146 can be used to detect the user's presence on the bed 112, e.g., via a gross pressure change determination and/or via one or more of a respiration rate signal, heart rate signal, and/or other biometric signals. For example, a simple pressure detection process can identify an increase in pressure as an indication that the user is present on the bed 112. As another example, the processor 136 can determine that the user is present on the bed 112 if the detected pressure increases above a specified threshold (so as to indicate that a person or other object above a certain weight is positioned on the bed 112). As yet another example, the processor 136 can identify an increase in pressure in combination with detected slight, rhythmic fluctuations in pressure as corresponding to the user being present on the bed 112. The presence of rhythmic fluctuations can be identified as being caused by respiration or heart rhythm (or both) of the user. The detection of respiration or a heartbeat can distinguish between the user being present on the bed and another object (e.g., a suit case) being placed upon the bed.

[0041] In some implementations, fluctuations in pressure can be measured at the pump 120. For example, one or more pressure sensors can be located within one or more internal cavities of the pump 120 to detect fluctuations in pressure within the pump 120. The fluctuations in pressure detected at the pump 120 can indicate fluctuations in pressure in one or both of the chambers 114A and 114B. One or more sensors located at the pump 120 can be in fluid communication with the one or both of the chambers 114A and 114B, and the sensors can be operative to determine pressure within the chambers 114A and 114B. The control box 124 can be configured to determine at least one vital sign (e.g., heart rate, respiratory rate) based on the pressure within the chamber 114A or the chamber 114B.

[0042] In some implementations, the control box 124 can analyze a pressure signal detected by one or more pressure sensors to determine a heart rate, respiration rate, and/or other vital signs of a user lying or sitting on the chamber 114A or the chamber 114B. More specifically, when a user lies on the bed 112 positioned over the chamber 114A, each of the user's heart beats, breaths, and other movements can create a force on the bed 112 that is transmitted to the chamber 114A. As a result of the force input to the chamber 114A from the user's movement, a wave can propagate through the chamber 114A and into the pump 120. A pressure sensor located at the pump 120 can detect the wave, and thus the pressure signal output by the sensor can indicate a heart rate, respiratory rate, or other information regarding the user.

[0043] With regard to sleep state, air bed system 100 can determine a user's sleep state by using various biometric

signals such as heart rate, respiration, and/or movement of the user. While the user is sleeping, the processor 136 can receive one or more of the user's biometric signals (e.g., heart rate, respiration, and motion) and determine the user's present sleep state based on the received biometric signals. In some implementations, signals indicating fluctuations in pressure in one or both of the chambers 114A and 114B can be amplified and/or filtered to allow for more precise detection of heart rate and respiratory rate.

[0044] The control box 124 can perform a pattern recognition algorithm or other calculation based on the amplified and filtered pressure signal to determine the user's heart rate and respiratory rate. For example, the algorithm or calculation can be based on assumptions that a heart rate portion of the signal has a frequency in the range of 0.5-4.0 Hz and that a respiration rate portion of the signal has a frequency in the range of less than 1 Hz. The control box 124 can also be configured to determine other characteristics of a user based on the received pressure signal, such as blood pressure, tossing and turning movements, rolling movements, limb movements, weight, the presence or lack of presence of a user, and/or the identity of the user. Techniques for monitoring a user's sleep using heart rate information, respiration rate information, and other user information are disclosed in U.S. Patent Application Publication No. 20100170043 to Steven J. Young et al., titled "APPARATUS FOR MONITORING VITAL SIGNS," the entire contents of which is incorporated herein by reference.

[0045] For example, the pressure transducer 146 can be used to monitor the air pressure in the chambers 114A and 114B of the bed 112. If the user on the bed 112 is not moving, the air pressure changes in the air chamber 114A or 114B can be relatively minimal, and can be attributable to respiration and/or heartbeat. When the user on the bed 112 is moving, however, the air pressure in the mattress can fluctuate by a much larger amount. Thus, the pressure signals generated by the pressure transducer 146 and received by the processor 136 can be filtered and indicated as corresponding to motion, heartbeat, or respiration.

[0046] In some implementations, rather than performing the data analysis in the control box 124 with the processor 136, a digital signal processor (DSP) can be provided to analyze the data collected by the pressure transducer 146. Alternatively, the data collected by the pressure transducer 146 could be sent to a cloud-based computing system for remote analysis.

[0047] In some implementations, the example air bed system 100 further includes a temperature controller configured to increase, decrease, or maintain the temperature of a bed, for example for the comfort of the user. For example, a pad can be placed on top of or be part of the bed 112, or can be placed on top of or be part of one or both of the chambers 114A and 114B. Air can be pushed through the pad and vented to cool off a user of the bed. Conversely, the pad can include a heating element that can be used to keep the user warm. In some implementations, the temperature controller can receive temperature readings from the pad. In some implementations, separate pads are used for the different sides of the bed 112 (e.g., corresponding to the locations of the chambers 114A and 114B) to provide for differing temperature control for the different sides of the bed.

[0048] In some implementations, the user of the air bed system 100 can use an input device, such as the remote

control 122, to input a desired temperature for the surface of the bed 112 (or for a portion of the surface of the bed 112). The desired temperature can be encapsulated in a command data structure that includes the desired temperature as well as identifies the temperature controller as the desired component to be controlled. The command data structure can then be transmitted via Bluetooth or another suitable communication protocol to the processor 136. In various examples, the command data structure is encrypted before being transmitted. The temperature controller can then configure its elements to increase or decrease the temperature of the pad depending on the temperature input into remote control 122 by the user.

[0049] In some implementations, data can be transmitted from a component back to the processor 136 or to one or more display devices, such as the display 126. For example, the current temperature as determined by a sensor element of temperature controller, the pressure of the bed, the current position of the foundation or other information can be transmitted to control box 124. The control box 124 can then transmit the received information to remote control 122 where it can be displayed to the user (e.g., on the display 126).

[0050] In some implementations, the example air bed system 100 further includes an adjustable foundation and an articulation controller configured to adjust the position of a bed (e.g., the bed 112) by adjusting the adjustable foundation that supports the bed. For example, the articulation controller can adjust the bed 112 from a flat position to a position in which a head portion of a mattress of the bed is inclined upward (e.g., to facilitate a user sitting up in bed and/or watching television). In some implementations, the bed 112 includes multiple separately articulable sections. For example, portions of the bed corresponding to the locations of the chambers 114A and 114B can be articulated independently from each other, to allow one person positioned on the bed 112 surface to rest in a first position (e.g., a flat position) while a second person rests in a second position (e.g., an reclining position with the head raised at an angle from the waist). In some implementations, separate positions can be set for two different beds (e.g., two twin beds placed next to each other). The foundation of the bed 112 can include more than one zone that can be independently adjusted. The articulation controller can also be configured to provide different levels of massage to one or more users on the bed 112.

[0051] Example of a Bed in a Bedroom Environment

[0052] FIG. 3 shows an example environment 300 including a bed 302 in communication with devices located in and around a home. In the example shown, the bed 302 includes pump 304 for controlling air pressure within two air chambers 306a and 306b (as described above with respect to the air chambers 114A-114B). The pump 304 additionally includes circuitry for controlling inflation and deflation functionality performed by the pump 304. The circuitry is further programmed to detect fluctuations in air pressure of the air chambers 306a-b and used the detected fluctuations in air pressure to identify bed presence of a user 308, sleep state of the user 308, movement of the user 308, and biometric signals of the user 308 such as heart rate and respiration rate. In the example shown, the pump 304 is located within a support structure of the bed 302 and the control circuitry 334 for controlling the pump 304 is integrated with the pump 304. In some implementations, the

control circuitry 334 is physically separate from the pump 304 and is in wireless or wired communication with the pump 304. In some implementations, the pump 304 and/or control circuitry 334 are located outside of the bed 302. In some implementations, various control functions can be performed by systems located in different physical locations. For example, circuitry for controlling actions of the pump 304 can be located within a pump casing of the pump 304 while control circuitry 334 for performing other functions associated with the bed 302 can be located in another portion of the bed 302, or external to the bed 302. As another example, control circuitry 334 located within the pump 304 can communicate with control circuitry 334 at a remote location through a LAN or WAN (e.g., the internet). As yet another example, the control circuitry 334 can be included in the control box 124 of FIGS. 1 and 2.

[0053] In some implementations, one or more devices other than, or in addition to, the pump 304 and control circuitry 334 can be utilized to identify user bed presence, sleep state, movement, and biometric signals. For example, the bed 302 can include a second pump in addition to the pump 304, with each of the two pumps connected to a respective one of the air chambers 306a-b. For example, the pump 304 can be in fluid communication with the air chamber 306b to control inflation and deflation of the air chamber 306b as well as detect user signals for a user located over the air chamber 306b such as bed presence, sleep state, movement, and biometric signals while the second pump is in fluid communication with the air chamber 306a to control inflation and deflation of the air chamber 306a as well as detect user signals for a user located over the air chamber 306a.

[0054] As another example, the bed 302 can include one or more pressure sensitive pads or surface portions that are operable to detect movement, including user presence, user motion, respiration, and heart rate. For example, a first pressure sensitive pad can be incorporated into a surface of the bed 302 over a left portion of the bed 302, where a first user would normally be located during sleep, and a second pressure sensitive pad can be incorporated into the surface of the bed 302 over a right portion of the bed 302, where a second user would normally be located during sleep. The movement detected by the one or more pressure sensitive pads or surface portions can be used by control circuitry 334 to identify user sleep state, bed presence, or biometric signals.

[0055] In some implementations, information detected by the bed (e.g., motion information) is processed by control circuitry 334 (e.g., control circuitry 334 integrated with the pump 304) and provided to one or more user devices such as a user device 310 for presentation to the user 308 or to other users. In the example depicted in FIG. 3, the user device 310 is a tablet device; however, in some implementations, the user device 310 can be a personal computer, a smart phone, a smart television (e.g., a television 312), or other user device capable of wired or wireless communication with the control circuitry 334. The user device 310 can be in communication with control circuitry 334 of the bed 302 through a network or through direct point-to-point communication. For example, the control circuitry 334 can be connected to a LAN (e.g., through a Wi-Fi router) and communicate with the user device 310 through the LAN. As another example, the control circuitry 334 and the user device 310 can both connect to the Internet and communi-

cate through the Internet. For example, the control circuitry 334 can connect to the Internet through a WiFi router and the user device 310 can connect to the Internet through communication with a cellular communication system. As another example, the control circuitry 334 can communicate directly with the user device 310 through a wireless communication protocol such as Bluetooth. As yet another example, the control circuitry 334 can communicate with the user device 310 through a wireless communication protocol such as ZigBee, Z-Wave, infrared, or another wireless communication protocol suitable for the application. As another example, the control circuitry 334 can communicate with the user device 310 through a wired connection such as, for example, a USB connector, serial/RS232, or another wired connection suitable for the application.

[0056] The user device 310 can display a variety of information and statistics related to sleep, or user 308's interaction with the bed 302. For example, a user interface displayed by the user device 310 can present information including amount of sleep for the user 308 over a period of time (e.g., a single evening, a week, a month, etc.) amount of deep sleep, ratio of deep sleep to restless sleep, time lapse between the user 308 getting into bed and the user 308 falling asleep, total amount of time spent in the bed 302 for a given period of time, heart rate for the user 308 over a period of time, respiration rate for the user 308 over a period of time, or other information related to user interaction with the bed 302 by the user 308 or one or more other users of the bed 302. In some implementations, information for multiple users can be presented on the user device 310, for example information for a first user positioned over the air chamber 306a can be presented along with information for a second user positioned over the air chamber 306b. In some implementations, the information presented on the user device 310 can vary according to the age of the user 308. For example, the information presented on the user device 310 can evolve with the age of the user 308 such that different information is presented on the user device 310 as the user 308 ages as a child or an adult.

[0057] The user device 310 can also be used as an interface for the control circuitry 334 of the bed 302 to allow the user 308 to enter information. The information entered by the user 308 can be used by the control circuitry 334 to provide better information to the user or to various control signals for controlling functions of the bed 302 or other devices. For example, the user can enter information such as weight, height, and age and the control circuitry 334 can use this information to provide the user 308 with a comparison of the user's tracked sleep information to sleep information of other people having similar weights, heights, and/or ages as the user 308. As another example, the user 308 can use the user device 310 as an interface for controlling air pressure of the air chambers 306a and 306b, for controlling various recline or incline positions of the bed 302, for controlling temperature of one or more surface temperature control devices of the bed 302, or for allowing the control circuitry 334 to generate control signals for other devices (as described in greater detail below).

[0058] In some implementations, control circuitry 334 of the bed 302 (e.g., control circuitry 334 integrated into the pump 304) can communicate with other first, second, or third party devices or systems in addition to or instead of the user device 310. For example, the control circuitry 334 can communicate with the television 312, a lighting system 314,

a thermostat 316, a security system 318, or other household devices such as an oven 322, a coffee maker 324, a lamp 326, and a nightlight 328. Other examples of devices and/or systems that the control circuitry 334 can communicate with include a system for controlling window blinds 330, one or more devices for detecting or controlling the states of one or more doors 332 (such as detecting if a door is open, detecting if a door is locked, or automatically locking a door), and a system for controlling a garage door 320 (e.g., control circuitry 334 integrated with a garage door opener for identifying an open or closed state of the garage door 320 and for causing the garage door opener to open or close the garage door 320). Communications between the control circuitry 334 of the bed 302 and other devices can occur through a network (e.g., a LAN or the Internet) or as point-to-point communication (e.g., using Bluetooth, radio communication, or a wired connection). In some implementations, control circuitry 334 of different beds 302 can communicate with different sets of devices. For example, a kid bed may not communicate with and/or control the same devices as an adult bed. In some embodiments, the bed 302 can evolve with the age of the user such that the control circuitry 334 of the bed 302 communicates with different devices as a function of age of the user.

[0059] The control circuitry 334 can receive information and inputs from other devices/systems and use the received information and inputs to control actions of the bed 302 or other devices. For example, the control circuitry 334 can receive information from the thermostat 316 indicating a current environmental temperature for a house or room in which the bed 302 is located. The control circuitry 334 can use the received information (along with other information) to determine if a temperature of all or a portion of the surface of the bed 302 should be raised or lowered. The control circuitry 334 can then cause a heating or cooling mechanism of the bed 302 to raise or lower the temperature of the surface of the bed 302. For example, the user 308 can indicate a desired sleeping temperature of 74 degrees while a second user of the bed 302 indicates a desired sleeping temperature of 72 degrees. The thermostat 316 can indicate to the control circuitry 334 that the current temperature of the bedroom is 72 degrees. The control circuitry 334 can identify that the user 308 has indicated a desired sleeping temperature of 74 degrees, and send control signals to a heating pad located on the user 308's side of the bed to raise the temperature of the portion of the surface of the bed 302 where the user 308 is located to raise the temperature of the user 308's sleeping surface to the desired temperature.

[0060] The control circuitry 334 can also generate control signals controlling other devices and propagate the control signals to the other devices. In some implementations, the control signals are generated based on information collected by the control circuitry 334, including information related to user interaction with the bed 302 by the user 308 and/or one or more other users. In some implementations, information collected from one or more other devices other than the bed 302 are used when generating the control signals. For example, information relating to environmental occurrences (e.g., environmental temperature, environmental noise level, and environmental light level), time of day, time of year, day of the week, or other information can be used when generating control signals for various devices in communication with the control circuitry 334 of the bed 302. For example, information on the time of day can be combined with

information relating to movement and bed presence of the user 308 to generate control signals for the lighting system 314. In some implementations, rather than or in addition to providing control signals for one or more other devices, the control circuitry 334 can provide collected information (e.g., information related to user movement, bed presence, sleep state, or biometric signals for the user 308) to one or more other devices to allow the one or more other devices to utilize the collected information when generating control signals. For example, control circuitry 334 of the bed 302 can provide information relating to user interactions with the bed 302 by the user 308 to a central controller (not shown) that can use the provided information to generate control signals for various devices, including the bed 302.

[0061] Still referring to FIG. 3, the control circuitry 334 of the bed 302 can generate control signals for controlling actions of other devices, and transmit the control signals to the other devices in response to information collected by the control circuitry 334, including bed presence of the user 308, sleep state of the user 308, and other factors. For example, control circuitry 334 integrated with the pump 304 can detect a feature of a mattress of the bed 302, such as an increase in pressure in the air chamber 306b, and use this detected increase in air pressure to determine that the user 308 is present on the bed 302. In some implementations, the control circuitry 334 can identify a heart rate or respiratory rate for the user 308 to identify that the increase in pressure is due to a person sitting, laying, or otherwise resting on the bed 302 rather than an inanimate object (such as a suitcase) having been placed on the bed 302. In some implementations, the information indicating user bed presence is combined with other information to identify a current or future likely state for the user 308. For example, a detected user bed presence at 11:00 am can indicate that the user is sitting on the bed (e.g., to tie her shoes, or to read a book) and does not intend to go to sleep, while a detected user bed presence at 10:00 pm can indicate that the user 308 is in bed for the evening and is intending to fall asleep soon. As another example, if the control circuitry 334 detects that the user 308 has left the bed 302 at 6:30 am (e.g., indicating that the user 308 has woken up for the day), and then later detects user bed presence of the user 308 at 7:30 am, the control circuitry 334 can use this information that the newly detected user bed presence is likely temporary (e.g., while the user 308 ties her shoes before heading to work) rather than an indication that the user 308 is intending to stay on the bed 302 for an extended period.

[0062] In some implementations, the control circuitry 334 is able to use collected information (including information related to user interaction with the bed 302 by the user 308, as well as environmental information, time information, and input received from the user) to identify use patterns for the user 308. For example, the control circuitry 334 can use information indicating bed presence and sleep states for the user 308 collected over a period of time to identify a sleep pattern for the user. For example, the control circuitry 334 can identify that the user 308 generally goes to bed between 9:30 pm and 10:00 pm, generally falls asleep between 10:00 pm and 11:00 pm, and generally wakes up between 6:30 am and 6:45 am based on information indicating user presence and biometrics for the user 308 collected over a week. The control circuitry 334 can use identified patterns for a user to better process and identify user interactions with the bed 302 by the user 308.

[0063] For example, given the above example user bed presence, sleep, and wake patterns for the user 308, if the user 308 is detected as being on the bed at 3:00 pm, the control circuitry 334 can determine that the user's presence on the bed is only temporary, and use this determination to generate different control signals than would be generated if the control circuitry 334 determined that the user 308 was in bed for the evening. As another example, if the control circuitry 334 detects that the user 308 has gotten out of bed at 3:00 am, the control circuitry 334 can use identified patterns for the user 308 to determine that the user has only gotten up temporarily (for example, to use the rest room, or get a glass of water) and is not up for the day. By contrast, if the control circuitry 334 identifies that the user 308 has gotten out of the bed 302 at 6:40 am, the control circuitry 334 can determine that the user is up for the day and generate a different set of control signals than those that would be generated if it were determined that the user 308 were only getting out of bed temporarily (as would be the case when the user 308 gets out of the bed 302 at 3:00 am). For other users 308, getting out of the bed 302 at 3:00 am can be the normal wake-up time, which the control circuitry 334 can learn and respond to accordingly.

[0064] As described above, the control circuitry 334 for the bed 302 can generate control signals for control functions of various other devices. The control signals can be generated, at least in part, based on detected interactions by the user 308 with the bed 302, as well as other information including time, date, temperature, etc. For example, the control circuitry 334 can communicate with the television 312, receive information from the television 312, and generate control signals for controlling functions of the television 312. For example, the control circuitry 334 can receive an indication from the television 312 that the television 312 is currently on. If the television 312 is located in a different room from the bed 302, the control circuitry 334 can generate a control signal to turn the television 312 off upon making a determination that the user 308 has gone to bed for the evening. For example, if bed presence of the user 308 on the bed 302 is detected during a particular time range (e.g., between 8:00 pm and 7:00 am) and persists for longer than a threshold period of time (e.g., 10 minutes) the control circuitry 334 can use this information to determine that the user 308 is in bed for the evening. If the television 312 is on (as indicated by communications received by the control circuitry 334 of the bed 302 from the television 312) the control circuitry 334 can generate a control signal to turn the television 312 off. The control signals can then be transmitted to the television (e.g., through a directed communication link between the television 312 and the control circuitry 334 or through a network). As another example, rather than turning off the television 312 in response to detection of user bed presence, the control circuitry 334 can generate a control signal that causes the volume of the television 312 to be lowered by a pre-specified amount.

[0065] As another example, upon detecting that the user 308 has left the bed 302 during a specified time range (e.g., between 6:00 am and 8:00 am) the control circuitry 334 can generate control signals to cause the television 312 to turn on and tune to a pre-specified channel (e.g., the user 308 has indicated a preference for watching the morning news upon getting out of bed in the morning). The control circuitry 334 can generate the control signal and transmit the signal to the television 312 to cause the television 312 to turn on and tune

to the desired station (which could be stored at the control circuitry 334, the television 312, or another location). As another example, upon detecting that the user 308 has gotten up for the day, the control circuitry 334 can generate and transmit control signals to cause the television 312 to turn on and begin playing a previously recorded program from a digital video recorder (DVR) in communication with the television 312.

[0066] As another example, if the television 312 is in the same room as the bed 302, the control circuitry 334 does not cause the television 312 to turn off in response to detection of user bed presence. Rather, the control circuitry 334 can generate and transmit control signals to cause the television 312 to turn off in response to determining that the user 308 is asleep. For example, the control circuitry 334 can monitor biometric signals of the user 308 (e.g., motion, heart rate, respiration rate) to determine that the user 308 has fallen asleep. Upon detecting that the user 308 is sleeping, the control circuitry 334 generates and transmits a control signal to turn the television 312 off. As another example, the control circuitry 334 can generate the control signal to turn off the television 312 after a threshold period of time after the user 308 has fallen asleep (e.g., 10 minutes after the user has fallen asleep). As another example, the control circuitry 334 generates control signals to lower the volume of the television 312 after determining that the user 308 is asleep. As yet another example, the control circuitry 334 generates and transmits a control signal to cause the television to gradually lower in volume over a period of time and then turn off in response to determining that the user 308 is asleep.

[0067] In some implementations, the control circuitry 334 can similarly interact with other media devices, such as computers, tablets, smart phones, stereo systems, etc. For example, upon detecting that the user 308 is asleep, the control circuitry 334 can generate and transmit a control signal to the user device 310 to cause the user device 310 to turn off, or turn down the volume on a video or audio file being played by the user device 310.

[0068] The control circuitry 334 can additionally communicate with the lighting system 314, receive information from the lighting system 314, and generate control signals for controlling functions of the lighting system 314. For example, upon detecting user bed presence on the bed 302 during a certain time frame (e.g., between 8:00 pm and 7:00 am) that lasts for longer than a threshold period of time (e.g., 10 minutes) the control circuitry 334 of the bed 302 can determine that the user 308 is in bed for the evening. In response to this determination, the control circuitry 334 can generate control signals to cause lights in one or more rooms other than the room in which the bed 302 is located to switch off. The control signals can then be transmitted to the lighting system 314 and executed by the lighting system 314 to cause the lights in the indicated rooms to shut off. For example, the control circuitry 334 can generate and transmit control signals to turn off lights in all common rooms, but not in other bedrooms. As another example, the control signals generated by the control circuitry 334 can indicate that lights in all rooms other than the room in which the bed 302 is located are to be turned off, while one or more lights located outside of the house containing the bed 302 are to be turned on, in response to determining that the user 308 is in bed for the evening. Additionally, the control circuitry 334 can generate and transmit control signals to cause the

nightlight 328 to turn on in response to determining user 308 bed presence or whether the user 308 is asleep. As another example, the control circuitry 334 can generate first control signals for turning off a first set of lights (e.g., lights in common rooms) in response to detecting user bed presence, and second control signals for turning off a second set of lights (e.g., lights in the room in which the bed 302 is located) in response to detecting that the user 308 is asleep.

[0069] In some implementations, in response to determining that the user 308 is in bed for the evening, the control circuitry 334 of the bed 302 can generate control signals to cause the lighting system 314 to implement a sunset lighting scheme in the room in which the bed 302 is located. A sunset lighting scheme can include, for example, dimming the lights (either gradually over time, or all at once) in combination with changing the color of the light in the bedroom environment, such as adding an amber hue to the lighting in the bedroom. The sunset lighting scheme can help to put the user 308 to sleep when the control circuitry 334 has determined that the user 308 is in bed for the evening.

[0070] The control circuitry 334 can also be configured to implement a sunrise lighting scheme when the user 308 wakes up in the morning. The control circuitry 334 can determine that the user 308 is awake for the day, for example, by detecting that the user 308 has gotten off of the bed 302 (i.e., is no longer present on the bed 302) during a specified time frame (e.g., between 6:00 am and 8:00 am). As another example, the control circuitry 334 can monitor movement, heart rate, respiratory rate, or other biometric signals of the user 308 to determine that the user 308 is awake even though the user 308 has not gotten out of bed. If the control circuitry 334 detects that the user is awake during a specified time frame, the control circuitry 334 can determine that the user 308 is awake for the day. The specified time frame can be, for example, based on previously recorded user bed presence information collected over a period of time (e.g., two weeks) that indicates that the user 308 usually wakes up for the day between 6:30 am and 7:30 am. In response to the control circuitry 334 determining that the user 308 is awake, the control circuitry 334 can generate control signals to cause the lighting system 314 to implement the sunrise lighting scheme in the bedroom in which the bed 302 is located. The sunrise lighting scheme can include, for example, turning on lights (e.g., the lamp 326, or other lights in the bedroom). The sunrise lighting scheme can further include gradually increasing the level of light in the room where the bed 302 is located (or in one or more other rooms). The sunrise lighting scheme can also include only turning on lights of specified colors. For example, the sunrise lighting scheme can include lighting the bedroom with blue light to gently assist the user 308 in waking up and becoming active.

[0071] In some implementations, the control circuitry 334 can generate different control signals for controlling actions of one or more components, such as the lighting system 314, depending on a time of day that user interactions with the bed 302 are detected. For example, the control circuitry 334 can use historical user interaction information for interactions between the user 308 and the bed 302 to determine that the user 308 usually falls asleep between 10:00 pm and 11:00 pm and usually wakes up between 6:30 am and 7:30 am on weekdays. The control circuitry 334 can use this information to generate a first set of control signals for controlling the lighting system 314 if the user 308 is detected

as getting out of bed at 3:00 am and to generate a second set of control signals for controlling the lighting system 314 if the user 308 is detected as getting out of bed after 6:30 am. For example, if the user 308 gets out of bed prior to 6:30 am, the control circuitry 334 can turn on lights that guide the user 308's route to a restroom. As another example, if the user 308 gets out of bed prior to 6:30 am, the control circuitry 334 can turn on lights that guide the user 308's route to the kitchen (which can include, for example, turning on the nightlight 328, turning on under bed lighting, or turning on the lamp 326).

[0072] As another example, if the user 308 gets out of bed after 6:30 am, the control circuitry 334 can generate control signals to cause the lighting system 314 to initiate a sunrise lighting scheme, or to turn on one or more lights in the bedroom and/or other rooms. In some implementations, if the user 308 is detected as getting out of bed prior to a specified morning rise time for the user 308, the control circuitry 334 causes the lighting system 314 to turn on lights that are dimmer than lights that are turned on by the lighting system 314 if the user 308 is detected as getting out of bed after the specified morning rise time. Causing the lighting system 314 to only turn on dim lights when the user 308 gets out of bed during the night (i.e., prior to normal rise time for the user 308) can prevent other occupants of the house from being woken by the lights while still allowing the user 308 to see in order to reach the restroom, kitchen, or another destination within the house.

[0073] The historical user interaction information for interactions between the user 308 and the bed 302 can be used to identify user sleep and awake time frames. For example, user bed presence times and sleep times can be determined for a set period of time (e.g., two weeks, a month, etc.). The control circuitry 334 can then identify a typical time range or time frame in which the user 308 goes to bed, a typical time frame for when the user 308 falls asleep, and a typical time frame for when the user 308 wakes up (and in some cases, different time frames for when the user 308 wakes up and when the user 308 actually gets out of bed). In some implementations, buffer time can be added to these time frames. For example, if the user is identified as typically going to bed between 10:00 pm and 10:30 pm, a buffer of a half hour in each direction can be added to the time frame such that any detection of the user getting onto the bed between 9:30 pm and 11:00 pm is interpreted as the user 308 going to bed for the evening. As another example, detection of bed presence of the user 308 starting from a half hour before the earliest typical time that the user 308 goes to bed extending until the typical wake up time (e.g., 6:30 am) for the user can be interpreted as the user going to bed for the evening. For example, if the user typically goes to bed between 10:00 pm and 10:30 pm, if the user's bed presence is sensed at 12:30 am one night, that can be interpreted as the user getting into bed for the evening even though this is outside of the user's typical time frame for going to bed because it has occurred prior to the user's normal wake up time. In some implementations, different time frames are identified for different times of the year (e.g., earlier bed time during winter vs. summer) or at different times of the week (e.g., user wakes up earlier on weekdays than on weekends).

[0074] The control circuitry 334 can distinguish between the user 308 going to bed for an extended period (such as for the night) as opposed to being present on the bed 302 for a

shorter period (such as for a nap) by sensing duration of presence of the user 308. In some examples, the control circuitry 334 can distinguish between the user 308 going to bed for an extended period (such as for the night) as opposed to going to bed for a shorter period (such as for a nap) by sensing duration of sleep of the user 308. For example, the control circuitry 334 can set a time threshold whereby if the user 308 is sensed on the bed 302 for longer than the threshold, the user 308 is considered to have gone to bed for the night. In some examples, the threshold can be about 2 hours, whereby if the user 308 is sensed on the bed 302 for greater than 2 hours, the control circuitry 334 registers that as an extended sleep event. In other examples, the threshold can be greater than or less than two hours.

[0075] The control circuitry 334 can detect repeated extended sleep events to determine a typical bed time range of the user 308 automatically, without requiring the user 308 to enter a bed time range. This can allow the control circuitry 334 to accurately estimate when the user 308 is likely to go to bed for an extended sleep event, regardless of whether the user 308 typically goes to bed using a traditional sleep schedule or a non-traditional sleep schedule. The control circuitry 334 can then use knowledge of the bed time range of the user 308 to control one or more components (including components of the bed 302 and/or non-bed peripherals) differently based on sensing bed presence during the bed time range or outside of the bed time range.

[0076] In some examples, the control circuitry 334 can automatically determine the bed time range of the user 308 without requiring user inputs. In some examples, the control circuitry 334 can determine the bed time range of the user 308 automatically and in combination with user inputs. In some examples, the control circuitry 334 can set the bed time range directly according to user inputs. In some examples, the control circuitry 334 can associate different bed times with different days of the week. In each of these examples, the control circuitry 334 can control one or more components (such as the lighting system 314, the thermostat 316, the security system 318, the oven 322, the coffee maker 324, the lamp 326, and the nightlight 328), as a function of sensed bed presence and the bed time range.

[0077] The control circuitry 334 can additionally communicate with the thermostat 316, receive information from the thermostat 316, and generate control signals for controlling functions of the thermostat 316. For example, the user 308 can indicate user preferences for different temperatures at different times, depending on the sleep state or bed presence of the user 308. For example, the user 308 may prefer an environmental temperature of 72 degrees when out of bed, 70 degrees when in bed but awake, and 68 degrees when sleeping. The control circuitry 334 of the bed 302 can detect bed presence of the user 308 in the evening and determine that the user 308 is in bed for the night. In response to this determination, the control circuitry 334 can generate control signals to cause the thermostat to change the temperature to 70 degrees. The control circuitry 334 can then transmit the control signals to the thermostat 316. Upon detecting that the user 308 is in bed during the bed time range or asleep, the control circuitry 334 can generate and transmit control signals to cause the thermostat 316 to change the temperature to 68. The next morning, upon determining that the user is awake for the day (e.g., the user 308 gets out of bed after

6:30 am) the control circuitry 334 can generate and transmit control circuitry 334 to cause the thermostat to change the temperature to 72 degrees.

[0078] In some implementations, the control circuitry 334 can similarly generate control signals to cause one or more heating or cooling elements on the surface of the bed 302 to change temperature at various times, either in response to user interaction with the bed 302 or at various pre-programmed times. For example, the control circuitry 334 can activate a heating element to raise the temperature of one side of the surface of the bed 302 to 73 degrees when it is detected that the user 308 has fallen asleep. As another example, upon determining that the user 308 is up for the day, the control circuitry 334 can turn off a heating or cooling element. As yet another example, the user 308 can pre-program various times at which the temperature at the surface of the bed should be raised or lowered. For example, the user can program the bed 302 to raise the surface temperature to 76 degrees at 10:00 pm, and lower the surface temperature to 68 degrees at 11:30 pm.

[0079] In some implementations, in response to detecting user bed presence of the user 308 and/or that the user 308 is asleep, the control circuitry 334 can cause the thermostat 316 to change the temperature in different rooms to different values. For example, in response to determining that the user 308 is in bed for the evening, the control circuitry 334 can generate and transmit control signals to cause the thermostat 316 to set the temperature in one or more bedrooms of the house to 72 degrees and set the temperature in other rooms to 67 degrees.

[0080] The control circuitry 334 can also receive temperature information from the thermostat 316 and use this temperature information to control functions of the bed 302 or other devices. For example, as discussed above, the control circuitry 334 can adjust temperatures of heating elements included in the bed 302 in response to temperature information received from the thermostat 316.

[0081] In some implementations, the control circuitry 334 can generate and transmit control signals for controlling other temperature control systems. For example, in response to determining that the user 308 is awake for the day, the control circuitry 334 can generate and transmit control signals for causing floor heating elements to activate. For example, the control circuitry 334 can cause a floor heating system for a master bedroom to turn on in response to determining that the user 308 is awake for the day.

[0082] The control circuitry 334 can additionally communicate with the security system 318, receive information from the security system 318, and generate control signals for controlling functions of the security system 318. For example, in response to detecting that the user 308 is in bed for the evening, the control circuitry 334 can generate control signals to cause the security system to engage or disengage security functions. The control circuitry 334 can then transmit the control signals to the security system 318 to cause the security system 318 to engage. As another example, the control circuitry 334 can generate and transmit control signals to cause the security system 318 to disable in response to determining that the user 308 is awake for the day (e.g., user 308 is no longer present on the bed 302 after 6:00 am). In some implementations, the control circuitry 334 can generate and transmit a first set of control signals to cause the security system 318 to engage a first set of security features in response to detecting user bed presence of the

user 308, and can generate and transmit a second set of control signals to cause the security system 318 to engage a second set of security features in response to detecting that the user 308 has fallen asleep.

[0083] In some implementations, the control circuitry 334 can receive alerts from the security system 318 (and/or a cloud service associated with the security system 318) and indicate the alert to the user 308. For example, the control circuitry 334 can detect that the user 308 is in bed for the evening and in response, generate and transmit control signals to cause the security system 318 to engage or disengage. The security system can then detect a security breach (e.g., someone has opened the door 332 without entering the security code, or someone has opened a window when the security system 318 is engaged). The security system 318 can communicate the security breach to the control circuitry 334 of the bed 302. In response to receiving the communication from the security system 318, the control circuitry 334 can generate control signals to alert the user 308 to the security breach. For example, the control circuitry 334 can cause the bed 302 to vibrate. As another example, the control circuitry 334 can cause portions of the bed 302 to articulate (e.g., cause the head section to raise or lower) in order to wake the user 308 and alert the user to the security breach. As another example, the control circuitry 334 can generate and transmit control signals to cause the lamp 326 to flash on and off at regular intervals to alert the user 308 to the security breach. As another example, the control circuitry 334 can alert the user 308 of one bed 302 regarding a security breach in a bedroom of another bed, such as an open window in a kid's bedroom. As another example, the control circuitry 334 can send an alert to a garage door controller (e.g., to close and lock the door). As another example, the control circuitry 334 can send an alert for the security to be disengaged.

[0084] The control circuitry 334 can additionally generate and transmit control signals for controlling the garage door 320 and receive information indicating a state of the garage door 320 (i.e., open or closed). For example, in response to determining that the user 308 is in bed for the evening, the control circuitry 334 can generate and transmit a request to a garage door opener or another device capable of sensing if the garage door 320 is open. The control circuitry 334 can request information on the current state of the garage door 320. If the control circuitry 334 receives a response (e.g., from the garage door opener) indicating that the garage door 320 is open, the control circuitry 334 can either notify the user 308 that the garage door is open, or generate a control signal to cause the garage door opener to close the garage door 320. For example, the control circuitry 334 can send a message to the user device 310 indicating that the garage door is open. As another example, the control circuitry 334 can cause the bed 302 to vibrate. As yet another example, the control circuitry 334 can generate and transmit a control signal to cause the lighting system 314 to cause one or more lights in the bedroom to flash to alert the user 308 to check the user device 310 for an alert (in this example, an alert regarding the garage door 320 being open). Alternatively, or additionally, the control circuitry 334 can generate and transmit control signals to cause the garage door opener to close the garage door 320 in response to identifying that the user 308 is in bed for the evening and that the garage door 320 is open. In some implementations, control signals can vary depend on the age of the user 308.

[0085] The control circuitry 334 can similarly send and receive communications for controlling or receiving state information associated with the door 332 or the oven 322. For example, upon detecting that the user 308 is in bed for the evening, the control circuitry 334 can generate and transmit a request to a device or system for detecting a state of the door 332. Information returned in response to the request can indicate various states for the door 332 such as open, closed but unlocked, or closed and locked. If the door 332 is open or closed but unlocked, the control circuitry 334 can alert the user 308 to the state of the door, such as in a manner described above with reference to the garage door 320. Alternatively, or in addition to alerting the user 308, the control circuitry 334 can generate and transmit control signals to cause the door 332 to lock, or to close and lock. If the door 332 is closed and locked, the control circuitry 334 can determine that no further action is needed.

[0086] Similarly, upon detecting that the user 308 is in bed for the evening, the control circuitry 334 can generate and transmit a request to the oven 322 to request a state of the oven 322 (e.g., on or off). If the oven 322 is on, the control circuitry 334 can alert the user 308 and/or generate and transmit control signals to cause the oven 322 to turn off. If the oven is already off, the control circuitry 334 can determine that no further action is necessary. In some implementations, different alerts can be generated for different events. For example, the control circuitry 334 can cause the lamp 326 (or one or more other lights, via the lighting system 314) to flash in a first pattern if the security system 318 has detected a breach, flash in a second pattern if garage door 320 is on, flash in a third pattern if the door 332 is open, flash in a fourth pattern if the oven 322 is on, and flash in a fifth pattern if another bed has detected that a user of that bed has gotten up (e.g., that a child of the user 308 has gotten out of bed in the middle of the night as sensed by a sensor in the bed 302 of the child). Other examples of alerts that can be processed by the control circuitry 334 of the bed 302 and communicated to the user include a smoke detector detecting smoke (and communicating this detection of smoke to the control circuitry 334), a carbon monoxide tester detecting carbon monoxide, a heater malfunctioning, or an alert from any other device capable of communicating with the control circuitry 334 and detecting an occurrence that should be brought to the user 308's attention.

[0087] The control circuitry 334 can also communicate with a system or device for controlling a state of the window blinds 330. For example, in response to determining that the user 308 is in bed for the evening, the control circuitry 334 can generate and transmit control signals to cause the window blinds 330 to close. As another example, in response to determining that the user 308 is up for the day (e.g., user has gotten out of bed after 6:30 am) the control circuitry 334 can generate and transmit control signals to cause the window blinds 330 to open. By contrast, if the user 308 gets out of bed prior to a normal rise time for the user 308, the control circuitry 334 can determine that the user 308 is not awake for the day and does not generate control signals for causing the window blinds 330 to open. As yet another example, the control circuitry 334 can generate and transmit control signals that cause a first set of blinds to close in response to detecting user bed presence of the user 308 and a second set of blinds to close in response to detecting that the user 308 is asleep.

[0088] The control circuitry 334 can generate and transmit control signals for controlling functions of other household devices in response to detecting user interactions with the bed 302. For example, in response to determining that the user 308 is awake for the day, the control circuitry 334 can generate and transmit control signals to the coffee maker 324 to cause the coffee maker 324 to begin brewing coffee. As another example, the control circuitry 334 can generate and transmit control signals to the oven 322 to cause the oven to begin preheating (for users that like fresh baked bread in the morning). As another example, the control circuitry 334 can use information indicating that the user 308 is awake for the day along with information indicating that the time of year is currently winter and/or that the outside temperature is below a threshold value to generate and transmit control signals to cause a car engine block heater to turn on.

[0089] As another example, the control circuitry 334 can generate and transmit control signals to cause one or more devices to enter a sleep mode in response to detecting user bed presence of the user 308, or in response to detecting that the user 308 is asleep. For example, the control circuitry 334 can generate control signals to cause a mobile phone of the user 308 to switch into sleep mode. The control circuitry 334 can then transmit the control signals to the mobile phone. Later, upon determining that the user 308 is up for the day, the control circuitry 334 can generate and transmit control signals to cause the mobile phone to switch out of sleep mode.

[0090] In some implementations, the control circuitry 334 can communicate with one or more noise control devices. For example, upon determining that the user 308 is in bed for the evening, or that the user 308 is asleep, the control circuitry 334 can generate and transmit control signals to cause one or more noise cancellation devices to activate. The noise cancellation devices can, for example, be included as part of the bed 302 or located in the bedroom with the bed 302. As another example, upon determining that the user 308 is in bed for the evening or that the user 308 is asleep, the control circuitry 334 can generate and transmit control signals to turn the volume on, off, up, or down, for one or more sound generating devices, such as a stereo system radio, computer, tablet, etc.

[0091] Additionally, functions of the bed 302 are controlled by the control circuitry 334 in response to user interactions with the bed 302. For example, the bed 302 can include an adjustable foundation and an articulation controller configured to adjust the position of one or more portions of the bed 302 by adjusting the adjustable foundation that supports the bed. For example, the articulation controller can adjust the bed 302 from a flat position to a position in which a head portion of a mattress of the bed 302 is inclined upward (e.g., to facilitate a user sitting up in bed and/or watching television). In some implementations, the bed 302 includes multiple separately articulable sections. For example, portions of the bed corresponding to the locations of the air chambers 306a and 306b can be articulated independently from each other, to allow one person positioned on the bed 302 surface to rest in a first position (e.g., a flat position) while a second person rests in a second position (e.g., a reclining position with the head raised at an angle from the waist). In some implementations, separate positions can be set for two different beds (e.g., two twin beds placed next to each other). The foundation of the bed 302 can include more than one zone that can be indepen-

dently adjusted. The articulation controller can also be configured to provide different levels of massage to one or more users on the bed 302 or to cause the bed to vibrate to communicate alerts to the user 308 as described above.

[0092] The control circuitry 334 can adjust positions (e.g., incline and decline positions for the user 308 and/or an additional user of the bed 302) in response to user interactions with the bed 302. For example, the control circuitry 334 can cause the articulation controller to adjust the bed 302 to a first recline position for the user 308 in response to sensing user bed presence for the user 308. The control circuitry 334 can cause the articulation controller to adjust the bed 302 to a second recline position (e.g., a less reclined, or flat position) in response to determining that the user 308 is asleep. As another example, the control circuitry 334 can receive a communication from the television 312 indicating that the user 308 has turned off the television 312, and in response the control circuitry 334 can cause the articulation controller to adjust the position of the bed 302 to a preferred user sleeping position (e.g., due to the user turning off the television 312 while the user 308 is in bed indicating that the user 308 wishes to go to sleep).

[0093] In some implementations, the control circuitry 334 can control the articulation controller so as to wake up one user of the bed 302 without waking another user of the bed 302. For example, the user 308 and a second user of the bed 302 can each set distinct wakeup times (e.g., 6:30 am and 7:15 am respectively). When the wakeup time for the user 308 is reached, the control circuitry 334 can cause the articulation controller to vibrate or change the position of only a side of the bed on which the user 308 is located to wake the user 308 without disturbing the second user. When the wakeup time for the second user is reached, the control circuitry 334 can cause the articulation controller to vibrate or change the position of only the side of the bed on which the second user is located. Alternatively, when the second wakeup time occurs, the control circuitry 334 can utilize other methods (such as audio alarms, or turning on the lights) to wake the second user since the user 308 is already awake and therefore will not be disturbed when the control circuitry 334 attempts to wake the second user.

[0094] Still referring to FIG. 3, the control circuitry 334 for the bed 302 can utilize information for interactions with the bed 302 by multiple users to generate control signals for controlling functions of various other devices. For example, the control circuitry 334 can wait to generate control signals for, for example, engaging the security system 318, or instructing the lighting system 314 to turn off lights in various rooms until both the user 308 and a second user are detected as being present on the bed 302. As another example, the control circuitry 334 can generate a first set of control signals to cause the lighting system 314 to turn off a first set of lights upon detecting bed presence of the user 308 and generate a second set of control signals for turning off a second set of lights in response to detecting bed presence of a second user. As another example, the control circuitry 334 can wait until it has been determined that both the user 308 and a second user are awake for the day before generating control signals to open the window blinds 330. As yet another example, in response to determining that the user 308 has left the bed and is awake for the day, but that a second user is still sleeping, the control circuitry 334 can generate and transmit a first set of control signals to cause the coffee maker 324 to begin brewing coffee, to cause the

security system **318** to deactivate, to turn on the lamp **326**, to turn off the nightlight **328**, to cause the thermostat **316** to raise the temperature in one or more rooms to 72 degrees, and to open blinds (e.g., the window blinds **330**) in rooms other than the bedroom in which the bed **302** is located. Later, in response to detecting that the second user is no longer present on the bed (or that the second user is awake) the control circuitry **334** can generate and transmit a second set of control signals to, for example, cause the lighting system **314** to turn on one or more lights in the bedroom, to cause window blinds in the bedroom to open, and to turn on the television **312** to a pre-specified channel.

[0095] Examples of Data Processing Systems Associated with a Bed

[0096] Described here are examples of systems and components that can be used for data processing tasks that are, for example, associated with a bed. In some cases, multiple examples of a particular component or group of components are presented. Some of these examples are redundant and/or mutually exclusive alternatives. Connections between components are shown as examples to illustrate possible network configurations for allowing communication between components. Different formats of connections can be used as technically needed or desired. The connections generally indicate a logical connection that can be created with any technologically feasible format. For example, a network on a motherboard can be created with a printed circuit board, wireless data connections, and/or other types of network connections. Some logical connections are not shown for clarity. For example, connections with power supplies and/or computer readable memory may not be shown for clarity sake, as many or all elements of a particular component may need to be connected to the power supplies and/or computer readable memory.

[0097] FIG. 4A is a block diagram of an example of a data processing system **400** that can be associated with a bed system, including those described above with respect to FIGS. 1-3. This system **400** includes a pump motherboard **402** and a pump daughterboard **404**. The system **400** includes a sensor array **406** that can include one or more sensors configured to sense physical phenomenon of the environment and/or bed, and to report such sensing back to the pump motherboard **402** for, for example, analysis. The system **400** also includes a controller array **408** that can include one or more controllers configured to control logic-controlled devices of the bed and/or environment. The pump motherboard **400** can be in communication with one or more computing devices **414** and one or more cloud services **410** over local networks, the Internet **412**, or otherwise as is technically appropriate. Each of these components will be described in more detail, some with multiple example configurations, below.

[0098] In this example, a pump motherboard **402** and a pump daughterboard **404** are communicably coupled. They can be conceptually described as a center or hub of the system **400**, with the other components conceptually described as spokes of the system **400**. In some configurations, this can mean that each of the spoke components communicates primarily or exclusively with the pump motherboard **402**. For example, a sensor of the sensor array may not be configured to, or may not be able to, communicate directly with a corresponding controller. Instead, each spoke component can communicate with the motherboard **402**. The sensor of the sensor array **406** can report a sensor

reading to the motherboard **402**, and the motherboard **402** can determine that, in response, a controller of the controller array **408** should adjust some parameters of a logic controlled device or otherwise modify a state of one or more peripheral devices. In one case, if the temperature of the bed is determined to be too hot, the pump motherboard **402** can determine that a temperature controller should cool the bed.

[0099] One advantage of a hub-and-spoke network configuration, sometimes also referred to as a star-shaped network, is a reduction in network traffic compared to, for example, a mesh network with dynamic routing. If a particular sensor generates a large, continuous stream of traffic, that traffic may only be transmitted over one spoke of the network to the motherboard **402**. The motherboard **402** can, for example, marshal that data and condense it to a smaller data format for retransmission for storage in a cloud service **410**. Additionally or alternatively, the motherboard **402** can generate a single, small, command message to be sent down a different spoke of the network in response to the large stream. For example, if the large stream of data is a pressure reading that is transmitted from the sensor array **406** a few times a second, the motherboard **402** can respond with a single command message to the controller array to increase the pressure in an air chamber. In this case, the single command message can be orders of magnitude smaller than the stream of pressure readings.

[0100] As another advantage, a hub-and-spoke network configuration can allow for an extensible network that can accommodate components being added, removed, failing, etc. This can allow, for example, more, fewer, or different sensors in the sensor array **406**, controllers in the controller array **408**, computing devices **414**, and/or cloud services **410**. For example, if a particular sensor fails or is deprecated by a newer version of the sensor, the system **400** can be configured such that only the motherboard **402** needs to be updated about the replacement sensor. This can allow, for example, product differentiation where the same motherboard **402** can support an entry level product with fewer sensors and controllers, a higher value product with more sensors and controllers, and customer personalization where a customer can add their own selected components to the system **400**.

[0101] Additionally, a line of air bed products can use the system **400** with different components. In an application in which every air bed in the product line includes both a central logic unit and a pump, the motherboard **402** (and optionally the daughterboard **404**) can be designed to fit within a single, universal housing. Then, for each upgrade of the product in the product line, additional sensors, controllers, cloud services, etc., can be added. Design, manufacturing, and testing time can be reduced by designing all products in a product line from this base, compared to a product line in which each product has a bespoke logic control system.

[0102] Each of the components discussed above can be realized in a wide variety of technologies and configurations. Below, some examples of each component will be further discussed. In some alternatives, two or more of the components of the system **400** can be realized in a single alternative component; some components can be realized in multiple, separate components; and/or some functionality can be provided by different components.

[0103] FIG. 4B is a block diagram showing some communication paths of the data processing system **400**. As

previously described, the motherboard **402** and the pump daughterboard **404** may act as a hub for peripheral devices and cloud services of the system **400**. In cases in which the pump daughterboard **404** communicates with cloud services or other components, communications from the pump daughterboard **404** may be routed through the pump motherboard **402**. This may allow, for example, the bed to have only a single connection with the internet **412**. The computing device **414** may also have a connection to the internet **412**, possibly through the same gateway used by the bed and/or possibly through a different gateway (e.g., a cell service provider).

[0104] Previously, a number of cloud services **410** were described. As shown in FIG. 4B, some cloud services, such as cloud services **410d** and **410e**, may be configured such that the pump motherboard **402** can communicate with the cloud service directly—that is the motherboard **402** may communicate with a cloud service **410** without having to use another cloud service **410** as an intermediary. Additionally or alternatively, some cloud services **410**, for example cloud service **410f**, may only be reachable by the pump motherboard **402** through an intermediary cloud service, for example cloud service **410e**. While not shown here, some cloud services **410** may be reachable either directly or indirectly by the pump motherboard **402**.

[0105] Additionally, some or all of the cloud services **410** may be configured to communicate with other cloud services. This communication may include the transfer of data and/or remote function calls according to any technologically appropriate format. For example, one cloud service **410** may request a copy for another cloud service's **410** data, for example, for purposes of backup, coordination, migration, or for performance of calculations or data mining. In another example, many cloud services **410** may contain data that is indexed according to specific users tracked by the user account cloud **410c** and/or the bed data cloud **410a**. These cloud services **410** may communicate with the user account cloud **410c** and/or the bed data cloud **410a** when accessing data specific to a particular user or bed.

[0106] FIG. 5 is a block diagram of an example of a motherboard **402** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. 1-3. In this example, compared to other examples described below, this motherboard **402** consists of relatively fewer parts and can be limited to provide a relatively limited feature set.

[0107] The motherboard includes a power supply **500**, a processor **502**, and computer memory **512**. In general, the power supply includes hardware used to receive electrical power from an outside source and supply it to components of the motherboard **402**. The power supply can include, for example, a battery pack and/or wall outlet adapter, an AC to DC converter, a DC to AC converter, a power conditioner, a capacitor bank, and/or one or more interfaces for providing power in the current type, voltage, etc., needed by other components of the motherboard **402**.

[0108] The processor **502** is generally a device for receiving input, performing logical determinations, and providing output. The processor **502** can be a central processing unit, a microprocessor, general purpose logic circuitry, application-specific integrated circuitry, a combination of these, and/or other hardware for performing the functionality needed.

[0109] The memory **512** is generally one or more devices for storing data. The memory **512** can include long term stable data storage (e.g., on a hard disk), short term unstable (e.g., on Random Access Memory) or any other technologically appropriate configuration.

[0110] The motherboard **402** includes a pump controller **504** and a pump motor **506**. The pump controller **504** can receive commands from the processor **502** and, in response, control the function of the pump motor **506**. For example, the pump controller **504** can receive, from the processor **502**, a command to increase the pressure of an air chamber by 0.3 pounds per square inch (PSI). The pump controller **504**, in response, engages a valve so that the pump motor **506** is configured to pump air into the selected air chamber, and can engage the pump motor **506** for a length of time that corresponds to 0.3 PSI or until a sensor indicates that pressure has been increased by 0.3 PSI. In an alternative configuration, the message can specify that the chamber should be inflated to a target PSI, and the pump controller **504** can engage the pump motor **506** until the target PSI is reached.

[0111] A valve solenoid **508** can control which air chamber a pump is connected to. In some cases, the solenoid **508** can be controlled by the processor **502** directly. In some cases, the solenoid **508** can be controlled by the pump controller **504**.

[0112] A remote interface **510** of the motherboard **402** can allow the motherboard **402** to communicate with other components of a data processing system. For example, the motherboard **402** can be able to communicate with one or more daughterboards, with peripheral sensors, and/or with peripheral controllers through the remote interface **510**. The remote interface **510** can provide any technologically appropriate communication interface, including but not limited to multiple communication interfaces such as WiFi, Bluetooth, and copper wired networks.

[0113] FIG. 6 is a block diagram of an example of a motherboard **402** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. 1-3. Compared to the motherboard **402** described with reference to FIG. 5, the motherboard in FIG. 6 can contain more components and provide more functionality in some applications.

[0114] In addition to the power supply **500**, processor **502**, pump controller **504**, pump motor **506**, and valve solenoid **508**, this motherboard **402** is shown with a valve controller **600**, a pressure sensor **602**, a universal serial bus (USB) stack **604**, a WiFi radio **606**, a Bluetooth Low Energy (BLE) radio **608**, a ZigBee radio **610**, a Bluetooth radio **612** and a computer memory **512**.

[0115] Similar to the way that the pump controller **504** converts commands from the processor **502** into control signals for the pump motor **506**, the valve controller **600** can convert commands from the processor **502** into control signals for the valve solenoid **508**. In one example, the processor **502** can issue a command to the valve controller **600** to connect the pump to a particular air chamber out of the group of air chambers in an air bed. The valve controller **600** can control the position of the valve solenoid **508** so that the pump is connected to the indicated air chamber.

[0116] The pressure sensor **602** can read pressure readings from one or more air chambers of the air bed. The pressure sensor **602** can also preform digital sensor conditioning.

[0117] The motherboard 402 can include a suite of network interfaces, including but not limited to those shown here. These network interfaces can allow the motherboard to communicate over a wired or wireless network with any number of devices, including but not limited to peripheral sensors, peripheral controllers, computing devices, and devices and services connected to the Internet 412.

[0118] FIG. 7 is a block diagram of an example of a daughterboard 404 that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. 1-3. In some configurations, one or more daughterboards 404 can be connected to the motherboard 402. Some daughterboards 404 can be designed to offload particular and/or compartmentalized tasks from the motherboard 402. This can be advantageous, for example, if the particular tasks are computationally intensive, proprietary, or subject to future revisions. For example, the daughterboard 404 can be used to calculate a particular sleep data metric. This metric can be computationally intensive, and calculating the sleep metric on the daughterboard 404 can free up the resources of the motherboard 402 while the metric is being calculated. Additionally and/or alternatively, the sleep metric can be subject to future revisions. To update the system 400 with the new sleep metric, it is possible that only the daughterboard 404 that calculates that metric need be replaced. In this case, the same motherboard 402 and other components can be used, saving the need to perform unit testing of additional components instead of just the daughterboard 404.

[0119] The daughterboard 404 is shown with a power supply 700, a processor 702, computer readable memory 704, a pressure sensor 706, and a WiFi radio 708. The processor can use the pressure sensor 706 to gather information about the pressure of the air chamber or chambers of an air bed. From this data, the processor 702 can perform an algorithm to calculate a sleep metric. In some examples, the sleep metric can be calculated from only the pressure of air chambers. In other examples, the sleep metric can be calculated from one or more other sensors. In an example in which different data is needed, the processor 702 can receive that data from an appropriate sensor or sensors. These sensors can be internal to the daughterboard 404, accessible via the WiFi radio 708, or otherwise in communication with the processor 702. Once the sleep metric is calculated, the processor 702 can report that sleep metric to, for example, the motherboard 402.

[0120] FIG. 8 is a block diagram of an example of a motherboard 800 with no daughterboard that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. 1-3. In this example, the motherboard 800 can perform most, all, or more of the features described with reference to the motherboard 402 in FIG. 6 and the daughterboard 404 in FIG. 7.

[0121] FIG. 9 is a block diagram of an example of a sensory array 406 that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. 1-3. In general, the sensor array 406 is a conceptual grouping of some or all the peripheral sensors that communicate with the motherboard 402 but are not native to the motherboard 402.

[0122] The peripheral sensors of the sensor array 406 can communicate with the motherboard 402 through one or more of the network interfaces of the motherboard, includ-

ing but not limited to the USB stack 604, a WiFi radio 606, a Bluetooth Low Energy (BLE) radio 608, a ZigBee radio 610, and a Bluetooth radio 612, as is appropriate for the configuration of the particular sensor. For example, a sensor that outputs a reading over a USB cable can communicate through the USB stack 604.

[0123] Some of the peripheral sensors 900 of the sensor array 406 can be bed mounted 900. These sensors can be, for example, embedded into the structure of a bed and sold with the bed, or later affixed to the structure of the bed. Other peripheral sensors 902 and 904 can be in communication with the motherboard 402, but optionally not mounted to the bed. In some cases, some or all of the bed mounted sensors 900 and/or peripheral sensors 902 and 904 can share networking hardware, including a conduit that contains wires from each sensor, a multi-wire cable or plug that, when affixed to the motherboard 402, connect all of the associated sensors with the motherboard 402. In some embodiments, one, some, or all of sensors 902, 904, 906, 908, and 910 can sense one or more features of a mattress, such as pressure, temperature, light, sound, and/or one or more other features of the mattress. In some embodiments, one, some, or all of sensors 902, 904, 906, 908, and 910 can sense one or more features external to the mattress. In some embodiments, pressure sensor 902 can sense pressure of the mattress while some or all of sensors 902, 904, 906, 908, and 910 can sense one or more features of the mattress and/or external to the mattress.

[0124] FIG. 10 is a block diagram of an example of a controller array 408 that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. 1-3. In general, the controller array 408 is a conceptual grouping of some or all peripheral controllers that communicate with the motherboard 402 but are not native to the motherboard 402.

[0125] The peripheral controllers of the controller array 408 can communicate with the motherboard 402 through one or more of the network interfaces of the motherboard, including but not limited to the USB stack 604, a WiFi radio 606, a Bluetooth Low Energy (BLE) radio 608, a ZigBee radio 610, and a Bluetooth radio 612, as is appropriate for the configuration of the particular sensor. For example, a controller that receives a command over a USB cable can communicate through the USB stack 604.

[0126] Some of the controllers of the controller array 408 can be bed mounted 1000. These controllers can be, for example, embedded into the structure of a bed and sold with the bed, or later affixed to the structure of the bed. Other peripheral controllers 1002 and 1004 can be in communication with the motherboard 402, but optionally not mounted to the bed. In some cases, some or all of the bed mounted controllers 1000 and/or peripheral controllers 1002 and 1004 can share networking hardware, including a conduit that contains wires for each controller, a multi-wire cable or plug that, when affixed to the motherboard 402, connects all of the associated controllers with the motherboard 402.

[0127] FIG. 11 is a block diagram of an example of a computing device 412 that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. 1-3. The computing device 412 can include, for example, computing devices used by a user of a bed. Example computing devices

412 include, but are not limited to, mobile computing devices (e.g., mobile phones, tablet computers, laptops) and desktop computers.

[0128] The computing device **412** includes a power supply **1100**, a processor **1102**, and computer readable memory **1104**. User input and output can be transmitted by, for example, speakers **1106**, a touchscreen **1108**, or other not shown components such as a pointing device or keyboard. The computing device **412** can run one or more applications **1110**. These applications can include, for example, application to allow the user to interact with the system **400**. These applications can allow a user to view information about the bed (e.g., sensor readings, sleep metrics), or configure the behavior of the system **400** (e.g., set a desired firmness to the bed, set desired behavior for peripheral devices). In some cases, the computing device **412** can be used in addition to, or to replace, the remote control **122** described previously.

[0129] FIG. 12 is a block diagram of an example bed data cloud service **410a** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. 1-3. In this example, the bed data cloud service **410a** is configured to collect sensor data and sleep data from a particular bed, and to match the sensor and sleep data with one or more users that use the bed when the sensor and sleep data was generated.

[0130] The bed data cloud service **410a** is shown with a network interface **1200**, a communication manager **1202**, server hardware **1204**, and server system software **1206**. In addition, the bed data cloud service **410a** is shown with a user identification module **1208**, a device management **1210** module, a sensor data module **1210**, and an advanced sleep data module **1214**.

[0131] The network interface **1200** generally includes hardware and low level software used to allow one or more hardware devices to communicate over networks. For example the network interface **1200** can include network cards, routers, modems, and other hardware needed to allow the components of the bed data cloud service **410a** to communicate with each other and other destinations over, for example, the Internet **412**. The communication manager **1202** generally comprises hardware and software that operate above the network interface **1200**. This includes software to initiate, maintain, and tear down network communications used by the bed data cloud service **410a**. This includes, for example, TCP/IP, SSL or TLS, Torrent, and other communication sessions over local or wide area networks. The communication manager **1202** can also provide load balancing and other services to other elements of the bed data cloud service **410a**.

[0132] The server hardware **1204** generally includes the physical processing devices used to instantiate and maintain bed data cloud service **410a**. This hardware includes, but is not limited to processors (e.g., central processing units, ASICs, graphical processors), and computer readable memory (e.g., random access memory, stable hard disks, tape backup). One or more servers can be configured into clusters, multi-computer, or datacenters that can be geographically separate or connected.

[0133] The server system software **1206** generally includes software that runs on the server hardware **1204** to provide operating environments to applications and services. The server system software **1206** can include operating systems running on real servers, virtual machines instanti-

ated on real servers to create many virtual servers, server level operations such as data migration, redundancy, and backup.

[0134] The user identification **1208** can include, or reference, data related to users of beds with associated data processing systems. For example, the users can include customers, owners, or other users registered with the bed data cloud service **410a** or another service. Each user can have, for example, a unique identifier, user credentials, contact information, billing information, demographic information, or any other technologically appropriate information.

[0135] The device manager **1210** can include, or reference, data related to beds or other products associated with data processing systems. For example, the beds can include products sold or registered with a system associated with the bed data cloud service **410a**. Each bed can have, for example, a unique identifier, model and/or serial number, sales information, geographic information, delivery information, a listing of associated sensors and control peripherals, etc. Additionally, an index or indexes stored by the bed data cloud service **410a** can identify users that are associated with beds. For example, this index can record sales of a bed to a user, users that sleep in a bed, etc.

[0136] The sensor data **1212** can record raw or condensed sensor data recorded by beds with associated data processing systems. For example, a bed's data processing system can have a temperature sensor, pressure sensor, and light sensor. Readings from these sensors, either in raw form or in a format generated from the raw data (e.g. sleep metrics) of the sensors, can be communicated by the bed's data processing system to the bed data cloud service **410a** for storage in the sensor data **1212**. Additionally, an index or indexes stored by the bed data cloud service **410a** can identify users and/or beds that are associated with the sensor data **1212**.

[0137] The bed data cloud service **410a** can use any of its available data to generate advanced sleep data **1214**. In general, the advanced sleep data **1214** includes sleep metrics and other data generated from sensor readings. Some of these calculations can be performed in the bed data cloud service **410a** instead of locally on the bed's data processing system, for example, because the calculations are computationally complex or require a large amount of memory space or processor power that is not available on the bed's data processing system. This can help allow a bed system to operate with a relatively simple controller and still be part of a system that performs relatively complex tasks and computations.

[0138] FIG. 13 is a block diagram of an example sleep data cloud service **410b** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. 1-3. In this example, the sleep data cloud service **410b** is configured to record data related to users' sleep experience.

[0139] The sleep data cloud service **410b** is shown with a network interface **1300**, a communication manager **1302**, server hardware **1304**, and server system software **1306**. In addition, the sleep data cloud service **410b** is shown with a user identification module **1308**, a pressure sensor manager **1310**, a pressure based sleep data module **1312**, a raw pressure sensor data module **1314**, and a non-pressure sleep data module **1316**.

[0140] The pressure sensor manager **1310** can include, or reference, data related to the configuration and operation of

pressure sensors in beds. For example, this data can include an identifier of the types of sensors in a particular bed, their settings and calibration data, etc.

[0141] The pressure based sleep data **1312** can use raw pressure sensor data **1314** to calculate sleep metrics specifically tied to pressure sensor data. For example, user presence, movements, weight change, heart rate, and breathing rate can all be determined from raw pressure sensor data **1314**. Additionally, an index or indexes stored by the sleep data cloud service **410b** can identify users that are associated with pressure sensors, raw pressure sensor data, and/or pressure based sleep data.

[0142] The non-pressure sleep data **1316** can use other sources of data to calculate sleep metrics. For example, user entered preferences, light sensor readings, and sound sensor readings can all be used to track sleep data. Additionally, an index or indexes stored by the sleep data cloud service **410b** can identify users that are associated with other sensors and/or non-pressure sleep data **1316**.

[0143] FIG. **14** is a block diagram of an example user account cloud service **410c** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. **1-3**. In this example, the user account cloud service **410c** is configured to record a list of users and to identify other data related to those users.

[0144] The user account cloud service **410c** is shown with a network interface **1400**, a communication manager **1402**, server hardware **1404**, and server system software **1406**. In addition, the user account cloud service **410c** is shown with a user identification module **1408**, a purchase history module **1410**, an engagement module **1412**, and an application usage history module **1414**.

[0145] The user identification module **1408** can include, or reference, data related to users of beds with associated data processing systems. For example, the users can include customers, owners, or other users registered with the user account cloud service **410a** or another service. Each user can have, for example, a unique identifier, and user credentials, demographic information, or any other technologically appropriate information.

[0146] The purchase history module **1410** can include, or reference, data related to purchases by users. For example, the purchase data can include a sale's contact information, billing information, and salesperson information. Additionally, an index or indexes stored by the user account cloud service **410c** can identify users that are associated with a purchase.

[0147] The engagement **1412** can track user interactions with the manufacturer, vendor, and/or manager of the bed and or cloud services. This engagement data can include communications (e.g., emails, service calls), data from sales (e.g., sales receipts, configuration logs), and social network interactions.

[0148] The usage history module **1414** can contain data about user interactions with one or more applications and/or remote controls of a bed. For example, a monitoring and configuration application can be distributed to run on, for example, computing devices **412**. This application can log and report user interactions for storage in the application usage history module **1414**. Additionally, an index or indexes stored by the user account cloud service **410c** can identify users that are associated with each log entry.

[0149] FIG. **15** is a block diagram of an example point of sale cloud service **1500** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. **1-3**. In this example, the point of sale cloud service **1500** is configured to record data related to users' purchases.

[0150] The point of sale cloud service **1500** is shown with a network interface **1502**, a communication manager **1504**, server hardware **1506**, and server system software **1508**. In addition, the point of sale cloud service **1500** is shown with a user identification module **1510**, a purchase history module **1512**, and a setup module **1514**.

[0151] The purchase history module **1512** can include, or reference, data related to purchases made by users identified in the user identification module **1510**. The purchase information can include, for example, data of a sale, price, and location of sale, delivery address, and configuration options selected by the users at the time of sale. These configuration options can include selections made by the user about how they wish their newly purchased beds to be setup and can include, for example, expected sleep schedule, a listing of peripheral sensors and controllers that they have or will install, etc.

[0152] The bed setup module **1514** can include, or reference, data related to installations of beds that users' purchase. The bed setup data can include, for example, the date and address to which a bed is delivered, the person that accepts delivery, the configuration that is applied to the bed upon delivery, the name or names of the person or people who will sleep on the bed, which side of the bed each person will use, etc.

[0153] Data recorded in the point of sale cloud service **1500** can be referenced by a user's bed system at later dates to control functionality of the bed system and/or to send control signals to peripheral components according to data recorded in the point of sale cloud service **1500**. This can allow a salesperson to collect information from the user at the point of sale that later facilitates automation of the bed system. In some examples, some or all aspects of the bed system can be automated with little or no user-entered data required after the point of sale. In other examples, data recorded in the point of sale cloud service **1500** can be used in connection with a variety of additional data gathered from user-entered data.

[0154] FIG. **16** is a block diagram of an example environment cloud service **1600** that can be used in a data processing system that can be associated with a bed system, including those described above with respect to FIGS. **1-3**. In this example, the environment cloud service **1600** is configured to record data related to users' home environment.

[0155] The environment cloud service **1600** is shown with a network interface **1602**, a communication manager **1604**, server hardware **1606**, and server system software **1608**. In addition, the environment cloud service **1600** is shown with a user identification module **1610**, an environmental sensor module **1612**, and an environmental factors module **1614**.

[0156] The environmental sensors module **1612** can include a listing of sensors that users' in the user identification module **1610** have installed in their bed. These sensors include any sensors that can detect environmental variables—light sensors, noise sensors, vibration sensors,

thermostats, etc. Additionally, the environmental sensors module **1612** can store historical readings or reports from those sensors.

[0157] The environmental factors module **1614** can include reports generated based on data in the environmental sensors module **1612**. For example, for a user with a light sensor with data in the environment sensors module **1612**, the environmental factors module **1614** can hold a report indicating the frequency and duration of instances of increased lighting when the user is asleep.

[0158] In the examples discussed here, each cloud service **410** is shown with some of the same components. In various configurations, these same components can be partially or wholly shared between services, or they can be separate. In some configurations, each service can have separate copies of some or all of the components that are the same or different in some ways. Additionally, these components are only supplied as illustrative examples. In other examples each cloud service can have different number, types, and styles of components that are technically possible.

[0159] FIG. 17 is a block diagram of an example of using a data processing system that can be associated with a bed (such as a bed of the bed systems described herein) to automate peripherals around the bed. Shown here is a behavior analysis module **1700** that runs on the pump motherboard **402**. For example, the behavior analysis module **1700** can be one or more software components stored on the computer memory **512** and executed by the processor **502**. In general, the behavior analysis module **1700** can collect data from a wide variety of sources (e.g., sensors, non-sensor local sources, cloud data services) and use a behavioral algorithm **1702** to generate one or more actions to be taken (e.g., commands to send to peripheral controllers, data to send to cloud services). This can be useful, for example, in tracking user behavior and automating devices in communication with the user's bed.

[0160] The behavior analysis module **1700** can collect data from any technologically appropriate source, for example, to gather data about features of a bed, the bed's environment, and/or the bed's users. Some such sources include any of the sensors of the sensor array **406**. For example, this data can provide the behavior analysis module **1700** with information about the current state of the environment around the bed. For example, the behavior analysis module **1700** can access readings from the pressure sensor **902** to determine the pressure of an air chamber in the bed. From this reading, and potentially other data, user presence in the bed can be determined. In another example, the behavior analysis module can access a light sensor **908** to detect the amount of light in the bed's environment.

[0161] Similarly, the behavior analysis module **1700** can access data from cloud services. For example, the behavior analysis module **1700** can access the bed cloud service **410a** to access historical sensor data **1212** and/or advanced sleep data **1214**. Other cloud services **410**, including those not previously described can be accessed by the behavior analysis module **1700**. For example, the behavior analysis module **1700** can access a weather reporting service, a 3rd party data provider (e.g., traffic and news data, emergency broadcast data, user travel data), and/or a clock and calendar service.

[0162] Similarly, the behavior analysis module **1700** can access data from non-sensor sources **1704**. For example, the

behavior analysis module **1700** can access a local clock and calendar service (e.g., a component of the motherboard **402** or of the processor **502**).

[0163] The behavior analysis module **1700** can aggregate and prepare this data for use by one or more behavioral algorithms **1702**. The behavioral algorithms **1702** can be used to learn a user's behavior and/or to perform some action based on the state of the accessed data and/or the predicted user behavior. For example, the behavior algorithm **1702** can use available data (e.g., pressure sensor, non-sensor data, clock and calendar data) to create a model of when a user goes to bed every night. Later, the same or a different behavioral algorithm **1702** can be used to determine if an increase in air chamber pressure is likely to indicate a user going to bed and, if so, send some data to a third-party cloud service **410** and/or engage a peripheral controller **1002**.

[0164] In the example shown, the behavioral analysis module **1700** and the behavioral algorithm **1702** are shown as components of the motherboard **402**. However, other configurations are possible. For example, the same or a similar behavioral analysis module and/or behavior algorithm can be run in one or more cloud services, and the resulting output can be sent to the motherboard **402**, a controller in the controller array **408**, or to any other technologically appropriate recipient.

[0165] FIG. 18 shows an example of a computing device **1800** and an example of a mobile computing device that can be used to implement the techniques described here. The computing device **1800** is intended to represent various forms of digital computers, such as laptops, desktops, workstations, personal digital assistants, servers, blade servers, mainframes, and other appropriate computers. The mobile computing device is intended to represent various forms of mobile devices, such as personal digital assistants, cellular telephones, smart-phones, and other similar computing devices. The components shown here, their connections and relationships, and their functions, are meant to be exemplary only, and are not meant to limit implementations of the inventions described and/or claimed in this document.

[0166] The computing device **1800** includes a processor **1802**, a memory **1804**, a storage device **1806**, a high-speed interface **1808** connecting to the memory **1804** and multiple high-speed expansion ports **1810**, and a low-speed interface **1812** connecting to a low-speed expansion port **1814** and the storage device **1806**. Each of the processor **1802**, the memory **1804**, the storage device **1806**, the high-speed interface **1808**, the high-speed expansion ports **1810**, and the low-speed interface **1812**, are interconnected using various busses, and can be mounted on a common motherboard or in other manners as appropriate. The processor **1802** can process instructions for execution within the computing device **1800**, including instructions stored in the memory **1804** or on the storage device **1806** to display graphical information for a GUI on an external input/output device, such as a display **1816** coupled to the high-speed interface **1808**. In other implementations, multiple processors and/or multiple buses can be used, as appropriate, along with multiple memories and types of memory. Also, multiple computing devices can be connected, with each device providing portions of the necessary operations (e.g., as a server bank, a group of blade servers, or a multi-processor system).

[0167] The memory **1804** stores information within the computing device **1800**. In some implementations, the memory **1804** is a volatile memory unit or units. In some implementations, the memory **1804** is a non-volatile memory unit or units. The memory **1804** can also be another form of computer-readable medium, such as a magnetic or optical disk.

[0168] The storage device **1806** is capable of providing mass storage for the computing device **1800**. In some implementations, the storage device **1806** can be or contain a computer-readable medium, such as a floppy disk device, a hard disk device, an optical disk device, or a tape device, a flash memory or other similar solid state memory device, or an array of devices, including devices in a storage area network or other configurations. A computer program product can be tangibly embodied in an information carrier. The computer program product can also contain instructions that, when executed, perform one or more methods, such as those described above. The computer program product can also be tangibly embodied in a computer- or machine-readable medium, such as the memory **1804**, the storage device **1806**, or memory on the processor **1802**.

[0169] The high-speed interface **1808** manages bandwidth-intensive operations for the computing device **1800**, while the low-speed interface **1812** manages lower bandwidth-intensive operations. Such allocation of functions is exemplary only. In some implementations, the high-speed interface **1808** is coupled to the memory **1804**, the display **1816** (e.g., through a graphics processor or accelerator), and to the high-speed expansion ports **1810**, which can accept various expansion cards (not shown). In the implementation, the low-speed interface **1812** is coupled to the storage device **1806** and the low-speed expansion port **1814**. The low-speed expansion port **1814**, which can include various communication ports (e.g., USB, Bluetooth, Ethernet, wireless Ethernet) can be coupled to one or more input/output devices, such as a keyboard, a pointing device, a scanner, or a networking device such as a switch or router, e.g., through a network adapter.

[0170] The computing device **1800** can be implemented in a number of different forms, as shown in the figure. For example, it can be implemented as a standard server **1820**, or multiple times in a group of such servers. In addition, it can be implemented in a personal computer such as a laptop computer **1822**. It can also be implemented as part of a rack server system **1824**. Alternatively, components from the computing device **1800** can be combined with other components in a mobile device (not shown), such as a mobile computing device **1850**. Each of such devices can contain one or more of the computing device **1800** and the mobile computing device **1850**, and an entire system can be made up of multiple computing devices communicating with each other.

[0171] The mobile computing device **1850** includes a processor **1852**, a memory **1864**, an input/output device such as a display **1854**, a communication interface **1866**, and a transceiver **1868**, among other components. The mobile computing device **1850** can also be provided with a storage device, such as a micro-drive or other device, to provide additional storage. Each of the processor **1852**, the memory **1864**, the display **1854**, the communication interface **1866**, and the transceiver **1868**, are interconnected using various buses, and several of the components can be mounted on a common motherboard or in other manners as appropriate.

[0172] The processor **1852** can execute instructions within the mobile computing device **1850**, including instructions stored in the memory **1864**. The processor **1852** can be implemented as a chipset of chips that include separate and multiple analog and digital processors. The processor **1852** can provide, for example, for coordination of the other components of the mobile computing device **1850**, such as control of user interfaces, applications run by the mobile computing device **1850**, and wireless communication by the mobile computing device **1850**.

[0173] The processor **1852** can communicate with a user through a control interface **1858** and a display interface **1856** coupled to the display **1854**. The display **1854** can be, for example, a TFT (Thin-Film-Transistor Liquid Crystal Display) display or an OLED (Organic Light Emitting Diode) display, or other appropriate display technology. The display interface **1856** can comprise appropriate circuitry for driving the display **1854** to present graphical and other information to a user. The control interface **1858** can receive commands from a user and convert them for submission to the processor **1852**. In addition, an external interface **1862** can provide communication with the processor **1852**, so as to enable near area communication of the mobile computing device **1850** with other devices. The external interface **1862** can provide, for example, for wired communication in some implementations, or for wireless communication in other implementations, and multiple interfaces can also be used.

[0174] The memory **1864** stores information within the mobile computing device **1850**. The memory **1864** can be implemented as one or more of a computer-readable medium or media, a volatile memory unit or units, or a non-volatile memory unit or units. An expansion memory **1874** can also be provided and connected to the mobile computing device **1850** through an expansion interface **1872**, which can include, for example, a SIMM (Single In Line Memory Module) card interface. The expansion memory **1874** can provide extra storage space for the mobile computing device **1850**, or can also store applications or other information for the mobile computing device **1850**. Specifically, the expansion memory **1874** can include instructions to carry out or supplement the processes described above, and can include secure information also. Thus, for example, the expansion memory **1874** can be provide as a security module for the mobile computing device **1850**, and can be programmed with instructions that permit secure use of the mobile computing device **1850**. In addition, secure applications can be provided via the SIMM cards, along with additional information, such as placing identifying information on the SIMM card in a non-hackable manner.

[0175] The memory can include, for example, flash memory and/or NVRAM memory (non-volatile random access memory), as discussed below. In some implementations, a computer program product is tangibly embodied in an information carrier. The computer program product contains instructions that, when executed, perform one or more methods, such as those described above. The computer program product can be a computer- or machine-readable medium, such as the memory **1864**, the expansion memory **1874**, or memory on the processor **1852**. In some implementations, the computer program product can be received in a propagated signal, for example, over the transceiver **1868** or the external interface **1862**.

[0176] The mobile computing device **1850** can communicate wirelessly through the communication interface **1866**, which can include digital signal processing circuitry where necessary. The communication interface **1866** can provide for communications under various modes or protocols, such as GSM voice calls (Global System for Mobile communications), SMS (Short Message Service), EMS (Enhanced Messaging Service), or MMS messaging (Multimedia Messaging Service), CDMA (code division multiple access), TDMA (time division multiple access), PDC (Personal Digital Cellular), WCDMA (Wideband Code Division Multiple Access), CDMA2000, or GPRS (General Packet Radio Service), among others. Such communication can occur, for example, through the transceiver **1868** using a radio-frequency. In addition, short-range communication can occur, such as using a Bluetooth, WiFi, or other such transceiver (not shown). In addition, a GPS (Global Positioning System) receiver module **1870** can provide additional navigation- and location-related wireless data to the mobile computing device **1850**, which can be used as appropriate by applications running on the mobile computing device **1850**.

[0177] The mobile computing device **1850** can also communicate audibly using an audio codec **1860**, which can receive spoken information from a user and convert it to usable digital information. The audio codec **1860** can likewise generate audible sound for a user, such as through a speaker, e.g., in a handset of the mobile computing device **1850**. Such sound can include sound from voice telephone calls, can include recorded sound (e.g., voice messages, music files, etc.) and can also include sound generated by applications operating on the mobile computing device **1850**.

[0178] The mobile computing device **1850** can be implemented in a number of different forms, as shown in the figure. For example, it can be implemented as a cellular telephone **1880**. It can also be implemented as part of a smart-phone **1882**, personal digital assistant, or other similar mobile device.

[0179] Various implementations of the systems and techniques described here can be realized in digital electronic circuitry, integrated circuitry, specially designed ASICs (application specific integrated circuits), computer hardware, firmware, software, and/or combinations thereof. These various implementations can include implementation in one or more computer programs that are executable and/or interpretable on a programmable system including at least one programmable processor, which can be special or general purpose, coupled to receive data and instructions from, and to transmit data and instructions to, a storage system, at least one input device, and at least one output device.

[0180] These computer programs (also known as programs, software, software applications or code) include machine instructions for a programmable processor, and can be implemented in a high-level procedural and/or object-oriented programming language, and/or in assembly/machine language. As used herein, the terms machine-readable medium and computer-readable medium refer to any computer program product, apparatus and/or device (e.g., magnetic discs, optical disks, memory, Programmable Logic Devices (PLDs)) used to provide machine instructions and/or data to a programmable processor, including a machine-readable medium that receives machine instructions as a machine-readable signal. The term machine-readable signal

refers to any signal used to provide machine instructions and/or data to a programmable processor.

[0181] To provide for interaction with a user, the systems and techniques described here can be implemented on a computer having a display device (e.g., a CRT (cathode ray tube) or LCD (liquid crystal display) monitor) for displaying information to the user and a keyboard and a pointing device (e.g., a mouse or a trackball) by which the user can provide input to the computer. Other kinds of devices can be used to provide for interaction with a user as well; for example, feedback provided to the user can be any form of sensory feedback (e.g., visual feedback, auditory feedback, or tactile feedback); and input from the user can be received in any form, including acoustic, speech, or tactile input.

[0182] The systems and techniques described here can be implemented in a computing system that includes a back end component (e.g., as a data server), or that includes a middleware component (e.g., an application server), or that includes a front end component (e.g., a client computer having a graphical user interface or a Web browser through which a user can interact with an implementation of the systems and techniques described here), or any combination of such back end, middleware, or front end components. The components of the system can be interconnected by any form or medium of digital data communication (e.g., a communication network). Examples of communication networks include a local area network (LAN), a wide area network (WAN), and the Internet.

[0183] The computing system can include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other.

[0184] FIGS. 19-21 are schematic diagrams of example beds supporting two users. As will be understood, in modern times some beds are designed to support a single user, while some beds are designed to support two sleepers laying side-by-side. In general, the beds designed to support two users are wider, with one user sleeping on one side (e.g., the “left” or “right”) and the other user sleeping on the other side. However, in use, one or both users are capable of moving in their sleep, or even before sleep. For example, one sleeper may roll over in their sleep and migrate from their side of the bed toward the other user’s side of the bed. The rolling sleeper may then partially or fully end up on the other side of the bed. In another example, the two users may cuddle together as they fall asleep or as they are sleeping. This can result in one or both users being partly or wholly on the other side of the bed.

[0185] FIG. 1900 shows two users **1902** and **1904** that are sleeping on their respective support portions **1903** and **1905** of a bed **1906**. In some cases, the support portions **1903** and **1905** are or contain air bladders that have an adjustable firmness controlled by a controller **1908**. In some cases, the support portions **1903** and **1905** are connected to one or more sensors (e.g., in the controller **1908**) that are able to sense pressure values of the support portions **1903** and **1905**, which can change depending on the movement, weight, position, etc., of the users **1902** and **1904**. In general, a first support portion **1903** can be configured to receive and support a first user **1902** laying on the first portion **1903**; and the

second support portion 1905 can be configured to receive and support the second user 1904 laying on the second support portion 1905.

[0186] The first support portion 1903 and the second support portion 1905 are adjacent to each other such that the first user is 1902 capable of rolling over from the first support portion 1903 to the second support portion 1905 while sleeping on the first support portion 1903. FIG. 19 shows the first user 1902 centered on the first support portion 1903, for example as a result of laying down on the first support portion 1903 to go to sleep. FIG. 20 shows the user 1902 having rolled toward the second support portion 1905. For example, the user 1902 may have rolled from sleeping on their back to their left side, resulting in a movement that has moved the user 1902 partially on the support portion 1903 and partly on the support portion 1905. FIG. 21 shows the user 1902 having rolled onto the second support portion 1905. For example, the user 1902 may have reached out to the user 1904 in order to cuddle while the two users sleep. As used here, roll over of a user can include movements that move a user to a different part of the bed without any actual rolling action. However, for brevity and clarity, scoots, slides, shimmy and other actions are included in the roll over action.

[0187] The controller 1908 can receive data from the one or more sensors and use that data to monitor information about the users 1902 and 1904. For example, the controller 1908 can determine heart action 1910 and 1912, breathing action 1914 and 1916, and metrics 1918 and 1920 from pressure sensing of the first support portion 1903 and 1905. As shown here, the user 1902 being centered on the support portion 1903 and the user 1904 being centered on the support portion 1904 result in heart action and breathing action measurements that mimic the heart action and breathing of a single human. Their metrics 1918 and 1920 represent accurate measures of their actual physical state.

[0188] In FIG. 20, with the user 1902 partially on the support portion 1905, heart action 2010 and 2012, breathing action 2014 and 2016, and metrics 2018 and 2020 are shown as they could be calculated without accounting for the user 1902 being partly on the support portion 1905. As shown, the amplitude of the heart action 2010 and breathing action 2014 are significantly reduced compared to heart action 1910 and breathing action 1914. Similarly, the metrics 2018 have changed, and now no longer reflect the actual state of the user 1902. That is to say, the metrics shown here are not accurate measures of the user's biological activity and are in fact outside of reasonable values for a healthy human.

[0189] Meanwhile, heart action 2012, breathing action 2116, and metrics 2020 have been influenced by the presence of the user 1902 and no longer show valid information about a single user, neither user 1902 nor user 1904. However, if the controller 1908 does compensate for the fact that the user 1902 has moved partly to the support portion 1903, the controller 1908 is able to calculate the correct heart action, breathing action, and metrics as shown in FIG. 19.

[0190] In FIG. 21, with the user 1902 completely on the support portion 1905, heart action 2110 and 2112, breathing action 2114 and 2116, and metrics 2118 and 2120 are shown as they could be calculated without accounting for the user 1902 being completely on the support portion 1905. As shown, there is no detected heart action 2110 or breathing action 2114. Similarly, the metrics 2118 have changed, and

now no longer reflect the actual state of the user 1902. Meanwhile, heart action 2112, breathing action 2116, and metrics 2120 have been influenced by the presence of the user 1902 and no longer show valid information about a single user, neither user 1902 nor user 1904. However, if the controller 1908 does compensate for the fact that the user 1902 has moved partly to the support portion 1903, the controller 1908 is able to calculate the correct heart action, breathing action, and metrics as shown in FIG. 19.

[0191] As will be understood, there are many cases in which a single user is sleeping in a bed large enough for two users like the bed 1906. In such a case, when the user transitions from one side to the other, the system can identify this rollover event and continue tracking user data (e.g., biometrics) on the other side of the bed, recognizing that it is still the same user. As such, the tracked data can be stored to the same profile as before the user rolled over, as opposed to a different user's profile. This functionality can advantageously allow for improved tracking of single users in beds large enough for two users to sleep on.

[0192] FIG. 22 is a swimlane diagram of an example process 2200 for identifying roll over events. In the process 2200, a first user and a second user are laying on a bed, with the first user resting on a first support portion of the bed and a second user resting on a second support portion of the bed. A pressure sensor 2202 is arranged to sense pressure in the first support portion and the second support portion, and is configured to communicate data with a controller 2204. A memory device is in data communication with the controller 2204, either as being part of the controller 2204 or separate, including in a remote location (e.g., a remote server). A controllable device 2206 is in data communication with the controller 2204, and is able to make changes to the environment of the bed, for either the first user, the second user, or both.

[0193] The pressure sensor 2202 senses first pressure in the first support portion and senses second pressure in the second support portion (2210). For example, the pressure sensor 2202, which may include one or more sensors, can sense pressure values of a first air bladder within the first support portion and of a second air bladder within the second support portion. The pressure sensor can generate, for example, two streams of electrical data or signals that represent or are proportional to the sensed pressure within the air bladders.

[0194] The pressure sensor 2202 transmits, the controller 2204, data of the first pressure and the second pressure (2212) and the controller 2204 receives the data of the first pressure and the second pressure (2214). For example, the pressure sensor 2202 can transmit the data across a wired or wireless network channel so that it is received by the controller 2204. In some cases, if the controller 2204 has not detected user presence from the data of the pressures, the process 2200 can wait until presence is detected.

[0195] The controller 2204 determines, from the data of the first pressure and the second pressure, if the first user has rolled over from the first support portion to the second support portion (2216). For example, in order to determine if a user has rolled over, the controller 2204 can (i) create epochs by segmenting the data into a series of pressure data segments in time, (ii) determine, for each epoch, one or more parameter values of the pressure variations for each support portion, (iii) compare the parameter values and changes in the parameter values, ranges, or patterns of changes indica-

tive of movement, (iv) cross-comparing the one or more parameter values from the first support surface with the one or more parameter values from the second support surface, (v) generate, within each epoch, one or more relational parameters indicative of a change in one support portion relative to the other, and (iv) use the relational parameters to determine if a rollover has occurred.

[0196] In some cases, determining **2216** can include identifying an increase in one of the pressures while there is a decrease in the other of the pressures. For example, an increase in the first pressure contemporaneous with a decrease in second pressure can be used to determine that there has been a rollover of a user from the second side to the first side. In addition or in the alternative, a contemporaneous change to data (e.g., **1910**, **1914**, **1918**) with a decrease in pressure can indicate a rollover away from the area with the pressure decrease. The detection of the increase can include determining that the increase is greater than a threshold value or passes another test. This testing can be used to detect only increases that are indicative of a rollover. This testing can be used to exclude minor increases not indicative of a rollover. For example, a change in pressure faster (or slower) than a particular rate can be identified for this determining, while a change in pressure slower (or faster) than the particular rate can be ignored for this purpose.

[0197] The controller **2204** can apply a filter to the data, for example to reduce noise and enhance motion components of the data. Examples of the kind of filter(s) that can be applied include, but are not limited to lowpass, highpass, bandpass, bandstop, notch filters, and/or a combination thereof.

[0198] In order to create the epochs, the controller **2204** can partition the data from the pressure sensor **2202** into segments bounded by timestamps a regular distance apart. For example, the controller **2204** can generate blocks of data that represent 1 second, 30 seconds, or 1 minute in time. In some cases, the epochs can overlap.

[0199] The controller **2204** can normalize the data of the first support surface and the second support portion. In some cases, physical differences between the first support portion and the second support portion, between the first user and the second user, and other factors can cause differences in the sensitivity of the sensing of pressure or other differences. The controller can apply one or more normalizing factors in order to bring the signal in the data of the two supports into the same range. Example normalization factors include, but are not limited to, normalizing maximum values, normalizing for a predefined percentage of the first and second support portions, removing the mean of the data streams and dividing by the standard deviation (either using each streams individual mean and standard deviation, or using combined values for mean and standard deviations).

[0200] The controller **2204** can generate a first parameter, from the data, that represents a measure of at least one from the first user and the first support portion and the controller **2204** can generate a second parameter, from the data, that represents a measure of at least one from the second user and the second support portion. Example parameters include, but are not limited to, user movement, user breathing rate, user breathing amplitude, user heart rate, and user heart beat amplitude.

[0201] Using the first parameter, the controller **2204** can determine a movement value for the first user. For example, the movement value may be a binary value indicating

moving/not moving. In some examples, the movement value can represent a confidence value that indicates the confidence produced by a statistical test on an epoch's worth of pressure data to determine if it is likely or unlikely to represent user movement.

[0202] If the controller **2206** determined a movement value indicates movement for the first user in an epoch, the controller **2206** can identify a rollover event in the epoch, if present, using a comparison of covariations for the first support portion with the parameter for the second support portion. In general, the covariation is a measure of the correlation of the variations of two measured or calculated values, one value for the first support structure and one value for the second support structure. The controller **2204** can use this covariation as part of decision logic to determine if a rollover is present. For example, the controller **2204** may use a threshold value and if the covariation is above the threshold value, a rollover is detected.

[0203] The covariations represent measures of one of the group consisting of amplitudes of pressure waves; rates of change of amplitudes of pressure waves; rates of motions of users; coherence measures; entropy of pressures; amplitude modulations of pressure waves; frequency modulations of pressure waves; phase differences of pressure waves; breathing rates; breathing amplitudes; heartbeat rates; and heartbeat amplitudes. Using these covariant, the process **2000** can track changes to directly measured features of the bed (e.g., pressure waves in an air bladder,) or user physiological signals (e.g., heartbeat amplitudes.) In the case of physiological signals, a significant change in the measured covariations (i.e. a change outside the scope of normal physiological variability) may be used as an indicator not of user physiological change, but of movement of the user from a location of high-quality measurement (i.e. their side of the bed) to a location of low-quality measurement (i.e. half of their side of the bed, half on the other side of the bed.)

[0204] If the first user has rolled over (**2218**), the controller **2204** transmits a storage signal to the computer memory **2208** (**2220**) and the computer memory **2208** stores the roll over information (**2220**). For example, when the roll over event is determined, the controller **2204** can transmit a message to the computer memory to store information about the roll over event. This message can include a timestamp of the roll over, a user identity of the user that rolled over, information about the roll over event calculations (e.g., the values used in calculating the rollover event). In some examples, the controller can transmit a storage signal that includes data about a user's length of roll over. For example, the controller **2204** may determine that a user has rolled over and then stayed in place for a certain amount of time until, for example the user wakes up or rolls over again. In such a case, the controller **2204** can transmit a storage message that includes the length of time the user has rolled and stayed in place, and the computer memory **2208** can store that information. In some cases, this can cause the recordation in computer memory an amount of time that the first user has rolled onto the second support portion.

[0205] In some cases, the controller **2204** can determine an extent of roll over (e.g., fully rolled over, partially rolled over). In some cases, the controller **2204** can determine a length of time a user has spent on the other side of the bed, sometimes called a cuddle time. In some cases, the control-

ler **2204** can determine if a roll over has negatively impacted the sleep quality of the other user before taking an action in response to roll over.

[0206] If the first user has rolled over (**2218**), the controller **2204** transmits a control signal to a controllable device **2206** to engage the controllable device **2206** (**2224**) and the controllable device **2206** receives the control signal to engage the controllable device **2206** (**2226**). For example, the controller **2204** can determine that, in response to a roll over event, one or more environmental modifications should be undertaken. This mapping of modifications can be generated by the user (e.g., a user may specify through a graphical user interface (GUI) and store information associated with their profile data), may be general across many users (e.g., a vendor may determine that many users would like a particular adjustment), or may be generated by a third party on an individual user basis (e.g., a machine learning system may determine that a particular adjustment after a roll over leads to better sleep), or may be generated in a different way.

[0207] In some cases, the adjustment may be multi-part. For example, an adjustment may call for a change to temperature and a change to bed pressure. In such an example, the controller **2204** can transmit two different (or similar) control signals to two different (or similar) controllable devices. In this example, the controller **2204** can send a temperature adjustment message to a thermostat that controls HVAC and a pressure adjustment message to a pump that controls pressure in the bed.

[0208] Responsive to receiving the control signal to engage the controllable device **2206**, the controllable device **2206** engages in order to alter the environment (**2228**). In one example, the controllable device is a pressure controller. In this example, engaging in order to alter the environment comprises changing the pressure of the second support portion. That is, when the first user rolls onto the second support portion, the controller can change the pressure of the support portion that the first user is now on. This may be useful in a number of situations. In one situation, the second user may not wish the first user to remain on the second support portion, and the controller can increase the pressure of the second support portion to encourage the first user to roll back off the second support portion. In another situation, the second user may wish to allow the first user to remain on the second support portion, e.g., because the second user enjoys cuddling with the first user while they sleep. In such a situation, the controller **2204** can send a pressure adjustment message to the pressure controller to reach a target pressure that is stored for use when the first and second users are cuddling on one of the support portions. This cuddle pressure may be set for the bed as a whole and applied to either the first support portion or the second support portion. In one situation, the second user may be absent from the bed (e.g., traveling) while the first user remains in the bed. The first user may roll over onto the second support portion that is otherwise set to the pressure preferred by the second user. However, as the second user is not in the bed, the controller **2204** may determine that the second support portion should be set to the preferred pressure of the first user that is actually in the second support portion at the time.

[0209] In one example, the controllable device is a temperature controller and engaging in order to alter the environment comprises changing the temperature of the second support portion. For example, the temperature controller can

engage to change the temperature in a portion of the bed (e.g., a foot-warming device) or to change the temperature in the entire bed (e.g., a heating or cooling element across the entire bed). The controller **2204** may send a control signal to, for example, halt a heating or engage a cooling to effectively lower the temperature of the bed environment to account for the increased warming each of the users will experience while cuddling, resulting in a more even temperature experience by both users. Alternatively, or additionally, the temperature controller can control a ceiling fan, HVAC, etc. In one example, the controllable device is an articulation controller and engaging in order to alter the environment comprises articulating the second support portion. For example, in order to encourage the first user to roll back onto the first support portion, the controller **2204** can send an articulation command to an articulation controller to lift a head area of the second support portion to encourage the first user to roll back to the lower second support area. In another example, to allow for a comfortable sleeping surface for the first user when partially on the first support portion and partially on the second support portion, the controller **2204** can lower any elevated areas in the bed so that the transition from the first support portion to the second support portion.

[0210] In one example, the control (**2228**) includes disabling one or more home automation devices. For example, some home automation devices should only function when each user is on their own side of a bed, or should be disabled when two users are on one side of the bed. In some cases, a bed's articulation controller may be configured such that the articulation is only comfortable and/or only safe when a user is alone on their side of the bed. In such a case, the control (**2228**) can include disabling the articulation controller of the bed of the two users.

[0211] In one example, the controllable device is a lighting controller and engaging in order to alter the environment comprises disabling the lighting controller when a rollover event is observed. For example, an under-bed lighting feature may be configured to activate when there is an indication that a user exits their side of the bed. In this way, when the left side user or the right side user exits the bed, the under-bed lighting may illuminate, for example to help the user navigate to the door in an otherwise dark room. However, when the user exits their side of the bed by rolling over onto the other side of the bed, the under-bed lighting need not be activated. It can be disabled. This can be advantageous, because even though the user has exited their side of the bed, they did not do so in order to navigate to the door—they did so to roll onto the other side of the bed. In such a case, engaging the lighting feature is not needed and is likely unexpected. Disabling the lighting feature in such a case can advantageously provide the user with a more expected and preferred functionality set.

[0212] While the previous example describes the controller **2204** identifying roll over events of the first user onto the second support surface, it will be understood that the controller can also simultaneously monitor for roll over events of the second user onto the first support surface.

[0213] In addition to or in the alternative, the system can take other actions when a rollover is identified. For example, logged data can be thrown out. In some cases, a user wishing to have greater privacy protection may not wish to have a record made of roll over events. In such a case, the user can

set a privacy setting indicating their desire, and the system can respect that choice by not logging some or any data when a roll over is detected.

What is claimed is:

1. A system comprising:
a mattress comprising:
a first support portion configured to receive and support a first user laying on the first portion; and
a second support portion configured to receive and support a second user laying on the second portion; wherein the first support portion and the second support portion are adjacent to each other such that the first user is capable of rolling over from the first support portion to the second support portion while sleeping on the first support portion;
a sensor configured to:
sense first pressure in the first support portion;
sense second pressure in the second support portion;
and
transmit, to a controller, data of the first pressure and the second pressure; and
a controller configured to:
receive the data of the first pressure and the second pressure; and
from the data of the first pressure and the second pressure, determine if the first user has rolled over from the first support portion to the second support portion.
2. The system of claim 1, wherein responsive to determining that the first user has rolled over from the first support portion to the second support portion, the controller is further configured to:
transmit a control signal to a controllable device to engage the controllable device.
3. The system of claim 2, the system further comprising the controllable device, the controllable device configured to:
receive the control signal to engage the controllable device;
responsive to receiving the control signal to engage the controllable device, engage in order to alter the environment.
4. The system of claim 3, wherein the controllable device is a pressure controller and wherein engaging in order to alter the environment comprises changing the pressure of the second support portion.
5. The system of claim 3, wherein the controllable device is a temperature controller and wherein engaging in order to alter the environment comprises changing the temperature of the second support portion.
6. The system of claim 3, wherein the controllable device is an articulation controller and wherein engaging in order to alter the environment comprises articulating the second support portion.
7. The system of claim 1, wherein the controller is further configured to:
record in computer memory an amount of time that the first user has rolled onto the second support portion.
8. The system of claim 1, wherein the controller is further configured to:
record a degree of roll over.
9. The system of claim 1, wherein the controller is further configured to:
determine if the roll over has negatively impacted the sleep quality of the second user.

10. The system of claim 1, wherein to determine if the first user has rolled over from the first support portion to the second support portion, the controller is configured to:

generate a first parameter, from the data, that represents a measure of at least one from the group consisting of:
the first user and the first support portion;

using the first parameter, determine a movement value for the first user;

if the determined movement value indicates movement for the first user, identify a rollover event using a covariation measure between the first support structure and the second support structure.

11. The system of claim 9, wherein the covariation measure between the first support structure and the second support structure represent measures of one of the group consisting of:

amplitudes of pressure waves;
rates of change of amplitudes of pressure waves;
rates of motions of users;
coherence measures;
entropy of pressures;
amplitude modulations of pressure waves;
frequency modulations of pressure waves;
phase differences of pressure waves;
breathing rates;
breathing amplitudes;
heartbeat rates;
heartbeat amplitudes.

12. The system of claim 1, wherein to determine if the first user has rolled over from the first support portion to the second support portion, the controller is configured to:

detecting a decrease in the data of first pressure while also
detecting an increase in the data of second pressure.

13. A system comprising:

a means for supporting a mattress

the mattress, the mattress comprising:

a first support portion configured to receive and support a first user laying on the first portion; and

a second support portion configured to receive and support a second user laying on the second portion;

wherein the first support portion and the second support portion are adjacent to each other such that the first user is capable of rolling over from the first support portion to the second support portion while sleeping on the first support portion;

a sensor configured to:

sense first pressure in the first support portion;

sense second pressure in the second support portion;
and

transmit, to a controller, data of the first pressure and the second pressure; and

a controller configured to:

receive the data of the first pressure and the second pressure; and

from the data of the first pressure and the second pressure, determine if the first user has rolled over from the first support portion to the second support portion.

14. The system of claim 13, wherein responsive to determining that the first user has rolled over from the first support portion to the second support portion, the controller is further configured to:

transmit a control signal to a controllable device to engage the controllable device.

15. The system of claim **14**, the system further comprising the controllable device, the controllable device configured to: receive the control signal to engage the controllable device;

responsive to receiving the control signal to engage the controllable device, engage in order to alter the environment.

16. The system of claim **15**, wherein the controllable device is a pressure controller and wherein engaging in order to alter the environment comprises changing the pressure of the second support portion.

17. A controller configured to:

communicate with a sensor that is connected to a mattress, the mattress comprising:

a first support portion configured to receive and support a first user laying on the first portion; and

a second support portion configured to receive and support a second user laying on the second portion; wherein the first support portion and the second support portion are adjacent to each other such that the first user is capable of rolling over from the first support portion to the second support portion while sleeping on the first support portion;

wherein the sensor is configured to:

sense first pressure in the first support portion;

sense second pressure in the second support portion; and

transmit, to a controller, data of the first pressure and the second pressure; and

wherein the controller is further configured to:

receive the data of the first pressure and the second pressure; and

from the data of the first pressure and the second pressure, determine if the first user has rolled over from the first support portion to the second support portion.

18. The controller of claim **17**, wherein to determine if the first user has rolled over from the first support portion to the second support portion, the controller is configured to:

generate a first parameter, from the data, that represents a measure of at least one from the group consisting of: the first user and the first support portion;

using the first parameter, determine a movement value for the first user;

if the determined movement value indicates movement for the first user, identify a rollover event using a covariation measure between the first support structure and the second support structure.

19. The controller of claim **18**, wherein the covariation measure between the first support structure and the second support structure represent measures of one of the group consisting of:

amplitudes of pressure waves;

rates of change of amplitudes of pressure waves;

rates of motions of users;

coherence measures;

entropy of pressures;

amplitude modulations of pressure waves;

frequency modulations of pressure waves;

phase differences of pressure waves;

breathing rates;

breathing amplitudes;

heartbeat rates;

heartbeat amplitudes.

20. The controller of claim **19**, wherein to determine if the first user has rolled over from the first support portion to the second support portion, the controller is configured to:

detecting a decrease in the data of first pressure while also detecting an increase in the data of second pressure.

* * * * *

专利名称(译)	床具有侧翻识别功能		
公开(公告)号	US20190201266A1	公开(公告)日	2019-07-04
申请号	US16/233238	申请日	2018-12-27
[标]发明人	SAYADI OMID HEWITT CARL YOUNG STEVEN JAY		
发明人	SAYADI, OMID HEWITT, CARL YOUNG, STEVEN JAY		
IPC分类号	A61G7/018 A61B5/00 A47C21/00 A61G7/015		
CPC分类号	A61G7/018 A61B5/4815 A47C21/003 A61B5/4809 A61B5/4812 A61G7/015 A61B5/4818 A61B5/7267 A61G7/05769 A47C27/083 A61B5/11 A61B5/6892 A47C31/008 A61B5/024 A61B5/0816 A61B5/1116 A61G7/05776 A61G2203/12 A61G2203/30 A61G2203/34 A61G2203/46		
优先权	62/611084 2017-12-28 US		
外部链接	Espacenet USPTO		

摘要(译)

床垫具有第一支撑部分和第二支撑部分，第一支撑部分构造成接收和支撑第一用户，第二支撑部分构造成接收和支撑第二用户。第一支撑部分和第二支撑部分彼此相邻，使得第一使用者能够在睡在第一支撑部分上时从第一支撑部分翻转到第二支撑部分。传感器配置成感测第一支撑部分中的第一压力并感测第二支撑部分中的第二压力。传感器还被配置为传输第一压力 and 第二压力的数据。控制器被配置为接收数据并且从第一压力和第二压力的数据接收，确定第一用户是否已经从第一支撑部分翻转到第二支撑部分。

