



US009267793B2

(12) **United States Patent**
Vock et al.

(10) **Patent No.:** **US 9,267,793 B2**
(45) **Date of Patent:** **Feb. 23, 2016**

(54) **MOVEMENT MONITORING DEVICE FOR ATTACHMENT TO EQUIPMENT**

A61B 5/6833 (2013.01); *A63B 24/0062* (2013.01); *A63B 71/0605* (2013.01); *G01B 7/004* (2013.01); *G01C 22/006* (2013.01);
(Continued)

(71) Applicant: **TVIPR, LLC**, Lafayette, CO (US)

(72) Inventors: **Curtis A. Vock**, Niwot, CO (US); **Burl W. Amsbury**, Denver, CO (US); **Paul Jonjak**, Lafayette, CO (US); **Adrian Larkin**, Essex (GB); **Perry Youngs**, Mead, CO (US)

(58) **Field of Classification Search**
CPC . A43B 3/005; A61B 2503/04; A61B 2503/10
USPC 702/150, 182-185
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 58 days.

3,612,265 A 10/1971 Dickerson
3,807,388 A 4/1974 Orr et al.
(Continued)

(21) Appl. No.: **14/188,475**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Feb. 24, 2014**

EP 0917893 A1 5/1999
JP 2000122044 11/2001

(65) **Prior Publication Data**

US 2014/0172358 A1 Jun. 19, 2014

(Continued)

OTHER PUBLICATIONS

Related U.S. Application Data

(60) Continuation of application No. 13/866,494, filed on Apr. 19, 2013, now Pat. No. 8,660,814, which is a continuation of application No. 13/356,009, filed on Jan. 23, 2012, now Pat. No. 8,428,904, which is a
(Continued)

Bernard Wysocki, Jr., Staff Reporter, "Do Devices Measuring Body Signs Appeal to the Sick or Healthy?", Pittsburgh, US (undated).
(Continued)

Primary Examiner — Edward Raymond

(74) *Attorney, Agent, or Firm* — Lathrop & Gage LLP


(51) **Int. Cl.**
G06F 19/00 (2011.01)
G01B 21/00 (2006.01)
(Continued)

(57) **ABSTRACT**

A movement monitoring device attaches to equipment and includes a housing and a transmitter. The housing includes an integrated circuit with (a) a detector sensitive to physical movement of the equipment when the housing is attached to the equipment and (b) a processor for processing data of the detector to determine an event experienced by the equipment. The transmitter communicatively couples with the integrated circuit for communicating the event to a remote receiver.

(52) **U.S. Cl.**
CPC . *G01B 21/00* (2013.01); *A43B 3/00* (2013.01); *A43B 3/0005* (2013.01); *A43B 5/06* (2013.01); *A61B 5/0002* (2013.01); *A61B 5/1112* (2013.01); *A61B 5/1117* (2013.01); *A61B 5/1126* (2013.01); *A61B 5/6807* (2013.01);

18 Claims, 45 Drawing Sheets



Related U.S. Application Data

continuation of application No. 12/968,170, filed on Dec. 14, 2010, now Pat. No. 8,126,675, which is a continuation of application No. 11/866,269, filed on Oct. 2, 2007, now Pat. No. 7,856,339, which is a continuation of application No. 11/647,035, filed on Dec. 28, 2006, now Pat. No. 7,620,520, which is a division of application No. 11/358,508, filed on Feb. 21, 2006, now Pat. No. 7,171,331, which is a continuation of application No. 10/601,208, filed on Jun. 20, 2003, now Pat. No. 7,174,277, which is a continuation of application No. 10/297,270, filed as application No. PCT/US01/51620 on Dec. 17, 2001, now Pat. No. 8,280,682.

- (60) Provisional application No. 60/256,069, filed on Dec. 15, 2000, provisional application No. 60/257,386, filed on Dec. 22, 2000, provisional application No. 60/259,271, filed on Dec. 29, 2000, provisional application No. 60/261,359, filed on Jan. 13, 2001, provisional application No. 60/285,032, filed on Apr. 19, 2001, provisional application No. 60/323,601, filed on Sep. 20, 2001.

(51) Int. Cl.

A43B 3/00 (2006.01)
A43B 5/06 (2006.01)
A61B 5/00 (2006.01)
A61B 5/11 (2006.01)
A63B 24/00 (2006.01)
A63B 71/06 (2006.01)
G01C 22/00 (2006.01)
G01G 19/44 (2006.01)
G01G 23/00 (2006.01)
G01G 23/37 (2006.01)
G01P 1/12 (2006.01)
G01P 15/08 (2006.01)
G06Q 10/08 (2012.01)
G01B 7/004 (2006.01)
G01P 3/00 (2006.01)
A61B 5/113 (2006.01)
A63B 69/00 (2006.01)

(52) U.S. Cl.

CPC *G01G19/44* (2013.01); *G01G 23/00* (2013.01); *G01G 23/3728* (2013.01); *G01P 1/127* (2013.01); *G01P 3/00* (2013.01); *G01P 15/0891* (2013.01); *G06F 19/00* (2013.01); *G06Q 10/08* (2013.01); *G06Q 10/083* (2013.01); *G06Q 10/0833* (2013.01); *A61B 5/113* (2013.01); *A61B 2503/10* (2013.01); *A61B 2560/0412* (2013.01); *A61B 2562/0219* (2013.01); *A61B 2562/08* (2013.01); *A61B 2562/242* (2013.01); *A63B 69/00* (2013.01); *A63B 69/0028* (2013.01); *A63B 2208/12* (2013.01); *A63B 2220/20* (2013.01); *A63B 2220/30* (2013.01); *A63B 2225/50* (2013.01); *A63B 2230/01* (2013.01); *A63B 2244/10* (2013.01)

(56) References Cited

U.S. PATENT DOCUMENTS

3,958,459 A 5/1976 Shimomura
 4,101,873 A 7/1978 Anderson et al.
 4,114,450 A 9/1978 Shulman et al.

4,195,642 A 4/1980 Price et al.
 4,210,024 A 7/1980 Ishiwatari et al.
 4,248,244 A 2/1981 Charnitski et al.
 4,317,126 A 2/1982 Gragg, Jr.
 4,371,188 A 2/1983 Hull
 4,371,945 A 2/1983 Karr et al.
 4,375,674 A 3/1983 Thornton
 4,423,630 A 1/1984 Morrison
 4,434,801 A 3/1984 Jiminez et al.
 4,516,865 A 5/1985 Hideo
 4,578,769 A 3/1986 Frederick
 4,625,733 A 12/1986 Saynajakangas
 4,694,694 A 9/1987 Vlakancic et al.
 4,699,379 A 10/1987 Chateau et al.
 4,720,093 A 1/1988 Del Mar
 4,722,222 A 2/1988 Purdy et al.
 4,736,312 A 4/1988 Dassler et al.
 4,745,564 A 5/1988 Tennes et al.
 4,757,453 A 7/1988 Nasiff
 4,757,714 A 7/1988 Purdy et al.
 4,763,284 A 8/1988 Carlin
 4,771,394 A 9/1988 Cavanagh
 4,774,679 A 9/1988 Carlin
 4,775,948 A 10/1988 Dial et al.
 4,812,541 A 3/1989 Mallya et al.
 4,813,272 A 3/1989 Miyazaki et al.
 4,821,218 A 4/1989 Potsch
 4,824,107 A 4/1989 French
 4,829,812 A 5/1989 Parks et al.
 4,862,394 A 8/1989 Thompson et al.
 4,862,395 A 8/1989 Fey et al.
 4,876,500 A 10/1989 Wu
 4,883,271 A 11/1989 French
 4,911,016 A 3/1990 Miyazaki et al.
 4,955,980 A 9/1990 Masuo
 5,033,013 A 7/1991 Kato et al.
 5,045,035 A 9/1991 Ganoung
 5,088,836 A 2/1992 Yamada et al.
 5,178,016 A 1/1993 Dauenhauer et al.
 5,243,993 A 9/1993 Alexander et al.
 5,295,085 A 3/1994 Hoffacker
 5,324,038 A 6/1994 Sasser
 5,339,699 A 8/1994 Carignan
 5,343,445 A 8/1994 Cherdak
 5,426,595 A 6/1995 Picard
 5,442,221 A 8/1995 Mosser et al.
 5,446,775 A 8/1995 Wright et al.
 5,452,269 A 9/1995 Cherdak
 5,471,405 A 11/1995 Marsh
 5,475,725 A 12/1995 Nakamura
 5,485,402 A 1/1996 Smith et al.
 5,486,815 A 1/1996 Wagner
 5,513,854 A 5/1996 Daver
 5,524,637 A 6/1996 Erickson
 5,526,326 A 6/1996 Fekete et al.
 5,528,228 A 6/1996 Wilk
 5,541,604 A 7/1996 Meier
 5,546,974 A 8/1996 Bireley
 5,564,698 A 10/1996 Honey et al.
 5,592,401 A 1/1997 Kramer
 5,608,374 A 3/1997 Ikejiri
 5,615,132 A 3/1997 Horton et al.
 5,621,316 A 4/1997 Dames et al.
 5,627,548 A 5/1997 Woo et al.
 5,633,070 A 5/1997 Murayama et al.
 5,636,146 A 6/1997 Flentov et al.
 5,671,525 A 9/1997 Fidalgo
 5,690,119 A 11/1997 Rytky et al.
 5,690,773 A 11/1997 Fidalgo et al.
 5,694,340 A 12/1997 Kim
 5,701,257 A 12/1997 Miura et al.
 5,721,539 A 2/1998 Goetzl
 5,723,786 A 3/1998 Klapman
 5,724,265 A 3/1998 Hutchings
 5,738,104 A 4/1998 Lo et al.
 5,745,037 A 4/1998 Guthrie et al.
 5,761,096 A 6/1998 Zakutin
 5,767,503 A 6/1998 Gloton
 5,779,576 A 7/1998 Smith et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,807,284 A 9/1998 Foxlin
 5,812,056 A 9/1998 Law
 5,862,803 A 1/1999 Besson et al.
 RE36,200 E 4/1999 Berrian et al.
 5,899,963 A 5/1999 Hutchings
 5,901,303 A 5/1999 Chew
 5,917,434 A 6/1999 Murphy
 5,925,001 A 7/1999 Hoyt et al.
 5,929,335 A 7/1999 Carter
 5,930,741 A 7/1999 Kramer
 5,936,523 A 8/1999 West
 5,946,643 A 8/1999 Zakutin
 5,947,917 A 9/1999 Cart  t et al.
 5,955,667 A 9/1999 Fyfe
 5,959,568 A 9/1999 Woolley
 5,960,380 A 9/1999 Flentov et al.
 5,963,523 A 10/1999 Kayama et al.
 5,963,891 A 10/1999 Walker et al.
 5,977,877 A 11/1999 McCulloch et al.
 5,983,724 A 11/1999 Yoshida
 6,009,629 A 1/2000 Gnepf et al.
 6,011,491 A 1/2000 Goetzl
 6,018,677 A 1/2000 Vidrine et al.
 6,018,705 A 1/2000 Gaudet et al.
 6,043,747 A 3/2000 Altenhofen
 6,052,654 A 4/2000 Gaudet et al.
 6,057,756 A 5/2000 Engellenner
 6,059,576 A 5/2000 Brann
 6,073,086 A 6/2000 Marinelli
 6,074,089 A 6/2000 Hollander et al.
 6,075,443 A 6/2000 Schepps et al.
 6,078,056 A 6/2000 Teder
 6,089,098 A 7/2000 Tylisz et al.
 6,091,342 A 7/2000 Janesch et al.
 6,122,340 A 9/2000 Darley et al.
 6,122,959 A 9/2000 Hoshal et al.
 6,125,686 A 10/2000 Haan et al.
 6,127,931 A 10/2000 Mohr
 6,148,271 A 11/2000 Marinelli
 6,151,563 A 11/2000 Marinelli
 6,151,647 A 11/2000 Sarat
 6,157,898 A 12/2000 Marinelli
 6,163,021 A 12/2000 Mickelson
 6,167,356 A 12/2000 Squadron et al.
 6,218,941 B1 4/2001 Cromer et al.
 6,226,622 B1 5/2001 Dabbieri
 6,238,338 B1 5/2001 DeLuca et al.
 6,305,221 B1 10/2001 Hutchings
 6,360,597 B1 3/2002 Hubbard, Jr.
 6,385,473 B1 5/2002 Haines et al.
 6,441,747 B1 8/2002 Khair et al.
 6,469,664 B1 10/2002 Michaelson et al.
 6,501,390 B1 12/2002 Chainer et al.
 6,512,478 B1 1/2003 Chien
 6,516,284 B2 2/2003 Flentov et al.
 6,527,711 B1 3/2003 Stivorc
 6,531,982 B1 3/2003 White et al.
 6,539,336 B1 3/2003 Vock et al.
 6,563,417 B1 5/2003 Shaw
 6,595,929 B2 7/2003 Stivorc
 6,600,418 B2 7/2003 Francis et al.
 6,605,038 B1 8/2003 Teller
 6,611,782 B1 8/2003 Wooster et al.
 6,617,962 B1 9/2003 Horwitz et al.
 6,619,835 B2 9/2003 Kita
 6,643,608 B1 11/2003 Hershey et al.
 6,714,121 B1 3/2004 Moore
 6,735,630 B1 5/2004 Gelvin et al.
 6,813,586 B1 11/2004 Vock et al.
 6,825,777 B2 11/2004 Vock et al.
 6,856,934 B2 2/2005 Vock et al.
 6,898,492 B2 5/2005 de Leon et al.
 6,900,732 B2 5/2005 Richards
 6,904,359 B2 6/2005 Jones
 6,959,259 B2 10/2005 Vock et al.

7,009,517 B2 3/2006 Wood
 7,035,856 B1 4/2006 Morimoto
 7,174,277 B2 2/2007 Vock et al.
 7,200,517 B2 4/2007 Darley et al.
 7,219,067 B1 5/2007 McMullen et al.
 7,307,245 B2 12/2007 Faries et al.
 2002/0057340 A1 5/2002 Fernandez et al.
 2002/0070862 A1 6/2002 Francis et al.
 2003/0014210 A1 1/2003 Vock et al.
 2003/0093248 A1 5/2003 Vock et al.
 2008/0309551 A1 12/2008 Gelbman

FOREIGN PATENT DOCUMENTS

WO WO 95/14430 A1 6/1995
 WO WO 2009/806466 A2 2/1998
 WO WO 00/51259 A1 8/2000
 WO WO 01/01706 A1 1/2001

OTHER PUBLICATIONS

Civil Action 05-CV-02323; Complaint; Nov. 16, 2005.
 Civil Action 06-CV-01100-WDM-PAC, Defendants Polar Electro Inc.'s and Polar Electro Oy's Answer and Affirmative Defenses; Polar Electro Inc.'s Counterclaim and Demand for Jury Trial, Jun. 29, 2006.
 Civil Action 06-CV-01100-WDM-PAC; Complaint; Jun. 8, 2006.
 Civil Action 06-CV-01447 MSK-BNB; Answer, Affirmative Defenses, Counterclaims and Demand for Jury Trial; Sep. 26, 2006.
 Civil Action 06-CV-01447 MSK-BNB; First Amended Complaint; Aug. 16, 2006.
 Civil Action 06-CV-01447-MSK-BNB; Complaint; Jul. 26, 2006.
 Civil Action 06-CV-01447-MSK-BNB; Disclosure Statement; Sep. 26, 2006.
 Civil Action 06-CV-01447-MSK-BNB; Plaintiff's Supplemental Answers and Objections to Defendant Timex Corporations' Interrogatories Nos. 1,2,5,7-11, 13 and 15, Feb. 12, 2007.
 Civil Action 06-CV-02122-REB-MJW; Apple Computer, Inc.'s Answer to Complaint and Counterclaims, Mar. 19, 2007.
 Civil Action 06-CV-02122-REB-MJW; Complaint; Oct. 24, 2006.
 Civil Action 07-CV-00078-MSK-BNB, Answer; Feb. 9, 2007.
 Civil Action 07-CV-00078-MSK-BNB; Complaint; Jan. 12, 2007.
 Civil Action 07-CV-00238-REB, Complaint, Feb. 2007.
 Civil Action 07-CV-00238-REB, Nike, Inc.'s Answer and Affirmative Defenses to First Complaint.
 Civil Action No. 07-CV-00238; Apple Inc.'s Answer to Complaint, Counterclaims and Jury Demand; Mar. 19, 2007.
 Dave Sellers, Gear to Go, Mitch Mandel Photography, Mar. 2001, pp. 61-62.
 Ellen Licking, Special Report: E-Health, "This is the Future of Medicine", Business Week E.Biz, Dec. 11, 2000, pp. 77 and 78 US.
 George Cole, "The little label with an explosion of applications", Technology, Financial Times, 2001 US.
 GPS Locator for Children, Klaas Kids Foundation (undated).
 Mark of Fitness Flyer, "High Quality, Self-Taking Blood Pressure Monitors," two pages, Shrewsbury, NJ, US (undated).
 Mark of Fitness Flyer, Blood Pressure Monitors, Shrewsbury, NJ US (undated).
 Melanie Martella, Product News, "Temperature Monitoring System", Nov. 2000, p. 77.
 No author listed, "Ever Forget to Bring Your Cell Phone or Keys?", Catalog Page, Pi Manufacturing Corp, 20732 Currier Rd., Walnut, CA 91789, Home Office Accessory, Catalog Nos. TA-100N; TA-100M; TA-100F, US (undated).
 No author listed, "Your Next . . .", Newsweek, Jun. 25, 2001, p. 52 US.
 No author listed, The GPS Connection, Popular Mechanics, Feb. 2001, p. 65.
 No author listed, WarmMark Time Temperature Indicators, www.coldice.com/warmmark.sub.--temperature.sub.--indicators.html, Cold Ice., Inc. accessed on the Internet Nov. 20, 2000 3 pages.
 Paradiso et al., Design and Implementation of Expressive Footwear, May 12, 2000, IBM Systems Journal, vol. 39, Nos. 3&4, pp. 511-529.

(56)

References Cited

OTHER PUBLICATIONS

- Paradiso et al., Instrumented Footwear for Interactive Dance, Sep. 24-26, 1998, XII Colloquium on Musical Informatics, Italy, version 1.1.
- Paradiso, Joseph, et al. "Instrumented Footwear for Interactive Dance" Version 1.1, Presented at the XII Colloquium on Musical Informatics, Gorizia, Italy, Sep. 24-26, 1998, pp. 1-4.
- PCT/US01/51620 International Search Report mailed Sep. 25, 2002.
- Ron Desmarais and Jim Breuer, Temperature, *www.sensorsmag.com*, Jan. 2001, pp. 30-36.
- Sagawa et al., Classification of Human Moving Patterns Using Air Pressure and Acceleration, 1998 IEEE, pp. 1214-1219.
- Sagawa et al., Non-Restricted Measurement of Walking Distance, Oct. 8-11, 2000, IEEE International Conference on Systems, Man, and Cybernetics vol. 3, pp. 1847-1852.
- Shannon P. Jackson and Harold Kirkham, "Weighing Scales Based on Low-Power Strain-Gauge Circuits", NASA Tech Briefs, Jun. 2001, p. 49 US.
- Sharp, K.R.; A Sense of the Real World, *www.idsystems.com/reader/2000.sub.-09/sens0900.htm*, Sep. 2000, 4 pages, Technology Edge, id Systems, 174 Concord St., Peterborough, NH 03458.
- Skaloud et al., DGPS—Calibrated Accelerometric System for Dynamic Sports Events, Sep. 24-26, 1998, XII Colloquium on Musical Informatics, Italy, version 1.1.
- Skaloud et al., DGPS—Calibrated Accelerometric System for Dynamic Sports Events, Sep. 19-22, 2000, ION GPS 2000.
- Steven Smith and Norman Coker, "Flexible and Survivable Non-Volatile Memory Data Recorder", AFRL Technology Horizons, Dec. 2000, p. 26.
- U.S. Appl. No. 10/297,270 Notice of Acceptance, May 13, 2003.
- U.S. Appl. No. 10/297,270 Office Action mailed Dec. 13, 2004.
- U.S. Appl. No. 10/297,270 Office Action mailed Feb. 9, 2006.
- U.S. Appl. No. 10/297,270 Office Action mailed Jan. 11, 2007.
- U.S. Appl. No. 10/297,270 Office Action mailed Jul. 13, 2005.
- U.S. Appl. No. 10/297,270 Office Action mailed Jul. 26, 2007.
- U.S. Appl. No. 10/297,270 Office Action mailed Jul. 29, 2004.
- U.S. Appl. No. 10/297,270 Office Action mailed Sep. 25, 2006.
- U.S. Appl. No. 10/297,270 Preliminary Amendment filed Dec. 4, 2002.
- U.S. Appl. No. 10/297,270 Response to Office Action mailed Dec. 13, 2004; filed Apr. 13, 2005.
- U.S. Appl. No. 10/297,270 Response to Office Action mailed Feb. 9, 2006; filed Jul. 10, 2006.
- U.S. Appl. No. 10/297,270 Response to Office Action mailed Jan. 11, 2007; filed May 10, 2007.
- U.S. Appl. No. 10/297,270 Response to Office Action mailed Jul. 13, 2005; filed Aug. 19, 2005.
- U.S. Appl. No. 10/297,270 Response to Office Action mailed Jul. 26, 2007; filed Nov. 21, 2007.
- U.S. Appl. No. 10/297,270 Response to Office Action mailed Jul. 29, 2004; filed Oct. 29, 2004.
- U.S. Appl. No. 10/297,270 Response to Office Action mailed Sep. 25, 2006; filed Oct. 16, 2006.
- U.S. Appl. No. 10/297,270, Office Action mailed Apr. 1, 2010; 16 pages.
- U.S. Appl. No. 10/297,270, Office Action mailed Apr. 29, 2009; 12 pages.
- U.S. Appl. No. 10/297,270, Office Action mailed Aug. 30, 2010; 17 pages.
- U.S. Appl. No. 10/297,270, Office Action mailed Feb. 18, 2011, 27 pages.
- U.S. Appl. No. 10/297,270, Office Action mailed Jul. 28, 2008; 18 pages.
- U.S. Appl. No. 10/297,270, Office Action mailed Oct. 1, 2009; 12 pages.
- U.S. Appl. No. 10/297,270, Response to Office Action Dec. 21, 2009; 18 pages.
- U.S. Appl. No. 10/297,270, Response to Office Action filed Dec. 22, 2008; 23 pages.
- U.S. Appl. No. 10/297,270, Response to Office Action Jun. 21, 2010; 13 pages.
- U.S. Appl. No. 10/297,270, Response to Office Action Jun. 8, 2009; 16 pages.
- U.S. Appl. No. 10/297,270, Response to Office Action Nov. 30, 2010; 13 pages.
- U.S. Appl. No. 10/297,270; Appeal Brief and Notice of Appeal filed Apr. 30, 2008; 50 pages.
- U.S. Appl. No. 10/297,270; Office Action mailed Feb. 5, 2008; 20 pages.
- U.S. Appl. No. 10/601,208, Notice of Allowance, Dec. 8, 2006.
- U.S. Appl. No. 10/601,208, Office Action, mailed Aug. 26, 2004.
- U.S. Appl. No. 10/601,208, Office Action, mailed Feb. 15, 2006.
- U.S. Appl. No. 10/601,208, Office Action, mailed Jun. 15, 2004.
- U.S. Appl. No. 10/601,208, Office Action, mailed May 11, 2005.
- U.S. Appl. No. 10/601,208, Office Action, mailed Sep. 26, 2006.
- U.S. Appl. No. 10/601,208, Preliminary Amendment mailed, Jun. 20, 2003.
- U.S. Appl. No. 10/601,208, Response to Office Action dated Jun. 15, 2004.
- U.S. Appl. No. 10/601,208, Response to Office Action of Aug. 26, 2004.
- U.S. Appl. No. 10/601,208, Response to Office Action, mailed Feb. 15, 2006.
- U.S. Appl. No. 10/601,208, Response to Office Action, mailed May 11, 2005.
- U.S. Appl. No. 10/601,208, Response to Office Action, mailed Sep. 26, 2006.
- U.S. Appl. No. 10/601,208, Second Response to Office Action of Aug. 26, 2004.
- U.S. Appl. No. 11/647,035, Notice of Allowance mailed Jul. 9, 2009, 4 pages.
- U.S. Appl. No. 11/647,035, Office Action mailed Apr. 9, 2009, 5 pages.
- U.S. Appl. No. 11/647,035, Office Action mailed Jul. 9, 2009, 4 pages.
- U.S. Appl. No. 11/647,035, Response to Office Action Jun. 5, 2009; 9 pages.
- U.S. Appl. No. 11/864,748, Notice of Allowance mailed Aug. 13, 2009, 10 pages.
- U.S. Appl. No. 12/968,170, Notice of Allowance mailed Nov. 23, 2011, 8 pages.
- U.S. Appl. No. 10/197,270, Office Action dated Sep. 1, 2011; 30 pages.
- U.S. Appl. No. 10/197,270, Office Action mailed Feb. 16, 2012, 15 pages.
- U.S. Appl. No. 10/197,270, Response to Office Action filed Mar. 12, 2012, 9 pages.
- U.S. Appl. No. 10/197,270, Response to Office Action filed Dec. 1, 2011; 23 pages.
- U.S. Appl. No. 13/356,009, Notice of Allowance dated Dec. 24, 2012, 5 pages.
- U.S. Appl. No. 13/356,009, Office Action dated Sep. 4, 2012, 8 pages.
- U.S. Appl. No. 13/356,009, Response to Office Action filed Dec. 4, 2012, 8 pages.
- U.S. Appl. No. 10/297,270, Notice of Allowance dated Apr. 19, 2012, 10 pages.
- Unattributed, 3M MonitorMark Indicator Data Sheet [online], [retrieved on Aug. 9, 2004], retrieved from the Internet: URL: <http://www.3m.com/us/healthcare/medicalspecialties/monitor/products.html>; 4 pages.
- Unattributed, Wireless Temperature Monitor [online], Nov. 20, 2000, [retrieved on Aug. 9, 2004], retrieved from the Internet: URL: <http://www.echo-on.net/mob>.
- Webster's II New Riverside Dictionary 1988, The Riverside Publishing Company, p. 1138.
- Yael Li-Ron, Tomorrow's Cures, Health & Fitness Special Section Online, Newsweek, Dec. 10, 2001, pp. 3-10.
- U.S. Appl. No. 13/866,494 Notice of Allowance dated Nov. 5, 2013, 11 pages.




FIG. 1









FIG. 1A






FIG. 2E




FIG. 3


















FIG. 3A












FIG. 8




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9




FIG. 10





FIG. 10A






FIG. 10D




FIG. 10E






FIG. 10F






FIG. 11





FIG. 12






FIG. 14




FIG. 14A




FIG. 15







FIG. 16






FIG. 20




FIG. 21







FIG. 22






FIG. 26




FIG. 27















FIG. 28












FIG. 40







FIG. 41






FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50






FIG. 51






FIG. 54




FIG. 55




FIG. 56









FIG. 57








FIG. 63




FIG. 64




FIG. 65




FIG. 66




FIG. 67




FIG. 68








FIG. 69







MOVEMENT MONITORING DEVICE FOR ATTACHMENT TO EQUIPMENT

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 13/866,494 filed Apr. 19, 2013 which is a continuation of U.S. application Ser. No. 13/356,009 (now U.S. Pat. No. 8,428,904), filed Jan. 23, 2012, which is a continuation of U.S. application Ser. No. 12/968,170 (now U.S. Pat. No. 8,126,675), filed Dec. 14, 2010, which is a continuation of U.S. application Ser. No. 11/866,269, filed Oct. 2, 2007 (now U.S. Pat. No. 7,856,339), which is a continuation of U.S. application Ser. No. 11/647,035, filed Dec. 28, 2006 (now U.S. Pat. No. 7,620,520) which is a divisional of U.S. application Ser. No. 11/358,508 filed Feb. 21, 2006 (now U.S. Pat. No. 7,171,331), which is a continuation of U.S. application Ser. No. 10/601,208 filed Jun. 20, 2003 (now U.S. Pat. No. 7,174,277), and a continuation of U.S. application Ser. No. 10/297,270 filed Dec. 4, 2002 (now U.S. Pat. No. 8,280,682), which claims priority to PCT Application No. PCT/US01/51620, filed Dec. 17, 2001 and to the following six U.S. Provisional Patent Applications: U.S. Provisional Application No. 60/256,069, filed Dec. 15, 2000; U.S. Provisional Application No. 60/257,386, filed Dec. 22, 2000; U.S. Provisional Application No. 60/259,271, filed Dec. 29, 2000; U.S. Provisional Application No. 60/261,359, filed Jan. 13, 2001; U.S. Provisional Application No. 60/285,032, filed Apr. 19, 2001, and U.S. Provisional Application No. 60/323,601, filed Sep. 20, 2001. The foregoing applications are expressly incorporated herein by reference.

FIELD OF THE INVENTION

The invention relates to sensing systems monitoring applications in sports, shipping, training, medicine, fitness, wellness and industrial production. The invention specifically relates to sensing and reporting events associated with movement, environmental factors such as temperature, health functions, fitness effects, and changing conditions.

BACKGROUND

The movement of objects and persons occurs continuously but is hardly quantified. Rather, typically only the result of the movement is known (i.e., object X moved from point A to point B; or, person Y ran to the store). Advances in technology have provided some quantification of movement. For example, GPS products now assist in determining the location of golf carts, vehicles and persons.

However, the detail of movement, minute to minute, second to second, is still not generally determinable in the prior art. For example, the movement of tangible objects typically involves (a) the shipment or carrying of goods and (b) electro-mechanical or motorized apparatus (e.g., planes, trains, automobiles, robots). The exact movements of such objects, and the conditions that they are subjected to, from point to point, are only qualitatively known. By way of example, a package is moved from location to location through delivery services like FEDERAL EXPRESS or UPS; however what occurred during transportation, and what transpired to the package, is anyone's guess. Occasionally, an object within the package is broken, indicating that the package experienced excessive abuse; but whose fault it is, or how or when it happened, are not known. What environments the package experienced is also not readily known.

The movement of persons, on the other hand, typically involves human-powered transportation, e.g., facilitated by biking, a wheelchair, or a motorized vehicle, e.g., a car. Body movement involved in transportation is subjected to many forces, some of which are dangerous. But the prior art does not provide for this knowledge; there is no effective way, currently, to efficiently quantify human movement. In sports, physical fitness, and training, precise information about movement would assist in many ways. By way of example, how effective a hand strike is in karate or boxing is, today, only qualitatively known. Quantitative feedback would be beneficial.

It is, accordingly, one feature of the invention to provide systems and methods addressing the aforementioned difficulties. A further feature of the invention is to provide methods and devices to quantify movement in a number of applications. Another feature of the invention is to monitor and report meaningful environment information such as temperature and humidity. These and other features will be apparent in the description that follows.

SUMMARY OF THE INVENTION

Movement Monitoring Devices

In one aspect, the invention provides a movement monitor device ("MMD") including an adhesive strip, a processor, a detector, and a communications port. In another aspect, two or more of the processor, port and detector are combined in a single application specific integrated circuit ("ASIC"). In one aspect the detector is an accelerometer, and preferably an accelerometer embedded into silicon within the ASIC. In other aspects, the detector is one of a strain gauge, force-sensing resistor, and piezoelectric strip. In still another aspect, the MMD includes a battery. In the preferred aspect of the invention, the MMD and battery are packaged in a protective wrapper. Preferably, the battery is packaged with the MMD in such a way that it does not "power" the MMD until the wrapper is removed. Preferably, the MMD includes a real time clock so that the MMD tags "events" (as hereinafter defined) with time and/or date information.

In yet another aspect, the MMD with adhesive strip collectively take a form similar to an adhesive bandage. More particularly, the adhesive strip of the invention is preferably like or similar to the adhesive of the adhesive bandage; and the processor (or protective wrapper) is embedded with the strip much the way the cotton is with the adhesive bandage. Preferably, a soft material (e.g., cotton or cloth) is included to surround the processor so as to (a) soften contact of rigid MMD components with a person and/or (b) protect the processor (and/or other components of the MMD). In still another aspect, the battery is also coupled with the soft material. In still another aspect, the processor and other elements of the MMD are combined into a single system-on-chip integrated circuit. A protective cover may surround the chip to protect the MMD from breakage.

In one aspect, one MMD of the invention takes a form similar to a smart label, with an adhesive substantially disposed with the label, e.g., on one side of the label. The adhesive strip of this MMD includes all or part of the back of the label with adhesive or glue permitting attachment of the label to other objects (or to a person).

In still another aspect, the MMD of the invention takes the form of a rigid monolithic that attaches to objects through one of known techniques. In this aspect, the device has a processor, communications port, and detector. A battery is typically included with the MMD. The MMD is attached to objects or persons by one of several techniques, including by glue or

mechanical attachment (e.g., a pin or clip). An MMD of this aspect can for example exist in the form of a credit card, wherein the communications port is either a contact transponder or a contactless transponder. The MMD of one aspect includes a magnetic element that facilitates easily attaching the MMD to metal objects.

In operation, the MMD of the invention is typically interrogated by an interrogation device ("ID"). The MMD is responsive to the ID to communicate information within the MMD and, preferably, over secure communications protocols. By way of example, one MMD of the invention releases internal data only to an ID with the correct passwords and/or data protocols. The ID can take many forms, including a cell phone or other electronic device (e.g., an MP3 player, pager, watch, or PDA) providing communications with the MMD transmitter

However, in another aspect, the MMD communicates externally to a remote receiver ("RR"). The RR listens for data from the MMD and collects that data for subsequent relay or use. In one aspect, the MMD's communications port is a one-way transmitter. Preferably, the MMD communicates data from the MMD to the RR either (a) upon the occurrence of an "event" or (b) in repeated time intervals, e.g., once every ten minutes. Alternatively, the MMD's communication port is a transceiver that handshakes with the RR to communicate data from the MMD to the RR. Accordingly, the MMD responds to data requests from the RR, in this aspect. In still another aspect, the RR radiates the MMD with transponder frequencies; and the MMD "reflects" movement data to the RR.

Accordingly, the communications port of one aspect is a transponder responsive to one or more frequencies to relay data back to an ID. By way of example, these frequencies can be one of 125 kHz and 13.56 MHz, the frequencies common with "contactless" RFID tags known in the art. In other aspects, communications frequencies are used with emission power and frequencies that fall within the permissible "unlicensed" emission spectrum of part 15 of FCC regulations, Title 47 of the Code of Federal Regulations. In particular, one desirable feature of the invention is to emit low power, to conserve battery power and to facilitate use of the MMD in various environments; and therefore an ID is placed close to the MMD to read the data. In other words, in one aspect, wireless communications from the MMD to the ID occurs over a short distance of a fraction of an inch to no more than a few feet. By way of example, as described herein, one ID of the invention takes the form of a cell phone, which communicates with the MMD via one or more secure communications techniques. Data acquired from the MMD is then communicated through cellular networks, if desired, to relay MMD data to end-users.

Or, in another aspect, the ID has a larger antenna to pick up weak transmission signals from an MMD at further distances separation.

In another aspect, the communications port is an infrared communications port. Such a port, in one aspect, communicates with the cell phone in secure communication protocols. In other aspects, an ID communicates with the infrared port to obtain the data within the MMD.

In yet another aspect, the communications port includes a transceiver. The MMD listens for interrogating signals from the RR and, in turn, relays movement "event" data from the MMD to the RR. Alternatively, the MMD relays movement "event" data at set time intervals or when the MMD accumulates data close to an internal storage limit. In one aspect, thereby, the MMD includes internal memory; and the MMD stores one or more "event" data, preferably with time-tag

information, in the memory. When the memory is nearly full, the MMD transmits the stored data wirelessly to a RR. Alternatively, stored data is transmitted to an IR when interrogated. In a third alternative, the MMD transmits stored data at set intervals, e.g., once per ½ hour or once per hour, to relay stored data to a RR. Other transmission protocols can be used without departing from the scope of the invention.

In still another aspect, data from the MMD is relayed to an ID through "contact" communication between the ID and the communications port. In one aspect, the MMD includes a small conductive plate (e.g., a gold plate) that contacts with the ID to facilitate data transfer. Smart cards from the manufacturer GEMPLUS may be used in such aspects of the invention.

In one aspect, the MMD includes a printed circuit board ("PCB"). A battery—e.g., a 2032 or 1025 Lithium coin cell—is also included, in another aspect of the invention. To make the device small, the PCB preferably has multilayers—and two of the internal layers have a substantial area of conducting material forming two terminals for the battery. Specifically, the PCB is pried apart at one edge, between the terminals, and the battery is inserted within the PCB making contact and providing voltage to the device. This advantageously removes the need for a separate and weighty battery holder.

In another aspect, the PCB has first and second terminals on either side of the PCB, and a first side of the battery couples to the first terminal, while a clip connects the second side of the battery to the second terminal, making the powered connection. This aspect advantageously removes the need for a separate and weighty battery holder.

In still another aspect, a terminal is imprinted on one side of the PCB, and a first side of the battery couples to that terminal. A conductive force terminal connects to the PCB and the second side of the battery, forming a circuit between the battery and the PCB.

By way of background for transponder technology, the following U.S. Patents are incorporated herein by reference: U.S. Pat. No. 6,091,342 and U.S. Pat. No. 5,541,604.

By way of background for smart card and smart tag technology, the following U.S. patents are incorporated herein by reference: U.S. Pat. No. 6,151,647; U.S. Pat. No. 5,901,303; U.S. Pat. No. 5,767,503; U.S. Pat. No. 5,690,773; U.S. Pat. No. 5,671,525; U.S. Pat. No. 6,043,747; U.S. Pat. No. 5,977,877; and U.S. Pat. No. 5,745,037.

By way of background for adhesive bandages, the following U.S. patents are incorporated herein by reference: U.S. Pat. No. 5,045,035; U.S. Pat. No. 5,947,917; U.S. Pat. No. 5,633,070; U.S. Pat. No. 4,812,541; and U.S. Pat. No. 3,612,265.

By way of background for pressure and altitude sensing, the following U.S. patents are incorporated herein by reference: U.S. Pat. No. 5,178,016; U.S. Pat. No. 4,317,126; U.S. Pat. No. 4,813,272; U.S. Pat. No. 4,911,016; U.S. Pat. No. 4,694,694; U.S. Pat. No. 4,911,016; U.S. Pat. No. 3,958,459.

By way of background for rotation sensors, the following U.S. Patents are incorporated herein by reference: U.S. Pat. No. 5,442,221; U.S. Pat. No. 6,089,098; and U.S. Pat. No. 5,339,699. Magnetorestrictive elements are further discussed in the following patents, also incorporated herein by reference: U.S. Pat. No. 5,983,724 and U.S. Pat. No. 5,621,316.

In accord with one aspect of the invention, the communications port is one of a transponder (including a smart tag or RFID tag), transceiver, or one-way transmitter. In other aspects, data from the MMD is communicated off-board (i.e., away from the MMD) by one of several techniques, including: streaming the data continuously off-board to get a real-time signature of data experienced by the MMD; transmis-

sion triggered by the occurrence of an "event" as defined herein; transmission triggered by interrogation, such as interrogation by an ID with a transponder; transmission staggered in "bursts" or "batches," such as when internal storage memory is full; and transmission at predetermined intervals of time, such as every minute or hour.

In one preferred aspect of the invention, the above-described MMDs are packaged like an adhesive bandage. Specifically, in one aspect, one or more protective strips rest over the adhesive portion of the device so as to protect the adhesive until the protective strips are removed. The strips are substantially stick-free so that they are easily removed from the adhesive prior to use. In another aspect, a "wrapper" is used to surround the MMD; the wrapper for example is similar to wrappers of adhesive bandages. In accord with one preferred aspect, the battery electrically couples with the electronics of the MMD when the wrapper is opened and/or when the protective strips are removed. In this way, the MMD can be "single use" with the battery energizing the electronics only when the MMD is opened and applied to an object or person; the battery power being conserved prior to use by a decoupling element associated with the wrapper or protective strips. Those skilled in the art should appreciate that other techniques can be used without departing from the scope of the invention.

The MMDs of the invention are preferably used to detect movement "metrics," including one or more of airtime, speed, power, impact, drop distance, jarring and spin. WO9854581A2 is incorporated herein by reference as background to measuring speed, drop distance, jarring, impact and airtime. U.S. Pat. Nos. 6,157,898, 6,151,563, 6,148,271 and 6,073,086, relating to spin and speed measurement, are incorporated herein by reference. In one aspect, the detector and processor of the MMD collectively detect and determine "airtime," such as set forth in U.S. Pat. No. 5,960,380, incorporated herein by reference. By way of example, one detector is an accelerometer, and the processor analyzes acceleration data from the accelerometer as a spectrum of information and then detects the absence of acceleration data (typically in one or more frequency bands of the spectrum of information) to determine airtime. In another aspect, the detector and processor of the MMD collectively detect and determine drop distance. By way of example, one drop distance detector is a pressure sensor, and the processor analyzes data from the pressure sensor to determine changes in pressure indicating altitude variations (a) over a pre-selected time interval, (b) between a maximum and minimum altitude to assess overall vertical travel, and/or (c) between local minimums and maximums to determine jump distance. By way of a further example, a drop distance detector is an accelerometer, and the processor analyzes data from the accelerometer to determine distance, or changes in distance, in a direction perpendicular to ground, or perpendicular to forward movement, to determine drop distance.

In one preferred aspect, the accelerometer has "free fall" capability (e.g., with near zero hertz detection) to determine drop distance (or other metrics described herein) based, at least on part, on free fall physics. This aspect is for example useful in detecting dropping events of packages in shipment.

In another aspect, the detector and processor of the MMD collectively detect and determine spin. By way of example, one detector is a magnetorestrictive element ("MRE"), and the processor analyzes data from the MRE to determine spin (rotation per second, number of degrees, and/or degrees per second) based upon the MME's rotation through the earth's magnetic fields. By way of a further example, another detector is a rotational accelerometer, and the processor analyzes

data from the rotational accelerometer to determine spin. In another aspect, the detector and processor of the MMD collectively detect and determine jarring, power and/or impact. By way of example, one detector is an accelerometer, and the processor analyzes data from the accelerometer to determine the jarring, impact and/or power. As used herein, jarring is a function of a higher power of velocity in a direction approximately perpendicular to forward movement (typically in a direction perpendicular to ground, a road, or a floor). As used herein, power is an integral of filtered (and preferably rectified) acceleration over some pre-selected time interval, typically greater than about 1/2 second. As used herein, impact is an integral of filtered (and preferably rectified) acceleration over a time interval less than about 1/2 second. Impact is often defined as immediately following an "airtime" event (i.e., the "thump" of a landing).

In one aspect, the MMD continuously relays a movement metric by continuous transmission of data from the detector to a RR. In this way, an MMD attached to a person may beneficially track movement, in real time, of that person by recombination of the movement metrics at a remote computer. In one aspect, multiple MMDs attached to a person quantify movement of a plurality of body parts or movements, for example to assist in athletic training (e.g., for boxing or karate). In another aspect, multiple MMDs attached to an object quantify movement of a plurality of object parts or movements, for example to monitor or assess different components or sensitive parts of an object. For example, multiple MMDs can be attached to an expensive medical device to monitor various critical components during shipment; when the device arrives at the customer, these MMDs are interrogated to determine whether any of the critical components experienced undesirable conditions—e.g., a high impact or temperature or humidity.

By way of background for moisture sensing, the following U.S. patents are incorporated herein by reference: U.S. Pat. No. 5,486,815; U.S. Pat. No. 5,546,974; and U.S. Pat. No. 6,078,056.

By way of background for humidity sensing, the following U.S. patents are incorporated herein by reference: U.S. Pat. No. 5,608,374; U.S. Pat. No. 5,546,974; and U.S. Pat. No. 6,078,056.

By way of background for temperature sensing, the following U.S. patents are incorporated herein by reference: U.S. Pat. No. 6,074,089; U.S. Pat. No. 4,210,024; U.S. Pat. No. 4,516,865; U.S. Pat. No. 5,088,836; and U.S. Pat. No. 4,955,980.

In accord with further aspects of the invention, the MMD measures one or more of the following environmental metrics: temperature, humidity, moisture, altitude and pressure. These environmental metrics are combined into the MMD with a detector that facilitates the monitoring of movement metrics such as described above. For temperature, the detector of one aspect is a temperature sensor such as a thermocouple or thermister. For altitude, the detector of one aspect is an altimeter. For pressure, the detector of one aspect is a pressure sensor such as a surface mount semiconductor element made by SENSYS.

In accord with one aspect, an MMD monitors one or more movement metrics for "events," where data is acquired that exceeds some predetermined threshold or value. By way of example, in one aspect the detector is a triaxial accelerometer and the processor coupled to the accelerometer seeks to determine impact events that exceed a threshold, in any or all of three axes. In another aspect, a single axis accelerometer is used as the detector and a single axis is monitored for an impact event. In another example, the detector and processor

collectively monitor and detect spin events, where for example it is determined that the device rotated more than 360 degrees in $\frac{1}{2}$ second or less (an exemplary "event" threshold). In still another aspect, the detector is a force detector and the processor and detector collectively determine a change of weight of an object resting on the MMD over some pre-selected time period. In one specific object, the invention provides for an MMD to monitor human weight to report that weight, on demand, to individuals. Preferably, such an MMD is in a shoe.

In one aspect, the movement metric of rotation is measured by an MMD with a Hall effect detector. Specifically, one aspect of the Hall effect detector with an MMD of the invention monitors when the MMD is inverted. In one other aspect, the Hall effect detector is used with the processor to determine when an object is inverted or rotated through about 180 degrees. An "event" detected by this aspect can for example be one or more inversions of the MMD of about 180 degrees.

In still another aspect, the MMD has a MRE as the detector, and the MMD measures spin or rotation experienced by the MRE.

In one aspect, a plurality of MMDs are collated and packaged in a single container, preferably similar to the cans or boxes containing adhesive bandages. Preferably, in another aspect, MMDs of the invention are similarly programmed within the container. By way of example, one container carries 100 MMDs that each respond to an event of "10 g's." In another example, another container carries 200 MMDs that respond to an event of "100 g's." Packages of MMDs can be in any suitable number N greater than or equal to two; typically however MMDs are packaged together in groups of 50, 100, 150, 200, 250, 500 or 1000. A variety pack of MMDs are also provided, in another aspect, for example containing ten 5 g MMDs, ten 10 g MMDs, ten 15 g MMDs, ten 20 g MMDs, ten 25 g MMDs, ten 30 g MMDs, ten 35 g MMDs, ten 40 g MMDs, ten 45 g MMDs, and ten 50 g MMDs. Another variety package can for example include groups of MMDs spaced at 1 g or 10 g intervals.

In one preferred aspect, the MMD of the invention includes internal memory. Preferably the memory is within the processor or ASIC. Event data is stored in the memory, in accord with one aspect, until transmitted off-board. In this way, the MMD monitors and stores event data (e.g., an "event" occurrence where the MMD experiences 10 g's). Preferably, the event data is time tagged with data from a real-time clock; and thus a real time clock is included with the MMD (or made integral with the processor or ASIC). A crystal or other clocking mechanism may also be used.

In one aspect, the MMD is programmed with a time at the initial time of use (i.e., when the device is powered). In one other aspect, the MMD is packaged with power so that real time clock data is available when the product is used. In this aspect, therefore, a container of MMDs will typically have a "stale" date when the MMD's battery power is no longer usable. In one aspect, the MMD has a replaceable battery port so that a user can replace the battery.

The invention has certain advantages. An MMD of the invention can practically attach to almost anything to obtain movement information. By way of example, an MMD of the invention can attach to furniture to monitor shipping of furniture. If the furniture were dropped, an impact event occurs and is recorded within the MMD, or transmitted wirelessly, with an associated time tag. When the furniture is damaged prior to delivery, a reader (e.g., an ID) reads the MMD to determine when the damage occurred—leading to the responsible party who may then have to pay for the damage. In a further example, if furniture is rated to "10 g's", an MMD

(programmed and enabled to detect 10 g events) is attached to the furniture when leaving the factory, so that any 10 g event before delivery is recorded and time-stamped, again leading to a responsible party. Similarly, in other aspects, devices of the invention are attached to packages (e.g., FED EX or UPS shipments) to monitor handling. By way of example, fragile objects may be rated to 5 g; and an appropriately programmed MMD of the invention is attached to the shipment to record and time-tag 5 g events. In another aspect, fragile objects that should be maintained at a particular orientation (i.e., packages shipped with "This Side Up" instructions) are monitored by an MMD detecting inversions of about 180 degrees, such as through a Hall Effect detector.

In one aspect, the MMD includes a tamper proof detector that ensures the MMD is not removed or tampered with once applied to an object or person, until an authorized person removes the MMD. In one aspect, the tamper proof detector is a piezoelectric strip coupled into or with the adhesive strip. Once the MMD is powered and applied to an object or person, a quiescent period ensues and the MMD continually monitors the tamper proof detector (in addition to the event detector) to record tampering activity. In the case of the piezoelectric strip, removal of the MMD from a person or object after the quiescent period provides a relatively large voltage spike, indicating removal. That spike is recorded and time stamped. If there is more than one such record (i.e., one record represents the final removal), then tampering may have occurred. Since date and time are tagged with the event data, the tamper time is determined, leading to identify the tampering person (i.e., the person responsible for the object when the tamper time was tagged).

In one aspect, the invention provides an ID in the form of a cell phone. Nearly one in three Americans uses a cell phone. According to the teachings of the invention, data movement "metrics" are read from an MMD through the cell phone. Preferably, data communicated from the MMD to the cell phone is made only through secure communications protocols so that only authorized cell phones can access the MMD. In one specific aspect, MMD events are communicated to a cell phone or cellular network, and from that point are relayed to persons or additional computer networks for use at a remote location.

Miniature tension or compression load cells are used in certain aspects of the invention. By way of example, an MMD incorporating such cells are used in measuring and monitoring tension and/or compression between about fifty grams and 1000 lbs, depending upon the application. In one aspect, the MMD generates a warning signal when the load cell exceeds a pre-selected threshold.

In accord with the invention, several advantages are apparent. The following lists some of the non-limiting movement events monitored and captured by select MMDs of the invention, in accord with varied aspects of the invention:

- impact or "g's" experienced by the MMD that exceed a predetermined threshold, e.g., 10 or 50 g's
- accumulated or integrated rectified acceleration experienced by the MMD over a predetermined time interval
- rotations experienced by the MMD in increments of 90 degrees, such as 90, 180, 270, 360 degrees, or multiples thereof
- frequency-filtered, rectified, and low-pass filtered acceleration detecting impact events, by the MMD, exceeding thresholds such as 5, 10, 20, 25, 50 and 100 g's, preferably after an airtime event
- rotational velocities experienced by the MMD exceeding some pre-selected "degrees per second" or "revolutions per minute" threshold

airtime events experienced by the MMD exceeding $\frac{1}{4}$, $\frac{1}{5}$, or $\frac{1}{2}$ second, or multiples thereof
 speed events experienced by the MMD exceeding miles per hour thresholds of 10, 20, 30, 40, 50, 60 mph (those skilled in the art should appreciate that other "speed" units can be used, e.g., km/hour, m/s or cm/s)
 drop distance events experienced by the MMD exceeding set distances such as 1, 2, 3, 4, 5, 10, 20, 50 and 100 feet (or inches, centimeters or meters)
 altitude variation events between maximum and minimum values over a daily time interval
 jerk variations proportional to V^n or $\partial^n V / \partial t^n$, where V is velocity in a direction perpendicular to movement along a surface (e.g., ground), where n is some integer greater than or equal to 2, and where t is time

The above movement events may be combined for a variety of metrics useful to users of the invention. For example, in one aspect, altitude variations are used to accurately gauge caloric burn through the variations. Such information is particularly useful for mountain bikers and in mountain sports.

The invention of one aspect provides a quantizing accelerometer that detects one or more specific g-levels in a manner particularly useful as a detector in an MMD of the invention.

There are thus several applications of the invention, including the monitoring of movement for people, patients, packages, athletes, competitors, shipments, furniture, athletes in training (e.g., karate), and industrial robotics. The benefits derived by such monitoring can be used by insurance companies and manufacturers, which, for example, insure shipments and packages for safe delivery to purchasers. Media broadcasters, including Internet content providers, can also benefit by augmenting information associated with a sporting event (e.g., airtime of a snowboarder communicated in real time to the Internet, impact of a football or soccer ball during a game, boxing glove strike force during a fight, tennis racket strike force during a match). The MMD of the invention is small, and may be attached to practically any object—so ease of use is clearly another advantage. By way of example, an MMD can be mounted to the helmet or body armor of each football player or motocross competitor to monitor movement and jerk of the athlete. In such applications, data from the MMD preferably transmits event data in real time to a RR in the form of a network, so that MMD data associated with each competitor is available for broadcast to a scoreboard, TV or the Internet. Other advantages should be apparent in the description within.

Event Monitoring Devices

The invention also provides certain sensors and devices used to monitor and report temperature, humidity, chemicals, heart rate, pulse, pressure, stress, weight, environmental factors and hazardous conditions.

In one aspect, the invention provides an event monitor device ("EMD") including an adhesive strip, a processor, a detector, and a communications port. In another aspect, two or more of the processor, port and detector are combined in a single application specific integrated circuit ("ASIC"). In one aspect the detector is a humidity or temperature sensor, and preferably that detector is embedded into silicon within the ASIC. In other aspects, the detector is one of an EKG sensing device, weight-sensing detector, and chemical detector. In still another aspect, the EMD includes a battery. In the preferred aspect of the invention, the EMD and battery are packaged in a protective wrapper. Preferably, the battery is packaged with the EMD in such a way that it does not "power" the EMD until the wrapper is removed. Preferably, the EMD includes a real time clock so that the EMD tags "events" with time and/or date information.

In yet another aspect, the EMD with adhesive strip collectively take a form similar to an adhesive bandage. More particularly, the adhesive strip of the invention is preferably like or similar to the adhesive of the adhesive bandage; and the processor is embedded with the strip much the way the cotton is with the adhesive bandage. Preferably, a soft material (e.g., cotton or cloth) is included to surround the processor so as to (a) soften contact of rigid EMD components with a person and/or (b) protect the processor (and/or other components of the EMD). In still another aspect, the battery is also coupled with the soft material. In still another aspect, the processor and other elements of the EMD are combined into a single system-on-chip integrated circuit. A protective cover may surround the chip to protect the EMD from breakage.

In one aspect, one EMD of the invention takes a form similar to a smart label, with an adhesive substantially disposed with the label, e.g., on one side of the label. The adhesive strip of this EMD includes all or part of the back of the label with adhesive or glue permitting attachment of the label to other objects (or to a person).

In still another aspect, the EMD of the invention takes the form of a rigid monolithic that attaches to objects through one of known techniques. In this aspect, the device has a processor, communications port, and detector. A battery is typically included with the EMD. The EMD is attached to objects or persons by one of several techniques, including by glue or mechanical attachment (e.g., a pin or clip). An EMD of this aspect can for example exist in the form of a credit card, wherein the communications port is either a contact transponder or a contactless transponder. The EMD of one aspect includes a magnetic element that facilitates easily attaching the EMD to metal objects.

In operation, the EMD of the invention is typically interrogated by an ID. The EMD is responsive to the ID to communicate information within the EMD and, preferably, over secure communications protocols. By way of example, one EMD of the invention releases internal data only to an ID with the correct passwords and/or data protocols. The ID can take many forms, including a cell phone or other electronic device (e.g., an MP3 player, pager, watch, or PDA) providing communications with the EMD transmitter.

However, in another aspect, the EMD communicates externally to a RR. The RR listens for data from the EMD and collects that data for subsequent relay or use. In one aspect, the EMD's communications port is a one-way transmitter. Preferably, the EMD communicates data from the EMD to the RR either (a) upon the occurrence of an "event" or (b) in repeated time intervals, e.g., once every minute or more. Alternatively, the EMD's communication port is a transceiver that handshakes with the RR to communicate data from the EMD to the RR. Accordingly, the EMD responds to data requests from the RR, in this aspect. In still another aspect, the RR radiates the EMD with transponder frequencies; and the EMD "reflects" the data to the RR.

Accordingly, the communications port of one EMD is a transponder responsive to one or more frequencies to relay data back to an ID. By way of example, these frequencies can be one of 125 kHz and 13.56 MHz, the frequencies common with "contactless" RFID tags known in the art. In other aspects, communications frequencies are used with emission power and frequencies that fall within the permissible "unlicensed" emission spectrum of part 15 of FCC regulations, Title 47 of the Code of Federal Regulations. In particular, one desirable feature of the invention is to emit low power, to conserve battery power and to facilitate use of the EMD in various environments; and therefore an ID is placed close to the EMD to read the data. In other words, in one aspect,

wireless communications from the EMD to the ID occurs over a short distance of a fraction of an inch to no more than a few feet. By way of example, as described herein, one ID of the invention takes the form of a cell phone, which communicates with the EMD via one or more secure communications techniques. Data acquired from the EMD is then communicated through cellular networks, if desired, to relay EMD data to end-users. Or, in another aspect, a sensitive or directional antenna is used to increase the distance to detect data of the EMD.

In another aspect, the communications port is an infrared communications port. Such a port, in one aspect, communicates with the cell phone in secure communication protocols. In other aspects, an ID communicates with the infrared port to obtain the data within the EMD.

In yet another aspect, the communications port includes a transceiver. The EMD listens for interrogating signals from the RR and, in turn, relays "event" data from the EMD to the RR. Alternatively, the EMD relays "event" data at set time intervals or when the EMD accumulates data close to an internal storage limit. In one aspect, thereby, the EMD includes internal memory; and the EMD stores one or more "event" data, preferably with time-tag information, in the memory. When the memory is nearly full, the EMD transmits the stored data wirelessly to a RR. Alternatively, stored data is transmitted to an IR when interrogated. In a third alternative, the EMD transmits stored data at set intervals, e.g., once per ½ hour or once per hour, to relay stored data to a RR. Other transmission protocols can be used without departing from the scope of the invention.

In still another aspect, data from the EMD is relayed to an ID through "contact" communication between the ID and the communications port. In one aspect, the EMD includes a small conductive plate (e.g., a gold plate) that contacts with the ID to facilitate data transfer. Smart cards from the manufacturer GEMPLUS may be used in such aspects of the invention.

In one aspect, the EMD includes a printed circuit board ("PCB"). A battery—e.g., a 2032 or 1025 Lithium coin cell—is also included, in another aspect of the invention. To make the device small, the PCB preferably has multilayers—and two of the internal layers have a substantial area of conducting material forming two terminals for the battery. Specifically, the PCB is pried apart at one edge, between the terminals, and the battery is inserted within the PCB making contact and providing voltage to the device. This advantageously removes the need for a separate and weighty battery holder. Flex circuit boards may also be used.

In another aspect, the PCB has first and second terminals on either side of the PCB, and a first side of the battery couples to the first terminal, while a clip connects the second side of the battery to the second terminal, making the powered connection. This aspect advantageously removes the need for a separate and weighty battery holder.

In still another aspect, a terminal is imprinted on one side of the PCB, and a first side of the battery couples to that terminal. A conductive force terminal connects to the PCB and the second side of the battery, forming a circuit between the battery and the PCB.

In accord with one aspect of the invention, the communications port is one of a transponder (including a smart tag or RFID tag), transceiver, or one-way transmitter. In other aspects, data from the EMD is communicated off-board (i.e., away from the EMD) by one of several techniques, including: streaming the data continuously off-board to get a real-time signature of data experienced by the EMD; transmission triggered by the occurrence of an "event" as defined herein;

transmission triggered by interrogation, such as interrogation by an ID with a transponder; transmission staggered in "bursts" or "batches," such as when internal storage memory is full; and transmission at predetermined intervals of time, such as every minute or hour.

In one preferred aspect of the invention, the above-described EMDs are packaged like an adhesive bandage. Specifically, in one aspect, one or more protective strips rest over the adhesive portion of the device so as to protect the adhesive until the protective strips are removed. The strips are substantially stick-free so that they are easily removed from the adhesive prior to use. In another aspect, a "wrapper" is used to surround the EMD; the wrapper being similar to existing wrappers of adhesive bandages. In accord with one preferred aspect, the battery electrically couples with the electronics of the EMD when the wrapper is opened and/or when the protective strips are removed. In this way, the EMD can be "single use" with the battery energizing the electronics only when the EMD is opened and applied to an object or person; the battery power being conserved prior to use by a decoupling element associated with the wrapper or protective strips. Those skilled in the art should appreciate that other techniques can be used without departing from the scope of the invention.

In one aspect, the EMD continuously relays an environmental metric (e.g., temperature, humidity, or chemical content) by continuous transmission of data from the detector to a RR. In this way, an EMD attached to a person or object may beneficially track conditions, in real time, of that person or object by recombination of the environmental metrics at a remote computer. In one aspect, multiple EMDs attached to a person or object quantify data for a plurality of locations, for example to monitor sub-parts of an object or person.

In accord with further aspects of the invention, the EMD measures one or more of the following environmental metrics: temperature, humidity, moisture, altitude and pressure. For temperature, the detector of one aspect is a temperature sensor such as a thermocouple or thermister. For altitude, the detector of one aspect is an altimeter. For pressure, the detector of one aspect is a pressure sensor such as a surface mount semiconductor element made by SENSYS.

In accord with one aspect, an EMD monitors one or more metrics for "events," where data is acquired that exceeds some predetermined threshold or value. By way of example, in one aspect the detector is a temperature sensor and the processor coupled to the temperature sensor seeks to determine temperature events that exceed a threshold. In another aspect, a humidity sensor is used as the detector and this sensor is monitored for a humidity event (e.g., did the EMD experience 98% humidity conditions). In another example, the detector and processor collectively monitor stress events, where for example it is determined that the EMD attached to a human senses increased heart rate of over 180 beats per minute (an exemplary "event" threshold). In still another aspect, the detector is a chemical (or pH) detector and the processor and detector collectively determine a change of chemical composition of an object connected with the EMD over some pre-selected time period.

In one aspect, a plurality of EMDs are collated and packaged in a single container, preferably similar to the cans or boxes containing adhesive bandages. Preferably, in another aspect, EMDs of the invention are similarly programmed within the container. By way of example, one container carries 100 EMDs that each respond to an event of "5 degrees" variation from some reference temperature. In another example, another container carries 200 EMDs that respond to an event of "90 degrees" change absolute. Temperature sen-

sors may be programmed to determine actual temperatures, e.g., 65 degrees, or changes in temperature from some reference point, e.g., 10 degrees from reference.

Packages of EMDs can be in any suitable number N greater than or equal to two; typically however EMDs are packaged together in groups of 50, 100, 150, 200, 250, 500 or 1000.

In one preferred aspect, the EMD of the invention includes internal memory. Preferably the memory is within the processor or ASIC. Event data is stored in the memory, in accord with one aspect, until transmitted off-board. In this way, the EMD monitors and stores event data (e.g., an "event" occurrence where the EMD experiences 100 degree temperatures). Preferably, the event data is time tagged with data from a real-time clock; and thus a real time clock is included with the EMD (or made integral with the processor or ASIC). In one aspect, the EMD is programmed with a time at the initial time of use (i.e., when the device is powered). In one other aspect, the EMD is packaged with power so that real time clock data is available when the product is used. In this aspect, therefore, a container of EMDs will typically have a "stale" date when the EMD's battery power is no longer usable. In one aspect, the EMD has a replaceable battery port so that a user can replace the battery.

The invention has certain advantages. An EMD of the invention can practically attach to almost anything to obtain event information. By way of example, an EMD of the invention can attach to patients to track health and conditions in real time and with remote monitoring capability.

In one aspect, the EMD includes a tamper proof detector that ensures the EMD is not removed or tampered with once applied to an object or person, until an authorized person removes the EMD. In one aspect, the tamper proof detector is a piezoelectric strip coupled into or with the adhesive strip. Once the EMD is powered and applied to an object or person, a quiescent period ensues and the EMD continually monitors the tamper proof detector (in addition to the event detector) to record tampering activity. In the case of the piezoelectric strip, removal of the EMD from a person or object after the quiescent period provides a relatively large voltage spike, indicating removal. That spike is recorded and time stamped. If there is more than one such record (i.e., one record represents the final removal), then tampering may have occurred. Since date and time are tagged with the event data, the tamper time is determined, leading to identify the tampering person (i.e., the person responsible for the object when the tamper time was tagged).

In one aspect, the invention provides an ID in the form of a cell phone. Nearly one in three Americans use a cell phone. According to the teachings of the invention, data event "metrics" are read from an EMD through the cell phone. Preferably, data communicated from the EMD to the cell phone is made only through secure communications protocols so that only authorized cell phones can access the EMD. In one specific aspect, EMD events are communicated to a cell phone or cellular network, and from that point are relayed to persons or additional computer networks for use at a remote location.

In accord with the invention, several advantages are apparent. The following lists some of the non-limiting events monitored and captured by select EMDs of the invention, in accord to varied aspects of the invention:

- absolute or relative temperatures
- heart rate or other fitness characteristics
- stress characteristics
- humidity or relative humidity
- fitness or patient health characteristics

The invention will next be described in connection with preferred embodiments. In addition to those described above, certain advantages should be apparent in the description which follows.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a monitor device (e.g., a "MMD" or "EMD") and receiver (ID or RR) constructed according to the invention;

FIG. 1A shows an alternative monitor device of the invention, and in data communication with a receiver via "contact" transponder technology;

FIG. 2 shows a front view of one monitor device of the invention and formed with an adhesive strip and padding to soften physical connection to persons or objects;

FIG. 2A shows a cross-sectional top view of the monitor device and strip of FIG. 2;

FIG. 2B shows a cross-sectional top view of one monitor device of the invention integrated with (a) a battery and (b) protective non-stick strips over the adhesive strip, all enclosed within a protective wrapper;

FIG. 2C shows a front view of the monitor device of FIG. 2B, without a protective wrapper;

FIG. 2D shows an alternative monitor device of the invention and integrated directly with the adhesive strip to ensure detector contact;

FIG. 2E shows one monitor device of the invention used to detect and/or track heart rate, in accord with the invention;

FIG. 3 shows a cross-sectional view (not to scale) of one monitor device of the invention for integrating a battery with a printed circuit board;

FIG. 3A is a cross-sectional top view of part of the monitor device of FIG. 3;

FIG. 3B shows an operational view of the monitor device of FIG. 3, with a battery inserted between layers of the printed circuit board;

FIG. 3C shows a cross-sectional view (not to scale) of one monitor device of the invention for integrating a battery with a printed circuit board;

FIG. 3D shows an operational view of the monitor device of FIG. 3C, with a battery attached to sides of the underlying printed circuit board;

FIG. 3E shows an operational view of another monitor device of the invention, with a battery attached to one side of the underlying printed circuit board;

FIG. 3F shows one battery attachment mechanism, including batteries, for use with a monitor device of the invention;

FIG. 3G shows the mechanism of FIG. 3F without the batteries;

FIGS. 4 and 4A illustrate one technique for powering a monitor device, in accord with the invention;

FIGS. 5 and 5A illustrate one monitor device integrated within a label, in accord with the invention;

FIG. 6 shows a monolithic monitor device constructed according to the invention for attachment to an object by way of mechanical attachment;

FIG. 7 shows one monitor device of the invention used to monitor patient health characteristics;

FIG. 7A shows a system of the invention used to monitor pulse characteristics for patient health, with the device of FIG. 7;

FIG. 7B shows an alternative monitor device of the invention used to monitor respiratory behavior such as with the system of FIG. 7A;

15

FIG. 8 illustrates application of a plurality of MMDs, of the invention, to athletes to facilitate training and/or to provide excitement in broadcast media;

FIG. 8A illustrates real time data acquisition, reconstruction and display for data wirelessly transmitted from the MMDs of FIG. 8;

FIG. 8B illustrates a television display showing data generated in accord with the teachings of the invention;

FIG. 8C shows one MMD applied to a human fist in accord with the invention;

FIG. 9 shows a flow-chart illustrating "event" based and timed sequence data transmissions between a monitor device and a receiver, in accord with the invention;

FIG. 10 shows a sensor dispensing canister constructed according to the invention;

FIG. 10A shows an array of sensors arranged for mounting within the canister of FIG. 10;

FIG. 10B shows one sensor of the array of sensors of FIG. 10A;

FIG. 10C shows an interface between one sensor and a base assembly in the canister of FIG. 10;

FIG. 10D shows an operational disconnect of one sensor from the base assembly in FIG. 10C;

FIG. 10E schematically illustrates canister electronics and a sensor as part of the canister of FIG. 10;

FIG. 10F illustrates imparting time-tag information to a sensor through a canister such as in FIG. 10;

FIG. 10G shows one receiver constructed according to the invention;

FIG. 10H shows one receiver in the form of a ski lift ticket constructed according to the invention;

FIG. 10I shows one ticket sensor constructed according to the invention;

FIG. 11 schematically shows an electrical logic and process flow chart for use with determining "airtime" in accord with the invention;

FIG. 12 schematically shows a state machine used in association with determining airtime in association with an algorithm such as in FIG. 11;

FIG. 13 graphically shows accelerometer data and corresponding process signals used to determine airtime in accord with preferred embodiments of the invention;

FIG. 14 and FIG. 14A show a state diagram illustrating one-way transmission protocols according to one embodiment of the invention;

FIG. 15 schematically illustrates functional blocks for one sensor of the invention;

FIG. 16 schematically illustrates functional blocks for one display unit of the invention;

FIG. 17 shows a perspective view of one sensor housing constructed according to the invention, for use with a sensor such as a monitor device;

FIG. 18 illustrates a sensor, such as an MMD, within the housing of FIG. 17;

FIG. 19 shows a top perspective view of another housing constructed according to the invention, for use with a sensor such as an MMD and for mounting to a vehicle;

FIG. 20 shows one vehicle and vehicle attachment bracket to which the housing of FIG. 19 attaches;

FIG. 21 shows another vehicle and vehicle attachment bracket to which the housing of FIG. 19 attaches;

FIG. 22 shows a bottom perspective view of the housing of FIG. 19;

FIG. 23 shows a bracket constructed according to the invention and made for attachment between the housing of FIG. 19 and a vehicle attachment bracket;

FIG. 24 shows a top element of the housing of FIG. 19;

16

FIG. 25 shows a bottom element of the housing of FIG. 19;

FIG. 26 shows a perspective view of one housing constructed according to the invention;

FIG. 27 shows a perspective view of a top portion of the housing of FIG. 26;

FIG. 28 shows a perspective view of a bottom portion of the housing of FIG. 27;

FIG. 29 shows a perspective view of one monitor device constructed according to the invention for operational placement within the housing of FIG. 26;

FIG. 30 shows a mounting plate for attaching monitor devices to flat surfaces in accord with one embodiment of the invention;

FIG. 31 shows a perspective view of the plate of FIG. 30 with a monitor device coupled thereto;

FIG. 32 shows an end view of the plate and device of FIG. 31;

FIG. 33 shows, in a top view, a low-power, long life accelerometer sensor constructed according to the invention;

FIG. 34 shows a cross-sectional view of one portion of the accelerometer sensor of FIG. 33, illustrating operation of the moment arm quantifying g's in accord with the invention;

FIG. 35 shows a circuit illustrating operation of the accelerometer sensor of FIG. 33;

FIG. 36 illustrates a runner speedometer system constructed according to the invention;

FIG. 37 illustrates an alternative runner speedometer system constructed according to the invention;

FIG. 38 illustrates data capture and analysis principles for determining speed with the system of FIG. 37;

FIG. 39 illustrates one sensor for operation with a shoe in a speedometer system such as described in FIG. 37;

FIG. 40 shows another runner speedometer system of the invention, including a GPS sensor;

FIG. 41 shows a biking work function system constructed according to the invention;

FIG. 42 shows one racecar monitoring system constructed according to the invention;

FIG. 43 shows one data capture device for operation with a racecar in a race monitoring system such as shown in FIG. 42;

FIG. 44 shows one crowd data device for operation with spectators in a race monitoring system such as shown in FIG. 42;

FIG. 45 shows one body-armor incorporating a monitor device in accord with the invention;

FIG. 46 shows one system for measuring rodeo and/or bull riders in accord with other embodiments of the invention;

FIG. 47 shows a representative television display of a bull and rider configured with a system monitoring characteristics of the bull and/or rider, in accord with the invention;

FIG. 48 shows one EMD of the invention utilizing flex strip as the "PCB" in accord with the invention;

FIG. 49 depicts one computerized gaming system of the invention;

FIG. 50 schematically shows one flow chart implanting game algorithms in accord with the invention;

FIG. 51 shows one speed detection system for a ski resort in accord with the invention;

FIG. 52 shows one bar code reader suitable for use in the system of FIG. 51;

FIG. 53 shows one monitor device constructed according to the invention and incorporating a GPS receiver;

FIG. 54 shows a system suitable for use with the device of FIG. 53;

FIG. 55 shows an infant monitoring system constructed according to the invention;

FIG. 56 schematically shows a flow chart of operational steps used in the system of FIG. 55;

FIG. 57 shows one MMD of the invention used to gauge patient weight;

FIG. 58 shows a weight monitoring system constructed according to the invention;

FIG. 59 shows another weight monitoring system of the invention;

FIG. 60 shows a force-sensing resistor suitable for use in the weight monitoring systems of FIG. 58 and FIG. 59 and in the MMD of FIG. 57;

FIG. 61 shows one weight-sensing device in the form of a shoe or shoe insert, in accord with the invention;

FIG. 62 illustrates fluid cavities suitable for use in a device of FIG. 61;

FIG. 63 shows a wrestling performance monitoring system constructed according to the invention;

FIG. 64 shows a representative graphic output from the system of FIG. 63;

FIG. 65 shows a surfing event system according to the invention;

FIG. 66 shows a Green Room surfing event system according to the invention;

FIG. 67 shows a personal item network constructed according to the invention;

FIG. 68 shows a communications interface between a computer and one of items of FIG. 67;

FIG. 69 illustrates electronics for one of the items within the network of FIG. 67;

FIG. 70 and FIG. 71 show an electronic drink coaster constructed according to the invention;

FIG. 72 shows a package management system of the invention; and

FIG. 73 shows a product integrity tracking system of the invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

FIG. 1 shows a monitor device 10 constructed according to the invention. Device 10 can for example operate as an MMD or EMD described above. Device 10 includes a detector 12, processor 14, communications port 16, and battery 18. Preferably, device 10 also includes solid-state memory 20. Memory 20 can be integral with processor 14 (or other element of device 10, including port 16), or a stand-alone element within device 10. As an MMD, for example, detector 12 senses movement experienced by device 10 and generates signals indicative of that movement. Processor 12 then processes the signals to extract desired movement metrics, as described herein. Typically, when the movement metrics exceed a predetermined threshold, processor 12 stores data as an "event" within memory 20. Events are also preferably tagged with time information, typically date and time, as provided by clock 22.

As an EMD, for example, detector 12 senses temperature experienced by device 10 and generates signals indicative of temperature (either absolute, or relative). Processor 12 then processes the signals to extract desired data. Preferably, data such as temperature are time tagged with date and/or time information so that a limited recording is made of environmental conditions.

Communications port 16 communicates event data from device 10 to a receiver 24 as wireless data 30a. Port 16 typically performs such communications in response to commands from processor 14. Communications port 26 receives wireless data 30a for use within receiver 24. If desired, com-

munications port 26 can also communicate with port 16 to transmit wireless data 30b to device 10. In such an embodiment, ports 16, 26 are preferably radio-frequency, infrared or magnetically-inductive transceivers. Alternatively, port 26 is a transmitter that interrogates device 10; and port 16 is a transponder that reflects event data to receiver 24. In one preferred embodiment, receiver 24 is part of the circuitry and packaging of a cell phone, which relays events (e.g., a movement event) to a remote storage facility. In other embodiments, receiver 24 is part of the circuitry and packaging of an MP3 player, pager, watch, or electronic PDA. Receiver 24 may connect with headphones (not shown) to provide information to a user corresponding to "event" data.

Data communication between device 10 and receiver 24 is preferably "secure" so that only a receiver with the correct identification codes can interrogate and access data from device 10. In such a mode, receiver 24 is an interrogation device ("ID"); and wireless communications 30a, 30b between ports 16, 26 can be through one of several electromagnetic communications spectrums, including radio-frequencies, microwave frequencies, ultrasound or infrared. However, communications between device 10 and receiver 24 can also be one way, e.g., wireless data 30a from device 10 to receiver 24; and in such an embodiment receiver 24 preferably understands the communications protocols of data 30a to correctly interpret the data from device 10. Receiver 24 in this embodiment "listens" for data transmitted from device 10. Receiver 24 thus may function as a remote receiver ("RR") stationed some distance (e.g., tens or hundreds of feet or more) from device 10.

FIG. 1A shows an alternative communication scheme between device 10' and receiver 24'. Like numbered items in FIG. 1A have like functions as in FIG. 1; except that in FIG. 1A, ports 16', 26' function to transfer data from device 10' to receiver 24' as a "contact" transponder. Device 10' and receiver 24' are separate elements, though they appear immediately adjacent. A conductive pad 17 with port 16' facilitates communication with port 26' via its conductive pad 19. Accordingly, event data from device 10' transfers data to receiver 24' without "wireless" data 30 (FIG. 1), but rather through the circuit formed between device 10' and receiver 24' when contact is made between pads 17, 19, as shown in FIG. 1A.

A monitor device 10, 10' of the invention preferably includes an adhesive strip that provides for convenient attachment of the device to an object or person. As shown in FIG. 2, one such device 10" is shown coupled to adhesive strip 32 for just this purpose. Strip 32 is preferably flexible so as to bend and attach device 10" to nearly any surface shape. Strip 32 includes an adhesive 34 that bonds strip 32 to a person or object, such that device 10" attaches to that person or object in a substantially fixed location. FIG. 2 also shows that device 10" preferably resides adjacent to padding 36, to protect device 10" from physical harm and to provide a cushion interface between device 10" and a person or object. Padding 36 can for example be cotton or other soft material; and padding 36 can be made from soft material typically found with adhesive bandages of the prior art. Device 10" preferably includes a protective housing 11 (FIG. 2A) surrounding integrated circuits to protect the circuits from breakage.

FIG. 2A shows a top cross-sectional view of monitor device 10" and strip 32. As illustrated, strip 32 is flexible such that it can conform to a surface (e.g., curved surface 37) for attachment thereto. Adhesive 34 is shown covering substantially all of the back of strip 32 to provide for complete attachment to surface 37. Though padding 36 is not required, it preferably encapsulates device 10" to provide for optimum

protection for device 10" when attached to surface 37. Note that padding 36 also protects surface 37 from scratching by any rigid elements of device 10" (e.g., battery 18, FIG. 1). Those skilled in the art should appreciate that padding 36 can be formed partially about device 10" to achieve similar goals and without departing from the scope of the invention; for example, padding 36 can reside adjacent only one side of device 10".

Those skilled in the art should appreciate that two or more of elements 14, 16, 18, 22 (FIG. 1) can be, and preferably are, integrated within an ASIC. Further, in one preferred embodiment, the detector 12 is also integrated within the ASIC as a solid-state accelerometer (e.g., using MEM technology). However, detector 12 can be a stand-alone element such as a piezoelectric strip, strain gauge, force-sensing resistor, weight sensor, temperature sensor, humidity sensor, chemical sensor, or heart rate detector.

FIG. 2B shows one monitor device 10z, with battery 18z, coupled within a protective wrapper 27. Protective non-stick strips 29 are also shown to cover adhesive (e.g., adhesive 34, FIG. 2) on adhesive strips 32z until device 10z is operatively used and applied to a person or object. Preferably, wrapper 27 and non-stick strips 29 are similar in design to the wrapper and strips of a common adhesive bandage. Accordingly, users of device 10z intuitively know how to open and attach device 10z to an object or surface (e.g., surface 37, FIG. 2A)—by opening wrapper 27, removing device 10z by pulling adhesive strip 32z from wrapper 27, and then removing non-stick strips 29 so that adhesive strips 32z are exposed for application to the object or surface. FIG. 2C illustrates device 10z in a back view with wrapper 27 removed, showing fuller detail of non-stick strips 29 covering and protecting the underlying adhesive (e.g., adhesive 34, FIG. 2) on strip 32z.

A device 10 can also integrate directly with the adhesive strip, as shown in FIG. 2D. Specifically, device 10" of FIG. 2D couples directly with adhesive strip 32'. In addition, there is no padding with device 10"—as in certain circumstances it is desirable to have optimal fixation between device 10" and strip 32'. A housing 11' preferably protects device 10" from breakage. In one example, when the detector of device 10" is an accelerometer, direct coupling between device 10" and strip 32' provides for more accurate data capture of accelerations of the object to which strip 32' is adhered. As such, adhesive 34' preferably extends across the whole width of strip 32', as shown, such that device 10" is tightly coupled to the object adhered to by strip 32'.

FIG. 2E shows one heart-rate monitor 10w constructed according to the invention. Like device 10, 10", device 10w preferably couples directly with an adhesive strip 32w with adhesive 34w. Monitor 10w includes a heart rate detector 12w that may for example detect EKG signals. By way of background, the following heart rate monitoring patents are incorporated herein by reference: U.S. Pat. No. 4,625,733; U.S. Pat. No. 5,243,993; U.S. Pat. No. 5,690,119; U.S. Pat. No. 5,738,104; U.S. Pat. No. 6,018,677; U.S. Pat. No. 3,807,388; U.S. Pat. No. 4,195,642; and U.S. Pat. No. 4,248,244. Two electrodes 15 electrically coupled to detector 12w with monitor 10w via conductive paths 13. Electrodes 15 couple with human skin when adhesive strip 32w is applied to the skin such that electromagnetic pulses from the heart are detected by detector 12w. By way of example, detector 12w of one embodiment detects potential differences between electrodes 15 to determine heart rate. Once heart rate is detected, information is passed to other sections to process and/or retransmit the data as wireless data 17 to a remote receiver. For example, data from detector 12w may be transmitted to processor and/or communications port 14w, 16w; from there, data may be

relayed off-board. In one embodiment, wireless data 17 is a signal indicative of the existence of heart rate—so that monitor 10w may be used in patient safety to warn of patient heart failure (i.e., the absence of a heart rate may mean that a patient went into cardiac arrest). In another embodiment, wireless data 17 is a signal indicative of actual heart rate, e.g., 100 beats per minute, such that monitor 10w may be used in fitness applications. Monitor 10w thus provides an alternative to "strap" heart rate monitors; users of the invention stick on monitor 10w via adhesive strip 32w to monitor heart rate in real time. Data 17 may be captured by a receiver such as a watch to display the data to the wearing user. Monitor 10w can also be used in patient monitoring applications, such as in hospitals, so that patient health is monitored remotely and efficiently. By way of example, a monitor 10w may be attached to each critical care patient so that a facility (e.g., a hospital) can monitor each patient at a single monitoring location (i.e., at the location receiving signals 17).

As an alternative heart rate monitor, device 10 of FIG. 1 has a detector in the form of a microphone. Processor 12 then processes microphone detector data to "listen" for breathing sounds to report breathing—or not breathing—as a health metric.

The invention also provides for efficiently integrating battery 18 with a monitor device. FIG. 3 illustrates one technique, wherein the monitor device (e.g., device 10) includes a printed circuit board ("PCB") 40 that forms the back-plane forming the electrical interconnectivity with elements 42 (elements 42 can for example be any of items 12, 14, 16, 20, 22, FIG. 1). PCB 40 of FIG. 3 is a multi-layer board, as illustrated by layer line 44. Between two layers 46a, 46b, PCB 40 is manufactured with two opposing terminals 48a, 48b. Terminals 48a, 48b can for example be copper tracks in PCB 40, or copper with gold flash to facilitate good electrical connection. FIG. 3A shows a top view of one terminal 48a with layer 46a, illustrating that terminal 48a is typically larger than other tracks 50 within PCB 40. Accordingly, terminal 48a is large enough to form good electrical connection with a battery inserted between layers 46, such as shown in FIG. 3B. Specifically, FIG. 3B shows PCB 40 separated between layers 46, and a battery 52 inserted therebetween, to make powered connection to PCB 40 and its elements 42. For purposes of clarity, only part of PCB 40 is shown in FIG. 3B, and none of elements 42 are shown. Layers 46a, 46b may be separated by prying layers 46 apart. Battery 52 can for example be a Li coin cell battery known in the art.

FIG. 3C shows another PCB 40' for use with a monitor device of the invention; except, in FIG. 3C, terminals 48a', 48b' are on opposing sides of PCB 40', as shown. PCB 40' can be a single layer board, or multi-layer board. Batteries 52' are coupled to PCB 40' as shown in FIG. 3D; and held to PCB 40' by end clip 54. FIG. 3D illustrates clip 54 as a stand-alone element 54-A; and alternatively as element 54-B holding batteries 52' in place to PCB 40'. End clip 54 slides over PCB 40' and batteries 52' as illustrated by arrow 56. End clip 54 is preferably conductive to complete the circuit to power PCB 40' (at a contact point with PCB 40') and its elements 42 for use as monitor device.

Battery attachment to PCB 40" can also be made as in FIG. 3E, where battery (or batteries) 52" is attached to one side of PCB 40". To make overall circuit connectivity, battery 52" connects to terminal 48a", and end clip 54' makes connection with terminal 48b", as shown. A contact point with PCB 40" can be made to complete desired circuit functions. End clip 54 is thus preferably conductive to complete the circuit to power PCB 40" and its elements 42 for use as a monitor device.

The battery integrations with PCBs of FIGS. 3D and 3E provide for simple and secure ways to mount batteries 52 within a package. Specifically, a housing 56 made to surround PCB 40 abuts end clip 54 and PCB 40, as shown, to secure the monitor device for use in varied environments, and as a small package. Housing configurations are shown and described in greater detail below.

FIG. 3F shows another PCB 60 for use with a monitor device of the invention. A battery 62 couples to PCB 60, as shown, and a connecting element 64 completes the circuit between battery 62 and PCB 60 to power the monitor device. Preferably, element 64 is tensioned to help secure battery 62 to PCB 60. FIG. 3G shows PCB 60 and element 64 coupled together and without battery 62. A terminal 66 (similar to terminals 48) is also shown in FIG. 3G to contact with one side of battery 62.

FIG. 4 illustrates a preferred embodiment of the invention, not to scale, where packaging associated with a monitor device “powers” the device upon removal of the packaging. Specifically, in FIG. 4, one monitor device 70, with adhesive strips 72, is shown with a protective wrapper 74 and non-stick strips 76. One non-stick strip 76a has an extension 77 that electrically separates device 70 and a battery 78 so as to prevent electrical contact therebetween. Non-stick strip 76a is preferably thin, such as paper coated with non-stick material. Once strip 76a is removed by a user, connecting element 80 forces battery 78 to contact monitor device 70, thereby powering the device. In this way, battery power is conserved until monitor device 70 is used operationally. Element 80 can for example take the form of element 64, FIG. 3G. FIG. 4A shows monitor device 70 with wrapper 74 and non-stick strips 76 removed; as such, element 80 forces battery 78 to device 70 to make electrical contact therewith, powering device 70. Those skilled in the art should appreciate that changes can be made within the above description without departing from the scope of the invention, including a monitor device with a single non-stick strip (instead of two) that has an extension to decouple the battery from device 70 until the strip is removed. Alternatively, the wrapper can couple with the extension to provide the same feature; so that when the wrapper is removed, the monitor device is powered.

FIG. 5 shows a monitor device 82 formed within a label 84. Instead of adhesive strips, device 82 is disposed within label 84 for attachment, as above, to objects and persons. Label 84 has an adhesive 86 over one side, and preferably a non-stick strip 88 covering adhesive 86 until removed. For purposes of illustration, strip 88 is not shown in contact with adhesive 86, though in fact adhesive 86 is sandwiched in contact between strip 88 and label 84. Device 82 and label 84 provide an alternative to the monitor devices with adhesive strips described above, though with many of the advantages. FIG. 5A shows a front view of device 82, with adhesive 86 covering the one side of label 84, and with strip 88 shown transparently in covering adhesive 86 until removed.

FIG. 6 shows a monolithic monitor device 90 constructed according to the invention. A rigid outer housing 92 surrounds PCB 94 and internal elements 96 (e.g., elements 10-22, FIG. 1), which provide functionality for device 90. A magnetic element 98 couples with device 90 so that device 90 is easily attached to metal objects 100. Accordingly, device 90 is easily attached to, or removed from, object 100. Those skilled in the art should appreciate that alternative mechanical attachments are possible to couple device 90 to object 100, including a mechanical pin or clip.

The MMDs of the invention operates to detect movement “metrics.” These metrics include, for example, airtime, speed, power, impact, drop distance, jarring and spin; typically one

MMD detects one movement metric, though more than one metric can be simultaneously detected by a given MMD, if desired (potentially employing multiple detectors). The MMD detector is chosen to provide signals from which the processor can interpret and determine the desired metric. For example, to detect airtime, the detector is typically one of an accelerometer or piezoelectric strip that detects vibration of an object to which the MMD is attached. Furthermore, the MMD of the invention preferably monitors the desired metric until the metric passes some threshold, at which time that metric is tagged with time and date information, and stored or transmitted off-board. If the MMD operates within a single day, only time information is typically tagged to the metric.

By way of example, if the detector is an accelerometer and the MMD is designed to monitor “impact” (e.g., acceleration events that are less than about ½ second)—and yet impact data is not considered interesting unless the MMD experiences an impact exceeding 50 g’s—the preferred MMD used to accomplish this task would continuously monitor impact and tag only those impact events that exceed 50 g’s. The “event” in this example is thus a “50 g event.” Such an MMD is for example useful when attached to furniture, or a package, in monitoring shipments for rough treatment. The MMD might for example record a 50 g event associated with furniture shipped on Oct. 1, 2000, from a manufacturer in California, and delivered on Oct. 10, 2000 to a store in Massachusetts. If an event stored in MMD memory indicates that on Oct. 5, 2000, at 2:30 pm, the furniture was clearly dropped, responsibility for any damages can be assessed to the party responsible for the furniture at that time. Accuracy of the time tag information can be days, hours, minutes and even seconds, depending on desired resolution and other practicalities.

Accordingly, data from such an MMD is preferably stored in internal memory (e.g., memory 20, FIG. 1) until the data are retrieved by receiver 24. In the example above, the interrogation to read MMD data occurs at the end of travel of the MMD from point A to point B. Multiple events may in fact occur for an MMD during travel; and multiple events are usually stored. Alternatively, an MMD may communicate the event at the time of occurrence so long as a receiver 24 is nearby to capture the data. By way of example, if each FEDEX truck contained a receiver integrated with the truck, then any MMD contained with parcels in the truck can transmit events to the receiver at the occurrence of the event.

In another application, one or more monitor devices are attached to patients in a hospital, and one or more receivers are integrated with existing electronics at the hospital (e.g., with closed circuit television, phone systems, etc.). In operation, these devices are for example used to detect “events” that indicate useful information about the patients—information that should be known. If for example the monitor device has a Hall Effect detector that detects when the device is inverted, then a device attached to the collar bone (or clothing) of a patient would generate an “event” when the patient falls or lays down. An impact detector may also be used advantageously, to detect for example a 10 g event associated with a patient who may have fallen. Accordingly, monitor devices applied to patients in hospitals typically transmit event data at occurrence, so that in real time a receiver relays important medical information to appropriate personnel.

Movement devices of the invention can also transmit movement or other metrics at select intervals. If for example “impact” data is monitored by an MMD, then the MMD can transmit the maximum impact data for a selected interval—e.g., once per minute or once per five minutes, or other time interval. In this way, an MMD applied to a patient monitors

movement; and any change in movement patterns are detected in the appropriate time interval and relayed to the receiver. An MMD may thus be used to inform a hospital when a patient is awake or asleep: when asleep, the MMD transmits very low impact events; when awake, the MMD transmits relatively high impact events (e.g., indicating that the patient is walking around).

FIG. 7 shows one monitor device 120 constructed according to the invention. Similar to device 10" of FIG. 2 with regard to the adhesive bandage features of the device, device 120 has a detector in the form of a piezoelectric strip 122 disposed with the adhesive strip 124 (and, preferably, padding 121). Strip 124 has adhesive 125 such as described above so that device 120 is easily attached to a human, e.g., to human arm 130. In operation, as shown by schematic 130 of FIG. 7A, bending of strip 124 also bends piezoelectric strip 122, generating voltage spikes 123 detected by device processor 126. Device 120 may thus operate to detect the heart pulse of a person: the tiny physical perturbation of piezoelectric strip 122 caused by arterial pressure changes is detected and processed by device 120 as movement metric 127, which is then transmitted by port 129 to remote receiver(s) 132 as wireless data 133. The pulse data 127, over time, is usefully reconstructed for analytical purposes, e.g., as data 134 on display 136, and may indicate stress or other patient condition that should be known immediately. By way of example, an "event" determined by device 120 based on movement metric 127 can be the absence or variation of a pulse, perhaps indicating that the patient died or went into cardiac arrest. It is clear that if arm 130 moves, the voltage signal generated by piezoelectric detector 122 may swamp any signal from the patient's pulse; however, since pulse data is detected at approximately 50 to 250 times per second, the underlying signal can be recovered, particularly after arm 130 ceases movement. Device 120 can include an A/D converter and/or voltage-limiting device 121 to facilitate measurement of voltage signals 123 from piezoelectric strip detector 122. A battery 138 such as a Lithium coin cell can be used to power device 120.

Device 120 may alternatively detect patient movement to provide real time detection of movement of a person or of part of that person. For example, such a device 120 may be used to monitor movement of an infant (instead of arm 150) or other patient.

Note that the application of a monitor device 120 as described in FIG. 7 and FIG. 7A can be expanded to detect respiratory behavior of a patient. FIG. 7B shows a simplified schematic of one device 120' with a longer piezoelectric strip detector 122'. Detector 122' circumferentially extends, at least part way, around the chest 150 of a patient; and movement of chest 150 during breathing generates voltage variations (e.g., similar to variations 133, FIG. 7) in response to physical perturbations of detector 122'. Similar to pulse rate and pulse strength, therefore, device 120' detects respiratory rate and/or strength. Pulse rate is determined by signal frequencies associated with movement metric 127; and pulse strength is determined by magnitudes associated with movement metric 127. Note that strip detector 122' may be attached about chest 150 by one of several techniques, including by an adhesive strip (not shown) such as described above. A strap or elastic member 152 may be used to surround chest 150 to closely couple detector 122' to chest 150.

Devices such as device 120 or 120' have additional application such as for infant monitoring. Attaching such a device to the chest (instead of arm 150) of an infant to monitor respiration, pulse and/or movement provides a remote monitoring tool and may prevent death by warning the infant's

parents. A monitor device 10w, FIG. 2E, may alternatively be used in such an application. Specifically, if for example a monitor device of the invention is attached to chest 150 of a child, processor 126 searches for "events" in the form of the absence of pulse, respiration and/or movement data. The device may thus track pulse or respiratory rate to synch up to the approximate frequency of the rate. When the device detects an absence in the repetitive signals of the pulse or respiratory rate, the device sends a warning message to an alarm for the parents. A system suitable for application with such an application is discussed in more detail in FIGS. 55 and 56.

Data transmissions from a monitor device of the invention, to a receiver, typically occur in one of three forms: continuous transmissions, "event" transmissions, timed sequence transmissions, and interrogated transmissions. In continuous transmissions, a monitor device transmits detector signals (or possibly processed detector signals) in substantially real time from the monitor device to the receiver. Data reconstruction at the receiver, or at a computer arranged in network with, or in communication with, the receiver, then proceeds to analyze the data for desired characteristics. By way of example, by attaching multiple monitor devices to a person, all transmitting real-time data signals to the receiver, a reconstruction of that person's activity is determined.

Consider for example FIG. 8. In FIG. 8, a plurality of MMDs 150 are attached to person "A" and person "B". As shown, person A is engaged in karate training with person B. Data from MMDs 150 "stream" to a remote receiver, such as to the reconstruction computer and receiver 152 of FIG. 8A. Each MMD 150 preferably has a unique identifier so that receiver 152 can decode data from any given MMD 150. MMDs are placed on persons A, B at appropriate locations, e.g., on each foot and hand, head, knee, and chest; and receiver 152 associates data from each MMD 150 with the particular location. As data streams from MMD 150 to receiver 152, data is reconstructed such as shown in plots 154 and 156. Data plot 154 shows exemplary data from MMD 150a on the fist 160 of person A, and data plot 156 shows exemplary data from MMD 150b on the head 162 of person B. Each plot 154, 156 are shown in FIG. 8A as a function of time 164. Other data plots for other sensors 150 (e.g., for illustrative sensors 2, 3, 4) are not shown, for purposes of clarity.

Data plots 154, 156 have obvious advantages realized by use of the MMDs of the invention. For example, plot 154 illustrates several fist "strikes" 166 generated by person A on person B, and data plot 156 illustrates corresponding blows 168 to the head of person B. Data 154, 156 may for example be used in training, where person B learns to anticipate person A more effectively to soften or eliminate blows 168.

Data plots 154, 156 have further advantages for broadcast media; specifically, data 154, 156 may be simultaneously relayed to the Internet or television 170 to display impact speed and intensity for blows given or received by persons A, B, and in real time, to enhance the pleasure and understanding of the viewing audience (i.e., viewers of television, and users of the Internet). Moreover, MMDs of the invention remove some or all of the subjectivity of impact events: a blow to an opponent is no longer qualitative but quantitative. By way of example, the magnitude of strikes 166 and blows 168 are preferably provided in the data streamed from MMDs 150, indicating magnitude or force of the blow or strike. Data 154, 156 thus represents real time movement metric data, such as acceleration associated with body parts of persons A, B. Data 154, 156 may thereafter be analyzed, at receiver 152, to

determine “events”, such as when data **154**, **156** indicates an impact exceeding 50 g’s (or other appropriate or desired measure).

FIG. 8B illustrates a representative display on television **157**, including appropriate event “data” **159** generated by an MMD system of the invention. Data **159** can for example derive from receiver **152**, which communicates the appropriate event data **159** to the broadcaster for TV **157**. Such event data **159** can include magnitude or power spectral density of acceleration data generated by MMDs **150**. Data **159** is preferably displayed in an easy to understand format, such as through bar graphs **161**, each impact detected by one or more MMDs **150** (in certain instances, combining one or more MMDs as data **159** can be useful). Bar graphs **161** preferably indicate magnitude of the impact shown by data **159** by peak bar graph element **161a** on TV **157**.

Those skilled in the art should appreciate that any number of MMDs **150** may be used for applications such as shown in FIG. 8. In boxing, for example, it may be appropriate to attach one MMD **150** per fist. One useful MMD in this application is for example monitor device **10** of FIGS. 2, 2D. That is, such a device is easily attached to the boxer’s fist **158a** or wrist **158b** and, if desired, prior to applying gloves and wrapping **158c**, as shown in FIG. 8C. The device can alternatively be placed with wrapping **158c**—making the device practically unnoticeable to the boxer. Preferably, MMD **10** of FIG. 8C includes an accelerometer (as the MMD detector) oriented with a sensitivity axis **158d** as shown; axis **158d** being substantially aligned with the strike axis **158e** of fist **158a**. Data from the MMD wirelessly transmits through the gloves and wrapping to receiver **152**. Alternatives are also suitable, for example applying the MMDs to the boxer’s wrapping or glove. An MMD can also be integrated within the boxing glove, if desired. In the event that the detector of the MMD is an accelerometer, then the sensitive axis of the accelerometer is preferably arranged along a strike axis of the boxer.

Data acquired from MMDs in sports like boxing and karate are also preferably collated and analyzed for statistical purposes. Data **154**, **156** can be analyzed for statistical detail such as: impacts per minute; average strike force per boxer; average punch power received to the head; average body blow power; and peak striking impact. Rotational information may also be derived with the appropriate detector, including typical wrist rotation at impact, a movement metric that may be determined with a spin sensor.

Other than continuous transmissions, such as illustrated in FIG. 8, data from monitor devices of the invention also occur via one of “event” transmissions, timed sequence transmissions, and/or interrogated transmissions. FIG. 1 illustrates how interrogated transmissions preferably function: e.g., receiver **24** interrogates device **10** to obtain metrics. Event transmissions according to preferred embodiments are illustrated as a flow chart **170** of FIG. 9. Timed sequence transmissions according to preferred embodiments are also illustrated within flow chart **170** of FIG. 9. In FIG. 9, flow chart **170** begins in step **172** by powering the monitor device—either by inserting the battery, turning the device on, or removing a wrapper (or by similar mechanism) to power the device at the appropriate time. Once powered, the monitor device monitors detector signals, in step **174**, for metrics such as movement, temperature and/or g’s. By way of example, to measure airtime or impact, the device processor monitors an accelerometer for the movement metric of acceleration. Step **176** assesses the metric for “events” such as airtime or “impact” (or, for example, for an event such as when temperature exceeds a certain threshold, or an event such as when humidity decreases below a certain threshold). Typically,

though not required, all events are not reported, stored or transmitted. Rather, as shown in step **178**, events that meet or pass a pre-selected threshold are reported. By way of example, is an airtime event greater than ½ second—a magnitude deemed interesting by snowboarders? If so, such an event may be reported. If not, an airtime event of less than ½ second is not reported, and decision “No” from **178** is taken. If the event exceeds some threshold, decision tree “Yes” from **178** sends the event data to the communications port (e.g., communications port **26**, FIG. 1) in step **180**. The communications port then transmits the event to a receiver (e.g., receiver **24**, FIG. 1) in step **182**. As an alternative, decision tree Yes₂ sends the event data to memory such that it is stored for later transmission, in step **184**. The Yes₂ decision tree is used for example when a receiver is not presently available (e.g., when no receiving device is available to listen to and capture data transmitted from the monitor device). Eventually, however, event data is transmitted off-board, in step **186**, such as when memory is full (a receiver should be available to capture the event data before memory becomes full) or when the monitor device is scheduled to transmit the data at a pre-selected time interval (i.e., a timed sequence transmission). For example, event data stored in memory may be transmitted off board every five minutes or every hour; data captured within that time interval is preferably stored in memory until transmission at steps **180** and **182**.

Note that timed sequence transmission of event data approaches “continuous” transmission of movement metric data for smaller and smaller timed sequence transmissions. For example, if data from the monitor device is communicated off-board each second (or less, such as each one tenth of a second), then that data becomes more and more similar to continuously transmitted data from the detector. Indeed, if sampling of the detector occurs at X Hz, and timed transmissions also occur at X Hz, then “continuous” or “timed sequence” data may be substantially identical. Timed sequence or event data, therefore, provides for the opportunity to process the detector signals, between transmissions, to derive useful events or to weed out noise or useless information.

FIG. 10 shows a sensor-dispensing canister **200** constructed according to the invention. Canister **200** is shown containing a plurality of sensor **202**. A lid **204** may be coupled with canister **200** to enclose sensors **202** within canister **200**, as desired. Each of sensors **202** can for example be a monitor device such as described above; however canister **200** can be used for other battery-powered sensors. Although canister **200** is shown with two-dozen sensors **202**, a larger or smaller number of sensors may be contained within its cavity **200a**. As described in more detail below, canister **200** preferably contains one or both of (a) canister electronics and (b) a base assembly. Lid **204** preferably functions as a switch, to power the canister electronics when lid **204** is open, and to cause canister electronics to sleep when lid **204** is closed.

FIG. 10A shows sensors **202** with base assembly **206**, and, for purposes of clarity, without the rest of canister **200**. Each of sensors **202** is shown with a monitor device **202a** and an adhesive strip **202b**; however, canister **200** may be used with other sensors (i.e., sensors that are not MMDs or EMDs) without departing from the scope of the invention. FIG. 10B illustrates one sensor **202** in the preferred embodiment, and also illustrates a Mylar battery insulator strip **208** that keeps the sensor battery from touching its contact or terminal (not shown) within monitor device **202a**. Strip **208** can for example serve as the “non-stick” strip or extension **77** discussed above in connection with FIG. 4. Strip **208** preferably couples to base assembly **206** such as shown in FIG. 10C.

Accordingly, when a user removes a sensor **202** from canister **200**, strip **208** remains with base assembly **206**—and is no longer in contact with sensor **202**—and the monitor device's internal battery powers the device for use with its intended application, as shown in FIG. **10D**.

In one preferred embodiment of the invention, a canister **200'** (e.g., similar to canister **200** but with internal electronics) has its own battery **210**, micro-controller **212**, sensor time tag interface **214a**, and real time clock **216** (collectively the “canister electronics”), as shown in FIG. **10E**. With such an embodiment, a sensor **202'** for use with canister **200'** has a mating time tag interface **214b**. In addition to time tag interface **214b**, sensor **202'** has a clock **218**, processor **220**, battery **222**, detector **224** and communications port **226**. In operation, sensor **202'** is generally not powered by battery **222** until removed from canister **200'**, as described above. Accordingly, real time clock information (e.g., the exact date and time) cannot be maintained within sensor **202'** while un-powered (i.e., so long as insulator strip **208'** prevents battery **222** from powering sensor **202'**) since clock **218** and other electronics require power to operate. However, in FIG. **10E**, the advantage provided by the canister electronics is that time tag information from real time clock **216** is imported to sensor **202'** through interfaces **214a**, **214b** after battery **222** powers device **202a'** but before interfaces **214a**, **214b** disconnect so that sensor **202'** can be used operationally. As such, in the preferred embodiment shown in FIG. **10F**, interface **214a** takes the form of flex cable **230** that remains attached between canister electronics and device **202a'** until flex cable **230** extends to its full length, whereinafter sensor **202'** disconnects from cable **230**. Time tag relay **214b** of device **202a'**, FIG. **10F**, thus takes the form of a plug (not shown) to connect and alternatively disconnect with flex cable **230**. In FIG. **10F**, canister electronics (e.g., elements **210**, **212**, **216**) are disposed within base assembly **206'** and therefore flex cable **230** appears to extend only to base assembly **206'** when in fact cable **230** extends to canister electronics disposed therein. When a user removes sensor **202'** from canister **200'**, device **202a'** is powered when strip **208'**, held with base assembly **206'** (or electronics therein) disconnects from sensor **202'**; and at that time clock **218** is enabled to track real time. Before flex cable **230** disconnects from sensor **202'**, time and/or data information is communicated between interfaces **214a**, **214b** to provide the “real” time to sensor **202'** as provided by clock **216**. Once real time is provided to sensor **202'**, clock **218** maintains and tracks advancing time so that sensor **202'** can tag events with time and/or date information, as described herein.

One advantage of sensor canister **200'** is that once used, it may be reused by installing additional sensors within the cavity. In addition, one canister can carry multiple monitor devices, such as 100 MMDs that each respond to an event of “10 g's.” In another example, another canister carries 200 MMDs that respond to an event of “100 g's.” A canister of MMDs can be in any suitable number that meets a given application; typically however sensors within the canister of the invention are packaged together in groups of 50, 100, 150, 200, 250, 500 or 1000. A variety pack of MMDs can also be packaged within a canister, such as a canister containing ten 5 g MMDs, ten 10 g MMDs, ten 15 g MMDs, ten 20 g MMDs, ten 25 g MMDs, ten 30 g MMDs, ten 35 g MMDs, ten 40 g MMDs, ten 45 g MMDs, and ten 50 g MMDs. Another variety package can for example include groups of MMDs spaced at 10 g intervals. EMDs can also be packaged in variety configurations within canisters **200**, **200'**.

Canisters **200**, **200'** can also function to dispense one or a plurality of receivers. Specifically, each of elements **202** of

FIG. **10** may alternatively be a receiver such as receiver **24** of FIG. **1**. In this way, a plurality of receivers may be dispensed and powered as described above. FIG. **10G** shows one receiver **231** constructed according to the invention. Receiver **231** has a communications port **232**, battery **233** and indicator **234**. Receiver **231** can further include processor **235**, memory **236** and clock **237**, as a matter of design choice and convenience such as to implement functionality described in connection with FIGS. **10G**, **10H**. Receiver **231** can for example be dispensed as one of a plurality of receivers—as an element **202**, **202'** dispensed from canisters **200**, **200'** above. In operation, battery **233** powers receiver **231** and receiver **231** receives inputs in the form of wireless communications (e.g., in accord with the teachings herein, wireless communications can include known transmission protocols such as radio-frequency communication, infrared communication and inductive magnetic communication) from a sensor such as an MMD. Communications port **232** serves to capture the wireless communications data such that indicator **234** re-communicates appropriate “event” data to a person or machine external to receiver **231**. Specifically, in one embodiment, receiver **231** operates to relay very simple information regarding event data from a movement device. If for example an MMD sends event data to receiver **231** that reported the MMD experienced an airtime event of five seconds, and it was important that this information was known immediately, then receiver **231** is programmed (e.g., through processor **235**) to indicate the occurrence of that five-second airtime event through indicator **234**. Such data may also be stored in memory **236**, if desired, until a person or machine requiring the data acquires it through indicator **234**. By way of another example, receiver **231** can take the form of a ski lift ticket **238** shown in FIG. **10H**. Lift ticket **238** is thus a receiver with an indicator **239** in the form of a LED. Lift ticket **238** is preferably made like other lift tickets, and may for example include bar code **240**, indicating that a person purchased the ticket for a particular day, and ticket connecting wire **241** to couple ticket **238** to clothing. Lift ticket **238** may beneficially be used with an MMD having a speed sensor detector; and that MMD reports (by wireless communication) speed “events” that exceed a certain threshold, e.g., 40 mph. Lift ticket receiver **238** captures that event data and reports it through indicator **239**. A person wearing lift ticket receiver **238** with a speed sensing MMD will thus be immediately known by the ski lift area that the person skis recklessly, as a lift operator can view the speeding violation indicator LED **239**. Alternatively, indicator **239** is itself a wireless relay that communicates with a third receiver such as a ski ticket reader currently used to review bar code **240**. Lift ticket receiver **238** can further include circuitry as in monitor device **10** of FIG. **1** so that it responds to wireless requests for appropriate “event data,” such as speed violation data. As such, indicator **239** may take the form of a transmitter relaying requested event data to the third receiver, for example. Event data may be stored in memory **236** until requested by the third receiver interrogating lift ticket receiver **238**.

Preferably, canisters **200'** imparts a unique ID to the dispensed electronics—e.g., to each sensor or receiver taken from canister **200'**—for security reasons. More particularly, in addition to communicating a current date and time to the dispensed electronics, canister **200'** also preferably imparts a unique ID code which is used in subsequent interrogations of the dispensed electronics to obtain data therein. Therefore, data within a monitor device, for example, cannot be tampered with without the appropriate access code; and that code is only known by the party controlling canister **200'** and dispensing the electronics.

FIG. 10G and FIG. 10H illustrate certain advantages of the invention. First, receivers in the form of lift tickets **238** may be packaged and dispensed to power the lift ticket upon use. Lift tickets are dispensed by the thousands and are sometimes stored for months prior to use. Accordingly, battery power may be conserved until dispensed so that internal electronics function when used by a skier for the day. Further, tickets **238** monitor a user's performance behavior during the day to look for offending events: e.g., exceeding the ski resort speed limit of 35 mph; exceeding the jump limit of two seconds; or performing an overhead flip on the premises. Whatever the monitor device is set to measure and transmit as "events" may be visually displayed (e.g., a LED or LCD) at indicator **234** or re-transmitted to read the offending information. Receiver **231** may incorporate transponders as discussed above to facilitate the indicator functionality, i.e., to relay data as appropriate.

Batteries used in the above MMDs and devices like the lift ticket can benefit by using paper-like batteries such as set forth in U.S. Pat. No. 5,897,522, incorporated herein by reference. Such batteries provide flexibility in several of the monitor devices described herein. Powering such batteries when dispensing a sensor or receiver still provides advantages to conserve battery power until the sensor or receiver is used. A device battery **18** of FIG. 1 can for example be a paper-like battery or coin cell.

FIG. 10I shows yet another sensor **231'** constructed according to the invention. Like receiver **231**, sensor **231'** preferably conforms to a shape of a license ticket, e.g., a ski lift ticket. However sensor **231'** does not couple to a separate monitor device; rather, sensor **231'** is a stand-alone device that serves to monitor and gauge speeding activity. Like other sensors of the invention, an "event" is generated and communicated off-board (i.e., to a person or external electronics) when sensor **231'** exceeds a pre-assigned value. Typically, that value is a speed limit associated with the authority issuing sensor **231'** (e.g., a resort that issues a ski lift ticket). Sensor **231'** is preferably dispensed through one of the "power on" techniques described herein, such as by dispensing sensor **231'** from a canister **200**, **200'**. Typically, when sensor **231'** detects a speeding event, (a) data is communicated off-board (e.g., sensor **231'** generates a wireless signal of the speed violation), and/or (b) a visual indicator is generated to inform the authority (e.g., via a ski lift operator of the ski lift area) of the violation. In case (a), indicator **234'** may for example be a communications port such as port **16**, FIG. 1; in case (b), indicator **234'** may for example be an LED or other visual indicator that one can visually detect to learn of the speeding violation. Indicator **234'** of one embodiment is a simple LED that turns black (ON), or alternatively white (OFF), after the occurrence of a speeding event. A quick visual review of sensor **231'** thus informs the resort of the speeding violation.

Sensor **231'** also has a battery **233'** that is preferably powered when sensor **231'** is dispensed to a user (e.g., to a snowboarder at a resort). Optionally, position locator **243** is included with sensor **231'** to track earth location of sensor **231'**; processor **235'** thereafter determines speed based upon movement between locations over a time period (e.g., distance between a first location and a second location, divided by the time differential defined by arriving at the second location after leaving the first location, provides speed). Clock **237'** provides timing to sensor **231'**. Optionally, memory **236'** serves one of several functions as a matter of design choice. Data gathered by sensor **231'** may be stored in memory **236'**; such data may be communicated off-board during subsequent interrogations. As discussed above, data may also be communicated off-board at the occurrence of a speeding "event." As

an alternative, indicator **234'** may be a transponder RFID tag to be read by a ticket card reader. In one embodiment, on slope transmitters irradiate sensor **231'** with a signal that reflects to determine Doppler speed; that speed is imparted to sensor memory **236'** and reported to the resort.

Preferably, sensor **231'** operates in "low power" mode. Position locator **243** in one preferred embodiment is a GPS receiver. GPS receiver and processor **243**, **235'** for example collectively operate to make timed measurements of earth location so as to coarsely measure speed. For example, by measuring earth location each five seconds, and by dividing the distance traveled in those five seconds by five seconds, a coarse measure of speed is determined. Other timed measurements could be made as a matter of design choice, e.g., $\frac{1}{2}$, 1, 15, 20, 25, 30 or 60 seconds. By taking fewer measurements, and by reducing processing, battery power is conserved over the course of a day, as it is preferable that the ticket determines speeding violations for at least a full day, in Winter. Finely determining speed at about one-second intervals is useful in the preferred embodiment of the invention.

Memory **236'** may further define location information relative to one or more "zones" at a resort, such that speed may be assigned to each zone. In this manner, for example, a resort can specify that ski run "X" (of zone "A") has a speed limit of 35 mph, while ski run "Y" (of zone "B") has a speed limit of 30 mph. Speeding violations within any of zones A or B are then communicated to the resort. The advantage of this feature of the invention is that certain slopes or mountain areas permit higher speeds, and yet other slopes (e.g., a tree skiing area) do not support higher speeds. The resort may for example specify speed limits according to terrain. GPS receiver **243** determines earth position—which processor **235'** determines is within a particular zone—and speed violations are then determined relative to the speed limit within the particular zone, providing a more flexible system for the ski resort.

Position locator **243** of another embodiment is an altimeter, preferably including a solid-state pressure sensor. Altimeter **243** of one embodiment provides gross position information such as the maximum and minimum altitude on a ski mountain. For a particular resort, maximum and minimum altitude approximately correspond to a distance of "Z" meters, the distance needed to traverse between the minimum and maximum altitude. Processor **235'** then determines speed based upon dividing Z by the time between determining the minimum and maximum altitudes. Fractional speeds may also be determined. If for example a particular skier traverses between a maximum altitude and half-way between the minimum and maximum altitudes, then processor **235'** determines speed based upon dividing Z/2 by the time between determining (a) the maximum altitude and (b) the midpoint between the minimum and maximum altitudes.

As discussed above, one MMD of the invention includes an airtime sensor. FIG. 11 and FIG. 12 collectively illustrate the preferred embodiment for determining and detecting airtime in accord with the invention. An MMD configured to measure airtime preferably uses an accelerometer as the detector; and FIG. 11 depicts electrical and process steps **250** for processing acceleration signals to determine an "airtime" event. FIG. 12 illustrates state machine logic **280** used in reporting this airtime. By way of example, FIG. 12 shows that motion is preferably determined prior to determining airtime, as airtime is meaningful in certain applications (e.g., wakeboarding) when the vehicle (e.g., the wakeboard) is moving and non-stationary.

More particularly, FIG. 11 depicts discrete-time signal processing steps of an airtime detection algorithm. Acceleration

data 252 derive from a detector in the form of an accelerometer. Two pseudo-power level signals 266a, 272a are produced from data 252 by differentiating (step 254), rectifying (step 256), and then filtering through respective low-pass filters at steps 266 or 272. More particularly, a difference signal of data 252 is taken at step 254. The difference signal for example operates to efficiently filter data 252. The difference signal is next rectified, preferably, at step 256. Optionally, a limit filter serves to limit rectified data at step 258. Rectified, limited data may be rescaled, if desired, at step 260. The limiting and rescaling steps 258, 260 help reduce quantization effects on the resolution of power signals 266a, 272a. Filtering at steps 266, 272 incorporate different associated time constants, and feed binary hysteresis functions with different trigger levels, to produce "power" signals 266a, 272a.

More particularly, data from step 260 is bifurcated along fast-signal path 262 and slow-signal path 264, as shown. In path 262, a low pass filter operation (here shown as a one pole, 20 Hz low pass filter) first occurs at step 266 to produce power signal 266a. Two comparators compare power signal 266a to thresholds, at step 268, to generate two signals 270 used to identify possible takeoffs and landings for an airtime event. In path 264, a low pass filter operation (here shown as a one pole 2 Hz low pass filter) first occurs at step 272 to produce power signal 272a. Three comparators compare power signal 272a to thresholds, at step 274, to generate three "confidence" signals 276 used to assess confidence of takeoffs and landings for an airtime event. Finally, a state machine 280, described in more detail in FIG. 12, evaluates signals 270, 276 to generate airtime events 278.

Those skilled in the art should appreciate that the airtime detection scheme of FIG. 11 also may be used for other detectors, such as those in the form of piezoelectric strips and microphones, without departing from the scope of the invention.

FIG. 12 schematically shows state machine logic 280 used to report and identify airtime events, in accord with the invention. State machine 280 includes several processes, including determining motion 282, determining potential takeoffs 284 (e.g., of the type determined along path 262, FIG. 11), determining takeoff confirmations 286 (e.g., of the type determined along path 264, FIG. 11), determining potential landings 288 (e.g., of the type determined along path 262, FIG. 11), and determining landing confirmations 290 (e.g., of the type determined along path 264, FIG. 11). Logic flow between processes 282, 284, 286, 288, 290 occurs as illustrated and annotated according to the preferred embodiment of the invention.

In summary, the relative fast signal from fast-signal path 262, FIG. 11, isolates potential takeoffs and potential landings from data 252 with timing accuracy (defined by filter 266) that meets airtime accuracy specifications, e.g., $\frac{1}{100}^{th}$ of a second. The drawback of detections along path 262 is that it may react to accelerometer signal fluctuations that do not represent real events, which may occur with a ski click in the middle of an airtime jump by a skier. This problem is solved by confirming potential takeoffs and landings with confirmation takeoffs and landings triggered by a slower signal, i.e., along path 264. The slower signal 272a is thus used to confirm landings and takeoffs, but is not used for timing because it does not have sufficient time resolution.

An accelerometer signal described in FIG. 11 and FIG. 12 is preferably sensitive to the vertical axis (i.e., the axis perpendicular to the direction of motion, e.g., typically the direction of forward velocity, such as the direction down a hill for a snowboarder) to produce a raw acceleration signal (i.e., data

252, FIG. 11) for processing. Other accelerometer orientations can also be used effectively. The raw acceleration signal may for example be sampled at high frequencies (e.g., 4800 Hz) and then acted upon by the algorithm of FIG. 11. With a stream of accelerometer data, the algorithm produces an output stream of time-tagged airtime events.

FIG. 13 graphically shows representative accelerometer data 300 captured by a device of the invention and covering an airtime event 302. Event 302 occurs between takeoff 304 and landing 306, both determined through the algorithm of FIG. 11. Data representing power signals 266a and 272a are also shown. A ski click 310 illustrating the importance of signals 266a, 272a shows how the invention prevents identification of ski click 310 as a landing or second takeoff.

Data transmission from a sensor (e.g., an MMD) to a display unit (e.g., a receiver) is generally at least 99.9% reliable. In the case of one-way communication, a redundant transmission protocol is preferably used to cover for lost data transmissions. Communications are also preferably optimized so as to reduce battery consumption. One way to reduce battery consumption is to synchronize transmission with reception. The "transmission period" (the period between one transmission and the next), the size of the storage buffer in sensor memory, and the number of times data is repeated (defining a maximum age of an event) are adjustable to achieve battery consumption goals.

A state diagram for transmission protocols between one sensor and display unit, utilizing one-way transmission, is shown in FIG. 14 and FIG. 14A. FIG. 14 and FIG. 14A specifically show the operational state transitions for the sensor (chart 273) and display unit (chart 274) with respect to transmission protocols, in one embodiment of the invention. The numerical times provided in FIG. 14 are illustrative, without limitation, and may be adjusted to optimize performance. As those skilled in the art should appreciate, alternative protocols may be used in accord with the invention between sensors and receivers. With reference to FIG. 14 and FIG. 14A, the display unit is generally in a low power mode unless receiving data, to conserve power in the display unit. To accomplish this, transmissions between the sensor and display unit are synchronized such that the display unit knows when the sensor can next transmit. When the sensor has no data to transmit, there preferably is no transmission; however, synchronization is still maintained by short transmissions. Synchronization need not be performed at each transmission period, but preferably at a suitably spaced multiple of the transmission period. The period between synchronization-only transmissions is then determined by the amount of clock drift between the display unit and the sensor unit. The sync-only transmission may include the power up sequence and the sync byte, such that the display unit maintains sync with sensor transmissions. The transmission period is preferably selectable by software for both the sensor and the display unit.

By way of example, one sensor unit is monitor device 10 of FIG. 1, and one display unit is receiver 24 of FIG. 1. When the sensor and receiver function as a pair, the sensor unit preferably has an identification (ID) number communicated to the display unit in transmission so that the display unit only decodes data from one particular sensor.

Preferably, the display unit determines the sync pattern for sensor transmissions by active listening until receipt of a synchronization or data transmission with the matching sensor ID. Once a valid transmission from the matching sensor is received, the display unit calculates the time of the next possible transmission and controls the display unit accordingly. When the sensor is an MMD used to determine airtime, and the sensor does not necessarily have a real time clock;

data sent to the display unit includes airtime values with time information as to when the airtime occurred. As this sensor does not necessarily maintain a real time clock, the time information sent from the sensor is relative to the packet transmission time. Preferably, the display unit, which has a real time clock, will convert the relative time into an absolute time such that airtime as an event is tagged with appropriate time and/or date information.

The amount of data communicated between the sensor and display unit varies. By way of example, for typical skier and snowboarder operation, an airtime event covering the 0-5 second range with a resolution of $1/100^{th}$ second is generally adequate. The coding of such airtime events can use nine data bits. Ten bits allow for measurement of up to approximately ten seconds, if desired. For an age, where the resolution of age is one second (i.e., a time stamp resolution) and the maximum age of a repeat transmission is fifteen seconds, four bits are used. Data transmission also typically has overhead, such as startup time, synchronization byte, sensor ID used to verify correct sensor reception, a product identifier to allow backwards compatibility in future receivers, a count of the number of data items in the packet, and, following the actual data, a checksum to gain confidence in the received data. This overhead is approximately six bytes in length. To reduce the effect of overhead, stored data in the sensor is preferably sent in one message. An airtime event for example can be stored in the sensor until transmitted with the desired redundancy, after which it is typically discarded. Thus, the number of airtime events included in a transmission depends upon the number of items still in the sensor's buffer (e.g., in memory 20, FIG. 1). When the buffer is empty, there is, generally, no data transmission.

A typical data transmission can for example include: <P/up> <Sync> <Sensor ID> <Product ID> <Count> [<Age> <Airtime>] <Checksum>. <P/up> is the power-up time for the transmitter. A character may be transmitted during power up to aid the transmitter startup, and help the receiver start to synchronize on the signal. The <Sync> character is sent so that the receiver can recognize the start of a new message. <Sensor ID> defines each sensor with a unique ID number such that the display unit can selectively use data from a matching sensor. <Product ID> defines each sensor with a product ID to allow for backward compatibility in future receivers. <Count> defines how many age/airtime values are included in a message. The <Age> field provides the age of an associated airtime value, which may be used by the display unit to identify when an airtime is retransmitted. <Airtime> is the actual airtime value. <Checksum> provides verification that the data was received correctly.

A sensor's buffer length should accommodate the maximum number of airtime jumps for the duration of retransmissions. By way of example, transmissions can be restricted so that no more than one jump every three seconds is recognized; and retransmissions should generally finish within a selected time interval (e.g., six seconds). Therefore, this exemplary sensor need only store two airtime events at any one time. The buffer length is preferably configurable, and can for example be set to hold four or more airtime events.

Transmission electronics within the sensor and display units may use a UART, meaning that data is defined in byte-sized quantities. As those skilled in the art understand, alternative transmission protocols can utilize bit level resolution to further reduce transmission length.

By way of example, consider an airtime event of 1.72 seconds, occurring 2.1 seconds before start of transmission. In accord with FIG. 14 and FIG. 14A, the transmitted data would be as follows:

```
<P/up> <Sync> <Sensor ID> <Product ID> <Count>
[<Age> <Airtime>] <Checksum> <0xAA> <0xAD>
<0x12> <0x01> <0x01> <0x02> <0x158> <0x21>
```

Assuming that the age and airtime data are combined into two bytes, and that <P/up> is one byte in length, the entire packet is eight bytes in length. At a transmission speed of 1200 baud, a typical transmission speed between a sensor and receiver, the eight bytes takes 67 ms to transmit. Assuming sequential transmission periods of 500 ms, the transmission duty cycle is 13.4% for a single jump.

Those skilled in the art should appreciate that alternatives from the above-described protocols may be made without departing from the scope of the invention. In one alternative, pseudo random transmissions are used between a sensor and receiver. If for example two sensors are together, and transmitting, the transmissions may interfere with one another if both transmissions synchronously overlap. Therefore, in situations like this, a pseudo random transmission interval may be used, and preferably randomized by the unique sensor identification number <Sensor ID>. If both the display unit and the sensor follow the same sequence, they can remain in complete sync. Accordingly, a collision of one transmission (by two adjacent sensors) will likely not occur on the next transmission. In another alternative, it may also be beneficial for the receiver to define a bit pattern for the <Sync> byte that does not occur anywhere else in the transmitted data, such as used, for example, with the HDLC bit stuffing protocol. In another alternative, it may be beneficial to use an error correction protocol, instead of retransmissions, to reduce overall data throughput. In still another alternative, a more elaborate checksum is used to reduce the risk of processing invalid data.

In still another alternative, a "Hamming Code" may be used in the transmission protocol. Hamming codes are typically used with continuous streams of data, such as for a CD player, or for the system described in connection with FIG. 8; however they are not generally used with event or timed sequence transmissions described in connection with FIG. 14. Nevertheless, Hamming codes may make the data paths more robust. The wireless receiver in the display unit may take a finite time in start-up before it can receive each message. Since a further goal of the transmission protocol is generally to reduce the overall number of transmissions from the sensor, it may be beneficial to add additional data to the transmission and send it fewer times rather than to retransmit data several times. For example, rather than sending all buffered airtime values with each transmission, two data items can be sent, together with a count of airtimes in the sensor buffer, and a sum of the airtimes. If the display unit misses one airtime (e.g., determined by the count value), it can use the sum value received and the summation of the airtimes it has previously received to determine the missing airtime. A similar scheme can be used for age values so as to determine the time of the missing airtime.

The display unit receiver is typically in the physical form of a watch, pager, cell phone or PDA; and, further, receivers also typically have corresponding functionality. By way of example, one receiver is a cell phone that additionally functions as a receiver to read and interpret data from an MMD. Furthermore, a display unit is preferably capable of receiving and displaying more than one movement metric. As such, data packets described above preferably include the additional metric data, e.g., containing both impact and airtime event data. Display units of the invention preferably have versatile attachment options, such as to facilitate attachment to a wrist (e.g., via a watch or Velcro strap for over clothing), a neck (e.g., via a necklace), or body (e.g., by a strap or belt).

35

Sensors such as the monitor devices described above, and corresponding display unit receivers, preferably have certain characteristics, and such as to accommodate extreme temperature, vibration and shock environments. One representative sensor and receiver used to determine airtime in action sports can for example have the following non-limiting characteristics: sensor attaches to a flat surface (e.g., to snowboard, ski, wakeboard); sensor stays attached during normal aggressive use; display unit attachable to outside of clothing or gear; waterproof; display unit battery life three months or more; sensor battery life one week or more of continuous use; on/off functionality by switch or automatic operation; characters displayed at data unit visible from a minimum of eighteen inches; minimum data comprehension time for data minimum of 0.5 second; last airtime data accessible with no physical interaction; one second maximum time delay for display of airtime data after jump; displayed data readable in sunlight; displayed data includes time and/or date information of airtime; user selection of accumulated airtime; display unit provides real time information; display unit operable with a maximum of two buttons; physical survivability for five foot drop onto concrete; scratch and stomp resistant; no sharp edges; minimum data precision $\frac{1}{30}^{th}$ second; minimum data accuracy $\frac{1}{15}^{th}$ second; minimum data resolution $\frac{1}{100}^{th}$ second; minimum data reliability $\frac{99}{1000}$ messages received; algorithm performance less than one percent false positive and less than two percent false negative indications per day; and temperature range minimum of -10° C. -60° C.

Those skilled in the art should appreciate that the above description of communication protocols of "airtime" between sensor and receiver can be applied to monitor devices sensing other metrics, e.g., temperature, without departing from the scope of the invention.

By way of example, FIG. 15 shows functional blocks 320, 322, 324, 326, 328, 330 of one sensor of the invention. The sensor's algorithm analyzes signals from an internal detector and determines an event such as airtime. This event information is stored and made ready for transmission to the display unit. FIG. 16 shows functional blocks 332, 334, 336, 338, 340, 342, 344 of one display unit of the invention. Transmission protocols between functional blocks 326, 332 ensure that data is received reliably. The internal detector of the sensor of FIG. 15 for example is an accelerometer oriented to measure acceleration in the Z direction (i.e., perpendicular to the X, Y plane of motion). Signals generated from the detector are sampled at a suitable frequency, at block 320, and then processed by an event algorithm, at block 322. The algorithm applies filters and control logic to determine event, e.g., the takeoff and landing times for airtime events. Event data such as airtime is passed to the data storage at block 324. Data is stored to meet transmission protocol requirements; preferably, data is stored in a cyclic buffer, and once all data transmissions are performed, the data is discarded. Transmission can be performed by a UART, at block 326, where data content is arranged to provide sufficient robustness. Power control at block 328 monitors signal activity level to determine if the sensor should be in 'operating' mode, or in 'sleep' mode. Sleep mode preserves the battery to obtain a greater operative life. While in sleep mode, the processor wakes periodically to check for activity. Timing and control at block 330 maintains timing and scheduling of software components.

With regard to FIG. 16, receiver message handler at block 332 performs data reconstruction and duplication removal from transmission protocols. Resulting data items are sent to data management and storage at block 334. Stored data ensures that the user can select desired information for display,

36

at block 336. The display driver preferably performs additional data processing, such as in displaying Total Lists (e.g., values representing cumulative of a metric), Best lists (e.g., values representing the best or highest or lowest metric), and Current Lists (e.g., values representing latest metric). These lists are filled automatically, but may be cleared or reset by the user. Buttons typically control the display unit, at block 338. Button inputs by users are scanned for user input, with corresponding information passed to the user interface/menu control block 344. The display driver of block 336 selects and formats data for display, and sends it to the receiver's display device (e.g., an LCD). This information may also include menu items to allow the user to select, or perform functions on, stored data, or to select different operation modes. A real time clock of block 340 maintains the current time and date even when the display is inactive. The time and date is used to time stamp event data (e.g., an airtime event). Timing and control at block 342 maintains timing and scheduling of various software components. User interface at block 344 accepts input from the button interface, to select data items for display. A user preferably can scroll through menu items, or data lists, as desired.

FIG. 17 shows one housing suitable for use with a monitor device (e.g., an MMD) of the invention. The housing is shown with three pieces: a top element 362, a bottom element 364, and an o-ring 366. As shown in FIG. 18, elements 362, 364 form a watertight seal with o-ring 366 to form an internal cavity that contains and protects sensor electronics 368 (e.g., detector 12, processor 14, communications port 16 of FIG. 1) disposed within the cavity. Batteries 370 power sensor electronics 368, such as described in connection with FIGS. 3F, 3G. In combination, the housing is preferably small, with volume dimensions less than about 35 mm $\times$ 15 mm $\times$ 15 mm. Generally, one dimension of the housing is longer than the other dimensions, as illustrated; though this is not required.

FIG. 19 shows an alternative housing 372 suitable for use with a sensor (e.g., an MMD) of the invention. Housing 372 is shown with three pieces: a top element 374, a bottom element 376, and an o-ring 378. As above, elements 374, 376 form a watertight seal with o-ring 378 to form an internal cavity that contains and protects sensor electronics disposed therein. FIG. 19 also shows housing 372 coupled to sensor bracket 380. A mating screw 382 passes through housing 372, as shown, and through sensor bracket 380 for attachment to a vehicle attachment bracket. FIG. 20 illustrates one vehicle attachment bracket 390; FIG. 21 illustrates another vehicle attachment bracket 400. Mating screw 382 preferably has a large head 382a so that human fingers can efficiently manipulate screw 382, thereby attaching and detaching housing 372 from the vehicle attachment bracket, and, thereby, from the underlying vehicle. Screw 382 also preferably clamps together elements 374, 376, 378 at a single location to seal sensor electronics within housing 372.

Bracket 390 of FIG. 20 attaches directly to vehicle 392. Vehicle 392 is for example a sport vehicle such as a snowboard, ski, wakeboard, or skateboard. Vehicle 392 may also be part of a car or motorcycle. A surface 394 of vehicle 392 may be flat; and thus bracket 390 preferably has a corresponding flat surface so that bracket 390 is efficiently bonded, glued, screwed, or otherwise attached to surface 394. Bracket 390 also has screw hole 396 into which mating screw 382 threads to, along direction 399.

FIG. 21 shows one alternative vehicle attachment bracket 400. Bracket 400 has an L-shape to facilitate attachment to bicycle frame 398. Frame 398 is for example part of a bicycle or mountain biking sports vehicle. A seat 402 is shown for purposes of illustration. Bracket 400 has a screw hole 404 into

which mating screw 382 threads to, along direction 406. Sensor outline 408 illustrates how housing 372 may attach to bracket 400.

Brackets 380, 390, 400 illustrate how sensors of the invention may beneficially attach to sporting vehicles of practically any shape, and with low profile once attached thereto. The brackets of the invention preferably conform to the desired vehicle and provide desired orientations for the sensor within its housing. By way of example, L-shaped bracket 400 may be used to effectively orient a sensor to bike 398. If for example the sensor includes a two-axis accelerometer as the detector, with sensitive axes 410, 412 arranged as shown, then vehicle vibration substantially perpendicular to ground (i.e., ground being the plane of movement for the vehicle, illustrated by vector A) may be detected in sensor orientations illustrated by attachment of housing 372 to attachments 390, 400 of FIGS. 20 and 21, respectively. In addition, such an arrangement provides for mounting the sensor to a vehicle with a low profile extending from the vehicle.

Vehicle attachment brackets (and sensor brackets) are preferably made with sturdy material, e.g., Aluminum, such that, once attached to a vehicle (e.g., vehicle 390 or 398), the vibration characteristics of the underlying vehicle transmit through to the housing attached thereto; the sensor within the housing may then monitor movement signals (e.g., vibration of the vehicle, generally generated perpendicular to "A" in FIG. 20 and FIG. 21) directly and with little signal loss or degradation.

FIG. 22 shows housing 374 from a lower perspective view, and specifically shows sensor bracket 380 configured with back connecting elements 376a of housing element 376. FIG. 23 further illustrates bracket 380. FIG. 24 further illustrates element 374, including screw hole 374a for mating screw 382, and in forming part of the cavity 374b for sensor electronics. FIG. 25 further illustrates element 376, including screw aperture 376b for mating screw 382. Elements 376, 374 may optionally be joined together via attachment channels 377, with screws or alignment pins.

FIG. 26 shows one housing 384 for a monitor device of the invention. Housing 384 is preferably made from mold urethane and includes a top portion 384a and bottom portion 384b. An o-ring (not shown) between portions 384a, 384b serves to keep electronics within housing 384 dry and free from environmental forces external to housing 384. FIG. 27 shows the inside of top portion 384a; FIG. 28 shows the inside of bottom portion 384b; and FIG. 29 shows one monitor device 386, constructed according to the invention, for operational placement within housing 384. Portions 384a, 384b are clamped together by screw attachment channels 388. In FIG. 29, device 386 includes batteries 389a, 389b used to power a radio-frequency transmitter 390 and other electronics coupled with PCB 391. Data from device 386 is communicated to remote receivers through antenna 392. When transmitter 390 is a 433 MHz transmitter, for example, antenna 392 is preferably coil-shaped, as shown, running parallel to the short axis 393 of PCB 391 and about 4.5 mm above the non-battery edge 394 of PCB 391. Coil antenna 392 is preferably about 15 mm long along length 392a and about 5.5 mm in diameter along width 392b; and coil antenna 392 is preferably made from about 20 turns 392c of enameled copper wire. Antenna 392 may be coupled to housing 384 via protrusions 385. The o-ring between portions 384a, 384b may be placed on track 386.

FIG. 30, FIG. 31 and FIG. 32 collectively illustrate one mounting system for attaching monitor devices of the invention to objects with flat surfaces. FIG. 30 shows a plate 396 that is preferably injection molded using a tough metal

replacement material such as the Verton™. Plate 396 is preferably permanently secured to the flat surface (e.g., to a ski or snowboard) with 3M VHB tape or other glue or screw. Skis, bicycles, and other vehicles use a corresponding shaped plate that accepts the same sensor. FIG. 31 shows plate 396 in perspective view with a monitor device 397 of the invention. FIG. 32 shows an end view illustrating how plate 396 couples with device 397, and particularly with a lower portion 397a of device 397.

FIG. 33 shows a top view of a long-life accelerometer sensor 420 constructed according to the invention. Sensor 420 can for example be an MMD. Accelerometer sensor 420 includes a PCB 422, a processor 424 (preferably with internal memory 424a; memory 424a may be FLASH), a coin cell battery 426, a plurality of g-quantifying moment arms 428a-e, and communications module 430. PCB 422 has a matching plurality of contacts 432a-e, which sometimes connect in circuit with corresponding moment arms 428a-e. In one embodiment, module 430 is a transponder or RFID tag with internal FLASH memory 430a. The five moment arms 428a-e and contacts 432a-e are shown for illustrative purposes; fewer arm and contacts can be provided with accelerometer sensor, as few as one to four or more than five.

Battery 426 serves to power sensor 420. PCB 422 and processor 424 serve to collect data from accelerometer(s) 428a-e when one or more contact with contacts 432a-e. Communications module 430 serves to transmit data from sensor 422 to a receiver, such as in communications ports 16, 26. Operation of accelerometer sensor 420 is described with discussion of FIG. 34.

In illustrative example of operation of sensor 420, moment arm 428d moves in direction 434a when force moves arm 428d in the other direction 434b. Once arm 428d moves far enough (corresponding to space 436), then arm 428d contacts contact 432d. At that point, a circuit is completed between arm 428d, processor 424 and battery 426, such as through track lines 438a, 438b connecting, respectively, contact 432d and arm 428d to other components with PCB 422. A certain amount of force is required to move arm 428d to contact 432d; arm 428d is preferably constructed in such a way that that force is known. For example, arm 428d can be made to touch contact 432d in response to 10 g of force in direction 434a. Other arms 428a-c, 428e have different lengths (or at least different masses) so that they respond to different forces 434 to make contact with respective contacts 432. In this way, the array of moment arms 428 quantize several g's for accelerometer 100.

In the preferred embodiment, processor 424 includes A/D functionality and has a "sleep" mode, such as the "pic" 16F873 by MICROCHIP. Accordingly, accelerometer sensor 422 draws very little current during sleep mode and only wakes up to record contacts between arms 428 and contacts 432. The corresponding battery life of accelerometer sensor 422 is then very long since the only "active" component is processor 424—which is only active for a very short period outside of sleep mode. Communications module is also active for just a period required to transmit data from sensor 420.

Processor 424 thus stores data events for the plurality of moment arms 428. By way of example, moment arms 428a-e can be made to complete the circuit with contacts 432 at 25 g (arm 428e), 20 g (arm 428d), 15 g (arm 428c), 10 g (arm 428b) and 5 g (arm 428a), and processor 424 stores results from the highest g measured by any one arm 428. For example, if the accelerometer sensor experiences a force 434b of 20 g, then each of arms 428e, 428d, 428c and 428b touch respective contacts 432; however only the largest result (20 g for arm 428b) needs to be recorded since the other arms (428e-c)

cannot measure above their respective g ratings. Longer length arms **428** generally measure less force due to their increased responsiveness to force. Those skilled in the art should appreciate that arms **428** can be made with different masses, and even with the same length, to provide the same function as shown in FIGS. **33** and **34**.

Data events from arms **428** may be recorded in memory **424a** or **430a**. If for example communications module **430** is a transponder or RFID tag, with internal FLASH memory **430a**, then data is preferably stored in memory **430a** when accelerometer sensor **420** wakes up; data is then off-loaded to a receiver interrogating transponder from memory **430a**. Alternatively, processor **424** has memory **424a** and event data is stored there. Module **430** might also be an RF transmitter that wirelessly transmits data off-board at predetermined intervals.

FIG. **35** shows a circuit **440** illustrating operation of accelerometer sensor **420**. Processor **424** is minimally powered by battery **426** through PCB **422**, and is generally in sleep mode until a signal is generated by one or more moment arms **428** with corresponding contacts **432**. Each arm and contact combination **428**, **432** serve to sense quantized g loads, as described above, and to initiate an "event" recording at processor **424**, the event being generated when the g loads are met. Processor **424** then stores or causes data transmission of the time tagged g load events similar to the monitor device and receiver of FIG. **1**.

FIG. **36** shows a runner speedometer system **450** constructed according to the invention. A sensor **452** is located with each running shoe **454**. For purpose of illustration, shoes **454A**, **454B** are shown at static locations "A" and "B", corresponding to sequential landing locations of shoes **454**. In reality, however, shoes **454** are not stationary while running, and typically they do not simultaneously land on ground **456** as they appear in FIG. **36**. Sensor **452A** is located with shoe **454A**; sensor **452B** is located with shoe **454B**. Sensors **452** may be within each shoe **454** or attached thereto. Sensors **452A**, **452B** cooperatively function as a proximity sensor configured to determine stride distance **461** between sensors **452**, while running. One or both of sensors **452** have an antenna **458** and internal transmitter (not shown). A sensor **452** can for example be a monitor device such as shown in FIG. **1**, where detector **12** is the proximity sensor and the transmitter is the communications port **16**. Receiver **462** is preferably in the form of a runner's watch with an antenna **466** and a communications port (e.g., port **26**, FIG. **1**) to receive signals from sensor(s) **452**. Receiver **462** also preferably includes a processor and driver to drive a display **468**. Receiver **462** can for example have elements **14**, **18**, **20**, **22**, **16** of device **10** of FIG. **1**. Receiver **462** preferably provides real time clock information in addition to other functions such as displaying speed and distance data described herein.

In the preferred embodiment, sensors **452** internally process proximity data to calculate velocity and/or distance as "event" data, and then wirelessly communicate the event data to receiver **462**. Alternatively, proximity data is relayed to receiver **462** without further calculation at sensors **452**. Calculations to determine distance or velocity performed by a runner using shoes **454** can be accomplished in sensor(s) **452** or in receiver **462**, or in combination between the two. Distance is determined by a maximum separation between sensors **452** for a stride; preferably, that maximum distance is scaled by a pre-selected value determined by empirical methods, since the maximum distance between sensors **452A**, **452B** determined while running is not generally equal to the actual separation **461** between successive foot landings (i.e., while running, only one of shoes **454** is on the ground at any

one time typically, and so the maximum running separation is less than actual footprint separation **461**—the scaling value accounts for this difference and calibrates system **450**).

Velocity is then determined by the maximum stride distance (and preferably scaled to the pre-selected value) divided by the time associated with shoe **454** impacting ground **456**. An accelerometer may be included with sensor **452** to assist in determining impacts corresponding to striking ground **456**, and hence the time between adjacent impacts for shoe positions A and B. Events may be queued and transmitted in bursts to receiver **462**; however events are typically communicated at each occurrence. Events are preferably time tagged, as described above, to provide additional timing detail at receiver **462**.

FIG. **37** shows an alternative runner speedometer system **480** constructed according to the invention. A sensor **482** is located with one running shoe **484**. For purpose of illustration, shoe **484** is shown at two distinct but separate static locations "A" and "B", corresponding to successive landing locations of shoe **484**. In reality, shoe **484** is not stationary while running, and also does not simultaneously land at two separate locations A, B on ground **486** as it appears in FIG. **37**. Shoe **484** can correspond to the left or right foot of a runner using system **480**. Sensor **482** is located with shoe **484**; it may be within shoe **484** or attached thereto. Sensor **482** has an accelerometer oriented along axis **490**, direction **490** being generally oriented towards the runner's direction of motion **491**. Sensor **482** has an antenna **488** and internal transmitter (not shown). Sensor **482** can for example be a monitor device such as shown in FIG. **1**, where detector **12** is the accelerometer oriented with sensitivity along direction **490**, and the transmitter is the communications port **16**. Sensor **482** transmits travel or acceleration data to receiver **492**. Receiver **492** is preferably in the form of a runner's watch with an antenna **496** and a communications port (e.g., port **26**, FIG. **1**) to receive signals from sensor **482**. Receiver **492** also preferably includes a processor and driver to drive a display **498**. Receiver **492** can for example have elements **14**, **18**, **20**, **22**, **16** of device **10** of FIG. **1**. Receiver **492** preferably provides real time clock information in addition to other functions such as displaying speed and distance data described herein.

In one embodiment, sensor **482** transmits continuous acceleration data to receiver **492**; and receiver **492** calculates velocity and/or distance based upon the data, as described in more detail below. Sensor **492** thus operates much like an MMD **150** described in FIG. **8**, and receiver **492** processes real time feeds of acceleration data to determine speed and/or distance. In the preferred embodiment, however, sensor **482** internally processes acceleration data from its accelerometer (s) to calculate velocity and/or distance as "event" data; it then wirelessly communicates the event data to receiver **492** as wireless data **493**. Events are preferably queued and transmitted in bursts to receiver **492**; however events are typically communicated at each occurrence (i.e., after each set of successive steps from A to B). Events are preferably time tagged, as described above, to provide additional timing detail at receiver **492**.

Generally, sensor **482** calculates a velocity and/or distance event after sensing two "impacts." Impacts **500** are shown in FIG. **38**. Each impact is detected by the sensor's accelerometer; when shoe **484** strikes ground **486** during running, a shock is transmitted through shoe **484** and sensor **482**; and sensor **482** detects that impact **500**. An additional accelerometer in sensor **482**, oriented with sensitivity perpendicular to motion direction **491**, may also be included to assist in detecting the impact; however even one accelerometer oriented

along motion direction **490** receives jarring motion typically sufficient to determine impact **500**.

Alternatively, sensor **482** calculates velocity and/or distance between successive low motion regions **502**. Regions **502** correspond to when shoe is relatively stationary (at least along direction **491**) after landing on ground **486** and prior to launching into the air.

Once impact **500** or low motion region **502** is determined within sensor **482**, sensor **482** integrates acceleration data generated by its internal accelerometer until the next impact or low motion region to determine velocity; a double integration of the acceleration data may also be processed to determine distance. Preferably, data from the sensor accelerometer is processed through a low pass filter. Preferably, that filter is an analog filter with a pole of about 50 Hz (those skilled in the art should appreciate that other filters can be used). However, generally only velocity is calculated within sensor **482**; and distance is calculated in receiver **492** based on the velocity information and time T between impacts **500** (or low motion regions **502**) of sensor **482**. Preferably, velocity is only calculated over the time interval T_i between each impact **500**. Velocity may alternatively be calculated over an interval that is shorter than T, such that runner velocity is scaled to velocity over the lesser interval. The shorter interval is useful in that acceleration data is sometimes more consistent over the shorter interval, and thus much more appropriate as a scalable gauge for velocity. Given the short time of T, very little drift of accelerometer data occurs, and velocity may be determined sufficiently. T_i is typically less than about one second, and is typically about $\frac{1}{2}$ second or less.

Briefly, the processor within sensor **482** samples accelerometer data within each "T" period, or portion of the T period, and integrates that data to determine velocity. The initial velocity starting from each impact **500** (or low motion region **502**) is approximately zero. If A_i represents one sample of accelerometer data, and the sampling rate of the processor is 200 Hz (i.e., preferably a rate higher than the low pass filter), then $A_i/200$ represents the velocity for one sample period ($\frac{1}{200}$ second) of the processor. Data **504** illustrates data A_i over time t. Since T (in seconds)*200 samples=x samples are taken for each period T, then the sum of all of the $A_i/200$ for each of the x samples, divided by the number x, determines average velocity over period T. For integrations over a period that is less than T, fewer samples (less than x) are used to calculate velocity.

Sensor **482** calculates and transmits its velocity data to receiver **492**. Velocity data V_1 corresponds to period T_1 , velocity data V_2 corresponds to period T_2 , and so on. Generally, because of processing time, sensor **482** in this example transmits V_1 in period T_2 , transmits V_2 during period T_3 , and so on. Receiver **492** averages V_i , over time, and communicates the average to the runner in useful units, e.g., 10 mph or 15 kmph.

Note that if only one accelerometer is provided with each shoe **484**, then calibration of velocity V_i may be made for sensor **452** by calibration against a known reference, e.g., by running after a car or running on a treadmill. More particularly, since the accelerometer is oriented in various ways during a period T, other than along direction **491**, then errors are induced due to the acceleration of gravity and other forces. However, since V_i is reported sequentially to receiver **492**, a correction factor may be applied to these velocities prior to display on display **498**. By way of example, if one runner substantially maintains his shoes **484** level, such that accelerometers in sensors **492** maintain a constant orientation along direction **491** during period T, then the reported V_i reasonably approximates actual velocity over that period.

However if the runner points his shoes with toe towards ground **486**, during period T, then only a component of the detected acceleration vector is oriented along direction **491**. However, by calibrating system **480** against a known reference, a substantially true velocity for each period T may be obtained. Moreover, shoe sensor **482** can have a different adjustment factor applied for different gaits (e.g., jogging or running, as shoe orientations during period T may vary for different gaits).

Generally, a calibration for velocity is made at least once for each shoe using the invention, to account for variations in electronic components and other effects. Calibration also adjusts for the gait of the runner in orienting the accelerometer relative to ground **486**. Preferably, like several of the MMDs described herein, a battery powers sensor **482**; and that battery can be replaced once depleted. Implanting the MMD within shoe **484** is beneficial in that a fixed orientation, relative to direction **491**, is made at each landing.

To alleviate the problems associated with acceleration errors, one preferred sensor **482'** for a shoe **484'** is shown in FIG. 39. Sensor **482'** is shown in a side cross sectional view (not to scale); and motion direction **491'** of the runner is shown in relation to accelerometer orientation axes **506a**, **506b** and ground **486'**. Shoe **484'** is shown flat on ground **486'** and generally having a sole orientation **487** also at angle θ relative to accelerometer axis **506a**. Sensor **482'** has at least a two-axis accelerometer **510** (or, alternatively, a three axis accelerometer, with the third axis oriented in direction **506c**) as the sensor detector, with one axis **506a** oriented at angle θ relative to ground **486'** (and hence relative to shoe sole **487** on ground **486'**). Angle θ is chosen, preferably, such that accelerometer axis **506a** maximally orients along axis **491'** while the runner runs. Specifically, since during a period T the toe of shoe **484'** tips towards ground **486'** while running, then angle θ approximately orients that accelerometer such that its sensitive axis **506a** is parallel with axis **491'** for at least part of period T_i . Angle θ can be approximately forty-five degrees. Other angles are also suitable; for example an angle θ of zero degrees is described in connection with FIG. 37, and other angles up to about seventy-five degrees may also function sufficiently. Axis **506b** is preferably oriented with sensitivity perpendicular to orientation **506a**. Data from accelerometer **510** is communicated to low pass filter **511** and then to processor **512** where it is sampled as data $A_{i,a,b,c}$ (a, b, c representing the two or three separate axes **506a-c** of sensitivity for accelerometer **510**). Data $A_{i,a,b,c}$ is then used to (a) determine impacts **500** (and/or low motion regions **502**), as above, and (b) determine V_i based upon $A_{i,a,b,c}$ for any given period T_i (or for any part of a period T). Errors in V_i are corrected by processing the several components $A_{i,a,b,c}$ of the acceleration data. If for example data $A_{i,a}$ is "zero" for part of period T, then either the shoe is at constant velocity, or stopped; or if $A_{i,a}$ is "one" then it is substantially oriented with the toe greatly tipped towards ground **486'**, such that that accelerometer reads the acceleration due to gravity only. Data $A_{i,b}$ may be used to determine which physical case it is, and to augment the whole A_i data stream in determining V_i .

Once processor **512** determines V_i for period T_i , then communications port **514** transmits V_i to the user's watch receiver (e.g., receiver **492**, FIG. 37) as wireless data **515**. The watch receiver calculates a useful runner speed, e.g., 15 km/hour, and displays that to the user. Battery **516** powers sensor **482'**.

Note that the systems of FIGS. 36, 37, 39 provide other benefits associated with upward or downward movement and work functions. Such upward or downward movement, when determined, defines a change of potential energy that may be reported as work or caloric burn. For example, accelerometer

510 can include multiple axes, such that angle θ may be determined. By knowing vertical climb, even over short distances, a work function is created. An inclinometer or angle measurement may also be integrated into such systems, and work functions may also be determined on a hill. Certain MMDs of the invention include for example speed detectors (e.g., accelerometers or Doppler radar devices) to determine speed. By using the hill angle for the upward or downward movement, with speed, another work function is created associated with the climb or descent. Such a work function can add to caloric consumption calculations in fitness or biking applications. Such inventions are also useful in determining whether the climb occurred on a hill or on stairs, also assisting the work function calculation.

There are several advantages of the invention of FIGS. 36-39. The prior art such as shown in U.S. Pat. No. 6,052,654, incorporated by reference, describes a calculating pedometer; but the system does not automatically calculate speed and distance as the invention does. Another patent, U.S. Pat. No. 5,955,667, also incorporated herein by reference, requires the use of a tilt sensor or other mechanism that determines the angular orientation of accelerometers relative to a datum plane. The invention does not require tilt sensors or the continual determination of the angle of the accelerometers relative to a fresh datum plane.

FIG. 40 shows one runner speedometer system 520 constructed according to the invention. System 520 includes a GPS monitor device 522, accelerometer-based monitor device 524, and wrist instrument 526. Device 522 is similar to device 10 of FIG. 1 except detector 12 is a GPS chipset receiving and decoding GPS signals. Device 522 has a processor (e.g., processor 12, FIG. 1) that communicates with the chipset detector to determine speed and/or distance. Speed and/or distance can be accurately determined without knowing absolute location, as in the GPS sensors of the prior art. Speed and/or distance information is then wirelessly communicated, via its communications port, to wrist instrument 526 as wireless data 531. Instrument 526 is preferably a digital watch with functionality such as receiver 24, FIG. 1. Preferably, device 522 clips into clothing pocket of the runner's shirt 530. As described above, system 520 includes one or two accelerometer-based devices 524 in runner shoes 532. Device (s) 524 in shoe(s) 532 augment GPS device 522 to improve speed and/or distance accuracy of system 520; however either device 522, 524 may be used without the other. Together, however, system 520 preferably provides approximately 99% or better accuracy (for speed and/or distance) under non-obscured sky conditions. Wrist instrument 526 collates data from GPS device 522 and accelerometer device(s) 524 to provide overall speed and distance traveled information, as well as desired timing and fitness data metrics.

System 520 thus preferably has at least one MMD 524 attached to, or within, runner shoe 532; MMD 524 of the preferred embodiment includes at least one accelerometer arranged to detect forward acceleration of runner 525. A processor within MMD 524 processes the forward acceleration to determine runner speed. Additional accelerometers in MMD 524 may be used, as described herein, to assist in determining speed with improved accuracy. In the preferred embodiment, MMD 524 wirelessly transmits speed as wireless data 527 to wrist instrument 526, where speed is displayed for runner 525. System 520 providing speed from a single MMD 524 can provide speed accuracy of about 97%. To improve accuracy, a second MMD 524 (not shown) is attached to, or placed within, a second shoe 532; the second MMD 524 also determining runner speed. Speed information from a second shoe 532b is thus combined with speed infor-

mation from shoe 532a to provide improved speed accuracy to runner 525; for example, the two speeds from shoes 532a, 532b are averaged. System 520 providing speed from a pair of MMDs 524 can provide speed accuracy of better than 97%.

System 520 works as a runner speedometer with MMD 524 (or multiple MMDs 524, one in each shoe 532). However, to improve accuracy of speed delivered to runner 525, a GPS chip device 522 is attached to clothing 530 of runner 525. Device 522 may for example be placed within a pocket of clothing 530, the pocket being in the shoulder region so that device 522 has a good view of the sky. Device 522 processes successive GPS signals to determine a speed based upon successive positions. System 520 utilizing device 522 thus provides enhanced speed to runner 525 when using device 522. Speed from device 522 is communicated to wrist instrument 526 where it is displayed for runner 525. Preferably, instrument 526 uses speed from device 522 when speed data is consistent and approximately similar to speed data from MMD 524. Instrument 526 alternatively combines speed data from device 522 and device 524 to provide a composite speed. If device 522 is obscured, so GPS signals are not available, then system 520 provides speed to runner 525 solely from MMD 524 (or multiple MMDs 524, one in each shoe). As an alternative, device 522 can be integrated within a pocket in a hat worn by runner 525, such that device 522 again has an un-obscured view of the sky.

FIG. 41 shows a computerized bicycle system 540 constructed according to the invention. In use, system 540 determines caloric burn or "work" energy expended, among other functions described herein. System 540 includes fore/aft tilt sensor 542 and speed sensor 544; sensors 542, 544 determine then wirelessly transmit bicycle tilt information and speed information, respectively, and as wireless data 545, to receiver and display 546. A processor (not shown) in receiver and display 546 combines data from sensors 542, 544 to determine elevation change, and, hence, work energy (e.g., change of potential energy); receiver and display 546 then displays work energy to a user of bicycle system 540. Work energy may be converted to caloric burn, in one embodiment of the invention. Sensor 542 may include a small gyroscope or an electrolytic type tilt device, known in the art, as the detector for measuring bicycle tilt. Speed sensor 544 is readily known in the art; however the combination of speed sensor 544 with other sensors of FIG. 41 provides new and useful data in accord with the invention.

System 540 can additionally include crank torque measurement sensor 548. Sensor 548 preferably includes a strain gauge connected with bicycle crank 550 to measure force applied to pedals 552 and wheels 554. Preferably, a sensor 548 is applied to each pedal so that system 540 determines the full effort applied by the cyclist on any terrain. Sensor(s) 548 accumulate, process and transmit tension data to receiver and display 546. System 540 can additionally include tension measurement sensor 556 used to measure tension of chain 558. Sensor 556 similarly accumulates, processes and transmits tension data to receiver and display 546. Device 546 preferably includes processing and memory elements (e.g., similar to receiver 231, FIG. 10G) to accumulate and process data from one or more of sensors 542, 544, 548, 556 in the desired way for a user of system 540.

As alternatives to system 540, without departing from the scope of the invention, those skilled in the art should appreciate that (1) sensor 542 may be combined with either of sensor 544 or receiver 546; (2) sensors 542 and 544 may communicate through electrical wiring instead of through wireless communications; (3) a GPS sensor providing earth location and altitude may instead provide the data of sensors

542, 544 for system 540; and (4) receiver and display 546 may instead be a watch mounted to a user's wrist. Preferably, system 540 includes memory, e.g., within receiver and display 546, that stores gradient information associated with a certain ride on terrain, and then provides a "trail difficulty" assessment for the stored data. Maximum and minimum gradients are also preferably stored and annotated in memory for later review by a user of system 540.

FIG. 42 shows a system 600 constructed according to the invention. System 600 is particularly useful for application to spectator sports like NASCAR. System 600 in one application thus includes an array of data capture devices 602 coupled to racecars 604. A data capture device 602 may for example be a monitor device as described herein, with one or a plurality of detectors to monitor movement metrics. As described below, data capture devices 602 preferably have wireless transmitters connected with antennas to transmit wireless data 606 to listening receivers 608. Receivers 608 can take the form of a computer relay 608a and/or a crowd data device 608b, each of which is described below. In the preferred embodiment, data capture devices 602 communicate wireless data 606 to computer relay 608a; and computer relay 608a relays select wireless data 610 to a plurality of crowd data devices 608b. However, data capture devices 602 can directly relay wireless data 606 to crowd data devices 608b, if desired, and as a matter of design choice. Crowd data devices 608b are provided to spectators 612 during a sporting event, such as a NASCAR race of racecars 604 on racetrack 605. Devices 608b may be rented, sold or otherwise provided to spectators 612, such as in connection with ticketing to access racetrack 605, and to sit in spectator stands 616. Data devices 608b may also be modified personal data devices or cell phones enabled to interpret wireless data 606 and/or 610 for display of relevant information to its owner-spectator. Access to data 606, 610 in this manner is preferably accomplished contractually such that the cell phones or data devices have encoded information necessary to decode wireless data 606 and/or 610.

Wireless data 606 can for example be at 2.4 GHz since data capture device 602 may be sufficiently powered from racecars 604. Wireless data 610 can for example be unlicensed frequencies such as 433 MHz or 900-928 MHz, so that each crowd data device 608b may be powered by small batteries such as described herein in connection with receivers for monitor devices. Wireless data 610 can further derive from cellular networks, if desired, to communicate directly with a crowd data device. Wireless link 606 and 610 can encompass two way communications, if desired, such as through wireless transceivers.

Computer relay 608a may further provide data directly to a display scoreboard 614 so that spectators 612 may view scoreboard 614 for information derived by system 600. Scoreboard 614 may for example be near to spectator stand 616.

FIG. 43 shows one data capture device 602' constructed according to the invention. Device 602' may be attached to car 604' or integrated with car 604'. For purposes of illustration, car 604' is only partially shown, with wheels 605 and body 607. Preferably, device 602' is integrated with existing car electronics 618. For example, car electronics 618 typically include a speedometer and tachometer, and other gauges for fuel and overheating. Device 602' thus preferably integrates and communicates with car electronics 618, as illustrated by overlapping dotted lines between items 602' and 618. Device 602' also communicates desired metric information to spectators 612 (either directly or through computer relay 608a).

Device 602' thus includes a wireless transmitter 620 and antenna 622 to generate wireless data 606'.

Data relayed to spectators 612 can be of varied format. Device 602' can for example be an MMD with a detector providing acceleration information. Acceleration data in the form of "g's" and impact is one preferred data communicated to spectators 612 through wireless data 606'. Car 604' may in addition have accelerometers as part of car electronics; and device 602' preferably communicates on-board acceleration data as wireless data 606'. Device 602' and car electronics 618 can for example include a speedometer, accelerometer, tachometer, gas gauge, spin sensor, temperature gauge, and driver heart rate sensor. An on-board computer can further provide position information about car 604' position within the current race (e.g., 4th out of fifteen racecars). Accordingly, device 602' collects data from these sensors and electronic sources and communicates one or more of the following information as wireless data 606': racecar speed, engine revolutions per minute, engine temperature, driver heart rate, gas level, impact, g's, race track position, and spin information. As described in connection with the monitor devices above, data 606' may be continually transmitted or transmitted at timed sequence intervals, e.g., every minute. Data 606' may also be transmitted when an event occurs, e.g., when a major impact is reported by a device 602' (e.g., in the form of an MMD) such as when car 604' experiences a crash. A spin sensor also preferably quantifies rollover rate, acceleration and total rotations (e.g., four flips of the car is 1440 degrees).

FIG. 44 shows one crowd data device 608b' constructed according to the invention. Device 608b' in one embodiment is a cell phone constructed and adapted to interpret information from wireless data 606' (or data 610). Device 608b' can also be a receiver such as receiver 24 of FIG. 1. Device 608b' preferably includes a display 621 to display metrics acquired from information within wireless data 606' (and/or data 610). Communications port 623 and antenna 624 capture data 606' and/or 610. An internal processor decodes and drives display 621. On-Off button 628 turns device 608b' on and off. Car selector button 630 provides for selecting which car 604' to review data from. Data mode button 632 provides for selecting which data to view from selected car 604'.

Data captured by device 608b' may be from one car or from multiple cars 604. Car selection button 630 can be pressed to capture all data 606' from all cars, or only certain data from one car, or variants thereof. In one embodiment, the update rate transferred as wireless data 606' from any car 604' to any crowd data device is about one second; and so each device generally acquires data from one car at any one time and "immediately" (i.e., within about one second) acquires data from another car if selected by button 630. Alternatively, all data 606' from all cars 604 are communicated and captured to each device 608b'. This alternative mode however uses more data bandwidth to devices 608b'.

Accordingly, users of crowd data device 608b' may view performance and data metrics from any car of choice during a race. Currently, spectators only have a vague feel for what is actually happening to a car at a race between multiple cars 604. With the invention, a spectator can monitor her car of choice and review data personally desired. One spectator might for example be interested in the driver heart rate of one car; one other spectator might for example be interested in the speed of the lead car; yet another spectator might for example be interested in the temperature of the top four cars; most spectators are concerned about which car is the lead car. In accord with the invention, each spectator may acquire personal desired data in near real time and display it on individual crowd data devices in accord with the invention. Data

captured from system 600 can further be relayed to the Internet or to broadcast media through computer relay 608a, if desired, so that performance metrics may be obtained at remote locations and, again, in near real time.

The invention also provides for displaying certain data at display scoreboard 614. Computer relay 608a may in addition connect to race officials with computers that quantify or collate car order and other details like car speed. Such data can be relayed to individuals through crowd data devices 608b or through scoreboard 614, or both.

System 600 may be applied to many competitive sports. For example, when the data capture device is like an MMD, system 600 can be applied to sports like hockey, basketball, football, soccer, volleyball and rodeos. An MMD in the form of an adhesive bandage, described above, is particularly useful. Such an MMD can for example be applied with football body armor or padding, as illustrated in FIG. 45. FIG. 45 shows a football player's padding 650 with an MMD 652. MMD 652 can be applied externally to padding 650, though it is preferably constructed internally to padding 650. MMD 652 operates like a data capture device 602 of system 600 (FIG. 42). MMD 652 can for example capture and relay impact information to spectators of a football game, where each of the players wears body armor or padding such as padding 650, to provide performance metrics for all players and to individual spectators. Impacts from blows between players may then be obtained for any player for relay to any spectator or user of the Internet according to the teachings of the invention. Device 652 can alternatively include other detectors, e.g., heart-rate detectors, to monitor fitness and tiredness levels of athletes in real time; preferably, in this aspect, MMD 652 attaches directly to the skin of the player.

Likewise, an MMD of the invention is effectively used in rodeo, as shown in FIG. 46. Preferably one MMD 654 attaches to the saddle 656 of the animal 658 ridden in the rodeo (or to the horn of a bull, or to a rope attached to the animal), and one MMD 660 attaches to the rider 662 on animal 658. Each MMD generates a signal, similar to signals 154, 156 of FIG. 8A. As such, data from each MMD 654, 660 can be compared to the other to assess how well rider 662 rides in saddle 656. This comparison may be beneficially used in judging, removing subjectivity from the sport. For example, by attaching MMD 660 with the pant-belt 662A of rider 662, if signals from MMDs 654, 660 collate appropriately, then rider 662 is efficiently riding animal 658. Of course, one MMD 654 or 660 can also be used beneficially to report metrics such as impact to the audience.

FIG. 47 shows a representative television or video monitor display 678 of a bull 670 and bull rider 672, as well as a plurality of MMDs 674A-D attached thereto to monitor certain aspects of bull and rider activity, in accord with the invention. Display 678 also includes a graphic 676 providing data from one or more of MMDs 674 so that a view of display 678 can review movement metric content associated with bull and/or rider activity. In exemplary operation, MMD 674A is attached to back rope 680 so as to monitor, for example, rump bounce impacts and frequency; MMD 674B is attached to rider rope 682 so as to monitor, for example, loosening of the grip of rider 672 onto bull 670; MMD 674C is attached to bull horn 684 so as to monitor, for example, bull head bounce and frequency; and MMD 674D is attached to rider 672 so as to monitor, for example, rider bounce and frequency, and impact upon being thrown from bull 670. A sensor (not shown) may also attach to the rider's foot or boot, if desired. MMDs 674 can for example be coupled to a reconstruction computer and receiver 152 of FIG. 8A, so as to process multiple MMDs 674 and to report meaningful data to a television, scoreboard

and/or the Internet. Data collected from MMDs 674 in one embodiment are collated and stored in a database so as to characterize bull strength and throwing efficiency over time. For example, by looking at magnitude and frequency of acceleration data from MMD 674C over time for a particular bull provides detail as to how the bull behaves over time. Professional bull riding media can then better gauge which bulls to use for which riders and events.

Those skilled in the art should also appreciate that MMDs 674 can include different detectors providing data desired by sports media. For example, if the MMD contains a linear accelerometer, linear motion forces are reported; if the MMD contains a rotational accelerometer, rotational forces are reported. These MMDs may be placed on various parts of bull 670 or rider 672, such as on the body and head. Data from MMDs may be relayed to television, scoreboards and/or the Internet. Data collated on the Internet preferably includes bull and rider performance summaries.

FIG. 48 shows one EMD or MMD 684 constructed according to the invention. EMD or MMD 684 has specific advantages as a "wearable" sensor, similar to MMD 10, FIG. 2. EMD or MMD 684 utilizes "flex strip" 688 (known in the art) to mount mini-PCBs 686 (devices 686 can also be silicon chips) directly thereto. As a whole, EMD or MMD 684 can "wrap" about objects and persons to fulfill the variety of needs disclosed herein. By way of example, EMD or MMD 684 is useful for comfortable attachment to the rodeo rider 662, FIG. 46, such as to monitor and report "impact" events. Another such EMD or MMD 684 may be attached to a bull or rider to monitor and report heartbeat. In one embodiment, a Kapton flex circuit 688 connects battery 690 to the PCBs 686, and PCBs 686 to one other, so as to flexibly conform to the shape of the underlying object or body. In one option, EMD or MMD 684 is all housed high-density foam or similar flexible housing 694; this can maximize the EMD or MMD's protection and allow it to be worn close to the object of body. For example, such an EMD or MMD 684 may be worn on the torso of a person, where accurate g-levels seen by the body can be measured. In one embodiment, battery 690 is a plastic Lithium-ion power cell that has a malleable plastic case with any variety of form factor. Other batteries may also be used, in accord with the invention.

The invention of one preferred embodiment employs data taken from monitor devices such as described above and applies that data to video games, arcade games, computer games and the like (collectively a "game") to "personalize" the game to real ability and persons. For example, when a monitor device is used to capture airtime (and e.g., heart rate) of a snowboarder, that data is downloaded to a database for a game and used to "limit" how a game competitor plays the game. In this way, a snowboard game player can compete against world-class athletes, and others, with some level of realism provided by the real data used in the game.

More particularly, one missing link in the prior art between video games and reality is that one person can be great at a video game and relatively poor at a corresponding real sport (e.g., if the game is a snowboard game, the player may not be a good snowboarder; if the game is a car race, the person may not be a good racecar driver; and so on). With performance metrics captured as described herein, the data is applied such that an entirely new option is provided with games. As known in the art, games take the form of PLAYSTATION, SEGA, GAMEBOY, etc.

In operation the invention of the preferred embodiment works as follows. Individuals use a monitor device to measure one or more performance metrics in real life. Data from the monitor devices are then downloaded into a game (or com-

puter running the game) for direct use by the game. Data used in the game may be averaged or it may be the best score for a particular player. By way of example, when the performance metric is "airtime", the option applied to the game allows the game player (typically a teenager) to measure a certain number of airtimes, in real life, and download them into the game so that the air the game player 'catches' during the game corresponds to his real airtime (e.g., best airtime, average airtime, etc.). Data used in games can be collated and interpreted in many ways, such as an individual's best seven airtimes of a day or a personal all time record for an airtime jump.

The effect of the invention applied to games is that game users are somewhat restricted in what they can do. In a ski game, for example, a kid that does not have the natural athletic ability to do flips will not, if the option is selected, be permitted to perform flips in a game. Competitions within games then become far more real. If a kid catches only one second of airtime, on average, then it is unlikely that he can catch three seconds of airtime like Olympic athletes; accordingly, when the gaming option is selected, those kids will not be permitted within the game to throw airtime (and corresponding tricks that require like airtimes) of three seconds or higher, for example. The game restricts them to doing tricks that could actually be completed in their normal airtime.

There would of course still be elements making the game unrealistic, and fun. The invention applied to games does however add a measure of realism to the games. For example, limiting a game to airtime may restrict movements to certain types, e.g., one flip instead of two. This is one example of how the invention applied to games makes the game much more real. Another gaming option is to permit the gaming user to expand their current real performance by some percentage. For example, a gaming user can instruct the game to permit 100% performance boost to his real data in competitions in the game. In this way, the gaming user knows how far off his real performance is from gaming performance. If for example it takes a 120% performance boost to beat a well-known Olympic athlete, then she knows (at least in some quasi-quantitative measure) how much harder she will need to work (i.e., 20%) to compete with the Olympic athlete.

Similar limitations to the games may be done with other metrics discussed herein, including drop distance, speed and impact, heart rate and other metrics. For example, by acquiring "impact" data through an MMD of the invention, it is known how much impact a particular athlete achieves during a jump or during a particular activity. By way of example, by collecting impact data from a boxer or karate athlete, it is roughly known the magnitude of impacts that that person endures. Such limitations are applied to games, in accord with other embodiments of the invention. Accordingly, a video game competitor may be limited to actions that he or she can actually withstand in real life. Spin rates too can limit the game in similar ways.

In the preferred embodiment of the invention, data from monitor devices applied to persons are downloaded as performance metrics into games. These metrics become parameters that are adhered to by the player if the gaming option is selected within the game. The ability to play the game, and the moving of the correct buttons, joystick or whatever, is thus linked to the real sport. By way of example, PLAYSTATION has a 'world championship' for the games. In accord with the invention, game players may now compete with their ability tied to competitions within the game, making it much more realistic on the slopes, vert ramp or other game obstacles.

In accord with one embodiment, systems like system 600 are also effectively applied to "venues" like skateparks. The

data capture devices (preferably in the form of MMDs) are applied to individual users of the venue, e.g., skateboarders. Data acquired from the users are transmitted to a computer relay that in turn connects directly to game providers or Internet gaming sources. The venues are thus linked to games. Resorts with venues such as terrain parks are thus incentivized to make their venue part of the gaming world, where kids play in their park in synthesized video, and then actually use the venue to acquire data for use with the game. By tying competitors together from real venues to gaming, a real venue and a game venue become much more alike. Stigmas associated with playing games may also be reduced because gaming is then tied to reality and kids can participate in meaningful ways, both at the venue and within the game. Kids can then compete based upon real ability at both the game and in real life.

FIG. 49 shows one network gaming system 700 constructed according to the invention. System 700 operates to collect data from one or more monitor devices 702, such as through an Internet connection 703 with multiple home users of devices 702. A server 704 collates performance data and relays parameters to games. By way of example, server 704 relays these parameters to a computer game 705 through Internet connection 706. Game 705 includes a real personal data module 708 that stores parameters from server 704. Users of computer game 705 may select an option to invoke the parameters of module 708, thereby limiting the game as described above.

As an alternative, users of devices 702 may directly download game parameters to computer game 705, as through a local data link 710. Users may also type game parameters directly into module 708. In either case, computer game 705 has real limiting functions to gaming actions via the invention. Preferably server 704 controls the download of data to computer game 705 so that data is controlled and collated in a master database for other uses and competitions.

System 700 can further network with an arcade game 720 in a similar manner, such as through Internet connection 718. Real performance data is again stored in real personal data module 722 in game 720 (or at the computer controlling game 720) so that users have restrictions upon play. User ID codes facilitate storing and accessing data to a particular person. In this way, users of arcade games can access and limit their games to real data associated with their skill. Competitions between players at arcade games, each with their own real personal data in play, increase the competitiveness and fairness of game playing.

FIG. 50 illustrates a simplified flow chart of game operation such as described above. A start of a game maneuver starts at step 730. A start may be initiated by a joy stick action, or button action, for example. Prior to performing the action, the game compares the desired game maneuver with real personal data, at step 732. At step 734, a comparison is made to determine whether the requested maneuver is within pre-selected limits (e.g., within a certain percentage from real personal data) related to the real personal data. If the answer is yes, then the game performs the maneuver, at step 736. If the answer is no, then the game modifies, restricts or stops the maneuver, at step 738.

FIG. 51 shows one speed detection system 800 constructed according to the invention. System 800 includes a ticket reader 802 for each ski lift 804. For example, reader 802-1 covers ski lift 804-1 to read tickets of persons riding ski lift 804-1; reader 802-2 covers lift 804-2 to read tickets of persons riding lift 804-2. Lift 804-1 carries persons (e.g., skiers and snowboarders) between locations "A" and "B"; lift 804-2 carries persons from locations "C" to "D". These persons

travel (e.g., by ski or snowboard) from location B to A by approximate distance B-A, from location B to C by approximate distance B-C, from location D to A by approximate distance D-A, and from location D to C by approximate distance D-C.

Approximate distances B-A, B-C, D-A, D-C are stored in remote computer 806. Specifically, computer 806 has memory 808 to store distances B-A, B-C, D-A, D-C. Computer 806 and readers 804 preferably communicate by wireless data 810-1, 810-2; thus computer 806 preferably has antenna 812, and associated receiver and transmitter 814, to facilitate communications 810. Computer 806 further has a processor 816 to process data and to facilitate control of computer 806.

A representative reader 802' is shown in FIG. 52. Reader 802' has an antenna 820 and transmitter/receiver 822 to facilitate communications 810' with computer 806. Among other functions, reader 802' reads ski lift tickets such as ticket 826 of a person riding lifts 804 via a scan beam 807. Ticket 826 usually includes a bar code 828 read by reader 802'.

In operation, a ticket 826 is read each time for persons riding lifts 804. A time is associated with when the ticket is read and logged into computer 806. When that ticket 826 again is read, e.g., either at lift 804-1 or 804-2, a second reading time is logged into computer 806. Processor 816 of computer 806 then determines speed based upon (a) the two reading times, (b) the approximate lift time for the appropriate lift 804, and (c) the distance traveled (i.e., one of distances B-A, B-C, D-A, D-C). For example, suppose a person enters lift 804-1 at 9 am exactly and enters lift 804-2 at 9:14 am. Suppose lift 804-1 takes ten minutes, on average, to move a rider from A to B. Accordingly, this person traveled distance B-C in four minutes. If distance B-C is two miles, then that person traversed distance B-C with a speed of 30 mph. If the resort where system 800 is installed sets a maximum speed of 25 mph for the mountain 801, then that person exceeded the speed and may be expelled from the resort. Note further that the resort may specify speed zones, corresponding to each of the paths B-A, B-C, D-A, D-C. If for example path B-A has a wide path, then a speed may be set at 30 mph. A person successively repeating lift 804-1 may thus be checked for speeds exceeding 30 mph. If on the other hand path D-A has a lot of trees, then a speed of 20 mph may be set; and a rider who rides lift 804-2 and arrives at lift 804-1 can be checked for violations along route D-A.

When a ski lift 804 stops, then additional time is added to that person's journey. A feedback data mechanism tracking lift movement can augment data in computer 806 to adjust skier speed calculations on dynamic basis.

Note that system 800 serves to replace or augment sensor 231' of FIG. 101. Since sensor 231' independently determines speed, then reader 802 may for example read sensor 231' to see whether speeds were exceeded for one or more zones. Sensor 231' may instead have a visual indicator which is triggered when a person exceeds a speed limit in any of zones for B-A, B-C, D-A, D; and a human operator sees the indicator when there is a violation.

As shown in FIG. 53, one monitor device 840 of the invention incorporates a GPS receiver chip 842 to locate device 840. Device 840 is preferably integrated with an adhesive strip such as discussed in FIG. 2. Device 840 also preferably "powers on" when opened and dispensed, such as shown in FIGS. 4 and 10. In operation, device 840 is generally applied to persons or objects to assess, locate and log "events". By way of example, by attaching device 840 to a new computer shipped to a retailer, an impact event may be recorded and stored in memory 846 by an accelerometer detector 844, as

described above, and a location associated with the impact event is also stored, as provided by GPS chip 842. As such, for example, the exact amount of damage received by the computer, as well as the exact location of where the damage occurred, is stored in memory 846. As described herein, other detectors 844 may be used to generate "events" (e.g., a spin event, or an airtime event, temperature, humidity, flip-over events, etc.) in conjunction with GPS chip 842. Data in memory 846 is relayed to a receiver 850 having data access codes of device 840. Alternatively, data is communicated to receiver 850 by wireless and timed-sequence transmissions. Communications ports 852, 854 facilitate data transfers 860 between device 840 and receiver 850. Transfers 860 may be one way, or two-way, as a matter of design choice. A clock 862 may be incorporated into device 840 to provide timing and/or real-time clock information used to time tag data events from one or both of detector 844 and GPS chip 842. As above, a battery 864 serves to power device 840. A processor 848 serves to manage and control device 840 to achieve its functionality.

FIG. 54 shows a system 866 suitable for use with a device 840, or with other MMDs or EMDs disclosed herein. System 866 has particular advantages in the shipping industry, wherein a device 865 (e.g., device 840, or one or more EMDs or MMDs) attaches to a package 867 (or to the goods 868 within package 867) so that system 866 can monitor data associated with shipment of goods and package 868, 867. Multiple devices 865 may be attached to package 867 or goods 868 as needed or required to obtain the data of interest. Certain data determined by device 865, during shipment, include, for example, impact data or g's, temperature, data indicating being inverted, humidity and other metrics. In sum, one or more of these data are wirelessly communicated, as wireless data 863, to an interrogation device reader 869 to assess the data corresponding to shipment conditions and/or abuse of package 867 and/or goods 868. Data 863 preferably includes "time tag" data indicating when a certain "event" occurred, e.g., when goods 868 experienced a 10 g event. Preferably, data from reader 869 is further relayed to a remote database 871 so that system 866 may be operated with other similar systems 866 so as to monitor a large amount of packages and goods shipments at different locations. Damaged goods can for example be evaluated by any reader 869 and recorded into a common database 871 by the controlling company.

The invention of FIG. 54 thus has certain advantages. Companies that ship expensive equipment 868 have an incentive to prove to the receiver that any damage incurred was not the result of faulty packaging 867 or unsatisfactory production and assembly. Also, shipment insurers want to know when and where damage occurs, so that premiums may be adjusted appropriately or so that evidence may be offered to encourage the offending party to improve handling procedures.

The monitor devices of the invention have further application in medicine and patient health. One monitor device 870 of the invention is shown in FIG. 55. Specifically, device 870 attaches to a baby's body 872 (e.g., to a baby's chest, throat, leg, arm, buttocks or back) to monitor movement such as respiratory rate, pulse rate, or body accelerations. Device 870 of the preferred embodiment synchronizes to repetitive movements (e.g., pulse rate or respiratory rate) and generates an "event" in the absence of the repetitive movements. Device 870 can for example be device 10w, FIG. 2E, facilitating easy placement on the infant by the adhesive strip (which is also beneficially sterilized) to measure heart rate as an event. Device 870 can alternatively be a monitor device using a microphone to detect "breathing" as a health metric for the

infant. Regardless of the metric, the event reported by device **870** is preferably communicated immediately as wireless signals **874** to a remote monitor **876**, with an antenna **878** to receive signals **874**. Monitor **876** is preferably portable so as to be carried with the infant's parents. Monitor **876** generates an audible or visual alarm when an event is received from signals **874**. Device **870** seeks to address the very realistic concern of parents relative to Sudden Infant Death Syndrome, or other illnesses. Device **870** preferably relays a warning event data to alarm monitor **876** within seconds of detecting trouble with the infant. For example, if device **870** detects the absence of heart rate or breathing, the alarm at monitor **876** is made in near real time.

Like other monitor devices herein, device **870** has a detector **870a** to detect the desired metric. For purposes of illustration, other elements such as the device's communications port and processor are not shown, though reference may be made to FIG. 1 to construct device **870**. In one embodiment, detector **870a** is a piezoelectric element that generates a voltage signal at every pulse or breath of baby **872**, such as shown and described in FIG. 7-7B. Detector **870a** may alternatively be an accelerometer arranged to sense accelerations of the infant's chest (or other body portion); and thus chest (or other body portion) accelerations are used to determine the repetitive signal (or simply movement or absence of movement). Preferably, the sensitive axis of the accelerometer is perpendicular to baby body **872**. For example, such an accelerometer can be used to sense accelerations of the baby's chest, rising and falling. In still another embodiment, detector **870a** is a force-sensing resistor or electro-resistive element generating signals responsive to force or weight applied to device **870**. Such a device is useful to sense when baby body **872** rolls onto device **870**. Yet another detector **870a** is a Hall Effect detector; that detector within device **870** detects when baby body **872** inverts, that is when the baby rolls over. A roll over event is one particular event of interest by parents; and in this embodiment, a warning signal **874** is generated at each roll over. Detector **870a** can alternatively be a microphone; and the device's processor processes the sound data to detect recurring audible data indicative of breathing sounds.

Preferably, device **870** is integrated with an adhesive strip **880**; and device **870** and strip **880** form an adhesive bandage monitor device such as described above in connection with FIGS. 2-2D, 8C. Device **870** and strip **880** are also preferably packaged so as to "power on" when dispensed or used. A wrapper such as described in FIGS. 4-4A may be used; or preferably device **870** and wrapper **880** dispense from a canister **200**, **200'** such as described above in FIGS. 10-10F. In this way, device **870** is conveniently dispensed and applied to baby body **872**, and without contamination and germs.

Those skilled in the art should appreciate that device **870** may also attach to the infant in a variety of places depending on the parent's desire. Device **870** may for example attach to the back or bottom of the infant, and generate an event for every time the infant rolls over.

FIG. 56 shows a flowchart of steps associated with applying and using one monitor device according to the invention. At start **884**, the device is unwrapped and/or dispensed from a container. The device is then applied to a baby's body, preferably as an adhesive bandage package, in step **886**. Once applied, the device synchronizes to baby body movement (such as repetitive movements associated with pulse or respiratory rate), breathing sounds or heart rate, in step **888**. The device then searches for "events" in the form of the absence of repetitive signals, indicating for example the danger of an absence of pulse, heart rate or respiration, in step **890**. In step **892**, the monitor device generates a wireless signal as a warn-

ing; that signal is received at a remote receiver at step **894**. Once received, remote receiver generates an audible alarm (e.g., a buzzer sounds) or visible alarm (e.g., an LED is lit), in step **896**. Preferably, steps **890-896** occur in less than one or several seconds (e.g., less than five or ten or fifteen seconds). Once the alarm occurs, a parent checks the infant (step **898**) to determine whether the alarm is real and, if needed, to administer aid. If for some reason the alarm was incorrect, the remote receiver is reset (step **898**) and the monitor device continues to assess distressing situations to generate events.

As an alternative, the detector of the monitor device (FIG. 55) is a temperature (or alternatively a humidity) detector, and the alarm monitor merely tracks infant temperature for worried parents; such a device is useful for sick infants in particular. The temperature sensor can be coupled with other detectors (e.g., heart rate) to provide multiple functions, if desired.

The MMDs and EMDs of the invention thus have several other advantages. They may be used discretely and safely as medical diagnostic and monitoring detectors. With appropriate detectors, EMDs of the invention can for example provide for portable, wireless pulse oximeters or blood glucose monitors. With the appropriate detectors in MMDs, rehabilitation clinicians would be able to quantitatively monitor metrics such as limb movement and balance. EMDs equipped with certain detectors may find use as real time, remote and inexpensive pH monitors and blood gas monitors.

One MMD **900** of the invention and useful in medical applications is shown in FIG. 57. MMD **900** is similar to device **10** of FIG. 1, but in addition (or alternatively) has a detector **902** that senses weight. Detector **902** for example is a force sensing resistor or electro-resistive device. Preferably, MMD **900** is applied to one or more locations at the bottom of a human foot **906** via attachment with adhesive strips **908**. Those skilled in the art should appreciate that MMD **900** can alternatively be located at other locations on the human body. On the occurrence of an "event", MMD **900** generates wireless signals **910** for receipt at a remote receiver **912**, here shown in the form of a watch with antenna **914**. Watch **912** is generally worn by the person having foot **906**.

MMD **900** is preferably in the form of an MMD **10z** of FIGS. 2B-2C, though with a weight sensing detector. In operation, MMD **900** is first calibrated: all the weight of person with foot **906** is applied to MMD **900** so that detector **902** is calibrated to that entire weight. Alternatively, a separate weight simply calibrates MMD **900**. Thereafter, MMD **900** generates "events" corresponding to fractions of the entire weight that the person with foot **906** applies to MMD **900**. For example, one MMD **900** generates wireless data **910** each time MMD **900** experiences at least one-fourth the entire weight; that data **910** is converted and displayed on receiver **912**, as shown. In this way, when a cast is applied to a person, MMD **900** may be applied under foot, so that the person may obey doctor's orders to put no more than $\frac{1}{4}$ weight on foot **906**, for example. As an alternative, MMD **900** is already calibrated to certain weights, e.g., 200 lbs, 180 lbs, etc. A pre-calibrated MMD **900** may then be applied to 200 lb persons to generate events as needed. For example, an MMD **900** is used effectively to generate an event, to inform the person, that $\frac{1}{2}$ or $\frac{3}{4}$ of the person's entire weight is on one foot.

A weight sensing MMD may also take the form of MMD **920**, FIG. 58. Here, MMD **920** has an array of detectors **922**. Detectors **922** may be force sensing resistors or other weight sensitive elements. Detectors **922** collectively and electrically couple to processor **924**. Other elements (not shown) connect with processor **924**, e.g., a communications port and battery, such as monitor device **10** of FIG. 1. In operation,

MMD 920 senses weight applied to foot 930 while walking or standing. Over time, MMD 920 ascertains the actual weight of the person of foot 930. Once weight is determined, MMD 920 relays weight information to a remote receiver, e.g., watch 940 with antenna 940a, via wireless signals 942. Receiver 940 displays pertinent data, e.g., what fractional weight is applied onto foot 930.

In this way, a person may track his or her weight at any time. MMD 920 and receiver 940 may also communicate two-way, so that watch 940 queries MMD 920 for weight data, thereby conserving battery power. Those skilled in the art should appreciate that MMD and receiver 920, 940 may be configured differently and still be within the scope of the invention. In one embodiment, MMD 920 is integrated with a shoe pad insert to fit into any shoe. Alternatively, MMD 920 is integrated directly into a shoe, as shown in FIG. 59. Detector 922 may also have fewer or more detectors depending upon design placement of detectors relative to foot 930; that is, a single detector can be used to measure weight if arranged to accurately detect all or part of a person's weight. In such a configuration, MMD 920 may take the form of an adhesive bandage monitor device with a single detector and applied to the sole of a foot, as shown in FIG. 57. Preferably, weight is calibrated prior to use (e.g., when shoe is lifted off the ground) so that weight is determined relatively. In another embodiment, selectively positioning elements 922 to high impact areas of foot 930 (e.g., at the ball and heel of foot 930), the invention monitors impact and improper walking or running events so as to provide corrective feedback to users or doctors.

FIG. 59 shows a shoe-based weight sensing system 950 constructed according to the invention. System 950 has one or more weight sensing detectors 952 coupled to a processing section 954 (and, as a matter of design choice, other components such as shown in device 10 of FIG. 1)—all arranged with a shoe 956 (or within an insert for shoe 956). In operation, shoe 956 generates wireless signals 958 for a remote receiver (e.g., watch 940, FIG. 58) to inform the person wearing shoe 956 of his or her weight or weight loss. By integrating a transceiver and antenna 959 with processing section 954, the remote receiver interrogates shoe 956 for weight information. In this way, health conscious persons can wear shoe 956 and learn of their weight at any desired time. Such a shoe 956 is for example useful in determining weight loss. By way of example, a runner may use shoe 956 to determine weight loss in ounces, informing the runner that he or she should drink replacement water. Accordingly, in the preferred embodiment, a runner first calibrates his or her weight prior to a race; then system 950 reports weight loss relative to the calibrated weight. Those skilled in the art should appreciate that alternatives from the foregoing may be achieved without departing from the scope of the invention.

FIG. 60 shows one force-sensing resistor 960 suitable for use with the systems and/or MMD of FIGS. 57-59. Resistor 960 includes resistive material 962 and interdigitated contacts 964A, 964B; material 962 forms an electrical path between contact 964A and contact 964B. In operation, a force applied to resistor 960 increases the conductivity in the path between contacts 964A, 964B. By measuring resistance or conductance between contacts 964A, 964B, the applied force onto resistor 960 is known. Typically, resistor 960 is calibrated so that a particular resistance translates into an applied force; as such, a processor such as processor 954 or 924 may be used to monitor and report force at any given time. In one embodiment, force is reported to users in pounds, providing a typically used weight designation for such users.

Preferably, resistor 960 includes flexible polymers as active spring agents as the sensing element for loading con-

ditions. Such polymers provide load-sensing resistors with enhanced performance and with preferable mechanical characteristics.

FIG. 61 shows another weight sensing device 970 constructed according to the invention. Device 970 is formed of a shoe 972 and includes a fluid cavity 974 that displaces and pressurizes with applied force—a force such as provided by a user wearing shoe 972. A pressure sensor 976A coupled with cavity 974, through a small conduit 975, measures pressure. A processor (e.g., processor 954, 924 above) coupled with sensor 976A monitors pressure signals and converts the signals to weight. As above, preferably device 970 is calibrated such that a particular pressure corresponds to a particular weight. Preferably, and for increased accuracy, cavity 974 does not completely displace away from any portion of cavity 974 when a user applies weight to cavity 974 while wearing shoe 972.

As an alternative to a single cavity 974, cavity 974 can also be made up of separate fluid cells, as exemplified by sections 974A, 974B, 974C, and 974D, and multiple sensors 976A, 976B. In this embodiment, cavity membrane walls 978 separate sections 974A, 974B, 974C, 974D; optionally two or more of sections 974A, 974B, 974C, 974D have an individual pressure sensor monitoring pressure of the particular section, such as sensor 976A for section 974D and sensor 976B for section 974C. This embodiment is particularly useful in providing highly accurate weight sensing for a user of shoe 972. Each fluid cell 974A-D may for example have differing pressurization characteristics to manage the overall weight application of a human foot. For example, cells 974B, 974C may be formed with higher pressure cavities as they are, respectively, under the ball or heel of the foot and likely have to accommodate higher pressures (i.e., higher applied weight to those sections). In either event, a processor connected to the several pressure sensors 976A, 976B beneficially determines weight as a combination of different pressures of the different fluid cells. Alternatively, a single pressure sensor 976A may be used to sequentially measure pressure from various fluid cells 974A-D; and the processor (not shown) then determines weight based upon the several measurements.

Those skilled in the art should appreciate that the number of cells 974A-D, and the number of sensors 976A, 976B, are a matter of design choice and do not depart from the scope of the invention; more or fewer cells 974 or sensors 976 may be used without departing from the scope of the invention. Those skilled in the art should also appreciate that a shoe insert can alternatively house cavity 974 (and/or sections 974A, 974B); for example, shoe 972 can be a shoe insert instead of a shoe—constructed and arranged such that a user applies weight on cavity 974 in use.

A weight-sensing device of the invention, for example as set forth in FIG. 61 may benefit from additional information such as temperature, as fluid pressure characteristics vary with temperature. Accordingly, in one embodiment of the invention, an additional detector is integrated with the processor to monitor temperature. As such, a device 970 for example can include one or more pressure detector 976 and a temperature detector (not shown), both of which input data to the processor for processing to determine weight applied to cavity 974 (or sections 974A-D).

FIG. 62 shows an alternative arrangement of fluid sections 974' (e.g., shown as fluid sections 976', 1000, 1004) integrated with a shoe insert 972'. Preferably, sections 974' are integrated within insert 972', though FIG. 62 shows sections 974' external to insert 972' for purposes of illustration. In operation, a user stepping on insert 972' pressurizes the various sections 974'—and a processor (not shown) determines

weight based upon pressure data from pressure sensors 976' connected with the various sections 974'. Higher pressure areas 1000 and lower pressure areas 1002 are then preferably measured by separate pressure sensors 976'. One or more pressure conduits 1004 may be used to couple like-pressure areas so that a single sensor 976' monitors a single like-sensor area.

The invention thus has several advantages in regard to weight loss, monitoring and human fitness. In accord with the above invention, a user of a weight monitoring system or device disclosed herein can review his or her weight at nearly any time. Runners using such a system and device to know their hydration loss; chiropractors may wish to monitor weight distribution over a patient's feet; and athletic trainers may wish to analyze weight distribution and forces. The invention of these figures assists in these areas. In making these measurements, force-sensing resistors may be used; but strain gauge pressure sensors in the shoe may also be used. Preferably, in such embodiments, the bottom surface of the foot is covered by sensors, as weight is not often evenly distributed. Accordingly, a single sensor may not encompass a preferred arrangement, and therefore multiple sensors are preferred in the sole of the shoe (or in a shoe insert), with the results of all sensors summed or combined to a single "weight" answer. In one embodiment, only a portion of the foot needs to be covered, covering a certain percentage of the overall weight; and that percentage is scaled to a user's full weight. Weight and compression forces monitored in a shoe or shoe insert, in accord with the invention, can further assist in gauging caloric and/or physical effort.

FIG. 63 shows a professional wrestling rink system 1100 constructed according to the invention. System 1100 has a rink 1102 within which professional wrestlers compete (oftentimes theatrically). Adjacent rink 1102 are tables 1104 and chairs 1106, sometimes used in conjunction with rink 1102 (e.g., items 1104 and 1106 are sometimes used to smash over a wrestler as part of a performance). A plurality of sensors (e.g., MMDs or EMDs) 1108 are placed (attached, stuck to, etc.) throughout rink, table and/or chairs 1102, 1104, 1106. For example, in one preferred embodiment a plurality of MMD sensors 1108 are placed under rink canvas 1110, such as at positions marked "X", so as to report "impact" of wrestlers in rink 1102. MMD sensors 1108 may also be placed on one or more of the corner posts 1112 or ropes 1114—used to form rink 1102. Sensors 1108 are shown illustratively in a few positions about items 1102, 1104, 1106, 1110, 1112, 1114 for purposes of illustration—when in reality such sensors 1108 would be difficult to see, or would be hidden from view (for example, sensors 1108 are preferably under canvas 1110).

Data from sensors 1108 typically include information such as impact, as described above. Events associated with "impact" are communicated wirelessly to a receiving computer 1120 as wireless data 1122. Data 1122 for example includes digital data representing impact data received at any of sensors 1108 when wrestlers hit canvas 1110, move ropes 1114, or hit post 1112. Receiving computer 1120 preferably has an antenna 1124 and communications port 1126 to receive data 1122. Computer 1120 typically re-processes and then retransmits data 1122 to a media site 1129, such as television, scoreboard or the Internet, so that viewers may see data 1122 associated with wrestling at rink 1102. Since wrestling in and about rink 1102 is often based on choreographed action, computer 1120 preferably includes a data manipulation section 1130 which post processes data 1122 in predetermined ways. For example, section 1130 may apply an exponential or quadratic function to data 1122 so that, in effect, and by way of example, a 25 g impact on canvas 1110

is reported as a 25 g impact, but a 50 g impact on canvas 1110 is reported as a 1000 g impact.

Section 1130 may also manipulate data for a particular player. For example, FIG. 64 shows a representative television display 1131 that includes data from system 1100. FIG. 53 also shows representative wrestlers 1132 in rink 1102. In a preferred embodiment, one or more sensors 1108 are also placed on wrestlers 1132, such as shown, to monitor events such as impact received directly on wrestlers 1132. In one embodiment, sensors 1108 of FIG. 64 are of the form of an adhesive bandage MMD, described above. In another embodiment, sensors 1108 are integrated into the waistband of the wrestler; this has advantages as being close to the wrestler's center of gravity and is thus more representative of total impact received by a particular wrestler.

Data from computer 1120 is thus reported to a media destination 129 such as television so that it may be displayed to audience members. FIG. 64 shows one exemplary data display 1134 overlaid with the actual wrestling performance—for television display 1131- and showing impact data in "qualitative" bar scales. Display 1134 may include qualitative wording such as shown. Display 1134 also preferably includes an advertiser overlay 1136 promoting a certain brand; typically that advertiser pays for some or all of the content provided for by system 1100 and shown in display 1134.

Thus, FIGS. 63 and 64 demonstrate benefits in which the TV viewer desires to see information such as a display of forces acting on wrestlers in real- or near real-time; the data being presented in graphical or numeric form and with a range of possible analyses performed on the forces such as latest, largest average and total. These forces typically act in at least two planes (i.e., from the side and from the front or back), though the invention may also take account of forces in all three planes. Typically, the forces of interest are those acting on the main mass (torso) of the wrestler, while flailing feet and arms are not generally as important as body slams. The system of the invention thus resolves forces on individuals and can detect the force of collision between two wrestlers.

In the preferred embodiment, at least one sensor 1108 attached to ropes 1114 preferably takes the form of a long thin sensor (e.g., 0.5"x3") with a short piece wire (e.g., 3") protruding from one end to function as the antenna. This sensor's electronics utilizes a small low power accelerometer as the sensing detector, and incorporates a simple gain block, a small micro controller such as Microchips' PIC12LC672, and a small low power transmitter such as RFMs'RX6000 or RF Solutions' TX1. These electronics mount on flex circuit (e.g., as shown in FIG. 48) to allow for the excessive bending forces likely to be encountered. The power source is preferably a single small (thinnest available) lithium cell.

In the preferred embodiment, at least one sensor 1108 attached to posts 1112 incorporates a gas pressure sensor as the detector; such a sensor is incorporated into the cushions protecting the corner posts 1112 and thus registers an increase reading as the wrestlers collide with the posts. Alternatively, such a sensor may be incorporated directly into a cushion attached to post 1112; preferably such a cushion is airtight. FIG. 61 shows one fluid-based pressure sensor that may be configured to such an application as the cushion with post; gas may for example replace the fluid or gel of FIG. 61. In an alternative configuration, sensors 1108 integrated with the posts 1112 may include strain gauges as the detector. Mounted directly to the posts 1112, these sensors indicate the forces acting on the post as the wrestlers impact the posts

1112. In another alternative, a post sensor may include vibration or accelerometer detector so that the sensor 1108 determines impact forces.

In one embodiment, at least one of the sensors attached to ropes 1114 include extension detectors (or LVDT devices) at the points where the ropes are mounted. Sensors 1108 with strain gauges may also be used. Sensors attached to ropes 1114 preferably detect "rope deflection" as a reported metric.

In one embodiment, sensors 1108 in the floor incorporate piezoelectric cables mounted as an interlocking grid attached to the underside of the floor. For example, such cables connect the "x" locations of FIG. 63. In such a configuration, only one sensor 1108 may be needed to monitor floor impact as all cables act as a single "detector" for an MMD sensor 1108. Floor or canvas sensors 1108 may also incorporate strain gauges attached in an array on the underside or around the perimeter at points where the floor 1110 is suspended. Vibration sensors and accelerometers may alternatively be used as the detector in any floor-monitoring sensor 1108.

FIG. 65 shows one surfing application for an MMD 1140 of the invention. MMD 1140 of one preferred embodiment includes an accelerometer detector (e.g., as in MMD 10 above) and MMD 1140 determines "G's" for big bottom turns. On-board signal processing for example preferably determines the location of a big bottom turn and records an "event" associated with the number of G's in the turn. G's may also be reported for other locations. One difficulty with such measurements is that there may be many larger G forces affecting surfboard 1146 from flips, kicks and other actions; however the invention solves this difficulty by filtering out such actions. In one embodiment, the processor within MMD 1140 monitors the low frequency component of the accelerometer detector to determine the difference in the peaks and troughs of sinusoidal movement, so that MMD 1140 reports wave size and height over time.

One MMD 1140 may also gauge the power of a wave landing on top of the surfer 1142. Such an MMD 1140 preferably includes a pressure detector to determine pressure within water 1144 when a wave lands on surfboard 1146 and on surfer 1142. A "maximum pressure" event is then reported by MMD 1140.

Another MMD 1140 includes an inclinometer or other angle determination detector to determine and report angle of the surfboard 1146; for example a maximum angle is reported for a given run or day.

Data from any particular metric (e.g., g's in a turn, angle of surfboard, pressure under water) provided by MMD 1140 is preferably reported wirelessly to a watch worn by surfer 1142; however such data may also be displayed on a display integrated with surfboard 1146 or directly with sensor 1140, such as shown with an airtime sensor in U.S. Pat. No. 5,960,380, incorporated herein by reference. In the form of a wrist-watch, one MMD of the invention includes a pressure sensor housed in the watch; the MMD watch then reports the maximum pressure events without need of a separate MMD 1140 mounted to surfboard 1146 (or integrated therein).

In one preferred embodiment, MMD 1140 includes a speed detector (such as a Doppler module or accelerometers as discussed herein or in U.S. Pat. No. 5,960,380) so that surfer speed is reported to surfer 1142. Preferably, in this embodiment, distance traveled is also reported; by way of example the receiver of data from MMD 1140 (e.g., a digital watch) converts speed to distance by multiplying speed by a time duration traveled over that speed. FIG. 66 shows MMD 1140' including a Doppler module that radiates energy 1150, as shown, to determine whether the rider of surfboard 1146' is within the "Green Room"—i.e., within a wave 1152. Prefer-

ably, such an MMD 1140' also includes a speed sensor which indicates that board 1146' is in motion so that the time duration of riding within the Green Room is determined accurately.

FIG. 67 shows a personal network system 1300 constructed according to the invention. System 1300 keeps track of personal items, such as cell phone 1302, car keys 1304, wallet or purse 1306, personal data assistant 1308, digital watch 1309, and/or personal computer 1310. Additional, fewer or different personal items can be tracked in system 1300, at the selection of a user of system 1300. For example, a user can set up system 1300 to keep track of cell phone 1302 and keys 1304 only. Briefly, each personal item of FIG. 67 includes a network transceiver: cell phone 1302 has transceiver 1302a, car keys 1304 has transceiver 1304a, wallet or purse 1306 has transceiver 1306a, data assistant 1308 has transceiver 1308a, watch 1309 has a transceiver 1309a, and computer 1310 has transceiver 1310a. Each transceiver 1302a, 1304a, 1306a, 1308a, 1309a, 1310a communicates with every other transceiver substantially all the time via a wireless link 1320. Those skilled in the art appreciate that each transceiver 1302a, 1304a, 1306a, 1308a, 1309a, 1310a include an antenna to receive and communicate data on link 1320. In the preferred embodiment, each transceiver 1302a, 1304a, 1306a, 1308a, 1309a, 1310a only maintains communications with any other transceiver over a selected distance, e.g., 100 feet, herein identified as the Network Distance. For example, cell phone transceiver 1302a maintains communications with every other transceiver 1304a, 1306a, 1308a, 1309a, 1310a so long as cell phone 1302 is within the Network Distance of every other device 1304, 1306, 1308, 1309, 1310. However, for example, once cell phone 1302 is separated from keys 1304 by more than the Network Distance, then cell phone 1302 ceases communications with keys 1304 but maintains communications with other items 1306, 1308, 1309, 1310 (assuming items 1306, 1308, 1309, 1310 are within the Network Distance from cell phone 1302).

In one preferred embodiment, each transceiver 1302a, 1304a, 1306a, 1308a, 1309a, 1310a includes a Bluetooth microchip and transceiver known in the art. Bluetooth transceivers only maintain a communication link (at a frequency of about 2.4 GHz in the ISM band) over a short range, e.g., 50 feet, and are not generally suitable for longer communication distances.

Optionally, one or more of transceivers 1302a, 1304a, 1306a, 1308a, 1309a, 1310a are instead transponders; and at least one of items 1302a, 1304a, 1306a, 1308a, 1309a, 1310a provides excitation energy to the transponders to "reflect" data along link 1320 to provide the functionality described herein. Those skilled in the art should appreciate that items 1302a, 1304a, 1306a, 1308a, 1309a, 1310a may incorporate other technology, such as transmitters, to facilitate like functionality. That is, not every item 1302, 1304, 1306, 1308, 1309, 1310 needs to transmit and receive data on link 1320. For example, wallet 1306 can include a transmitter instead of a transceiver to provide data about itself on link 1320; and other items 1302, 1304, 1308, 1309, 1310 can use wallet data to know whether it is in the network or not (even though wallet 1306 does not know whether other items 1302, 1304, 1308, 1309, 1310 are in the network). Transponders can provide like functionality for certain items 1302, 1304, 1306, 1308, 1309, 1310 as a matter of design choice.

Wireless link 1320 includes information about time and items in the network; preferably the information also includes location information. For example, data 1320 informs each item 1302-1310 that every other item is still within the network, and, thus, that one or more items have not moved to

beyond the Network Distance. If one item—e.g., keys **1304**—leaves the network so that item **1304** no longer communicates on link **1320**, every other item **1302**, **1306**, **1308**, **1310** knows that item **1304** is no longer linked and data is stored on every other item **1302**, **1306**, **1308**, **1310** indicating a time when item **1304** left the network. Preferably, the stored data in every other item also includes where the network was when keys **1304** disappeared.

In the simplest embodiment, each of items **1302-1310** includes a corresponding indicator **1302b-1310b**; each of indicators **1302b-1310b** can for example be a LED, LCD, buzzer or vibrator. When any of items **1301-1310** are “lost” from the network—e.g., one item moves beyond the Network Distance—then the indicator in one or more of the other items tells the user of system **1300** that an item has “left”. That person can then expend effort to locate the lost item. By way of example, each of indicators **1302b-1310b** may provide a beep, sound or vibration to provide the user with knowledge of a lost item **1302-1310**.

In a more complex embodiment, data stored on any item **1302-1310** indicating the loss of any item within network **1300** is a “cookie” of information detailing when and where an item left the network. In this way, a user of system **1300** can locate and find the lost item by reviewing cookies in any other item. By way of example, consider a network **1300** made from keys **1304**, wallet **1306**, digital watch **1309** and cell phone **1302**—items commonly carried by a male business person. In the preferred embodiment, this person would designate items **1302**, **1304**, **1306**, **1309** as being “in network” (such as described below in connection with FIG. **68**)—and system **1300** thereafter monitors items **1302**, **1304**, **1306**, **1309** so that the person can keep track of items **1302**, **1304**, **1306**, **1309**. If for example this person leaves his cell phone **1302** in a restaurant, then items **1304**, **1306**, **1309** know this occurred and inform him of the time, and preferably the location, of when cell phone **1302** was lost. Thus for example, watch **1309** can light an LED (as indicator **1309b**) that an item is lost; item **1304** can indicate (through a LCD indicator **1304b**) that cell phone **1302** was lost in a cell area corresponding to downtown Boston at 15:15 pm. Specifically, in one embodiment, cell phone **1302** provides “location” information of at least a cell area; and cell phone **1302** provides “time” information by its real time clock (those skilled in the art appreciate that keys **1304**, digital watch **1309** or any other item can also include a real time clock as a matter of design choice). Accordingly, link **1320** has location and time information updated to each item **1304**, **1306**, **1309**. In leaving his cell phone at the restaurant, keys **1304**, wallet **1306**, watch **1309** receive a “cookie” deposited in internal memory indicating when and where cell phone **1302** left the network of items **1302**, **1304**, **1306**, **1309**. Accordingly, the person reviews data in either of items **1304**, **1306**, **1309** to learn of where he left his cell phone. Note that if he then lost item **1304**, he may also learn something of when item **1304** left the smaller network of items **1304**, **1306**, **1309** depending upon time and location data available. Those skilled in the art appreciate that cell phone technology enables more precise location information of where a cell phone is; and preferably this information will be provided to network system **1300** so that more precise location information is available to all network items. GPS receiver chips may also be incorporated into any of items **1302-1310** to provide the location information as described herein in connection with system **1300**.

Users of system **1300** “program” which items are in the network preferably through a personal computer interface, shown in FIG. **68**. In FIG. **68**, a personal computer **1312** connects with a transceiver controller **1314** to program a

network transceiver **1316a** (representative of any transceiver **1302a**, **1304a**, **1306a**, **1308a**, **1310a**, for example). Controller **1314** preferably includes a transceiver that wirelessly communicates with transceiver **1316a** via a data control link **1321**. Computer **1312** provides security and ID information so that items networked in system **1300** are secure relative to other users with other networks. By way of example, computer **1312** may provide a password key that is only known and used by items of network **1300**; so that other items of other networks do not communicate on link **1320**.

Note that a “wallet” or “purse” do not generally have electronics associated therewith, to provide the functionality described above. Therefore, in the preferred embodiment, a transceiver **1306a** is “attached” to a wallet or purse to provide the underlying electronics. By way of example, such a transceiver takes the form of a credit card inserted into the wallet or purse. FIG. **69** illustrates one non-electronic item **1340**, e.g., a wallet **1306**, attached to a transceiver **1340a** suitable for construction as an attachment like a smart card. Transceiver **1340a** can for example include a Bluetooth microchip **1324a** or alternatively a transmitter or transponder **1324b**. A GPS receiver **1322** can alternatively be included with transceiver **1340a**. An antenna **1326**, if needed, provides for communication along link **1320**, FIG. **67**. An LCD or LED data interface provides data and/or warnings to users reviewing item **1340** (and specifically transceiver **1340a**). A user interface **1340c** permits access to and/or modification of data or functionality of transceiver **1340a**. A real time clock **1330** preferably provides time data for time stamping “lost” item information onto network link **1320**, so that a user would know when item **1340** (or other items) were lost. In the preferred embodiment, a cookie memory stores “events” associated with lost items—e.g., a cell phone was lost at GPS coordinates X,Y at noon, providing obvious benefit in finding the lost item.

FIG. **70** and FIG. **71** show an electronic drink coaster **1400** constructed according to the invention. Internal electronics **1402** sense the weight of a drink **1404** on coaster **1400** to automatically inform a restaurant or bar, via wireless signals **1406** to a restaurant or bar receiver **1408**, that the customer needs a drink or refill. In one embodiment, a customer can also place an order from coaster **1400**. Liquid (e.g., beer) **1410** may be used to calibrate electronics **1402** so that electronics **1402** knows when glass **1412** is full or empty, to report the information as data **1406**.

FIG. **71** shows a top plan view of coaster **1400**, including customer order or calibration buttons **1410a**, **1410b**. Electronics **1402**, typically internal to coaster **1400**, include a weight detector **1420**, communications port **1422**, processor **1424**, and antenna **1426**; electronics **1402** are similar in design to many of the MMDs or EMDs described herein. Weight detector **1420** detects weight on coaster **1400**; and processor **1422** decides how to use the weight information in a meaningful way. By way of example, processor **1422** knows the approximate weight of glass **1412** onto weight detector **1420**, and once glass **1412** is filled with beer it also knows when glass **1412** is empty—creating one reporting event to bar receiver **1408**, if desired. Users of coaster **1400** can also select inputs to coaster electronics **1402** so as to place orders, wirelessly, to restaurant receiver **1408**. For example, a user of coaster **1400** can order “another beer” by pressing button **1410a**. Other order functions can of course be included with coaster **1400**, including an LED **1430** that provides the status of orders, sent to coaster **1400** via receiver **1408**.

FIG. **72** shows a package management system **1500**, and sensor **1502**, of the invention. Sensor **1502** (e.g., an MMD or EMD described herein) may be integrated directly with a

shipping label **1504** for attachment to a box or envelope to ship products, goods or other material. Sensor **1502** includes an integrated circuit **1502A**, a communications port **1502B** and a battery **1502C** to communicate data (e.g., impact, temperature, humidity) experienced by label **1504** to external devices. By way of example, a remote receiver **1508** may be used to interrogate or read data from sensor **1502**. In the preferred embodiment, sensor **1502** also includes a unique package identifier (e.g., like a bar code) so as to identify label **1504** and the goods associated therewith. A receiver **1508** linked to a transportation channel of label **1504** (e.g., a transportation channel traveled by a shipping truck **1510**) may then communicate with sensor **1502**, e.g., via wireless link **1505**, to determine whether label **1504** is in the correct channel. Accordingly, sensor **1502** helps track label **1504** and may further prevent theft of packages linked to label **1504** since the wireless system may automatically determine inappropriate location of label **1504**. A remote wireless relay tower **1512** may communicate with receiver **1508** so as to manage and track label **1504** movement and location during shipment. The invention may augment or even replace manual scanning of labels for shipping packages; the invention may also prevent theft of packages by automatically identifying inappropriate packages in shipment channels.

In the preferred embodiment, a dispenser **1514** may contain several labels similar to label **1504**; dispenser preferably issues label **1504** in a manner similar to canister **200**, FIG. **10**, so as to “power on” label **1504** with an internal time stamp. A location code and/or time code are thus preferably communicated from dispenser **1514** to sensor **1502** when label **1504** issues **1516** from dispenser **1514**.

FIG. **73** shows a product integrity tracking system **1600** of the invention. One or more sensors **1602** (e.g., each of the sensors being an MMD or EMD) attach to a customer product **1604**. Preferably, sensors **1602** “stick” to product **1604** similar to MMDs or EMDs discussed herein. Product **1604** may be any product of value, including, for example, medical devices, computers, furniture and pharmaceuticals (in the case of pharmaceuticals, sensors **1604** may for example attach to packaging containing the pharmaceuticals, or be arranged adjacent to product **1604**, such as indicated by sensor **1602A**). Typically, product **1604** initiates shipment along a shipping channel at the customer facility **1610** (e.g., a plant or laboratory). The company of facility **1610** may for example independently attach sensors **1602** to product **1604**. A shipping channel may for example include a separate shipping company such as FED EX with a truck **1612**. At the conclusion of travel, product **1604** reaches its destination **1614** (e.g., a place controlled by the customer of the company of facility **1610**). At destination **1614**, sensors **1604** are read through wireless link **1619** by an interrogating device **1620** so as to see how product **1604** fared during travel. The shipping company may have persons **1622** to take the reading or this may occur automatically at destination **1614**. Data acquired from sensor **1602** may for example include impact (or “acceleration information”) and temperature, each preferably with a time stamp to help track event occurrences (e.g., an acceleration event greater than 10 g’s at 9:10 AM, Monday). Multiple sensors **1602** provide for detecting event occurrences at different locations on product **1604**. This is particularly useful for complex medical devices that may have a relatively sturdy base and a fragile robotic arm, each with different performance specifications (e.g., each with a maximum load allowance); sensors **1602** may thus each attach to separate areas of product **1604** so that product integrity information **1619** may be determined for multiple locations. Data from device **1620** may communicate automatically, via link **1621**, and back to

facility **1610** through network **1630** (e.g., the Internet) and through a firewall **1632** so as to communicate product integrity information, in near real-time, to the company of product **1604**. In this way, this company may better manage its brand integrity of product **1604** during shipment. If a damaging event occurred to product **1604**, during shipment, that company will learn about it and may ship a replacement product (or move to refurbish product **1604**).

What is claimed is:

1. Movement monitoring device for attachment to equipment, comprising:

- a housing having an integrated circuit with (a) a detector sensitive to physical movement of the equipment when the housing is attached to the equipment and (b) a processor for processing data of the detector to determine an event experienced by the equipment; and
- a transmitter communicatively coupled with the integrated circuit for communicating the event to a remote receiver.

2. Movement monitoring device of claim 1, wherein the detector comprises an accelerometer sensitive to acceleration of the equipment.

3. Movement monitoring device of claim 1, the housing being a rigid monolithic.

4. Movement monitoring device of claim 1, the event comprising one of power, impact, acceleration.

5. Movement monitoring device of claim 1, further comprising glue or a mechanical fastener for attaching the housing to the equipment.

6. Movement monitoring device of claim 1, the transmitter communicating the event by infrared.

7. Movement monitoring device of claim 1, the transmitter communicating the event in response to an interrogation device.

8. Movement monitoring device of claim 1, the event comprising at least one movement metric selected from the group of airtime, power, impact, drop distance, jarring and spin.

9. Movement monitoring device of claim 1, the detector comprising a magnetorestrictive element.

10. Movement monitoring device of claim 1, the integrated circuit and transmitter being integrated on a single printed circuit board including terminals to hold a battery to power the integrated circuit and transmitter.

11. Movement monitoring device for attachment to equipment, comprising:

- a housing;
- a detector within the housing and sensitive to physical movement of the equipment when the housing is attached to the equipment; and
- a transmitter communicatively coupled with the detector for communicating data indicative of the physical movement to a remote receiver and in a repeated time interval.

12. Movement monitoring device of claim 11, the detector comprising one of a pressure sensor, an altitude sensor, a force sensing resistor, a piezoelectric device.

13. Environmental monitoring device for attachment to equipment, comprising:

- a housing;
- a detector within the housing and sensitive to an environment experienced by the equipment when the housing is attached to the equipment;
- a transmitter communicatively coupled with the detector for communicating data indicative of the environment to a remote receiver.

14. Environmental monitoring device of claim 13, the detector comprising one of a humidity sensor, moisture sensor, and temperature sensor.

65

15. Environmental monitoring device of claim 13, the housing being a rigid monolithic.

16. Environmental monitoring device of claim 15, further comprising glue or a mechanical fastener for attaching the housing to the equipment. 5

17. Environmental monitoring device of claim 13, further comprising a processor that processes the data to determine an event, the transmitter communicating the event by infrared.

18. Environmental monitoring device of claim 17, each of 10 the processor, detector and transmitter being integrated with a single PCB disposed within the housing and having terminals to hold a battery to power the processor and transmitter.

* * * * *

66

专利名称(译)	用于连接设备的运动监控装置		
公开(公告)号	US9267793	公开(公告)日	2016-02-23
申请号	US14/188475	申请日	2014-02-24
[标]申请(专利权)人(译)	TVIPR		
申请(专利权)人(译)	TVIPR , LLC		
当前申请(专利权)人(译)	TVIPR , LLC		
[标]发明人	VOCK CURTIS A AMSBURY BURL W JONJAK PAUL LARKIN ADRIAN YOUNGS PERRY		
发明人	VOCK, CURTIS A. AMSBURY, BURL W. JONJAK, PAUL LARKIN, ADRIAN YOUNGS, PERRY		
IPC分类号	G06F19/00 A63B24/00 A61B5/11 A61B5/00 A43B5/06 A43B3/00 G01B21/00 A63B71/06 G01P3/00 G01B7/04 G06Q10/08 G01P15/08 G01P1/12 G01G23/37 G01G23/00 G01G19/44 G01C22/00 A61B5/ /113 A63B69/00 G01B7/004		
CPC分类号	G01B21/00 A43B3/00 A43B3/0005 A43B5/06 A61B5/0002 A61B5/1112 A61B5/1117 A61B5/1126 A61B5/6807 A61B5/6833 A63B24/0062 A63B71/0605 G01B7/004 G01C22/006 G01G19/44 G01G23/ /00 G01G23/3728 G01P1/127 G01P3/00 G01P15/0891 G06F19/00 G06Q10/08 G06Q10/083 G06Q10/ /0833 A61B5/113 A61B2503/10 A61B2560/0412 A61B2562/0219 A61B2562/08 A61B2562/242 A63B69/ /00 A63B69/0028 A63B2208/12 A63B2220/20 A63B2220/30 A63B2225/50 A63B2230/01 A63B2244/10 G01P15/02		
审查员(译)	RAYMOND , EDWARD		
优先权	60/256069 2000-12-15 US 60/323601 2001-09-20 US PCT/US2001/051620 2001-12-17 WO 60/259271 2000-12-29 US 60/285032 2001-04-19 US 60/257386 2000-12-22 US 60/261359 2001-01-13 US		
其他公开文献	US20140172358A1		
外部链接	Espacenet USPTO		

摘要(译)

运动监测装置连接到设备并包括壳体和发射器。壳体包括集成电路，其具有 (a) 当壳体连接到设备时对设备的物理运动敏感的检测器和 (b) 处理器，用于处理检测器的数据以确定设备所经历的事件。发射器通信地与集成电路耦合，用于将事件传送到远程接收器。

