



US009370398B2

(12) **United States Patent**
Ladtkow et al.

(10) **Patent No.:** **US 9,370,398 B2**
(45) **Date of Patent:** **Jun. 21, 2016**

(54) **MICROWAVE ABLATION CATHETER AND METHOD OF UTILIZING THE SAME**

(2013.01); *A61B 5/01* (2013.01); *A61B 5/1114* (2013.01); *A61B 6/032* (2013.01); *A61B 6/12* (2013.01); *A61B 6/487* (2013.01); *A61B 10/0233* (2013.01); *A61B 10/04* (2013.01); *A61B 10/06* (2013.01); *A61B 1/2676* (2013.01); *A61B 5/0538* (2013.01); *A61B 5/062* (2013.01);
(Continued)

(71) Applicant: **Covidien LP**, Mansfield, MA (US)

(72) Inventors: **Casey M. Ladtkow**, Erie, CO (US); **Joseph D. Brannan**, Erie, CO (US); **Darion R. Peterson**, Boulder, CO (US); **Eric W. Larson**, Thornton, CO (US); **Kaylen J. Haley**, Westminster, CO (US); **William J. Dickhans**, Longmont, CO (US); **Jason A. Case**, Longmont, CO (US)

(58) **Field of Classification Search**
CPC *A61B 18/18*; *A61B 18/1815*; *A61B 10/04*; *A61B 1/2676*; *A61B 2019/2211*; *A61B 2019/2219*

See application file for complete search history.

(73) Assignee: **COVIDIEN LP**, Mansfield, MA (US)

(56) **References Cited**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 196 days.

U.S. PATENT DOCUMENTS
D223,367 S 4/1972 Kountz
D263,020 S 2/1982 Rau, III
(Continued)

(21) Appl. No.: **13/837,978**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Mar. 15, 2013**

CA 2832593 A1 7/2012
CN 1103807 A 6/1995

(65) **Prior Publication Data**

US 2014/0046176 A1 Feb. 13, 2014

(Continued)

OTHER PUBLICATIONS

Related U.S. Application Data

LigaSure™ Vessel Sealing System, the Seal of Confidence in General, Gynecologic, Urologic, and Laparoscopic Surgery, Sales/Product Literature, Jan. 2004.

(60) Provisional application No. 61/680,555, filed on Aug. 7, 2012, provisional application No. 61/783,921, filed on Mar. 14, 2013, provisional application No. 61/784,048, filed on Mar. 14, 2013, provisional application No. 61/784,176, filed on Mar. 14, 2013, provisional application No. 61/784,297, filed on Mar. 14, 2013, provisional application No. 61/784,407, filed on Mar. 14, 2013.

(Continued)

Primary Examiner — Robert N Wieland

(51) **Int. Cl.**
A61B 18/04 (2006.01)
A61B 18/18 (2006.01)


(Continued)

(57) **ABSTRACT**

A method for treating lung tissue of a patient is provided. A pathway to a point of interest in a lung of a patient is generated. An extended working channel is advanced transorally into the lung and along the pathway to the point of interest. The extended working channel is positioned in a substantially fixed orientation at the point interest. A tool is advanced through the extended working channel to the point of interest. The lung tissue is treated at the point of interest.

(52) **U.S. Cl.**
CPC *A61B 18/1815* (2013.01); *A61B 1/018*

25 Claims, 39 Drawing Sheets



- (51) **Int. Cl.**
- | | | | | |
|-------------------|---|-----------------|---------|---------------------|
| <i>A61B 6/12</i> | (2006.01) | 6,706,040 B2 | 3/2004 | Mahon et al. |
| <i>A61B 5/01</i> | (2006.01) | 6,723,091 B2 | 4/2004 | Goble et al. |
| <i>A61B 6/03</i> | (2006.01) | 6,740,108 B1 | 5/2004 | Just et al. |
| <i>A61B 10/02</i> | (2006.01) | 6,770,070 B1 | 8/2004 | Balbierz |
| <i>A61B 10/04</i> | (2006.01) | 6,780,183 B2 | 8/2004 | Jimenez, Jr. et al. |
| <i>A61B 10/06</i> | (2006.01) | D496,997 S | 10/2004 | Dycus et al. |
| <i>A61B 5/11</i> | (2006.01) | D499,181 S | 11/2004 | Dycus et al. |
| <i>A61B 1/018</i> | (2006.01) | 6,869,431 B2 | 3/2005 | Maguire et al. |
| <i>A61B 6/00</i> | (2006.01) | 6,893,436 B2 | 5/2005 | Woodard et al. |
| <i>A61B 1/267</i> | (2006.01) | 6,932,776 B2 | 8/2005 | Carr |
| <i>A61B 5/053</i> | (2006.01) | 6,997,925 B2 | 2/2006 | Maguire et al. |
| <i>A61B 5/00</i> | (2006.01) | 7,004,938 B2 | 2/2006 | Ormsby et al. |
| <i>A61B 18/00</i> | (2006.01) | 7,047,068 B2 | 5/2006 | Haissaguerre |
| CPC | <i>A61B 5/064</i> (2013.01); <i>A61B 5/4836</i> (2013.01); <i>A61B 5/7425</i> (2013.01); <i>A61B 5/7445</i> (2013.01); <i>A61B 2010/0216</i> (2013.01); <i>A61B 2018/00541</i> (2013.01); <i>A61B 2018/00577</i> (2013.01); <i>A61B 2018/1861</i> (2013.01) | D525,361 S | 7/2006 | Hushka |
| | | 7,089,063 B2 | 8/2006 | Lesh et al. |
| | | 7,113,832 B2 | 9/2006 | Longo |
| | | D531,311 S | 10/2006 | Guerra et al. |
| | | D533,942 S | 12/2006 | Kerr et al. |
| | | D535,027 S | 1/2007 | James et al. |
| | | 7,197,356 B2 | 3/2007 | Carr |
| | | D541,418 S | 4/2007 | Schechter et al. |
| | | 7,200,445 B1 | 4/2007 | Dalbec et al. |
| | | D541,938 S | 5/2007 | Kerr et al. |
| | | 7,233,820 B2 | 6/2007 | Gilboa |
| | | 7,261,001 B2 | 8/2007 | Heijnsdijk et al. |
| | | 7,263,398 B2 | 8/2007 | Carr |
| | | 7,285,116 B2 | 10/2007 | de la Rama et al. |
| | | 7,294,125 B2 | 11/2007 | Phalen et al. |
| | | 7,300,436 B2 | 11/2007 | Penny et al. |
| | | 7,303,558 B2 | 12/2007 | Swanson |
| | | D564,662 S | 3/2008 | Moses et al. |
| | | 7,402,168 B2 | 7/2008 | Sanderson et al. |
| | | 7,410,486 B2 | 8/2008 | Fuimaono et al. |
| | | D576,932 S | 9/2008 | Strehler |
| | | 7,467,015 B2 | 12/2008 | van der Weide |
| | | 7,507,229 B2 | 3/2009 | Hewitt et al. |
| | | D594,736 S | 6/2009 | Esjunin |
| | | D594,737 S | 6/2009 | Kelly et al. |
| | | 7,559,916 B2 | 7/2009 | Smith et al. |
| | | 7,608,056 B2 | 10/2009 | Kennedy, II |
| | | 7,611,508 B2 | 11/2009 | Yang et al. |
| | | D606,203 S | 12/2009 | Husheer et al. |
| | | D613,412 S | 4/2010 | DeCarlo |
| | | 7,713,259 B2 | 5/2010 | Gosiengfiao et al. |
| | | 7,734,330 B2 | 6/2010 | Carr |
| | | 7,769,469 B2 | 8/2010 | Carr et al. |
| | | 7,850,685 B2 | 12/2010 | Kunis et al. |
| | | D634,010 S | 3/2011 | DeCarlo |
| | | 7,921,855 B2 | 4/2011 | Danek et al. |
| | | 7,933,660 B2 | 4/2011 | Carr |
| | | 7,993,351 B2 | 8/2011 | Worley et al. |
| | | 8,152,795 B2 | 4/2012 | Farr et al. |
| | | 8,182,466 B2 | 5/2012 | Stehr et al. |
| | | 8,226,566 B2 | 7/2012 | Nita |
| | | 8,251,987 B2 | 8/2012 | Willyard |
| | | 8,289,551 B2 | 10/2012 | Wu |
| | | 8,292,881 B2 | 10/2012 | Brannan et al. |
| | | 8,340,740 B2 | 12/2012 | Holzer et al. |
| | | D681,810 S | 5/2013 | Decarlo |
| | | 8,476,242 B2 | 7/2013 | Mon |
| | | 8,632,461 B2 | 1/2014 | Glossop |
| | | 8,768,485 B2 | 7/2014 | Hancock et al. |
| | | 8,951,225 B2 | 2/2015 | Evard et al. |
| | | 2002/0022836 A1 | 2/2002 | Goble et al. |
| | | 2002/0042564 A1 | 4/2002 | Cooper et al. |
| | | 2003/0191451 A1 | 10/2003 | Gilmartin |
| | | 2004/0082860 A1 | 4/2004 | Haissaguerre |
| | | 2004/0097805 A1 | 5/2004 | Verard et al. |
| | | 2004/0133254 A1 | 7/2004 | Sterzer et al. |
| | | 2004/0176740 A1 | 9/2004 | Chouinard |
| | | 2005/0043713 A1 | 2/2005 | Zhou |
| | | 2005/0080334 A1 | 4/2005 | Willis |
| | | 2005/0215942 A1 | 9/2005 | Abrahamson et al. |
| | | 2005/0273006 A1 | 12/2005 | Stewart et al. |
| | | 2006/0009833 A1 | 1/2006 | Chobotov et al. |
| | | 2006/0089637 A1 | 4/2006 | Werneth et al. |
| | | 2006/0167416 A1 | 7/2006 | Mathis et al. |
| | | 2006/0241564 A1 | 10/2006 | Corcoran et al. |
| | | 2006/0253102 A1 | 11/2006 | Nance et al. |
- (52) **U.S. Cl.**
- (56) **References Cited**
- U.S. PATENT DOCUMENTS
- | | | |
|--------------|---------|------------------|
| D266,842 S | 11/1982 | Villers et al. |
| D278,306 S | 4/1985 | McIntosh |
| 4,583,589 A | 4/1986 | Kasevich |
| D295,893 S | 5/1988 | Sharkany et al. |
| D295,894 S | 5/1988 | Sharkany et al. |
| 5,301,687 A | 4/1994 | Wong et al. |
| 5,370,644 A | 12/1994 | Langberg |
| D354,218 S | 1/1995 | Van de Peer |
| 5,545,137 A | 8/1996 | Rudie et al. |
| 5,603,697 A | 2/1997 | Grundy et al. |
| 5,624,392 A | 4/1997 | Saab |
| 5,693,082 A | 12/1997 | Warner et al. |
| 5,741,249 A | 4/1998 | Moss et al. |
| 5,974,343 A | 10/1999 | Brevard et al. |
| 5,980,505 A | 11/1999 | Wilson |
| 5,993,447 A | 11/1999 | Blewett et al. |
| 5,995,875 A | 11/1999 | Blewett et al. |
| 6,014,581 A | 1/2000 | Whayne et al. |
| D424,693 S | 5/2000 | Pruter |
| D424,694 S | 5/2000 | Tetzlaff et al. |
| D425,201 S | 5/2000 | Tetzlaff et al. |
| 6,061,551 A | 5/2000 | Sorrells et al. |
| 6,106,524 A | 8/2000 | Eggers et al. |
| 6,117,101 A | 9/2000 | Diederich et al. |
| 6,139,527 A | 10/2000 | Laufer et al. |
| 6,186,978 B1 | 2/2001 | Samson et al. |
| 6,188,355 B1 | 2/2001 | Gilboa |
| 6,210,367 B1 | 4/2001 | Carr |
| 6,235,024 B1 | 5/2001 | Tu |
| 6,277,113 B1 | 8/2001 | Berube |
| D449,886 S | 10/2001 | Tetzlaff et al. |
| 6,355,016 B1 | 3/2002 | Bagaoisan et al. |
| D457,958 S | 5/2002 | Dycus et al. |
| D457,959 S | 5/2002 | Tetzlaff et al. |
| 6,398,781 B1 | 6/2002 | Goble et al. |
| 6,485,486 B1 | 11/2002 | Trembly et al. |
| 6,496,737 B2 | 12/2002 | Rudie et al. |
| 6,496,738 B2 | 12/2002 | Carr |
| 6,514,249 B1 | 2/2003 | Maguire et al. |
| 6,547,788 B1 | 4/2003 | Maguire et al. |
| 6,599,288 B2 | 7/2003 | Maguire et al. |
| 6,629,951 B2 | 10/2003 | Laufer et al. |
| 6,629,974 B2 | 10/2003 | Penny et al. |
| 6,635,055 B1 | 10/2003 | Cronin |
| 6,645,234 B2 | 11/2003 | Evans et al. |
| 6,652,515 B1 | 11/2003 | Maguire et al. |
| 6,676,657 B2 | 1/2004 | Wood |
| D487,039 S | 2/2004 | Webster et al. |

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0027385 A1 2/2007 Brister et al.
 2007/0060944 A1 3/2007 Boldenow et al.
 2007/0088319 A1 4/2007 Martone
 2007/0129717 A1 6/2007 Brown et al.
 2007/0185554 A1 8/2007 Appling et al.
 2007/0282319 A1 12/2007 van der Weide et al.
 2007/0287912 A1 12/2007 Khuri-Yakub et al.
 2008/0091169 A1 4/2008 Heideman et al.
 2008/0147056 A1 6/2008 van der Weide et al.
 2008/0208031 A1 8/2008 Kurpad et al.
 2008/0208039 A1 8/2008 Kurpad et al.
 2008/0228167 A1 9/2008 Mittermeyer et al.
 2008/0255507 A1 10/2008 Mushtaha
 2008/0262342 A1 10/2008 Averbuch
 2008/0262472 A1 10/2008 Lunn et al.
 2009/0076409 A1 3/2009 Wu et al.
 2009/0187180 A1 7/2009 Brannan
 2009/0222002 A1 9/2009 Bonn et al.
 2009/0234220 A1 9/2009 Maschke
 2009/0312754 A1 12/2009 Lenihan et al.
 2010/0004631 A1 1/2010 Zhou
 2010/0036369 A1 2/2010 Hancock
 2010/0076424 A1 3/2010 Carr
 2010/0160719 A1 6/2010 Kassab et al.
 2010/0185191 A1 7/2010 Carr et al.
 2010/0249754 A1 9/2010 Griffin et al.
 2010/0256621 A1 10/2010 Babkin et al.
 2010/0262134 A1 10/2010 Jensen et al.
 2010/0268196 A1 10/2010 Hastings et al.
 2010/0305559 A1 12/2010 Brannan et al.
 2011/0004205 A1 1/2011 Chu et al.
 2011/0029049 A1 2/2011 Vertikov et al.
 2011/0034913 A1 2/2011 Brannan
 2011/0034917 A1 2/2011 Brannan
 2011/0040300 A1 2/2011 Brannan
 2011/0054458 A1 3/2011 Behnke
 2011/0077634 A1 3/2011 Brannan
 2011/0085720 A1 4/2011 Averbuch
 2011/0118721 A1 5/2011 Brannan
 2011/0130750 A1 6/2011 Ormsby et al.
 2011/0166518 A1 7/2011 Nguyen et al.
 2011/0166519 A1 7/2011 Nguyen et al.
 2011/0282336 A1 11/2011 Brannan et al.
 2011/0301587 A1 12/2011 Deem et al.
 2012/0029359 A1 2/2012 Sterzer et al.
 2012/0035603 A1 2/2012 Lenihan
 2012/0065481 A1 3/2012 Hunter et al.
 2012/0071822 A1 3/2012 Romo et al.
 2012/0078175 A1 3/2012 Vreeman
 2012/0078230 A1 3/2012 Lowe et al.
 2012/0101370 A1 4/2012 Razaque et al.
 2012/0277730 A1 11/2012 Salahieh et al.
 2013/0116679 A1* 5/2013 Van Der Weide et al. 606/33
 2013/0137977 A1 5/2013 Eder
 2013/0197481 A1 8/2013 Guo et al.
 2013/0197482 A1 8/2013 Akitomo
 2014/0024909 A1* 1/2014 Vij et al. 600/373
 2014/0094793 A1 4/2014 Sharonov
 2015/0141985 A1 5/2015 Mayse et al.

FOREIGN PATENT DOCUMENTS

DE 390937 C 3/1924
 DE 1099658 B 2/1961
 DE 1139927 B 11/1962
 DE 1149832 B 6/1963
 DE 1439302 A1 1/1969
 DE 2439587 A1 2/1975
 DE 2455174 A1 5/1975
 DE 2407559 A1 8/1975
 DE 2415263 A1 10/1975
 DE 2429021 A1 1/1976
 DE 2460481 A1 6/1976
 DE 2602517 A1 7/1976

DE 2504280 A1 8/1976
 DE 2627679 A1 1/1977
 DE 2540968 A1 3/1977
 DE 2820908 A1 11/1978
 DE 2803275 A1 8/1979
 DE 2823291 A1 11/1979
 DE 2946728 A1 5/1981
 DE 3143421 A1 5/1982
 DE 3045996 A1 7/1982
 DE 3120102 A1 12/1982
 DE 3510586 A1 10/1986
 DE 3604823 A1 8/1987
 DE 8712328 U1 2/1988
 DE 3711511 C1 6/1988
 DE 3904558 A1 8/1990
 DE 3942998 A1 7/1991
 DE 4238263 A1 5/1993
 DE 04303882 C2 2/1995
 DE 4339049 A1 5/1995
 DE 29616210 U1 11/1996
 DE 19608716 C1 4/1997
 DE 19751106 A1 5/1998
 DE 19717411 A1 11/1998
 DE 19751108 A1 5/1999
 DE 19801173 C1 7/1999
 DE 19848540 A1 5/2000
 DE 10224154 A1 12/2003
 DE 10310765 A1 9/2004
 DE 10328514 B3 3/2005
 DE 102004022206 A1 12/2005
 DE 202005015147 U1 2/2006
 DE 102009015699 A1 5/2010
 EP 0 246 350 A1 11/1987
 EP 0 521 264 A2 1/1993
 EP 0 556 705 A1 8/1993
 EP 0 558 429 A1 9/1993
 EP 0 648 515 A1 4/1995
 EP 0 836 868 A2 4/1998
 EP 0 882 955 A1 12/1998
 EP 1034747 A1 9/2000
 EP 1034748 9/2000
 EP 1055400 11/2000
 EP 1 159 926 A2 12/2001
 EP 2147651 A1 1/2010
 EP 2322113 A1 5/2011
 FR 179 607 11/1906
 FR 1 275 415 A 11/1961
 FR 1 347 865 A 1/1964
 FR 2 235 669 A1 1/1975
 FR 2 276 027 A1 1/1976
 FR 2 313 708 A1 12/1976
 FR 2 502 935 A1 10/1982
 FR 2 517 953 A1 6/1983
 FR 2 573 301 A1 5/1986
 FR 2 862 813 A1 5/2005
 FR 2 864 439 A1 7/2005
 JP 5-5106 1/1993
 JP 05-40112 2/1993
 JP 06343644 A 12/1994
 JP 07265328 A 10/1995
 JP 08056955 A 3/1996
 JP 08252263 A 10/1996
 JP 09000492 A 1/1997
 JP 09010223 A 1/1997
 JP 11244298 A 9/1999
 JP 2000342599 A 12/2000
 JP 2000350732 A 12/2000
 JP 2001003776 A 1/2001
 JP 2001008944 A 1/2001
 JP 2001029356 A 2/2001
 JP 2001037775 A 2/2001
 JP 2001128990 A 5/2001
 JP 2001231870 A 8/2001
 JP 2008142467 A 6/2008
 KR 20070093068 A 9/2007
 KR 20100014406 A 2/2010
 KR 20120055063 A 5/2012
 SU 166452 11/1964
 SU 401367 A1 10/1973

(56) **References Cited**

FOREIGN PATENT DOCUMENTS

SU	727201	A2	4/1980
WO	94/16632	A1	8/1994
WO	97/24074	A1	7/1997
WO	00/10456	A1	3/2000
WO	00/36985	A2	6/2000
WO	0057811	A1	10/2000
WO	0100114	A1	1/2001
WO	01/67035	A1	9/2001
WO	02/45790	A2	6/2002
WO	2006084676	A1	8/2006
WO	2008/068485	A2	6/2008
WO	2010/035831	A1	4/2010
WO	2011/140087	A2	11/2011
WO	2011139589	A2	11/2011

OTHER PUBLICATIONS

Livraghi et al., (1995) "Saline-enhanced RF Tissue Ablation in the Treatment of Liver Metastases", *Radiology*, p. 140 (Abstr).

Lyndon B. Johnson Space Center, Houston, Texas, "Compact Directional Microwave Antenna for Localized Heating," NASA Tech Briefs, Mar. 2008.

M. A. Astrahan, "A Localized Current Field Hyperthermia System for Use with 192-Iridium Interstitial Implants" *Medical Physics*. 9(3), May/June. 1982.

Magdy F. Iskander et al., "Design Optimization of Interstitial Antennas", *IEEE Transactions on Biomedical Engineering*, vol. 36, No. 2, Feb. 1989, pp. 238-246.

McGahan et al., (1995) "Percutaneous Ultrasound-guided Radiofrequency Electrocautery Ablation of Prostate Tissue in Dogs", *Acad Radiol*, vol. 2, No. 1: pp. 61-65.

McLellan et al., "Vessel Sealing for Hemostasis During Pelvic Surgery" *Int'l Federation of Gynecology and Obstetrics FIGO World Congress 2000*, Washington, DC.

MDTECH product literature (Dec. 1999) "FlexStrand": product description, 1 page.

MDTECH product literature (Mar. 2000) I'D Wire: product description, 1 page.

Medtrex Brochure "The O.R. Pro 300" 1 page, Sep. 1998.

Michael Choti, "Abdominoperineal Resection with the LigaSure™ Vessel Sealing System and LigaSure™ Atlas 20 cm Open Instrument" *Innovations That Work*, Jun. 2003.

Muller et al., "Extended Left Hemicolectomy Using the LigaSure™ Vessel Sealing System" *Innovations That Work*. L.J, Sep. 1999.

Murakami, R. et al., (1995). "Treatment of Hepatocellular Carcinoma: Value of Percutaneous Microwave Coagulation," *American Journal of Radiology (AJR)* 164:1159-1164.

Ni Wei et al., "A Signal Processing Method for the Coriolis Mass Flowmeter Based on a Normalized . . ." *Journal of Applied Sciences-Yingyong Kexue Xuebao*, Shanghai CN, vol. 23, No. 2:(Mar. 2005); pp. 160-184.

Ogden, "Goertzel Alternative to the Fourier Transform" Jun. 1993 pp. 485-487 *Electronics World*; Reed Business Publishing, Sutton, Surrey, BG, vol. 99, No. 9, 1687.

Olsson M.D. et al., "Radical Cystectomy in Females" *Current Surgical Techniques in Urology*, vol. 14, Issue 3, 2001.

Organ, L W., "Electrophysiologic Principles of Radiofrequency Lesion Making" *Appl. Neurophysiol*, vol. 39: pp. 69-76 (1976/77).

P.R. Stauffer et al., "Interstitial Heating Technologies", *Thermoradiotherapy and Thermochemotherapy* (1995) vol. I, Biology, Physiology, Physics, pp. 279-320.

Palazzo et al., "Randomized clinical trial of LigaSure™ versus open haemorrhoidectomy" *British Journal of Surgery* 2002,89,154-157 "Innovations in Electrosurgery" Sales/Product Literature; Dec. 31, 2000.

Paul G. Horgan, "A Novel Technique for Parenchymal Division During Hepatectomy" *The American Journal of Surgery*, vol. 181, No. 3, Apr. 2001, pp. 236-237.

Peterson et al., "Comparison of Healing Process Following Ligation with Sutures and Bipolar Vessel Sealing" *Surgical Technology International* (2001).

R. Gennari et al., (Jun. 2000) "Use of Technetium-99m-Labeled Colloid Albumin for Preoperative and Intraoperative Localization of Non palpable Breast Lesions," *American College of Surgeons*. 190(6):692-699.

Valleylab Brochure, "Reducing Needlestick Injuries in the Operating Room" 1 page, Mar. 2001.

Reidenbach, (1995) "First Experimental Results with Special Applicators for High-Frequency Interstitial Thermotherapy", *Society Minimally Invasive Therapy*, 4(Suppl 1):40 (Abstr).

Richard Wolf Medical Instruments Corp. Brochure, "Kleppinger Bipolar Forceps & Bipolar Generator" 3 pages, Jan. 1989.

Rothenberg et al., "Use of the LigaSure™ Vessel Sealing System in Minimally Invasive Surgery in Children" *Int'l Pediatric Endosurgery Group (I PEG)* 2000.

Sayfan et al., "Sutureless Closed Hemorrhoidectomy: A New Technique" *Annals of Surgery*, vol. 234, No. 1, Jul. 2001, pp. 21-24.

Sengupta et al., "Use of a Computer-Controlled Bipolar Diathermy System in Radical Prostatectomies and Other Open Urological Surgery" *ANZ Journal of Surgery* (2001) 71.9 pp. 538-540.

Sigel et al., "The Mechanism of Blood Vessel Closure by High Frequency Electrocoagulation" *Surgery Gynecology & Obstetrics*, Oct. 1965 pp. 823-831.

Solbiati et al., (2001) "Percutaneous Radio-frequency Ablation of Hepatic Metastases from Colorectal Cancer: Longterm Results in 117 Patients", *Radiology*, vol. 221, pp. 159-166.

Solbiati et al. (1995) "Percutaneous US-guided RF Tissue Ablation of Liver Metastases: Long-term Follow-up", *Radiology*, pp. 195-203.

Strasberg et al., "Use of a Bipolar Vessel-Sealing Device for Parenchymal Transection During Liver Surgery" *Journal of Gastrointestinal Surgery*, vol. 6, No. 4, Jul./Aug. 2002 pp. 569-574.

Sugita et al., "Bipolar Coagulator with Automatic Thermocontrol" *J. Neurosurg.*, vol. 41, Dec. 1944, pp. 777-779.

Sylvain Labonte et al., "Monopole Antennas for Microwave Catheter Ablation", *IEEE Trans. On Microwave Theory and Techniques*, vol. 44, No. 10, pp. 1832-1840, Oct. 1995.

T. Matsukawa et al., "Percutaneous Microwave Coagulation Therapy in Liver Tumors", *Acta Radiologica*, vol. 38, pp. 410-415, 1997.

T. Seki et al., (1994) "Ultrasonically Guided Percutaneous Microwave Coagulation Therapy for Small Hepatocellular Carcinoma," *Cancer* 74(3):817825.

Urologix, Inc.-Medical Professionals: Targis™ Technology (Date Unknown). "Overcoming the Challenge" located at: <<http://www.urologix.com/medicaUtechnology.html>> Nov. 18, 1999; 3 pages.

Urrutia et al., (1988). "Retractable-Barb Needle for Breast Lesion Localization: Use in 60 Cases," *Radiology* 169 (3):845-847.

Valleylab Brochure, "Valleylab Electroshield Monitoring System" 2 pages, Nov. 1995.

ValleyLab Brochure, "Electrosurgery: A Historical Overview", *Innovations in Electrosurgery*, 1999.

Vallfors et al., "Automatically Controlled Bipolar Electrocoagulation-COA-COMP" *Neurosurgical Review* 7:2-3 (1984) pp. 187-190.

W. Scott Helton, "LigaSure™ Vessel Sealing System: Revolutionary Hemostasis Product for General Surgery" *Sales/Product Literature* 1999.

Wald et al., "Accidental Burns", *JAMA*, Aug. 16, 1971, vol. 217, No. 7, pp. 916-921.

Walt Boyles, "Instrumentation Reference Book", 2002, Butterworth-Heinemann, pp. 262-264.

Wonnell et al., "Evaluation of Microwave and Radio Frequency Catheter Ablation in a Myocardium-Equivalent Phantom Model", *IEEE Transactions on Biomedical Engineering*, vol. 39, No. 10, Oct. 1992; pp. 1086-1095.

U.S. Appl. No. 08/136,098, filed Oct. 14, 1993; Roger A. Stern.

U.S. Appl. No. 08/483,742, filed Jun. 7, 1995; Roger A. Stern.

U.S. Appl. No. 13/419,981, filed Mar. 14, 2012, Joseph D. Brannan.

U.S. Appl. No. 13/430,810, filed Mar. 27, 2012, Joseph D. Brannan.

U.S. Appl. No. 13/440,690, filed Apr. 5, 2012, Joseph D. Brannan.

U.S. Appl. No. 13/460,440, filed Apr. 30, 2012, Arnold V. DeCarlo.

U.S. Appl. No. 13/464,021, filed May 4, 2012, Joseph D. Brannan.

(56) References Cited

OTHER PUBLICATIONS

- U.S. Appl. No. 13/477,260, filed May 22, 2012, William R. Reid, Jr.
- U.S. Appl. No. 13/477,320, filed May 22, 2012, Joseph D. Brannan.
- U.S. Appl. No. 13/711,086, filed Dec. 11, 2012, Joseph D. Brannan.
- U.S. Appl. No. 13/835,183, filed Mar. 15, 2013, Arts.
- U.S. Appl. No. 13/835,513, filed Mar. 15, 2013, Brannan.
- U.S. Appl. No. 13/836,014, filed Mar. 15, 2013, Arts.
- U.S. Appl. No. 13/836,353, filed Mar. 15, 2013, Arts.
- U.S. Appl. No. 13/839,562, filed Mar. 15, 2013, Zheng.
- U.S. Appl. No. 13/867,834, filed Jul. 22, 2013, Brannan.
- U.S. Appl. No. 13/871,142, filed Apr. 26, 2013, Ohri.
- U.S. Appl. No. 13/886,080, filed May 2, 2013, Bahney.
- U.S. Appl. No. 13/889,989, filed May 8, 2013, Lee.
- U.S. Appl. No. 13/903,668, filed May 28, 2013, Podhajsky.
- U.S. Appl. No. 13/904,478, filed May 29, 2013, Ohri.
- U.S. Appl. No. 13/908,463, filed Jun. 3, 2013, Brannan.
- U.S. Appl. No. 13/908,555, filed Jun. 3, 2013, Dunning.
- U.S. Appl. No. 13/920,367, filed Jun. 18, 2013, Sharonov.
- U.S. Appl. No. 13/920,411, filed Jun. 18, 2013, Sharonov.
- U.S. Appl. No. 13/922,006, filed Jun. 19, 2013, Nau.
- U.S. Appl. No. 13/942,833, filed Jul. 16, 2013, Sharonov.
- U.S. Appl. No. 13/942,864, filed Jul. 16, 2013, Sharonov.
- U.S. Appl. No. 13/943,452, filed Jul. 16, 2013, Behnke.
- U.S. Appl. No. 13/945,519, filed Jul. 18, 2013, Prakash.
- U.S. Appl. No. 13/945,718, filed Jul. 18, 2013, Rossetto.
- U.S. Appl. No. 13/957,087, filed Aug. 1, 2013, Brannan.
- U.S. Appl. No. 13/973,543, filed Aug. 2, 2013, Orszulak.
- U.S. Appl. No. 14/011,414, filed Aug. 27, 2013, Ohri.
- U.S. Appl. No. 14/011,438, filed Aug. 27, 2013, Ohri.
- U.S. Appl. No. 14/014,937, filed Aug. 30, 2013, Willyard.
- U.S. Appl. No. 14/017,995, filed Sep. 4, 2013, Brannan.
- U.S. Appl. No. 14/018,081, filed Sep. 4, 2013, Brannan.
- Alexander et al., "Magnetic Resonance Image-Directed Stereotactic Neurosurgery: Use of Image Fusion with Computerized Tomography to Enhance Spatial Accuracy" *Journal Neurosurgery*, 83 (1995), pp. 271-276.
- Anderson et al., "A Numerical Study of Rapid Heating for High Temperature Radio Frequency Hyperthermia" *International Journal of Bio-Medical Computing*, 35 (1994), pp. 297-307.
- Anonymous. (1999) Auto Suture MIBB Site Marker: Single Use Clip Applier, United States Surgical (Product instructions), 2 pages.
- Anonymous. (2001) Disposable Chiba Biopsy Needles and Trays, Biopsy and Special Purpose Needles Cook Diagnostic and Interventional Products Catalog (products list), 4 pages.
- Anonymous. (1987) Homer Mammalok™ Breast Lesion Needle/Wire Localizer, Namic® Angiographic Systems Division, Glens Falls, New York, (Hospital products price list), 4 pages.
- Anonymous. (1999) MIBB Site Marker, United States Surgical (Sales brochure), 4 pages.
- Anonymous. Blunt Tubes with Finished Ends. Pointed Cannula, Popper & Sons Biomedical Instrument Division, (Products Price List), one page, Jul. 19, 2000.
- Anonymous. Ground Cannulae, ISPG, New Milford, CT, (Advertisement) one page, Jul. 19, 2000.
- B. Levy M.D. et al., "Randomized Trial of Suture Versus Electrocautery Bipolar Vessel Sealing in Vaginal Hysterectomy" *Obstetrics & Gynecology*, vol. 102, No. 1, Jul. 2003. cited by applicant.
- B. Levy M.D. et al., "Update on Hysterectomy New Technologies and Techniques" *OBG Management*, Feb. 2003. cited by applicant.
- B. Levy M.D., "Use of a New Vessel Ligation Device During Vaginal Hysterectomy" FIGO 2000, Washington, D.C. cited by applicant.
- B. F. Mullan et al., (May 1999) "Lung Nodules: Improved Wire for CT-Guided Localization," *Radiology* 211:561-565.
- B. T. Heniford M.D. et al., "Initial Research and Clinical Results with an Electrothermal Bipolar Vessel Sealer" Oct. 1999. cited by applicant.
- Bergdahl et al., "Studies on Coagulation and the Development of an Automatic Computerized Bipolar Coagulator" *Journal of Neurosurgery* 75:1 (Jul. 1991), pp. 148-151. cited by applicant.
- Bulletin of the American Physical Society, vol. 47, No. 5, Aug. 2002, p. 41. cited by applicant.
- C. F. Gottlieb et al., "Interstitial Microwave Hyperthermia Applicators having Submillimetre Diameters", *Int. J. Hyperthermia*, vol. 6, No. 3, pp. 707-714, 1990. cited by applicant.
- C. H. Durney et al., "Antennas for Medical Applications", *Antenna Handbook: Theory Application and Design*, p. 24-40, Van Nostrand Reinhold, 1988 New York, V.T. Lo, S.W. Lee. cited by applicant.
- Carbonell et al., "Comparison of the Gyrus PlasmaKinetic Sealer and the Valleylab LigaSure™. Device in the Hemostasis of Small, Medium, and Large-Sized Arteries" *Carolinas Laparoscopic and Advanced Surgery Program, Carolinas Medical Center, Charlotte, NC 2003*. cited by applicant.
- Carus et al., "Initial Experience With the LigaSure™. Vessel Sealing System in Abdominal Surgery" *Innovations That Work*, Jun. 2002. cited by applicant.
- Chicharo et al., "A Sliding Goertzel Algorithm" Aug. 1996 DOS pp. 283-297 *Signal Processing, Elsevier Science Publishers B.V. Amsterdam, NL*, vol. 52, No. 3. cited by applicant.
- Chou, C.K., (1995) "Radiofrequency Hyperthermia in Cancer Therapy," Chapter 94 In *Biologic Effects of Nonionizing Electromagnetic Fields*, CRC Press, Inc., pp. 1424-1428. cited by applicant.
- Chung et al., "Clinical Experience of Sutureless Closed Hemorrhoidectomy with LigaSure™" *Diseases of the Colon & Rectum*, vol. 46, No. 1, Jan. 2003.
- Cosman et al., "Methods of Making Nervous System Lesions" in William RH, Rengachary SS (eds): *Neurosurgery*, New York: McGraw-Hill, vol. 111, (1984), pp. 2490-2499. cited by applicant.
- Cosman et al., "Radiofrequency Lesion Generation and its Effect on Tissue Impedance", *Applied Neurophysiology*, 51:230-242, 1988. cited by applicant.
- Cosman et al., "Theoretical Aspects of Radiofrequency Lesions in the Dorsal Root Entry Zone" *Neurosurgery* 15: (1984), pp. 945-950. cited by applicant.
- Crawford et al., "Use of the LigaSure™. Vessel Sealing System in Urologic Cancer Surger" *Grand Rounds in Urology 1999*, vol. 1, Issue 4, pp. 10-17. cited by applicant.
- Dulemba et al., "Use of a Bipolar Electrothermal Vessel Sealer in Laparoscopically Assisted Vaginal Hysterectomy" *Sales/Product Literature; Jan. 2004*. cited by applicant.
- E. David Crawford, "Evaluation of a New Vessel Sealing Device in Urologic Cancer Surgery" *Sales/Product Literature 2000*. cited by applicant.
- E. David Crawford, "Use of a Novel Vessel Sealing Technology in Management of the Dorsal Venous Complex" *Sales/ Product Literature 2000*. cited by applicant.
- Esterline, "Light Key Projection Keyboard" *Advanced Input Systems*, located at: <<http://www.advanced-input.com/lightkey>> 2002. Esterline Product Literature, "Light Key: Visualize a Virtual Keyboard. One With No Moving Parts", Nov. 1, 2003; 4 pages. cited by applicant.
- Geddes et al., "The Measurement of Physiologic Events by Electrical Impedance" *Am. J. MI*, Jan. Mar. 1964, pp. 16-27.
- Goldberg et al., "Image-guided Radiofrequency Tumor Ablation: Challenges and Opportunities—Part I", (2001) *JVasc. Interv. Radiol*, vol. 12, pp. 1021-1032.
- Goldberg et al. (1995) "Saline-enhanced RF Ablation: Demonstration of Efficacy and Optimization of Parameters", *Radiology*, 197(P): 140 (Abstr).
- Goldberg et al., "Tissue Ablation with Radiofrequency: Effect of Probe Size, Gauge, Duration, and Temperature on Lesion Volume" *Acad Radio* (1995) vol. 2, No. 5, pp. 399-404.
- H. Schwarzmaier et al., "Magnetic Resonance Imaging of Microwave Induced Tissue Heating" *Dept. of Laser Medicine & Dept. of Diagnostic Radiology; Heinrich-Heine-University, Duesseldorf, Germany; Dec. 8, 1994; pp. 729-731*.
- Heniford et al., "Initial Results with an Electrothermal Bipolar Vessel Sealer" *Surgical Endoscopy* (2001) 15:799-801.
- Herman et al., "Laparoscopic Intestinal Resection With the LigaSure™ Vessel Sealing System: A Case Report" *Innovations That Work*, Feb. 2002.

(56)

References Cited

OTHER PUBLICATIONS

Humphries Jr. et al., "Finite-Element Codes to Model Electrical Heating and Non-Linear Thermal Transport in Biological Media", Proc. ASME HTD-355, 131 (1997).

Ian D. McRury et al., The Effect of Ablation Sequence and Duration on Lesion Shape Using Rapidly Pulsed Radiofrequency Energy Through Electrodes, Feb. 2000, Springer Netherlands, vol. 4; No. 1, pp. 307-320.

Jarrett et al., "Use of the LigaSure™ Vessel Sealing System for Peri-Hilar Vessels in Laparoscopic Nephrectomy" Sales/Product Literature 2000.

Johnson et al., "Evaluation of a Bipolar Electrothermal Vessel Sealing Device in Hemorrhoidectomy" Sales/Product Literature, Jan. 2004.

Johnson, "Evaluation of the LigaSure™ Vessel Sealing System in Hemorrhoidectomy" American College of Surgeons (ACS) Clinic La Congress Poster (2000).

Johnson et al., "New Low-Profile Applicators for Local Heating of Tissues", IEEE Transactions on Biomedical Engineering, vol. BME-31, No. 1, Jan. 1984, pp. 28-37.

Johnson, "Use of the LigaSure™ Vessel Sealing System in Bloodless Hemorrhoidectomy" Innovations That Work, Mar. 2000.

Joseph G. Andriole M.D. et al., "Biopsy Needle Characteristics Assessed in the Laboratory", Radiology 148: 659-662, Sep. 1983.

Joseph Ortenberg, "LigaSure™ System Used in Laparoscopic 1st and 2nd Stage Orchiopexy" Innovations That Work, Nov. 2002.

Kennedy et al., "High-burst-strength, feedback-controlled bipolar vessel sealing" Surgical Endoscopy (1998) 12: 876-878.

Kopans, D.B. et al., (Nov. 1985) "Spring Hookwire Breast Lesion Localizer: Use with Rigid-Compression. Mammographic Systems," Radiology 157(2):537-538.

Koyle et al., "Laparoscopic Palomo Varicocele Ligation in Children and Adolescents" Pediatric Endosurgery & Innovative Techniques, vol. 6, No. 1, 2002.

Search Report dated Nov. 4, 2015 received with Office Action dated Nov. 16, 2015 issued in Chinese Patent Application No. 201380041763.4 by the Chinese Patent Office and English translation (4 pages).

International Search Report corresponding to PCT/US2013/052166, completed Nov. 15, 2013 and mailed Nov. 18, 2013; (12 pp).

International Search Report corresponding to PCT/US2013/052182, completed Nov. 6, 2013 and mailed Nov. 6, 2013; (14 pp).

International Search Report corresponding to PCT/US2013/052187, completed Nov. 4, 2013 and mailed Nov. 4, 2013; (19 pp).

International Search Report corresponding to PCT/US2013/052196, completed Nov. 11, 2013 and mailed Nov. 11, 2013; (21 pp).

Extended European Search Report corresponding to European Patent Application No. 13827919.5, completed Apr. 1, 2016 and mailed Apr. 11, 2016; (9 pp).

Extended European Search Report corresponding to European Patent Application No. 13828360.1, completed Apr. 1, 2016 and mailed Apr. 11, 2016; (9 pp).

Extended European Search Report Corresponding to European Patent Application No. 13827441.0, completed Apr. 5, 2016 and mailed Apr. 14, 2016; (9 pp).

* cited by examiner





Fig. 1






Fig. 4




FIG. 6




FIG. 7




FIG. 8




FIG. 9




Fig. 10




FIG. 11




Fig. 12B

Fig. 12A




Fig. 12C




Fig. 13A




Fig. 13B




Fig. 14




Fig. 15A




Fig. 15B




Fig. 16A




Fig. 16B




Fig. 16C




Fig. 16D




Fig. 16E




FIG. 17

FIG. 18




Fig. 19A




Fig. 19B




Fig. 20




Fig. 21




Fig. 22




FIG. 23




Fig. 24





Fig. 25

Fig. 26






Fig. 27




Fig. 28




Fig. 29




Fig.30




Fig. 31




Fig. 32




Fig. 33




Fig. 35

Fig. 34




Fig. 36B




Fig. 36A




Fig.37B




Fig.37A




Fig. 38




Fig. 39A




Fig. 39B




Fig. 40B




Fig. 40A




Fig. 41




Fig. 42




Fig.43




Fig. 44




FIG. 45




Fig. 46B




Fig. 46A

MICROWAVE ABLATION CATHETER AND METHOD OF UTILIZING THE SAME

CROSS REFERENCE TO RELATED APPLICATIONS

The present application claims the benefit of and priority to U.S. Provisional Patent Application Ser. No. 61/680,555 filed on Aug. 7, 2012 by Brannan et al.; U.S. Provisional Patent Application Ser. No. 61/783,921 filed on Mar. 14, 2013 by Ladtkow et al.; U.S. Provisional Patent Application Ser. No. 61/784,048 filed on Mar. 14, 2013 by Ladtkow et al.; U.S. Provisional Patent Application Ser. No. 61/784,176 filed on Mar. 14, 2013 by Ladtkow et al.; U.S. Provisional Patent Application Ser. No. 61/784,297 filed on Mar. 14, 2013 by Ladtkow et al.; and U.S. Provisional Patent Application Ser. No. 61/784,407 filed on Mar. 14, 2013 by Ladtkow et al., the entire contents of each being incorporated herein by reference.

BACKGROUND

1. Technical Field

The present disclosure relates to a microwave ablation catheter and method of utilizing the same. More particularly, the present disclosure relates to a microwave ablation catheter that is positionable through one or more branched luminal networks of a patient for treating tissue.

2. Description of Related Art

Microwave ablation may be utilized for treating various maladies, e.g., nodules, of different organs like the liver, brain, heart, lung and kidney. When a nodule is found, for example, within a lung, several factors are considered in making a diagnosis. For example, a biopsy of the nodule may be taken using a biopsy tool under CT guidance. If the biopsy reveals that the nodule is malignant, it may prove useful to ablate the nodule. In this instance, microwave ablation, which typically includes transmitting microwave energy to a percutaneous needle, may be utilized to ablate the nodule. Under certain surgical scenarios, certain current percutaneous methods of microwave ablation procedures can result in pneumothoraces (air leaks) and a collection of air in the space around the lungs which if not appreciated by the clinician can ultimately lead to collapse of the lung or a portion thereof.

Endobronchial navigation uses CT image data to create a navigation plan to facilitate advancing a navigation catheter (or other suitable device) through a bronchoscope and a branch of the bronchus of a patient to the nodule. Electromagnetic tracking may also be utilized in conjunction with the CT data to facilitate guiding the navigation catheter through the branch of the bronchus to the nodule. In certain instances, the navigation catheter may be positioned within one of the airways of the branched luminal networks adjacent to or within the nodule or point of interest to provide access for one or more tools. Once the navigation catheter is in position, fluoroscopy may be used to visualize biopsy tools, such as, for example, biopsy brushes, needle brushes and biopsy forceps as they are passed through the navigation catheter and into the lung and to the nodule or point of interest.

SUMMARY

As can be appreciated, a microwave ablation catheter that is positionable through one or more branched luminal networks of a patient to treat tissue may prove useful in the surgical arena.

Aspects of the present disclosure are described in detail with reference to the drawing figures wherein like reference numerals identify similar or identical elements. As used herein, the term “distal” refers to the portion that is being described which is further from a user, while the term “proximal” refers to the portion that is being described which is closer to a user.

An aspect of the present disclosure provides a method for treating lung tissue of a patient. A pathway to a point of interest in a lung of a patient is generated. An extended working channel is advanced transorally into the lung and along the pathway to the point of interest. The extended working channel is positioned in a substantially fixed orientation at the point interest. A tool is advanced through the extended working channel to the point of interest. The lung tissue is treated at the point of interest.

A bronchoscope may be positioned within a patient. A locatable guide may be positioned within the extended working channel for positioning the extended working channel to the point of interest. Prior to advancing the tool through the extended working channel, the locatable guide may be removed from the extended working channel. The tool may be a microwave ablation catheter, a biopsy brush, needle brushes or biopsy forceps.

The lung tissue may be biopsied. The lung tissue may then be ablated. Prior to treating the lung tissue, the placement of the extended working channel at the point of interest may be confirmed. The lung tissue may be penetrated at the point of interest. Effective treatment of the lung tissue may be confirmed.

The microwave ablation catheter may be provided with a coaxial cable that is connected at its proximal end to a microwave energy source and at its distal end to a distal radiating section. The coaxial cable includes inner and outer conductors and a dielectric positioned therebetween. The inner conductor extends distally past the outer conductor and is in sealed engagement with the distal radiating section. A balun is formed in part from a conductive material electrically connected to the outer conductor of the coaxial cable and extends along at least a portion of the coaxial cable. The conductive material has a braided configuration and is covered by at least one insulative material.

Generating may include utilizing a guidance system that is configured for planning the pathway to the point of interest and for guiding and navigating one of the tool, extended working channel or the locatable guide through the lungs of a patient. The pathway may be generated based on computed tomographic (CT) data of the luminal network, and may be displayed in a generated model. The pathway may be generated from CT data to identify a pathway to the point of interest identified by a user in the CT data, and the pathway may be generated for acceptance by the user before use in navigating.

A plurality of sensors may be positioned adjacent the diseased lung tissue. The plurality of sensors may be configured to communicate with at least one controller that is in communication with one of the guidance system and the microwave energy source. One or more of the plurality of sensors may be pointed within an airway adjacent the lung tissue.

The plurality of sensors may be utilized to measure at least one property of the lung tissue. The property of the lung tissue may be impedance of the lung tissue, temperature of the lung tissue or dielectric of the lung tissue.

An aspect of the present disclosure provides a method for treating lung tissue of a patient. An ablation device is advanced endobronchially to a target in a lung of a patient. The ablation device is inserted into a center of the target.

Placement of the ablation device within the target is confirmed using an imaging modality. The ablation device is energized to heat the target.

A pathway to the target may be generated. A bronchoscope may be positioned within a patient. An extended working channel may be positioned in a substantially fixed orientation at the target. A locatable guide may be positioned within the extended working channel for positioning the extended working channel at the point of interest. Prior to advancing the tool through the extended working channel, the locatable guide may be removed from the extended working channel.

The tool may be microwave ablation catheter, a biopsy brush, needle brushes or biopsy forceps. The target may be biopsied. The target may then be ablated. Prior to treating target, placement of the extended working channel at the point of interest may be confirmed. The target at the point of interest may be penetrated. Effective treatment of the target may be confirmed.

An aspect of the present disclosure provides a method for treating tissue through a branched luminal network of a patient. A pathway to a point of interest in branched luminal network of a patient is generated. An extended working channel is advanced transorally into the branched luminal network and along the pathway to the point of interest. The extended working channel may be positioned in a substantially fixed orientation at the point interest. A tool is advanced through the extended working channel to the point of interest. Tissue at the point of interest is treated.

A scope may be positioned within a patient. A locatable guide may be positioned within the extended working channel for positioning the extended working channel to the point of interest. Prior to advancing the tool through the extended working channel, the locatable guide may be removed from the extended working channel.

The tool may be a microwave ablation catheter, a biopsy brush, needle brushes and biopsy forceps. The tissue may be biopsied. The tissue may be ablated. Prior to treating the tissue, placement of the extended working channel at the point of interest may be confirmed. The tissue may be penetrated at the point of interest. Effective treatment of the tissue may be confirmed.

The microwave ablation catheter may be provided with a coaxial cable including a proximal end configured to couple to a microwave energy source and a distal end including a distal radiating section. The coaxial cable including inner and outer conductors and a dielectric positioned therebetween. The inner conductor extends distally past the outer conductor and into sealed engagement with the distal radiating section for treating the lung tissue. A choke may be formed in part from a conductive material electrically connected to the outer conductor of the coaxial cable and extending along at least a portion of the coaxial cable. The conductive material has a braided configuration and covered by at least one insulative material.

Generating the pathway to a point of interest may include utilizing a guidance system that is configured for planning the pathway to the point of interest and for guiding and navigating one of the tool, extended working channel or the locatable guide through the branched luminal network of a patient. The pathway may be generated based on computed tomographic (CT) data of the luminal network, and may be displayed in a generated model. The pathway may be generated from CT data to identify a pathway to the point of interest identified by a user in the CT data, and the pathway may be generated for acceptance by the user before use in navigating.

A plurality of sensors may be positioned adjacent the tissue. The plurality of sensors may be configured to communi-

cate with at least one controller that is in communication with one of the guidance system and the microwave energy source. One or more of the plurality of sensors may be pointed within an airway adjacent the tissue.

The plurality of sensors may be utilized to measure at least one property of the tissue. The property of the tissue may be impedance of the tissue, temperature of the tissue or dielectric of the tissue.

BRIEF DESCRIPTION OF THE DRAWING

Various embodiments of the present disclosure are described hereinbelow with references to the drawings, wherein:

FIG. 1 is a perspective view of a microwave ablation system including a microwave ablation catheter assembly configured for use with a microwave ablation system according to an embodiment of the instant disclosure;

FIG. 2 is a front view of an embodiment of a lumen configuration configured for use with the microwave catheter assembly shown in FIG. 1;

FIG. 3A is a front view of an another embodiment of a lumen configuration configured for use with the microwave catheter assembly shown in FIG. 1;

FIG. 3B is a front view of an another embodiment of a lumen configuration configured for use with the microwave catheter assembly shown in FIG. 1;

FIG. 3C is a front view of an another embodiment of a lumen configuration configured for use with the microwave catheter assembly shown in FIG. 1, whereby the lumen supporting the coaxial microwave structure also communicates cooling fluid with inflow or outflow ports;

FIG. 4 is a perspective view of a distal end of a microwave ablation catheter configured for use with the microwave ablation assembly shown in FIG. 1;

FIG. 5 is a cross-sectional view taken along line section 5-5 in FIG. 4;

FIG. 6 is a screen shot of a CT based luminal navigation system in accordance with an embodiment of the present disclosure;

FIG. 7 is a perspective view of a microwave ablation system and luminal navigation system configured for use the microwave ablation catheter assembly shown in FIG. 1 and microwave ablation catheter shown in FIG. 2 in accordance with an embodiment of the present disclosure;

FIG. 8 is a side view of a luminal catheter delivery assembly including an extended working channel and locatable guide catheter in accordance with an embodiment of the present disclosure;

FIG. 9 is a partial, perspective view of a distal end of the locatable guide catheter shown in FIG. 8;

FIG. 10 is a side view of the extended working channel shown in FIG. 8 with the microwave ablation catheter extending from a distal end thereof;

FIG. 11 is a screen shot of a CT based luminal navigation system in accordance with an embodiment of the present disclosure;

FIG. 12A is a schematic, plan view of the extended working channel positioned within a bronchoscope prior to being positioned within a trachea of a patient;

FIG. 12B is a schematic, plan view of the bronchoscope shown in FIG. 12A positioned within the trachea of the patient with the extended working channel extending distally therefrom;

FIG. 12C is a partial, cutaway view of the extended working channel and locatable guide positioned within the bronchoscope;

FIG. 13A is a schematic, plan view of the bronchoscope positioned within the trachea of the patient with the extended working channel extending distally therefrom;

FIG. 13B is a partial, cutaway view of the extended working channel and a biopsy tool positioned within the bronchoscope;

FIG. 14 is a schematic, plan view of the bronchoscope positioned within the trachea of the patient with the extended working channel removed from the bronchoscope;

FIG. 15A is a schematic, plan view of the bronchoscope positioned within the trachea of the patient with an extended working channel according to an alternate embodiment extending distally therefrom;

FIG. 15B is a partial, cutaway view of the extended working channel shown in FIG. 15A positioned within the bronchoscope;

FIG. 16A is a schematic, plan view of the bronchoscope positioned within the trachea of the patient with the extended working channel shown in FIG. 15A extending distally therefrom;

FIG. 16B is a schematic, plan view of the bronchoscope positioned within the trachea of the patient with the extended working channel shown in FIG. 15A extending distally therefrom and adjacent target tissue;

FIG. 16C is a partial, cutaway view of the extended working channel and the microwave ablation catheter shown in FIG. 2 coupled to one another and positioned within the bronchoscope;

FIG. 16D is a cross-sectional view taken along line section 16D-16D in FIG. 16C;

FIG. 17 is a schematic, plan view of another embodiment of the extended working shown in FIGS. 9 and 15A with the extended working channel positioned within the lung of a patient and having a balloon coupled thereto in an deflated configuration;

FIG. 18 is an enlarged area of detail of FIG. 17 and showing the balloon in an inflated configuration;

FIG. 19A is a schematic, plan view of an alternate embodiment of a balun configured for use with the microwave ablation catheter shown in FIG. 2 with the balun shown in an expanded configuration;

FIG. 19B is a schematic, plan view of the balun shown in FIG. 19A in a non-expanded configuration;

FIG. 20 is a schematic, plan view of a distal tip configuration that may be utilized with the microwave ablation catheter assembly shown in FIG. 1, the microwave ablation catheter shown in FIG. 2 or the extended working channel shown in FIG. 15A;

FIG. 21 is a schematic, plan view of an alternate embodiment of the extended working channel shown in FIG. 15A;

FIG. 22 is a schematic, plan view of yet another embodiment of the extended working channel shown in FIG. 15A;

FIG. 23 is a perspective view of an alternate embodiment of the luminal navigation system shown in FIG. 7;

FIG. 24 is a partial, cutaway view of another embodiment of the microwave ablation catheter shown in FIG. 1;

FIG. 25 is a cross-sectional view taken along line section 25-25 in FIG. 24;

FIG. 26 is a cross-sectional view taken along line section 26-26 in FIG. 24;

FIG. 27 is a partial, cutaway view of yet another embodiment of the microwave ablation catheter shown in FIG. 1;

FIG. 28 is a schematic, plan view of still yet another embodiment of the microwave ablation catheter shown in FIG. 1;

FIG. 29 is a schematic, plan view illustrating a circulation feedback loop that is configured for use with the extended

working channels shown in FIGS. 15A, 17 and 21, and the microwave ablation catheter shown in FIGS. 1, 24 and 27-28;

FIG. 30 is a schematic, plan view of still yet another embodiment of the extended working channel shown in FIG. 15A;

FIG. 31 is a schematic, plan view of still yet another embodiment of the extended working channel shown in FIG. 15A with the microwave ablation catheter shown in FIG. 2 in a retracted configuration;

FIG. 32 is a schematic, plan view of the extended working channel shown in FIG. 31 with the microwave ablation catheter shown in an extended configuration;

FIG. 33 is a schematic, plan view of still yet another embodiment of the extended working channel shown in FIG. 15A;

FIG. 34 is a schematic, plan view of still yet another embodiment of the extended working channel shown in FIG. 15A with the extended working channel shown in a non-expanded configuration;

FIG. 35 is a schematic, plan view of the extended working channel shown in FIG. 34 in an expanded configuration;

FIG. 36A is a front view of an alternate embodiment of the microwave ablation catheter shown in FIG. 2 including a conductive balloon coupled thereto and shown in a deflated configuration;

FIG. 36B is a front view of the microwave catheter shown in FIG. 36A with the conductive balloon shown in an inflated configuration;

FIG. 37A is a front view of an alternate embodiment of the microwave ablation catheter shown in FIG. 2 including a plurality of thermally conductive fins coupled thereto and shown in a non-deployed configuration;

FIG. 37B is a front view of the microwave catheter shown in FIG. 37A with the plurality of thermally conductive fins shown in a deployed configuration;

FIG. 38 is a schematic, plan view of still yet another embodiment of the extended working channel shown in FIG. 15A;

FIG. 39A is a schematic, plan view of an alternate embodiment of the microwave ablation catheter shown in FIG. 2 including a balloon coupled thereto and shown in a deflated configuration;

FIG. 39B is a schematic, plan view of the microwave catheter shown in FIG. 39A with the balloon shown in an inflated configuration;

FIG. 40A is a schematic, plan view of various fiducial markers configured for use with the microwave ablation system shown in FIG. 7, wherein the fiducial markers are shown adjacent target tissue that has not been ablated;

FIG. 40B is a schematic, plan view of the fiducial markers shown in FIG. 40A, wherein the fiducial markers are shown adjacent target tissue that has been ablated;

FIG. 41 is a schematic, plan view of a guide wire including a plurality of thermocouples configured for use with the microwave ablation system shown in FIG. 7;

FIG. 42 is a perspective view of an electrical measurement system configured for use with the microwave ablation system shown in FIG. 7;

FIG. 43 is a schematic, plan view of a feedback configuration configured for use with the microwave ablation system shown in FIG. 7;

FIG. 44 is a schematic, plan view of an another embodiment of a feedback configuration configured for use with the microwave ablation system shown in FIG. 7;

FIG. 45 is schematic, plan view of a yet another embodiment of a feedback configuration configured for use with the microwave ablation system shown in FIG. 7;

FIG. 46A is a fluoroscopic images of a patient, having a catheter placed therein; and

FIG. 46B is a virtual fluoroscopic image of a patient depicting a target.

DETAILED DESCRIPTION

Detailed embodiments of the present disclosure are disclosed herein; however, the disclosed embodiments are merely examples of the disclosure, which may be embodied in various forms. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a basis for the claims and as a representative basis for teaching one skilled in the art to variously employ the present disclosure in virtually any appropriately detailed structure.

As can be appreciated an energy device, such as a microwave ablation catheter, that is positionable through one or more branched luminal networks of a patient to treat tissue may prove useful in the surgical arena and the present disclosure is directed to such apparatus, systems and methods. Access to lumenal networks may be percutaneous or through natural orifice. In the case of natural orifice, an endobronchial approach may be particularly useful in the treatment of lung disease. Targets, navigation, access and treatment may be planned pre-procedurally using a combination of imaging and/or planning software. In accordance with these aspects of the present disclosure the planning software may offer custom guidance using pre-procedure images). Navigation of the luminal network may be accomplished using image-guidance. These image-guidance systems may be separate or integrated with the energy device or a separate access tool and may include MRI, CT, fluoroscopy, ultrasound, electrical impedance tomography, optical, and device tracking systems. Methodologies for locating the separate or integrated to the energy device or a separate access tool include EM, IR, echolocation, optical, and others. Tracking systems may integrated to imaging device, where tracking is done in virtual space or fused with preoperative or live images. In some cases the treatment target may be directly accessed from within the lumen, such as for the treatment of the endobronchial wall for COPD, Asthma, lung cancer, etc. In other cases, the energy device and/or an additional access tool may be required to pierce the lumen and extend into other tissues to reach the target, such as for the treatment of disease within the parenchyma. Final localization and confirmation of energy device placement may be performed with imaging and/or navigational guidance using the modalities listed above. The energy device has the ability to deliver an energy field for treatment (including but not limited to electromagnetic fields) and may have the ability to monitor treatment during energy application. The monitoring of the treatment may include thermometry, electrical impedance, radiometry, density measurement, optical absorption, hydration, ultrasound, and others. Additionally or alternatively treatment may be monitored from within the lumen or extracorporeally using an additional device or the image-guidance modalities described above. After treatment, the energy device and/or an additional device may have the ability to confirm adequate treatment was performed, employing at least the techniques described above with respect to treatment monitoring. Further, treatment confirmation may be from within the lumen or extracorporeal. The long term treatment performance may be performed with imaging which may be integrated into a follow-up software application.

One embodiment of the present disclosure is directed, in part, to a microwave ablation catheter that is positionable

through one or more branched luminal networks of a patient to treat tissue. The microwave ablation catheter is part of an ablation system that includes a microwave energy source and a planning and navigation system for the placement of the catheter at a desired location within the luminal network. Further, the system includes imaging modalities that can be employed to confirm placement of the catheter and the effect of the application of energy. The microwave catheter itself may include the capability to aide in the confirmation of the placement within the tissue to be treated, or additional devices may be used in combination with the microwave catheter to confirm placement within the tissue to be treated. Still further, one or more thermocouples or temperature sensors on the microwave catheter detect the temperature of the microwave catheter or the tissue surrounding the catheter and enable monitoring of the microwave catheter temperature and the tissue temperature during and after treatment both for safety purposes and for dosage and treatment pattern monitoring purposes. The microwave catheter may also assist in the access to the target tissue, either intraluminal or outside the lumen. The microwave catheter may also assist in the monitoring of the treatment through various measurement techniques and may also be used for treatment confirmation, in addition to assistance from other monitoring and confirmation devices.

FIGS. 1-5 depict various aspects of a microwave ablation system 10 (system 10). The system 10, as show in FIG. 1 includes a microwave ablation catheter assembly 12 (assembly 12) configured to house a microwave ablation catheter 14 (ablation catheter 14) (shown in FIG. 4). Assembly 12 and ablation catheter 14 are configured to couple to a microwave energy source (energy source 16) that is configured to transmit microwave energy to the catheter 14 to treat target tissue, e.g., lung tissue.

The assembly 12 shown in FIG. 1 is configured to receive the ablation catheter 14 and to provide a pathway for a cooling medium to circulate within the assembly 12 and cool the ablation catheter 14 when the ablation catheter 14 is energized. With these purposes in mind, assembly 12 is formed by overmolding plastic to form a generally elongated housing 23 having an outer sheath 18 (FIG. 2) and a plurality of lumens 19a, 19b, and 19c extending from a proximal end 20 to a distal end 22 that includes a relatively pointed or appropriately rounded distal tip 21. A hub portion 24 is provided at the proximal end 20 and includes ports 26a, 26b, 26c that couple to corresponding distal ends (not explicitly shown) of connection tubes 28a, 28b, 28c. Connection tubes 28a, 28c include respective proximal ends 30a, 30c that are configured to releasably couple either directly or indirectly to a fluid source 32 including hoses 31a, 31b that provide one or more suitable cooling mediums (e.g., water, saline, air or combination thereof) to the ablation catheter 14. In embodiments, the fluid source 32 may be a component of a cooling system that is disclosed in U.S. patent application Ser. No. 13/835,625, entitled "Recirculating Cooling System For Energy Delivery Device", filed on Mar. 15, 2013, by Larson et al the entirety of which is incorporated herein by reference. A proximal end 30b of connection tube 28b is configured to couple either directly or indirectly to the energy source 16 to energize the ablation catheter 14. An optional pair of wings 34a, 34b may be provided at the proximal end 20 of the assembly 12. The wings 34a, 34b may extend laterally from respective right and left sides of the proximal end 20 and may be configured to rest on a patient or to be grasped by a clinician for manipulation of the assembly 12.

The ports 26a, 26c of the assembly 12 are in fluid communication with corresponding lumens 19a, 19c of the plurality

of lumens 18 provided within the assembly 12 (FIG. 2) and are configured to provide one of the aforementioned cooling mediums to the assembly 12. In an embodiment, such as the embodiment illustrated in FIG. 2, port 26a is an outflow port and provides a point of egress for the cooling medium from outflow lumen 19a and port 26c is an inflow port and provides point of ingress for the cooling medium into the inflow lumen 19c.

FIG. 3A illustrates an alternate lumen configuration that may be utilized with the assembly 12. In this embodiment, two outflow lumens 19a' and one inflow lumen 19c' are provided and are in fluid communication with the respective ports 26a, 26c.

FIG. 3B illustrates an alternate lumen configuration that may be utilized with the assembly 12. In this embodiment, two outflow lumens 19a' and one inflow lumen 19c' are provided and are in fluid communication with the respective ports 26a, 26c. Additionally, the lumen supporting the coaxial microwave structure is also used for either fluid inflow or outflow.

FIG. 3C illustrates an alternate lumen configuration similar to FIGS. 3a and 3b that may be utilized with the assembly 12. In this embodiment, two outflow lumens 19a' and two inflow lumens 19c' are provided and are in fluid communication with the respective ports 26a, 26c.

A third lumen 19b is provided within the assembly 12 and is configured to support the ablation catheter 14 when the ablation catheter 14 is coupled to the assembly 12. In the embodiment illustrated in FIG. 2, the outflow and inflow lumens 19a, 19c are formed above the lumen 19b. In the embodiment illustrated in FIG. 3A, the lumen 19b is centered between the outflow lumens 19a and inflow lumens 19c to provide two opposing outflow lumens 19a and two opposing inflow lumens 19c around the lumen 19b. In the embodiments illustrated in FIGS. 3A and 3B, the lumen 19b is centered between the outflow lumens 19a and inflow lumen 19c to provide two opposing outflow lumens 19a and one opposing inflow lumen 19c around the lumen 19b. The lumen configurations illustrated in FIGS. 2 and 3A-3C provide the assembly 12 with the needed flexibility to move within the relatively thin conductive airways (and/or vessels) in the branch of the bronchus.

In an embodiment, the assembly 12 may include a 4 lumen configuration (not shown). In this embodiment, three (3) outer lumens (e.g., a combination of outflow and inflow lumens 19a, 19c, respectively) may be equally spaced around a center lumen (e.g., lumen 19b) that is configured to support the ablation catheter 14 when the ablation catheter 14 is coupled to the assembly 12. In one particular embodiment, the three (3) outer lumens may be configured to include two (2) inflow lumens 19c and one (1) outflow lumen 19a (or vice versa).

The outflow and inflow lumens 19a, 19c extend a predetermined distance within the assembly 12 and can function with various coolant feedback protocols (e.g., open or closed feedback protocols). In the embodiments illustrated in FIGS. 2 and 3A-3C, the inflow lumens 19c extend distally of the outflow lumens 19a to allow an adequate amount of cooling medium to circulate around the ablation catheter 14. It should be understood, regardless of the number of or configuration of lumens, space not filled within the lumen supporting the coaxial cable and radiating section may be used for additional fluid ingress or egress to improve fluid flow and directly cool through intimate fluid contact the coaxial microwave structures. In addition to supporting the ablation catheter, the lumen 19b may also support additional outflow or inflow of

coolant, whereby lumen 19b may couple to connection tubes 28a, 28c and their respective proximal ends 30a, 30c.

Referring now to FIGS. 4 and 5, the ablation catheter 14 is illustrated. Ablation catheter 14 includes a coaxial cable 36. Coaxial cable 36 includes a proximal end 38 that couples to port 26b (shown in FIG. 1) that provides electrical connection to the inner conductor 40 and outer conductor 48 of the coaxial cable 36 and the energy source 16.

A distal radiating section 42 is provided at a distal end 44 of the coaxial cable 36 and is configured to receive the inner conductor 40, as best seen in FIG. 5. The distal radiating section 42 may be formed from any suitable material. In embodiments, the distal radiating section 42 may be formed from ceramic or metal, e.g., copper, gold, silver, etc. The distal radiating section 42 may include any suitable configuration including but not limited to a blunt configuration, flat configuration, hemispherical configuration, pointed configuration, bar-bell configuration, tissue piercing configuration, etc. The distal radiating section 42 may couple to the distal end 44 of the coaxial cable via soldering, ultrasonic welding, adhesive, or the like. In one embodiment the distal radiating section 42 is sealed to the inner conductor 40 and a dielectric 50 to prevent fluid from contacting the inner conductor 40. As an alternative, the seal may be just between the inner conductor 40 and the dielectric 50.

An outer conductor 48 is braided and extends along the dielectric 50 positioned between the inner and outer conductors 40, 48, respectively (FIG. 5). As defined herein braided means made by intertwining three or more strands, and while described as a braid, the actual construction is not so limited and may include other formations of outer conductors of coaxial cables as would be understood by those of ordinary skill in the art. One advantage of a braided configuration of the outer conductor 48 is that it provides the ablation catheter 14 with the flexibility to move within the relatively narrow luminal structures such as the airways of the lungs of a patient. Additionally, through the use of flat wire braiding and follow on braid compression with an appropriately sized die, the cross sectional dimension of the braided conductor may be minimized significantly in comparison to other conductive structures, such as a drawn copper tubing, while maintain an acceptable electrical performance.

A choke or balun 52 is formed in part of a conductive layer 51 that extends along a portion of the coaxial cable 36. The conductive layer 51 may be a braided material of similar construction as the outer conductor 48 and is connected to the outer conductor 48. Specifically, a portion of the outer conductor 48 is shorted (e.g., soldered, interbraided or otherwise affixed) to a proximal portion 54 of the conductive layer 51.

The balun 52 also includes an insulative layer 56, which may be formed of a polytetrafluoroethylene (PTFE). The insulative layer 56 is generally formed between the conductive material 52 and the outer conductor 48. The insulative layer 56 extends distally past a distal end of the conductive material 52. The insulative layer 56 and its orientation extending beyond the conductive layer can be adjusted during manufacture to control the overall phase, energy field profile, and temperature response of the coaxial cable 36.

The outer conductor 48 extends distally beyond the insulative layer 56. A portion of the outer conductor 48 is removed to expose the dielectric 50 of the coaxial cable 36 and form a feedgap 58. The feedgap 58 is located distally from the balun 52 and proximal of and immediately adjacent the distal radiating section 42. The feedgap 58 and distal radiating section 42 are located and dimensioned to achieve a specific radiation pattern for the ablation catheter 14.

The ablation catheter **14** may optionally include an outer sheath **62** that extends to the proximal end **54** of the balun **52**. Alternatively, no outer sheath **62** is employed and just a thin layer of insulative material **60** (e.g., a layer of polyethylene terephthalate (PET)) may be used to cover a portion of the outer conductor **48**, and the balun **52** up to the point the insulative layer **56** extends beyond the conductive layer **51** of the balun **52** (FIG. 5). In yet a further embodiment the layer of PET **60** may be configured to extend proximally along the length of the coaxial cable **36** to assist in maintaining the braided configuration of the outer conductor **48** and conductive layer **51**. As will be appreciated by those of skill in the art, removal of the outer sheath **62** and replacing it with a thin material, either along the length of the coaxial cable **36** or just at the balun **52** increases the flexibility of the ablation catheter **14**. This added flexibility is beneficial for enabling greater ranges of movement when the ablation catheter **14** is used in luminal networks having small diameters and having a branched structure of multiple sharp turns, as will be described in greater detail below.

The flexibility of the ablation catheter **14** can be altered to accommodate a specific surgical procedure, a specific luminal structure, specific target tissue, a clinician's preference, etc. For example, in an embodiment, it may prove advantageous to have an ablation catheter **14** that is very flexible for movement through the relatively narrow airway of the lungs of a patient. Alternatively, it may prove advantageous to have an ablation catheter **14** that is only slightly flexible, e.g., where the ablation catheter **14** is needed to pierce or puncture target tissue. Still further, to achieve the desired amount of flexibility it may be desirable to form the balun **52** in a manner consistent with the disclosure of U.S. patent application Ser. No. 13/834,581 entitled "Microwave Energy-Delivery Device and System" filed on Mar. 15, 2013 by Brannan et al., the entire contents of which is incorporated herein by reference. Still further, although the microwave ablation catheter described here may be specific, it should be understood to those of skill in the art that other microwave ablation catheter embodiments, either simplified or more complex in structural detail, may be employed without departing from the scope of the instant disclosure.

In embodiments, a temperature monitoring system **3** (FIG. 1), e.g., microwave thermometry, may be utilized with the ablation catheter **14** to observe/monitor tissue temperatures in or adjacent an ablation zone. In an embodiment, for example, one or more temperature sensors "TS" may be provided on the ablation catheter **14**, e.g., adjacent the distal radiating section **42** (as shown in FIG. 5) and may be configured to measure tissue temperatures in or adjacent an ablation zone. The temperature monitoring system **3** can be, for example, a radiometry system, a thermocouple based system, or any other tissue temperature monitoring system known in the art. The temperature monitoring system **3** may be incorporated into the energy source **16** to provide feedback to the energy source, or alternatively be housed in a separate box providing audible or visual feedback to the clinician during use of the ablation catheter **14**. In either embodiment, the temperature monitoring system **3** may be configured to provide tissue temperature and ablation zone temperature information to the energy source **16** (or other suitable control system). In embodiments, temperature sensors **3** may be included along the coaxial cable **36**, or along assembly **12** (described with reference to FIG. 1), or along the EWC **90** to provide a greater array of temperature data collection points and greater detail on the temperature of the tissue following application of energy.

In at least one embodiment, the tissue temperature and/or ablation zone temperature information may be correlated to specific known ablation zone sizes or configurations that have been gathered through empirical testing and stored in one or more data look-up tables and stored in memory of the temperature sensing monitoring system **3** and/or the energy source **16**. The data look-up tables may be accessible by a processor of the temperature sensing monitoring system **3** and/or the energy source **16** and accessed by the processor while the distal radiating section **42** is energized and treating target tissue. In this embodiment, the temperature sensors "TS" provide tissue temperature and/or ablation zone temperature to the microprocessor which then compares the tissue temperature and/or ablation zone temperature to the known ablation zone sizes stored in the data look-up tables. The microprocessor may then send a command signal to one or more modules of the temperature sensing monitoring system **3** and/or the energy source **16** to automatically adjust the microwave energy output to the distal radiating section **42**. Alternatively, a manual adjustment protocol may be utilized to control the microwave energy output to the distal radiating section **42**. In this embodiment, the microprocessor may be configured to provide one or more indications (e.g., visual, audio and/or tactile indications) to a user when a particular tissue temperature and/or ablation zone temperature is matched to a corresponding ablation zone diameter or configuration.

System **10**, depicted in FIG. 1 is configured to treat tissue, and as further set forth in FIG. 7 enables a method of identifying target tissue (hereinafter simply referred to as "a target") utilizing computed tomographic (CT) images, and once identified further enables the use of a navigation or guidance system to place the catheter assembly **12** or other tools at the target. CT data facilitates the planning of a pathway to an identified target as well as providing the ability to navigate through the body to the target location, this includes a preoperative and an operative component (i.e., pathway planning and pathway navigation).

The pathway planning phase includes three general steps. The first step involves using software for generating and viewing a three-dimensional model of the bronchial airway tree ("BT") and viewing the CT data to identify targets. The second step involves using the software for selection of a pathway on the BT, either automatically, semi-automatically, or manually, if desired. The third step involves an automatic segmentation of the pathway(s) into a set of waypoints along the path that can be visualized on a display. It is to be understood that the airways are being used herein as an example of a branched luminal network. Hence, the term "BT" is being used in a general sense to represent any such luminal network (e.g., the circulatory system, or the gastro-intestinal tract, etc.)

Using a software graphical interface **64** as shown in FIG. 6, generating and viewing a BT, starts with importing CT scan images of a patient's lungs into the software. The software processes the CT scans and assembles them into a three-dimensional CT volume by arranging the scans in the order they were taken and spacing them apart according to the setting on the CT when they were taken. The software uses the newly-constructed CT volume to generate a three-dimensional map, or BT, of the airways. The software then displays a representation of the three-dimensional map **66** on the software graphical interface **64**. A user may be presented with various views to identify masses or tumors that the medical professional would like to biopsy or treat, and to which the medical professional would like to use the system **10** to navigate.

Next, the software selects a pathway to a target, e.g., target **68** identified by a medical professional. In one embodiment, the software includes an algorithm that does this by beginning at the selected target and following lumina back to the entry point. The software then selects a point in the airways nearest the target. The pathway to the target may be determined using airway diameter.

After the pathway has been determined, or concurrently with the pathway determination, the suggested pathway is displayed for user review. This pathway is the path from the trachea to the target that the software has determined the medical professional is to follow for treating the patient. This pathway may be accepted, rejected, or altered by the medical professional. Having identified a pathway in the BT connecting the trachea in a CT image with a target, the pathway is exported for use by system **10** to place a catheter and tools at the target for biopsy of the target and eventually treatment if necessary. Additional methods of determining a pathway from CT images are described in commonly assigned U.S. patent application Ser. No. 13/838,805 entitled "Pathway Planning System and Method" filed on Mar. 15, 2013, by Baker et al, the entirety of which is incorporated herein by reference.

FIG. 7 shows a patient "P" lying on an operating table **70** and connected to a system enabling navigation along the determined pathway within the luminal network to achieve access to the identified target. A bronchoscope **72** is inserted into the patient's lungs. Bronchoscope **72** is connected to monitoring equipment **74**, and typically includes a source of illumination and a video imaging system. In certain cases, the devices of the present disclosure may be used without a bronchoscope, as will be described below. System **10** monitors the position of the patient "P", thereby defining a set of reference coordinates. Specifically, system **10** utilizes a six degrees-of-freedom electromagnetic position measuring system according to the teachings of U.S. Pat. No. 6,188,355 and published PCT Application Nos. WO 00/10456 and WO 01/67035, which are incorporated herein by reference. A transmitter arrangement **76** is implemented as a board or mat positioned beneath patient "P." A plurality of sensors **78** are interconnected with a tracking module **80** which derives the location of each sensor **78** in 6 DOF (degrees of freedom). One or more of the reference sensors **78** (e.g., 3 sensors **78**) are attached to the chest of patient "P" and their 6 DOF coordinates sent to a computer **82** (which includes the software) where they are used to calculate the patient coordinate frame of reference.

FIG. 8 depicts a positioning assembly **84**, constructed and operative according to the teachings of the present disclosure. Positioning assembly **84** includes a locatable guide **86** which has a steerable distal tip **88**, an extended working channel **90** and, at its proximal end, a control handle **92**.

There are several methods of steering the extended working channel **90**. In a first method, a single direction of deflection may be employed. Alternatively, a multi-directional steering mechanism with a manual direction selector may be employed to allow selection of a steering direction by the practitioner without necessitating rotation of the catheter body. With multi-directional steering four elongated tensioning elements ("steering wires") **98a** are implemented as pairs of wires formed from a single long wire extending from handle **92** to distal tip **88**. Steering wires **98a** are bent over part of a base **98b** and return to handle **92**. Steering wires **98a** are deployed such that tension on each wire individually will steer the distal tip **88** towards a predefined lateral direction. In the case of four steering wires **98a**, the directions are chosen to be opposite directions along two perpendicular

axes. In other words, the four steering wires **98a** are deployed such that each wire, when actuated alone, causes deflection of the distal tip **98** in a different one of four predefined directions separated substantially by multiples of 90°.

Locatable guide **86** is inserted into the extended working channel **90** within which it is locked in position by a locking mechanism **94**. A position sensor element **96** of system **10** is integrated with the distal tip **88** of the locatable guide **86** and allows monitoring of the tip position and orientation (6 DOF) relative to the reference coordinate system.

In embodiments, locatable guide **86** may have a curved or hooked configuration as shown in FIG. 10. This alternative is currently marketed by Covidien LP under the name EDGED®. In such a system, it is the extended working channel **90** that is formed with a curved tip **91**. Differing amounts of pre-curve implemented in the extended working channel **90** can be used, however, common curvatures include 45, 90, and 180 degrees. The 180 degree extending working channel **90** has been found particularly useful for directing the locatable guide **86** to posterior portions of the upper lobe of the lung which can be particularly difficult to navigate. The locatable guide **86** is inserted into the extended working channel **90** such that the position sensor **96** projects from the distal tip **88** of the extended working channel **90**. The extended working channel **90** and the locatable guide **86** are locked together such that they are advanced together into the lung passages of the patient "P." In this embodiment, the extended working channel **90** may include a steering mechanism similar to the one already described above. As can be appreciated, certain modifications may need to be made to the extended working channel **90** in order for the extended working channel to function as intended.

In embodiments, an integrated radial ultrasound probe "US" (FIG. 10) may be provided on the extended working channel **90**, the locatable guide **86**, catheter assembly **12** and/or the ablation catheter **14**. For illustrative purposes, the ultrasound probe "US" is shown disposed on the extended working channel **90** and the locatable guide **86**. The ultrasound probe "US" may be configured to provide ultrasound feedback to one or more modules of the system **10** during navigation and insertion of the ablation catheter **14** to facilitate positioning the ablation catheter **14** adjacent target tissue. As will be appreciated a US probe may also be used without the extended working channel but in conjunction with an endoscope for imaging central lesions that would be accessible to the endoscope. Furthermore, the US probe may be used to monitor treatment progression and/or confirm treatment completion.

As noted above, the present disclosure employs CT data (images) for the route planning phase. CT data is also used for the navigation phase. Specifically, the CT system of coordinates is matched with the patient system of coordinates; this is commonly known as registration. Registration is generally performed by identifying locations in both the CT and on or inside the body, and measuring their coordinates in both systems. Manual, semi-automatic or automatic registration can be utilized with the system **10**. For purposes herein, the system **10** is described in terms of use with automatic registration. Reference is made to commonly assigned U.S. patent application Ser. No. 12/780,678, which is incorporated herein by reference, for a more detailed description of automatic registration techniques.

The automatic registration method includes moving locatable guide **86** containing position sensor **96** within a branched structure of a patient "P." Data pertaining to locations of the position sensor **96** while the position sensor **96** is moving through the branched structure is recorded using the trans-

mitter arrangement **80**. A shape resulting from the data is compared to an interior geometry of passages of the three-dimensional model of the branched structure. And, a location correlation between the shape and the three-dimensional model based on the comparison is determined.

In addition to the foregoing, the software of the system **10** identifies non-tissue space (e.g. air filled cavities) in the three-dimensional model. Thereafter, the software records position data of the position sensor **96** of the locatable guide **86** as the locatable guide **86** is moved through one or more lumens of the branched structure. Further, the software aligns an image representing a location of the locatable guide **86** with an image of the three-dimensional model based on the recorded position data and an assumption that the locatable guide **86** remains located in non-tissue space in the branched structure.

Once in place in the patient "P," a screen **93** will be displayed by the software on the monitoring equipment **74** (FIG. **11**). The right image is the actual bronchoscopic image **95** generated by the bronchoscope **72**. Initially there is no image displayed in the left image **97**, this will be a virtual bronchoscopy generated from the CT image data once registration is complete.

Starting with the locatable guide **86**, and specifically the position sensor **96** approximately 3-4 cm above the main carina, as viewed through the bronchoscope **72**, the bronchoscope **72** is advanced into both the right and left lungs to, for example, the fourth generation of the lung passages. By traversing these segments of the lungs, sufficient data is collected as described above such that registration can be accomplished.

Now that the targets have been identified, the pathway planned, the bronchoscope **72** including locatable guide **86** inserted into the patient "P," and the virtual bronchoscopy image registered with the image data of the bronchoscope **72**, the system **10** is ready to navigate the position sensor **96** to the target **68** within the patient's lungs. The computer **80** provides a display similar to that shown in FIG. **11** identifying the target **68** and depicting the virtual bronchoscopy image **99**. Appearing in each of the images on the display is the pathway from the current location of the position sensor **96** to the target **68**. This is the pathway that was established during the pathway planning phase discussed above. The pathway may be represented, for example, by a colored line. Also appearing in each image is a representation of the distal tip **88** of the locatable guide **86** and position sensor **96**. Once the pathway is established, a clinician may utilize system **10** to treat the target tissue **68**.

Operation of the system **10** to treat target tissue is described with reference to FIGS. **12A-16C**. It is assumed the pathway to the target **68** had been ascertained via the methods described above. After, advancing the bronchoscope **72** including the extended working channel **90** and the locatable guide **86** to a point of being wedged within the luminal network, the extended working channel and locatable guide are further advanced along the identified pathway to the target **68** (see FIGS. **12A-12C**).

In some cases the target tissue may be directly accessed from within the lumen (such as for the treatment of the endobronchial wall for COPD, Asthma, lung cancer, etc.), however in other instances, the target is not in direct contact with the BT and use of the locatable guide alone does not achieve access to the target. Additional access tools may be required to cross the lumen and access the target tissue (such as for the treatment of disease within the parenchyma).

Final localization and confirmation of the locatable guide or access tool with extended working channel may be performed with imaging and/or navigational guidance (this may

include the same or different combinations of imaging and navigation techniques listed above).

Once the locatable guide **86** or an additional access tool has successfully been navigated to the target **68** location, the locatable guide **86** or access tool may be removed, leaving the extended working channel **90** in place as a guide channel for a biopsy tool **84** to the target **68** location (FIGS. **13A-13B**). The medical tools may be biopsy tools that can be used to sample the target **68**. Details of this system are included in U.S. Pat. No. 7,233,820, already incorporated herein by reference.

Once the locatable guide **86** has successfully been navigated to the target **68** location, the locatable guide **86** may be removed, leaving the extended working channel **90** in place as a guide channel for bringing a tool **84** to the target **68** location (FIGS. **13A-13B**). The medical tools may be biopsy tools that can be used to sample the target **68**. These samples are retrieved and sent to pathology for analysis to determine if treatment of the target is necessary. The biopsy analysis can happen in real time after the biopsy procedure such that the ablation can be performed immediately, or there can be some period of time, e.g., hours, days, weeks, between the time when the biopsy is taken and when the ablation procedure is performed.

If it is determined that the target **68** requires treatment (e.g., ablation), the assembly **12** including the ablation catheter **14** may be positioned through the bronchoscope **72** and the extended working channel **90** to enable treatment. Placement of the assembly may occur after the extended working channel **90** has been navigated to the target **68**, or the extended working channel **90** may be navigated with the assembly **12** to reach the target **68**. This second option may require a sensor providing 6 DOF positioning within either the extended working channel **90** or the assembly **12**. As noted above, the braided configuration of the outer conductor **48** and the conductive layer **51** of the balloon **52** in combination with the lumen configurations depicted in FIGS. **2-3**, provides the assembly **12** with the needed flexibility to move within the relatively narrow airways.

In embodiments, the target tissue "T" may be pierced or penetrated to allow placement of the distal radiating section **42** within the target **68** (e.g., centered within the mass for treatment). For example, a guide wire, piercing tool, a biopsy tool **84** or the distal end **21** of the assembly **12** (described with reference to FIG. **1**) may be utilized to pierce or penetrate the target **68**. In the instance where the guide wire or piercing tool is utilized to penetrate or pierce tissue, the guide wire or piercing tool may be passed through the extended working channel **90** to penetrate the target **68**. Once pierced, the extended working channel **90** may be held in place and the guide wire or piercing tool removed to allow the assembly **12**, housing the ablation catheter **14**, to be inserted into the opening created by the tool or the guide wire in the target **68**. Alternatively, while the guide wire or piercing tool is in the target **68**, the extended working channel **90** may be extended to place the distal end of the extended working channel **90** within the opening created in the target **68**. Following placement of the extended working channel **90** within the target **68**, the guide wire or piercing tool can be removed to allow for insertion of the assembly **12** including ablation catheter **14**. This second method helps assure proper placement of the ablation catheter **14**, housed within the assembly **12**, into the target **68**.

One or more imaging modalities may be utilized to confirm that the ablation catheter **14** has been properly positioned (e.g. within the target **68**.) For example, computer tomography (CT), ultrasound, fluoroscopy, and other imaging modalities may be utilized individually or in combination with one

another to confirm that the ablation catheter **14** has been properly positioned within the target **68**. One methodology employing both CT and fluoroscopy imaging modalities is described in commonly assigned U.S. application Ser. No. 12/056,123 entitled "CT-Enhanced Fluoroscopy," the contents of which is incorporated herein by reference.

Yet a further alternative method of ablation catheter **14** placement confirmation is disclosed herein. FIG. **46A** represents a live fluoroscopic image depicting the placement of an extended working channel **90** and an ablation assembly **12** or biopsy tool **84** extending therefrom, after performing one of the navigation procedures described herein. FIG. **46B** is a virtual fluoroscopic image depicting the same patient and displaying a target **68** thereon. The virtual fluoroscopic image is generated from the same CT data used in both the planning and navigation methods described above. The CT data is manipulated to create a computer model of a fluoroscopic image of the patient. The target **68** is the same target **68** identified in the planning phase, and the location of the target **68** in the virtual fluoroscopic image corresponds to the location of the target identified by the clinician during planning.

The virtual fluoroscopic image and the live fluoroscopic image may be registered to one another. This may be done using, for example, one or more fiducial markers placed either prior to the CT scan and that will also appear on the fluoroscopic image, or by identifying landmarks within the physiology that may act as fiducial markers (e.g., curvature and spacing of the rib cage). The two images, the live fluoroscopic image and the static virtual fluoroscopic image provide the clinician with the ability to compare placement of the extended working channel **90** and the ablation assembly **12** with the location of the target **68**. This may be done in either a side by side comparison mode as shown in FIGS. **46A** and **46B**. For example, in FIG. **46A**, the live fluoroscopic image, a mass **67** that has been identified as the target **68** during the planning phase may only be lightly visible under fluoroscopy, often soft tissue is difficult to discern in fluoroscopic images, but by comparing the location of the extended working channel **90** and the ablation assembly **12** as shown in FIG. **46A** to the location of the target **68** shown in FIG. **46B**, the necessary adjustments to positioning for proper ablation can be readily ascertained.

Alternatively, where the live and the virtual fluoroscopic images are registered to one another, comparison may be made by overlaying the virtual image (FIG. **46B**) over the live image (FIG. **46A**) such that a composite image is created. This composite image then depicts the relative position of the target **68** to the placement of the ablation assembly **12** and extended working channel **90**. By continuing live fluoroscopy visualization of the placement of the extended working channel **90** and/or the ablation assembly **12**, or a biopsy tool **84** into the target **68** is enabled, thus enabling the clinician to actually see the proper placement into a target **68** in real time using a combination of a live fluoroscopic image and an overlaid virtual fluoroscopic image. Once placement of the ablation catheter **14** is confirmed within the target **68**, microwave energy can be transmitted to the ablation catheter **14** to treat the target **68**.

Following treatment of the target **68**, one of the aforementioned imaging modalities may be utilized to confirm that a suitable ablation zone has been formed around the target **68** and to determine whether additional application of energy are necessary. These steps of treating and imaging may be repeated iteratively until a determination is made that the target has been successfully ablated. Moreover, the methodology described above using the imaging modalities to confirm the extent of treatment and determine whether additional

application of energy is necessary can be combined with the radiometry and temperature sensing techniques described above to both confirm what is depicted by the imaging modality and to assist in determining treatment cessation points.

In an embodiment, such as, for example, when the target **68** is relatively close to a distal end of the bronchoscope **72**, the extended working channel **90** may be removed (FIG. **14**), or not used at all, and the bronchoscope **72** kept in place to visually guide access tools and the assembly **12** including the ablation catheter **14** to target **68**. Alternately, the extended working channel **90** and accompanying access tools may be placed without use of the bronchoscope **72**, or the bronchoscope **72** can be removed after placement of the extended working channel **90** in combination with access tools at the target **68** and kept in place and the assembly **12** including the ablation catheter **14** can be extended through the extended working channel **90** to treat the target **68**.

As noted above, temperature monitoring system **3** can be used to determine and monitor temperature of the target tissue **68**, ablation zone size, etc. In embodiments, the temperature monitoring system **3** can incorporated into one or more components (e.g., software graphical interface **64**) that are configured for use with the system **10**.

In embodiments, placement of the extended working channel **90** and/or the ablation catheter **14** within the luminal network may accomplished without the use of the aforementioned pathway planning and pathway navigation methods. In this instance, computer tomography, ultrasound and/or fluoroscopy may be utilized to facilitate positioning the extended working channel **90**, and/or access tools and/or the ablation catheter **14** within the luminal network.

In embodiments, the distal radiating section **42** may be covered by a temperature sensitive "wax" material "W" that melts when energy is applied to the inner conductor **20**, thereby absorbing heat from the distal radiating section **42** by changing phase.

Moreover, in place of fluid cooling the distal radiation section **42** may be frozen to create an ice formation therearound. When the distal radiating section is energized, the ice turns to gas which may result in high heat dissipation, which, in turn, cools the distal radiating section **42**.

Further, in accordance with the instant disclosure, it may prove advantageous to utilize the ablation catheter **14** without the assembly **12**. In this particular embodiment, the extended working channel **90** may be modified to provide for fluid cooling of the ablation catheter **14**, for example one of the aforementioned lumen and port configurations and a closed distal tip. As can be appreciated, one or more other modifications may also have to be made to the extended working channel **90** in order for the extended working channel **90** to function as intended herein.

FIGS. **15A-15B** illustrate an extending working channel **190** having a closed distal end and a modified catheter assembly **12** inserted therein. Rather than a closed distal end as shown in FIG. **1**, the catheter assembly **12** has an open distal end. A space between the inner surface of the extended working channel **190** and the catheter assembly **12** establishes a fluid inflow lumen **119a**. A fluid outflow lumen **119c** is exposed by the opening of the distal end of the catheter assembly **12**. The lumens **119a** and **119c** allow for cooling fluid to flow in the extended working channel **190** and catheter assembly **12** to cool an the ablation catheter **14** located within the catheter assembly **12**. A cross section of the extended working channel **190** with modified catheter assembly **12** is shown in FIG. **16D**. The catheter assembly **12** may optionally include a position sensor **96** such that the catheter assembly **12** acts as a locatable guide **86** (FIG. **12**) to assist in the

positioning of the extended working channel at a target **68**. The extended working channel **190** may be formed to meet the flexibility criteria described above. Alternatively, the extended working channel may be placed as described above using a locatable guide **86**. Thereafter, the locatable guide **86** may be removed and the extended working channel **190** kept in place. With the locatable guide **86** removed, the modified catheter assembly **12** and ablation catheter **14** may be positioned within the extended working channel **190** (FIG. **16A**) and energized to form an ablation zone "AB" suitable for treating target **68** (FIG. **16B**). FIG. **16C** shows yet another optional configuration, where the ablation catheter **14** is placed into the extended working channel **190** without any assembly following placement of the extended working channel **190** and removal of the locatable guide **86**. Water may be circulated within the extended working channel **190** to cool the distal radiating section in a manner as described above.

As can be appreciated, a result of the flexible assembly **12** including the ablation catheter **14** being inserted endobrachially is that the likelihood of pneumothoraces occurring is greatly reduced by navigating through the luminal branches of the lung. Moreover, the ability of the system **10** to create a pathway to target tissue takes the guess work out of positioning the locatable guide, the extended working channel and the assembly **12** including the ablation catheter **14**.

From the foregoing and with reference to the various figure drawings, those skilled in the art will appreciate that certain modifications can also be made to the present disclosure without departing from the scope of the same. For example, one or modifications may be made in the way of device delivery and placement; device cooling and antenna buffering; and sensor feedback. The following are a variety of non-limiting examples of such modifications considered within the scope of the present disclosure.

I. Device Delivery and Placement

In accordance with the instant disclosure, various methods may be utilized to deliver the ablation catheter **14** and/or the extended working channel **90/190** into a desired location in the target tissue **68**.

For example, to address the occurrence of bleeding within the patient as a result of biopsy or ablation, the bronchoscope may be employed to create tamponade; that is, the bronchoscope can be wedged into the bronchus to stop the bleeding at points the bronchoscope can reach. However, in accordance with the instant disclosure, the extended working channels **90/190** could be navigated to the target **68** and one or more expandable members may be provided on the extended working channels **90/190** to create tamponade. The expandable member, e.g., a balloon, can be inflated to stop bleeding at these remote locations.

Specifically, FIGS. **17** and **18** illustrate the extended working channels **90/190** including a balloon "B" that is positioned on an exterior surface of the extended working channels **90/190**. The balloon "B" is initially in a deflated configuration (FIG. **17**) for navigating the extended working channel **90/190** through a conductive airway and positioning the extended working channels **90/190** adjacent the target **68**. Subsequently, the balloon is inflated for anchoring the extended working channel **90/190** in place and to create a tamponade (FIG. **18**).

In the embodiment where the balloon "B" is provided on the extended working channel **90**, one or more lumens may be provided on the extended working channel **90** and may be in fluid communication with the balloon "B" to provide one or more suitable fluids from the fluid source **32** to the balloon "B" to move the balloon "B" from the inflated configuration to the deflated configuration (and vice versa). Moreover, in

this embodiment, the balloon "B" may be configured to control local lung properties which change with respiration. For example, the relative permittivity of deflated lung tissue at 2450 MHz is 48 and the relative permittivity of inflated lung tissue at the same frequency is 20; this large permittivity range makes it difficult to tune an antenna to a single frequency. It has been found through empirical testing that by adding the balloon "B," the lung can be locally isolated during an inflated or deflated state to produce one or more desired properties, e.g., electrical and thermal. Specifically, thermal conductivity changes with inflation and deflation of the lungs. For example, if local respiration was stopped with the lung inflated and the ablation catheter **14** was matched to the target **68** with a relative permittivity of 45, heating can be focused thermally and electrically to the target **68**. Likewise, if the lung were fixed in a deflated configuration, more lung tissue could be thermally treated to produce additional margin around the target **68**.

FIGS. **19A-19B** illustrate an ablation catheter **214** according to another embodiment of the present disclosure. Ablation catheter **214** is similar to ablation catheter **14**. Accordingly, only those features unique to ablation catheter **214** are described in detail. An expandable balun **252** is provided on a coaxial cable **236**. The balun **252** functions in a manner as described above with respect to the balun **52**. Unlike balun **52**, however, the balun **252** is expandable (air/fluid pressure) and configured to provide the functions of the balloon "B" as described above.

One or more lumens (not shown) may be provided on the ablation catheter **214** and configured to receive one or more suitable fluids from the fluid source **32** to move the balun **252** between the deflated and inflated configurations, see FIGS. **19A-19B**. Alternatively, the lumens **19a, 19c** of the assembly **12** may be in fluid communication with the balun **252** and configured to provide one or more suitable fluids from the fluid source **32** to the balun **252** to move the balun **252** between inflated and deflated configurations. As can be appreciated, other methods and/or devices may be utilized to move the balun **252** between inflated and deflated configurations.

FIG. **20** illustrates an extended working channel **290** according to another embodiment of the instant disclosure. In this embodiment, a closed distal tip **291** is energizable for penetrating tissue "T." Specifically, an electrode **292** may be coupled at the distal tip **291** of the extending working channel **290**. The electrode **291** may be in electrical communication with the energy source **16** via one or more leads or wires **293** that extend within the extended working channel **290**. The electrode **292** may be configured for monopolar operation. A return pad (not shown) may be positioned on a patient and utilized as a return electrode. Alternatively, a second electrode (not shown) can be provided on the extended working channel **290** to create a bipolar electrode configuration. In use, when the electrode **291** is energized, the distal tip **291** may be utilized to penetrate tissue to facilitate positioning the extended working channel **290** adjacent target tissue.

FIG. **21** illustrates an extended working channel **390** according to another embodiment of the instant disclosure. The extended working channel **390** includes a closed distal end and at least one water filled lumen or chamber (e.g., a lumen **319a** of the cooling water loop utilized to cool the distal radiating section **42**) that includes a piston assembly **321** including a base **323** and a needle **325** extending distally from the base and through an aperture (not shown) at a distal end of the lumen **319a**. A seal (not shown) may be provided within the aperture of the lumen **319a** to maintain the pressure within the lumen. An optional seal **327** may be provided at a

distal tip of the extended working channel 390 and may be configured to maintain a fluid tight seal. The piston assembly 321 is movable within the lumen 319a to move the needle 325 from a retracted configuration to an extended configuration (shown in phantom in FIG. 21) through the seal 327. In the extended configuration, the needle 325 may be utilized to anchor the extended working channel 390 to tissue and/or penetrate tissue.

In use, water may be provided to the extended working channel 390 to move the needle 325 to the extended configuration for penetrating tissue; this may be done prior to energizing the distal radiating section 42 and/or when the distal radiating section 42 is energized. Thus, the cooling water loop serves a dual purpose (cooling of the distal radiating section and extension of the needle 325) and may eliminate the need for a separate push/pull member or sheath.

FIG. 22 illustrates an extended working channel 490 according to another embodiment of the instant disclosure. The extended working channel 490 includes an open distal end and an electrode 492 operably coupled thereto. Electrode 492 is similar to the electrode 292 illustrated in FIG. 20. Unlike electrode 292, however, electrode 492 may extend along an outer peripheral surface of the extended working channel 490. Additionally, a pair of upright electrode extensions 494a, 494b may be provided on the electrode 492 and configured to function as a monopolar pencil to treat tissue.

The electrode 492 may be in electrical communication with the energy source 16 via one or more leads or wires 493 that extend within the extended working channel 490. The electrode 492 may be configured for monopolar operation. A return pad (not shown) may be positioned on a patient and utilized as a return electrode. Alternatively, a second electrode (not shown) can be provided on the extended working channel 490 to create a bipolar electrode configuration. In use, after tissue has been ablated, the upright extensions 494a, 494b may be utilized to transmit microwave energy (or RF) to neighboring tissue. After the tissue has been treated, the upright extensions 494a, 494b may be utilized to scrape the electrosurgically treated tissue. As can be appreciated, having the electrode 492 on the extended working channel 490, allows a user to treat tissue with the electrode 492 while leaving ablation catheter 14 in place within the extended working channel 490.

FIG. 23 illustrates a head-up display 81 (e.g., Google glasses) that communicates with the guidance system for providing a virtual internal image to a clinician. The virtual internal image includes information pertaining to planning the pathway to the target 68 and for guiding and navigating one of the aforementioned tools, extended working channels and the locatable guides through the lungs of a patient "P." The head-up display 81 may include one or more electromagnetic sensors 83 for providing a position of the head-up display 81 relative to a patient "P" for projecting the virtual internal image into a clinician's view of the patient "P" with the proper orientation.

II. Device Cooling and Antenna Buffering

The following embodiments are configured to protect a patient from unintended heating from the coaxial cable 36 and/or the distal radiating section 42 and/or configured to provide dielectric buffering to the distal radiating section 42.

FIGS. 24-26 illustrate an assembly 512 according to an embodiment of the instant disclosure. Assembly 512 is similar to assembly 12. Accordingly, only those features unique to assembly 512 are described in detail.

A partition 511 is provided within the housing 523 adjacent the distal end of the assembly 512 to provide a chamber 514 that is configured to isolate the distal radiating section 542

from the rest of the coaxial cable 536. A dielectric (e.g., ceramic, hydrogel, etc.) 513 is provided within the chamber 514 to cover the distal radiating section 542 and is configured to cool the distal radiating section 542 and the inner conductor 540 when contacted by fluid being transmitted through the lumens 519a, 519c and into contact with the partition 511. In accordance with the instant disclosure, the dielectric 513 is capable of withstanding heat without changing properties to buffer the distal radiating section 542 and create a separate active cooling system around the coaxial cable 536. This reduces, if not eliminates, phase changes around the distal radiating section 542 during activation thereof and may reduce the active cooling requirements on the coaxial cable 536.

FIG. 27 illustrates an assembly 612 according to an embodiment of the instant disclosure. A plurality of ceramic elements 613 extend at least partially along the coaxial cable 636 and form a nested configuration. The ceramic elements 613 serve as a heat sink to cool a distal radiating section 642 and an inner conductor 640. The ceramic elements 613 may be actuatable to move from a relaxed configuration wherein the plurality of ceramic elements 613 are spaced apart from one another (as shown in FIG. 27) to allow the coaxial cable 636 to flex, to a compressed configuration wherein the ceramic elements 613 are moved towards one another to increase cooling of the distal radiating section 642 and the inner conductor 640, and to secure the position of the location of the assembly. A pair pull wire 617 operably couples to the ceramic elements 613 and is configured to move the ceramic elements 613 to the compressed configuration.

FIG. 28 illustrates an extended working channel 790 according to an embodiment of the instant disclosure. The extended working channel 790 functions as a structural thermal sink that is configured to sink heat either by itself or in conjunction with a cooling fluid. In the embodiment illustrated in FIG. 28, the extended working channel 790 is formed from a material that is a good thermal conductor to pull away heat from the distal radiating section 742. A heat sink 791 is operably coupled to a proximal end 793 of the extended working channel 790. For example, lumens 719a, 719c (shown in phantom) extend to a proximal end of a balun 752 to cool the proximal end 793 of the extended working channel 790. In this particular embodiment, the fluid may flow up to the proximal end of the balun 752 and turn around; this would keep the extended working channel 790 cool at the proximal end 793. Conduction is utilized to move cool air through a distal end of the extending working channel 790 distal to the balun 752 to the cooled proximal end 793 of the extended working channel 790 proximal to the balun 752. Additionally or alternatively, a ceramic paste "CP" may at least partially cover the distal radiating section 742 and may serve as a dielectric buffer to provide static cooling of the distal radiating section 742. Use of the ceramic paste "CP" may allow the extended working channel 790 to be formed without the lumens 719a, 719c, which, in turn, would allow the extended working channel 790 to remain flexible while providing static cooling and/or buffering.

FIG. 29 illustrates an extended working channel 890 according to an embodiment of the present disclosure. By using a vacuum pump to pull water through a the extended working channel 890, the boiling point of the water circulating through the extended working channel 890 can be lowered. At this pressure water boils at about body temperature and the boiling water will rapidly vaporize and the change of phase results in cooling of the fluid and components adjacent to it and create an additional cooling effect for an ablation catheter 814. To this end, a vacuum pump 33 operably couples

to a fluid return port (not shown) on the extended working channel to pressurize a fluid circulating through lumens **819c** for lowering a boiling point of the fluid circulating through the lumens **819c**. In embodiments, an air-mist mixture may be utilized as the cooling medium and circulated through the lumens **819a**, **819c**; this embodiment takes advantage of the large energy needed to change phase from liquid to vapor, even where temperature remains constant.

FIG. **30** illustrates an extended working channel **990**. The extended working channel **990** may include a two lumen configurations (not explicitly shown). In this embodiment, one lumen is dedicated for communication with a fluid intake port (not shown) of the extended working channel **990** and one lumen dedicated to support the ablation catheter **914**. Unlike the previous disclosed lumen configurations, the fluid intake port and the lumen are configured for an open loop cooling protocol. The open loop cooling protocol may improve fluid flow within the extended working channel **990**. Moreover, energy delivery and microwave energy absorption may be improved by hydrating the target. Further, the open loop cooling protocol may be combined with expandable balloon "B" and/or expandable balloon **252** to lock the extended working channel **990** in place, which, in turn, may increase dielectric buffering around the distal radiating section **942**.

In embodiments, the extended working channel **990** may include a fluid return port and a corresponding third lumen that is configured to provide suction for suctioning the cooling fluid dispensed from the extended working channel **990**; this may provide a user with the ability to perform a Bronchoalveolar Lavage (BAL) at the end of the microwave ablation procedure, i.e., by stopping fluid flow and sucking the fluid back to retrieve one or more tissue samples.

FIGS. **31-32** illustrate an extended working channel **1090** according to another embodiment of the present disclosure. In this embodiment, the extended working channel **1090** may be utilized as a thermal and electrical control by extending the distal radiating section **1042** through a seal structure **1091** that is provided at a distal end of the extended working channel **1090**. The seal structure **1091** is configured for sealed engagement with the distal radiating section **1042** to maintain a fluid tight seal when the distal radiating section **1042** is extended therethrough for treating tissue.

FIG. **33** illustrates an extended working channel **1190** according to another embodiment of the present disclosure. In this embodiment, no flow fluid buffering is utilized to cool the distal radiating section **1142**. With this purpose in mind, a chamber **1191** is provided at a distal end of the extended working channel **1190** and is not in fluid communication with lumens **1119a**, **1119c**. The chamber **1191** surrounds the distal radiating section **1142** and configured to receive a high boiling point liquid (e.g., water, saline, etc.) being therein to cool the distal radiating section **1142**. In this embodiment seal members **1121a**, **1121b** may be optionally provided at distal ends of the lumens **1119a**, **1119c** and are configured to maintain the high boiling point liquid within the chamber **1191**. The higher boiling point liquid in chamber **1191** absorbs heat generated by the distal radiating section **1142** and transfers it to the fluid circulated through lumens **1119a** and **1119c**.

FIGS. **34** and **35** illustrate an extended working channel **1290** according to another embodiment of the instant disclosure. In this embodiment, a heat sink **1291** having an accordion configuration is coupled to a distal end of the extended working channel **1290**. The heat sink **1291** is configured to couple to the distal radiating section **1242** via one or more suitable coupling methods when the distal radiating section **1242** is extended through the extended working channel

1290. In the illustrated embodiment, for example, a seal (not shown) may be provided at a distal end of the extended working channel **1290** and may be configured to releasably engage (via a press or friction fit) the distal radiating section **1242** as the distal radiating section is extended from the extended working channel **1290** (FIG. **34**). As the heat sink heats, it begins to extend distally away from the extended working channel **1290** bringing the distal radiating section **1242** coupled thereto with it. In the extended configuration, the distal radiating section **1242** will have been moved away from surrounding tissue, which, in turn, may reduce collateral damage to the surrounding tissue (FIG. **35**).

FIGS. **36A** and **36B** illustrate an ablation catheter **1314** according to an embodiment of the instant disclosure. In the embodiment illustrated in FIGS. **36A** and **36B**, a heat sink is created with the walls of a lung ("LW"), which, typically, include a temperature in the range of about 37° C. To this end, a thermally conductive balloon **1321** is positioned adjacent a distal radiating section (not explicitly shown) of the ablation catheter **1314** and is expandable (via one or more of the aforementioned lumen configurations) to dissipate heat from the distal radiating section into the wall of a lung "LW" of patient. Specifically, when the distal radiating section is energized, the conductive balloon **1321** is inflated and expands into contact with the wall of the lung "LW," which, in turn sinks the heat absorbed by the thermally conductive balloon **1321**.

Alternatively, a plurality of thermally conductive fins **1323** (FIGS. **37A-37B**) may be positioned adjacent the distal radiating section. In this embodiment, the fins **1323** are expandable to absorb and dissipate heat from the distal radiating section when the distal radiating section is energized. In the embodiment illustrated in FIGS. **37A-37B**, the fins **1323** are formed from a shape memory metal that is configured to move to an expanded configuration when heated as a result of the distal radiating section being energized. Once expanded, airflow may be introduced into the bronchus and across the plurality of thermally conductive fins **1323** to cool the conductive fins **1323**, which, in turn, will cool the distal radiating section.

FIG. **38** illustrates an extended working channel **1490** according to an embodiment of the instant disclosure. In this embodiment, the extended working channel **1490** includes a proximal end **1491** including a diameter "D1" that is larger than a tapered distal end **1492** that includes a diameter "D2." The larger diameter D1 of the proximal end **1491** allows for more cooling for a given length of extended working channel **1490**. In accordance with the instant disclosure, the diameter "D1" of the proximal end **1491** should be large enough to minimize coolant pressure drop but small enough to fit in airways.

FIGS. **39A-39B** illustrate an ablation catheter **1514** according to an embodiment of the instant disclosure. Specifically, a balloon **1515** may be positioned adjacent the radiating section **1542** (and/or the balloon not shown) and may be in fluid communication with the lumens (not explicitly shown) within the ablation catheter **1514**. The balloon **1515** is movable from a deflated configuration (FIG. **39A**) for extending the ablation catheter **1514** through an extended working channel **1590** to an inflated configuration (FIG. **39B**). In the inflated configuration, the balloon **1515** may serve to expand a buffering volume, i.e., there is more volume to heat. Moreover, the balloon **1515** may be configured to anchor the distal radiating section **1542** in an airway of the lung. Further, the balloon **1515** may be configured to increase flow rate around the balloon of the ablation catheter **1514**.

III. Sensor Feedback

The following embodiments are configured to provide sensor and/or visual feedback to the system **10** or physician relating device placement (e.g., the extended working channel **90/190**, the catheter assembly **12** and/or the ablation catheter **14**), tissue environment, ablation progress, device performance, safety, etc.

In accordance with the instant disclosure, one or more feedback mechanisms may be utilized with the instant disclosure. For example, FIGS. **40A-40B** illustrate various fiducial markers that may be detectable by the system **10**. Any of the aforementioned extended working channels that include an open distal end, e.g., the working channel **90**, may be utilized as a conduit for the placement of one or more fiducial markers within the patient following removal of the locatable guide **86**. These markers can be used for a variety of purposes including identifying tumors and lesions for follow-up analysis and monitoring, to identify locations that biopsy sampling has been undertaken, and to identify the boundaries or the center of a tumor or lesion for application of treatment. Other uses will be understood by those of skill in the art as falling within the scope of the present disclosure.

In embodiments, the fiducial markers may be formed from a shape memory alloy "SM." In this embodiment, the fiducial markers "SM" are configured to change shape when heated to a predetermined temperature. Additionally or alternatively, the fiducial markers may be formed from poloxamers "PM." Poloxamers can be transformed from liquid to solid using energy from the distal radiating section of the ablation catheter, e.g., distal radiating section **42**. Once in the body, the fiducial markers "PM" cool to body temp and transform back to liquid and are dissolved in the bloodstream. In solid form, the fiducial markers "PM" may be visible under CT, ultrasound, and other imaging modalities to reveal the real time growth of the ablation zone "AZ."

FIG. **41** illustrates another feedback mechanism that may be utilized with the system **10**. In this embodiment, a guide wire **73** that is positionable within one of the aforementioned extended working channels (e.g., the extended working channel **90**) and deployable therefrom may be utilized for measuring a temperature of the aforementioned distal radiating sections (e.g., distal radiating section **42**). The guide wire **73** includes at least one thermocouple **75** at a distal end thereof. The thermocouples **75** may be configured to capture temperature measurements when deployed from the extended working channel. The thermal couples **75** may be in communication with a microcontroller of the energy source **16** to monitor rate of change of the temperature of or surrounding the distal radiating section **42**; the rate of change can be analyzed to correlate with a specific ablation size. In embodiments, the guide wire **73** may be utilized to deploy the ablation catheter **14** from the extended working channel **90**.

FIGS. **42-43** illustrate another feedback mechanism that may be utilized with the system **10**. In the embodiment illustrate in FIG. **42**, the system **10** is capable of detecting placement of an ablation catheter **1642** in healthy vs. tumor tissue or if bleeding occurs along the ablation catheter **1642**. With this purpose in mind, one or more electrodes **1641** (two electrodes **1641** shown in FIG. **42**) are provided adjacent a distal radiating section **1642** and are configured to detect data pertaining to the target tissue prior to, during or after activation of the distal radiating section **1642**. The data pertaining to tissue may include electrical properties of the tissue, e.g., RF impedance.

In embodiments, the electrodes **1641** can be utilized to capture dielectric measurements of the surrounding tissue to ensure placement in tumor tissue. The amount and type of

buffering of the distal radiating section **1642** will play a role in how well the electrodes **1641** can capture these measurements. With either of the RF or dielectric measurement types, a controller **17** (or another system **23**, e.g., a laptop) connected to the ablation catheter **1614** will be needed to capture and analyze the data to interpret to the user. After the data is analyzed, the controller **17** provides the relevant information to a user, e.g., on a display **37**.

In embodiments, the controller **17** may be configured to perform S-parameter (FIG. **43**) analysis between input and output ports of the microwave energy source. In this embodiment, the S-parameter analysis is utilized to determine ablation size "AZ", to control operation of the energy source **16** and/or to detect damage to the distal radiating section **1642** in real-time.

In embodiments, one or more sensor configurations may be utilized with the system **10**. For example, a hydration sensor "HS" (see FIG. **43** for example) may be utilized to measure the water content of the tissue at some distance from distal radiating section **42** to monitor ablation progress and/or completion. In this instance, the extended working channel **90** may be utilized to position the "HS" at a predetermined point away from where the distal radiating section **42** is going to be positioned. As moisture is driven out of the tissue, the sensor "HS" tracks the rate of change and can tell the user when the ablation is complete. Dielectric properties can be directly correlated with hydration levels of the tissue.

Moreover, one or more fiber optic cables "FC" may through the extended working channel **90** for positioning adjacent to target tissue for providing a visual perspective of the target tissue to a clinician. Alternately, the fiber optic cable "FC" may be provided adjacent to the distal radiating section **42** (see FIG. **5** for example). In this embodiment, one or more lenses (not shown) may be provided adjacent to the distal radiating section **42** and coupled to a distal end of the fiber optic cable "FC." Further, one or more force sensor "FS" configured to provide feedback on force being applied by the distal radiating section **42** to penetrate tissue. In this instance, the force sensor "FS" may be operably coupled adjacent the distal radiating section (see FIG. **5** for example).

In embodiments, one or more chemical sensor "CS" may be configured to detect one or ore chemicals of tissue prior to, during or after activation of the distal radiating section **42** (see FIG. **5** for example). In this embodiment, the chemical sensor "CS" may be in operable communication with the microcontroller **17** that is configured to detect chemicals associated with the target tissue, e.g., acids and proteins. The chemicals detected may be correlated to a progression of thermal ablation growth and stored in one or more data look-up tables (not shown) that is accessible to the microcontroller **17**.

FIG. **44** illustrates a method of placement configuration for various sensor configurations. Specifically, alternate airways may be utilized to deploy sensors (e.g., acoustic, thermocouples, electrical sensors, etc). In one particular embodiment, the ablation catheter **14** may be extended through the extended working channel **90** and positioned in between two opposing sensors, e.g., acoustic sensors "AS" that are positioned in opposite airways. During operation of the distal radiating section **42**, a ping across the airways can be generated to measure tissue properties, e.g., measure impedance, dielectric or temperature.

FIG. **45** illustrates another feedback mechanism that may be utilized with the system **10**. In this embodiment, two antennas for ablation (e.g., procedural/completeness) monitoring are provided, a sensor patch **1840** and a distal radiating section **1842** of an ablation catheter **1814** (shown not positioned within an extended working channel for clarity). Sen-

sensor patch **1840** is positionable on a patient and configured to calibrate the ablation catheter **1814** prior to treating tissue and determine when the tissue has been adequately ablated. The sensor patch **1840** is in operable communication with controller **17** configured to monitor the amount of power received by the sensor patch **1840** as the distal radiating section **1842** is energized. The graph indicates received power at the sensor patch **1840** during both calibration (points A-B) and an ablation cycle (points C-D). The calibration cycle baselines transmission path. As ablation progresses, transmission path between distal radiating section **1842** and sensor patch **1840** becomes less lossy due to desiccation resulting in increasing received power. Ablation completeness is determined by amount of increased power received above calibration. For example, 1.5 cm ablation zone "AZ" increases power to sensor patch **1840** by approximately 15%. In an embodiment, when the power at the sensor patch **1840** reaches the calibration level or surpasses the calibration level, the microcontroller **17** automatically shuts power off to ablation catheter **1814**.

While several embodiments of the disclosure have been shown in the drawings, it is not intended that the disclosure be limited thereto, as it is intended that the disclosure be as broad in scope as the art will allow and that the specification be read likewise. Therefore, the above description should not be construed as limiting, but merely as exemplifications of particular embodiments. Those skilled in the art will envision other modifications within the scope and spirit of the claims appended hereto.

What is claimed is:

1. A method for treating lung tissue of a patient, comprising:

generating a pathway to a point of interest in a lung of a patient;

advancing an extended working channel trans-orally into the lung and along the pathway to the point of interest;

positioning the extended working channel in a substantially fixed orientation at the point of interest;

advancing a microwave ablation catheter through the extended working channel to the point of interest, the microwave ablation catheter having a coaxial cable connected at the proximal end of the coaxial cable to a microwave energy source and at the distal end of the coaxial cable to a distal radiating section, the coaxial cable including inner and outer conductors and a dielectric positioned therebetween, the inner conductor extending distally past the outer conductor and in sealed engagement with the distal radiating section; and

treating the lung tissue at the point of interest.

2. The method according to claim 1, including positioning a bronchoscope within a patient.

3. The method according to claim 1, including positioning a locatable guide within the extended working channel for positioning the extended working channel to the point of interest.

4. The method according to claim 3, including, prior to advancing the tool through the extended working channel, removing the locatable guide from the extended working channel.

5. The method according to claim 1, including ablating the lung tissue.

6. The method according to claim 1, including, prior to treating the lung tissue, confirming the placement of the extended working channel at the point of interest.

7. The method according to claim 1, including penetrating the lung tissue at the point of interest.

8. The method according to claim 1, including confirming that the lung tissue has been effectively treated.

9. The method according to claim 1, including providing the microwave ablation catheter with

a balun formed in part from a conductive material electrically connected to the outer conductor of the coaxial cable and extending along at least a portion of the coaxial cable, the conductive material having a braided configuration and covered by at least one insulative material.

10. The method according to claim 1, wherein generating includes utilizing a guidance system that is configured for planning the pathway to the point of interest and for guiding and navigating one of the tool, extended working channel or the locatable guide through the lungs of a patient.

11. The method according to claim 10, wherein the pathway is generated based on computed tomographic (CT) data of the luminal network, and is displayed in a generated model.

12. The method according to claim 10, wherein the pathway is generated from CT data to identify a pathway to the point of interest identified by a user in the CT data, and the pathway is generated for acceptance by the user before use in navigating.

13. The method according to claim 1, including positioning a plurality of sensors adjacent the diseased lung tissue, wherein the plurality of sensors are configured to communicate with at least one controller that is in communication with one of the guidance system and the microwave energy source.

14. The method according to claim 13, wherein positioning includes positioning at least one of the plurality of sensors within an airway adjacent the lung tissue.

15. The method according to claim 13, including utilizing the plurality of sensors to measure at least one property of the lung tissue, wherein the at least one property of the lung tissue is selected from the group consisting of impedance of the lung tissue, temperature of the lung tissue or dielectric of the lung tissue.

16. A method for treating lung tissue of a patient, comprising:

advancing an ablation device endobronchially to a target in a lung of a patient, the ablation device having a coaxial cable connected at the proximal end of the coaxial cable to an energy source and at the distal end of the coaxial cable to a distal radiating section, the coaxial cable including inner and outer conductors and a dielectric positioned therebetween, the inner conductor extending distally past the outer conductor and in sealed engagement with the distal radiating section;

inserting the ablation device into a center of the target;

confirming placement of the ablation device within the target using an imaging modality; and

energizing the ablation device to heat the target.

17. The method according to claim 16, including generating a pathway to the target.

18. The method according to claim 16, including positioning a bronchoscope within a patient.

19. The method according to claim 16, including positioning an extended working channel in a substantially fixed orientation at the target.

20. The method according to claim 19, including positioning a locatable guide within the extended working channel for positioning the extended working channel at the point of interest.

21. The method according to claim 16, including, prior to advancing the ablation device through the extended working channel, removing the locatable guide from the extended working channel.

22. The method according to claim 16, including ablating the target.

23. The method according to claim 16, including, prior to treating the target, confirming the placement of the extended working channel at the point of interest.

24. The method according to claim 16, including penetrating the target at the point of interest.

5

25. The method according to claim 16, including confirming that the target has been effectively treated.

* * * * *

专利名称(译)	微波消融导管及其使用方法		
公开(公告)号	US9370398	公开(公告)日	2016-06-21
申请号	US13/837978	申请日	2013-03-15
[标]申请(专利权)人(译)	柯惠有限合伙公司		
申请(专利权)人(译)	COVIDIEN LP		
当前申请(专利权)人(译)	COVIDIEN LP		
[标]发明人	LADTKOW CASEY M BRANNAN JOSEPH D PETERSON DARION R LARSON ERIC W HALEY KAYLEN J DICKHANS WILLIAM J CASE JASON A		
发明人	LADTKOW, CASEY M. BRANNAN, JOSEPH D. PETERSON, DARION R. LARSON, ERIC W. HALEY, KAYLEN J. DICKHANS, WILLIAM J. CASE, JASON A.		
IPC分类号	A61B18/04 A61B6/12 A61B5/01 A61B6/03 A61B10/02 A61B10/04 A61B10/06 A61B5/11 A61B1/018 A61B18/18 A61B6/00 A61B1/267 A61B5/053 A61B18/00 A61B5/06 A61B5/00		
CPC分类号	A61B1/018 A61B18/1815 A61B6/12 A61B5/01 A61B10/06 A61B10/04 A61B10/0233 A61B6/032 A61B5 /1114 A61B6/487 A61B2018/00577 A61B2018/1861 A61B5/0538 A61B1/2676 A61B2010/0216 A61B5 /7425 A61B5/7445 A61B5/062 A61B5/064 A61B5/4836 A61B2018/00541 A61B8/0841 A61B8/12 A61B5/0036 A61B18/1477 A61B2017/00026 A61B2017/00084 A61B2018/00702		
优先权	61/680555 2012-08-07 US 61/783921 2013-03-14 US 61/784048 2013-03-14 US 61/784176 2013-03-14 US 61/784297 2013-03-14 US 61/784407 2013-03-14 US		
其他公开文献	US20140046176A1		
外部链接	Espacenet USPTO		

摘要(译)

提供了一种治疗患者肺组织的方法。产生通向患者肺部感兴趣点的途径。延伸的工作通道经口进入肺部并沿着通向感兴趣点的通道。延伸的工作通道在点兴趣处定位在基本固定的方向上。工具通过扩展的工作通道前进到感兴趣的点。在感兴趣的点处治疗肺组织。

