



US010226187B2

(12) **United States Patent**
Al-Ali et al.

(10) **Patent No.:** **US 10,226,187 B2**
(45) **Date of Patent:** **Mar. 12, 2019**

(54) **PATIENT-WORN WIRELESS
PHYSIOLOGICAL SENSOR**

(71) Applicant: **Masimo Corporation**, Irvine, CA (US)

(72) Inventors: **Ammar Al-Ali**, San Juan Capistrano,
CA (US); **Kevin Forrest**, Rancho Santa
Margarita, CA (US)

(73) Assignee: **Masimo Corporation**, Irvine, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/253,536**

(22) Filed: **Aug. 31, 2016**

(65) **Prior Publication Data**

US 2017/0055851 A1 Mar. 2, 2017

Related U.S. Application Data

(60) Provisional application No. 62/212,467, filed on Aug.
31, 2015, provisional application No. 62/212,472,
(Continued)

(51) **Int. Cl.**
A61B 5/02 (2006.01)
A61B 5/0205 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 5/02055** (2013.01); **A61B 5/002**
(2013.01); **A61B 5/0004** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61B 2562/0219; A61B 2562/0402; A61B
2562/0408; A61B 2562/1117; A61B
2562/6801

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,646,606 A 2/1972 Buxton et al.
3,690,313 A 9/1972 Weppner et al.
(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 735 499 10/1996
EP 2 335 569 6/2011
(Continued)

OTHER PUBLICATIONS

US 8,845,543, 09/2014, Diab et al. (withdrawn)
(Continued)


Primary Examiner — Puya Agahi

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson
& Bear, LLP

(57) **ABSTRACT**

A wireless, patient-worn, physiological sensor configured to, among other things, help manage a patient that is at risk of forming one or more pressure ulcers is disclosed. According to an embodiment, the sensor includes a base having a top surface and a bottom surface. The sensor also includes a substrate layer including conductive tracks and connection pads, a top side, and a bottom side, where the bottom side of the substrate layer is disposed above the top side of the base. Mounted on the substrate layer are a processor, a data storage device, a wireless transceiver, an accelerometer, and a battery. In use, the sensor senses a patient's motion and wirelessly transmits information indicative of the sensed motion to, for example, a patient monitor. The patient monitor receives, stores, and processes the transmitted information.

11 Claims, 28 Drawing Sheets



Related U.S. Application Data

filed on Aug. 31, 2015, provisional application No. 62/212,484, filed on Aug. 31, 2015, provisional application No. 62/212,480, filed on Aug. 31, 2015.

(51) Int. Cl.

A61B 5/0408 (2006.01)
A61B 5/11 (2006.01)
A61B 5/113 (2006.01)
A61B 5/00 (2006.01)
A61B 5/05 (2006.01)
A61B 5/053 (2006.01)
A61B 5/1455 (2006.01)
A61B 5/01 (2006.01)
A61B 5/0402 (2006.01)
G06F 19/00 (2018.01)
A61G 7/057 (2006.01)
A61B 5/08 (2006.01)

(52) U.S. Cl.

CPC **A61B 5/0015** (2013.01); **A61B 5/0022** (2013.01); **A61B 5/01** (2013.01); **A61B 5/0205** (2013.01); **A61B 5/0402** (2013.01); **A61B 5/0408** (2013.01); **A61B 5/05** (2013.01); **A61B 5/053** (2013.01); **A61B 5/113** (2013.01); **A61B 5/1113** (2013.01); **A61B 5/1116** (2013.01); **A61B 5/1117** (2013.01); **A61B 5/1118** (2013.01); **A61B 5/1121** (2013.01); **A61B 5/1126** (2013.01); **A61B 5/14552** (2013.01); **A61B 5/447** (2013.01); **A61B 5/6801** (2013.01); **A61B 5/6833** (2013.01); **A61B 5/7264** (2013.01); **A61B 5/7275** (2013.01); **A61B 5/7282** (2013.01); **A61B 5/742** (2013.01); **A61B 5/743** (2013.01); **A61B 5/746** (2013.01); **G06F 19/00** (2013.01); **A61B 5/0816** (2013.01); **A61B 5/14551** (2013.01); **A61B 2560/0475** (2013.01); **A61B 2562/0204** (2013.01); **A61B 2562/029** (2013.01); **A61B 2562/0219** (2013.01); **A61B 2562/0223** (2013.01); **A61B 2562/0271** (2013.01); **A61G 7/057** (2013.01); **A61G 2203/32** (2013.01); **A61G 2203/36** (2013.01); **A61G 2203/42** (2013.01); **A61G 2203/46** (2013.01)

(56)**References Cited****U.S. PATENT DOCUMENTS**

3,978,849 A	9/1976	Geneen	5,296,688 A	3/1994	Hamilton et al.
4,108,166 A	8/1978	Schmid	5,318,037 A	6/1994	Evans et al.
4,129,125 A	12/1978	Lester et al.	5,319,355 A	6/1994	Russek
4,231,354 A	11/1980	Kurtz et al.	5,331,549 A	7/1994	Crawford, Jr.
4,589,415 A	5/1986	Haaga	5,333,106 A	7/1994	Lanpher et al.
4,662,378 A	5/1987	Thomis	5,337,744 A	8/1994	Branigan
4,838,275 A	6/1989	Lee	5,341,805 A	8/1994	Stavridi et al.
4,852,570 A	8/1989	Levine	5,348,008 A	9/1994	Bornn et al.
4,960,128 A	10/1990	Gordon et al.	5,358,519 A	10/1994	Grandjean
4,964,408 A	10/1990	Hink et al.	D353,195 S	12/1994	Savage et al.
4,966,154 A	10/1990	Cooper et al.	D353,196 S	12/1994	Savage et al.
5,041,187 A	8/1991	Hink et al.	5,375,599 A	12/1994	Schimizu
5,069,213 A	12/1991	Polczynski	5,377,676 A	1/1995	Vari et al.
5,092,340 A	3/1992	Yamaguchi et al.	5,400,794 A	3/1995	Gorman
5,140,519 A	8/1992	Friesdorf et al.	5,416,695 A	5/1995	Stutman et al.
5,159,932 A	11/1992	Zanetti et al.	D359,546 S	6/1995	Savage et al.
5,161,539 A	11/1992	Evans et al.	5,431,170 A	7/1995	Mathews
5,163,438 A	11/1992	Gordon et al.	5,434,611 A	7/1995	Tamura
5,262,944 A	11/1993	Weisner et al.	D361,840 S	8/1995	Savage et al.
5,277,189 A	1/1994	Jacobs	D362,063 S	9/1995	Savage et al.
5,278,627 A	1/1994	Aoyagi et al.	5,452,717 A	9/1995	Branigan et al.
5,282,474 A	2/1994	Valdes Sosa et al.	D363,120 S	10/1995	Savage et al.
			5,456,252 A	10/1995	Vari et al.
			5,479,934 A	1/1996	Imran
			5,482,036 A	1/1996	Diab et al.
			5,483,968 A	1/1996	Adam et al.
			5,490,505 A	2/1996	Diab et al.
			5,494,041 A	2/1996	Wilk
			5,494,043 A	2/1996	O'Sullivan et al.
			5,503,149 A	4/1996	Beavin
			5,505,202 A	4/1996	Mogi et al.
			5,533,511 A	7/1996	Kaspari et al.
			5,534,851 A	7/1996	Russek
			5,544,649 A	8/1996	David et al.
			5,553,609 A	9/1996	Chen et al.
			5,558,638 A	9/1996	Evers et al.
			5,561,275 A	10/1996	Savage et al.
			5,562,002 A	10/1996	Lalin
			5,566,676 A	10/1996	Rosenfeldt et al.
			5,566,678 A	10/1996	Cadwell
			5,576,952 A	11/1996	Stutman et al.
			5,579,001 A	11/1996	Dempsey et al.
			5,590,649 A	1/1997	Caro et al.
			5,602,924 A	2/1997	Durand et al.
			5,619,991 A	4/1997	Sloane
			5,632,272 A	5/1997	Diab et al.
			5,638,816 A	6/1997	Kiani-Azarbayjany et al.
			5,638,818 A	6/1997	Diab et al.
			5,640,967 A	6/1997	Fine et al.
			5,645,440 A	7/1997	Tobler et al.
			5,685,299 A	11/1997	Diab et al.
			5,685,314 A	11/1997	Geheb et al.
			5,687,717 A	11/1997	Halpern et al.
			5,694,020 A	12/1997	Lang et al.
			5,724,580 A	3/1998	Levin et al.
			5,724,983 A	3/1998	Selker et al.
			5,725,308 A	3/1998	Smith et al.
			5,734,739 A	3/1998	Sheehan et al.
			D393,830 S	4/1998	Tobler et al.
			5,743,262 A	4/1998	Lepper, Jr. et al.
			5,758,079 A	5/1998	Ludwig et al.
			5,758,644 A	6/1998	Diab et al.
			5,760,910 A	6/1998	Lepper, Jr. et al.
			5,769,785 A	6/1998	Diab et al.
			5,772,585 A	6/1998	Lavin et al.
			5,782,757 A	7/1998	Diab et al.
			5,782,805 A	7/1998	Meinzer
			5,785,659 A	7/1998	Caro et al.
			5,791,347 A	8/1998	Flaherty et al.
			5,801,637 A	9/1998	Lomholt
			5,810,734 A	9/1998	Caro et al.
			5,813,403 A	9/1998	Soller et al.
			5,822,544 A	10/1998	Chaco et al.
			5,822,546 A	10/1998	George
			5,823,950 A	10/1998	Diab et al.
			5,830,131 A	11/1998	Caro et al.
			5,833,618 A	11/1998	Caro et al.
			5,855,550 A	1/1999	Lai et al.
			5,860,919 A	1/1999	Kiani-Azarbayjany et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,890,929 A	4/1999	Mills et al.	6,322,502 B1	11/2001	Schoenberg et al.
5,904,654 A	5/1999	Wohltmann et al.	6,325,761 B1	12/2001	Jay
5,910,139 A	6/1999	Cochran et al.	6,329,139 B1	12/2001	Nova et al.
5,919,134 A	7/1999	Diab	6,334,065 B1	12/2001	Al-Ali et al.
5,921,920 A	7/1999	Marshall et al.	6,338,039 B1	1/2002	Lonski et al.
5,924,074 A	7/1999	Evans	6,343,224 B1	1/2002	Parker
5,931,160 A	8/1999	Gilmore et al.	6,349,228 B1	2/2002	Kiani et al.
5,934,925 A	8/1999	Tobler et al.	6,354,235 B1	3/2002	Davies
5,940,182 A	8/1999	Lepper, Jr. et al.	6,360,114 B1	3/2002	Diab et al.
5,941,836 A	8/1999	Friedman	6,364,834 B1	4/2002	Reuss et al.
5,942,986 A	8/1999	Shabot et al.	6,368,283 B1	4/2002	Xu et al.
5,987,343 A	11/1999	Kinast	6,371,921 B1	4/2002	Caro et al.
5,987,519 A	11/1999	Peifer et al.	6,377,829 B1	4/2002	Al-Ali
5,995,855 A	11/1999	Kiani et al.	6,385,476 B1	5/2002	Osadchy et al.
5,997,343 A	12/1999	Mills et al.	6,385,589 B1	5/2002	Trusheim et al.
6,002,952 A	12/1999	Diab et al.	6,388,240 B2	5/2002	Schulz et al.
6,006,119 A	12/1999	Soller et al.	6,397,091 B2	5/2002	Diab et al.
6,011,986 A	1/2000	Diab et al.	6,430,437 B1	8/2002	Marro
6,014,346 A	1/2000	Malone	6,430,525 B1	8/2002	Weber et al.
6,018,673 A	1/2000	Chin et al.	6,463,311 B1	10/2002	Diab
6,024,699 A	2/2000	Surwit et al.	6,470,199 B1	10/2002	Kopotic et al.
6,027,452 A	2/2000	Flaherty et al.	6,470,893 B1	10/2002	Boesen
6,032,678 A	3/2000	Rottem	6,501,975 B2	12/2002	Diab et al.
6,035,230 A	3/2000	Kang	6,505,059 B1	1/2003	Kollias et al.
6,036,642 A	3/2000	Diab et al.	6,515,273 B2	2/2003	Al-Ali
6,036,718 A	3/2000	Ledford et al.	6,519,487 B1	2/2003	Parker
6,045,509 A	4/2000	Caro et al.	6,524,240 B1	2/2003	Thede
6,067,462 A	5/2000	Diab et al.	6,525,386 B1	2/2003	Mills et al.
6,081,735 A	6/2000	Diab et al.	6,526,300 B1	2/2003	Kiani et al.
6,088,607 A	7/2000	Diab et al.	6,541,756 B2	4/2003	Schulz et al.
6,093,146 A	7/2000	Filangeri	6,542,764 B1	4/2003	Al-Ali et al.
6,101,478 A	8/2000	Brown	6,544,173 B2	4/2003	West et al.
6,106,463 A	8/2000	Wilk	6,544,174 B2	4/2003	West et al.
6,110,522 A	8/2000	Lepper, Jr. et al.	6,551,243 B2	4/2003	Bocionek et al.
6,124,597 A	9/2000	Shehada	6,578,428 B1	6/2003	Dromms et al.
6,128,521 A	10/2000	Marro et al.	6,580,086 B1	6/2003	Schulz et al.
6,129,675 A	10/2000	Jay	6,582,393 B2	6/2003	Sage, Jr.
6,129,686 A	10/2000	Friedman	6,584,336 B1	6/2003	Ali et al.
6,132,218 A	10/2000	Benja-Athon	6,595,316 B2	7/2003	Cybulski et al.
6,139,494 A	10/2000	Cairnes	6,597,932 B2	7/2003	Tian et al.
6,144,868 A	11/2000	Parker	6,597,933 B2	7/2003	Kiani et al.
6,151,516 A	11/2000	Kiani-Azarbayjany et al.	6,606,511 B1	8/2003	Ali et al.
6,152,754 A	11/2000	Gerhardt et al.	6,616,606 B1	9/2003	Peterson et al.
6,157,850 A	12/2000	Diab et al.	6,632,181 B2	10/2003	Flaherty et al.
6,165,005 A	12/2000	Mills et al.	6,639,668 B1	10/2003	Trepagnier
6,167,258 A	12/2000	Schmidt et al.	6,640,116 B2	10/2003	Diab
D437,058 S	1/2001	Gozani	6,641,533 B2	11/2003	Causey et al.
6,168,563 B1	1/2001	Brown	6,643,530 B2	11/2003	Diab et al.
6,171,237 B1	1/2001	Avitall et al.	6,646,556 B1	11/2003	Smith et al.
6,183,417 B1	2/2001	Gehab et al.	6,650,917 B2	11/2003	Diab et al.
6,184,521 B1	2/2001	Coffin, IV et al.	6,650,939 B2	11/2003	Takpke, II et al.
6,185,448 B1	2/2001	Borovsky	6,654,624 B2	11/2003	Diab et al.
6,195,576 B1	2/2001	John	D483,872 S	12/2003	Cruz et al.
6,206,830 B1	3/2001	Diab et al.	6,658,276 B2	12/2003	Kianl et al.
6,221,012 B1	4/2001	Maschke et al.	6,661,161 B1	12/2003	Lanzo et al.
6,224,553 B1	5/2001	Nevo	6,671,531 B2	12/2003	Al-Ali et al.
6,229,856 B1	5/2001	Diab et al.	6,678,543 B2	1/2004	Diab et al.
6,230,142 B1	5/2001	Benigno et al.	6,684,090 B2	1/2004	Ali et al.
6,232,609 B1	5/2001	Snyder et al.	6,684,091 B2	1/2004	Parker
6,236,872 B1	5/2001	Diab et al.	6,694,180 B1	2/2004	Boesen
6,241,683 B1	6/2001	Macklem et al.	6,697,656 B1	2/2004	Al-Ali
6,253,097 B1	6/2001	Aronow et al.	6,697,657 B1	2/2004	Shehada et al.
6,256,523 B1	7/2001	Diab et al.	6,697,658 B2	2/2004	Al-Ali
6,263,222 B1	7/2001	Diab et al.	RE38,476 E	3/2004	Diab et al.
6,267,723 B1	7/2001	Matsumura et al.	6,699,194 B1	3/2004	Diab et al.
6,269,262 B1	7/2001	Kandori et al.	6,714,804 B2	3/2004	Al-Ali et al.
6,278,522 B1	8/2001	Lepper, Jr. et al.	RE38,492 E	4/2004	Diab et al.
6,280,213 B1	8/2001	Tobler et al.	6,719,694 B2	4/2004	Weng et al.
6,285,896 B1	9/2001	Tobler et al.	6,721,582 B2	4/2004	Trepagnier et al.
6,301,493 B1	10/2001	Marro et al.	6,721,585 B1	4/2004	Parker
6,304,767 B1	10/2001	Soller et al.	6,725,075 B2	4/2004	Al-Ali
6,308,089 B1	10/2001	von der Ruhr et al.	6,728,560 B2	4/2004	Kollias et al.
6,312,378 B1	11/2001	Bardy	6,735,459 B2	5/2004	Parker
6,317,627 B1	11/2001	Ennen et al.	6,745,060 B2	6/2004	Diab et al.
6,321,100 B1	11/2001	Parker	6,746,406 B2	6/2004	Lia et al.
			6,751,492 B2	6/2004	Ben-haim
			6,760,607 B2	7/2004	Al-Ali
			6,766,188 B2	7/2004	Soller
			6,770,028 B1	8/2004	Ali et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,771,994 B2	8/2004	Kiani et al.	7,225,006 B2	5/2007	Al-Ali et al.
6,783,492 B2	8/2004	Dominguez	7,225,007 B2	5/2007	Al-Ali
6,790,178 B1	9/2004	Mault et al.	RE39,672 E	6/2007	Shehada et al.
6,792,300 B1	9/2004	Diab et al.	7,229,415 B2	6/2007	Schwartz
6,795,724 B2	9/2004	Hogan	7,238,159 B2	7/2007	Banet et al.
6,796,186 B2	9/2004	Lia et al.	7,239,905 B2	7/2007	Kiani-Azarbayjany et al.
6,804,656 B1	10/2004	Rosenfeld	7,241,287 B2	7/2007	Shehada et al.
6,807,050 B1	10/2004	Whitehorn et al.	7,244,251 B2	7/2007	Shehada et al.
6,813,511 B2	11/2004	Diab et al.	7,245,373 B2	7/2007	Soller et al.
6,816,741 B2	11/2004	Diab	7,245,953 B1	7/2007	Parker
6,817,979 B2	11/2004	Nihtila et al.	7,252,659 B2	8/2007	Shehada et al.
6,822,564 B2	11/2004	Al-Ali	7,254,429 B2	8/2007	Schurman et al.
6,826,419 B2	11/2004	Diab et al.	7,254,431 B2	8/2007	Al-Ali
6,830,711 B2	12/2004	Mills et al.	7,254,433 B2	8/2007	Diab et al.
6,837,848 B2	1/2005	Bonner et al.	7,254,434 B2	8/2007	Schulz et al.
6,841,535 B2	1/2005	Divita et al.	7,256,708 B2	8/2007	Rosenfeld
6,850,787 B2	2/2005	Weber et al.	7,261,697 B2	8/2007	Berstein
6,850,788 B2	2/2005	Al-Ali	7,264,616 B2	9/2007	Shehada et al.
6,852,083 B2	2/2005	Caro et al.	7,267,671 B2	9/2007	Shehada et al.
6,855,112 B2	2/2005	Kao et al.	7,268,859 B2	9/2007	Sage, Jr. et al.
6,860,266 B2	3/2005	Blike	7,272,425 B2	9/2007	Al-Ali
6,861,639 B2	3/2005	Al-Ali	7,274,955 B2	9/2007	Kiani et al.
6,897,788 B2	5/2005	Khair et al.	D554,263 S	10/2007	Al-Ali
6,898,452 B2	5/2005	Al-Ali et al.	7,280,858 B2	10/2007	Al-Ali et al.
6,907,237 B1	6/2005	Dorenbosch et al.	7,285,090 B2	10/2007	Stivoric
6,915,149 B2	7/2005	Ben-haim	7,289,835 B2	10/2007	Mansfield et al.
6,920,345 B2	7/2005	Al-Ali et al.	7,292,883 B2	11/2007	De Felice et al.
6,931,268 B1	8/2005	Kiani-Azarbayjany et al.	7,295,866 B2	11/2007	Al-Ali
6,934,570 B2	8/2005	Kiani et al.	7,307,543 B2	12/2007	Rosenfeld
6,939,305 B2	9/2005	Flaherty et al.	7,313,423 B2	12/2007	Griffin et al.
6,943,348 B1	9/2005	Coffin, IV	7,314,446 B2	1/2008	Byrd et al.
6,950,687 B2	9/2005	Al-Ali	7,315,825 B2	1/2008	Rosenfeld
6,952,340 B2	10/2005	Son	7,321,862 B2	1/2008	Rosenfeld
6,961,598 B2	11/2005	Diab	7,322,971 B2	1/2008	Shehada et al.
6,970,792 B1	11/2005	Diab	7,328,053 B1	2/2008	Diab et al.
6,979,812 B2	12/2005	Al-Ali	7,332,784 B2	2/2008	Mills et al.
6,980,419 B2	12/2005	Smith et al.	7,336,187 B2	2/2008	Hubbard, Jr. et al.
6,983,179 B2	1/2006	Ben-haim	7,340,287 B2	3/2008	Mason et al.
6,985,764 B2	1/2006	Mason et al.	7,341,559 B2	3/2008	Schulz et al.
6,988,989 B2	1/2006	Weiner et al.	7,343,186 B2	3/2008	Lamego et al.
6,990,087 B2	1/2006	Rao et al.	D566,282 S	4/2008	Al-Ali et al.
6,993,371 B2	1/2006	Kiani et al.	7,355,512 B1	4/2008	Al-Ali
6,996,427 B2	2/2006	Ali et al.	7,356,178 B2	4/2008	Ziel et al.
6,997,884 B2	2/2006	Ulmsten	7,356,365 B2	4/2008	Schurman
6,999,904 B2	2/2006	Weber et al.	7,361,155 B2	4/2008	Sage, Jr. et al.
7,003,338 B2	2/2006	Weber et al.	7,371,981 B2	5/2008	Abdul-Hafiz
7,003,339 B2	2/2006	Diab et al.	7,373,193 B2	5/2008	Al-Ali et al.
7,004,907 B2	2/2006	Banet et al.	7,373,194 B2	5/2008	Weber et al.
7,015,451 B2	3/2006	Dalke et al.	7,376,453 B1	5/2008	Diab et al.
7,024,233 B2	4/2006	Ali et al.	7,377,794 B2	5/2008	Al-Ali et al.
7,025,729 B2	4/2006	De Chazal et al.	7,377,899 B2	5/2008	Weber et al.
7,027,849 B2	4/2006	Al-Ali	7,378,975 B1	5/2008	Smith et al.
7,030,749 B2	4/2006	Al-Ali	7,382,247 B2	6/2008	Welch et al.
7,033,761 B2	4/2006	Shafer	7,383,070 B2	6/2008	Diab et al.
7,035,686 B2	4/2006	Hogan	7,390,299 B2	6/2008	Weiner et al.
7,039,449 B2	5/2006	Al-Ali	7,395,216 B2	7/2008	Rosenfeld
7,041,060 B2	5/2006	Flaherty et al.	7,396,330 B2	7/2008	Banet et al.
7,044,918 B2	5/2006	Diab	7,411,509 B2	8/2008	Rosenfeld
7,048,687 B1	5/2006	Reuss et al.	7,413,546 B2	8/2008	Agutter et al.
7,063,666 B2	6/2006	Weng et al.	7,415,297 B2	8/2008	Al-Ali et al.
7,067,893 B2	6/2006	Mills et al.	7,419,483 B2	9/2008	Shehada
7,079,035 B2	7/2006	Bock et al.	7,428,432 B2	9/2008	Ali et al.
7,096,052 B2	8/2006	Mason et al.	7,433,827 B2	10/2008	Rosenfeld
7,096,054 B2	8/2006	Abdul-Hafiz et al.	7,438,683 B2	10/2008	Al-Ali et al.
7,132,641 B2	11/2006	Schulz et al.	7,439,856 B2	10/2008	Weiner et al.
7,142,901 B2	11/2006	Kiani et al.	7,440,787 B2	10/2008	Diab
7,149,561 B2	12/2006	Diab	7,454,240 B2	11/2008	Diab et al.
7,179,228 B2	2/2007	Banet	7,454,359 B2	11/2008	Rosenfeld
7,186,966 B2	3/2007	Al-Ali	7,454,360 B2	11/2008	Rosenfeld
7,188,621 B2	3/2007	DeVries et al.	7,462,151 B2	12/2008	Childre et al.
7,190,261 B2	3/2007	Al-Ali	7,467,002 B2	12/2008	Weber et al.
7,208,119 B1	4/2007	Kurtock et al.	7,467,094 B2	12/2008	Rosenfeld
7,215,984 B2	5/2007	Diab	7,469,157 B2	12/2008	Diab et al.
7,215,986 B2	5/2007	Diab	7,471,969 B2	12/2008	Diab et al.
7,221,971 B2	5/2007	Diab	7,471,971 B2	12/2008	Diab et al.
			7,475,019 B2	1/2009	Rosenfeld
			7,481,772 B2	1/2009	Banet
			7,483,729 B2	1/2009	Al-Ali et al.
			7,483,730 B2	1/2009	Diab et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,489,250 B2	2/2009	Bock et al.	7,865,232 B1	1/2011	Krishnaswamy et al.
7,489,958 B2	2/2009	Diab et al.	7,873,497 B2	1/2011	Weber et al.
7,496,391 B2	2/2009	Diab et al.	7,880,606 B2	2/2011	Al-Ali
7,496,393 B2	2/2009	Diab et al.	7,880,626 B2	2/2011	Al-Ali et al.
D587,657 S	3/2009	Al-Ali et al.	7,881,892 B2	2/2011	Soyemi et al.
7,497,828 B1	3/2009	Wilk et al.	7,890,156 B2	2/2011	Ooi et al.
7,499,741 B2	3/2009	Diab et al.	7,891,355 B2	2/2011	Al-Ali et al.
7,499,835 B2	3/2009	Weber et al.	7,894,868 B2	2/2011	Al-Ali et al.
7,500,950 B2	3/2009	Al-Ali et al.	7,899,507 B2	3/2011	Al-Ali et al.
7,509,154 B2	3/2009	Diab et al.	7,899,518 B2	3/2011	Trepagnier et al.
7,509,494 B2	3/2009	Al-Ali	7,904,132 B2	3/2011	Weber et al.
7,510,849 B2	3/2009	Schurman et al.	7,909,772 B2	3/2011	Popov et al.
7,515,043 B2	4/2009	Welch et al.	7,910,875 B2	3/2011	Al-Ali
7,515,044 B2	4/2009	Welch et al.	7,914,514 B2	3/2011	Calderon
7,526,328 B2	4/2009	Diab et al.	7,919,713 B2	4/2011	Al-Ali et al.
7,530,942 B1	5/2009	Diab	7,937,128 B2	5/2011	Al-Ali
7,530,949 B2	5/2009	Al-Ali et al.	7,937,129 B2	5/2011	Mason et al.
7,530,955 B2	5/2009	Diab et al.	7,937,130 B2	5/2011	Diab et al.
7,532,919 B2	5/2009	Soyemi et al.	7,941,199 B2	5/2011	Kiani
7,549,961 B1	6/2009	Hwang	7,951,086 B2	5/2011	Flaherty et al.
7,551,717 B2	6/2009	Tome et al.	7,957,780 B2	6/2011	Lamego et al.
7,559,520 B2	7/2009	Quijano et al.	7,962,188 B2	6/2011	Kiani et al.
7,563,110 B2	7/2009	Al-Ali et al.	7,962,190 B1	6/2011	Diab et al.
7,577,475 B2	8/2009	Consentino et al.	7,963,927 B2	6/2011	Kelleher et al.
7,588,558 B2	9/2009	Sage, Jr. et al.	7,967,749 B2	6/2011	Hutchinson et al.
7,590,950 B2	9/2009	Collins et al.	7,976,472 B2	7/2011	Kiani
7,596,398 B2	9/2009	Al-Ali et al.	7,988,637 B2	8/2011	Diab
7,597,665 B2	10/2009	Wilk et al.	7,988,639 B2	8/2011	Starks
7,612,999 B2	11/2009	Clark et al.	7,990,382 B2	8/2011	Kiani
7,616,303 B2	11/2009	Yang et al.	7,991,446 B2	8/2011	Al-Ali et al.
7,618,375 B2	11/2009	Flaherty	7,991,463 B2	8/2011	Kelleher et al.
D606,659 S	12/2009	Kiani et al.	7,991,625 B2	8/2011	Rosenfeld
7,639,145 B2	12/2009	Lawson et al.	7,993,275 B2	8/2011	Banet et al.
7,647,083 B2	1/2010	Al-Ali et al.	8,000,761 B2	8/2011	Al-Ali
7,650,291 B2	1/2010	Rosenfeld	8,008,088 B2	8/2011	Bellott et al.
D609,193 S	2/2010	Al-Ali et al.	RE42,753 E	9/2011	Kiani-Azarbayjany et al.
7,654,966 B2	2/2010	Westinskow et al.	8,019,400 B2	9/2011	Diab et al.
7,658,716 B2	2/2010	Banet et al.	8,027,846 B2	9/2011	Schoenberg
7,684,845 B2	3/2010	Juan	8,028,701 B2	10/2011	Al-Ali et al.
7,689,437 B1	3/2010	Teller et al.	8,029,765 B2	10/2011	Bellott et al.
RE41,236 E	4/2010	Seely	8,033,996 B2	10/2011	Behar
D614,305 S	4/2010	Al-Ali et al.	8,036,727 B2	10/2011	Schurman et al.
7,693,697 B2	4/2010	Westinskow et al.	8,036,728 B2	10/2011	Diab et al.
RE41,317 E	5/2010	Parker	8,036,736 B2	10/2011	Snyder et al.
7,722,542 B2	5/2010	Lia et al.	8,038,625 B2	10/2011	Afonso et al.
7,729,733 B2	6/2010	Al-Ali et al.	8,046,040 B2	10/2011	Ali et al.
7,734,320 B2	6/2010	Al-Ali	8,046,041 B2	10/2011	Diab et al.
7,736,318 B2	6/2010	Consentino et al.	8,046,042 B2	10/2011	Diab et al.
7,740,590 B2	6/2010	Bernstein	8,048,040 B2	11/2011	Kiani
7,761,127 B2	7/2010	Al-Ali et al.	8,050,728 B2	11/2011	Al-Ali et al.
7,761,128 B2	7/2010	Al-Ali et al.	8,068,104 B2	11/2011	Rampersad
7,763,420 B2	7/2010	Strizker et al.	8,073,707 B2	12/2011	Teller et al.
7,764,982 B2	7/2010	Dalke et al.	RE43,169 E	2/2012	Parker
D621,515 S	8/2010	Chua et al.	8,118,620 B2	2/2012	Al-Ali et al.
D621,516 S	8/2010	Kiani et al.	8,126,528 B2	2/2012	Diab et al.
7,766,818 B2	8/2010	Iketani et al.	8,128,572 B2	3/2012	Diab et al.
7,774,060 B2	8/2010	Westenskow et al.	8,130,105 B2	3/2012	Al-Ali et al.
7,778,851 B2	8/2010	Schoenberg et al.	8,145,287 B2	3/2012	Diab et al.
7,783,879 B2	8/2010	Krummel et al.	8,150,487 B2	4/2012	Diab et al.
7,791,155 B2	9/2010	Diab	D659,836 S	5/2012	Bensch et al.
7,794,407 B2	9/2010	Rothenberg	8,170,887 B2	5/2012	Rosenfeld
7,801,581 B2	9/2010	Diab	8,175,672 B2	5/2012	Parker
7,803,120 B2	9/2010	Banet et al.	8,175,895 B2	5/2012	Rosenfeld
7,806,830 B2	10/2010	Bernstein	8,180,420 B2	5/2012	Diab et al.
7,820,184 B2	10/2010	Strizker et al.	8,180,440 B2	5/2012	McCombie et al.
7,822,452 B2	10/2010	Schurman et al.	8,182,443 B1	5/2012	Kiani
RE41,912 E	11/2010	Parker	8,185,180 B2	5/2012	Diab et al.
7,831,450 B2	11/2010	Schoenberg	8,190,223 B2	5/2012	Al-Ali et al.
7,841,986 B2	11/2010	He et al.	8,190,227 B2	5/2012	Diab et al.
7,844,313 B2	11/2010	Kiani et al.	8,200,321 B2	6/2012	McCombie et al.
7,844,314 B2	11/2010	Al-Ali	8,203,438 B2	6/2012	Kiani et al.
7,844,315 B2	11/2010	Al-Ali	8,203,704 B2	6/2012	Merritt et al.
7,848,935 B2	12/2010	Gotlib	8,204,566 B2	6/2012	Schurman et al.
7,858,322 B2	12/2010	Tymianski et al.	8,206,312 B2	6/2012	Farquhar
7,865,222 B2	1/2011	Weber et al.	8,214,007 B2	7/2012	Baker et al.
			8,219,172 B2	7/2012	Schurman et al.
			8,224,411 B2	7/2012	Al-Ali et al.
			8,228,181 B2	7/2012	Al-Ali
			8,229,533 B2	7/2012	Diab et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,233,955	B2	7/2012	Al-Ali et al.	8,532,727	B2	9/2013	Ali et al.
8,235,907	B2	8/2012	Wilk et al.	8,532,728	B2	9/2013	Diab et al.
8,239,010	B2	8/2012	Banet et al.	D692,145	S	10/2013	Al-Ali et al.
8,239,780	B2	8/2012	Manetta et al.	8,545,417	B2	10/2013	Banet et al.
8,241,213	B2	8/2012	Lynn et al.	8,547,209	B2	10/2013	Kiani et al.
8,244,325	B2	8/2012	Al-Ali et al.	8,548,548	B2	10/2013	Al-Ali
8,249,815	B2	8/2012	Taylor	8,548,549	B2	10/2013	Schurman et al.
8,255,026	B1	8/2012	Al-Ali	8,548,550	B2	10/2013	Al-Ali et al.
8,255,027	B2	8/2012	Al-Ali et al.	8,554,297	B2	10/2013	Moon et al.
8,255,028	B2	8/2012	Al-Ali et al.	8,560,032	B2	10/2013	Al-Ali et al.
8,260,577	B2	9/2012	Weber et al.	8,560,034	B1	10/2013	Diab et al.
8,265,723	B1	9/2012	McHale et al.	8,570,167	B2	10/2013	Al-Ali
8,274,360	B2	9/2012	Sampath et al.	8,570,503	B2	10/2013	Vo et al.
8,280,473	B2	10/2012	Al-Ali	8,571,617	B2	10/2013	Reichgott et al.
8,294,588	B2	10/2012	Fisher et al.	8,571,618	B1	10/2013	Lamego et al.
8,294,716	B2	10/2012	Lord et al.	8,571,619	B2	10/2013	Al-Ali et al.
8,301,217	B2	10/2012	Al-Ali et al.	8,574,161	B2	11/2013	Banet et al.
8,306,596	B2	11/2012	Schurman et al.	8,577,431	B2	11/2013	Lamego et al.
8,310,336	B2	11/2012	Muhsin et al.	8,579,813	B2	11/2013	Causey, III et al.
8,311,747	B2	11/2012	Taylor	8,581,732	B2	11/2013	Al-Ali et al.
8,311,748	B2	11/2012	Taylor et al.	8,588,880	B2	11/2013	Abdul-Hafiz et al.
8,315,683	B2	11/2012	Al-Ali et al.	8,588,924	B2	11/2013	Dion
8,315,812	B2	11/2012	Taylor	8,591,411	B2	11/2013	Banet et al.
8,315,813	B2	11/2012	Taylor et al.	8,594,776	B2	11/2013	McCombie et al.
8,315,814	B2	11/2012	Taylor et al.	8,584,345	B2	12/2013	Al-Ali et al.
8,321,004	B2	11/2012	Moon et al.	8,600,467	B2	12/2013	Al-Ali et al.
8,321,150	B2	11/2012	Taylor	8,600,777	B2	12/2013	Schoenberg
RE43,860	E	12/2012	Parker	8,602,997	B2	12/2013	Banet et al.
8,326,649	B2	12/2012	Rosenfeld	8,606,342	B2	12/2013	Diab
8,337,403	B2	12/2012	Al-Ali et al.	8,620,678	B2	12/2013	Gotlib
8,346,330	B2	1/2013	Lamego	8,622,922	B2	1/2014	Banet et al.
8,353,842	B2	1/2013	Al-Ali et al.	8,626,255	B2	1/2014	Al-Ali et al.
8,355,766	B2	1/2013	MacNeish, III et al.	8,630,691	B2	1/2014	Lamego et al.
8,359,080	B2	1/2013	Diab et al.	8,634,889	B2	1/2014	Al-Ali et al.
8,360,936	B2	1/2013	Dibenedetto et al.	8,641,631	B2	2/2014	Sierra et al.
8,364,223	B2	1/2013	Al-Ali et al.	8,652,060	B2	2/2014	Al-Ali
8,364,226	B2	1/2013	Diab et al.	8,663,107	B2	3/2014	Kiani
8,364,250	B2	1/2013	Moon et al.	8,666,468	B1	3/2014	Al-Ali
8,374,665	B2	2/2013	Lamego	8,667,967	B2	3/2014	Al-Ali et al.
8,385,995	B2	2/2013	Al-Ali et al.	8,670,811	B2	3/2014	O'Reilly
8,385,996	B2	2/2013	Smith et al.	8,670,814	B2	3/2014	Diab et al.
D679,018	S	3/2013	Fullerton et al.	8,672,854	B2	3/2014	McCombie et al.
8,388,353	B2	3/2013	Kiani et al.	8,676,286	B2	3/2014	Weber et al.
8,399,822	B2	3/2013	Al-Ali	8,682,407	B2	3/2014	Al-Ali
8,401,602	B2	3/2013	Kiani	RE44,823	E	4/2014	Parker
8,401,874	B2	3/2013	Rosenfeld	RE44,875	E	4/2014	Kiani et al.
8,405,608	B2	3/2013	Al-Ali et al.	8,690,799	B2	4/2014	Telfort et al.
8,414,499	B2	4/2013	Al-Ali et al.	8,700,112	B2	4/2014	Kiani
8,418,524	B2	4/2013	Al-Ali	8,702,627	B2	4/2014	Telfort et al.
8,419,649	B2	4/2013	Banet et al.	8,706,179	B2	4/2014	Parker
8,423,106	B2	4/2013	Lamego et al.	8,712,494	B1	4/2014	MacNeish, III et al.
8,428,967	B2	4/2013	Olsen et al.	8,715,206	B2	5/2014	Telfort et al.
8,430,817	B1	4/2013	Al-Ali et al.	8,718,735	B2	5/2014	Lamego et al.
8,437,824	B2	5/2013	Moon et al.	8,718,737	B2	5/2014	Diab et al.
8,437,825	B2	5/2013	Dalvi et al.	8,718,738	B2	5/2014	Blank et al.
8,442,607	B2	5/2013	Banet et al.	8,720,249	B2	5/2014	Al-Ali
8,449,469	B2	5/2013	Banet et al.	8,721,541	B2	5/2014	Al-Ali et al.
8,455,290	B2	6/2013	Siskavich	8,721,542	B2	5/2014	Al-Ali et al.
8,457,703	B2	6/2013	Al-Ali	8,723,677	B1	5/2014	Kiani
8,457,707	B2	6/2013	Kiani	8,727,977	B2	5/2014	Banet et al.
8,463,349	B2	6/2013	Diab et al.	8,738,118	B2	5/2014	Moon et al.
8,466,286	B2	6/2013	Bellot et al.	8,740,792	B1	6/2014	Kiani et al.
8,471,713	B2	6/2013	Poeze et al.	8,740,802	B2	6/2014	Banet et al.
8,473,020	B2	6/2013	Kiani et al.	8,740,807	B2	6/2014	Banet et al.
8,475,370	B2	7/2013	McCombie et al.	8,747,330	B2	6/2014	Banet et al.
8,483,787	B2	7/2013	Al-Ali et al.	8,754,776	B2	6/2014	Poeze et al.
8,489,364	B2	7/2013	Weber et al.	8,755,535	B2	6/2014	Telfort et al.
8,498,684	B2	7/2013	Weber et al.	8,755,856	B2	6/2014	Diab et al.
8,504,128	B2	8/2013	Blank et al.	8,755,872	B1	6/2014	Marinow
8,506,480	B2	8/2013	Banet et al.	8,761,850	B2	6/2014	Lamego
8,509,867	B2	8/2013	Workman et al.	D709,846	S	7/2014	Oswaks
8,515,509	B2	8/2013	Bruinsma et al.	8,764,671	B2	7/2014	Kiani
8,523,781	B2	9/2013	Al-Ali	8,768,423	B2	7/2014	Shakespeare et al.
8,527,038	B2	9/2013	Moon et al.	8,771,204	B2	7/2014	Telfort et al.
8,529,301	B2	9/2013	Al-Ali et al.	8,777,634	B2	7/2014	Kiani et al.
				8,781,543	B2	7/2014	Diab et al.
				8,781,544	B2	7/2014	Al-Ali et al.
				8,781,549	B2	7/2014	Al-Ali et al.
				8,788,003	B2	7/2014	Schurman et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,790,268	B2	7/2014	Al-Ali	9,161,700	B2	10/2015	Banet et al.
8,801,613	B2	8/2014	Al-Ali et al.	9,161,713	B2	10/2015	Al-Ali et al.
8,808,188	B2	8/2014	Banet et al.	9,167,995	B2	10/2015	Lamego et al.
8,818,477	B2	8/2014	Soller	9,173,593	B2	11/2015	Banet et al.
8,821,397	B2	9/2014	Al-Ali et al.	9,173,594	B2	11/2015	Banet et al.
8,821,415	B2	9/2014	Al-Ali et al.	9,176,141	B2	11/2015	Al-Ali et al.
8,830,449	B1	9/2014	Lamego et al.	9,186,102	B2	11/2015	Bruinsma et al.
8,831,700	B2	9/2014	Schurman et al.	9,192,312	B2	11/2015	Al-Ali
8,840,549	B2	9/2014	Al-Ali	9,192,329	B2	11/2015	Al-Ali
8,847,740	B2	9/2014	Kiani et al.	9,192,351	B1	11/2015	Telfort et al.
8,849,365	B2	9/2014	Smith et al.	9,195,385	B2	11/2015	Al-Ali et al.
8,852,094	B2	10/2014	Al-Ali et al.	D745,167	S	12/2015	Canas et al.
8,852,994	B2	10/2014	Wojtczuk et al.	9,211,072	B2	12/2015	Kiani
8,866,620	B2	10/2014	Amir	9,211,095	B1	12/2015	Al-Ali
8,868,147	B2	10/2014	Stippick et al.	9,215,986	B2	12/2015	Banet et al.
8,868,150	B2	10/2014	Al-Ali et al.	9,218,454	B2	12/2015	Kiani et al.
8,870,792	B2	10/2014	Al-Ali et al.	9,226,696	B2	1/2016	Kiani
8,873,035	B2	10/2014	Yang et al.	9,241,662	B2	1/2016	Al-Ali et al.
8,878,888	B2	11/2014	Rosenfeld	9,245,668	B1	1/2016	Vo et al.
8,886,271	B2	11/2014	Kiani et al.	9,259,185	B2	2/2016	Abdul-Hafiz et al.
8,888,539	B2	11/2014	Al-Ali et al.	9,267,572	B2	2/2016	Barker et al.
8,888,700	B2	11/2014	Banet et al.	9,277,880	B2	3/2016	Poeze et al.
8,888,708	B2	11/2014	Diab et al.	9,289,167	B2	3/2016	Diab et al.
8,892,180	B2	11/2014	Weber et al.	9,295,421	B2	3/2016	Kiani et al.
8,897,847	B2	11/2014	Al-Ali	9,307,915	B2	4/2016	McCombie et al.
8,907,287	B2	12/2014	Vanderpohl	9,307,928	B1	4/2016	Al-Ali et al.
8,909,310	B2	12/2014	Lamego et al.	9,323,894	B2	4/2016	Kiani
8,909,330	B2	12/2014	McCombie et al.	D755,392	S	5/2016	Hwang et al.
8,911,377	B2	12/2014	Al-Ali	9,326,712	B1	5/2016	Kiani
8,912,909	B2	12/2014	Al-Ali et al.	9,333,316	B2	5/2016	Kiani
8,920,317	B2	12/2014	Al-Ali et al.	9,339,209	B2	5/2016	Banet et al.
8,921,699	B2	12/2014	Al-Ali et al.	9,339,211	B2	5/2016	Banet et al.
8,922,382	B2	12/2014	Al-Ali et al.	9,339,220	B2	5/2016	Lamego et al.
8,929,964	B2	1/2015	Al-Ali et al.	9,341,565	B2	5/2016	Lamego et al.
8,942,777	B2	1/2015	Diab et al.	9,351,673	B2	5/2016	Diab et al.
8,948,834	B2	2/2015	Diab et al.	9,351,675	B2	5/2016	Al-Ali et al.
8,948,835	B2	2/2015	Diab	9,364,158	B2	6/2016	Banet et al.
8,956,293	B2	2/2015	McCombie et al.	9,364,181	B2	6/2016	Kiani
8,956,294	B2	2/2015	McCombie et al.	9,368,671	B2	6/2016	Wojtczuk et al.
8,965,471	B2	2/2015	Lamego	9,370,325	B2	6/2016	Al-Ali et al.
8,979,765	B2	3/2015	Banet et al.	9,370,326	B2	6/2016	McHale et al.
8,983,564	B2	3/2015	Al-Ali	9,370,335	B2	6/2016	Al-Ali et al.
8,989,831	B2	3/2015	Al-Ali et al.	9,375,185	B2	6/2016	Al-Ali et al.
8,996,085	B2	3/2015	Kiani et al.	9,380,952	B2	7/2016	Banet et al.
8,998,809	B2	4/2015	Kiani	9,386,953	B2	7/2016	Al-Ali
9,028,429	B2	5/2015	Telfort et al.	9,386,961	B2	7/2016	Al-Ali et al.
9,037,207	B2	5/2015	Al-Ali et al.	9,392,945	B2	7/2016	Al-Ali et al.
9,055,928	B2	6/2015	McCombie et al.	9,397,448	B2	7/2016	Al-Ali et al.
9,057,689	B2	6/2015	Soller et al.	9,408,542	B1	8/2016	Kinast et al.
9,060,721	B2	6/2015	Reichgott et al.	9,408,573	B2	8/2016	Welch et al.
9,066,666	B2	6/2015	Kiani	9,436,645	B2	9/2016	Al-Ali et al.
9,066,680	B1	6/2015	Al-Ali et al.	9,439,574	B2	9/2016	McCombie et al.
9,072,474	B2	7/2015	Al-Ali et al.	9,445,759	B1	9/2016	Lamego et al.
9,078,560	B2	7/2015	Schurman et al.	9,466,919	B2	10/2016	Kiani et al.
9,084,569	B2	7/2015	Weber et al.	9,474,474	B2	10/2016	Lamego et al.
9,095,291	B2	8/2015	Soller et al.	9,480,422	B2	11/2016	Al-Ali
9,095,316	B2	8/2015	Welch et al.	9,480,435	B2	11/2016	Olsen
9,106,038	B2	8/2015	Telfort et al.	9,492,110	B2	11/2016	Al-Ali et al.
9,107,625	B2	8/2015	Telfort et al.	9,510,779	B2	12/2016	Poeze et al.
9,107,626	B2	8/2015	Al-Ali et al.	9,517,024	B2	12/2016	Kiani et al.
9,113,831	B2	8/2015	Al-Ali	9,532,722	B2	1/2017	Lamego et al.
9,113,832	B2	8/2015	Al-Ali	9,538,949	B2	1/2017	Al-Ali et al.
9,119,595	B2	9/2015	Lamego	9,538,980	B2	1/2017	Telfort et al.
9,131,881	B2	9/2015	Diab et al.	9,549,696	B2	1/2017	Lamego et al.
9,131,882	B2	9/2015	Al-Ali et al.	9,554,737	B2	1/2017	Schurman et al.
9,131,883	B2	9/2015	Al-Ali	9,560,996	B2	2/2017	Kiani
9,131,917	B2	9/2015	Telfort et al.	9,560,998	B2	2/2017	Al-Ali et al.
9,138,180	B1	9/2015	Coverston et al.	9,566,007	B2	2/2017	McCombie et al.
9,138,182	B2	9/2015	Al-Ali et al.	9,566,019	B2	2/2017	Al-Ali et al.
9,138,192	B2	9/2015	Weber et al.	9,579,039	B2	2/2017	Jansen et al.
9,142,117	B2	9/2015	Muhsin et al.	9,591,975	B2	3/2017	Dalvi et al.
9,149,192	B2	10/2015	Banet et al.	9,622,692	B2	4/2017	Lamego et al.
9,153,112	B1	10/2015	Kiani et al.	9,622,693	B2	4/2017	Diab
9,153,121	B2	10/2015	Kiani et al.	D788,312	S	5/2017	Al-Ali et al.
9,161,696	B2	10/2015	Al-Ali et al.	9,636,055	B2	5/2017	Al-Ali et al.
				9,636,056	B2	5/2017	Al-Ali
				9,649,054	B2	5/2017	Lamego et al.
				9,655,546	B2	5/2017	Shen et al.
				9,662,052	B2	5/2017	Al-Ali et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

9,668,679 B2	6/2017	Schurman et al.	2001/0011355 A1	8/2001	Kawai
9,668,680 B2	6/2017	Bruinsma et al.	2001/0046366 A1	11/2001	Susskind
9,668,703 B2	6/2017	Al-Ali	2002/0045836 A1	4/2002	Alkawwas
9,675,286 B2	6/2017	Diab	2002/0052311 A1	5/2002	Solomon et al.
9,687,160 B2	6/2017	Kiani	2002/0063690 A1	5/2002	Chung et al.
9,693,719 B2	7/2017	Al-Ali et al.	2002/0140675 A1	10/2002	Ali et al.
9,693,737 B2	7/2017	Al-Ali	2002/0177758 A1	11/2002	Schoenberg
9,697,928 B2	7/2017	Al-Ali et al.	2003/0027326 A1	2/2003	Ulmsten et al.
9,717,425 B2	8/2017	Kiani et al.	2003/0052787 A1	3/2003	Zerhusen et al.
9,717,458 B2	8/2017	Lamego et al.	2003/0058838 A1	3/2003	Wengrovitz
9,724,016 B1	8/2017	Al-Ali et al.	2003/0158466 A1	8/2003	Lynn et al.
9,724,024 B2	8/2017	Al-Ali	2003/0216670 A1	11/2003	Beggs
9,724,025 B1	8/2017	Kiani et al.	2004/0013647 A1	1/2004	Solomon et al.
9,728,061 B2	8/2017	Shen et al.	2004/0090742 A1	5/2004	Son et al.
9,730,640 B2	8/2017	Diab et al.	2004/0122787 A1	6/2004	Avinash et al.
9,743,887 B2	8/2017	Al-Ali et al.	2004/0126007 A1	7/2004	Ziel et al.
9,749,232 B2	8/2017	Sampath et al.	2004/0147818 A1	7/2004	Levy et al.
9,750,442 B2	9/2017	Olsen	2004/0179332 A1	9/2004	Smith et al.
9,750,443 B2	9/2017	Smith et al.	2004/0186357 A1	9/2004	Soderberg et al.
9,750,461 B1	9/2017	Telfort	2004/0230179 A1	11/2004	Shehada et al.
9,775,545 B2	10/2017	Al-Ali et al.	2004/0243017 A1	12/2004	Causevic
9,775,546 B2	10/2017	Diab et al.	2004/0254431 A1	12/2004	Shehada et al.
9,775,570 B2	10/2017	Al-Ali	2004/0254432 A1	12/2004	Shehada et al.
9,778,079 B1	10/2017	Al-Ali et al.	2005/0005710 A1	1/2005	Sage, Jr.
9,782,077 B2	10/2017	Lamego et al.	2005/0009926 A1	1/2005	Kreye et al.
9,782,110 B2	10/2017	Kiani	2005/0020918 A1	1/2005	Wilk et al.
9,787,568 B2	10/2017	Lamego et al.	2005/0038332 A1	2/2005	Saidara et al.
9,788,735 B2	10/2017	Al-Ali	2005/0038680 A1	2/2005	McMahon
9,788,768 B2	10/2017	Al-Ali et al.	2005/0065417 A1	3/2005	Ali et al.
9,795,300 B2	10/2017	Al-Ali	2005/0080336 A1	4/2005	Byrd et al.
9,795,310 B2	10/2017	Al-Ali	2005/0096542 A1	5/2005	Weng et al.
9,795,358 B2	10/2017	Telfort et al.	2005/0113653 A1	5/2005	Fox et al.
9,795,739 B2	10/2017	Al-Ali et al.	2005/0124864 A1	6/2005	Mack et al.
9,801,556 B2	10/2017	Kiani	2005/0125256 A1	6/2005	Schoenberg
9,801,588 B2	10/2017	Weber et al.	2005/0148882 A1	7/2005	Banet et al.
9,808,188 B1	11/2017	Perea et al.	2005/0164933 A1	7/2005	Tymianski et al.
9,814,418 B2	11/2017	Weber et al.	2005/0191294 A1	9/2005	Arap et al.
9,820,691 B2	11/2017	Kiani	2005/0208648 A1	9/2005	Sage, Jr. et al.
9,833,152 B2	12/2017	Kiani et al.	2005/0209518 A1	9/2005	Sage, Jr. et al.
9,833,180 B2	12/2017	Shakespeare et al.	2005/0228244 A1	10/2005	Banet
9,839,379 B2	12/2017	Al-Ali et al.	2005/0228299 A1	10/2005	Banet
9,839,381 B1	12/2017	Weber et al.	2005/0242946 A1	11/2005	Hubbard, Jr. et al.
9,847,002 B2	12/2017	Kiani et al.	2005/0245831 A1	11/2005	Banet
9,847,749 B2	12/2017	Kiani et al.	2005/0245839 A1 *	11/2005	Stivorac G06F 19/3418 600/549
9,848,800 B1	12/2017	Lee et al.	2005/0261594 A1	11/2005	Banet
9,848,806 B2	12/2017	Al-Ali et al.	2005/0261598 A1	11/2005	Banet et al.
9,848,807 B2	12/2017	Lamego	2005/0268401 A1	12/2005	Dixon et al.
9,861,298 B2	1/2018	Eckerbom et al.	2005/0277872 A1	12/2005	Colby, Jr. et al.
9,861,304 B2	1/2018	Al-Ali et al.	2006/0009697 A1	1/2006	Banet et al.
9,861,305 B1	1/2018	Weber et al.	2006/0009698 A1	1/2006	Banet et al.
9,867,578 B2	1/2018	Al-Ali et al.	2006/0049936 A1	3/2006	Collins, Jr. et al.
9,872,623 B2	1/2018	Al-Ali	2006/0058647 A1	3/2006	Strommer et al.
9,876,320 B2	1/2018	Coverston et al.	2006/0084878 A1	4/2006	Banet et al.
9,877,650 B2	1/2018	Muhsin et al.	2006/0089543 A1	4/2006	Kim et al.
9,877,686 B2	1/2018	Al-Ali et al.	2006/0094936 A1	5/2006	Russ
9,891,079 B2	2/2018	Dalvi	2006/0149393 A1	7/2006	Calderon
9,895,107 B2	2/2018	Al-Ali et al.	2006/0155175 A1	7/2006	Ogino et al.
9,913,617 B2	3/2018	Al-Ali et al.	2006/0161054 A1	7/2006	Reuss et al.
9,924,893 B2	3/2018	Schurman et al.	2006/0200009 A1	9/2006	Wekell et al.
9,924,897 B1	3/2018	Abdul-Hafiz	2006/0217684 A1	9/2006	Shehada et al.
9,936,917 B2	4/2018	Poeze et al.	2006/0217685 A1	9/2006	Shehada et al.
9,943,269 B2	4/2018	Al-Ali et al.	2006/0224413 A1	10/2006	Kim et al.
9,949,676 B2	4/2018	Al-Ali	2006/0235300 A1	10/2006	Weng et al.
9,955,937 B2	5/2018	Telfort	2006/0253042 A1	11/2006	Stahmann et al.
9,965,946 B2	5/2018	Al-Ali et al.	2007/0000490 A1	1/2007	DeVries et al.
9,980,667 B2	5/2018	Kiani et al.	2007/0021675 A1	1/2007	Childre et al.
D820,865 S	6/2018	Muhsin et al.	2007/0027368 A1	2/2007	Collins et al.
9,986,919 B2	6/2018	Lamego et al.	2007/0032733 A1	2/2007	Burton et al.
9,986,952 B2	6/2018	Dalvi et al.	2007/0055116 A1	3/2007	Clark et al.
9,989,560 B2	6/2018	Poeze et al.	2007/0055544 A1	3/2007	Jung et al.
9,993,207 B2	6/2018	Al-Ali et al.	2007/0060798 A1	3/2007	Krupnik et al.
10,007,758 B2	6/2018	Al-Ali et al.	2007/0088406 A1	4/2007	Bennett et al.
D822,215 S	7/2018	Al-Ali et al.	2007/0096897 A1	5/2007	Weiner
D822,216 S	7/2018	Barker et al.	2007/0100222 A1	5/2007	Mastrototaro et al.
10,010,276 B2	7/2018	Al-Ali et al.	2007/0118399 A1	5/2007	Avinash et al.
			2007/0140475 A1	6/2007	Kurtock et al.
			2007/0142715 A1	6/2007	Banet et al.
			2007/0156033 A1	7/2007	Causey et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0157285 A1	7/2007	Frank et al.	2009/0124867 A1	5/2009	Hirsch et al.
2007/0159332 A1	7/2007	Koblasz	2009/0131759 A1	5/2009	Sims et al.
2007/0163589 A1	7/2007	DeVries et al.	2009/0143832 A1	6/2009	Saba
2007/0180140 A1	8/2007	Welch et al.	2009/0157058 A1	6/2009	Ferren et al.
2007/0185390 A1	8/2007	Perkins et al.	2009/0171170 A1	7/2009	Li et al.
2007/0185393 A1	8/2007	Zhou et al.	2009/0171225 A1	7/2009	Gadodia et al.
2007/0232941 A1	10/2007	Rabinovich	2009/0177090 A1	7/2009	Grunwald et al.
2007/0244724 A1	10/2007	Pendergast et al.	2009/0182287 A1	7/2009	Kassab
2007/0250286 A1 *	10/2007	Duncan	2009/0226372 A1	9/2009	Ruoslanti et al.
		A61B 5/1121	2009/0247984 A1	10/2009	Lamego et al.
		702/139	2009/0264778 A1	10/2009	Markowitz et al.
2007/0254593 A1	11/2007	Jollota et al.	2009/0275813 A1	11/2009	Davis
2007/0255114 A1	11/2007	Ackermann et al.	2009/0275844 A1	11/2009	Al-Ali
2007/0255116 A1	11/2007	Mehta et al.	2009/0281462 A1	11/2009	Heliot et al.
2007/0255250 A1	11/2007	Moberg	2009/0299157 A1	12/2009	Telfort et al.
2007/0276261 A1	11/2007	Banet et al.	2009/0309755 A1	12/2009	Williamson et al.
2007/0276262 A1	11/2007	Banet et al.	2010/0004518 A1	1/2010	Vo et al.
2007/0276632 A1	11/2007	Banet et al.	2010/0030040 A1	2/2010	Poeze et al.
2007/0282478 A1	12/2007	Al-Ali et al.	2010/0030094 A1	2/2010	Lundback
2008/0000479 A1	1/2008	Elaz et al.	2010/0036209 A1	2/2010	Ferren et al.
2008/0003200 A1	1/2008	Arap et al.	2010/0069725 A1	3/2010	Al-Ali
2008/0021854 A1	1/2008	Jung et al.	2010/0125217 A1	5/2010	Kuo et al.
2008/0033661 A1	2/2008	Syroid et al.	2010/0130875 A1	5/2010	Banet et al.
2008/0051670 A1	2/2008	Banet et al.	2010/0144627 A1	6/2010	Vitek et al.
2008/0053438 A1	3/2008	DeVries et al.	2010/0160794 A1	6/2010	Banet et al.
2008/0058614 A1	3/2008	Banet et al.	2010/0160795 A1	6/2010	Banet et al.
2008/0058657 A1	3/2008	Schwartz et al.	2010/0160796 A1	6/2010	Banet et al.
2008/0077026 A1	3/2008	Banet et al.	2010/0160797 A1	6/2010	Banet et al.
2008/0082004 A1	4/2008	Banet et al.	2010/0160798 A1	6/2010	Banet et al.
2008/0090626 A1	4/2008	Griffin et al.	2010/0168536 A1	7/2010	Banet et al.
2008/0091089 A1	4/2008	Guillory et al.	2010/0168589 A1	7/2010	Banet et al.
2008/0091090 A1	4/2008	Guillory et al.	2010/0185101 A1	7/2010	Sakai et al.
2008/0091471 A1	4/2008	Michon et al.	2010/0198622 A1	8/2010	Gajic et al.
2008/0097167 A1	4/2008	Yudkovitch et al.	2010/0210958 A1	8/2010	Manwaring et al.
2008/0099366 A1	5/2008	Niemiec et al.	2010/0261979 A1	10/2010	Kiani
2008/0108884 A1	5/2008	Kiani	2010/0261982 A1	10/2010	Noury et al.
2008/0114220 A1	5/2008	Banet et al.	2010/0298650 A1	11/2010	Moon et al.
2008/0119412 A1	5/2008	Tymianski et al.	2010/0298651 A1	11/2010	Moon et al.
2008/0138278 A1	6/2008	Scherz et al.	2010/0298652 A1	11/2010	McCombie et al.
2008/0169922 A1	7/2008	Issokson	2010/0298653 A1	11/2010	McCombie et al.
2008/0171919 A1	7/2008	Stivoric et al.	2010/0298654 A1	11/2010	McCombie et al.
2008/0188795 A1	8/2008	Katz et al.	2010/0298655 A1	11/2010	McCombie et al.
2008/0194918 A1	8/2008	Kulik et al.	2010/0298656 A1	11/2010	McCombie et al.
2008/0208912 A1	8/2008	Garibaldi	2010/0298657 A1	11/2010	McCombie et al.
2008/0221396 A1	9/2008	Garces et al.	2010/0298658 A1	11/2010	McCombie et al.
2008/0221399 A1	9/2008	Zhou et al.	2010/0298659 A1	11/2010	McCombie et al.
2008/0221461 A1	9/2008	Zhou et al.	2010/0298660 A1	11/2010	McCombie et al.
2008/0228077 A1	9/2008	Wilk et al.	2010/0298661 A1	11/2010	McCombie et al.
2008/0275309 A1	11/2008	Stivoric et al.	2010/0298742 A1	11/2010	Perlman et al.
2008/0281167 A1	11/2008	Soderberg et al.	2010/0305412 A1	12/2010	Darrah et al.
2008/0281168 A1	11/2008	Gibson et al.	2010/0312103 A1	12/2010	Gorek et al.
2008/0281181 A1	11/2008	Manziona et al.	2010/0317936 A1	12/2010	Al-Ali et al.
2008/0287751 A1	11/2008	Stivoric et al.	2010/0317951 A1	12/2010	Rutkowski et al.
2008/0292172 A1	11/2008	Assmann et al.	2010/0324384 A1	12/2010	Moon et al.
2008/0300020 A1	12/2008	Nishizawa et al.	2010/0324385 A1	12/2010	Moon et al.
2008/0312542 A1	12/2008	Banet et al.	2010/0324386 A1	12/2010	Moon et al.
2008/0319275 A1	12/2008	Chiu et al.	2010/0324387 A1	12/2010	Moon et al.
2008/0319327 A1	12/2008	Banet et al.	2010/0324388 A1	12/2010	Moon et al.
2008/0319354 A1	12/2008	Bell et al.	2010/0324389 A1	12/2010	Moon et al.
2009/0005651 A1	1/2009	Ward et al.	2011/0001605 A1	1/2011	Kiani et al.
2009/0018409 A1	1/2009	Banet et al.	2011/0021930 A1	1/2011	Mazzeo et al.
2009/0018422 A1	1/2009	Banet et al.	2011/0023130 A1	1/2011	Gudgel et al.
2009/0018453 A1	1/2009	Banet et al.	2011/0028809 A1	2/2011	Goodman
2009/0018808 A1	1/2009	Bronstein et al.	2011/0046495 A1	2/2011	Osyppka
2009/0024008 A1	1/2009	Brunner et al.	2011/0066051 A1	3/2011	Moon et al.
2009/0052623 A1	2/2009	Torne et al.	2011/0077473 A1	3/2011	Lisogurski
2009/0054735 A1	2/2009	Higgins et al.	2011/0077488 A1	3/2011	Buxton et al.
2009/0054743 A1	2/2009	Stewart	2011/0078596 A1	3/2011	Rawlins et al.
2009/0062682 A1	3/2009	Bland et al.	2011/0080294 A1	4/2011	Tanishima et al.
2009/0069642 A1	3/2009	Gao et al.	2011/0082711 A1	4/2011	Poeze et al.
2009/0069868 A1	3/2009	Bengtsson et al.	2011/0087084 A1	4/2011	Jeong et al.
2009/0099480 A1	4/2009	Salgo et al.	2011/0087117 A1	4/2011	Tremper et al.
2009/0112072 A1	4/2009	Banet et al.	2011/0087756 A1	4/2011	Biondi et al.
2009/0118628 A1	5/2009	Zhou et al.	2011/0098583 A1	4/2011	Pandia et al.
2009/0119330 A1	5/2009	Sampath et al.	2011/0105854 A1	5/2011	Kiani et al.
2009/0119843 A1	5/2009	Rodgers et al.	2011/0118573 A1	5/2011	Mckenna
			2011/0125060 A1	5/2011	Telfort et al.
			2011/0152629 A1	6/2011	Eaton et al.
			2011/0172967 A1	7/2011	Al-Ali et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0184252 A1	7/2011	Archer et al.	2013/0046197 A1	2/2013	Dlugos, Jr. et al.
2011/0184253 A1	7/2011	Archer et al.	2013/0046204 A1	2/2013	Lamego et al.
2011/0208015 A1	8/2011	Welch et al.	2013/0060108 A1	3/2013	Schurman et al.
2011/0208018 A1	8/2011	Kiani	2013/0060147 A1	3/2013	Welch et al.
2011/0208073 A1	8/2011	Matsukawa et al.	2013/0079610 A1	3/2013	Al-Ali
2011/0209915 A1	9/2011	Telfort et al.	2013/0096405 A1	4/2013	Garfio
2011/0212090 A1	9/2011	Pedersen et al.	2013/0096936 A1	4/2013	Sampath et al.
2011/0213212 A1	9/2011	Al-Ali	2013/0109929 A1	5/2013	Menzel
2011/0224498 A1	9/2011	Banet et al.	2013/0109935 A1	5/2013	Al-Ali et al.
2011/0224499 A1	9/2011	Banet et al.	2013/0109937 A1	5/2013	Banet et al.
2011/0224500 A1	9/2011	Banet et al.	2013/0116515 A1	5/2013	Banet et al.
2011/0224506 A1	9/2011	Moon et al.	2013/0155889 A1	6/2013	Brownworth et al.
2011/0224507 A1	9/2011	Banet et al.	2013/0162433 A1	6/2013	Muhsin et al.
2011/0224508 A1	9/2011	Moon et al.	2013/0178749 A1	7/2013	Lamego
2011/0224556 A1	9/2011	Moon et al.	2013/0190581 A1	7/2013	Al-Ali et al.
2011/0224557 A1	9/2011	Banet et al.	2013/0197328 A1	8/2013	Diab et al.
2011/0224564 A1	9/2011	Moon et al.	2013/0211214 A1	8/2013	Olsen
2011/0227739 A1	9/2011	Gilham et al.	2013/0243021 A1	9/2013	Siskavich
2011/0230733 A1	9/2011	Al-Ali	2013/0253334 A1	9/2013	Al-Ali et al.
2011/0237911 A1	9/2011	Lamego et al.	2013/0261494 A1	10/2013	Bloom et al.
2011/0257489 A1	10/2011	Banet et al.	2013/0262730 A1	10/2013	Al-Ali et al.
2011/0257544 A1	10/2011	Kaasinen et al.	2013/0274571 A1	10/2013	Diab et al.
2011/0257551 A1	10/2011	Banet et al.	2013/0296672 A1	11/2013	O'Neil et al.
2011/0257552 A1	10/2011	Banet et al.	2013/0296713 A1	11/2013	Al-Ali et al.
2011/0257553 A1	10/2011	Banet et al.	2013/0317327 A1	11/2013	Al-Ali et al.
2011/0257554 A1	10/2011	Banet et al.	2013/0317370 A1	11/2013	Dalvi et al.
2011/0257555 A1	10/2011	Banet et al.	2013/0317393 A1	11/2013	Weiss et al.
2011/0263950 A1	10/2011	Larson et al.	2013/0324808 A1	12/2013	Al-Ali et al.
2011/0288421 A1	11/2011	Banet et al.	2013/0324817 A1	12/2013	Diab
2011/0295094 A1	12/2011	Doyle et al.	2013/0331660 A1	12/2013	Al-Ali et al.
2012/0001751 A1	1/2012	Baker et al.	2013/0331670 A1	12/2013	Kiani
2012/0004579 A1	1/2012	Luo et al.	2013/0338461 A1	12/2013	Lamego et al.
2012/0029300 A1	2/2012	Paquet	2013/0340176 A1	12/2013	Stevens et al.
2012/0029304 A1	2/2012	Medina et al.	2014/0005502 A1	1/2014	Klap et al.
2012/0029879 A1	2/2012	Sing et al.	2014/0012100 A1	1/2014	Al-Ali et al.
2012/0059230 A1	3/2012	Teller et al.	2014/0022081 A1	1/2014	Ribble et al.
2012/0059267 A1	3/2012	Lamego et al.	2014/0025010 A1	1/2014	Stroup et al.
2012/0071771 A1	3/2012	Behar	2014/0025306 A1	1/2014	Weber et al.
2012/0075464 A1	3/2012	Derenne et al.	2014/0031650 A1	1/2014	Weber et al.
2012/0095778 A1	4/2012	Gross et al.	2014/0034353 A1	2/2014	Al-Ali et al.
2012/0101353 A1	4/2012	Reggiardo et al.	2014/0046674 A1	2/2014	Rosenfeld
2012/0108983 A1	5/2012	Banet et al.	2014/0051952 A1	2/2014	Reichgott et al.
2012/0116175 A1	5/2012	Al-Ali et al.	2014/0051953 A1	2/2014	Lamego et al.
2012/0117209 A1	5/2012	Sinha	2014/0051954 A1	2/2014	Al-Ali et al.
2012/0123799 A1	5/2012	Nolen et al.	2014/0058230 A1	2/2014	Abdul-Hafiz et al.
2012/0136221 A1	5/2012	Killen et al.	2014/0066783 A1	3/2014	Kiani et al.
2012/0165629 A1	6/2012	Merritt et al.	2014/0073167 A1	3/2014	Al-Ali et al.
2012/0179006 A1	7/2012	Jansen et al.	2014/0077956 A1	3/2014	Sampath et al.
2012/0179011 A1	7/2012	Moon et al.	2014/0081097 A1	3/2014	Al-Ali et al.
2012/0184120 A1	7/2012	Basta et al.	2014/0081099 A1	3/2014	Banet et al.
2012/0190949 A1	7/2012	McCombie et al.	2014/0081100 A1	3/2014	Muhsin et al.
2012/0197619 A1	8/2012	Namer Yelin et al.	2014/0081175 A1	3/2014	Telfort
2012/0203078 A1	8/2012	Sze et al.	2014/0088385 A1	3/2014	Moon et al.
2012/0209082 A1	8/2012	Al-Ali	2014/0094667 A1	4/2014	Schurman et al.
2012/0209084 A1	8/2012	Olsen et al.	2014/0100434 A1	4/2014	Diab et al.
2012/0226160 A1	9/2012	Kudoh	2014/0114199 A1	4/2014	Lamego et al.
2012/0227739 A1	9/2012	Kiani	2014/0120564 A1	5/2014	Workman et al.
2012/0239434 A1	9/2012	Breslow et al.	2014/0121482 A1	5/2014	Merritt et al.
2012/0242501 A1	9/2012	Tran et al.	2014/0121483 A1	5/2014	Kiani
2012/0265039 A1	10/2012	Kiani	2014/0125495 A1	5/2014	Al-Ali
2012/0282583 A1	11/2012	Thaler et al.	2014/0127137 A1	5/2014	Bellott et al.
2012/0283524 A1	11/2012	Kiani et al.	2014/0128696 A1	5/2014	Al-Ali
2012/0284053 A1	11/2012	Rosenfeld	2014/0128699 A1	5/2014	Al-Ali et al.
2012/0286955 A1	11/2012	Welch et al.	2014/0129702 A1	5/2014	Lamego et al.
2012/0294801 A1	11/2012	Scherz et al.	2014/0135588 A1	5/2014	Al-Ali et al.
2012/0296178 A1	11/2012	Lamego et al.	2014/0142399 A1	5/2014	Al-Ali et al.
2012/0302894 A1	11/2012	Diab et al.	2014/0142401 A1	5/2014	Al-Ali et al.
2012/0319816 A1	12/2012	Al-Ali	2014/0142402 A1	5/2014	Al-Ali et al.
2012/0330112 A1	12/2012	Lamego et al.	2014/0142445 A1	5/2014	Banet et al.
2013/0006131 A1	1/2013	Narayan et al.	2014/0152673 A1	6/2014	Lynn et al.
2013/0006151 A1	1/2013	Main et al.	2014/0155712 A1	6/2014	Lamego et al.
2013/0023775 A1	1/2013	Lamego et al.	2014/0163344 A1	6/2014	Al-Ali
2013/0035603 A1	2/2013	Jaraus et al.	2014/0163393 A1	6/2014	McCombie et al.
2013/0041591 A1	2/2013	Lamego	2014/0163402 A1	6/2014	Lamego et al.
2013/0045685 A1	2/2013	Kiani	2014/0166076 A1	6/2014	Kiani et al.
			2014/0171763 A1	6/2014	Diab
			2014/0180038 A1	6/2014	Kiani
			2014/0180154 A1	6/2014	Sierra et al.
			2014/0180160 A1	6/2014	Brown et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0187973 A1	7/2014	Brown et al.	2015/0208966 A1	7/2015	Al-Ali
2014/0194709 A1	7/2014	Al-Ali et al.	2015/0216459 A1	8/2015	Al-Ali et al.
2014/0194711 A1	7/2014	Al-Ali	2015/0230755 A1	8/2015	Al-Ali et al.
2014/0194766 A1	7/2014	Al-Ali et al.	2015/0238722 A1	8/2015	Al-Ali
2014/0200415 A1	7/2014	McCombie et al.	2015/0245773 A1	9/2015	Lamego et al.
2014/0200420 A1	7/2014	Al-Ali	2015/0245794 A1	9/2015	Al-Ali
2014/0200422 A1	7/2014	Weber et al.	2015/0254956 A1	9/2015	Shen et al.
2014/0206963 A1	7/2014	Al-Ali	2015/0257689 A1	9/2015	Al-Ali et al.
2014/0213864 A1	7/2014	Abdul-Hafiz et al.	2015/0272481 A1	10/2015	Glaser et al.
2014/0235964 A1	8/2014	Banet et al.	2015/0272514 A1	10/2015	Kiani et al.
2014/0243627 A1	8/2014	Diab et al.	2015/0282717 A1	10/2015	McCombie et al.
2014/0249431 A1	9/2014	Banet et al.	2015/0351697 A1	12/2015	Weber et al.
2014/0249432 A1	9/2014	Banet et al.	2015/0351704 A1	12/2015	Kiani et al.
2014/0249433 A1	9/2014	Banet et al.	2015/0359429 A1	12/2015	Al-Ali et al.
2014/0249434 A1	9/2014	Banet et al.	2015/0366472 A1	12/2015	Kiani
2014/0249435 A1	9/2014	Banet et al.	2015/0366507 A1	12/2015	Blank et al.
2014/0249440 A1	9/2014	Banet et al.	2015/0374298 A1	12/2015	Al-Ali et al.
2014/0249441 A1	9/2014	Banet et al.	2015/0380875 A1	12/2015	Coverston et al.
2014/0249442 A1	9/2014	Banet et al.	2016/0000362 A1	1/2016	Diab et al.
2014/0257056 A1	9/2014	Moon et al.	2016/0007930 A1	1/2016	Weber et al.
2014/0257057 A1	9/2014	Reis Cunha et al.	2016/0022224 A1	1/2016	Banet et al.
2014/0266787 A1	9/2014	Tran	2016/0029932 A1	2/2016	Al-Ali
2014/0266790 A1	9/2014	Al-Ali et al.	2016/0029933 A1	2/2016	Al-Ali et al.
2014/0275808 A1	9/2014	Poeze et al.	2016/0045118 A1	2/2016	Kiani
2014/0275835 A1	9/2014	Lamego et al.	2016/0045163 A1	2/2016	Weisner et al.
2014/0275871 A1	9/2014	Lamego et al.	2016/0051205 A1	2/2016	Al-Ali et al.
2014/0275872 A1	9/2014	Merritt et al.	2016/0058338 A1	3/2016	Schurman et al.
2014/0275881 A1	9/2014	Lamego et al.	2016/0058347 A1	3/2016	Reichgott et al.
2014/0276115 A1	9/2014	Dalvi et al.	2016/0066823 A1	3/2016	Al-Ali et al.
2014/0276145 A1	9/2014	Banet et al.	2016/0066824 A1	3/2016	Al-Ali et al.
2014/0276175 A1	9/2014	Banet et al.	2016/0066879 A1	3/2016	Telfort et al.
2014/0288400 A1	9/2014	Diab et al.	2016/0072429 A1	3/2016	Kiani et al.
2014/0296664 A1	10/2014	Bruinsma et al.	2016/0073967 A1	3/2016	Lamego et al.
2014/0301893 A1	10/2014	Stroup et al.	2016/0081552 A1	3/2016	Wojtczuk et al.
2014/0303520 A1	10/2014	Telfort et al.	2016/0095543 A1	4/2016	Telfort et al.
2014/0309506 A1	10/2014	Lamego et al.	2016/0095548 A1	4/2016	Al-Ali et al.
2014/0309559 A1	10/2014	Telfort et al.	2016/0103598 A1	4/2016	Al-Ali et al.
2014/0316217 A1	10/2014	Purdon et al.	2016/0113527 A1	4/2016	Al-Ali
2014/0316218 A1	10/2014	Purdon et al.	2016/0143546 A1	5/2016	McCombie et al.
2014/0316228 A1	10/2014	Blank et al.	2016/0143548 A1	5/2016	Al-Ali
2014/0323825 A1	10/2014	Al-Ali et al.	2016/0166182 A1	6/2016	Al-Ali et al.
2014/0323897 A1	10/2014	Brown et al.	2016/0166183 A1	6/2016	Poeze et al.
2014/0323898 A1	10/2014	Purdon et al.	2016/0166188 A1	6/2016	Bruinsma et al.
2014/0330092 A1	11/2014	Al-Ali et al.	2016/0166210 A1	6/2016	Al-Ali
2014/0330098 A1	11/2014	Merritt et al.	2016/0183794 A1*	6/2016	Gannon A61B 5/0008 600/549
2014/0330099 A1	11/2014	Al-Ali et al.	2016/0192869 A1	7/2016	Kiani et al.
2014/0333440 A1	11/2014	Kiani	2016/0196388 A1	7/2016	Lamego
2014/0336481 A1	11/2014	Shakespeare et al.	2016/0197436 A1	7/2016	Barker et al.
2014/0343436 A1	11/2014	Kiani	2016/0213281 A1	7/2016	Eckerbom
2014/0343889 A1	11/2014	Ben Shalom et al.	2016/0228043 A1	8/2016	O'Neil et al.
2014/0357966 A1	12/2014	Al-Ali et al.	2016/0228050 A1	8/2016	Sugla et al.
2014/0375428 A1	12/2014	Park	2016/0233632 A1	8/2016	Scruggs et al.
2015/0005600 A1	1/2015	Blank et al.	2016/0234944 A1	8/2016	Schmidt et al.
2015/0011907 A1	1/2015	Purdon et al.	2016/0242681 A1	8/2016	Shen et al.
2015/0012231 A1	1/2015	Poeze et al.	2016/0256080 A1	9/2016	Shen et al.
2015/0018650 A1	1/2015	Al-Ali et al.	2016/0270735 A1	9/2016	Diab et al.
2015/0032029 A1	1/2015	Al-Ali et al.	2016/0275776 A1	9/2016	Shen et al.
2015/0038859 A1	2/2015	Dalvi et al.	2016/0278691 A1	9/2016	Larson et al.
2015/0045637 A1	2/2015	Dalvi	2016/0278692 A1	9/2016	Larson et al.
2015/0080754 A1	3/2015	Purdon et al.	2016/0283665 A1	9/2016	Sampath et al.
2015/0087936 A1	3/2015	Al-Ali et al.	2016/0287090 A1	10/2016	Al-Ali et al.
2015/0094546 A1	4/2015	Al-Ali	2016/0287786 A1	10/2016	Kiani
2015/0094618 A1	4/2015	Russell et al.	2016/0296159 A1	10/2016	Larson et al.
2015/0097701 A1	4/2015	Al-Ali et al.	2016/0296160 A1	10/2016	Larson et al.
2015/0099950 A1	4/2015	Al-Ali et al.	2016/0296169 A1	10/2016	McHale et al.
2015/0099955 A1	4/2015	Al-Ali et al.	2016/0302698 A1	10/2016	Perlman
2015/0101844 A1	4/2015	Al-Ali et al.	2016/0302715 A1	10/2016	Larson et al.
2015/0106121 A1	4/2015	Muhsin et al.	2016/0310052 A1	10/2016	Al-Ali et al.
2015/0112151 A1	4/2015	Muhsin et al.	2016/0314260 A1	10/2016	Kiani
2015/0116076 A1	4/2015	Al-Ali et al.	2016/0324486 A1	11/2016	Al-Ali et al.
2015/0126830 A1	5/2015	Schurman et al.	2016/0324488 A1	11/2016	Olsen
2015/0164437 A1	6/2015	McCombie et al.	2016/0327984 A1	11/2016	Al-Ali et al.
2015/0165312 A1	6/2015	Kiani	2016/0331332 A1	11/2016	Al-Ali
2015/0196249 A1	7/2015	Brown et al.	2016/0367170 A1	12/2016	Larson et al.
2015/0201874 A1	7/2015	Diab	2016/0367173 A1	12/2016	Dalvi et al.
			2017/0000394 A1	1/2017	Al-Ali et al.
			2017/0007134 A1	1/2017	Al-Ali et al.
			2017/0007198 A1	1/2017	Al-Ali et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2017/0014083	A1	1/2017	Diab et al.
2017/0014084	A1	1/2017	Al-Ali et al.
2017/0027456	A1	2/2017	Kinast et al.
2017/0027498	A1	2/2017	Larson et al.
2017/0042488	A1	2/2017	Muhsin
2017/0049365	A1	2/2017	Perlman et al.
2017/0053083	A1	2/2017	Perlman
2017/0055882	A1	3/2017	Al-Ali et al.
2017/0055887	A1	3/2017	Al-Ali
2017/0055896	A1	3/2017	Al-Ali et al.
2017/0079594	A1	3/2017	Telfort et al.
2017/0086723	A1	3/2017	Al-Ali et al.
2017/0143281	A1	5/2017	Olsen
2017/0147774	A1	5/2017	Kiani
2017/0156620	A1	6/2017	Al-Ali et al.
2017/0173632	A1	6/2017	Al-Ali
2017/0187146	A1	6/2017	Kiani et al.
2017/0188919	A1	7/2017	Al-Ali et al.
2017/0196464	A1	7/2017	Jansen et al.
2017/0196470	A1	7/2017	Lamego et al.
2017/0202490	A1	7/2017	Al-Ali et al.
2017/0224262	A1	8/2017	Al-Ali
2017/0228516	A1	8/2017	Sampath et al.
2017/0245790	A1	8/2017	Al-Ali et al.
2017/0251974	A1	9/2017	Shreim et al.
2017/0251975	A1	9/2017	Shreim et al.
2017/0258403	A1	9/2017	Abdul-Hafiz et al.
2017/0311851	A1	11/2017	Schurman et al.
2017/0311891	A1	11/2017	Kiani et al.
2017/0325728	A1	11/2017	Al-Ali et al.
2017/0332976	A1	11/2017	Al-Ali et al.
2017/0340293	A1	11/2017	Al-Ali et al.
2017/0360310	A1	12/2017	Kiani et al.
2017/0367632	A1	12/2017	Al-Ali et al.
2018/0008146	A1	1/2018	Al-Ali et al.
2018/0014752	A1	1/2018	Al-Ali et al.
2018/0028124	A1	2/2018	Al-Ali et al.
2018/0055385	A1	3/2018	Al-Ali
2018/0055390	A1	3/2018	Kiani et al.
2018/0055430	A1	3/2018	Diab et al.
2018/0064381	A1	3/2018	Shakespeare et al.
2018/0069776	A1	3/2018	Lamego et al.
2018/0082767	A1	3/2018	Al-Ali et al.
2018/0085068	A1	3/2018	Telfort
2018/0087937	A1	3/2018	Al-Ali et al.
2018/0103874	A1	4/2018	Lee et al.
2018/0103905	A1	4/2018	Kiani
2018/0110478	A1	4/2018	Al-Ali
2018/0116575	A1	5/2018	Perea et al.
2018/0125368	A1	5/2018	Lamego et al.
2018/0125430	A1	5/2018	Al-Ali et al.
2018/0125445	A1	5/2018	Telfort et al.
2018/0130325	A1	5/2018	Kiani et al.
2018/0132769	A1	5/2018	Weber et al.
2018/0132770	A1	5/2018	Lamego
2018/0146901	A1	5/2018	Al-Ali et al.
2018/0146902	A1	5/2018	Kiani et al.
2018/0153442	A1	6/2018	Eckerbom et al.
2018/0153447	A1	6/2018	Al-Ali et al.
2018/0153448	A1	6/2018	Weber et al.
2018/0161499	A1	6/2018	Al-Ali et al.
2018/0168491	A1	6/2018	Al-Ali et al.
2018/0174679	A1	6/2018	Sampath et al.
2018/0174680	A1	6/2018	Sampath et al.
2018/0182484	A1	6/2018	Sampath et al.
2018/0184917	A1	7/2018	Kiani

FOREIGN PATENT DOCUMENTS

EP	2 766 834	8/2014
EP	2 811 894	12/2014
JP	10-336064	12/1998
JP	2002-513602	5/2002
JP	2002-542493	12/2002
JP	2005-218036	8/2005

JP	2005-295375	10/2005
JP	2007-095365	4/2007
JP	2007-174051	7/2007
JP	2008-519635	6/2008
JP	2009-017959	1/2009
JP	2010-524510	7/2010
JP	2014-533997	12/2014
WO	WO 98/029790	7/1998
WO	WO 99/013766	3/1999
WO	WO 00/063713	10/2000
WO	WO 2004/056266	7/2004
WO	WO 2004/059551	7/2004
WO	WO 2010/135518	11/2010
WO	WO 2011/002904	1/2011
WO	WO 2013/056160	4/2013
WO	WO 2013/119982	8/2013
WO	WO 2015/054665	4/2015
WO	WO 2015/074007	5/2015
WO	WO 2017/040700	3/2017
WO	WO 2018/071715	4/2018

OTHER PUBLICATIONS

Dhillon et al., "Towards the Prevention of Pressure Ulcers with a Wearable Patient Posture Monitor Based on Adaptive Accelerometer Alignment", 34th Annual International Conference of the IEEE EMBS, San Diego, CA, Aug. 28-Sep. 1, 2012, pp. 4513-4516.

Invitation to Pay Additional Fees in PCT Application No. PCT/US2016/049751, dated Jan. 18, 2017.

Li et al., "Accurate, Fast Fall Detection Using Gyroscopes and Accelerometer-Derived Posture Information", Conference Paper, Sixth International Workshop on Wearable and Implantable Body Sensor Networks, BSN 2009, Berkeley, CA, USA, Jun. 3-5, 2009, pp. 6.

Aminian et al., "Spatio-Temporal Parameters of Gait Measured by an Ambulatory System Using Miniature Gyroscopes", Journal of Biomechanics, 2002, vol. 35, pp. 689-699.

Anliker et al., "AMON: A Wearable Multiparameter Medical Monitoring and Alert System", IEEE Transactions on Information Technology in Biomedicine, vol. 8, No. 4, Dec. 2004, pp. 415-427.

Asada et al., "Mobile Monitoring with Wearable Photoplethysmographic Biosensors", IEEE Engineering in Medicine and Biology Magazine, May/Jun. 2003, pp. 28-40.

Ayello et al., "How and Why to Do Pressure Ulcer Risk Assessment", Advances in Skin & Wound Care, May/Jun. 2002, vol. 15, No. 3, pp. 125-133.

Bergstrom et al., "A Prospective Study of Pressure Sore Risk Among Institutionalized Elderly", Journal of the American Geriatrics Society, Aug. 1992, vol. 40, No. 8, pp. 747-758.

Bourke et al., "Evaluation of a Threshold-Based Tri-Axial Accelerometer Fall Detection Algorithm", Gait & Posture, vol. 26, 2007, pp. 194-199.

Campo et al., "Wireless Fall Sensor with GPS Location for Monitoring the Elderly", 30th Annual International IEEE EMBS Conference Vancouver, British Columbia, Canada, Aug. 20-24, 2008, pp. 498-501.

Caporusso et al., "A Pervasive Solution for Risk Awareness in the Context of Fall Prevention", Pervasive Health, 2009, pp. 8.

Capuano et al., "Remote Telemetry—New Twists for Old Technology," Nursing Management, vol. 26, No. 7, Jul. 1995.

Chen et al., "In-Bed Fibre Optic Breathing and Movement Sensor for Non-Intrusive Monitoring", Proceedings of SPIE vol. 7173, 2009, pp. 6.

Chen et al., "Wearable Sensors for Reliable Fall Detection", Proceedings of the 2005 IEEE Engineering in Medicine and Biology 27th Annual Conference, Shanghai, China, Sep. 1-4, 2005, pp. 3551-3554.

Degen et al., "SPEEDY: A Fall Detector in a Wrist Watch", Proceedings of the Seventh IEEE International Symposium on Wearable Computers (ISWC'03), 2003, pp. 184-187.

Di Rienzo et al., "MagIC System: a New Textile-Based Wearable Device for Biological Signal Monitoring. Applicability in Daily Life and Clinical Setting", Proceedings of the 2005 IEEE Engineer-

(56)

References Cited

OTHER PUBLICATIONS

- ing in Medicine and Biology 27th Annual Conference Shanghai, China, Sep. 1-4, 2005, pp. 7167-7169.
- Dinh et al., "A Fall and Near-Fall Assessment and Evaluation System", *The Open Biomedical Engineering Journal*, 2009, vol. 3, pp. 1-7.
- Elmer-Dewitt, Philip, Apple's iWatch: The killer apps may be in hospitals, not health clubs, *Fortune.com*, Feb. 3, 2014, <http://fortune.com/2014/02/03/apples-iwatch-the-killer-apps-may-be-in-hospitals-not-health-clubs/>, in 4 pages.
- Giansanti et al., "Assessment of Fall-Risk by Means of a Neural Network Based on Parameters Assessed by a Wearable Device During Posturography", *Medical Engineering & Physics*, vol. 30, 2008, pp. 367-372.
- Giansanti, Daniele, "Investigation of Fall-Risk Using a Wearable Device with Accelerometers and Rate Gyroscopes", *Institute of Physics Publishing, Physiological Measurement*, vol. 27, 2006, pp. 1081-1090.
- Grundy et al., "Telemedicine in Critical Care: An Experiment in Health Care Delivery", *JACEP*, Oct. 1977, vol. 6, No. 10, pp. 439-444.
- Grundy et al., "Telemedicine in Critical Care: Problems in Design, Implementation and Assessment", *Jul. 1982*, vol. 10, No. 7, pp. 471-475.
- Gunningberg et al., "Accuracy in the Recording of Pressure Ulcers and Prevention after Implementing an Electronic Health Record in Hospital Care", *Quality Safe Health Care*, 2008, vol. 17, pp. 281-285.
- Gunningberg et al., "Improved Quality and Comprehensiveness in Nursing Documentation of Pressure Ulcers after Implementing an Electronic Health Record in Hospital Care", *Journal of Clinical Nursing*, 2009, vol. 18, pp. 1557-1564.
- Harada et al., "Portable Orientation Estimation Device Based on Accelerometers, Magnetometers and Gyroscope Sensors for Sensor Network", *IEEE Conference on Multisensor Fusion and Integration for Intelligent Systems 2003*, 2003, pp. 191-196.
- Hwang et al., "Development of Novel Algorithm and Real-time Monitoring Ambulatory System Using Bluetooth Module for Fall Detection in the Elderly", *Proceedings of the 26th Annual International Conference of the IEEE EMBS*, Sep. 1-5, 2004, pp. 2204-2207.
- International Preliminary Report on Patentability & Written Opinion in PCT Application No. PCT/US2013/025384, dated Aug. 21, 2014.
- International Search Report & Written Opinion in PCT Application No. PCT/US2013/025384, dated Aug. 6, 2013.
- Kang et al., "A Wrist-Worn Integrated Health Monitoring Instrument with a Tele-Reporting Device for Telemedicine and Telecare", *IEEE Transaction on Instrumentation and Measurement*, vol. 55, No. 5, Oct. 2006, pp. 1655-1661.
- Kärki et al., "Pressure Mapping System for Physiological Measurements", XVIII IMEKO World Congress, Metrology for a Sustainable Development, Sep. 17-22, 2006, Rio de Janeiro, Brazil, pp. 5.
- Lindemann et al., "Evaluation of a Fall Detector Based on Accelerometers: A Pilot Study", *Medical & Biological Engineering & Computing*, vol. 43, 2005, pp. 548-551.
- Linder-Ganz et al., "Real-Time Continuous Monitoring of Sub-Dermal Tissue Stresses Under the Ischial Tuberosities in Individuals with Spinal Cord Injury", *Proceedings of the ASME 2008 Summer Bioengineering Conference (SBC2008)*, Jun. 25-29, 2008, Marriott Resort, Marco Island, Florida, pp. 2.
- Luo et al., "A Dynamic Motion Pattern Analysis Approach to Fall Detection", 2004 IEEE International Workshop on Biomedical Circuits & Systems, Dec. 1-3, 2004, pp. S2.1-5-S2.1-8.
- Mathie et al., "A System for Monitoring Posture and Physical Activity Using Accelerometers", *Engineering in Medicine and Biology Society*, 2001. *Proceedings of the 23rd Annual International Conference of the IEEE*, Oct. 25-28, 2001, pp. 3654-3657.
- McInerney, Joan A., "Reducing Hospital-Acquired Pressure Ulcer Prevalence Through a Focused Prevention Program", *Advances in Skin & Wound Care*, vol. 21, No. 2, Feb. 2008, pp. 75-78.
- Merbitz et al., "Wheelchair Push-ups: Measuring Pressure Relief Frequency", *Archives of Physical Medicine and Rehabilitation*, vol. 66, No. 7, Jul. 1985, pp. 433-438.
- Narayanan et al., "Falls Management: Detection and Prevention, Using a Waist-Mounted Triaxial Accelerometer", *Proceedings of the 29th Annual International Conference of the IEEE EMBS Cité Internationale, Lyon, France*, Aug. 23-26, 2007, pp. 4037-4040.
- Noury, Norbert, "A Smart Sensor for the Remote Follow Up of Activity and Fall Detection of the Elderly", 2nd Annual International IEEE-EMBS Special Topic Conference on Microtechnologies in Medicine & Biology, May 2-4, 2002, pp. 314-317.
- Nyan et al., "A Wearable System for Pre-Impact Fall Detection", *Journal of Biomechanics*, vol. 41, 2008, pp. 3475-3481.
- Nyan et al., "Garment-Based Detection of Falls and Activities of Daily Living Using 3-Axis MEMS Accelerometer", *Institute of Physics Publishing, International MEMS Conference 2006, Journal of Physics: Conference Series 34*, 2006, pp. 1059-1067.
- O'Donovan et al., "A Context Aware Wireless Body Area Network", *Pervasive Health*, 2009, pp. 8.
- Pérolle et al., "Automatic Fall Detection and Activity Monitoring for Elderly", *Jan. 2007*, pp. 6.
- Po et al., "Overview of MEMSWear II—Incorporating MEMS Technology Into Smart Shirt for Geriatric Care", *Institute of Physics Publishing, International MEMS Conference 2006, Journal of Physics: Conference Series 34*, 2006, pp. 1079-1085.
- Prado et al., "Distributed Intelligent Architecture for Falling Detection and Physical Activity Analysis in the Elderly", *Proceedings of the Second Joint EMBS/BMES Conference*, Oct. 23-26, 2002, pp. 1910-1911.
- Rithalia et al., "Quantification of Pressure Relief Using Interface Pressure and Tissue Perfusion in Alternating Pressure Air Mattresses", *Archives of Physical Medicine and Rehabilitation*, vol. 81, Oct. 2000, pp. 1364-1369.
- Rysavy, Peter, "Making the Call with Two-Way Paging", *Network Computing*, Published Jan. 15, 1997, www.rysavy.com/Articles/twoway.htm, pp. 5.
- Sakai et al., "Continuous Monitoring of Interface Pressure Distribution in Intensive Care Patients for Pressure Ulcer Prevention", *Journal of Advanced Nursing*, vol. 65, No. 4, 2009, pp. 809-817.
- Spillman Jr., et al., "A 'Smart' Bed for Non-Intrusive Monitoring of Patient Physiological Factors", *Measurement Science and Technology*, Aug. 2004, vol. 15, No. 8, pp. 1614-1620.
- Wachter et al., "The Employment of an Iterative Design Process to Develop a Pulmonary Graphical Display", *Journal of the American Medical Informatics Association*, vol. 10, No. 4, Jul./Aug. 2003, pp. 363-372.
- Webster, John G., "A Pressure Mat for Preventing Pressure Sores", *IEEE Engineering in Medicine & Biology Society 11th Annual International Conference*, 1989, pp. 2.
- Williams et al., "A Remote Electronic Monitoring System for the Prevention of Pressure Sores", *Proceedings of the 19th International Conference, IEEE/EMBS Oct. 30-Nov. 2, 1997, Chicago, IL*, pp. 1076-1079.
- Wu et al., "Portable Preimpact Fall Detector With Inertial Sensors", *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, vol. 16, No. 2, Apr. 2008, pp. 178-183.
- International Search Report & Written Opinion in PCT Application No. PCT/US2016/049751, dated Mar. 13, 2017.
- International Preliminary Report on Patentability & Written Opinion in PCT Application No. PCT/US2016/049751, dated Mar. 6, 2018.
- International Search Report & Written Opinion in PCT Application No. PCT/US2017/056405, dated Jan. 26, 2018.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E




FIG. 1F




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 7E




FIG. 7F




FIG. 8A




FIG. 8B




FIG.9




FIG. 10





FIG. 11A






FIG.12




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 13D




FIG. 13E




FIG. 13F




FIG. 14




Fig. 15A




Fig. 15E




Fig. 15B




Fig. 15F




Fig. 15C




Fig. 15G




Fig. 15D




Fig. 15H




Fig. 16

1

PATIENT-WORN WIRELESS PHYSIOLOGICAL SENSOR

INCORPORATION BY REFERENCE TO ANY PRIORITY APPLICATIONS

The present application claims priority benefit under 35 U.S.C. § 119(e) to U.S. Provisional Application No. 62/212,467, filed Aug. 31, 2015, U.S. Provisional Application No. 62/212,472, filed Aug. 31, 2015, U.S. Provisional Application No. 62/212,484, filed Aug. 31, 2015, and U.S. Provisional Application No. 62/212,480, filed Aug. 31, 2015, which are hereby incorporated by reference herein in entirety.

FIELD OF THE DISCLOSURE

The present disclosure relates to the field of patient monitoring. More specifically, the disclosure describes among other things a wearable sensor that measures a patient's position, orientation, and movement and wirelessly communicates the measured information to a patient monitoring system.

BACKGROUND

In clinical settings, such as hospitals, nursing homes, convalescent homes, skilled nursing facilities, post-surgical recovery centers, and the like, patients are frequently confined to bed for extended periods of time. Sometimes the patients are unconscious or sedated to such an extent that they have limited ability to change or control their position in the bed. These patients can be at risk of forming pressure ulcers, which pose a serious risk to the patient's health and well-being. Pressure ulcers, which may also be referred to as "bed sores," "pressure sores," and "decubitus ulcers," comprise injury to a patient's skin, and often the underlying tissue, which results from prolonged pressure forces applied to a site on the patient's body. Frequently, pressure ulcers develop on skin that covers bony areas of the body which have less muscle and/or fat tissue below the surface to distribute pressure applied thereto resulting from prolonged contact with the surface of a bed or chair. Examples of such body locations include the back or side of the head, shoulders, shoulder blades, elbows, spine, hips, lower back, tailbone, heels, ankles, and skin behind the knees.

Pressure ulcers are caused by application of pressure at an anatomical site that occludes blood flow to the skin and other tissue near the location. Sustained pressure between a structural surface (such as a bed) and a particular point on the patient's body can restrict blood flow when the applied pressure is greater than the blood pressure flowing through the capillaries that deliver oxygen and other nutrients to the skin and other tissue. Deprived of oxygen and nutrients, the skin cells can become damaged, leading to tissue necrosis in as few as 2 to 6 hours. Despite commonly occurring in elderly and mobility-impaired populations, hospital-acquired pressure ulcers are considered to be preventable and have been termed "never events." Insurers have imposed restrictions on the amount they will reimburse a hospital for pressure ulcer treatment, and state and federal legislation now requires hospitals to report the occurrence of pressure ulcers in their facilities.

Risk factors for pressure ulcers can be categorized as modifiable and non-modifiable. Modifiable risk factors include actions that healthcare providers can take, while non-modifiable risk factors include aspects of patient health

2

and behavior. It is valuable to document such non-modifiable risk factors so that caregivers can identify and attend to patients at risk of developing pressure ulcers. It is recommended that caregivers develop a documented risk assessment policy to predict the risk of a patient developing a pressure ulcer. Such an assessment can encompass all aspects of a patient's health and environment, and may employ commonly used measures in the field, such as the Braden and Norton scales. The risk assessment tool may be used to direct preventative strategies not only when a patient is at rest in his or her bed, but also when undergoing surgery.

Additional factors that can contribute to the formation of pressure ulcers include friction and shear forces. Friction can occur when skin is dragged across a surface which can happen when patients are moved, especially when the skin is moist. Such frictional forces can damage the skin and make it more vulnerable to injury, including formation of a pressure ulcer. A shear is when two forces move in opposite directions. For example, when the head portion of a bed is elevated at an incline, the patient's spine, tailbone, and hip regions tend to slide downward due to gravity. As the bony portion of the patient's body moves downward, the skin covering the area can stay in its current position, thereby pulling in the opposite direction of the skeletal structure. Such shear motion can injure the skin and blood vessels at the site, causing the skin and other local tissue to be vulnerable to formation of a pressure ulcer.

An established practice for patients at risk of forming pressure ulcers is to follow a turning protocol by which the patient is periodically repositioned, or "turned" to redistribute pressure forces placed on various points of the patient's body. Individuals at risk for a pressure ulcer are repositioned regularly. It is commonly suggested that patients be repositioned every 2 hours at specific inclination angles, and that the method of doing so minimizes the amount of friction and shear on the patient's skin. A repositioning log can be maintained and include key information, such as the time, body orientation, and outcome.

Pressure ulcer prevention programs have been effective and can reduce long-term costs associated with treatment. A 2002 study employed a comprehensive prevention program in two long-term care facilities, costing \$519.73 per resident per month. Results of the program revealed pressure ulcer prevalence to be reduced by 87% and 76% in the two facilities. A later study found that prevention strategies were able to reduce pressure ulcer prevalence from 29.6% to 0% in a medical intensive care unit, and from 9.2% to 6.6% across all units of the hospital. These interventions employed strategies such as manual patient repositioning and logging, tissue visualization and palpation, pressure-reducing mattresses, and use of risk assessment tools.

Turning protocols, however, do not take into consideration position changes made by the patient between established turn intervals, which are neither observed nor recorded. Thus it is possible that in some circumstances, the act of following a turn protocol can have an unintended negative clinical effect.

SUMMARY

This disclosure describes, among other things, embodiments of systems, devices, and methods for monitoring the position and orientation of a patient at risk of forming one or more pressure ulcers.

One aspect of the present disclosure comprises a patient turn and movement monitoring system configured to help manage a patient that is at risk of forming one or more

pressure ulcers. Some embodiments of the patient turn and monitoring system include a patient-worn, wireless sensor having one or more sensors configured to obtain information describing the patient's orientation and to wirelessly transmit information indicative of the sensed orientation information. The system also includes a patient monitor configured to receive, store, and process the information transmitted by the wireless sensor and to display and transmit information (or data) indicative of the patient's orientation to help caregivers manage the patient's risk of formation of one or more pressure ulcers. The patient turn and movement monitoring system can identify the present orientation of the patient and determine how long the patient has been in the present orientation. If the patient remains in an orientation beyond a predefined, clinician-prescribed patient orientation duration, the system can notify the patient and/or caretakers that the patient is due to be repositioned. In certain embodiments, a patient orientation duration timer is used to monitor such orientation times. In certain embodiments of the disclosed patient turn and movement monitoring system, a signal repeater, located within reception range of the wireless sensor, is used to receive and forward the information indicative of the sensed orientation information from the wireless sensor to a network-based processing node.

Another aspect of the present disclosure includes a wireless sensor including one or more sensors configured to obtain position, orientation, and motion information from the patient. The one or more sensors can include an accelerometer, a gyroscope, and a magnetometer, which are configured to determine the patient's position and orientation in three-dimensional space. The wireless sensor is configured to wirelessly transmit the sensor data, and/or information representative of the sensor data, to a patient monitor. The patient monitor can be configured to process the received information, to display information indicative of, or derived from the received data, and to transmit information—including displays, alarms, alerts, and notifications—to a multi-patient monitoring system which may be located, for example, at a nurse's station.

Another aspect of the present disclosure is directed to a system and method for associating the wireless sensor with a patient monitor. In some embodiments, the wireless sensor includes an activation tab which, when removed, activates the wireless sensor. Upon activation, a wireless transceiver in the wireless sensor emits a low-power pairing signal having a pairing signal transmission range of up to approximately three inches. In some embodiments, the wireless sensor has a switch or button which, when depressed, places the wireless sensor in a pairing mode of operation, causing the wireless sensor to emit the low-power pairing signal. When the patient monitor is within range of the wireless sensor (e.g., within the about three-inch range), the wireless sensor and the patient monitor associate, thereby configuring the wireless sensor and patient monitor to communicate with each other. Once the pairing between the wireless sensor and the patient monitor is completed, the wireless sensor changes into a patient parameter sensing mode of operation in which the wireless sensor transmits a patient parameter sensing signal. The patient parameter sensing signal has a patient signal transmission range that is substantially greater than the pairing signal transmission range. The wireless sensor is then in condition to be placed on the patient.

In some aspects of the present disclosure the patient's position and orientation are monitored and recorded. Once the wireless sensor is affixed to the patient's body, such as, for example, the patient's torso, sensor data corresponding

to the patient's motion (e.g., acceleration and angular velocity) are obtained, pre-processed, and transmitted to the patient monitor. The patient monitor stores and further processes the received data to determine the patient's orientation. Illustratively, the patient monitor can determine whether the patient is standing, sitting, or lying down in the prone, supine, left side, or right side positions.

In some embodiments, the patient monitor determines the precise orientation of the patient's body. For example, the patient monitor can determine the degree to which the patient's body is inclined, vertically and/or horizontally, thereby generating an accurate description of the patient's position relative to the support structure (such as a bed) upon which the patient lies.

In another aspect of the present disclosure the patient monitor stores the determined position and orientation information and keeps track of how long the patient remains in each determined position, thereby creating a continuous record of the patient's positional history. The patient monitor analyzes and processes the stored data to provide clinically-relevant, actionable information to the patient's care providers. Illustratively, the patient monitor counts the number of in-bed turns performed by the patient and monitors and displays the amount of time that has elapsed since the patient last turned. When the elapsed time exceeds a clinician-defined duration (e.g., two hours), the patient monitor displays an indication that the maximum time between patient turns has been exceeded. The patient monitor can also transmit a notification to one or more clinicians responsible for caring for the patient via, for example, a multi-patient monitoring system, a clinician notification device, or the like. The patient monitor can also determine and display statistical information, such as the average, minimum, and maximum amount of time between turns for a given clinician-defined time period, such as for example, twenty-four hours. The patient monitor can also determine and display the number of turns in the same position and orientation over a clinician-defined period of time. Similarly, the patient monitor can display the total amount of time the patient remained in each specific position within a clinician-defined period. Moreover, the patient monitor can determine the frequency and duration of periods during which the patient remained in clinically-defined acceptable positions.

In yet another aspect of the present disclosure the patient monitor determines the mobility status of the patient, e.g., whether the patient is ambulatory, standing, sitting, reclining, or falling. In certain aspects, the wireless monitoring system can include an alert system to alert the caregiver that the patient is falling, getting out of bed, or otherwise moving in a prohibited manner or in a manner that requires caregiver attention. The alert can be an audible and/or visual alarm on the monitoring system, or the alert can be transmitted to a caregiver (e.g., nurses' station, clinician device, pager, cell phone, computer, or otherwise). Illustratively, the patient monitor can display the patient's mobility status and transmit a notification that the patient is active and away from the bed. In some circumstances, the patient monitor can determine whether the patient contravenes a clinician's order, such as, for example, instructions to remain in bed, or to walk to the bathroom only with the assistance of an attendant. In such circumstances, a notification, alert, or alarm can be transmitted to the appropriate caregivers.

In certain aspects, the information received by the wireless sensor can be used to create a time-sequenced representation of the patient's movement. This representation can be displayed on the patient monitor or transmitted to a nurses' station or other processing nodes to enable the

caregiver to monitor the patient. The time-sequenced representation can be viewed in real time and/or be recorded for playback. For example, if an alarm alerts the caregiver that the patient has fallen out of bed, the caregiver can access and review the historical sequence of the patient's movements prior to and during that period of time.

Another aspect of the present disclosure is directed to predicting a patient's risk of falling based on the patient's gait and other information (such as, for example, the patient's current medication regimen). When the patient monitor determines that the patient's risk of falling is above a predetermined threshold, the patient monitor can issue an alarm or alert to notify care providers of the identified risk in an effort to anticipate and therefore prevent a patient fall. Additionally, the patient monitor can determine when a patient has fallen and issue the appropriate alarms and alerts to summon care provider assistance.

In an aspect of the present disclosure the patient monitor accesses the patient's health records and clinician input via a network. Illustratively, the patients' positional history data, analyzed in view of the patient's health records, may reveal or suggest a turning protocol (or other treatment protocol) that will likely yield favorable clinical outcomes for the particular patient. Accordingly, the patient monitor analyzes the accessed information in conjunction with the received information from the wireless sensor to determine a recommended patient turn protocol (or other treatment protocol) for the patient.

In still another aspect of the present disclosure, the patient monitor assesses caregiver and facility compliance with the clinician-defined patient turn protocol established for the patient. For example, the patient monitor can identify the number of times that the patient remains in a position for a period greater than the prescribed duration, indicating a patient turn protocol violation, as well as the length of each such overexposure. The patient monitor can also track the clinician's response time upon issuance of a notification, alert, or alarm.

According to another aspect of the present disclosure, care provider workflow productivity, efficiency, and effectiveness can be determined, based on aggregated positional history data corresponding to multiple patients wherein each patient is equipped with the disclosed wireless sensor. Additionally, care for patients in a particular location, such as a hospital ward or nursing home floor where the ratio of patients to staff is relatively high, can be prioritized based on the determined risk of formation of pressure ulcers. Thus, patients determined to have the highest risk are designated to receive attention first.

In yet another aspect of the present disclosure, the wireless sensor includes sensors to obtain additional physiological measurements from the patient. For example, the wireless sensor can include a temperature sensor configured to measure the patient's body core body temperature by insulating the patient's skin surface around the temperature sensor. As a result of the insulation surrounding the temperature sensor, the natural temperature difference between the patient's skin surface and body core reach equilibrium, thereby arriving at the patient's body core temperature (which is typically higher in temperature than the patient's skin surface). The wireless sensor can also include an acoustic respiration sensor configured to sense vibrational motion generated by the patient's chest. The acoustic respiration sensor is configured to mechanically transmit the sensed vibrations through rigid structures of the device to the accelerometer. Processing of the accelerometer signal can provide, among other things, the patient's respiration

and heart rates. An electrocardiogram (ECG) sensor, configured to sense electrical signals from two or more electrodes in electrical contact with the patient's chest may also be included in the wireless sensor. The ECG signal can be processed to detect arrhythmias, such as bradycardia, tachyarrhythmia, ventricular fibrillation and the like. Additionally, the accelerometer signal (containing information indicative of the mechanically-transmitted vibrations from the acoustic respiration sensor) and/or the ECG signal can be processed to identify respiratory distress or dysfunction, including without limitation, snoring, coughing, choking, wheezing, apneic events, and airway obstruction.

In another aspect of the present disclosure, the patient monitor can determine a score that describes the patient's wellness/sickness state, which may also be referred to as a "Halo Index." Illustratively, the patient monitor accesses and analyzes the patient's health records, clinician input, positional history data provided by the wireless sensor, surface structure pressure data, and other physiological parameter data collected and provided by the wireless sensor (such as, by way of non-limiting example, the patient's temperature, respiration rate, heart rate, ECG signal, and the like) to assess the patient's overall health condition.

In an aspect of the present disclosure, the patient monitor accesses information provided by the patient's support structure (e.g., bed, mattress, bed sheet, mattress pad, and the like) to determine the extent of pressure forces exerted on particular anatomical sites of the patient's body. Illustratively, the patient's support structure can be configured with an array of pressure sensors that measure the pressure force exerted on the support structure by the patient at specific locations. The patient monitor can analyze the patient's postural history data in conjunction with the information provided by the support structure to determine a likelihood of pressure ulcer formation at a specific anatomical location based on the measured amount of pressure exerted on the anatomical location multiplied by the amount of time the anatomical location has been under such pressure. When the evaluated risk exceeds a predetermined threshold, the patient monitor can issue an alarm and/or an alert to reposition the patient so as to avoid formation of a pressure ulcer in the specified anatomical location. Additionally, the patient monitor can suggest particular positions and/or a patient turn protocol based on the combined analysis of pressure force exerted and length of time under such pressure.

For purposes of summarizing the disclosure, certain aspects, advantages, and novel features have been described herein. Of course, it is to be understood that not necessarily all such aspects, advantages, or features will be embodied in any particular embodiment.

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments will be described hereinafter with reference to the accompanying drawings. The drawings and the associated descriptions are provided to illustrate embodiments of the present disclosure and do not limit the scope of the claims. In the drawings, similar elements have similar reference numerals.

FIG. 1A is a perspective view of an embodiment of the disclosed patient monitoring system including a patient-worn wireless sensor in proximity to a patient monitor.

FIG. 1B is a functional block diagram of an embodiment of the display of the disclosed patient monitor.

FIG. 1C is a functional block diagram of an embodiment of the disclosed patient monitoring system.

FIG. 1D is a functional block diagram of an embodiment of the disclosed patient monitoring system.

FIG. 1E is a functional block diagram of an embodiment of the disclosed patient monitoring system.

FIG. 1F is a functional block diagram of an embodiment of the disclosed patient monitoring system.

FIG. 2A is a functional block diagram of an embodiment of the disclosed wireless sensor.

FIG. 2B is a functional block diagram of an embodiment of the disclosed wireless sensor including optional sensing components.

FIG. 3A is a schematic exploded perspective view of an embodiment of the disclosed wireless sensor.

FIG. 3B is a schematic assembled perspective view of the embodiment of the disclosed wireless sensor of FIG. 3A.

FIG. 3C is a schematic side view of the embodiment of the disclosed wireless sensor of FIGS. 3A and 3B.

FIG. 4A is a schematic cross-sectional view of an embodiment of the disclosed wireless sensor which includes a temperature sensor.

FIG. 4B is a schematic bottom view of the embodiment of the disclosed wireless sensor of FIG. 4A.

FIG. 4C is a schematic exploded perspective view of the embodiment of the disclosed wireless sensor of FIGS. 4A-B.

FIG. 5A is a schematic cross-sectional view of an embodiment of the disclosed wireless sensor which includes an acoustic respiration sensor.

FIG. 5B is a schematic bottom view of the embodiment of the disclosed wireless sensor of FIG. 5A.

FIG. 5C is a schematic exploded perspective view of the embodiment of the disclosed wireless sensor of FIGS. 5A-B.

FIG. 6A is a schematic cross-sectional view of an embodiment of the disclosed wireless sensor which includes a temperature sensor and an acoustic respiration sensor.

FIG. 6B is a schematic bottom view of the embodiment of the disclosed wireless sensor of FIG. 6A.

FIG. 6C is a schematic exploded perspective view of the embodiment of the disclosed wireless sensor of FIGS. 6A-B.

FIG. 7A is a perspective view of an embodiment of the disclosed patient monitoring system including a patient-worn wireless sensor having an ECG sensor in proximity to a patient monitor.

FIG. 7B is a schematic assembled perspective view of the embodiment of the disclosed wireless sensor of FIG. 7A.

FIG. 7C is a schematic side view of the embodiment of the disclosed wireless sensor of FIGS. 7A and 7B.

FIG. 7D is a cross-sectional view of an embodiment of the disclosed wireless sensor of FIGS. 7A-C.

FIG. 7E is a schematic bottom perspective view of the embodiment of the disclosed wireless sensor of FIGS. 7A-D.

FIG. 7F is a schematic exploded perspective view of the embodiment of the disclosed wireless sensor of FIGS. 7A-7E.

FIG. 8A is a schematic exploded perspective view of an embodiment of the disclosed wireless sensor having a temperature sensor, an acoustic respiration sensor, and an ECG sensor.

FIG. 8B is a schematic bottom view of the disclosed wireless sensor of FIG. 8A.

FIG. 9 is a flow diagram describing a process to associate a wireless sensor with a patient monitor according to an embodiment of the present disclosure.

FIG. 10 is a flow diagram describing a process to determine whether a patient has changed orientation according to an embodiment of the present disclosure.

FIG. 11A is an exemplary plot of processed accelerometer data over time used to determine a patient's orientation according to an embodiment of the present disclosure.

FIG. 11B is an exemplary plot of the duration of a patient's orientation according to an embodiment of the present disclosure.

FIG. 12 is a flow diagram describing a process to determine whether a patient has fallen according to an embodiment of the present disclosure.

FIGS. 13A-F illustrate embodiments of displays reflecting a patient's position according to an embodiment of the present disclosure.

FIG. 14 illustrates an example display of a patient monitor incorporating the icons illustrated in FIGS. 13A-F according to an embodiment of the present disclosure.

FIGS. 15A-15H illustrate various configurations of a room display displayed on a patient display monitor according to an embodiment of the present disclosure.

FIG. 16 illustrates an example method according to an embodiment of the present disclosure.

DETAILED DESCRIPTION

Embodiments of the present disclosure will now be described with reference to the accompanying figures, wherein like numerals refer to like elements throughout. The following description is merely illustrative in nature and is in no way intended to limit the disclosure, its application, or uses. It should be understood that steps within a method may be executed in different order without altering the principles of the present disclosure. Furthermore, embodiments disclosed herein can include several novel features, no single one of which is solely responsible for its desirable attributes or which is essential to practicing the systems, devices, and methods disclosed herein.

The present disclosure relates to systems, devices, methods, and computer-readable media to monitor and manage the position, orientation, and movement of a patient who is at risk of forming one or more pressure ulcers. In one embodiment, the system comprises a patient-worn, wireless sensor including one or more sensors configured to obtain position, orientation and movement information from the patient. The one or more sensors can include one or more accelerometers, gyroscopes, and magnetometers (i.e., compasses). Illustratively, the sensors continuously or periodically (e.g., every second) obtain information that describes the patient's orientation in three dimensions. The wireless sensor includes a processor that is configured to process the obtained sensor information. The wireless sensor also includes a transceiver configured to wirelessly transmit the processed sensor data, and/or information representative of the sensor data, to a patient monitor (or other processing device) for further processing. The patient monitor can be configured to store and further process the received information, to display information indicative of or derived from the received data, and to transmit information—including displays, alarms, alerts, and notifications—to other patient care systems including a multi-patient monitoring system which may be accessible from, for example, a nurses' station.

FIG. 1A is a perspective illustration of an embodiment of the disclosed patient monitoring system 100 in a clinical setting. The patient monitoring system 100 includes a wireless sensor 102 worn by a patient, in proximity to a patient monitor 106 located on a table 116 at the side of the patient's bed 118. The wireless sensor 102 may also be referred to herein as "a wireless physiological sensor 102," "a patient-

worn sensor 102,” “a movement sensor 102,” and “a wearable wireless sensor 102.” The wireless sensor 102 includes one or more sensors configured to measure the patient’s position, orientation, and motion. In some embodiments, the wireless sensor 102 includes an accelerometer configured to measure linear acceleration of the patient and a gyroscope configured to measure angular velocity of the patient. The measured linear acceleration and angular velocity information can be processed to determine the patient’s orientation in three dimensions. In some embodiments, a magnetometer is included in the wireless sensor 102 to measure the Earth’s gravitational field. Information measured by the magnetometer can be used to improve accuracy of the determined orientation of the patient.

The wireless sensor 102 also includes a wireless transceiver 206 (shown in FIGS. 2A and 2B) which can transmit to the patient monitor 106 information representative of sensor data obtained by the wireless sensor 102 from the patient. Advantageously, the patient is not physically coupled to the bedside patient monitor 106 and can therefore move freely into different positions on the bed 118.

In accordance with certain embodiments of the present disclosure, the wireless sensor 102 is affixed to the skin of the patient’s body under the patient’s garment as reflected in FIG. 1A by the phantom drawing of the wireless sensor 102. More particularly, the wireless sensor 102 can be placed on the patient’s chest over the patient’s manubrium, the broad upper portion of the sternum. In this position, the wireless sensor 102 is approximately centered relative to the longitudinal axis of the patient’s body and near the patient’s center of mass, a position that is useful in determining the patient’s orientation when, for example, the patient is in bed.

The wireless sensor 102 can be affixed to the patient’s skin using any form of medically-appropriate adherent material, including a pressure-sensitive adhesive that is coated or applied to the bottom surface of the wireless sensor 102. One skilled in the art will appreciate that many other materials and techniques can be used to affix the wireless sensor 102 to the patient without departing from the scope of the present disclosure.

Frequently in clinical settings, multiple medical sensors are attached or adhered to a patient to concurrently monitor multiple physiological parameters. Some examples of medical sensors include, but are not limited to, position, orientation, and movement sensors, temperature sensors, respiration sensors, heart rate sensors, blood oxygen sensors (such as pulse oximetry sensors), acoustic sensors, EEG sensors, ECG sensors, blood pressure sensors, sedation state sensors, to name a few. Typically, each sensor that is attached to a patient transmits, often by cable, the obtained physiological data to a nearby monitoring device configured to receive and process the sensor data, and transform it into clinical information to be used by the care providers to monitor and manage the patient’s condition. When a patient is concurrently monitored by several physiological sensors, the number of cables and the number of bedside monitoring devices used can be excessive and can limit the patient’s freedom of movement and impede care providers’ access to the patient. The cables connecting the patient to the bedside monitoring devices can also make it more difficult to move the patient from room to room or to switch to different bedside monitors.

Advantageously, the disclosed wireless sensor 102 can transmit data, wirelessly, to a patient data processing environment 105 in which the sensor data can be processed using one or more processing capabilities. As illustrated in FIG. 1A, the wireless sensor 102 transmits data via a wireless

communications link 104. The wireless communications link 104 can be received by the bedside patient monitor 106, and/or by an extender/repeater 107. Both the patient monitor 106 and extender/repeater 107 provide access, by way of high-speed and reliable communications interfaces, to the patient data processing environment 105. For illustration purposes, both the patient monitor 106 and the extender/repeater 107 are illustrated in FIG. 1A. However, typically only one such device is required to establish a wireless connection between the wireless sensor 102 and the patient data processing environment 105. The wireless communications link 104 can use any of a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth, ZigBee, cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like. The wireless sensor 102 can be configured to perform telemetry functions, such as measuring and reporting position, orientation, and movement information about the patient. According to one embodiment, the wireless sensor 102 uses the Bluetooth wireless communications standard to communicate wirelessly with the patient monitor 106.

The extender/repeater 107 can receive sensor data from the wireless sensor 102 by way of the wireless communications link 104 and forward the received sensor data, via the network 108, to one or more processing nodes within the patient data processing environment 105. For example, the extender/repeater 107 can forward the received sensor data to a patient monitor 106 that might be located beyond the range of the wireless communications link 104 of a particular wireless sensor 102. Alternatively, the extender/repeater 107 can route the sensor data to other processing nodes within the patient data processing environment 105, such as, for example, a multi-patient monitoring system 110 or a nurses’ station system 113. A skilled artisan will appreciate that numerous processing nodes and systems can be used to process the data transmitted by the wireless sensor 102.

FIG. 1A also illustrates an embodiment of the patient monitor 106, which may also be referred to herein as “a processing device 106,” “a portable computing device 106,” and “a patient monitoring device 106.” Examples of a patient monitor 106 are disclosed in U.S. Pat. Pub. Nos. 2013/0262730 and 2015/0099955, assigned to the assignee of the present disclosure, and which are incorporated by reference herein in their entirety. The patient monitor 106 is a processing device, and therefore includes the necessary components to perform the functions of a processing device, including at least one processor, a memory device, a storage device, input/output devices, and communications connections, all connected via one or more communication buses. Thus, in certain embodiments, the patient monitor 106 is configured to process the sensor data provided by the wireless sensor 102. In other embodiments, processing of the sensor data can be performed by other processing nodes within the patient data processing environment 105. The patient monitor 106 is configured to wirelessly communicate with the wireless sensor 102. The patient monitor 106 includes a display 120, and a docking station, which is configured to mechanically and electrically mate with a portable patient monitor 122 also having a display 130. The patient monitor 106 is housed in a movable, mountable, and portable housing formed in a generally upright, inclined shape configured to rest on a horizontal flat surface, as shown in FIG. 1A. Of course, a person skilled in the art will appreciate that the housing can be affixed in a wide variety of positions and mountings and can comprise a wide variety of shapes and sizes.

In an embodiment, the display **120**, alone or in combination with the display **130** of the portable patient monitor **122**, may present a wide variety of measurement and/or treatment data in numerical, graphical, waveform, or other display indicia. For example, the display **120** can display a variety of patient-specific configurations and/or parameters, such as the patient's weight, age, type of treatment, type of disease, type of medical condition, nutrition, hydration and/or length of stay, among others. In an embodiment, the display **120** occupies much of a front face of the housing, although an artisan will appreciate the display **120** may comprise a table or tabletop horizontal configuration, a laptop-like configuration, or the like. Other embodiments may include communicating display information and data to a tablet computer, smartphone, television, or any display system recognizable to an artisan. Advantageously, the upright inclined configuration of the patient monitor **106**, as illustrated in FIG. 1A, displays information to a caregiver in an easily viewable manner.

The portable patient monitor **122** of FIG. 1A may advantageously include an oximeter, co-oximeter, respiratory monitor, depth of sedation monitor, noninvasive blood pressure monitor, vital signs monitor or the like, such as those commercially available from Masimo Corporation of Irvine, Calif., and/or disclosed in U.S. Pat. Pub. Nos. 2002/0140675, 2010/0274099, 2011/0213273, 2012/0226117, 2010/0030040; U.S. patent application Ser. Nos. 61/242,792, 61/387457, 61/645,570, 13/554,908 and U.S. Pat. Nos. 6,157,850, 6,334,065, the contents of which are incorporated herein by reference in their entireties. The portable patient monitor **122** may communicate with a variety of noninvasive and/or minimally invasive devices such as, by way of non-limiting example, wireless sensor **102**, optical sensors with light emission and detection circuitry, acoustic sensors, devices that measure blood parameters from a finger prick, cuffs, ventilators, and the like. The portable patient monitor **122** may include its own display **130** presenting its own display indicia. The display indicia may change based on a docking state of the portable patient monitor **122**. When undocked, the display **130** may include parameter information and may alter its display orientation based on information provided by, for example, a gravity sensor or an accelerometer. Although disclosed with reference to particular portable patient monitors **122**, an artisan will recognize from the disclosure herein there is a large number and wide variety of medical devices that may advantageously dock with the patient monitor **106**.

FIG. 1B is a functional block diagram of an embodiment of the display **120** of the disclosed patient monitor **106** and the display **130** of the portable patient monitor **122**. Display **120** of the patient monitor **106** can be configured to present patient physiological data **124**, patient turn data **126**, and/or additional, optional patient data **128**. Patient physiological data can include, by way of non-limiting example, oxygen saturation, pulse rate, respiration rate, fractional arterial oxygen saturation, total hemoglobin, plethysmograph variability index, methemoglobin, carboxyhemoglobin, perfusion index, and oxygen content. Advantageously, the display **120** is configurable to permit the user to adjust the manner by which the physiologic parameters **124**, patient turn data **126**, and optional patient data **128** are presented on the display **120**. In particular, information of greater interest or importance to the clinician may be displayed in larger format and may also be displayed in both numerical and graphical formats to convey the current measurement as well as the historical trend of measurements for a period of time, such as, for example, the preceding hour.

As illustrated by dotted lines in FIG. 1B, the display **130** of the portable patient monitor **130** is an optional feature of the patient monitor **106** which may be configured to present patient physiological data **134**, patient turn data **136**, and additional, optional patient data **138**.

FIG. 1C is a simplified functional block diagram of an embodiment of the disclosed patient monitoring system **100**. The system includes the patient-worn wireless sensor **102** having one or more sensors, a wireless communications link **104**, through which sensor data from the wireless sensor **102** accesses the patient data processing environment **105** which includes a patient monitor **106**, a communications network **108**, a multi-patient monitoring system **110**, a hospital or facility information system **112**, one or more nurses' station systems **113**, and one or more clinician devices **114**. An artisan will appreciate that numerous other computing systems, servers, processing nodes, display devices, printers, and the like can be included in the disclosed patient monitoring system **100**.

The wireless sensor **102** is worn by a patient who has been determined to be at risk of forming one or more pressure ulcers, e.g., a patient who is confined to bed for an extended period of time. The wireless sensor **102** is capable of monitoring on a continuous or periodic (e.g., every second) basis the orientation of the patient to help determine whether the patient is repositioned frequently enough to reduce the patient's risk of forming a pressure ulcer. In certain embodiments, the wireless sensor **102** minimally processes measured acceleration and/or angular velocity data and wirelessly transmits the minimally-processed data to the patient monitor **106** by way of the wireless communications link **104**.

The wireless sensor **102** and the patient monitor **106** can be configured to utilize different wireless technologies to form the wireless communications link **104**. In certain scenarios, it may be desirable to transmit data over Bluetooth or ZigBee, for example, when the distance between the wireless sensor **102** and the patient monitor **106** is within range of Bluetooth or ZigBee communication. Transmitting data using Bluetooth or ZigBee is advantageous because these technologies require less power than other wireless technologies. Accordingly, longevity of embodiments of the disclosed wireless sensor **102** using batteries may be increased by using Bluetooth or ZigBee protocols.

In other scenarios, it may be desirable to transmit data using Wi-Fi or cellular telephony, for example, when the distance between the wireless sensor **102** and the patient monitor **106** is out of range of communication for Bluetooth or ZigBee. A wireless sensor **102** may be able to transmit data over a greater distance using Wi-Fi or cellular telephony than other wireless technologies. In still other scenarios, it may be desirable to transmit data using a first wireless technology and then automatically switching to a second wireless technology in order to maximize data transfer and/or energy efficiency.

In some embodiments, the wireless sensor **102** automatically transmits data over Bluetooth or ZigBee when the wireless sensor **102** is within a pre-determined distance from the bedside patient monitor **106**. The wireless sensor **102** automatically transmits data over Wi-Fi or cellular telephony when the wireless sensor **102** is beyond a pre-determined distance away from the bedside patient monitor **106**. In certain embodiments, the wireless sensor **102** can automatically convert from Bluetooth or ZigBee to Wi-Fi or cellular telephony, and vice versa, depending on the distance between the wireless sensor **102** and the bedside patient monitor **106**.

In some embodiments, the wireless sensor **102** automatically transmits data over Bluetooth or ZigBee when the Bluetooth or ZigBee signal strength is sufficiently strong or when there is interference with Wi-Fi or cellular telephony. The wireless sensor **102** automatically transmits data over Wi-Fi or cellular telephony when the Bluetooth or ZigBee signal strength is not sufficiently strong. In certain embodiments, the wireless sensor **102** can automatically convert from Bluetooth or ZigBee to Wi-Fi or cellular telephony, and vice versa, depending on signal strength.

The patient monitor **106** can be operable to receive, store and process the measured acceleration and angular velocity data transmitted by the wireless sensor **102** to determine the patient's orientation. Once determined, the patient monitor **106** can display the patient's current orientation. In some embodiments, the patient monitor **106** displays the patient's current orientation along with the patient's previous orientations over time, thereby providing the user the ability to view a historical record of the patient's orientation. In certain embodiments, e.g., as illustrated in FIGS. **13A-F** and **14**, the patient orientation is displayed by icons, such stick figures, enabling the clinician to readily understand the patient's present positional state and the patient's positional history. The patient monitor **106** can also be configured to keep track of the length of time the patient remains in a particular orientation. In some embodiments the patient monitor **106** displays the amount of time the patient has been in the current orientation. Additionally, the patient monitor **106** can determine when the patient remains in a particular orientation for a duration greater than that prescribed by a clinician according to a repositioning protocol. Under such conditions, the patient monitor **106** can issue alarms, alerts, and/or notifications to the patient and/or to caregivers indicating that the patient should be repositioned to adhere to the prescribed repositioning protocol to reduce the risk of pressure ulcer formation.

As illustrated in FIG. **1C**, the patient monitor **106** communicates over a network **108** with a patient data processing environment **105** that includes a multi-patient monitoring system **110**, a hospital/facility system **112**, nurses' station systems **113**, and clinician devices **114**. Examples of network-based clinical processing environments, including multi-patient monitoring systems **110**, are disclosed in U.S. Pat. Pub. Nos. 2011/0105854, 2011/0169644, and 2007/0180140, which are incorporated herein by reference in their entirety. In general, the multi-patient monitoring system **110** communicates with a hospital/facility system **112**, the nurses' station systems **113**, and clinician devices **114**. The hospital/facility system **112** can include systems such as electronic medical record (EMR) and/or admit, discharge, and transfer (ADT) systems. The multi-patient monitoring system **110** may advantageously obtain through push, pull or combination technologies patient information entered at patient admission, such as patient identity information, demographic information, billing information, and the like. The patient monitor **106** can access this information to associate the monitored patient with the hospital/facility systems **112**. Communication between the multi-patient monitoring system **110**, the hospital/facility system **112**, the nurses' station systems **113**, the clinician devices **114**, and the patient monitor **106** may be accomplished by any technique recognizable to an artisan from the disclosure herein, including wireless, wired, over mobile or other computing networks, or the like.

FIG. **1D** is a simplified functional block diagram of the disclosed patient monitoring system **100** of FIG. **1C** expanded to illustrate use of multiple wireless sensors **102**

with multiple patients within a caretaking environment. Advantageously, the patient monitoring system **100** can provide individual patient information on, for example, a patient monitor **106**, as well as aggregated patient information on, for example, a nurses' station server or system **114**. Thus a caretaker can have an overview of positional information corresponding to a population of patients located, for example, in a hospital floor or unit.

In some circumstances, there may not be the need, desire, or resources available to employ a bedside patient monitor **106** associated with a wireless sensor **102** being worn by a patient. For example, the clinical environment might be staffed such that patient data are collected, analyzed, displayed, and monitored at a central observation station, such as a nurses' station, rather than at the patient's bedside. Moreover, when the information is to be accessed by a clinician at the bedside, portable clinician devices **114**, such as, for example, tablets, PDAs or the like, may be used by caregivers to access the required patient-specific information while at the patient's bedside.

In such situations, as illustrated in FIGS. **1E** and **1F**, the wireless sensor **102** can communicate to the various systems of the clinical computing environment by way of a signal extender/repeater **107**. The extender/repeater **107** is located within range of the wireless sensor **102** (e.g., near the patient's bed **118**) and configured to relay data, via the network **108**, between the wireless sensor **102** and one or more computing systems capable of processing, storing, displaying, and/or transmitting the data collected by the wireless sensor **102**. Advantageously, a relatively low cost extender/repeater **107** can be used to receive signals transmitted from one or more wireless sensors **102** over the wireless communications link(s) **104** using a shorter-range, lower-power-consuming transmission mode, such as for example, Bluetooth or ZigBee. The extender/repeater **107** can then retransmit the received signals to one or more computing systems in the patient data processing environment **105** over the network **108**. In accordance with some embodiments, the extender/repeater **107** is a Bluetooth-to-Ethernet gateway that retransmits signals received from the wireless sensor **102** to computing nodes, such as, for example, the multi-patient monitoring system **110**, over the network **108**. In some embodiments, the extender/repeater **107** is a Bluetooth-to-WiFi bridge that provides access to the network **108** for the wireless sensor **102**. Of course, a skilled artisan will recognize that there are numerous ways to implement the extender/repeater **107**.

FIG. **2A** illustrates a simplified hardware block diagram of an embodiment of the disclosed wireless sensor **102**. As shown in FIG. **2A**, the wireless sensor **102** can include a processor **202**, a data storage device **204**, a wireless transceiver **206**, a system bus **208**, an accelerometer **210**, a gyroscope **212**, a battery **214**, and an information element **215**. The processor **202** can be configured, among other things, to process data, execute instructions to perform one or more functions, such as the methods disclosed herein, and control the operation of the wireless sensor **102**. The data storage device **204** can include one or more memory devices that store data, including without limitation, random access memory (RAM) and read-only memory (ROM). The wireless transceiver **206** can be configured to use any of a variety of wireless technologies, such as Wi-Fi (802.11x), Bluetooth, ZigBee, cellular telephony, infrared, RFID, satellite transmission, proprietary protocols, combinations of the same, and the like. The components of the wireless sensor **102** can be coupled together by way of a system bus **208**, which may represent one or more buses. The battery **214**

provides power for the hardware components of the wireless sensor **102** described herein. As illustrated in FIG. 2A, the battery **214** communicates with other components over system bus **208**. One skilled in the art will understand that the battery **214** can communicate with one or more of the hardware functional components depicted in FIG. 2A by one or more separate electrical connections. The information element **215** can be a memory storage element that stores, in non-volatile memory, information used to help maintain a standard of quality associated with the wireless sensor **102**. Illustratively, the information element **215** can store information regarding whether the sensor **102** has been previously activated and whether the sensor **102** has been previously operational for a prolonged period of time, such as, for example, four hours. The information stored in the information element **215** can be used to help detect improper re-use of the wireless sensor **102**.

In some embodiments, the accelerometer **210** is a three-dimensional (3D) accelerometer. The term 3D accelerometer as used herein includes its broad meaning known to a skilled artisan. The accelerometer **210** provides outputs responsive to acceleration of the wireless sensor **102** in three orthogonal axes, sometimes denoted as the “X,” “Y,” and “Z” axes. An accelerometer **210** may measure acceleration that it experiences relative to Earth’s gravity. An accelerometer **210** may provide acceleration information along three axes, and it and may provide acceleration information which is the equivalent of inertial acceleration minus local gravitational acceleration. Accelerometers **210** are well known to those skilled in the art. The accelerometer **210** may be a micro-electromechanical system (MEMS), and it may include piezoresistors, among other forms of implementation. The accelerometer **210** may be a high-impedance charge output or a low-impedance charge output accelerometer **210**. In some embodiments, the accelerometer **210** may be a tri-axis accelerometer, and the output of the accelerometer **210** may include three signals, each of which represents measured acceleration in particular axis. The output of the accelerometer **210** may be 8-bit, 12-bit, or any other appropriate-sized output signal. The outputs of the accelerometer may be in analog or digital form. The accelerometer **210** may be used to determine the position, orientation, and/or motion of the patient to which the wireless sensor **102** is attached.

In some embodiments, the gyroscope **212** is a three-axis digital gyroscope with angle resolution of two degrees and with a sensor drift adjustment capability of one degree. The term three-axis gyroscope as used herein includes its broad meaning known to a skilled artisan. The gyroscope **212** provides outputs responsive to sensed angular velocity of the wireless sensor **102** (as affixed to the patient) in three orthogonal axes corresponding to measurements of pitch, yaw, and roll. A skilled artisan will appreciate that numerous other gyroscopes **212** can be used in the wireless sensor **102** without departing from the scope of the disclosure herein. In certain embodiments, the accelerometer **210** and gyroscope **212** can be integrated into a single hardware component which may be referred to as an inertial measurement unit (IMU). In some embodiments, the IMU can also include an embedded processor that handles, among other things, signal sampling, buffering, sensor calibration, and sensor fusion processing of the sensed inertial data. In other embodiments, the processor **202** can perform these functions. And in still other embodiments, the sensed inertial data are minimally processed by the components of the wireless sensor **102** and transmitted to an external system, such as the patient monitor **106**, for further processing, thereby minimizing the

complexity, power consumption, and cost of the wireless sensor **102**, which may be a single-use, disposable product.

FIG. 2B is a simplified hardware functional block diagram of an embodiment of the disclosed wireless sensor **102** that includes the following optional (as reflected by dotted lines) sensing components: a magnetometer **216** which may also be referred to as a compass, a temperature sensor **218**, an acoustic respiration sensor **220**, an electrocardiogram (ECG) sensor **222**, one or more oximetry sensors **224**, a moisture sensor **226**, and an impedance sensor **228**. In some embodiments, the magnetometer **216** is a three-dimensional magnetometer that provides information indicative of magnetic fields, including the Earth’s magnetic field. While depicted in FIG. 2B as separate functional elements, a skilled artisan will understand that the accelerometer **210**, gyroscope **212**, and magnetometer **214** can be integrated into a single hardware component such as an inertial measurement unit.

According to an embodiment, a system and method are described herein to calculate three-dimensional position and orientation of an object derived from inputs from three sensors attached to the object: an accelerometer **210** configured to measure linear acceleration along three axes; a gyroscope **212** configured to measure angular velocity around three axes; and a magnetometer **214** configured to measure the strength of a magnetic field (such as the Earth’s magnetic field) along three axes. In an embodiment, the three sensors **210**, **212**, and **214** are attached to the wireless sensor **102** which is affixed to the patient. According to an embodiment, the sensors **210**, **212**, and **214** are sampled at a rate between approximately 10 Hz and approximately 100 Hz. One skilled in the art will appreciate that the sensors **210**, **212**, and **214** can be sampled at different rates without deviating from the scope of the present disclosure. The sampled data from the three sensors **210**, **212**, and **214**, which provide nine sensor inputs, are processed to describe the patient’s position and orientation in three-dimensional space. In an embodiment, the patient’s position and orientation are described in terms of Euler angles as a set of rotations around a set of X-Y-Z axes of the patient.

Also illustrated in FIG. 2B is a temperature sensor **218** which may be used to measure the patient’s body core temperature which is a vital sign used by clinicians to monitor and manage patients’ conditions. The temperature sensor **218** can include a thermocouple, a temperature-measuring device having two dissimilar conductors or semiconductors that contact each other at one or more spots. A temperature differential is experienced by the different conductors. The thermocouple produces a voltage when the contact spot differs from a reference temperature. Advantageously, thermocouples are self-powered and therefore do not require an external power source for operation. In an embodiment, the temperature sensor **218** includes a thermistor. A thermistor is a type of resistor whose resistance value varies depending on its temperature. Thermistors typically offer a high degree of precision within a limited temperature range.

The acoustic respiration sensor **220** can be used to sense vibrational motion from the patient’s body (e.g., the patient’s chest) that are indicative of various physiologic parameters and/or conditions, including without limitation, heart rate, respiration rate, snoring, coughing, choking, wheezing, and respiratory obstruction (e.g., apneic events). The ECG sensor **222** can be used to measure the patient’s cardiac activity. According to an embodiment, the ECG sensor **222** includes two electrodes and a single lead. The oximetry sensor(s) **224** can be used to monitor the patient’s

pulse oximetry, a widely accepted noninvasive procedure for measuring the oxygen saturation level of arterial blood, an indicator of a person's oxygen supply. A typical pulse oximetry system utilizes an optical sensor clipped onto a portion of the patient's body (such as, for example, a fingertip, an ear lobe, a nostril, and the like) to measure the relative volume of oxygenated hemoglobin in pulsatile arterial blood flowing within the portion of the body being sensed. Oxygen saturation (SpO₂), pulse rate, a plethysmograph waveform, perfusion index (PI), pleth variability index (PVI), methemoglobin (MetHb), carboxyhemoglobin (CoHb), total hemoglobin (tHb), glucose, and/or otherwise can be measured and monitored using the oximetry sensor(s) 224. The moisture sensor 226 can be used to determine a moisture content of the patient's skin which is a relevant clinical factor in assessing the patient's risk of forming a pressure ulcer. The impedance sensor 228 can be used to track fluid levels of the patient. For example, the impedance sensor 228 can monitor and detect edema, heart failure progression, and sepsis in the patient.

FIG. 3A is a schematic exploded perspective view of an embodiment of the disclosed wireless sensor 102 including a bottom base 310, a removable battery isolator 320, a mounting frame 330, a circuit board 340, a housing 350, and a top base 360. The bottom base 310 is a substrate having a top surface on which various components of the wireless sensor 102 are positioned, and a bottom surface that is used to affix the wireless sensor 102 to the patient's body. The bottom base 310 and top base 360 can be made of medical-grade foam material such as white polyethylene, polyurethane, or reticulated polyurethane foams, to name a few. As illustrated in the embodiment illustrated in FIG. 3A, the bottom base 310 and the top base 360 are each in a substantially oval shape, with a thickness of approximately 1 mm. The top base 360 includes a cut-out 362 through which the housing 350 fits during assembly. Of course, a skilled artisan will understand that there are numerous sizes and shapes suitable for the top and bottom bases 310 and 360 that can be employed without departing from the scope of the present disclosure. The bottom surface of the bottom base 310 is coated with a high tack, medical-grade adhesive, which when applied to the patient's skin, is suitable for long-term monitoring, such as, for example two days or longer. Portions of the top surface of the bottom base 310 are also coated with a medical-grade adhesive, as the bottom base 310 and the top base 360 are adhered together during assembly of the wireless sensor 102.

The removable battery isolator 320 is a flexible strip made of an electrically insulating material that serves to block electrical communication between the battery 214 and an electrical contact (not shown) on the circuit board 340. The battery isolator 320 is used to preserve battery power until the wireless sensor 102 is ready for use. The battery isolator 320 blocks electrical connection between the battery 214 and the circuit board 340 until the battery isolator 320 is removed from the wireless sensor 102. The battery isolator 320 can be made of any material that possesses adequate flexibility to be slidably removed from its initial position and adequate dielectric properties so as to electrically isolate the battery from the circuit board 340. For example, the battery isolator can be made of plastic, polymer film, paper, foam, combinations of such materials, or the like. The battery isolator 320 includes a pull tab 322 that extends through a slot 352 of the housing 350 when the wireless sensor 102 is assembled. The pull tab 322 can be textured to provide a frictional surface to aid in gripping and sliding the pull tab 322 out of its original assembled position. Once the battery

isolator 320 is removed the battery 214 makes an electrical connection with the battery contact to energize the electronic components of the wireless sensor 102.

The mounting frame 330 is a structural support element that helps secure the battery 214 to the circuit board 340. The mounting frame 340 has wings 342 that, when assembled are slid between battery contacts 342 and the battery 214. Additionally, the mounting frame 330 serves to provide rigid structure between the circuit board 340 and the bottom base 310. According to some embodiments that include an acoustic respiratory sensor, the rigid structure transmits vibrational motion (vibrations) emanating from the patient (such as, for example, vibrational motions related to respiration, heartbeat, snoring, coughing, choking, wheezing, respiratory obstruction, and the like) to the accelerometer 210 positioned on the circuit board 340.

The circuit board 340, which may also be referred to herein as a substrate layer 340 and a circuit layer 340, mechanically supports and electrically connects electrical components to perform many of the functions of the wireless sensor 102. The circuit board 340 includes conduction tracks and connection pads. Such electrical components can include without limitation, the processor 202, the storage device 204, the wireless transceiver 206, the accelerometer 210, the gyroscope 212, the magnetometer 214, the temperature sensor 218, the acoustic respiration sensor 220, the ECG sensor 222, the oximetry sensor 224, the moisture sensor 226, and the impedance sensor 228. In an embodiment, the circuit board 340 is double sided having electronic components mounted on a top side and a battery contact (not shown) on a bottom side. Of course a skilled artisan will recognize other possibilities for mounting and interconnecting the electrical and electronic components of the wireless sensor 102.

As illustrated in FIG. 3A, a battery holder 342 is attached to two sides of the top portion circuit board 340 and extends (forming a support structure) under the bottom side of the circuit board 340 to hold the battery 214 in position relative to the circuit board 340. The battery holder 342 is made of electrically conductive material. In some embodiments, the battery 214 is a coin cell battery having a cathode on the top side and an anode on the bottom side. Electrical connection between the anode of the battery 214 and the circuit board 340 is made by way of the battery holder which is in electrical contact with the anode of the battery 214 and the circuit board 340. The cathode of the battery 214 is positioned to touch a battery contact (not shown) on the bottom side of the circuit board 340. In some embodiments, the battery contact includes a spring arm that applies force on the battery contact to ensure that contact is made between the anode of the battery 214 and the battery contact. During assembly and prior to use, the battery isolator 320 is inserted between the anode of the battery 214 and the battery connector to block electrical contact.

The housing 350 is a structural component that serves to contain and protect the components of the wireless sensor 102. The housing 350 can be made of any material that is capable of adequately protecting the electronic components of the wireless sensor 102. Examples of such materials include without limitation thermoplastics and thermosetting polymers. The housing 350 includes a slot 352 through which the battery isolator 320 is inserted during assembly. The housing 350 also includes a rim 354 that extends around the outer surface of the housing 350. The rim 354 is used to secure the housing 350 in position relative to the bottom base 310 and the top base 360 when the wireless sensor 102 is assembled.

Assembly of the wireless sensor **102** is as follows: The circuit board **340** and battery holder **342** holding the battery **214** are placed into the housing **350**. The wings **332** of the mounting frame **330** are inserted in between the battery **214** and the battery holder **342**, so as to align the mounting frame **330** with the circuit board **340**. The battery isolator **320** is then positioned between the battery contact and the battery **214**. The pull tab **322** of the battery isolator **320** is then fed through the slot **352** in the housing **350**. The top base **360** is then positioned over the housing **350**, which now houses the assembled circuit board **340**, battery holder **342**, battery **214**, mounting frame **330**, and battery isolator **320**, using the cut-out **362** for alignment. The rim **354** of the housing **350** adheres to the bottom surface of the top base **360**, which is coated with high tack, medical-grade adhesive. The partial assembly, which now includes the top base **360**, the housing **350**, the circuit board **340**, the battery holder **342**, the battery **214**, the mounting frame **330**, and the battery isolator **320**, is positioned centrally onto the top surface of the bottom base **310**, aligning the edges of the base top **360** with the edges of the base bottom **310**. In some embodiments, a coupon (or die cutting tool) is used to cut away excess portions of the now combined top and bottom bases **360** and **310** to form a final shape of the wireless sensor **102**. The bottom surface of the bottom base **310** is then coated with a high tack, medical-grade adhesive, and a release liner (not shown) is placed on the bottom surface of the bottom base **310** to protect the adhesive until it is time for use.

A schematic perspective view of the assembled wireless sensor **102** is illustrated in FIG. 3B. Also illustrated in FIG. 3B is a button/switch **324** located on a top portion of the housing **350**. The button/switch **324** can be used to change modes of the wireless sensor **102**. For example, in some embodiments, pressing and holding the button/switch **324** can cause the wireless sensor **102** to switch into a pairing mode of operation. The pairing mode is used to associate the wireless sensor **102** with a patient monitor **106** or with an extender/repeater **107**. FIG. 3C provides a schematic side view of an embodiment of the assembled wireless sensor **102** with cross-section line A-A identified.

Referring now to FIGS. 4A and 4B, an embodiment of the wireless sensor **102** is disclosed which includes a temperature sensor **218**. FIG. 4A is a schematic cross-sectional view, sectioned along line A-A of FIG. 3C, illustrating an assembled embodiment of the disclosed wireless sensor **102** which includes the temperature sensor **218**. For easier visibility, the battery isolator **320** and the battery holder **342** are not illustrated. FIG. 4B is a schematic bottom view of the embodiment of the disclosed wireless sensor of FIG. 4A. The bottom surface of the bottom base **310** is illustrated. Also illustrated in phantom (i.e., dotted lines) is the outline of cut-out **362** which also indicates the position of the housing **350** in relation to the bottom surface of the bottom base **310**.

As explained above with respect to the assembly of the wireless sensor **102**, the top surface of the bottom base **310** is in contact with and adhered to the bottom surface of the top base **360**. The rim **354** of the housing **350** is sandwiched between the two bases **310** and **360** to secure the housing **350**. The housing **350** also protrudes through the cut-out **362** of the top base **360**. Within the housing, the battery **214** and the mounting frame **330** are adjacent the top surface of the bottom base **310**.

As illustrated in FIG. 4A, the temperature sensor **218** is mounted on the circuit board **340**. To perform its temperature sensing function, the temperature sensor **218** is in thermal contact with the patient's skin. To achieve this,

structure to transmit thermal energy from the patient's body to the temperature sensor **218** is provided. In particular, inputs to the temperature sensor **218** are thermally connected to multiple through-hole vias **410** located in the circuit board **340**. A through-hole via is a small vertical opening or pathway in the circuit board **340** through which thermally and/or electrically conductive material can be placed, thereby permitting transmission of thermal and/or electrical energy from one side of the circuit board **340** to the other side. Under the through-hole vias **410** is an aperture or opening **404** which extends through the mounting frame **330** (to form a mounting frame aperture) and through the bottom base **310** of the wireless sensor **102**. The aperture **404** provides access from the temperature sensor **218** to the patient's skin when the wireless sensor **102** is worn by the patient. The aperture **404** and the through-hole vias **410** are filled with thermally conductive material **402**. Thermally conductive materials are well known in the art and can include, by way of non-limiting example, thermally conductive elastomers, polymers, and resins, to name a few. Illustratively, in operation, the wireless sensor **102** is affixed to the patient's skin. The thermally conductive material **402**, exposed to the patient's skin, transmits thermal energy from the patient's body through the aperture **404** and the through-hole vias **410** to arrive at the inputs to the temperature sensor **218**.

Advantageously, the disclosed wireless sensor **102** can measure the patient's body core temperature (an established and useful vital sign) with the temperature sensor **218** using a technique by which deep tissue temperature can be measured from the skin surface. In the human body, there is a natural heat flux between the body core and the skin surface because the body core temperature is typically at a higher temperature than that of the skin surface. Thus heat flows from the body core to the skin. By insulating the skin surface at and around the point at which the skin temperature is measured—thereby blocking heat from escaping—the temperature gradient between the body core and the skin surface will decrease. The skin temperature, under the insulated area will rise until it reaches equilibrium with the warmest region (i.e., the body core) under the insulation, thereby approaching the body core temperature. When equilibrium is reached, the skin temperature is equal to the core body temperature. Advantageously, the bottom base **310** and top base **360** of the wireless sensor **102**, which are in contact with the patient's skin around the temperature sensor **218**, possess thermal insulation properties. Illustratively, by way of non-limiting example, the bottom base **310** and top base **360** can be made thermally insulating materials including polyurethane foam, polystyrene foam, neoprene foam, neoprene rubber, polyester (Mylar), polytetrafluoroethylene (PTFE), silicone foam, silicone rubber, or the like. Accordingly, the temperature sensor **218** can measure the patient's body core temperature.

FIG. 4C is a schematic exploded perspective view of the embodiment of the disclosed wireless sensor of FIGS. 4A and 4B. As shown, the temperature sensor **218** is mounted on the top surface of the circuit board **340**. The aperture **404** extends through the mounting frame **330** and the bottom base **310** and is aligned vertically with the through-hole vias **410** (not shown in FIG. 4C) and the temperature sensor **218**. The aperture **404** and the through-hole vias **410** are filled with thermally conductive material **402**. Thus the disclosed structure provides thermal connectivity between the patient's skin and the temperature sensor **218**.

Referring now to FIGS. 5A and 5B, an embodiment of the wireless sensor **102** is disclosed which includes an acoustic

21

respiration sensor 220. FIG. 5A is a schematic cross-sectional view, sectioned along line A-A of FIG. 3C, illustrating an assembled embodiment of the disclosed wireless sensor 102 which includes the acoustic respiration sensor 220. For easier visibility, the battery isolator 320 and the battery holder 342 are not illustrated. FIG. 5B is a schematic bottom view of the embodiment of the disclosed wireless sensor of FIG. 5A. The bottom surface of the bottom base 310 is illustrated. Also illustrated in phantom (i.e., dotted lines) is the outline of cut-out 362 which indicates the position of the housing 350 in relation to the bottom surface of the bottom base 310.

As illustrated in FIG. 5A, the acoustic respiration sensor 220 is mounted underneath the battery 214. Operationally, the acoustic respiration sensor 220 detects vibratory motion emanating from the patient's body (e.g., the patient's chest) and mechanically transmits the detected vibratory motion to the accelerometer 210. The accelerometer 210 senses the mechanically transmitted vibratory motion. The signal collected by accelerometer 210 can be processed to extract the vibratory motion from other sensed acceleration signals. Examples of such vibratory motion can include, without limitation, heart beats, respiration activity, coughing, wheezing, snoring, choking, and respiratory obstruction (e.g., apneic events). To mechanically transmit the sensed vibratory motion effectively, the acoustic respiration sensor 220 is in rigid structural contact with the accelerometer 210. To achieve this, the acoustic respiration sensor 220 is mounted to the bottom side of the battery 214. In particular, the acoustic respiration sensor 220 includes a rim 221 that is sandwiched between the bottom surface of the battery 214 and the bottom base 310. Accordingly, the rim 221 serves to rigidly secure the acoustic respiration sensor 220 to the bottom surface of the battery 214.

As illustrated in FIG. 5A, the acoustic respiration sensor 220 protrudes through an aperture or opening 502 in the bottom base 310, beyond the plane created by the bottom base 310. This is to ensure that the acoustic respiration sensor 220 is in direct contact with the patient's body (e.g., chest) so as to sense the vibrational motion emanating from the patient. Within the acoustic respiration sensor 220 is a flexible wire or other such structure under slight tension such that when the wire is exposed to vibratory motion, it will vibrate in a manner that is proportional to the sensed vibratory motion with respect to both frequency and magnitude of the sensed vibratory motion. The acoustic respiration sensor 220 is configured to transmit the sensed vibratory motion through rigid structures of the wireless sensor 102 such that the transmitted vibratory motion is sensed by the accelerometer 210. The rigid structure includes the battery 214 and the circuit board 340.

FIG. 5C is a schematic exploded perspective view of the embodiment of the disclosed wireless sensor of FIGS. 5A-B. As shown, the accelerometer 210 is mounted on the top surface of the circuit board 340 over the battery 214 which is secured underneath the circuit board 340. The acoustic respiration sensor 220 (not shown in FIG. 5C) fits between the battery 214 and the bottom base 310. The aperture 502 extends through the bottom base 310 and is aligned vertically with battery 214 such that the acoustic respiration sensor 220 is secured to rigid structure of the wireless sensor 102. Thus the disclosed structure provides the ability for the acoustic respiration sensor 220 to mechanically transmit vibratory motion from the patient's chest to the accelerometer 210.

FIGS. 6A-C illustrate an embodiment of the disclosed wireless sensor 102 which includes a temperature sensor 218

22

and an acoustic respiration sensor 220. FIG. 6A is a schematic cross-sectional view, sectioned along line A-A of FIG. 3C, illustrating an assembled embodiment of the disclosed wireless sensor 102 which includes the temperature sensor 218 and acoustic respiration sensor 220. For easier visibility, the battery isolator 320 and the battery holder 342 are not illustrated. FIG. 6B is a schematic bottom view of the embodiment of the disclosed wireless sensor of FIG. 6A. FIG. 6C is a schematic exploded perspective view of the embodiment of the disclosed wireless sensor 102 of FIGS. 6A and 6B.

Structurally, the embodiment depicted in FIGS. 6A-C is a combination of the embodiments depicted in FIGS. 4A-C and 5A-C. As illustrated in FIGS. 6A-B, the temperature sensor 218 is mounted on the circuit board 340. As previously described, inputs to the temperature sensor 218 are thermally coupled to multiple through-hole vias 410 located in the circuit board 340. Under the through-hole vias 410 is an aperture 404 which extends through the mounting frame 330 and through the bottom base 310 of the wireless sensor 102. The aperture 404 provides access from the temperature sensor 218 to the patient's skin when the wireless sensor 102 is worn by the patient. The aperture 404 and the through-hole vias 410 are filled with thermally conductive material 402. In operation, the wireless sensor 102 is affixed to the patient's skin. The thermally conductive material 402, exposed to the patient's skin, transmits thermal energy from the patient's body through the aperture 404 and the through-hole vias 410 to arrive at the inputs to the temperature sensor 218.

Also as illustrated in FIGS. 6A-B, the acoustic respiration sensor 220 is mounted underneath the battery 214. In particular, the acoustic respiration sensor 220 includes rim 221 that is sandwiched between the bottom surface of the battery 214 and the bottom base 310. Accordingly, the rim 221 serves to rigidly secure the acoustic respiration sensor 220 to the bottom surface of the battery 214. The acoustic respiration sensor 220 protrudes through the aperture 502 in the bottom base 310, beyond the plane created by the bottom base 310. The acoustic respiration sensor 220 is configured to transmit vibratory motion sensed from the patient (e.g., from the patient's chest) through rigid structures of the wireless sensor 102 such that the transmitted vibratory motion is sensed by the accelerometer 210. The rigid structure includes the battery 214 and the circuit board 340.

FIG. 6C is a schematic exploded perspective view of the embodiment of the disclosed wireless sensor of FIGS. 6A and 6B. As shown, the temperature sensor 218 is mounted on the top surface of the circuit board 340. The aperture 404 extends through the mounting frame 330 and the bottom base 310 and is aligned vertically with the through-hole vias 410 (not shown in FIG. 4C) and the temperature sensor 218. The aperture 404 and the through-hole vias 410 are filled with thermally conductive material 402. Additionally, the accelerometer 210 is mounted on the top surface of the circuit board 340 over the battery 214 which is secured underneath the circuit board 340. The acoustic respiration sensor 220 (not shown in FIG. 6C) fits between the battery 214 and the bottom base 310. In some embodiments, the acoustic respiration sensor 220 abuts against the mounting frame 330 in a manner such that the acoustic respiration sensor 220, the mounting frame 330, the battery 214 and the circuit board 340 form a rigid structure capable of mechanically transmitting vibratory motion sensed by the acoustic respiration sensor 220 to the accelerometer 210 mounted on the circuit board 340. The aperture 502 extends through the bottom base 310 and is aligned vertically with battery 214

such that the acoustic respiration sensor **220** is secured to rigid structure of the wireless sensor **102**. Thus the disclosed embodiment provides thermal connectivity between the patient's skin and the temperature sensor **218** and the ability for the acoustic respiration sensor **220** to mechanically transmit vibratory motion from the patient's chest to the accelerometer **210**.

Advantageously, the embodiment disclosed in FIGS. 6A-C is capable of providing, among other things, three vital signs: body core temperature, pulse rate, and respiration rate. Vital signs are measurements of the body's most basic functions and are used routinely by healthcare providers to assess and monitor a patient's status. The patient's body core temperature can be provided by the temperature sensor **218**. The patient's pulse rate and respiration rate can be provided by the acoustic respiration sensor **220** in combination with the accelerometer **210**.

Referring to FIGS. 7A-F, an embodiment of the disclosed wireless sensor **102** is shown which includes an electrocardiogram (ECG) sensor **222**. Chip-scale and/or component-scale ECG sensors, suitable for mounting on circuit boards are known in the art. Illustratively, by way of non-limiting example, solid state ECG sensors are offered by Texas Instruments and by Plessy Semiconductors Ltd., to name a few. FIG. 7A is a perspective view of the embodiment of the disclosed patient-worn wireless sensor **102** having an ECG sensor **222** including an ECG lead **706** that extends from the housing **350**. The wireless sensor **102** is adhered to the patient's chest, for example, over the manubrium as illustrated in FIG. 7A. The ECG lead **706** extends from the housing **350** of the wireless sensor **102** to a location on the patient's chest suitable to sense electrical signals generated by the patient's heart. The ECG lead **706** is in electrical communication with an ECG electrode **707** which, in operation, is adhered to the patient's chest. In certain embodiments, the ECG electrode **707** includes conducting gel embedded in the middle of a self-adhesive pad. The ECG electrode **707** senses electrical signals from the patient's chest and transmits the sensed signals, via the lead **706**, to the ECG sensor **222**. The electrode **707** adheres to the patient's skin and senses electrical signals therefrom. A skilled artisan will appreciate that many structures, forms, and formats of ECG electrodes are well known in the art and can be used to implement the ECG electrode **707**.

As illustrated in FIG. 7A, the ECG lead **706** extends to the left side of the patient's chest to a position across the heart from where the wireless sensor **102** is located. Another ECG electrode **702** (described below), also in contact with the patient's skin, is formed beneath the housing **350** at the bottom base **310**. Thus, a vector is formed between the ECG lead electrode **707** and the ECG electrode **702** by which the electrical signals of the patient's heart can be sensed. Illustratively, when the electrodes **702** and **707** are positioned as depicted in FIG. 7A, the ECG sensor **222** can sense ECG signals that are similar in morphology to ECG signals detected on Lead I or Lead II of a standard 12-lead ECG.

FIG. 7B is a schematic assembled perspective view of the embodiment of the disclosed wireless sensor **102** of FIG. 7A. The ECG lead **706** is connected to the ECG sensor **222** (shown in FIG. 7D) which is mounted on the circuit board **340**. As illustrated in FIG. 7B, the ECG lead extends through the housing **350** to a lockable retractable reel **708** that stores the ECG lead **706** in a coil when not in use. The ECG lead **706** can be extended from the reel **708** and locked in the desired position, thereby enabling placement of the ECG lead electrode **707** at a desired location on the patient's chest. In some embodiments, the locking mechanism is

engaged and disengaged by applying a pulling force on the lead **706**. Various forms and versions of lockable retractable reels are well known in the art and may be used to implement the reel **708**.

FIG. 7C provides a schematic side view of the embodiment of the assembled wireless sensor **102** of FIGS. 7A and 7B with cross-section line B-B identified. FIG. 7D is a cross-sectional view of the embodiment of FIGS. 7A-C sectioned along line B-B. As illustrated in FIG. 7D, the ECG sensor **222** is mounted on the circuit board **340**. To perform its sensing function, the ECG sensor **222** is in electrical contact with at least two points on the patient's skin. Two electrodes **702** and **707** are provided to achieve this purpose. While ECG electrode **707** has been described above, description of the ECG electrode **702** follows herewith.

ECG electrode **702** is located within the bottom base **310** of the wireless sensor **102**. An input to the ECG sensor **222** is electrically connected to multiple through-hole vias **710** located in the circuit board **340**. As previously described, through-hole vias are small vertical openings, or pathways, in the circuit board **340** through which electrically conductive material can be placed, thereby permitting transmission of electrical signals from one side of the circuit board **340** to the other side. Under the through-hole vias **710** is an aperture or opening **704** which extends through the mounting frame **330** (to form a mounting frame aperture) and through the bottom base **310** of the wireless sensor **102**. The aperture **704** provides access from the ECG sensor **222** to the patient's skin when the wireless sensor **102** is worn by the patient. The aperture **704** and the through-hole vias **710** are filled with electrically conductive material to form the ECG electrode **702**. Electrically conductive materials are well known in the art and can include, by way of non-limiting example, electrically conductive silicones, elastomers, polymers, epoxies, and resins, to name a few. In operation, the wireless sensor **102** is affixed to the patient's skin and the ECG electrode **702**, exposed to the patient's skin, senses and transmits electrical signals from the patient's skin surface through the aperture **704** and the through-hole vias **710** to arrive at an input to the ECG sensor **222**.

FIG. 7E is a schematic bottom view of the embodiment of the disclosed wireless sensor of FIGS. 7A-D. The bottom surface of the bottom base **310** is illustrated. Also illustrated in phantom (i.e., dotted lines) are the outline of cut-out **362** which also indicates the position of the housing **350** in relation to the bottom surface of the bottom base **310**, and the lockable retractable reel **708**. The ECG electrode **702** is also illustrated as it is positioned to make contact with the patient's skin. In some embodiments, the ECG electrode may be coated with a conducting gel to improve the electrode-to-skin interface.

FIG. 7F is a schematic exploded perspective view of the embodiment of the disclosed wireless sensor of FIGS. 7A-7E. As shown, the ECG sensor **222** is mounted on the top surface of the circuit board **340**. The aperture **704** extends through the mounting frame **330** and the bottom base **310** and is aligned vertically with the through-hole vias **710** (not shown in FIG. 7F) and the ECG sensor **222**. The aperture **704** and the through-hole vias **710** are filled with electrically conductive material to form electrode **702**. Thus the disclosed structure provides electrical connectivity between the patient's skin and the ECG sensor **222**.

FIG. 8A is a schematic exploded perspective view of an embodiment of the disclosed wireless sensor having a temperature sensor **218**, an acoustic respiration sensor **220**, and an ECG sensor **222**. FIG. 8B is a schematic bottom view of the disclosed wireless sensor of FIG. 8A. Structurally, the

embodiment depicted in FIGS. 8A-B is a combination of the embodiments depicted in FIGS. 4A-C and 5A-C and 7A-F. As illustrated in FIGS. 8A-B, the temperature sensor 218 is mounted on the circuit board 340. As previously described, inputs to the temperature sensor 218 are thermally coupled to multiple through-hole vias 410 located in the circuit board 340. Under the through-hole vias 410 is an aperture 404 which extends through the mounting frame 330 and through the bottom base 310 of the wireless sensor 102. The aperture 404 provides access from the temperature sensor 218 to the patient's skin when the wireless sensor 102 is worn by the patient. The aperture 404 and the through-hole vias 410 are filled with thermally conductive material 402.

The acoustic respiration sensor 220 is mounted underneath the battery 214, held in place by rim 221 that is sandwiched between the bottom surface of the battery 214 and the bottom base 310. Accordingly, the rim 221 serves to rigidly secure the acoustic respiration sensor 220 to the bottom surface of the battery 214. The acoustic respiration sensor 220 protrudes through the aperture 502 in the bottom base 310, beyond the plane created by the bottom base 310. The acoustic respiration sensor 220 transmits vibratory motion sensed from the patient (e.g., from the patient's chest) through rigid structures of the wireless sensor 102 such that the transmitted vibratory motion is sensed by the accelerometer 210. The rigid structure through which the vibratory motion is transmitted includes the battery 214 and the circuit board 340.

The ECG electrode 702 is located within the bottom base 310 of the wireless sensor 102. An input to the ECG sensor 222 is electrically coupled to multiple through-hole vias 710 located in the circuit board 340. Under the through-hole vias 710 is an aperture or opening 704 which extends through the mounting frame 330 and through the bottom base 310 of the wireless sensor 102. The aperture 704 provides access from the ECG sensor 222 to the patient's skin when the wireless sensor 102 is worn by the patient. The aperture 704 and the through-hole vias 710 are filled with electrically conductive material to form the ECG electrode 702.

In operation, the wireless sensor 102 is affixed to the patient's skin. The thermally conductive material 402, exposed to the patient's skin, transmits thermal energy from the patient's body through the aperture 404 and the through-hole vias 410 to arrive at the inputs to the temperature sensor 218. The acoustic respiratory sensor 220 senses vibratory motion from the patient and mechanically transmits the vibratory motion to the accelerometer 210 mounted on the circuit board. And the ECG electrodes 702 and 707, exposed to the patient's skin, sense and transmit electrical signals from the patient's skin surface to arrive at inputs to the ECG sensor 222.

FIG. 8B is a schematic bottom view of the embodiment of the disclosed wireless sensor of FIG. 8A. The bottom surface of the bottom base 310 is illustrated. Also illustrated in phantom (i.e., dotted lines) are the outline of cut-out 362 and the lockable retractable reel 708. Three sensor access points are shown in FIG. 8B. The thermally conductive material 402 provides a pathway for thermal energy to be transmitted from the patient's skin the temperature sensor 218 mounted on the circuit board 340. The acoustic respiration sensor 220 is in direct contact with the patient's skin and in rigid structural contact with the accelerometer 210 so as to mechanically transmit sensed vibratory motion emanating from the patient to the accelerometer 210 mounted on the circuit board 340. And the ECG electrode 702 provides a

pathway for electrical signals to be transmitted from the patient's skin to the ECG sensor 220 mounted on the circuit board 340.

In some scenarios, it may be desirable to pair, or associate, the wireless sensor 102 with the bedside patient monitor 106 to avoid interference from other wireless devices and/or to associate patient-specific information (stored, for example, on the patient monitor 106) with the sensor data that is being collected and transmitted by the wireless sensor 102. Illustratively, such patient-specific information can include, by way of non-limiting example, the patient's name, age, gender, weight, identification number (e.g., social security number, insurance number, hospital identification number, or the like), admission date, length of stay, physician's name and contact information, diagnoses, type of treatment, perfusion rate, hydration, nutrition, pressure ulcer formation risk assessments, patient turn protocol instructions, treatment plans, lab results, health score assessments, and the like. One skilled in the art will appreciate that numerous types of patient-specific information can be associated with the described patient-worn sensor without departing from the scope of the present disclosure. Additionally, pairing the wireless sensor 102 with the patient monitor 106 can be performed to provide data security and to protect patient confidentiality. Some wireless systems require the care provider to program the wireless sensor 102 to communicate with the correct patient monitor 106. Other wireless systems require a separate token or encryption key and several steps to pair the wireless device 102 with the correct bedside patient monitors 106. Some systems require the token to be connected to the bedside patient monitor 106, then connected to the wireless device 102, and then reconnected to the bedside patient monitor 106. In certain scenarios, it may be desirable to share wireless communication information between a wireless sensor 102 and a bedside patient monitor 106 without a separate token or encryption key. For security purposes, it may be desirable to use security tokens to ensure that the correct bedside patient monitor 106 receives the correct wirelessly transmitted data. Security tokens prevent the bedside patient monitor 106 from accessing the transmitted data unless the wireless sensor 102 and bedside patient monitor 106 share the same password. The password may be a word, passphrase, or an array of randomly chosen bytes.

FIG. 9 illustrates an exemplary method of associating a wireless sensor 102 with a patient monitor 106, which may be referred to as "pairing." At block 902 the wireless sensor 102 is set to operate in a pairing mode. In an embodiment, a user initiates the pairing mode of operation for the wireless sensor 102. This may include powering on the wireless sensor 102, switching the wireless sensor 102 to a special pairing state, and/or the like. For example, in certain embodiments, the wireless sensor 102 may include a battery isolator 320 which, when removed, activates the wireless sensor 102. Upon activation, the default mode of operation is the pairing mode. In some embodiments, the wireless sensor 102 may have a button/switch 324 that can be used to activate the wireless sensor 102 and place it in the pairing mode of operation. For example, a depressible button/switch 324 can be located on the top portion of the housing 350. When the button/switch 324 is depressed and continuously held down, the wireless sensor 102 enters into the pairing mode of operation and remains in the pairing mode of operation for as long as the button/switch 324 is depressed.

As reflected at block 904, the wireless sensor 102 transmits a pairing signal indicating that it is ready to pair, or associate, with a patient monitor 106. According to some

embodiments, the wireless transceiver **206** of the wireless sensor **102** is configured to emit a low-power pairing signal having a limited pairing signal transmission range. The limited pairing signal transmission range helps to prevent unintended or incidental association of the wireless sensor **102** with a patient monitor **106** that might be nearby but which is not intended to be paired with the wireless sensor **102**. Such circumstances can occur in hospitals, healthcare facilities, nursing homes, and the like where patients, sensors **102** patient monitors **106** are located in close physical proximity to one another. In certain embodiments, the low-power pairing signal has a pairing signal transmission range of up to approximately three inches. In other embodiments, the low-power pairing signal has a pairing signal transmission range of up to approximately six inches. In other embodiments, the low-power pairing signal has a pairing signal transmission range of up to approximately one foot (i.e., twelve inches). A skilled artisan will recognize that other ranges can be used for the pairing signal transmission range.

Next, at block **906**, the patient monitor **106**, when within the pairing signal transmission range, receives the pairing signal from the wireless sensor **102**. Upon detection of the pairing signal, the patient monitor **106**, at block **908**, associates with the wireless sensor **102** thereby configuring the wireless sensor **102** and patient monitor **106** to communicate with each other. Once the pairing is completed, the patient monitor **106** transmits a confirmation signal confirming that the patient-worn sensor **102** is associated with the patient monitor **106**, thereby indicating that the pairing process has been successfully completed, as reflected in block **910**. At block **912**, the wireless sensor **102** receives the confirmation signal. And at block **914**, the wireless sensor **102** exits the pairing mode of operation and enters into a patient parameter sensing mode of operation. In the patient parameter sensing mode of operation, the patient-worn sensor **102** transmits a patient parameter sensing signal having a patient parameter sensing signal transmission range. The wireless sensor **102** increases the power of the patient parameter sensing signal transmission range to a standard operating range, such as for example, approximately three meters. In some embodiments, the patient parameter sensing signal transmission range is approximately ten feet. In some embodiments, the patient parameter sensing signal transmission range is approximately thirty feet. In certain embodiments, the pairing signal transmission range is between approximately three and twelve inches, while the patient parameter sensing signal transmission range is approximately ten feet. In such embodiments, there is at least an order of magnitude difference between the pairing signal transmission range and the patient parameter sensing signal transmission range. Thus, the pairing signal transmission range is substantially less than the patient parameter sensing signal transmission range. Once the wireless sensor **102** enters into the patient parameter sensing mode of operation, the wireless sensor **102** is then in condition to be placed on the patient to perform sensing and monitoring functions.

In certain embodiments, an extender/repeater **107** is used to communicate with the wireless sensor **102** instead of than a patient monitor **106**. Pairing with the booster/repeater may be performed in the same manner described above with respect to FIG. 9.

According to certain embodiments, the disclosed patient monitoring system **100** helps to manage a patient that is at risk of forming one or more pressure ulcers by, among other things, detecting changes in the patient's orientation and by determining how long the patient remains in the present

orientation. Advantageously, the system **100** can detect when the patient is repositioned and begin timing the duration that the patient remains in that new orientation. Thus, if the patient repositions on his own without the observation of a care provider, the monitoring system **100** can detect the repositioning event and restart a timer.

The patient monitoring system **100** can aid in the administration of a clinician-established turning protocol for the patient. For example, if the patient remains in an orientation beyond a predefined, clinician-prescribed duration, the system **100** can notify the patient and/or caretakers that the patient is due to be repositioned. The wireless sensor **102** obtains sensor information indicative of the patient's orientation (e.g., acceleration data), pre-processes the sensed data, and transmits it to a processing device capable of processing the measurement data, such as, for example, the patient monitor **106**. Other devices capable of processing the measurement data include, without limitation, clinician devices **114**, nurses' station systems **113**, the multi-patient monitoring system **110**, a dedicated processing node, or the like. For ease of illustration, the description herein will describe the processing device as the patient monitor **106**; however, a skilled artisan will appreciate that a large number of processing devices may be used to perform the described functions without departing from the scope of the present disclosure.

The patient monitor **106** stores and further processes the received data to determine the patient's orientation. According to some embodiments, the patient monitor **106** can determine whether the patient is standing, sitting, or lying in the prone, supine, left side, or right side positions. The patient monitor **106** can store the determined orientation information and keep track of how long the patient remains in each determined orientation, thereby creating a continuous record of the patient's positional history. In certain embodiments, the information received from the wireless sensor **102** can be used to create a time-sequenced representation of the patient's positional history. This representation can be displayed on the patient monitor **106** or transmitted to a nurses' station or other processing node to enable caregivers to monitor the patient's position in bed. The time-sequenced representation can be viewed in real time and/or be accessed for playback. For example, if an alarm alerts the caregiver that the patient has exceeded the maximum amount of time to remain in the present orientation, the caregiver can access and review the historical sequence of the patient's orientations prior to and during that period of time to determine the next orientation to which the patient may be repositioned. In some embodiments, the system **100** suggests the orientation to which the patient may be repositioned.

Illustratively, the patient monitor **106** counts the number of in-bed turns performed by the patient and displays the amount of time that has elapsed since the patient last turned. When the elapsed time exceeds a clinician-defined duration (e.g., two hours), the patient monitor **106** displays an indication that the maximum time between patient turns has been exceeded. The patient monitor **106** can also transmit a notification to clinicians responsible for caring for the patient via, for example, the multi-patient monitoring system **110**, a clinician notification device **114**, or the like. The patient monitor **106** can also determine and display statistical information, such as the average, minimum, and maximum amount of time between turns for a given clinician-defined time period, such as for example, twenty-four hours. The patient monitor **106** can also determine and display the number of patient turns in the same orientation over a

clinician-defined period of time. Similarly, the patient monitor **106** can display the total amount of time the patient has remained in each specific orientation within a clinician-defined period. Moreover, the patient monitor **106** can determine the frequency and duration of periods that the patient remained in clinically-defined acceptable orientations.

In some embodiments of the present disclosure, the patient monitor **106** accesses the patient's health records and clinician input via the network **108**. Illustratively, the patients' positional history data, analyzed in view of the patient's health records, may reveal or suggest a turning protocol (or other treatment protocol) that will likely yield favorable clinical outcomes for the particular patient. Accordingly, the patient monitor **106** analyzes the accessed information in conjunction with the received information from the wireless sensor **102** to determine a recommended patient turn protocol (or other treatment protocol) for the patient.

According to some embodiments of the present disclosure, the patient monitor **106** assesses caregiver and facility compliance with the clinician-defined turning protocol established for the patient. For example, the patient monitor **106** can identify the number of times that the patient remains in a position for a period greater than the prescribed duration, as well as the length of each such overexposure. The patient monitor **106** can also track the time between issuance of a notification, alert, or alarm and action taken in response to the event that triggered the issuance, corresponding to clinician response time.

FIG. **10** illustrates a method **1000** of estimating and monitoring the orientation of a patient in bed according to an embodiment of the present disclosure. The method **1000** also identifies when the patient changes orientation and keeps track of the amount of time the patient spends in that orientation. The patient orientations that may be determined include, without limitation, whether the patient is prone, supine, on the left side, on the right side, sitting, and lying. In some embodiments, the patient monitor **106** determines the precise orientation of the patient's body. For example, the patient monitor **106** can determine the degree to which the patient's body is inclined, vertically and/or horizontally, thereby generating an accurate description of the patient's orientation relative to the support structure (such as a bed) upon which the patient lies.

According to an embodiment of the present disclosure, measurements from the accelerometer **210** of the wireless sensor **102** are used to determine the patient's orientation. The accelerometer **210** measures linear acceleration of the patient with respect to gravity. In some embodiments the accelerometer **210** measures linear acceleration in three axes. One axis, referred to as "roll," corresponds to the longitudinal axis of the patient's body. Accordingly, the roll reference measurement is used to determine whether the patient is in the prone position (i.e., face down), the supine position (i.e., face up), or on a side. Another reference axis of the accelerometer **210** is referred to as "pitch." The pitch axis corresponds to the locations about the patient's hip. Thus, the pitch measurement is used to determine whether the patient is sitting up or lying down. A third reference axis of the accelerometer **210** is referred to as "yaw." The yaw axis corresponds to the horizontal plane in which the patient is located. When in bed, the patient is supported by a surface structure that generally fixes the patient's orientation with respect to the yaw axis. Thus, in certain embodiments of the disclosed method **1000**, the yaw measurement is not used to determine the patient's orientation when in bed.

Illustratively, the described method **1000** continuously or periodically (e.g., every second) determines the patient's orientation based on the measurements of pitch and roll provided by the accelerometer **210**. The measurements are tracked over time, and the current measurement is compared to one or more measurements in the recent past (e.g., the previous few seconds) to determine whether an orientation change event has occurred.

The method **1000** is described in further detail herein with respect to FIG. **10**. The method **1000** begins at block **1002** in which acceleration measurement data are received from the wireless sensor **102** by a device capable of processing the measurement data, such as, for example, the patient monitor **106**. Other devices capable of processing the measurement data include, without limitation, clinician devices **114**, nurses' station systems **113**, the multi-patient monitoring system **110**, a processing node, or the like. For ease of illustration, the description herein will describe the processing device as the patient monitor **106**; however, a skilled artisan will appreciate that a large number of devices may be used to perform the described method **1000** without departing from the scope of the present disclosure.

The acceleration measurement data may be provided directly from the wireless sensor **102** to the patient monitor **106**, or the measurement data may be relayed over a network such as network **108**, by an extender/repeater **107**, for example. The acceleration measurement data may be initially sampled at a sampling rate suitable to provide an acceptable degree of precision, such as for example, 100 Hz. In some embodiments, the measured data are sub-sampled by the wireless sensor **102** before being transmitted in order to reduce power consumption of the battery **214** of the wireless sensor **102**. In an embodiment, the acceleration measurement data are initially sampled at 100 Hz and subsequently down-sampled, for transmission purposes, to a rate of 26 Hz. In an embodiment, the acceleration measurement data are initially sampled at a range between approximately 10 Hz and approximately 200 Hz and subsequently down-sampled, for transmission purposes, at a rate between approximately 5 Hz and approximately 40 Hz. A skilled artisan will understand that many other sampling rates and sub-sampling rates may be used.

At block **1004**, the patient monitor **106** determines the present orientation of the patient. The received acceleration measurement data are processed to determine orientation values for the roll and pitch axes. The processed acceleration measurement data are provided in units of degrees, ranging from -180 degrees to +180 degrees. A lookup table, based on empirical data, provides a correlation between pairs of roll and pitch measurements and patient orientations. Illustratively, by way of non-limiting example, a roll measurement of 180 degrees can mean that the patient is on his back, and a pitch measurement of 0 degrees can mean that the patient is lying down. Thus the combination of a roll measurement of 180 degrees and a pitch measurement of 0 degrees can correspond to an orientation in which the patient is lying down on his back. Similarly, a combination of a roll measurement of 180 degrees and a pitch measurement of 90 degrees can correspond to an orientation in which the patient is lying on his right side.

FIG. **11A** illustrates an exemplary plot **1100** of processed accelerometer **210** data over time (from 0 to 450 seconds) used to determine a patient's orientation according to an embodiment of the present disclosure. Initially, at for example, 50 seconds, the data corresponding to the roll (i.e., body length) axis **1102** is at approximately 180 degrees, indicating that the patient is on his back (i.e., in the supine

orientation). The data corresponding to the pitch (i.e., hip rotation) axis **1104** is at approximately 0 degrees, indicating that the patient is reclining. Thus, combining the orientation information provided by the accelerometer **210** with respect to the roll and pitch axes **1102** and **1104**, the patient is determined to be lying on his back. At approximately 360 seconds on the plot, denoted by vertical line **1106**, we see that the patient changes orientation. During a short transition period, the data oscillates, as illustrated in the data representing the pitch axis at transition point **1108** and in the data representing the roll axis at transition point **1110**. The oscillations can be caused by, among other things, jostling of the patient while moving from one position to the next. Shortly thereafter, the data achieves a steady state, as reflected by relatively stable graphs **1112** and **1114**. Notably, the data indicative of the pitch axis **1102** has moved from approximately 180 degrees to approximately 90 degrees. This corresponds to a ninety-degree rotation of the patient's longitudinal body axis to the patient's right side. The data indicative of the roll axis remains at approximately zero degrees, indicating that the patient remains in the reclining position. Thus, combining the orientation information provided by the accelerometer **210** with respect to the roll and pitch axes **1112** and **1114**, the patient is determined to be lying on his right side. In this manner, a lookup table of patient orientation change actions can be created. The table identifies profiles (e.g., combinations of pitch and roll axis measurements, within certain tolerances) of various possible orientations that a patient can assume while in bed. The table of profiles of patient orientation change actions can be based on empirical data that is collected and analyzed.

Referring back to FIG. 10, at block **1006**, previous patient orientation determinations are extracted and combined with the current orientation determinations to form a time window of patient orientation information. For example, the time window can include information indicative of the patient's orientation from one or more time periods that are in close temporal proximity to the present information indicative of the patient's orientation, such as for example, the previous few seconds. Of course, any number of previous patient orientations can be selected for the time window. In an embodiment, the patient's orientation determinations for the previous two seconds are combined with the present determination to create a three-second time window of the patient's orientation. The purpose for creating the time window is to determine whether the patient has recently repositioned.

At block **1008**, the time window is divided into segments for purposes of analysis. Any number of segments can be used for such analysis of the time window data. In an embodiment, the time window is segmented into three segments. In another embodiment, the time window is segmented into two segments. As illustrated in FIG. 11A at transition points **1108** and **1110**, it is possible that the measured data used for the time window contains multiple sources of noise, some of which can have spikes of notable magnitude. To reduce the impact of the noise in the analysis, a segment value for each segment is determined. As disclosed at block **1010**, the median value of the sampled data within each segment is used to determine the segment values for each segment. By taking the median value of each segment, a segment value is determined with minimal impact of potential noisy spikes. In certain embodiments, the segment value is a vector comprising values corresponding to each axis of measured data. Illustratively, by way of non-limiting example, each segment value comprises a vector including a roll axis segment component and a pitch

axis segment component. According to some embodiments, the units of the determined segment values and/or segment components are in units of degrees ranging from -180 degrees to +180 degrees.

At block **1012** the median values of each segment are pairwise compared. Illustratively, by way of non-limiting example, a time window that is segmented into three sections would have three pairwise comparisons: the first segment value compared to the second segment value, the first segment value compared to the third segment value, and the second segment value compared to the third segment value.

At block **1014**, each pairwise comparison is analyzed to determine whether an orientation change event occurred. The determination is made by comparing the magnitude of the difference of each pairwise comparison with a predetermined threshold value. If the magnitude of the difference of a pairwise comparison exceeds the threshold, then an orientation change event is considered to have occurred. If the magnitude of the difference of a pairwise comparison does not exceed the threshold, then no change in orientation is considered to have occurred. Thus, a change that exceeds a certain threshold in the roll dimension corresponds to an orientation change event that includes a rotation about the longitudinal axis of the patient's body. Similarly, a change that exceeds a certain threshold in the pitch dimension corresponds to an orientation change event that includes a transition from sitting up to lying down, or vice versa. A change that exceeds a certain threshold in both the roll and pitch dimensions corresponds to an orientation change event that includes a rotation about the longitudinal axis of the patient's body and a transition from sitting up to lying down, or vice versa. According to an embodiment, the threshold is 45 degrees and thus, if the magnitude of difference between any two segment values is greater than 45 degrees, then an orientation change event is determined to have occurred. In another embodiment, an additional comparison is made between consecutive one-second segments of data to determine whether a change of at least 30 degrees has occurred. This is to prevent repeated posture changes, when for instance, the patient is in a posture near 135 degrees, that is, right in the middle between two postures.

If an orientation change event is determined to have occurred, then at block **1016**, the detected event is classified. Reference is made to a look-up table of events which includes a set of profiles of orientation change actions or activities. In an embodiment, each profile includes four data points: a "before" and an "after" measurement for the roll axis, and a "before" and an "after" measurement for the pitch axis. For example, as illustrated in FIG. 11A, the profile of the orientation event activity of turning from lying on the back to lying on the right side can be as follows:

TABLE 1

Roll Before	Roll After	Pitch Before	Pitch After
180 degrees	90 degrees	0 degrees	0 degrees

As illustrated in Table 1, the roll axis changes from 180 degrees to 90 degrees indicating that the patient rotated from lying on his back to lying on his right side. The pitch axis does not change because the patient remains in a reclining orientation. The table of events is developed and updated off-line and is based on the analysis of empirical data of known orientation change events. Accordingly, classifica-

tion of orientation change events can be performed by identifying in the look-up table of events the orientation event profile that matches the data of the pairwise comparison when the magnitude of the difference of the pairwise comparison exceeds the predetermined threshold.

At block **1018**, a vote is placed for the classified event. Illustratively, for the example described with respect to Table 1, the vote would be for the orientation change event profile of turning from lying on the back to lying on the right side. At block **1020**, the method **1000** repeats the acts of determining whether an orientation change event occurred, classifying the orientation change event (if an event occurred), and voting for the classified orientation change event (again, if an event occurred), for each pairwise comparison. The maximum number of iterations for these blocks will be equal to the number of segments in the time window.

Once all of the pairwise comparisons have been analyzed, at block **1022**, the method **1000** tallies the votes recorded at block **1018**. The orientation change event that has the most votes is determined to be the orientation change event that occurred. The determined orientation change event is then reported as the orientation of the patient. At block **1024**, an orientation duration timer is reset to keep track of the time the patient remains in the new orientation. The method **1000** then returns to block **1002** to begin the analysis again with respect to the next incremental (e.g., second) of measurement data.

If at block **1014**, none of the pairwise comparisons result in a detected orientation change event (i.e., the patient has remained in the same orientation throughout the entire time window) then the method **1000** progresses to block **1026** to determine whether the patient has remained in the present orientation for a period of time greater than a predefined maximum duration, which may also be referred to herein as a predetermined duration or a predetermined maximum duration. If not, the method **1000** returns to block **1002** to begin the analysis again with respect to the next incremental set (e.g., second) of measurement data. If the patient has remained in the present orientation for a period of time greater than the predefined maximum duration, then at block **1028**, an alert is sent to, for example, the patient's caregiver, to notify the caregiver that the patient should be repositioned. The method **1000** then returns to block **1002** to begin the analysis again with respect to the next incremental (e.g., second) of measurement data.

FIG. **11B** is an exemplary plot of an embodiment of a patient position monitoring paradigm for determining when a patient's orientation needs to be changed, according to an embodiment of the present disclosure. In an embodiment, the plot **1102B** may be part of a display to a caregiver on a bedside monitor, a multi-room monitor, both, or the like. The plot can be updated in real time, at predefined intervals, and/or manually. In other embodiments, the paradigm may be illustrative of the signal processing performed by a signal processor to determine when to activate an alarm informing a caregiver of the potential of a pressure ulcer if a patient is not repositioned. In these embodiments, each portion of the paradigm may be customized to a particular patient, patient demographics, hospital protocol, unit protocol such as, for example, a protocol specific to a surgical IOU or other hospital unit, home care, or the like.

In the illustrated embodiment, a patient's position is monitored over time. A vertical axis **1105B** represents time and a horizontal axis **1107B** represents a patient movement event, such as, for example, In the illustrated embodiment, an alarm is set to alert a caregiver when a patient has been in a certain position for 3 hours or more. The illustrated

embodiment is a non-limiting example, as the alarm can be set to alert the caregiver at 1 hour, 2 hours, 3 hours, 4 hours, 5 hours, 6 hours, 7 hours, 8 hours, 9 hours, and/or 10 or more hours. The alarm can include a noise, color, and/or other indicator that will alert the caregiver. In some embodiments, the alarm can indicate to the caregiver that the patient has remained in the same position for a threshold amount of time (e.g., 3 hours). The threshold amount of time can be predefined or adjusted over time. In some embodiments, the alarm indicates to the caregiver that the patient has fallen, moved into an incorrect position, left the bed and/or the like. In an embodiment, empirical data about a particular patient, or a group of like patients, can be used to customized some or all of the parameters for the alarm discussed herein.

As shown in FIG. **11B**, the monitor begins monitoring a patient as the patient is in Position **1** (e.g., the patient is lying on their back, side, front, sitting slightly up, sitting mostly up, or the like). As the patient remains in Position **1**, a timing mechanism starts and a line **1101B** as its growth line. The slope of the line **1101B** depicts a growth rate as the patient remains in the same position. As shown in the illustrated embodiment, the growth rate can be depicted linearly. In some embodiments, the growth rate can be linear, non-linear, exponential, and/or the like. In some embodiments, the growth rate is predefined. In some embodiments, the growth rate can change in real time and/or adjust to various physiological parameters and/or empirical data, as described below. The growth rate can depend on a number of factors and empirical data already known and/or determined by the system, depending on for example, how the patient's skin reacts to remaining in a single position, how fast negative effects experienced by the patient (e.g., pressure sores) form or heal, the particular position the patient is lying in, and/or demographic information about the patient, including the patient's age, health, blood perfusion rates, hydration, and/or nutrition, among others. Accordingly, in some embodiments, the growth rate can indicate a growth rate of the effects (e.g. bed sores) as the patient remains in the same position (e.g., Position **1**) over a period of time.

As illustrated in FIG. **11B**, the patient remains in Position **1** for approximately 2 hours. At that time, the patient turns and/or is turned by a caregiver to Position **2**. In the illustrated embodiment, Position **2** is a different position from Position **1**. When the patient turns and/or is turned, the timing mechanism can restart a new line **1102B** and begin to measure, track, monitor, and/or calculate the amount of time the patient remains in Position **2**.

At the same time, line **1101B** transforms into its decay line. The decay line of line **1101B** can comprise data relating to a decay rate of a bed sore, potential bed sore, particular area of a patient's skin, and/or the amount of time the patient or a group of like patients, or all patients, takes to recover from remaining in a particular position (e.g., Position **1**), among other things. Similar to the growth rate, the decay rate can be linear, non-linear, and/or exponential, among others. In some embodiments, the decay rate is predefined. In some embodiments, the decay rate can change in real time and/or adjust to various physiological parameters and/or empirical data, as described below. The decay rate may depend on a number of factors and empirical data, depending on for example, how the patient's skin reacts to remaining in a single position, how fast negative effects experienced by the patient (e.g., pressure sores) heal, how quickly the patient recovers, the particular position the patient is lying in, and/or demographic information about the patient, including the patient's age, health, blood perfusion rates, hydration, and/or nutrition, among others. As shown in the illustrated embodi-

ment, when the patient is in one or more positions that are not Position 1, the decay line of Position 1 continues to decay at the decay rate. That is, in an embodiment, the decay line of Position 1 will continue to decay at its decay rate through one or multiple other positions until it approaches zero so long as that other one or multiple positions do not include Position 1. In this example, the decay rate, or recovery rate for example, approaches zero more quickly the longer the patient remains not in Position 1.

In the illustrated embodiment, the patient turns and/or is turned again at Turn 2. Turn 2 occurs at a time before the threshold amount of time is reached, and therefore, before the alarm alerts the caregiver to turn the patient. At Turn 2, the patient turns/is turned to Position 3. In some examples, Position 3 is the same as Position 1. In such embodiments, because the decay line of line 1101B associated with the previous Position 1 has reached zero, a line 1104B starts at zero as its growth line for Position 3/1. However in some examples, Position 3 is a different position from Position 1. In the illustrated example, Position 3 is different from Position 1 and its growth rate for line 1104B is different from that of Position 1. In some examples, the decay line of Position 1 can continue to decay as the decay line of Position 2 continues to decay when the patient turns and/or is turned to Position 3 as long as Position 3 is different from Positions 1 and 2. In this example, the patient can continue to heal as a result of the effects of remaining in both Positions 1 and 2. In some examples, Position 1 continues to decay as the patient turned and/or is turned to multiple positions, such as a second, third, fourth, and/or fifth or more positions.

As shown in the illustrated embodiment, the patient remains in Position 3 for a relatively short period of time. During that time, any effects of remaining in Position 2 begin to decay. Thereafter, however the patient turns and/or is turned back to Position 2. Advantageously, rather than restarting at time zero, the system can determine that the patient has turned back to Position 2 and the timing mechanism begins timing from the current value of the decay line of Line 1102B, which corresponds to point or time 1103B. Time 1103B is greater than zero in this example, but less than the threshold amount of time. Additionally, in this example, the time 1103B is less than the amount of time the patient originally remained in Position 2. In some embodiments time 1103B can be equal to the time the patient turned from Position 2. However, in the illustrated embodiment, the system can take into account the decay rate and the time the patient has spent recovering from remaining in Position 2. Thus, in the illustrated embodiment, Time 1103B can be determined by the system through a number of methods. For example, the system can subtract the recovery time from the growth time, and/or count down from the time of the turn (e.g., Turn 2), among other methods. Advantageously, the preferred embodiment of the system can ensure the patient does not exceed the threshold total time, taking into account the growth and decay rate, a patient spends in a particular location. Although in an embodiment, the system restarts the timer at each turn, without accounting for the previous time the patient spent at a particular position, such embodiments may not be as precise in allowing adequately recovery of tissue, blood pooling, or the like caused by the previous position, and therefore, a patient may be more likely to experience negative effects (e.g., bed sores). Accordingly, the preferred embodiment of the system can more precisely reduce a likelihood of a patient developing harmful effects, such as bed sores by ensuring a patient would not remain in a particular position for too long. Once the total time spent in a position, taking into account the patient's growth and

decay rates, reaches the threshold time (e.g. 3 hours in this example), an alarm can alert the caregiver.

In some embodiments, the alarm will alert the caregiver until the patient turns and/or is turned again, for example as illustrated by Turn 4 in FIG. 11B. In some embodiments, the growth line will continue to grow, thus requiring longer for the line to decay, when a patient has not been turned within the threshold time. Such continued growth ensures that a patient will not be too soon returned to a position where the patient spent too much time and can help ensure that the corresponding tissue has sufficient time to recover from a particular patient position. In an embodiment, the decay rate of the line is adjusted to account for exceed the threshold limit. As shown in the illustrated embodiment, the decay rate is reduced after exceed a threshold, meaning it will take longer for the line corresponding to the alarmed position to reach zero.

As discussed, in an embodiment, when the patient turns and/or is turned after the time of the alarm, the growth line will exceed the threshold time, as indicated by the plot of FIG. 11B. Once the patient turns and/or is turned, the decay line can be shown above the threshold (e.g. alarm) line. In some examples, the patient may take longer to recover when the time spent in a particular position exceeds the threshold time. In some examples, the alarm can alert the caregiver that the decay line has reached the threshold time as the line continues to decay towards zero and the patient remains in a different position. In some embodiments, the alarm does not alert the caregiver that the decay line has passed the threshold time.

According to certain embodiments of the present disclosure, the patient monitor 106 determines the mobility status of the patient, e.g., whether the patient is ambulatory, standing, sitting, reclining, or falling. The wireless monitoring system 100 can include an alert system to alert the caregiver that the patient is falling, getting out of bed, or otherwise moving in a prohibited manner or in a manner that requires caregiver attention. The alert can be an audible and/or visual alarm on the monitoring system or transmitted to a caregiver (e.g., nurses' station system 113, clinician device 114, pager, cell phone, computer, or otherwise). Illustratively, the patient monitor 106 can display the patient's mobility status and transmit a notification that the patient is active and away from the bed. In some circumstances, the patient monitor 106 can determine whether the patient contravenes a clinician's order, such as, for example, instructions to remain in bed, or to walk to the bathroom only with the assistance of an attendant. In such circumstances, a notification, alert, or alarm can be transmitted to the appropriate caregivers.

In certain aspects, the information received from the wireless sensor 102 can be used to create a time-sequenced representation of the patient's movement. This representation can be displayed on the patient monitor or transmitted to a nurses' station or other processing node to enable the caregiver to monitor the patient. The time-sequenced representation can be viewed in real time and/or be recorded for playback. For example, if an alarm alerts the caregiver that the patient has fallen, the caregiver can access and review the historical sequence of the patient's movements prior to and during that period of time.

In some embodiments, the patient monitoring system 100 can predict a patient's risk of falling based on analysis of the patient's movement (e.g., gait) and other information (such as, for example, the patient's current medication regimen). When the patient monitor 106 determines that the patient's risk of falling is above a predetermined threshold, the patient

monitor **106** can issue an alarm or alert to notify care providers of the identified risk in an effort to anticipate and therefore prevent a patient fall. Additionally, the patient monitor **106** can determine when a patient has fallen and issue the appropriate alarms and alerts to summon care provider assistance.

FIG. **12** illustrates a method **1200** of determining whether a patient has fallen according to an embodiment of the present disclosure. The method **1200** uses, among other things, information sensed by the accelerometer **210** and by the gyroscope **212** of the wireless sensor **102** to determine whether the patient has fallen. The method **1200** can be performed by the wireless sensor **102**, using its processor **202** and storage device **204**, or it can be performed by an external processing device that receives the sensed information from the wireless sensor **102**, such as, for example, the patient monitor **106**.

According to an embodiment of the present disclosure, measurements from the accelerometer **210** and the gyroscope **212** of the wireless sensor **102** are used, among other things, to determine whether the patient has fallen. As discussed above, the accelerometer **210** measures linear acceleration of the patient with respect to gravity in three axes. The three axes of the accelerometer **210** are represented in fixed, inertial references. The roll axis corresponds to the longitudinal axis of the patient's body. Accordingly, the roll reference measurement is used to determine whether the patient is in the prone position (i.e., face down), the supine position (i.e., face up), or on a side. The pitch axis corresponds to the locations about the patient's hip. Thus, the pitch measurement is used to determine whether the patient is upright or lying down. Advantageously, the pitch axis provided by the accelerometer **210** can be a useful source of information in determining whether a patient has fallen because it can indicate a change in the patient's orientation from standing to lying, a frequently-seen scenario when a patient falls. The yaw axis corresponds to the horizontal plane in which the patient is located.

The gyroscope **212** provides outputs responsive to sensed angular velocity of the wireless sensor **102**, as positioned on the patient, in three orthogonal axes corresponding to measurements of pitch, yaw, and roll. In contrast to the fixed, inertial reference frame relative to gravity of the accelerometer **210**, the frame of reference provided by the gyroscope is relative to the patient's body, which moves.

At block **1202**, the method **1200** begins in which acceleration measurement data and angular velocity data are received from the wireless sensor **102** by a device capable of processing the measurement data, such as, for example, the patient monitor **106**. Other devices capable of processing the measurement data include, without limitation, clinician devices **114**, nurses' station systems **113**, the multi-patient monitoring system **110**, or the like. For ease of illustration, the description herein will describe the processing device as the patient monitor **106**. A skilled artisan will appreciate that a large number of devices may be used to perform the described method **1200** without departing from the scope of the present disclosure.

At block **1204**, the received data are normalized, which may also be referred to as "scaling," to adjust values measured on different scales to a common scale, prior to further processing. According to an embodiment, training data are used to normalize the received data. The training data can include empirical data of multiple fall scenarios as well as non-fall scenarios that can be challenging to discriminate from fall scenarios. The training data are collected and analyzed to serve as the basis for establishing a weight

vector (discussed below with respect to block **1208**) used to determine whether a patient has fallen. The training data can include multiple falling and non-falling scenarios, performed multiple times, by multiple subjects. Illustratively, by way of non-limiting example, the training data can include the fall and non-fall scenarios described in Table 2.

TABLE 2

Fall and Non-Fall Scenarios	
Fall forward from vertical, ending in left/right lateral position	
Fall forward from vertical, ending in prone position	
Fall backward, from vertical, ending in left/right lateral position	
Fall backward from vertical, ending in supine position	
Fall to left/right from vertical, ending in left/right lateral position	
Fall to left/right from vertical, ending in prone position	
Fall to left/right from vertical falling, ending in supine position	
Collapse from vertical, ending in left/right lateral position	
Collapse from vertical, ending in prone position	
Collapse from vertical, ending in supine position	
Fall from vertical onto knees	
Fall from vertical to the left/right against a wall, sliding down	
Take a step down repeatedly from a podium with left foot first	
Take a step down repeatedly from a podium with right foot first	
In bed: roll onto left/right side, falling out of bed	
Sit down from vertical into a chair	
Jump off mattress repeatedly	
Stand quietly	
Stumble vigorously and fall onto mattress	

As with the received data, each sample of the training data includes six dimensions of information, corresponding to the three axes of accelerometer **210** data, and the three axes of gyroscope **212** data. Normalizing the received data standardizes the range of the variables of the received data. Since the range of values of raw data can vary widely, analytical algorithms may not work properly without normalization. For example, many classifiers calculate the distance between two points. If one of the independent variables has a broad range of values, the distance will be governed by this particular variable. Therefore, the range of all variables can be normalized so that each feature contributes approximately proportionately to the final distance. Normalization causes the values of each variable in the data to have zero-mean (when subtracting the mean in the numerator) and unit-variance. This can be performed by calculating standard scores. The general method of calculation is to determine the distribution mean and standard deviation for each variable of the entire set of training data. Next each determined mean is subtracted from the corresponding variable of the received data. Then the new value of each variable (having the mean already subtracted) is divided by the determined standard deviation. The result is a normalized set of values that can be further processed by the method **1200**.

At block **1206**, the normalized set of values is processed to determine features that are useful in determining whether a patient is falling. According to an embodiment, the method determines the following five features: the magnitude of the acceleration data (provided by the accelerometer **210**), the magnitude of the angular velocity data (provided by the gyroscope **212**), the magnitude of the jerk (i.e., the rate of change of acceleration); the fall duration which is used to

characterize a fall starting point and a fall impact point, and the change in pitch between two consecutively received data points. Other features can be used in determining whether a patient is falling such as, by way of non-limiting example, vertical velocities.

The magnitude of the received acceleration data is determined by calculating the Euclidian norm of the three-dimensional vector made up of the measurements from the accelerometer's **210** three axes. As is well understood by an artisan, this corresponds to the square root of the sum of the squares of the three accelerometer values, pitch, roll and yaw. Similarly, the magnitude of the angular velocity data is determined by calculating the Euclidian norm of the three-dimensional vector made up of the measurements from the gyroscope's **212** three axes. The magnitude of the jerk, which can also be referred to as "jolt," "surge," or "lurch," is calculated by taking the derivative of the acceleration vector, and then calculating the Euclidean norm of the derivative.

The fall duration, which is a scalar value, is determined by evaluating the acceleration magnitude profile of the patient's motion over a short duration of time. In particular, as the fall begins, acceleration of the patient relative to gravity decreases because the patient is falling. (A patient that is not falling would register an acceleration value in the up and down dimension equal to the force of gravity (i.e., 1 g or approximately 9.80665 m/s²). Thus, if the magnitude of the acceleration is below a first threshold, then it is considered to be a starting point of a fall, and the value of the fall duration is incremented by 1. If the magnitude of the acceleration is above the first threshold, then the value of the fall duration is decremented by 1. In an embodiment, the first threshold is 0.6 g (or approximately 5.88399 m/s²). A second threshold is used to determine the impact point of the fall. In an embodiment, the second threshold is 0.8 g (or approximately 7.84532 m/s²). If the magnitude of the acceleration is below the second threshold, then it is considered to be an impact point of the fall, and the value of the fall duration is incremented by 1. If the magnitude of the acceleration is above the second threshold, then the value of the fall duration is decremented by 1.

The pitch change feature is the result of a comparison of the present pitch orientation (as determined by the accelerometer **210** data) with the pitch orientation determined one second earlier. As discussed above, the pitch dimension of the accelerometer data is useful in detecting a fall because it distinguishes between the patient being in an upright position (e.g., standing up or sitting up) and reclining. Thus a change in pitch from being upright to reclining can indicate that a fall has occurred. The output of block **1206** is a five-dimensional feature vector made up of the five determined features.

At block **1208**, a weight vector of values is applied to the determined features. According to certain embodiments, the inner product of the received five-dimensional feature vector and a weight vector is calculated. In certain embodiments, the weight vector is derived using a machine learning algorithm. Machine learning is a sub-field of computer science based on the study of pattern recognition and computational learning theory in artificial intelligence. It includes the development of algorithms that can learn from and make predictions on data. Algorithms developed through machine learning operate by building a model from example inputs in order to make data-driven predictions or decisions, rather than following strictly static program instructions. Machine learning is employed in a range of computing tasks where use of explicit computer programs is

infeasible. When employed in industrial contexts, machine learning methods may be referred to as predictive analytics or predictive modelling. As applied in the present disclosure, the machine learning system includes supervised learning, where the machine learning algorithm is presented with training data that include example inputs and their known outputs, given by a "teacher", and the goal is to learn a general rule that maps the inputs to the outputs. In an embodiment, Fisher's linear discriminant is employed to derive the weight vector. Fisher's linear discriminant is a method used to find a linear combination of features that characterizes or separates two or more classes of objects or events. The resulting combination may be used as a linear classifier or for dimensionality reduction before later classification. Other methods of machine learning that can be used with the present disclosure include, without limitation, linear discriminant analysis, analysis of variance, regression analysis, logistic regression, and probit regression, to name a few. A skilled artisan will recognize that many other machine learning algorithms can be used to determine the weight vector without departing from the scope of the present disclosure.

The training data, described above, include empirical data collected from multiple fall and non-fall scenarios which can be used to identify the predictive indicators of patient falls. Illustratively, for each training scenario, the five features described above with respect to block **1206** are determined and provided as input to the machine learning system. Additionally, an output is provided for each training scenario that identifies whether the scenario describes a falling event or a non-falling event. The machine learning system analyzes the training data to derive a rule that maps the inputs to the outputs. According to certain embodiments of the present disclosure, the output of the machine learning system is five-dimensional weight vector that weights each of the five features according to their relative value in determining whether or not a fall has occurred. The weight vector is determined off-line and is provided as a fixed, five-dimensional vector to the method **1200**. Of course, the weight vector can be updated, based on analysis of additional empirical data.

The inner product (also referred to as the "dot product" and the "scalar product") of the received five-dimensional feature vector and the weight vector is calculated in a manner well understood by skilled artisans. The inner product yields a scalar value, also referred to herein as an activation value, that may be either positive or negative. At block **1210**, the method **1200** determines whether a fall has been detected. According to some embodiments, the sign of the inner product of the received five-dimensional feature vector and the weight vector indicates whether a fall has occurred. If the inner product is less than zero, then no fall has been detected, and the method returns to block **1202** to begin analyzing the next set of data from the wireless sensor **102**. If the inner product is greater than zero, then a fall has been detected and the method **1200** progresses to block **1214**, where a notification, alarm, and/or alert indicating that the patient has fallen is transmitted to, for example, clinician devices **114**, nurses' station systems **113**, multi-patient monitoring system **110**, and the like. The method returns to block **1202** to begin analyzing the next set of data from the wireless sensor **102**.

In some embodiments, the system can determine a spatial location of the patient within the patient's room. The system can monitor the room and spatially monitor and/or calculate how long the patient has been in a position, when the patient was in the position, and/or how long the patient was in the

position, among other parameters. As discussed above, the system uses, among other things, information sensed by the accelerometer **210** and by the gyroscope **212** of the wireless sensor **102** to track the patient. This method can be performed by the wireless sensor **102**, using its processor **202** and storage device **204**, or it can be performed by an external processing device that receives the sensed information from the wireless sensor **102**, such as, for example, the patient monitor **106**.

In some embodiments, the system can determine the position of the patient within the patient's room, relative to certain features of the patient's room, such as the patient's bed, a bathroom, a monitor, a doorway, and/or a window, among other room feature. In particular, using methods described herein, the system can determine a patient's vertical position, vertical displacement, horizontal position, horizontal displacement, angular position and/or angular displacement in the patient's room. For example, the accelerometer **210** and/or the gyroscope **212** can monitor the patient's movements as the patient walks throughout the patient's room. The system can determine whether the patient is falling, getting out of bed, or otherwise moving in a prohibited manner or in a manner that requires caregiver attention.

According to some embodiments, measurements from the accelerometer **210** and the gyroscope **212** of the wireless sensor **102** are used, among other things, to determine whether the patient is bending down and/or has fallen and/or where the patient has fallen (for example, by measuring the vertical displacement of the patient and/or the height of the patient relative to the floor). In some embodiments in which the patient has fallen, the clinician can determine the location of the fall according to an embodiment of the present disclosure. As discussed above, the accelerometer **210** measures linear acceleration of the patient with respect to gravity in three axes. The three axes of the accelerometer **210** are represented in fixed, inertial references. The gyroscope **212** provides outputs responsive to sensed angular velocity of the wireless sensor **102**, as positioned on the patient, in three orthogonal axes corresponding to measurements of pitch, yaw, and roll. Based on these measurements, the system can determine whether the patient has fallen according to methods described herein.

In such configurations, the system can record the position of the patient. In certain aspects, the information received from the wireless sensor **102** can be used to create a time-sequenced representation of the patient's movement. This representation can be displayed on the display **120** or transmitted to a nurses' station or other processing node to enable the caregiver to monitor the patient. The time-sequenced representation can be viewed in real time and/or be recorded for playback. For example, if an alarm alerts the caregiver that the patient has fallen, the caregiver can access and review the historical sequence of the patient's movements prior to and during that period of time.

FIGS. **15A-H** illustrate various configurations of a room display displayed on the patient display monitor. As illustrated in FIGS. **15A-H**, the caregiver and/or patient can select any number of room items and/or configurations of the room items. The caregiver can select a room item, and place it within the room on the room display. The caregiver can rotate and/or place the room item in any configuration. In an embodiment, the caregiver could select the location of a major element of a room at a time. For example, the caregiver could select a position of the bed, then a position of the bathroom, then a position of the door, equipment, tables, chairs, couches, etc. In other embodiments, various

room layout approximation are some to fully presented in selection screens and the determination of layout is made in one or just a few caregiver selections.

FIG. **16** illustrates an example method **1600** for detecting and/or predicting a patient's fall, determining a particular location of a patient within a patient's room, and/or determining whether the patient has moved outside of a prescribed movement of the patient, among others, for example.

At block **1602**, the caregiver can enter a room configuration. For example, the caregiver can select any number of room items to be displayed in any number of configurations within a patient room display. The room items can include a patient's bed, a bathroom, a monitor, a doorway, and/or a window, among other room items. The caregiver can select a room item by selecting, dragging, and/or dropping each room item around the room display. In some embodiments, the caregiver can select a certain size for each room item. In some embodiments, the caregiver can simply select a room item and select the location within the room display for the room item to be oriented and displayed. In some embodiments, the room item can be snapped into place in the room display.

At block **1604**, the caregiver can optionally enter a movement prescription. For example, the caregiver can enter instructions to the patient, including instructions to remain in bed, and/or to walk to the bathroom only with the assistance of an attendant.

At block **1608**, one or more of the sensors described herein can be activated. In some examples, the caregiver manually activates the one or more sensors. In some examples, the system activates the one or more sensors automatically to begin tracking, monitoring, measuring, and/or calculating certain physiological parameters, according to methods described herein.

At block **1610**, the patient monitoring system **100** can predict and/or detect a patient's fall and/or risk of falling based on analysis of the patient's movement (e.g., gait) and other information (such as, for example, the patient's current medication regimen). At block **1612**, when the patient monitor **106** determines that the patient's risk of falling is above a predetermined threshold, the patient monitor **106** can issue an alarm or alert to notify care providers of the identified risk in an effort to anticipate and therefore prevent a patient fall. Additionally, the patient monitor **106** can determine when a patient has fallen and issue the appropriate alarms and alerts to summon care provider assistance. The alert system can alert the caregiver that the patient is falling, getting out of bed, or otherwise moving in a prohibited manner or in a manner that requires caregiver attention. The alert can be an audible and/or visual alarm on the monitoring system or transmitted to a caregiver (e.g., nurses' station system **113**, clinician device **114**, pager, cell phone, computer, or otherwise).

If the patient monitoring system has not detected a patient's fall, the patient monitoring system **100** can optionally determine whether the patient has moved outside of the movement prescription. For example, as described above, the patient monitor **106** can determine the mobility status of the patient, e.g., whether the patient is ambulatory, standing, sitting, reclining, or falling.

If the patient monitoring system **100** determines that the patient has contravened a caregiver's order, such as, for example, instructions to remain in bed, or to walk to the bathroom only with the assistance of an attendant, a notification, alert, or alarm can be transmitted to the appropriate caregivers at block **1612**.

If the patient monitoring system **100** determines that the patient has not contravened a caregiver's order, the system will return to block **1610** to detect and/or predict whether the patient has fallen.

FIGS. **13A-F** illustrate embodiments of icon displays reflecting a patient's position according to an embodiment of the present disclosure. According to some embodiments, the graphical icons are used to visually depict the detected orientation of the patient. In particular, the icons of FIGS. **13A-F** show, in stick figure-type format, the patient sitting, standing, and lying in the supine position (on the back), the prone position (on the belly), on the left side, and on the right side, respectively.

FIG. **14** illustrates an example of how the icons described with respect to FIGS. **13A-F** can be presented on the display **120** of the patient monitor **106**. Toward the bottom of the main display **120** are a set of 3 icons **1402**, **1404**, and **1406** indicating the patient's position. The left-most icon **1404** shows the patient lying on his right side. The two icons to the right of the left-most icon **1404** and **1406** show the patient lying on his back. According to certain embodiments, the display **120** of the patient monitor **106** can include a touchscreen interface. The touchscreen interface can enable finger controls, including a touch gesture, a touch and move gesture, and a flick gesture. Illustratively, a clinician may use the touch gesture on an icon **1406** to expand the icon in the display **120** to include additional information associated with that icon **1406**. For example, additional information associated with the "touched" icon **1406** can include, the time at which the patient assumed the particular orientation, the time (if available) at which the patient moved from the orientation, the total duration of time the patient spent in the particular orientation, the number of discrete times that the patient has been in the particular orientation over a defined period (such as 24 hours), the total duration of time that the patient has been in the particular orientation over a defined period (such as 24 hours), and the like. The clinician may also use the flick finger gesture to scroll right and left, corresponding to moving forward and backward in time, to access the historical positional record of the patient.

The service life of the wireless sensor **102** disclosed herein can vary depending on, among other things, battery size, and data transmission characteristics such as data rate, frequency of transmission, and quantity of data transmitted. According to one embodiment, the wireless sensor **102** is configured to operate continuously or near continuously (e.g., waking up every second or so to sense and transmit the patient's physiological data) for approximately two days, after which the wireless sensor **102** is to be disposed of properly. Other embodiments of the wireless sensor **102**, equipped with a larger battery, for example, are configured to operate for longer periods of time before disposal. Some embodiments can be configured for sterilization and reuse.

Certain medical device manufacturers implement quality control measures for disposable medical devices, such as embodiments of the disclosed wireless sensor **102**, to carefully control and manage the performance characteristics of their disposable devices. In particular, there is a risk that used and disposed-of wireless sensors **102** can be salvaged and refurbished or retrofitted for additional use beyond the defined and intended service life of the wireless sensor **102**. Features can be included in the disclosed patient monitoring system **100** to help prevent improper use of the wireless sensor **102** beyond its defined service life.

According to one embodiment of the patient monitoring system **100**, the wireless sensor **102** is configured to set an activation flag in the storage device **204** of the wireless

sensor **102** upon initial activation, indicating that the wireless sensor **102** has been activated for use. In some embodiments, the activation flag is set in an information element **215** which is provided to store information about the usage of the wireless sensor **102** to help maintain quality control. Advantageously, the activation flag is set in nonvolatile memory of the storage device **204**, or in the information element **215**, so that disconnection from the battery **214** will not disrupt or erase the set activation flag. Thus, if the wireless sensor **102** is reconditioned such that it may be activated a second time, the activation flag will indicate, through a standard sensor **102** start-up routine, that the sensor **102** has been previously activated. Upon detection of the activation flag, the wireless sensor **102** can transmit a prior activation message and/or alert which can serve as a warning notification that the quality of the sensor **102** may be compromised. The transmitted warning or alert can be received by, for example, a patient monitor **106** which can then provide a menu of actions that the user may take in response to the transmitted quality warning or alert. The menu of actions can include the option to shut down the wireless sensor **102**. In certain situations it may be desirable to continue to use the wireless sensor **102**. Illustratively, it is possible that the battery **214** connection to the wireless sensor **102** is established and then unintentionally disconnected. For example, a battery isolator **322** may be initially removed from the sensor **102** but then re-inserted so as to once again isolate the battery **214** from the electronic circuitry of the wireless sensor **102**. Removing the battery isolator **322** a second time will result in transmission of a quality warning or alert as described above. In such a situation the user, being aware of the circumstances that led to the quality warning, may choose to continue to use the wireless sensor **102**.

According to another embodiment, the wireless sensor **102** is configured to set a prolonged service flag, after the wireless sensor has been in an activated state for a pre-defined period of time, such as, for example, four hours. The prolonged service flag can serve to indicate upon start-up that the sensor **102** has previously been active for a prolonged duration of time. In another embodiment, the wireless sensor **102** tracks and records on the storage device **204** the duration of time that the sensor **102** has been active. Advantageously, the sensor **102** can issue notifications and/or alerts to the user that the sensor **102** is nearing the end of service life, providing the user an opportunity to take steps to replace the wireless sensor **102** before it ceases to operate. Additionally, the recorded duration of time that the sensor **102** has been active can serve to detect when a sensor **102** has been refurbished to operate beyond its intended service life. The appropriate warning can then be transmitted to the user. According to some embodiments, once the wireless sensor has been active for a period of time equal to a maximum service life duration, the sensor **102** sets a flag in the storage device **204**, or otherwise configures itself to prohibit the sensor **102** from operating further.

In other embodiments, the wireless sensor **102** transmits to the patient monitor **106** a unique identifier such as, for example, a product serial number that is encoded in one of the hardware components of the wireless sensor **102**. Once the wireless sensor **102** is paired with a patient monitor or with an expander/repeater **107** and is operational, the patient monitor **106** or the expander/repeater **107** can transmit the sensor's **102** unique identifier to a central repository that lists the unique identifiers of sensors **102** known to have been operational. Illustratively, during the pairing operation, the patient monitor **106** or the expander/repeater **107** can

check the central repository to determine whether the wireless sensor **102** that is attempting to pair has been listed on in the central repository, thereby indicating that the wireless sensor **102** might have quality issues.

In other various embodiments, the wireless sensor **102** includes a sensor information element **215**, which can be provided through an active circuit such as a transistor network, memory chip, EEPROM (electronically erasable programmable read-only memory), EPROM (erasable programmable read-only memory), or other identification device, such as multi-contact single wire memory devices or other devices, such as those commercially available from Dallas Semiconductor or the like. The sensor information element **215** may advantageously store some or all of a wide variety of information, including, for example, sensor type designation, sensor configuration, patient information, sensor characteristics, software such as scripts or executable code, algorithm upgrade information, software or firmware version information, or many other types of data. In a preferred embodiment, the sensor information element **215** may also store useful life data indicating whether some or all of the sensor components have expired.

Many other variations than those described herein will be apparent from this disclosure. For example, depending on the embodiment, certain acts, events, or functions of any of the algorithms described herein can be performed in a different sequence, can be added, merged, or left out altogether (e.g., not all described acts or events are necessary for the practice of the algorithms). Moreover, in certain embodiments, acts or events can be performed concurrently, e.g., through multi-threaded processing, interrupt processing, or multiple processors or processor cores or on other parallel architectures, rather than sequentially. In addition, different tasks or processes can be performed by different machines and/or computing systems that can function together.

The various illustrative logical blocks, modules, and algorithm steps described in connection with the embodiments disclosed herein can be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. The described functionality can be implemented in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the disclosure.

The various illustrative logical blocks and modules described in connection with the embodiments disclosed herein can be implemented or performed by a machine, such as a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor can be a microprocessor, but in the alternative, the processor can be a controller, microcontroller, or state machine, combinations of the same, or the like. A processor can include electrical circuitry configured to process computer-executable instructions. In another embodiment, a processor includes an FPGA or other programmable device that performs logic operations without processing computer-executable instructions. A processor can also be implemented as a combination of computing devices, e.g., a

combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. A computing environment can include any type of computer system, including, but not limited to, a computer system based on a microprocessor, a mainframe computer, a digital signal processor, a portable computing device, a device controller, or a computational engine within an appliance, to name a few.

The steps of a method, process, or algorithm described in connection with the embodiments disclosed herein can be embodied directly in hardware, in a software module stored in one or more memory devices and executed by one or more processors, or in a combination of the two. A software module can reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, a removable disk, a CD-ROM, or any other form of non-transitory computer-readable storage medium, media, or physical computer storage known in the art. An example storage medium can be coupled to the processor such that the processor can read information from, and write information to, the storage medium. In the alternative, the storage medium can be integral to the processor. The storage medium can be volatile or nonvolatile. The processor and the storage medium can reside in an ASIC.

Conditional language used herein, such as, among others, “can,” “might,” “may,” “e.g.,” and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or states. Thus, such conditional language is not generally intended to imply that features, elements and/or states are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without author input or prompting, whether these features, elements and/or states are included or are to be performed in any particular embodiment. The terms “comprising,” “including,” “having,” and the like are synonymous and are used inclusively, in an open-ended fashion, and do not exclude additional elements, features, acts, operations, and so forth. Also, the term “or” is used in its inclusive sense (and not in its exclusive sense) so that when used, for example, to connect a list of elements, the term “or” means one, some, or all of the elements in the list. Further, the term “each,” as used herein, in addition to having its ordinary meaning, can mean any subset of a set of elements to which the term “each” is applied.

While the above detailed description has shown, described, and pointed out novel features as applied to various embodiments, it will be understood that various omissions, substitutions, and changes in the form and details of the systems, devices or methods illustrated can be made without departing from the spirit of the disclosure. As will be recognized, certain embodiments described herein can be embodied within a form that does not provide all of the features and benefits set forth herein, as some features can be used or practiced separately from others.

The term “and/or” herein has its broadest, least limiting meaning which is the disclosure includes A alone, B alone, both A and B together, or A or B alternatively, but does not require both A and B or require one of A or one of B. As used herein, the phrase “at least one of” A, B, “and” C should be construed to mean a logical A or B or C, using a non-exclusive logical or.

The apparatuses and methods described herein may be implemented by one or more computer programs executed

47

by one or more processors. The computer programs include processor-executable instructions that are stored on a non-transitory tangible computer readable medium. The computer programs may also include stored data. Non-limiting examples of the non-transitory tangible computer readable medium are nonvolatile memory, magnetic storage, and optical storage.

Although the foregoing disclosure has been described in terms of certain preferred embodiments, other embodiments will be apparent to those of ordinary skill in the art from the disclosure herein. Additionally, other combinations, omissions, substitutions and modifications will be apparent to the skilled artisan in view of the disclosure herein. Accordingly, the present invention is not intended to be limited by the description of the preferred embodiments, but is to be defined by reference to claims.

What is claimed is:

1. A wearable wireless sensor for monitoring a thermal energy of a patient and at least one of pressure ulcer risk, fall detection, or fall risk, said wearable wireless sensor comprising:

a housing including a predetermined position for at least a first sensor and a second sensor;

one or more accelerometers responsive to an acceleration of said patient and configured to output one or more signals indicative of at least one of said pressure ulcer risk, said fall detection, or said fall risk;

a base including a first aperture;

a circuit layer including a first through-hole via extending through said circuit layer; and

a temperature sensor responsive to said thermal energy of said patient, said temperature sensor mounted on said circuit layer, said temperature sensor including a thermal contact in thermal communication with said circuit layer, wherein said temperature sensor is at least one of the first sensor or the second sensor;

wherein said first through-hole via is aligned with said thermal contact of said temperature sensor and with said first aperture of said base, said first through-hole via is configured to provide a structure to transmit said thermal energy across a length of the first through-hole via from said patient to said temperature sensor,

wherein said first aperture and said first through-hole via include a thermally conductive material to cause said temperature sensor to be in thermal communication with a portion of said base corresponding to said first aperture, and

wherein the housing is configured to operably position the base and the circuit layer.

2. The wearable wireless sensor of claim 1, wherein said base insulates a portion of a patient's body surrounding said portion of said base corresponding to said first aperture.

3. The wearable wireless sensor of claim 1, further comprising:

48

a second aperture in said base;

a second through-hole via extending through said circuit layer between said top side and bottom side of said circuit layer;

an electrocardiogram (ECG) sensor mounted on said circuit layer, said ECG sensor responsive to electrical signals, said ECG sensor including an extendible lead with an electrode responsive to said electrical signals, said ECG lead also including an electrical contact in electrical communication with said circuit layer,

wherein said second through-hole via is aligned with said electrical contact of said ECG sensor on said circuit layer and with said second aperture of said base, and wherein said second aperture of said base and said second through-hole via of said circuit layer include an electrically conductive material, said ECG sensor in electrical communication with a portion of said base corresponding to said second aperture through said conductive material.

4. The wearable wireless sensor of claim 1, wherein said one or more accelerometers are mounted on said circuit layer, said one or more accelerometers responsive to acceleration of said patient, said wearable wireless sensor further comprising:

a third aperture in said base; and

an acoustic respiration sensor responsive to vibrational motion of said patient, said acoustic respiration sensor being disposed on said circuit layer and extending through said third aperture in said base, wherein said acoustic respiration sensor is rigidly secured to said circuit layer so as to mechanically transmit sensed vibrational motion to said one or more accelerometers.

5. The wearable wireless sensor of claim 1, further comprising a gyroscope mounted on said circuit layer, said gyroscope responsive to an angular velocity of said patient.

6. The wearable wireless sensor of claim 5, wherein said one or more accelerometers comprises a three-dimensional accelerometer and said gyroscope comprises a three-dimensional gyroscope.

7. The wearable wireless sensor of claim 6, further comprising non-volatile memory configured to store information indicative of whether said wearable wireless sensor has been previously activated.

8. The wearable wireless sensor of claim 1, wherein the second sensor is said one or more accelerometers.

9. The wearable wireless sensor of claim 1, wherein the housing includes a predetermined position for at least a third sensor.

10. The wearable wireless sensor of claim 8, wherein the housing includes a predetermined position for at least a fourth sensor.

11. The wearable wireless sensor of claim 10, wherein the third and fourth sensors include one or more of an acoustic sensor, an electrocardiogram sensor, a respiration sensor, a heart rate sensor, and a blood oxygen sensor.

* * * * *

专利名称(译)	耐用的无线生理传感器		
公开(公告)号	US10226187	公开(公告)日	2019-03-12
申请号	US15/253536	申请日	2016-08-31
[标]申请(专利权)人(译)	梅西莫股份有限公司		
申请(专利权)人(译)	Masimo公司		
当前申请(专利权)人(译)	Masimo公司		
[标]发明人	AL ALI AMMAR FORREST KEVIN		
发明人	AL-ALI, AMMAR FORREST, KEVIN		
IPC分类号	A61B5/02 A61B5/0402 A61B5/01 A61B5/1455 A61B5/053 A61B5/05 A61B5/113 A61B5/00 A61B5/11 A61B5/0408 A61B5/0205 A61B5/08 A61G7/057		
CPC分类号	A61B5/02055 A61B5/0004 A61B5/0015 A61B5/0022 A61B5/01 A61B5/0205 A61B5/0402 A61B5/0408 A61B5/05 A61B5/053 A61B5/113 A61B5/1113 A61B5/1116 A61B5/1117 A61B5/1118 A61B5/1121 A61B5/1126 A61B5/14552 A61B5/447 A61B5/6833 A61B5/7264 A61B5/7275 A61B5/7282 A61B5/742 A61B5/743 A61B5/6801 A61B5/746 A61B5/002 A61G2203/46 A61B5/0816 A61B5/14551 A61B2560/0475 A61B2562/0204 A61B2562/029 A61B2562/0219 A61B2562/0223 A61B2562/0271 A61G7/057 A61G2203/32 A61G2203/36 A61G2203/42 G16H50/30		
优先权	62/212467 2015-08-31 US 62/212472 2015-08-31 US 62/212484 2015-08-31 US 62/212480 2015-08-31 US		
其他公开文献	US20170055851A1		
外部链接	Espacenet		

摘要(译)

本发明公开了一种无线的，患者佩戴的生理传感器，其被配置为帮助管理有可能形成一个或多个压力性溃疡的患者。根据一个实施例，传感器包括具有顶表面和底表面的基部。传感器还包括基板层，基板层包括导电轨道和连接焊盘，顶侧和底侧，其中基板层的底侧设置在基座的顶侧上方。安装在基板层上的是处理器，数据存储设备，无线收发器，加速度计和电池。在使用中，传感器感测患者的运动并且将指示所感测的运动的信息无线地发送到例如患者监视器。患者监测器接收，存储和处理所传输的信息。

