



US009351654B2

(12) **United States Patent**
Albert

(10) **Patent No.:** **US 9,351,654 B2**
(45) **Date of Patent:** **May 31, 2016**

(54) **TWO ELECTRODE APPARATUS AND METHODS FOR TWELVE LEAD ECG**

5/6898 (2013.01); *G06Q 50/22* (2013.01);
A61B 5/0205 (2013.01); *A61B 5/0452*
(2013.01)

(71) Applicant: **ALIVECOR, INC.**, San Francisco, CA (US)

(58) **Field of Classification Search**

CPC *A61B 5/0404*; *A61B 5/0006*
USPC 600/509, 323, 309
See application file for complete search history.

(72) Inventor: **David E. Albert**, Oklahoma City, OK (US)

(73) Assignee: **AliveCor, Inc.**, San Francisco, CA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,717,857 A 2/1973 Evans
3,731,311 A 5/1973 Williams

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 287 days.

(21) Appl. No.: **14/254,310**

FOREIGN PATENT DOCUMENTS

CH 675675 10/1990
CN 101828915 A 9/2010

(Continued)

(22) Filed: **Apr. 16, 2014**

(65) **Prior Publication Data**

US 2014/0228665 A1 Aug. 14, 2014

Related U.S. Application Data

(63) Continuation-in-part of application No. 13/108,738, filed on May 16, 2011, now abandoned, which is a continuation-in-part of application No. 12/796,188, filed on Jun. 8, 2010, now Pat. No. 8,509,882.

(60) Provisional application No. 61/812,655, filed on Apr. 16, 2013.

U.S. Appl. No. 14/217,032, filed Mar. 17, 2014, Albert et al.

(Continued)

(51) **Int. Cl.**
A61B 5/00 (2006.01)
A61B 5/0404 (2006.01)
G06Q 50/22 (2012.01)

(Continued)

Primary Examiner — Nicole F Lavert

Assistant Examiner — Nadia A Mahmood


(74) *Attorney, Agent, or Firm* — Wilson Sonsini Goodrich & Rosati

(52) **U.S. Cl.**
CPC *A61B 5/0404* (2013.01); *A61B 5/0006* (2013.01); *A61B 5/0015* (2013.01); *A61B 5/0022* (2013.01); *A61B 5/044* (2013.01); *A61B 5/0408* (2013.01); *A61B 5/04028* (2013.01); *A61B 5/0432* (2013.01); *A61B*

(57) **ABSTRACT**

Described herein are methods, apparatuses, and systems for heart monitoring of a patient. The heart monitoring system can be used to take an electrocardiogram (ECG) using only two electrodes. A handheld device can be used to sequentially measure the electrical signal between different positions on a patient's body. The electrical signals can be processed and analyzed to prepare an ECG for the patient, including a 12-lead ECG.

36 Claims, 10 Drawing Sheets



- | | | | | | | | |
|------|------------------------------|-----------|--|-----------|---|---------|---------------------|
| (51) | Int. Cl. | | | 5,348,008 | A | 9/1994 | Bornn et al. |
| | <i>A61B 5/0402</i> | (2006.01) | | 5,360,005 | A | 11/1994 | Wilk |
| | <i>A61B 5/0408</i> | (2006.01) | | 5,365,935 | A | 11/1994 | Righter et al. |
| | <i>A61B 5/0432</i> | (2006.01) | | 5,410,587 | A | 4/1995 | Grunwell |
| | <i>A61B 5/044</i> | (2006.01) | | 5,417,222 | A | 5/1995 | Dempsey et al. |
| | <i>A61B 5/0452</i> | (2006.01) | | 5,433,736 | A | 7/1995 | Nilsson |
| | <i>A61B 5/0452</i> | (2006.01) | | 5,452,356 | A | 9/1995 | Albert |
| | <i>A61B 5/0205</i> | (2006.01) | | 5,466,246 | A | 11/1995 | Silvian |
| (56) | References Cited | | | 5,467,773 | A | 11/1995 | Bergelson et al. |
| | U.S. PATENT DOCUMENTS | | | 5,481,255 | A | 1/1996 | Albert et al. |
| | | | | 5,503,158 | A | 4/1996 | Coppock et al. |
| | | | | 5,518,001 | A | 5/1996 | Snell |
| | | | | 5,522,396 | A | 6/1996 | Langer et al. |
| | | | | 5,539,705 | A | 7/1996 | Akerman et al. |
| | | | | D372,785 | S | 8/1996 | Sabri et al. |
| | | | | 5,544,661 | A | 8/1996 | Davis et al. |
| | | | | 5,551,953 | A | 9/1996 | Lattin et al. |
| | | | | 5,561,712 | A | 10/1996 | Nishihara |
| | | | | 5,568,448 | A | 10/1996 | Tanigushi et al. |
| | | | | 5,579,284 | A | 11/1996 | May |
| | | | | D377,983 | S | 2/1997 | Sabri et al. |
| | | | | 5,608,723 | A | 3/1997 | Felsenstein |
| | | | | 5,634,468 | A | 6/1997 | Platt et al. |
| | | | | 5,652,570 | A | 7/1997 | Lepkofker |
| | | | | 5,661,699 | A | 8/1997 | Sutton |
| | | | | 5,675,325 | A | 10/1997 | Taniguchi et al. |
| | | | | 5,678,562 | A | 10/1997 | Sellers |
| | | | | 5,701,894 | A | 12/1997 | Cherry et al. |
| | | | | 5,704,364 | A | 1/1998 | Saltzstein et al. |
| | | | | 5,724,025 | A | 3/1998 | Tavori |
| | | | | 5,730,143 | A | 3/1998 | Schwarzberg |
| | | | | 5,735,285 | A | 4/1998 | Albert et al. |
| | | | | 5,742,251 | A | 4/1998 | Gerber |
| | | | | 5,748,103 | A | 5/1998 | Flach et al. |
| | | | | 5,764,763 | A | 6/1998 | Jensen et al. |
| | | | | 5,772,586 | A | 6/1998 | Heinonen et al. |
| | | | | 5,818,788 | A | 10/1998 | Kimura et al. |
| | | | | 5,825,718 | A | 10/1998 | Ueki et al. |
| | | | | 5,827,179 | A | 10/1998 | Lichter et al. |
| | | | | 5,840,020 | A | 11/1998 | Heinonen et al. |
| | | | | 5,844,997 | A | 12/1998 | Murphy, Jr. |
| | | | | 5,861,018 | A | 1/1999 | Feierbach |
| | | | | 5,873,369 | A | 2/1999 | Laniado et al. |
| | | | | 5,876,351 | A | 3/1999 | Rohde |
| | | | | 5,877,675 | A | 3/1999 | Rebstock et al. |
| | | | | 5,889,730 | A | 3/1999 | May |
| | | | | 5,929,761 | A | 7/1999 | Van Der Laan et al. |
| | | | | D414,870 | S | 10/1999 | Saltzstein et al. |
| | | | | 5,970,388 | A | 10/1999 | Will |
| | | | | 5,976,083 | A | 11/1999 | Richardson et al. |
| | | | | 5,982,297 | A | 11/1999 | Welle |
| | | | | 5,983,127 | A | 11/1999 | Depinto |
| | | | | 6,008,703 | A | 12/1999 | Perrott et al. |
| | | | | 6,024,705 | A | 2/2000 | Schlager et al. |
| | | | | 6,037,704 | A | 3/2000 | Welle |
| | | | | 6,048,319 | A | 4/2000 | Hudgins et al. |
| | | | | D427,315 | S | 6/2000 | Saltzstein et al. |
| | | | | 6,072,396 | A | 6/2000 | Gaukel |
| | | | | 6,083,248 | A | 7/2000 | Thompson |
| | | | | | | | |

(56)

References Cited

U.S. PATENT DOCUMENTS

6,478,736	B1	11/2002	Mault	8,130,093	B2	3/2012	Mazar et al.
6,485,416	B1	11/2002	Platt et al.	8,150,750	B2	4/2012	Ray
6,507,734	B1	1/2003	Berger et al.	8,160,276	B2	4/2012	Liao et al.
6,513,532	B2	2/2003	Mault et al.	8,165,677	B2	4/2012	Von Arx et al.
6,549,756	B1	4/2003	Engstrom	8,224,429	B2	7/2012	Prstojevich et al.
6,558,320	B1	5/2003	Causey et al.	8,265,907	B2	9/2012	Nanikashvili et al.
6,579,231	B1	6/2003	Phipps	8,275,635	B2	9/2012	Stivoric et al.
6,595,929	B2	7/2003	Stivoric et al.	8,282,550	B2	10/2012	Rasdal et al.
6,600,471	B2	7/2003	Lee et al.	8,285,356	B2	10/2012	Bly et al.
6,605,038	B1	8/2003	Teller et al.	8,301,232	B2	10/2012	Albert et al.
6,612,985	B2	9/2003	Eiffert et al.	8,301,236	B2	10/2012	Baumann et al.
6,616,613	B1	9/2003	Goodman	8,323,188	B2	12/2012	Tran
6,636,761	B2	10/2003	Brodnick	8,328,718	B2	12/2012	Tran
6,685,633	B2	2/2004	Albert et al.	8,332,233	B2	12/2012	Ott et al.
6,717,983	B1	4/2004	Toda	8,364,250	B2	1/2013	Moon et al.
6,790,178	B1	9/2004	Mault et al.	8,369,936	B2	2/2013	Farringdon et al.
6,804,558	B2	10/2004	Haller et al.	8,374,688	B2	2/2013	Libbus et al.
6,820,057	B1	11/2004	Loch et al.	8,449,471	B2	5/2013	Tran
6,845,263	B2	1/2005	Kawaguchi	8,500,636	B2	8/2013	Tran
6,893,396	B2	5/2005	Schulze et al.	8,509,882	B2	8/2013	Albert et al.
6,928,535	B2	8/2005	Yamashita et al.	8,519,835	B2	8/2013	Dunko
6,950,681	B2	9/2005	Hofmann	8,543,185	B2	9/2013	Yuen et al.
6,970,737	B1	11/2005	Brodnick et al.	8,548,770	B2	10/2013	Yuen et al.
6,987,965	B2	1/2006	Ng et al.	8,700,137	B2	4/2014	Albert et al.
7,018,339	B2	3/2006	Birnbaum et al.	2001/0027384	A1	10/2001	Schulze et al.
7,020,508	B2	3/2006	Stivoric et al.	2001/0031998	A1	10/2001	Nelson et al.
7,031,745	B2	4/2006	Shen	2001/0051766	A1	12/2001	Gazdzinski
7,061,381	B2	6/2006	Forcier et al.	2002/0016541	A1	2/2002	Glossop
7,103,407	B2	9/2006	Hjelt et al.	2002/0032386	A1	3/2002	Sackner et al.
7,107,095	B2	9/2006	Manolas	2002/0111556	A1	8/2002	Wegner
7,108,659	B2	9/2006	Ross et al.	2002/0143576	A1	10/2002	Nolvak et al.
7,153,262	B2	12/2006	Stivoric et al.	2003/0004425	A1	1/2003	Narimatsu et al.
7,162,294	B2	1/2007	Rowlandson et al.	2003/0093002	A1	5/2003	Kuo
7,188,151	B2	3/2007	Kumar et al.	2003/0107487	A1	6/2003	Korman et al.
7,222,054	B2	5/2007	Geva	2003/0117987	A1	6/2003	Brebner
7,236,818	B2	6/2007	McLeod et al.	2003/0149344	A1	8/2003	Nizan
7,257,448	B2	8/2007	Crowe et al.	2003/0193839	A1	10/2003	Singh
7,260,429	B2	8/2007	Siejko et al.	2004/0034284	A1	2/2004	Aversano et al.
7,261,690	B2	8/2007	Teller et al.	2004/0044292	A1	3/2004	Yasushi et al.
7,285,090	B2	10/2007	Stivoric et al.	2004/0059205	A1	3/2004	Carlson et al.
7,319,425	B2	1/2008	Fiorenza et al.	2004/0117212	A1	6/2004	Kong et al.
7,324,836	B2	1/2008	Steenstra et al.	2004/0143403	A1	7/2004	Brandon et al.
7,349,574	B1	3/2008	Sodini et al.	2004/0215088	A1	10/2004	Hubelbank
7,351,207	B2	4/2008	Priemer	2004/0215094	A1	10/2004	Baumer et al.
7,354,400	B2	4/2008	Asafusa et al.	2004/0220487	A1	11/2004	Vyshedskiy et al.
7,383,297	B1	6/2008	Atsmon et al.	2004/0220488	A1	11/2004	Vyshedskiy et al.
7,415,304	B2	8/2008	Rowlandson et al.	2004/0225199	A1	11/2004	Evanyk et al.
7,444,116	B2	10/2008	Ivanov et al.	2004/0228217	A1	11/2004	Szeto
7,509,159	B2	3/2009	Xue et al.	2004/0236819	A1	11/2004	Anati et al.
7,520,860	B2	4/2009	Guion-Johnson et al.	2004/0266407	A1	12/2004	Lee et al.
7,542,878	B2	6/2009	Nanikashvili	2004/0266480	A1	12/2004	Hjelt et al.
7,548,623	B2	6/2009	Manabe	2005/0014531	A1	1/2005	Findikli
7,596,405	B2	9/2009	Kurzweil et al.	2005/0027207	A1	2/2005	Westbrook et al.
7,603,148	B2	10/2009	Michalak	2005/0078533	A1	4/2005	Vyshedskiy et al.
7,654,148	B2	2/2010	Tomlinson, Jr. et al.	2005/0124864	A1	6/2005	Mack et al.
7,657,479	B2	2/2010	Henley	2005/0234353	A1	10/2005	Xue et al.
7,668,589	B2	2/2010	Bauer	2006/0022833	A1	2/2006	Ferguson et al.
7,689,437	B1	3/2010	Teller et al.	2006/0047215	A1	3/2006	Newman et al.
7,701,895	B2	4/2010	Gehasie et al.	2006/0173259	A1	8/2006	Flaherty et al.
7,733,224	B2	6/2010	Tran	2006/0190045	A1	8/2006	Marcus et al.
7,742,808	B2	6/2010	Nissila	2006/0193270	A1	8/2006	Gehasie et al.
7,819,814	B2	10/2010	Gavrieli et al.	2006/0252999	A1	11/2006	Devaul et al.
7,846,104	B2	12/2010	Macquarrie et al.	2007/0021677	A1	1/2007	Markel
7,904,160	B2	3/2011	Brodnick et al.	2007/0027386	A1	2/2007	Such et al.
7,945,064	B2	5/2011	O'Brien, Jr. et al.	2007/0032731	A1	2/2007	Lovejoy et al.
7,946,959	B2	5/2011	Shum et al.	2007/0063850	A1	3/2007	Devaul et al.
7,955,273	B2	6/2011	Rahe-Meyer	2007/0106179	A1	5/2007	Bagha et al.
7,983,749	B2	7/2011	Warren	2007/0156060	A1	7/2007	Cervantes
8,019,609	B2	9/2011	Tamir et al.	2007/0254604	A1	11/2007	Kim
8,034,006	B2	10/2011	Celik-Butler et al.	2007/0265038	A1	11/2007	Kim
8,062,090	B2	11/2011	Atsmon et al.	2008/0009759	A1	1/2008	Chetham
8,078,136	B2	12/2011	Atsmon et al.	2008/0058670	A1	3/2008	Mainini
8,078,278	B2	12/2011	Penner	2008/0112885	A1	5/2008	Okunev et al.
8,126,566	B2	2/2012	Stahmann et al.	2008/0146890	A1	6/2008	LeBoeuf et al.
8,126,728	B2	2/2012	Dicks et al.	2008/0171945	A1	7/2008	Dotter
				2008/0177162	A1	7/2008	Bae et al.
				2008/0198872	A1	8/2008	Pierce
				2008/0214903	A1	9/2008	Orbach
				2008/0228045	A1	9/2008	Gao et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0293453 A1 11/2008 Atlas et al.
 2009/0010461 A1 1/2009 Klinghult et al.
 2009/0024045 A1 1/2009 Prakash et al.
 2009/0037575 A1 2/2009 Crystal et al.
 2009/0117883 A1 5/2009 Coffing et al.
 2009/0144080 A1 6/2009 Gray et al.
 2009/0149767 A1 6/2009 Rossetti
 2009/0156908 A1 6/2009 Belalcazar et al.
 2009/0171170 A1 7/2009 Li et al.
 2009/0209873 A1 8/2009 Pinter et al.
 2009/0273467 A1 11/2009 Elixmann et al.
 2009/0279389 A1 11/2009 Irie
 2009/0287067 A1 11/2009 Dorogusker et al.
 2009/0312655 A1 12/2009 Lo
 2010/0027379 A1 2/2010 Saulnier et al.
 2010/0033303 A1 2/2010 Dugan et al.
 2010/0035927 A1 2/2010 Ojika et al.
 2010/0042008 A1 2/2010 Amitai et al.
 2010/0049006 A1 2/2010 Magar et al.
 2010/0049037 A1 2/2010 Pinter et al.
 2010/0063381 A1 3/2010 Greiser
 2010/0069735 A1 3/2010 Berkner
 2010/0076276 A1 3/2010 Gilland
 2010/0094152 A1 4/2010 Semmlow
 2010/0113950 A1 5/2010 Lin et al.
 2010/0148956 A1 6/2010 Song et al.
 2010/0184479 A1 7/2010 Griffin, Jr.
 2010/0204758 A1 8/2010 Boon et al.
 2010/0208434 A1 8/2010 Kim et al.
 2010/0217099 A1 8/2010 LeBoeuf et al.
 2010/0217100 A1 8/2010 LeBoeuf et al.
 2010/0217345 A1 8/2010 Wolfe et al.
 2010/0234746 A1 9/2010 Sebelius
 2010/0256509 A1 10/2010 Kuo et al.
 2010/0281261 A1 11/2010 Razzell
 2010/0298711 A1 11/2010 Pedersen et al.
 2010/0324378 A1 12/2010 Tran et al.
 2010/0331631 A1 12/2010 MacLaughlin
 2011/0015496 A1 1/2011 Sherman et al.
 2011/0035927 A1 2/2011 Griffin et al.
 2011/0060251 A1 3/2011 Verma et al.
 2011/0066042 A1 3/2011 Pandia et al.
 2011/0117529 A1 5/2011 Barash et al.
 2011/0134725 A1 6/2011 Su et al.
 2011/0160601 A1 6/2011 Wang et al.
 2011/0182445 A1 7/2011 Atsmon et al.
 2011/0235466 A1 9/2011 Booij et al.
 2011/0275950 A1 11/2011 Xue et al.
 2011/0288425 A1 11/2011 Stewart
 2011/0301435 A1 12/2011 Albert et al.
 2011/0301439 A1 12/2011 Albert et al.
 2012/0051187 A1 3/2012 Paulson
 2012/0053424 A1 3/2012 Kenalty et al.
 2012/0071734 A1 3/2012 Shimuta et al.
 2012/0123891 A1 5/2012 Patel
 2012/0127833 A1 5/2012 Ghen et al.
 2012/0143018 A1 6/2012 Skidmore et al.
 2012/0147921 A1 6/2012 Conti et al.
 2012/0157019 A1 6/2012 Li
 2012/0158090 A1 6/2012 Chavan et al.
 2012/0171963 A1 7/2012 Tsfaty
 2012/0172689 A1 7/2012 Albert et al.
 2012/0179056 A1 7/2012 Moulder et al.
 2012/0316413 A1 12/2012 Liu et al.
 2013/0030259 A1 1/2013 Thomsen et al.
 2013/0085364 A1 4/2013 Lu et al.
 2013/0122810 A1 5/2013 Kaufman
 2013/0156194 A1 6/2013 Tanioka
 2013/0159699 A1 6/2013 Torkkel
 2013/0197320 A1 8/2013 Albert et al.
 2013/0236980 A1 9/2013 Moretti et al.
 2013/0261414 A1 10/2013 Tal et al.
 2013/0331663 A1 12/2013 Albert et al.
 2014/0050321 A1 2/2014 Albert et al.
 2014/0066798 A1 3/2014 Albert et al.

2014/0128758 A1 5/2014 Galloway et al.
 2014/0194760 A1 7/2014 Albert et al.
 2014/0221859 A1 8/2014 Albert et al.

FOREIGN PATENT DOCUMENTS

CN 201918016 U 8/2011
 CN 102347804 A 2/2012
 DE 2506936 A 9/1976
 DE 4212670 A1 1/1994
 EP 0631226 A1 12/1994
 EP 1782229 A 5/2007
 EP 1181888 B1 9/2007
 EP 1238633 B1 10/2008
 EP 2030565 A1 3/2009
 EP 2116183 B1 2/2012
 FR 2740426 A1 4/1997
 GB 2181554 4/1987
 GB 2408105 A 5/2005
 JP 59-122032 A 7/1984
 JP 59-190742 A 10/1984
 JP 63-072231 A 4/1988
 JP 63-294044 A 10/1988
 JP 1-244328 A 9/1989
 JP 5-167540 A 7/1993
 JP 6-326669 A 11/1994
 JP 2002191562 A 7/2002
 JP 2002-261731 A 9/2002
 JP 2003-010177 A 1/2003
 JP 2005-295378 A 10/2005
 JP 2012-065073 A 3/2012
 KR 10-2010-0059198 A 6/2010
 MX 2009011781 A1 5/2011
 WO WO 82/00910 A1 3/1982
 WO WO 88/05282 A1 7/1988
 WO WO 90/08361 A1 7/1990
 WO WO 92/06551 A1 4/1992
 WO WO 97/31437 A1 8/1997
 WO WO 98/38611 A1 9/1998
 WO WO 99/44494 A1 9/1999
 WO WO 00/41620 A1 7/2000
 WO WO 01/47597 A2 7/2001
 WO WO 01/57619 A2 8/2001
 WO WO 02/080762 A1 10/2002
 WO WO 03/075118 A2 9/2003
 WO WO 03/094720 A1 11/2003
 WO WO 2004/037080 A1 5/2004
 WO WO 2006/001005 A2 1/2006
 WO WO 2007/014545 A2 2/2007
 WO WO 2007/088315 A1 8/2007
 WO WO 2008/005015 A1 1/2008
 WO WO 2008/066682 A2 6/2008
 WO WO 2010/025166 A1 3/2010
 WO WO 2010/108287 A1 9/2010
 WO WO 2010/113354 A1 10/2010
 WO WO 2010/144626 A1 12/2010
 WO WO 2011/006356 A1 1/2011
 WO WO 2011/008838 A1 1/2011
 WO WO 2011/014292 A1 2/2011
 WO WO 2011/022942 A1 3/2011
 WO WO 2011/040877 A1 4/2011
 WO WO 2011/040878 A1 4/2011
 WO WO 2011/113070 A1 9/2011
 WO WO 2011/137375 A2 11/2011
 WO WO 2011/156374 A2 12/2011
 WO WO 2012/046158 A1 4/2012
 WO WO 2012/108895 A1 8/2012
 WO WO 2012/129413 A1 9/2012
 WO WO 2012/160550 A1 11/2012
 WO WO 2013/036307 A1 3/2013
 WO WO 2013/066642 A1 5/2013
 WO WO 2013/093690 A1 6/2013
 WO WO 2013/122788 A1 8/2013
 WO WO 2013/138500 A1 9/2013
 WO WO 2013/155196 A2 10/2013
 WO WO 2013/192166 A1 12/2013

OTHER PUBLICATIONS

U.S. Appl. No. 14/328,962, filed Jul. 11, 2014, Thomson et al.

(56)

References Cited

OTHER PUBLICATIONS

- U.S. Appl. No. 14/494,191, filed Sep. 23, 2014, Albert et al.
 U.S. Appl. No. 14/479,105, filed Sep. 5, 2014, Albert et al.
 Adidas miCoach Pacer Review: Like Nike+, Only Better; printed from website <http://gizmodo.com/5479456/adidas> printed on Mar. 4, 2010• 5 pages.
 Australian Design Awards. Heartplus Micro; printed from website <http://www.designawards.com/au>; printed on Apr. 12, 2002• 6 pages.
 Bajaj, M.D.; "Event Recording in Ambulatory Patients with Syncope Events"; University of Kansas; Wichita, Kansas; (no date); pp. 15-18; printed on or before Apr. 14, 2010.
 Bluetooth. Headset Profile (HSP), printed from website <http://bluetooth.com/English/Technology/Works/Pates/HSP.aspx>, printed on May 12, 2010.
 Bramanti et al., Multichannel telemetric system for biomedical signals via switched telephone lines, Medical and Biological Engineering and Computing, Sep. 1982, vol. 20, No. 5, pp. 653-656.
 Burke, "A Micropower Dry-Electrode ECG Preamplifier", IEEE Transactions on Biomedical Engineering, Feb. 2000, vol. 47, No. 2, pp. 155-162.
 Card Guard CG-6108 ACT Ambulatory Cardiac Telemetry Brochure; Card Guard; The Telemedicine Company; Switzerland; 2006; 2 pages.
 Cardiocomm Solutions; GEMS AIR. (PC based ECG management) printed from website <http://www.cardiocommsolutions.com>; printed on Mar. 19, 2010; 1 page.
 Charuvastra. Transtelephonic Cardiac Event Recording for Arrhythmia Surveillance; printed from website <http://tchin.org/resource-room/c-art> printed on Mar. 26, 2010• 2 pages.
 Cheng, Allen C.; "Real-Time Cardiovascular Diseases Detection on a Smartphone"; Departments of Electrical and Computer Engineering, Bioengineering, Neurological Surgery and Computer Science; University of Pittsburgh; Pittsburgh, PA; printed on or before Apr. 14, 2010.
 Creative. PC-80B Portable ECG Monitor w/sd card extension slot; printed from website www.amazon.com/Portable-Monitor-extension-leather-shipping/dp/B0010jWKUE; printed on Feb. 4, 2010• 5 pages.
 Deveau, "Health Care eyes smart phones to heal ills", printed from the website <http://www.theQiobeandmail.com> on Sep. 17, 2009, 4 pages.
 Dinh. Heart activity monitoring on smartphone. IPCBEE-Int conf Biomedical Eng and Technol. Jun. 17-19, 2011. 11:45-49.
 Dobrev, et al., Bootstrapped two-electrode biosignal amplifier, Med Bio Eng Comput, 2008, 7 pages.
 Dolan; Qualcomm launches ECG smartphone program in China; Sep. 8, 2011; 11 pgs.; retrieved Mar. 19, 2014 from the internet (<http://mobihealthnews.com/13092/qualcomm-launches-ecg-smartphone-program-in-china/>).
 Elert, Glenn (Editor); Frequency Range of Human Hearing; The Physics Factbook; web version as of Mar. 29, 2010; 2 pgs.; printed Jun. 6, 2012 (<http://web.archive.org/web/20100329141847/http://hypertextbook.com/facts/2003/ChrisDAmbrose.shtml>).
 European search report and opinion dated Nov. 21, 2014 for EP Application No. 11865699.0.
 Favorite Plus. Handheld Easy ECG Monitor—Handheld Easy EKG Monitor; printed from website www.favoriteplus.com/easy-ecg-handheld-monitor-fp; printed on Feb. 4, 2010; 2 pages.
 Favorite Plus. Handheld ECG Monitor—Handheld EKG Monitor at Favoriteplus.com; printed from website www.favoriteplus.com/handheld-ecg-ekg-monitor; printed on Feb. 4, 2010; 3 pages.
 Favorite Plus. Handheld ECG Monitor—Handheld EKG Monitor InstantCheck; printed from website <http://www.favoriteplus.com/instantcheck-hand-held-ecg-ekg-monitor>; printed on Feb. 4, 2010; 2 pages.
 Ferrick, M.D.; "Holter Monitoring and cardiac Event Recording in Assessing Symptomatic Patients"; Albert Einstein College of Medicine; Bronx, New York; (no date)• pp. 11-14. printed on or before Apr. 14, 2010.
 FREE2MOVE. Vitaphone 2300; www.free2move.us/News/NewsVitaphone240105.htm printed May 12, 2010.
 Fulford-Jones, et al., "A Portable, Low-Power, Wireless Two-Lead EKG System", Division of Engineering and Applied Sciences, Harvard University, Sep. 2004, 4 pages.
 Garabelli et al. Accuracy and Novelty of an Inexpensive iPhone-based Event Recorder (Presentation Poster/Abstract) Heart Rhythm 2012, 33rd Annual Scientific Session. SP23. Innovation Poster Session II. No. IA02-1; May 11, 2012.
 GBI Portal. Qualcomm's wireless reach mHealth project to improve cardiovascular disease in resource scarce China; Feb. 17, 2012; 7 pgs. Retrieved Mar. 19, 2014 from www.intergrallc.com/2012/02/17/qualcooms-wireless-reach-mhealth-project-to-improve-cardiovascular-disease-in-resource-scarce-china/.
 Gillette, M.D.; "Diagnosis of Pediatric Arrhythmias with Event Recording"; Medical University of South Carolina; Charleston, South Carolina; (no date); pp. 25-32; printed on or before Apr. 14, 2010.
 Grier, James W.; "How to use 1-lead ECG recorders to obtain 12-lead resting ECGs and exercise ("stress") ECGs"; Department of Biological Sciences; printed from website <http://www.ndsu.edu/pubweb/rvgrier>; printed on Jun. 7, 2010; 13 pages.
 Hannaford, Kat; "How to Turn Your iPhone Into a Laser, Fan or Flashlight"; printed from website <http://m.gizmodo.com/5534904> printed on Feb. 3, 2011.
 Hartmann, "ECG Front-End Design is Simplified with MicroConverter" AnalogDialogue, Nov. 2003, vol. 37, pp. 1-5.
 Hayes, M.D.; "Approaches to Diagnosing Transient Arrhythmias" An Overview; Mayo Clinic; Rochester Minnesota; (no date); pp. 7-10; printed on or before Apr. 14, 2010.
 Hearing Loss Assoc. of Kentuckiana; Decibal Ratings/Hazardous Time Exposures of Common Noise (excerpt from Survivor's Manual); web version as of Oct. 5, 2008; 2 pgs.; printed Jun. 6, 2012 (<http://web.archive.org/web/20081005143856/http://www.hearinglossky.org/hlasurvival1.html>).
 Huang, Tina; Age-related hearing loss; Minnesota Medicine; 90(10); pp. 48-50; Oct. 2007; printed Jun. 6, 2012 from: <http://www.minnesotamedicine.com/PastIssues/PastIssues2007/October2007/CinicalHuangOctober2007.aspx>.
 IMEC News; IMEC extends flexible ECG patch to enable arrhythmia detection; printed from website <http://www2.imec.be/imec> printed on Aug. 18, 2009 1 page.
 Instromedix. Cardiac Event Recording Faq's; Instromedix A Card Guard Company, San Diego, CA.; printed from website www.instromedix.com/pdf/products/cardiac; printed on or before Apr. 14, 2010.
 Instromedix. The Arrhythmia Monitoring System; King of Hearts Express AF Recorder Brochure from Instromedix• A CardGuard Company; Rosemont IL; 2004• 3 pages.
 International search report and written opinion dated Feb. 17, 2012 for PCT/US2011/039445.
 International search report and written opinion dated Apr. 27, 2012 for PCT/US2011/053708.
 International search report and written opinion dated May 15, 2013 for PCT/US2013/023370.
 International search report dated Sep. 1, 2014 for PCT/US2014/034350.
 International search report dated Dec. 10, 2013 for PCT/US2013/057576.
 International search report dated Dec. 17, 2013 for PCT/US2013/055458.
 Jenkins II, W.; Time/Frequency Relationships for an FFT-Based Acoustic Modem; Naval Postgraduate School; pp. 1-1 02; Sep. 2010 (http://edocs.nps.edu/npspubs/scholarly/theses/2010/Sep/1_OSep_Jenkins.pdf) printed Oct. 2, 2013.
 Kim, et al., "Detection of Atrial Fibrillation Episodes using Multiple Heart Rate Variability Features in Different Time Periods", 2008, 4 pages.
 Koerner. The Author's Metrics; Wired Magazine Article; New York, NY; Jul. 2009; p. 93-126.
 Kumar, M.D., "Zio Patch", printed from website <http://www.irhythmtech.com/zio-solution/zio-gach/>, printed on Apr. 12, 2010.

(56)

References Cited

OTHER PUBLICATIONS

- Kumarak, Greg; "Visa officially announces their case that turns your iPhone into a credit card (and we've got pies!)" ; May 17, 2010; printed from website www.mobilecrunch.com • printed on Feb. 3, 2011.
- Lau et al. Validation of an iPhone ECG application suitable for community screening for silent atrial fibrillation—a novel way to prevent stroke (Presentation Abstract 16810); American Heart Association 2012 Scientific Sessions and Resuscitation Science Symposium; 126(1); Nov. 20, 2012.
- Lau, et al. iPhone ECG application for community screening to detect silent atrial fibrillation: A novel technology to prevent stroke. *Int J Cardiol.* Apr. 30, 2013; 165(1):193-4.
- Lau, et al. Performance of an Automated iPhone ECG Algorithm to Diagnose Atrial Fibrillation in a Community AF Screening Program (SEARCH-AF). *Heart, Lung and Circulation.* 2013; 22(1): S205; 2013 (Abstracts for the Cardiac Society of Australia and New Zealand Annual Scientific Meeting and the International Society for Heart Research Australasian Section Ann. Scientific Meeting, Aug. 8-11, 2013, Gold Coast).
- Leijdekkers et al., "Trial Results of a Novel Cardiac Rhythm Management System using Smart Phones and wireless ECG Sensors", Proceedings of the 10th International Conf. on Smart homes and health Telematics., Jul. 1-3, 2009, Tours, France.
- Levkov et al., "Removal of power-line interference from the ECG: a review of the subtraction procedure" *BioMedical Engineering Online* 2005, printed from website <http://www.biomedical-engineeringonline.com/content/4/1/50> pp. 1-18.
- Lowres, et al. Screening Education and Recognition in Community Pharmacies of Atrial Fibrillation to prevent stroke in an ambulant population aged >=65 years (SEARCH-AF stroke prevention study): a cross-sectional study protocol. *BMJ Open.* Jun. 25, 2012; 2(3); pii: e001355. doi: 10.1136/bmjopen-2012-001355.
- M Med Choice printed from website <http://www.choicemed.com/1xwm.asp>; printed on Dec. 28, 2009 • 1 page.
- M Med Choice. Handheld ECG Monitor MD100A1; printed from website <http://www.choicemed.com/products/show.asp>; printed on Dec. 28, 2009; 2 pages.
- M Med Choice. Handheld ECG Monitor MD100B; printed from website <http://www.choicemed.com/products/show.asp>; printed on Dec. 28, 2009 • 2 pages.
- M Med Choice. Handheld ECG Monitor Brochure; M Med Choice, Beijing Choice Electronic Technology Co. LTD. • published on or before Apr. 14, 2010.
- MacFarlane, et al. Resting 12-lead ECG electrode placement and associated problems; SCST update 1995; 15pgs. Printed Feb. 18, 2014 from www.scsst.org.uk/resources/RESTING_12.pdf.
- Mauvila ECG Tutorial; Basic ECG Interpretation Tutorial; Sections 1-12; printed from website <http://mauvila.com/ECG/ecg.htm> • printed on Mar. 26, 2010 • 56 pages.
- Medgadget. Zio Patch Wins Medical Design Award *MedGadget* interne journal of emerging medical technologies, printed from website http://medaadaet.com/archives/2010/04/zio_patch_wins_medial_design_award_1.html.
- MiCardioMobile: Remote Wireless Cardiac Rehabilitation Monitoring printed from website <http://alivetec.cable.nu/cardiomobile> • printed on or before Apr. 14, 2010.
- Mobility Mind. Use your Treo 650 as a portable ECG monitoring device, *Mobility Mind Celebrating mobile Internet lifestyle and culture*, Sep. 14, 2005, printed from website <http://www.treotoday.net/2005/09/14/use-your-treo-650-as-a-portable-ecg-monitoring-device/>.
- Modem Protocols Explained; <ftp://kermit.columbia.edu/kermit/cu/protocol.html>; 5 pgs.; printed Oct. 2, 2013.
- Modem Tutorial; <http://www.lsu.edu/OCS/its/unix/tutorial/ModemTutorial/ModemTutorial.html>; 2 pgs.; printed Oct. 2, 2013.
- Muench, Frederick, PhD; "HRV: The Manufacturers and Vendors Speak; The portable StressEraser Heart Rate Variability Biofeedback Device: Background and Research" • *Biofeedback* vol. 36 Issue 1, pp. 35-39 • published Spring 2008.
- Murph. RedEye mini converts iPhone, iPad or iPod touch into IR-beaming universal remote; printed from website <http://www.engadget.com/2010/03/02/redeye>; printed on Mar. 2, 2010; 3 pages.
- Nam et al.; An Ultrasonic Sensor Based Low-Power Acoustic Modem for Underwater Communication in Underwater Wireless Sensor Networks; Computer Network Lab, Dept. of Elec. Eng., Korea Univ.; pp. 494-504; Dec. 2007 (http://nesl.ee.ucla.edu/fw/torres/home/Dropbox/good_paper_mico_controller.pdf); 11 pgs.; printed Oct. 2, 2013).
- Neuroreille; Audiometry; web version as of Oct. 14, 2008; 1 pg.; printed Jun. 6, 2012 (<http://www.neuroreille.com/promenade/english/audiometry/audiometry.htm>).
- New Professional Quality ECG/EGK Portable Heart Monitor; printed from website <http://cgibay.com/ws/eBayISAPI.dll> • printed on Feb. 4, 2010 • 3 pages.
- Notice of allowance dated Jan. 8, 2014 for U.S. Appl. No. 14/015,303.
- Notice of allowance dated Jan. 27, 2014 for U.S. Appl. No. 14/015,303.
- Notice of allowance dated Feb. 26, 2014 for U.S. Appl. No. 14/015,303.
- Notice of allowance dated May 23, 2014 for U.S. Appl. No. 13/108,738.
- Notice of allowance dated Jul. 9, 2013 for U.S. Appl. No. 12/796,188.
- Notice of allowance dated Aug. 28, 2012 for U.S. Appl. No. 13/420,520.
- Notice of allowance dated Dec. 4, 2013 for U.S. Appl. No. 14/015,303.
- Office action dated Jan. 2, 2014 for U.S. Appl. No. 13/108,738.
- Office action dated Jun. 18, 2012 for U.S. Appl. No. 13/420,520.
- Office action dated Sep. 12, 2014 for U.S. Appl. No. 13/108,738.
- Office action dated Oct. 6, 2014 for U.S. Appl. No. 14/252,044.
- Office action dated Oct. 29, 2012 for U.S. Appl. No. 12/796,188.
- Office action dated Nov. 19, 2014 for U.S. Appl. No. 13/969,446.
- Omron Portable ECG EKG Handheld HCG-801 Monitor; printed from website <http://www.amazon.com/Omron-Portable-Handheld-HCG-801-Monitor/dp/B0019WH3EO> • printed on Feb. 24, 2010 • 5 pages.
- Omron Portable ECT Monitor; printed from website <http://www.target.com/gp/detail.html>; printed on Mar. 26, 2010 • 1 page.
- Oresko, et al., "Detecting Cardiovascular Diseases via Real-Time Electrocardiogram Processing on a Smartphone", 2009 Workshop on Biomedicine in Computing: Systems, Architectures, and Circuits, pp. 13-16.
- Perez, Sarah; No NFC? No Problem; New Startup Zoosh Provides Workaround Technology (Jun. 20, 2011); printed on or before Jun. 27, 2011 from website; 2 pgs.; (<http://www.readwriteweb.com/archives/>).
- Prystowsky, M.D., "The Clinical Application, Diagnostic Yield and Cost Considerations of Cardiac Event Recorders", Indianapolis, Indiana (no date) pp. 19-23. printed on or before Apr. 14, 2010.
- Prystowsky, M.D.; "Chairmans Introduction"; Duke University Medical Center; Indianapolis, Indiana • (no date) • pp. 5-6 • printed on or before Apr. 14, 2010.
- Prystowsky, M.D.; "Chairmans Summary"; Duke University Medical Center; Indianapolis Indiana; (no date); pp. 39-40 • printed on or before Apr. 14, 2010.
- Puurtinen, et al., Best Electrode Locations for a Small Bipolar ECG Device: Signal Strength Analysis of Clinical Data, *Annals of Biomedical Engineering*, vol. 37, No.s 2, Feb. 2009 (© 2008) pp. 331-336.
- Rajaa Heart-Rate and EKG Monitor Using the MSP430FG439, SLAA280—Oct. 2005—Revised Sep. 2007, 11 pages.
- Readmyheart Personal Handheld ECG Monitor with Free Illustrator Book & Free Electrodes V2.2; printed from website <http://www.amazon.com/Readmyheart-Personal-Handheld-illustrator-Electrodes/dp/B0010AN63W>; printed on Mar. 26, 2010; 4 pages.
- Read-My-Heart. ECG Machine Handheld Read MyHeart; (product item No. HH-3413) printed from website <http://www.helioliving.com/ECG-Machine-Handheld-ReadMyHeart>; printed on Feb. 4, 2010; 1 page.

(56)

References Cited

OTHER PUBLICATIONS

Ricker. Square payment dongle demoed for iPhone toting hippies and you (video); printed from website <http://www.engadget.com/2010/01/18/square-payment>; printed on Jan. 18, 2010; 6 pages.

Rockwood. The Networked Body Magazine Article from Fast Talk Magazine; Jul./Aug. 2009; pp. 19-26.

Salahuddin, et al., "Ultra Short Term Analysis of Heart Rate Variability using Normal Sinus Rhythm and Atrial Fibrillation ECG Data", Engineering in Medicine and Biology Society, Aug. 2007, pp. 4656-4659.

Saxon, et al. iPhone rhythm strip—the implications of wireless and ubiquitous heart rate monitoring. JACC; 59(13): E726; Mar. 2012.

Saxon. Ubiquitous Wireless ECG Recording: A Powerful Tool Physicians Should Embrace. J Cardiovasc Electrophysiol. 24(4): pp. 480-483; Apr. 2013.

Semler, M.D.; "The Future of Cardiac Event Monitoring"; St. Vincent Hospital and Medical Center; Portland Oregon; (no date); pp. 33-37; printed on or before Apr. 14, 2010.

SFO Medical. Choice Portable Handheld ECG EKG Monitor; printed from website <http://www.amazon.com/Choice-Portable-Handheld-ECG-Monitor/dp/B001Q74VOM>; printed on Mar. 26, 2010; 1 page.

Shenzhen New Element Med. Equipment. Wireless ECG Monitoring System, printed from website http://www.alibaba.com/product-gs/248168581/Wireless_ECG_Monitoring_system.html; printed on Mar. 26, 2010.

Shumaker, J.; Designing an Ultrasonic Modem for Robotic Communications; Army Research Laboratory; 26 pgs.; Mar. 2009 (<http://www.dtic.mil/cgi-bin/GetTRDoc?AD=ADA499556>) printed Oct. 2, 2013.

Smith. Smartphone may keep the cardiologist away, The Independent, Health & Families, Mar. 5, 2010, printed from website <http://www.independent.co.uk/life-style/health-and-families/healthnews/smartphone-may-keep-the-cardiologist-away-1916652.html>, printed on Mar. 26, 2010.

Stevens, "Apple's Seamlessly Embedded Heart Rate Monitor could turn the iPhone into a new-age mood ring", printed from the website <http://www.enaadaet.com> on May 6, 2010, 3 pages.

Taleb Medical. Observer Hand-held ECG Monitor MD100B; (no date); printed on or before Apr. 14, 2010.

Tei, et al., New index of combined systolic and diastolic myocardial performance: a simple and reproducible measure of cardiac function—a study in normals and dilated cardiomyopathy; J Cardiol.; 26(6):357-366; Dec. 1995.

Texas Instruments. Information for Medical Applications, "Biophysical Monitoring-Electrocardiogram (ECG) Front End", Apr. 2004, 2 pages.

Tschida. Power A's New Case Turns Your iPhone Into a Universal Remote; printed from website <http://appadvice.com/appnn>; printed on Mar. 1, 2010• 2 pages.

Vanhemert, Kyle; "XWave Headset Lets You Control iPhone Apps With Your Brain"; Sep. 8, 2010; printed from website <http://gizmodo.com>; printed on Sep. 8, 2010.

Vitaphone. Telemedicine since 1999: Modern health management is our special subject. 3 pgs. Retrieved Mar. 19, 2014 from www.vitaphone.de/en/company/history-of-vitaphone/.

Wikimedia Laboratories; Acoustics; web archive version dated Jan. 25, 2009; 2 pgs.; printed Jun. 6, 2012 (<http://liveweb.archive.org/http://en.labs.wikimedia.org/wild/Acoustics>).

Wikipedia. "Pulse oximetry", printed from website <http://en.wikipedia.org> on May 10, 2010, 4 pages.

Wikipedia; Aliasing; web version as of Apr. 3, 2011; 5 pgs.; printed Jun. 6, 2012 (<http://liveweb.archive.org/http://en.wikipedia.org/w/index.php?title=Aliasing&oldid=422141882>).

Wikipedia; Hearing Range; web version as of Feb. 6, 2010; 5 pgs.; printed Jun. 6, 2012 (http://web.archive.org/web/20100206213741/http://en.wikipedia.org/wiki/Hearing_range).

Wisneski, C.; Ultrasonic Local Area Communication; <http://alumni.media.mit.edu/~wiz/ultracom.html>; 2 pgs.; printed Oct. 2, 2013.

Woodward et al; "Bio-Potential-To-Frequency Converter/Modulator"; Electronic Design• Aug. 1999• p. 117.

Ziegler, Chris; "EPI Life phone sports ECG function, can let doctors know if you're gonna make it"; printed from website www.enoadoet.com/2010/06/; Jun. 17 2010.

International search report and written opinion dated Sep. 1, 2014 for PCT/US2014/034350.




FIG. 1
(Prior Art)




FIG. 2
(Prior Art)




FIG. 3
(Prior Art)




FIG. 4
(Prior Art)




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 6




FIG. 7C




FIG. 7B




FIG. 7A




FIG. 7E




FIG. 7D




FIG. 8

Subject 35 Below has the Highest Correlation
Averaged Across all Leads 0.98780




FIG. 9

1

TWO ELECTRODE APPARATUS AND METHODS FOR TWELVE LEAD ECG

CROSS REFERENCE TO RELATED APPLICATIONS/INCORPORATION BY REFERENCE STATEMENT

This application is a continuation-in-part of U.S. Ser. No. 13/108,738, filed May 16, 2011, which is a continuation-in-part of U.S. Ser. No. 12/796,188, filed Jun. 8, 2010, now U.S. Pat. No. 8,509,882, each of which is hereby expressly incorporated herein by reference in its entirety. This application also claims priority to U.S. Provisional Application No. 61/812,655 filed on Apr. 16, 2013 which is hereby expressly incorporated herein by reference in its entirety.

BACKGROUND OF THE INVENTIVE CONCEPTS

1. Field of the Inventive Concepts

The presently claimed and disclosed inventive concept(s) relates generally to heart monitoring devices and methods and, more particularly, but not by way of limitation, to devices, systems and software for generating and providing one or more 12-lead electrocardiograms utilizing only two electrodes.

2. Brief Description of Related Art

Electrocardiography has been used to study the electrical activity of the heart. Electrocardiograms (ECG) can be recorded or taken using electrodes placed on the skin of a patient. The electrical signals recorded between any two electrodes placed on the skin of the patient are referred to as "leads." Varying numbers of electrodes and leads can be used to take the ECG. Exemplary numbers of leads used conventionally for taking ECGs are 3, 5, and 12 leads. For a standard 12-lead ECG, ten electrodes are used with six electrodes positioned on the chest and one electrode on each of the patient's arms and legs.

FIG. 1 is a pictorial representation of the 10 electrodes of a conventional electrocardiograph being placed on the patient for obtaining a standard 12-lead ECG. The electrode placed on the right arm is commonly referred to as RA. The electrode placed on the left arm is referred to as LA. The RA and LA electrodes are placed at the same location on the left and right arms, preferably but not necessarily near the wrist. The leg electrodes can be referred to as RL for the right leg and LL for the left leg. The RL and LL electrodes are placed on the same location for the left and right legs, preferably but not necessarily near the ankle.

FIG. 2 illustrates the placement of the six electrodes on the chest in the prior art arrangement with such electrodes being labeled V_1 , V_2 , V_3 , V_4 , V_5 , and V_6 . V_1 is placed in the fourth intercostal space, for example between ribs 4 and 5, just to the right of the sternum. V_2 is placed in the fourth intercostal space, for example between ribs 4 and 5, just to the left of the sternum. V_3 is placed in the fifth intercostal space midway between electrodes V_2 and V_4 . V_4 is placed in the fifth intercostal space between ribs 5 and 6 on the left mid-clavicular line. V_5 is placed horizontally even with V_4 on the left anterior axillary line. V_6 is placed horizontally even with V_4 and V_5 on the left mid-axillary line.

The electrocardiograph then calculates and outputs three limb lead waveforms. Limb leads I, II, and III are bipolar leads having one positive and one negative pole. Lead I is the voltage between the left arm (LA) and right arm (RA), e.g. $I = LA - RA$. Lead II is the voltage between the left leg (LL) and right arm (RA), e.g. $II = LL - RA$. Lead III is the voltage

2

between the left leg (LL) and left arm (LA), e.g. $III = LL - LA$. Leads I, II and III are commonly referred to as "limb leads."

Unipolar leads also have two poles; however, the negative pole is a composite pole made up of signals from multiple other electrodes. In a conventional cardiograph for obtaining a 12-lead ECG, all leads except the limb leads are unipolar (aVR, aVL, aVF, V_1 , V_2 , V_3 , V_4 , V_5 , and V_6). Augmented limb leads (aVR, aVL, and aVF) view the heart from different angles (or vectors) and are determined from RA, RL, LL, and LA. For example, the augmented vector right (aVR) positions the positive electrode on the right arm, while the negative electrode is a combination of the left arm electrode and the left leg electrode, which "augments" the signal strength of the positive electrode on the right arm. Thus the augmented vector right (aVR) is equal to $RA - (LA + LL)/2$ or $-(I + II)/2$. The augmented vector left (aVL) is equal to $LA - (RA + LL)/2$ or $(I - II)/2$. The augmented vector foot (aVF) is equal to $LL - (RA + LA)/2$ or $(II - I)/2$.

The six electrodes on the chest of the patient are close enough to the heart that they do not require augmentation. A composite pole called Wilson's central terminal (often symbolized as CT_W , V_W , or WCT) is used as the negative terminal. Wilson's central terminal is produced by connecting the electrodes RA, LA, and LL together, via a simple resistive network, to give an average potential across the body, which approximates the potential at an infinite distance (i.e. zero). Wilson's central terminal, WCT, is calculated as $(RA + LA + LL)/3$.

FIG. 3 illustrates an example Lead I annotated to show PQRST waves generated by a 12-lead electrocardiograph. The identification and measurement of the PQRST waves based on the electrocardiogram is known in the art. FIG. 4 illustrates an example of a 12-lead electrocardiogram in a conventional format.

While a conventional 12-lead electrocardiogram gives very useful information concerning the health and condition of an individual's heart, the conventional electrocardiograph equipment is expensive and the procedure is not normally available in areas other than hospitals and medical doctors' offices. Therefore monitoring is not done frequently even in wealthy countries, and in poorer areas of the world an electrocardiograph may not even be available. To significantly reduce costs of obtaining an electrocardiogram, a 2-electrode electrocardiograph device as described in U.S. Pat. No. 8,301,232 was marketed. The 2-electrode electrocardiograph device utilizes a smart phone connected to and at least partially surrounded by a phone protective case incorporating and supporting the two electrodes. Such devices significantly simplify and reduce the cost of obtaining an electrocardiogram, although such an electrocardiogram does not include as much information as a 12-lead electrocardiogram produced by an electrocardiograph having 10 electrodes. The 12-lead electrocardiogram produced by the 10-electrode electrocardiograph offers additional and important heart-related information to the cardiologist, allowing the diagnosis of conditions like heart attacks (myocardial infarctions) that a single-lead ECG cannot do. It would be advantageous if a readily available and inexpensive device could generate and produce an electrocardiogram that substantially replicates the 12-lead electrocardiogram produced by a 10-electrode electrocardiograph.

SUMMARY OF THE DISCLOSURE

In general, described herein are apparatuses, methods and systems for producing an electrocardiogram that substantially replicates the electrocardiogram produced by a 10-electrode

trode electrocardiograph but using an electrocardiograph device having only two electrodes. In one embodiment, the electrocardiograph device has a first electrode assembly with a first electrode adapted to measure an electrical signal on a patient's body, and a second electrode assembly with a second electrode adapted to measure an electrical signal at another location on the patient's body. The electrocardiograph device also includes control circuitry configured to measure electrocardiogram signals between the first and second electrodes, and a data transmission module configured to transmit the measured electrocardiogram signals to a portable computing device by a wired or wireless transmission system and protocol such as, for example, those known in the art as USB, WI-FI®, BLUETOOTH®, NFC, or as audible or ultrasonic sound signals.

The electrocardiograph device can be used in combination with a portable computing device to form an electrocardiograph. The portable computing device is provided with computer hardware including a processor in communication with a non-transitory computer readable medium. The non-transitory computer readable medium stores software that includes instructions that when executed by the processor causes the processor to record the electrocardiogram signals between the first electrode and the second electrode while the first and second electrodes are sequentially placed in predetermined paired positions on a patient's body that are known by the processor. In one embodiment the processor is caused to (a) calculate an average PQRSST beat from the measured electrocardiogram signals as the first and second electrodes are sequentially placed in Limb Lead I, II, and III positions on a patient's body for a time required to measure at least one heartbeat in each Limb Lead position, the Limb Lead positions known by the processor; (b) use the relationship (Lead III=Lead II-Lead I) to time-align and display Limb Leads I, II, and III; and (c) calculate and display augmented Leads aVR, aVL, and aVF from the time-aligned Limb Leads I, II, and III.

The software can further include instructions that when executed by the processor causes the processor to calculate and display average time-aligned Leads V1, V2, and V3 from the measured electrocardiogram signals obtained from sequentially placing one of the first and second electrodes in a V1, V2, and V3 position while contacting the other of the first and second electrodes with a left arm of the patient for a time required to measure at least one heart beat (or more if an average beat is to be calculated). The processor is further caused to calculate and display average Leads V4, V5, and V6 from the measured electrocardiogram signals obtained from sequentially placing one of the first and second electrodes in a V4, V5, and V6 position while contacting the other of the first and second electrodes with a right arm of the patient for a time required to measure at least one heartbeat. The resulting 12-lead display and report replicated the 12-lead electrocardiogram produced by a 10-electrode electrocardiograph.

Methods are provided for generating a 12-lead electrocardiogram using an electrocardiograph comprising an electrocardiograph device and a portable computing device. The electrocardiograph device has a first electrode, a second electrode, control circuitry, and a data transmission module, the control circuitry configured to measure electrocardiogram signals between the first and second electrodes. In one embodiment, such a method includes directing, by the portable computing device, a user to place the first electrode and the second electrode at predetermined locations on a patient's body. The portable computing device receives and records location data indicative of the predetermined location on which the first electrode and the second electrode are placed.

The control circuitry of the electrocardiograph device receives electrocardiogram signals from the first electrode and the second electrode, and the data transmission module of the electrocardiograph device transmits the electrocardiogram signals to the portable computing device. The portable computing device generates a 12-lead electrocardiogram from the sequentially measured electrocardiogram signals between the first and second electrodes.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a pictorial representation of a prior art electrocardiograph having 10 electrodes positioned on a patient's body for taking a prior art 12-lead electrocardiogram.

FIG. 2 is a pictorial representation of a chest showing an example of electrode placement on the chest for taking a prior art 12-lead electrocardiogram.

FIG. 3 illustrates an example Lead I annotated to show PQRSST waves generated by a 12-lead electrocardiograph.

FIG. 4 shows an example 12-lead electrocardiogram in a conventional format.

FIG. 5A illustrates a front elevational view of one embodiment of an electrocardiograph constructed in accordance with the presently disclosed and claimed inventive concepts in which the electrocardiograph includes a two-electrode electrocardiograph device and a portable computing device.

FIG. 5B illustrates a rear elevational view of the electrocardiograph depicted in FIG. 5A.

FIG. 5C is a front elevational view of the electrocardiograph device depicted in FIG. 5A in which the electrocardiograph device has been removed from the portable computing device.

FIG. 5D is a cross-sectional view of the electrocardiograph device depicted in FIG. 5C and taken along the lines 5-5.

FIG. 6 is another embodiment of a two-electrode electrocardiograph device configured in a pen-shape and constructed in accordance with the inventive concepts disclosed herein.

FIG. 7A-FIG. 7E illustrates an example sequential electrode placement used by the electrocardiograph to generate a 12-lead electrocardiogram in accordance with the presently disclosed inventive concepts.

FIG. 8 shows a correlation of V1 leads for Subject 35 of the Example Clinical Trials.

FIG. 9 shows an excellent correlation of leads 1-8 for Subject 35 in the Example Clinical Trials.

DETAILED DESCRIPTION

Before explaining at least one embodiment of the inventive concepts disclosed herein in detail, it is to be understood that the inventive concepts are not limited in their application to the details of construction, experiments, exemplary data, and/or the arrangement of the components set forth in the following description, or illustrated in the drawings. The presently disclosed and claimed inventive concepts are capable of other embodiments or of being practiced or carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein is for purpose of description only and should not be regarded as limiting in any way.

In the following detailed description of embodiments of the inventive concepts, numerous specific details are set forth in order to provide a more thorough understanding of the inventive concepts. However, it will be apparent to one of ordinary skill in the art that the inventive concepts within the disclosure may be practiced without these specific details. In other

instances, well-known features have not been described in detail to avoid unnecessarily complicating the instant disclosure.

Further, unless expressly stated to the contrary, “or” refers to an inclusive or and not to an exclusive or. For example, a condition A or B is satisfied by any one of the following: A is true (or present) and B is false (or not present), A is false (or not present) and B is true (or present), and both A and B are true (or present).

In addition, use of the “a” or “an” are employed to describe elements and components of the embodiments herein. This is done merely for convenience and to give a general sense of the inventive concepts. This description should be read to include one or at least one and the singular also includes the plural unless it is obvious that it is meant otherwise.

Finally, as used herein, any reference to “one embodiment” or “an embodiment” means that a particular element, feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment.

The term “lead” in electrocardiography causes much confusion because it can be used to refer to two different things. In accordance with common usage, the word “lead” may be used to refer to the electrical cable attaching the electrodes to the electrocardiograph. Alternatively, and as used herein, the word “lead” refers to the tracing of the voltage difference between at least two electrodes. Conventionally, 10 electrodes are used to produce twelve of this type of lead, thereby forming a “12-lead” electrocardiogram as exemplified in FIG. 4.

A “12-lead electrocardiogram format” is used herein and in the appending claims to refer to presentation of electrocardiogram signals from at least Lead I, Lead II, and V_1 through V_6 leads, and optionally Lead III, aVR, aVL and aVF, displayed over the span of at least one heartbeat using a uniform time scale.

The term “patient” as used herein includes humans and other warm-blooded animals, such as mammals, for example, dogs, cats, horses, and cattle or cold-blooded animals such as reptiles, and refers to the person or animal whose heart-related signals are being measured. The term “user” refers to the one applying the electrodes to the body to measure the ECG. The user can be the same as the patient, or the user can be another such as, for example, a nurse, doctor, or veterinarian.

In general methods, devices, and systems are provided for measuring electrical signals on the body of a patient. Referring now to FIGS. 5A and 5B, shown therein is an exemplary embodiment of an electrocardiograph 8 constructed in accordance with the inventive concepts disclosed and claimed herein. The electrocardiograph 8 includes an electrocardiograph device 10 and a portable computing device 11. The electrocardiograph device 10 as discussed below is a two-electrode device; however, it should be understood that the electrocardiograph device 10 may include more than two electrodes. The electrocardiograph device 10 includes a first electrode assembly 12 having a first electrode 14, a second electrode assembly 16 having a second electrode 18, and a housing 20 containing control circuitry 22 and a data transmission module 24. The first electrode 14 and the second electrode 18 are adapted to measure an electrical signal on a patient’s body. The control circuitry 22, can communicate with the first and second electrodes 14 and 18 via ports 23-1 and 23-2, respectively, and is configured to measure electrocardiogram signals between the first and second electrodes 14

and 18, respectively. The electrocardiogram signals can be analog signals indicative of the electrical potentials on a body surface of the patient that are associated with heart muscle activity. The ports 23-1 and 23-2 may be designed to receive analog signals, and may include two, three or four contacts. In some embodiments, the ports 23-1 and 23-2 are standard female connectors in which a three-contact version is known in the art as a TRS connector, where T stands for “tip”, R stands for “ring” and S stands for “sleeve”. Similarly, two- and four-contact versions are known in the art as TS and TRRS connectors respectively.

The data transmission module 24 is configured to receive the measured electrocardiogram signals and transmit the measured electrocardiogram signals to the portable computing device 11. The data transmission module 24 may transmit the measured electrocardiogram signals to the portable computing device 11 using a wired or wireless transmission system and protocol such as those known in the art as USB, WI-FI®, BLUETOOTH®, NFC, or as audible or ultrasonic sound signals.

While there can be multiple electrodes, in one embodiment there are only two. The first electrode assembly 12 can be configured in any way consistent with its function, i.e., it should include the first electrode 14 in a manner available to make contact with a patient’s body on the hands, chest or other parts of the body, to measure an electrical signal for obtaining the patient’s electrocardiogram. The first electrode assembly 12 can include a non-conductive hand-held portion 26 as well as the first electrode 14. By using only two electrodes, and sequentially measuring electrocardiogram signals at separate and distinct instants of time as discussed below, a patient can easily measure his or her own electrocardiogram signals and produce a 12-lead electrocardiogram without the need to apply 10 electrodes and adhesives to the body as would be the case using a conventional electrocardiograph.

The second electrode assembly 16 can likewise be configured in any way consistent with its function. In one embodiment, the second electrode assembly 16 is configured to removably attach to an upper limb of the patient. For example, the electrocardiograph device 10 shown in FIGS. 5A and 5B includes a second electrode assembly 16 configured as a spring-hinged cuff. By allowing the second electrode assembly 16 to “grasp” the patient rather than the patient grasping an electrode, little or no electrical “noise” is created by the nerves and adjacent muscles holding the second electrode 18.

Other nonlimiting examples of suitable electrodes include suction cup electrodes, disposable snap electrodes, alligator clip electrode connectors with disposable electrodes, and any combination thereof.

The portable computing device 11 can be implemented as a personal computer, a smart phone, network-capable TV set, TV set-top box, a tablet, an e-book reader, a laptop computer, a desktop computer, a network-capable handheld device, a video game console, a server, and combinations thereof, for example. Preferably, the portable computing device 11 comprises an input device 30, an output device 32, and computer hardware 34 (which is shown in Phantom). The computer hardware 34 may be a system or systems that are able to embody and/or execute the logic of the processes described herein. Logic embodied in the form of software instructions and/or firmware may be executed on any appropriate hardware. For example, logic embodied in the form of software instructions or firmware may be executed on a dedicated system or systems, or on a personal computer system, or on a distributed processing computer system, and/or the like. In some embodiments, logic may be implemented in a stand-alone environment operating on a single computer system

and/or logic may be implemented in a networked environment, such as a distributed system using multiple computers and/or processors. The computer hardware 34 of the portable computing device 11 may have a processor and a non-transitory computer readable medium. The term “processor” as used herein may include a single processor or multiple processors working independently and/or together to execute the logic described herein. Exemplary non-transitory computer readable medium may include random access memory, read only memory, flash memory, and combinations thereof. The term non-transitory computer readable medium, as used herein, may be implemented as a single physical device or multiple physical devices of a distributed system that may or may not be logically related.

The input device 30 is capable of receiving information input from a user, and transmitting such information to the computer hardware 34. The input device 30 can be implemented as a keyboard, a touchscreen, a mouse, a trackball, a microphone, a fingerprint reader, an infrared port, a slide-out keyboard, a flip-out keyboard, a cell phone, a PDA, a video game controller, a remote control, a fax machine, and combinations thereof, for example.

The output device 32 outputs information in a form perceivable by a user. For example, the output device 32 can be a computer monitor, a screen, a touchscreen, a speaker, a website, a TV set, a smart phone, a PDA, a cell phone, a fax machine, a printer, a laptop computer, and combinations thereof. It is to be understood that the input device 30 and the output device 32 may be implemented as a single device, such as for example a touchscreen of a smartphone or a tablet.

In one embodiment, the housing 20 is configured as a protective cover for the portable computing device 11. As shown in FIG. 5C and FIG. 5D, the housing 20 may be provided with a base 35 having a perimeter 36. The base 35 has an interior surface 38 and an opposing exterior surface 40. The housing 20 may also be provided with a rim 42 extending from the interior surface 38 and generally following the perimeter 36 of the base 35. The rim 42 and the interior surface 38 define a space 44 that is sized and adapted to receive the portable computing device 11. The ports 23A and 23B may be proximate to the exterior surface 40 so as to be available when the portable computing device 11 is positioned within the space 44. The base 35, in some embodiments, surrounds and supports the control circuitry 22 and the data transmission module 24. In this embodiment, the base 35 may include a pocket for receiving a power source 45, such as a battery, for powering the control circuitry 22 and the data transmission module 24 and may also include a door 46 proximate to the interior surface 38 for providing access to the pocket such that a user can install and/or replace the power source 45. In other embodiments, the power source 45 may be a solar cell supported by the base 35 proximate to the exterior surface 40.

The housing 20 may be constructed as a single unit, or multiple units connected together. Exemplary materials forming the housing 20 include plastic, and/or a combination of plastic and elastomers.

In another embodiment that is shown in FIG. 6 and labeled by way of example with reference numeral 10-1, the electrocardiograph device combines the first and second electrodes 14 and 18 on opposing ends of a unit 50 shaped like a flash light or pen. For example, the electrocardiograph device 10-1 that is shown in FIG. 6 by way of example has a second electrode 18 on a cylindrical surface of one end of the “pen” touching a holder’s hand in use. The first electrode 14 is located on an opposing end and is used to contact the holder’s chest, hand or other body part when in use. The electrocar-

diograph device 10-1 can thus be used to measure the electrical signals between the opposing first and second electrodes 14 and 18, respectively.

The devices and apparatuses disclosed herein can also be configured to use one or more disposable first and second electrodes 14 and 18, respectively, or first and second electrode assemblies 12 and 16, respectively. Use of disposable electrodes or disposable electrode assemblies allows the electrocardiograph device 10 or 10-1 to be used by multiple patients with reduced chance spreading disease by transfer of microbes and bodily fluids from one patient to another.

The first and second electrodes 14 and 18, respectively, can be connected to the control circuitry 22 in a wired or wireless manner. In one embodiment, and as shown in FIGS. 5A and 5B, the first and second electrodes 14 and 18, respectively, are electrically connected to the control circuitry 22 by the ports 23-1 and 23-2, and wires or cables.

The control circuitry 22 measures the small voltage between the first and second electrodes 14 and 18, respectively. In one embodiment, the data transmission module 24 converts the voltage measurements to a frequency modulated electrocardiogram audio signal and transmits the signal to a receiver of the computer hardware 34 of the portable computing device 11 via cable, a wired audio jack connection, wirelessly (using, for example, a BLUETOOTH® connection) or acoustically. The receiver of the portable computing device 11 can thus be a cable connection, audio jack, BLUETOOTH® or similar wireless receiver, or a microphone. In order to provide enhanced privacy, in one embodiment, the data transmission module 24 encrypts the signals prior to transmitting to the portable computing device 11. Numerous encryption techniques are known to those skilled in the art.

Nonlimiting examples of portable computing device 11 having, or adaptable to have, such receivers include smartphones, personal digital assistants (PDAs), tablet personal computers, pocket personal computers, notebook computers, desktop computers, and server computers. The receiver may include an antenna and/or a microphone depending upon the types of signals to be transmitted from the data transmission module 24.

In one embodiment, the electrocardiogram signals are converted to a frequency modulated audio or sound signal having a carrier frequency in a range of from about 1 kHz to about 24 kHz or greater and in this case the receiver of the computer hardware 34 will include a microphone. In another embodiment, the data transmission module 24 converts the electrocardiogram signals to a frequency modulated sound signal having a carrier frequency in a range of from about 18 kHz to about 24 kHz or greater. Nonlimiting examples of suitable ultrasonic transmitters include, but are not limited to, miniature speakers, piezoelectric buzzers, and the like. The ultrasonic signals can be received by, for example, a microphone of the computer hardware 34 of the portable computing device 11.

Referring now to FIG. 7, a non-transitory computer readable medium of the computer hardware 34 stores a set of instructions, wherein the set of instructions are capable of being executed by the processor of the portable computing device 11. When the set of instructions are executed, the one or more portable computing device 11 is caused to receive and record electrocardiogram signals between the first electrode 14 and the second electrode 18, while the first and second electrodes 14 and 18, respectively, are sequentially placed in predetermined paired positions on a patient’s body at separate and distinct instants of time, and held in each predetermined paired position for multiple heartbeats. The computing device essentially steps the user through the positioning each lead

and can, for example, show a picture of a body on a computer screen with the desired electrode positioning indicated by a flashing point. The set of instructions further cause the portable computing device 11 to calculate the electrocardiogram signals into signal sets representing a heartbeat for each paired position, and from the signal sets representing a heartbeat, to calculate average heartbeat representations for each paired position. The set of instructions can then cause the portable computing device 11 to align the average heartbeat representations, and to store and output electrocardiogram data indicative of the average heartbeat representations in a standard 12-lead electrocardiogram format.

For example, ten seconds of each lead can be recorded and an average PQRST computed for each lead from each recording. The limb lead average beats (I, II, and III) can then be time-aligned. Augmented lead average beats are calculated from aligned average limb leads. The V1-V6 beats are averaged and aligned to create a 12-lead report from averaged beats.

The 12-lead electrocardiogram format output can display on the output device 32, such as a display screen of the portable computing device 11 or can be output through a printer. The set of instructions can cause the 12-lead electrocardiogram format output to be retained in a storage memory of the portable computing device 11, or to be transmitted to a computer external to the portable computing device 11, such as a web server via an internet connection on the portable computing device 11.

In one embodiment, the set of instructions can further cause the portable computing device 11 to digitize and demodulate the electrocardiogram signals using technology known to those skilled in the art or technology yet to be developed.

In another embodiment, when the set of instructions are executed, the portable computing device 11 is caused to interact with a user (e.g. via the output device 32) to provide audio and/or textual instructions to direct the placement of the first and second electrodes 14 and 18, respectively, and/or to request the user to confirm placement of the first and second electrodes 14 and 18, respectfully via the input device 30. For example, the portable computing device 11 can be made to provide textual instructions to a user for contacting the first electrode 14 to the patient's left arm and the second electrode 18 to the patient's right arm on a display screen, after which the electrocardiograph device 10 or the electrocardiograph device 10-1 and the portable computing device 11 measures and records the electrical signal between the left arm and right arm for a suitable time interval to correspond to Lead I in a 12-lead ECG. The instructions can further cause the portable computing device 11 to calculate and store an average heartbeat representation for Lead I. A suitable time interval for obtaining heartbeat data for Lead I, and all leads generally, can be between 5 seconds and 30 seconds. Longer times are possible but not necessary.

The set of instructions can further cause the portable computing device 11 to provide instructions to a user, or request placement confirmation from a user, to collect the electrocardiogram data. For example, after the portable computing device 11 has stored the data for Lead I, the portable computing device 11 may provide instructions to the user, or request placement confirmation from the user regarding contacting the first electrode 14 to the patient's left leg and the second electrode 18 to the patient's right arm, wherein the electrical signal measured between the left leg and right arm corresponds to Lead II, and to calculate and store an average heartbeat representation for Lead II.

Similarly, the set of instructions can further cause the portable computing device 11 to provide instructions to a user, or request placement confirmation from a user, regarding contacting the first electrode 14 to the patient's left leg and the second electrode 18 to the patient's left arm, wherein the electrical signal measured between the left leg and the left arm corresponds to Lead III in a 12-lead electrocardiogram and then to analyze the electrical signal corresponding to Lead III to calculate and store an average heartbeat representation for Lead III.

Using the average heartbeat representations Lead I and Lead II, the set of instructions can cause the computing device to calculate aVR, aVL, and aVF. The augmented vector right (aVR) is equal to $RA - (LA + LL)/2$ or $-(I + II)/2$. The augmented vector left (aVL) is equal to $LA - (RA + LL)/2$ or $(I - II)/2$. The augmented vector foot (aVF) is equal to $LL - (RA + LA)/2$ or $(II - I)/2$.

The set of instructions can further cause the portable computing device 11 to provide instructions to a user, or request placement confirmation from the user, for contacting the first electrode 14 with each of the V1, V2, V3, V4, V5, and V6 chest locations while contacting the second electrode 18 to one of the patient's left arm and the patient's right arm. The electrical signals measured between each of the V1, V2, V3, V4, V5, and V6 chest locations and the left arm or the right arm correspond to Leads V1, V2, V3, V4, V5, and V6 in a 12-lead electrocardiogram. The set of instructions can then further cause the portable computing device 11 to analyze the electrical signals corresponding to Leads V1, V2, V3, V4, V5, and V6 to calculate average heartbeat representations for Leads V1, V2, V3, V4, V5, and V6.

While not being bound by any particular theory, it has been discovered that use of multiple electrodes to achieve a composite pole such as Wilson's central terminal is not necessary. In one embodiment, the patient's right arm can be used as a negative terminal for each of Leads V1, V2, V3, V4, V5, and V6 captured with conventional placement of electrodes on the chest. In some individuals, however, V1, V2 and V3 measurements do not correlate well. In such individuals, the electrodes must be placed on either side of the heart to achieve duplication of conventional V1, V2 and V3 measurements. It has been definitively demonstrated that in such individuals, the left arm can be used for Leads V1, V2, and V3, while the right arm is used for Leads V4, V5, and V6, and excellent correlation to conventional measurements is achieved.

Once average heartbeat representations are calculated and stored for Leads I, II, III, aVR, aVL, aVF, V1, V2, V3, V4, V5, and V6, the set of instructions can cause the portable computing device 11 to align each of the heartbeat representations based on corresponding characteristics of the heartbeat representations. The averaged and aligned signals can be stored and output in a 12-lead electrocardiogram format.

While it is customary for the voltage measurements to be made in one direction, the software can be made to recognize when the first and second electrodes 14 and 18 are reversed and invert the average heartbeat representation. For example, it is customary for Lead I to measure the left arm (LA) minus the right arm (RA), e.g. $I = LA - RA$. However, if the first and second electrodes 14 and 18 were reversed such that RA-LA was measured instead, the software would recognize that the first and second electrodes 14 and 18 were reversed and would invert the average heartbeat representation for Lead I to obtain the traditional Lead one output.

Methods for generating a traditional 12-lead electrocardiogram using only two electrodes, e.g. the first and second electrodes 14 and 18, are provided by operating the portable computing device 11 and the above-described electrocardio-

11

graph device **10** or **10-1**. A 12-lead electrocardiogram can be generated by sequentially measuring electrical signals between the first and second electrodes **14** and **18** at separate and distinct instants of time after the first and second electrodes **14** and **18** are positioned at predetermined locations on a patient's body. Average heartbeat representations for each of the leads can be calculated as described above, and aligned to produce an electrocardiogram having a 12-lead electrocardiogram format.

There are several commonly used 12-lead electrocardiogram formats. The most common format is a 4x3 format; four columns of three leads. The first column includes Limb Leads I, II and III. The second column includes Leads aVR, aVL and aVF. The third column includes Leads V1, V2 and V3, while the fourth column includes Leads V4, V5 and V6.

In some embodiments, the portable computing device **11** is a commercially available smart phone having a standard operating system such as the operating systems identified in the art as "iOS" or "Android." In this embodiment, the electrocardiograph **8** for generating a 12-lead electrocardiogram using only two electrodes can be provided using the above-described electrocardiograph device **10** and software downloadable to the portable computing device **11**, wherein the software provides instructions to the portable computing device **11** as described above. In these embodiments, the control circuitry **22** and data transmission module **24** are configured to function and interact with the portable computing device **11** when the portable computing device **11** is executing an application downloadable to the portable computing device **11**.

In one embodiment, the systems and methods described above include sending the 12-lead electrocardiogram to a remote server or to a medical professional. In another embodiment, the systems and methods described above include a display and displaying the 12-lead electrocardiogram on a display screen. Similarly, the systems and methods described above can include a printer and printing the 12-lead electrocardiogram. In yet another embodiment, the methods and systems described above include saving the 12-lead electrocardiogram to a storage memory of the portable computing device **11**.

In order to further illustrate the present invention, the following examples are given. However, it is to be understood that the examples are for illustrative purposes only and are not to be construed as limiting the scope of the invention.

Example 1

The above-described system was tested on 121 patients in a clinical trial. Each patient was monitored using the conventional 10 electrodes, i.e., placing 6 electrodes on the patient's chest and one electrode on each of the patient's arms and legs. A conventional 12-lead electrocardiogram report was then prepared for each patient using a traditional stationary electrocardiograph sold under the trademark GE® MAC3500.

The electrocardiograph device **10-1** having the first and second electrodes **14** and **18** in a pen-type configuration was tested on each patient and a conventional format 8-lead report was prepared from the sequential measurements. The 2-electrode electrocardiograph calculated the V1-V6 leads using the right hand (RA) for the negative terminal and then the left hand (LA) for the negative terminal. A statistical analysis was made comparing the 2-electrode electrocardiograph results with the traditional 10-electrode electrocardiograph results.

12

FIG. **8** compares V1 for Subject 35 having the highest correlation between the 10-electrode and the 2-electrode measurements. A correlation coefficient of 0.99 was achieved.

FIG. **9** shows each of the 8 leads for Subject 35, comparing the 10-electrode results with the 2-electrode results. The correlation coefficient averaged over all of the leads was 0.988.

From the above descriptions, it is clear that the presently disclosed and claimed inventive concepts are well-adapted to carry out the objects and to attain the advantages mentioned herein, as well as those inherent in the presently disclosed and claimed inventive concept. While the presented embodiments have been described for purposes of this disclosure, it will be understood that numerous changes may be made which will readily suggest themselves to those skilled in the art and which are accomplished within the spirit of the presently disclosed and claimed inventive concepts.

What is claimed is:

1. An electrocardiograph comprising:

an electrocardiograph device having (a) a first electrode assembly with a first electrode adapted to measure an electrical signal on a patient's body; (b) a second electrode assembly with a second electrode adapted to measure an electrical signal on the patient's body; (c) control circuitry configured to measure electrocardiogram signals between the first and second electrodes; and (d) a data transmission module configured to transmit the measured electrocardiogram signals to a computing device; and

a computing device having a non-transitory computer-readable storage medium storing software that includes instructions that when executed by a processor causes the processor to (a) calculate an average PQRST beat from the measured electrocardiogram signals as the first and second electrodes are sequentially placed in Limb Lead I, II, and III positions on a patient's body for a time required to measure at least one heartbeat in each Limb Lead position, the Limb Lead positions known by the processor; (b) use the relationship (Lead III=Lead II-Lead I) to time-align and display Limb Leads I, II, and III; and (c) calculate and display augmented Leads aVR, aVL, and aVF from the time-aligned Limb Leads.

2. The electrocardiograph of claim 1, wherein software further includes instructions that when executed by the processor causes the processor to (d) calculate and display average Leads V1, V2, and V3 from the measured electrocardiogram signals obtained from sequentially placing one of the first and second electrodes in a V1, V2, and V3 position while contacting the other of the first and second electrodes with a left arm of the patient for a time required to measure at least one heart beat; and (e) calculate and display average Leads V4, V5, and V6 from the measured electrocardiogram signals obtained from sequentially placing one of the first and second electrodes in a V4, V5, and V6 position while contacting the other of the first and second electrodes with a right arm of the patient for a time required to measure at least one heartbeat.

3. The electrocardiograph of claim 1 or 2, wherein the data transmission module is configured to transmit the measured electrocardiogram signals to the computing device by wire.

4. The electrocardiograph of claim 1 or 2, wherein the data transmission module is configured to transmit the measured electrocardiogram signals to the computing device wirelessly.

5. The electrocardiograph of claim 1 or 2, wherein at least one of the first and second electrode assemblies comprises a spring-hinged cuff.

13

6. The electrocardiograph of claim 1 or 2, wherein at least one of the first and second electrode assemblies comprises a disposable electrode.

7. The electrocardiograph device of claim 1 or 2, wherein the portable computing device is a smartphone and the electrocardiograph device further comprises a housing for the control circuitry and the data transmission module, the housing adapted to fit onto or within a protective case for the smartphone.

8. The electrocardiograph device of claim 1 or 2, wherein the data transmission module is further configured to transmit the measured ECG signals as ultrasonic, frequency modulated (FM) sound signals.

9. The electrocardiograph device of claim 1 or 2, wherein the data transmission module is further configured to encrypt and transmit encrypted signals.

10. A non-transitory computer-readable storage medium storing software that includes instructions that when executed by a processor causes the processor to:

receive and record electrocardiogram signals between a first electrode and a second electrode, the first and second electrodes sequentially placed in predetermined paired positions on a patient's body for a time required to measure at least one heartbeat, the paired positions known by the processor and corresponding to Limb Leads I, II and III, and V1, V2, V3, V4, V5, and V6;

for each Limb Lead paired position, determine electrocardiogram signal sets representing a heartbeat and calculate average time-aligned heartbeat representations for Limb Leads I, II and III; and

calculate augmented leads aVR, aVL, and aVF from the average time-aligned heartbeat representations for Limb Leads I, II, and III and output the electrocardiogram signals in a 12-lead electrocardiogram format.

11. The non-transitory computer-readable storage medium of claim 10, wherein the electrocardiogram signals analyzed comprise at least one of wired electrical signals, wireless electromagnetic signals, and acoustic sound signals.

12. The non-transitory computer-readable storage medium of claim 10, wherein the set of instructions, when executed by the processor, further causes the processor to digitize and demodulate frequency modulated electrocardiogram acoustic signals.

13. The non-transitory computer-readable storage medium of claim 10, wherein the set of instructions, when executed by the processor, further causes the processor to interact with a user to identify first and second electrode paired positions corresponding to a lead.

14. The non-transitory computer-readable storage medium of claim 10, wherein the set of instructions, when executed by the processor, further causes the processor to (a) provide instructions to a user or request placement confirmation from the user regarding contacting the first electrode to the patient's left arm and the second electrode to the patient's right arm, wherein the electrical signal measured between the left arm and right arm corresponds to Lead I in a 12-lead electrocardiogram, and (b) analyze the electrical signal corresponding to Lead I to calculate an average heartbeat representation for Lead I.

15. The non-transitory computer-readable storage medium of claim 14, wherein the set of instructions, when executed by the processor, further causes the processor to (c) provide instructions to a user or request placement confirmation from the user regarding contacting the first electrode to the patient's left leg and the second electrode to the patient's right arm, wherein the electrical signal measured between the left leg and right arm corresponds to Lead II in a 12-lead electro-

14

cardiogram, and (d) analyze the electrical signal corresponding to Lead II to calculate an average heartbeat representation for Lead II.

16. The non-transitory computer-readable storage medium of claim 15, wherein the set of instructions, when executed by the processor, further causes the processor to (e) provide instructions to a user or request placement confirmation from the user regarding contacting the first electrode to the patient's left leg and the second electrode to the patient's left arm, wherein the electrical signal measured between the left leg and left arm corresponds to Lead III in a 12-lead electrocardiogram, and (f) analyze the electrical signal corresponding to Lead III to calculate an average heartbeat representation for Lead III.

17. The non-transitory computer-readable storage medium of claim 16, wherein the set of instructions, when executed by the processor, further causes the processor to time-align the average heartbeat representations for Lead I and Lead II and calculate aVR, aVL, and aVF average heartbeat representations from the time-aligned average heartbeat representations for Lead I and Lead II.

18. The non-transitory computer-readable storage medium of claim 17, wherein the set of instructions, when executed by the processor, further causes the processor to (g) provide instructions to a user or request placement confirmation from the user regarding contacting the first electrode with each of the V1, V2, V3, V4, V5, and V6 chest locations while contacting the second electrode to one of the patient's left arm and the patient's right arm, wherein the electrical signals measured between each of the V1, V2, V3, V4, V5, and V6 chest locations and the left arm or the right arm correspond to Leads V1, V2, V3, V4, V5, and V6 in a 12-lead electrocardiogram, and (h) analyze the electrical signals corresponding to Leads V1, V2, V3, V4, V5, and V6 to calculate average heartbeat representations for Leads V1, V2, V3, V4, V5, and V6.

19. The non-transitory computer-readable storage medium of claim 18, wherein the left arm is used for Leads V1, V2, and V3 and the right arm is used for Leads V4, V5, and V6.

20. The non-transitory computer-readable storage medium of claim 18, wherein the right arm is used for each of Leads V1, V2, V3, V4, V5, and V6.

21. The non-transitory computer-readable storage medium of claim 18, wherein the set of instructions, when executed by the processor, further causes the processor to (i) output the average heartbeat representations for Leads I, II, III, aVR, aVL, aVF, V1, V2, V3, V4, V5, and V6.

22. A method for generating a 12-lead electrocardiogram using an electrocardiograph comprising an electrocardiograph device and a portable computing device, the method comprising:

operating a portable computing device and an ECG device having a first electrode, a second electrode, control circuitry, and a data transmission module, the control circuitry configured to measure ECG signals between the first and second electrodes, the data transmission module configured to transmit the measured ECG signals to the portable computing device;

sequentially measuring ECG signals between the first and second electrodes positioned at predetermined locations on a patient's body; and
using the portable computing device to generate a 12-lead ECG from the sequentially measured ECG signals between the first and second electrodes.

23. The method of claim 22, wherein the step of sequentially measuring ECG signals comprises:

contacting one of the first and second electrodes with a left arm of a patient while contacting the other of the first and

15

second electrodes with a right arm of the patient to measure an electrical signal corresponding to a Lead I; contacting one of the first and second electrodes with a left leg of the patient while contacting the other of the first and second electrodes with the right arm of the patient to measure an electrical signal corresponding to a Lead II; contacting one of the first and second electrodes with the left leg of the patient while contacting the other of the first and second electrodes with the left arm of the patient to measure an electrical signal corresponding to a Lead III;

sequentially contacting one of the first and second electrodes with a V1, V2, V3, V4, V5, and V6 chest location on the patient while contacting the other of the first and second electrodes with the patient's left arm or the patient's right arm to measure electrical signals corresponding to a Leads V1, V2, V3, V4, V5, and V6, respectively.

24. The method of claim **22**, wherein the step of sequentially measuring ECG signals comprises:

contacting one the first and second electrodes with a left arm of a patient while contacting the other of the first and second electrodes with a right arm of the patient to measure an electrical signal corresponding to a Lead I; contacting one of the first and second electrodes with a left leg of the patient while contacting the other of the first and second electrodes with the right arm of the patient to measure an electrical signal corresponding to a Lead II; contacting one of the first and second electrodes with the left leg of the patient while contacting the other of the first and second electrodes with the left arm of the patient to measure an electrical signal corresponding to a Lead III;

sequentially contacting one of the first and second electrodes with a V1, V2, and V3 chest location on the patient while contacting the other of the first and second electrodes with the left arm of the patient to measure electrical signals corresponding to Leads V1, V2, and V3, respectively; and

sequentially contacting one of the first and second electrodes with a V4, V5 and V6 chest location on the patient while contacting the other of the first and second electrodes with the right arm of the patient to measure electrical signals corresponding to Leads V4, V5, and V6, respectively.

25. The method of claim **24**, further comprising using the portable computing device to time-align the average heartbeat representations for Lead I and Lead II, and calculate aVR, aVL, and aVF from the time-aligned average heartbeat representations for Lead I and Lead II.

26. The method of claim **25**, further comprising using the portable computing device to output the ECG signals in a 12-lead ECG format.

27. A system for generating a 12-lead ECG using two electrodes comprising:

a first electrode assembly having a first electrode adapted to measure an electrical signal on a patient's body;

a second electrode assembly configured to removably attach to an upper limb of the patient, the second electrode assembly having a second electrode adapted to measure an electrical signal on the patient's body;

control circuitry configured to measure ECG signals between the first and second electrodes;

a data transmission module configured to transmit the measured ECG signals to a portable computing device; and

a non-transitory computer-readable storage medium storing a set of instructions capable of being executed by one

16

or more computing devices, that when executed by the one or more computing devices causes the one or more computing devices to: (a) analyze ECG signals between a first electrode and a second electrode, the first and second electrodes sequentially placed in predetermined paired positions on a patient's body; (b) average the ECG signals for each paired position to calculate average heartbeat representations for each paired position; and (c) time-align the average heartbeat representations to output in a 12-lead ECG format.

28. The system of claim **27**, wherein the first electrode assembly is configured to be hand held.

29. The system of claim **27**, wherein the second electrode assembly comprises a spring-hinged cuff.

30. The system of claim **27**, wherein the set of instructions, when executed by the one or more computing devices, further causes the one or more computing devices to interact with a user to identify first and second electrode paired positions corresponding to a lead.

31. The system of claim **27**, wherein the set of instructions, when executed by the one or more computing devices, further causes the one or more computing devices to (a) provide instructions to a user or request placement confirmation from the user regarding contacting the first electrode to the patient's left arm and the second electrode to the patient's right arm, wherein the electrical signal measured between the left arm and right arm corresponds to Lead I in a 12-lead ECG, and (b) analyze the electrical signal corresponding to Lead I to calculate an average heartbeat representation for Lead I.

32. The system of claim **31**, wherein the set of instructions, when executed by the one or more computing devices, further causes the one or more computing devices to (c) provide instructions to a user or request placement confirmation from the user regarding contacting the first electrode to the patient's left leg and the second electrode to the patient's right arm, wherein the electrical signal measured between the left arm and right arm corresponds to Lead II in a 12-lead ECG, and (d) analyze the electrical signal corresponding to Lead II to calculate an average heartbeat representation for Lead II.

33. The system of claim **32**, wherein the set of instructions, when executed by the one or more computing devices, further causes the one or more computing devices to (e) provide instructions to a user or request placement confirmation from the user regarding contacting the first electrode to the patient's left leg and the second electrode to the patient's left arm, wherein the electrical signal measured between the left arm and right arm corresponds to Lead III in a 12-lead ECG, and (f) analyze the electrical signal corresponding to Lead III to calculate an average heartbeat representation for Lead III.

34. The system of claim **33**, wherein the set of instructions, when executed by the one or more computing devices, further causes the one or more computing devices to time-align the average heartbeat representations for Lead I and Lead II and calculate aVR, aVL, and aVF from the time-aligned average heartbeat representations for Lead I and Lead II.

35. The system of claim **34**, wherein the set of instructions, when executed by the one or more computing devices, further causes the one or more computing devices to (g) provide instructions to a user or request placement confirmation from the user regarding contacting the first electrode with each of the V1, V2, V3, V4, V5, and V6 chest locations while contacting the second electrode to one of the patient's left arm and the patient's right arm, wherein the electrical signals measured between each of the V1, V2, V3, V4, V5, and V6 chest locations and the left arm or the right arm correspond to Leads V1, V2, V3, V4, V5, and V6 in a 12-lead ECG, and (h) analyze the electrical signals corresponding to Leads V1, V2, V3, V4,

17

V5, and V6 to calculate average heartbeat representations for Leads V1, V2, V3, V4, V5, and V6.

36. The system of claim **35**, wherein the left arm is used for Leads V1, V2, and V3 and the right arm is used for Leads V4, V5, and V6.

5

* * * * *

18

专利名称(译)	用于十二导联ECG的两个电极设备和方法		
公开(公告)号	US9351654	公开(公告)日	2016-05-31
申请号	US14/254310	申请日	2014-04-16
[标]申请(专利权)人(译)	阿利弗克公司		
申请(专利权)人(译)	ALIVECOR INC.		
当前申请(专利权)人(译)	ALIVECOR INC.		
[标]发明人	ALBERT DAVID E		
发明人	ALBERT, DAVID E.		
IPC分类号	A61B5/00 A61B5/0404 G06Q50/22 A61B5/0402 A61B5/0408 A61B5/0432 A61B5/044 A61B5/0452 A61B5/0205		
CPC分类号	A61B5/0404 A61B5/0006 A61B5/0015 A61B5/0022 A61B5/044 A61B5/0408 A61B5/04028 A61B5/0432 A61B5/6898 G06Q50/22 A61B5/0205 A61B5/0452 G16H40/60 A61B5/002 A61B5/0245 A61B5/04012		
代理机构(译)	WILSON SONSINI盈丰 & ROSATI		
优先权	61/812655 2013-04-16 US		
其他公开文献	US20140228665A1		
外部链接	Espacenet USPTO		

摘要(译)

本文描述了用于患者的心脏监测的方法，装置和系统。心脏监测系统可以用于仅使用两个电极来进行心电图（ECG）。手持式设备可以用于顺序地测量患者身体上不同位置之间的电信号。可以处理和分析电信号以为患者准备ECG，包括12导联ECG。

