



US010610158B2

(12) **United States Patent**
Aumer et al.

(10) **Patent No.: US 10,610,158 B2**
(45) **Date of Patent: Apr. 7, 2020**

(54) **PHYSIOLOGICAL MONITORING DEVICES
AND METHODS THAT IDENTIFY SUBJECT
ACTIVITY TYPE**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **Valencell, Inc.**, Raleigh, NC (US)

3,595,219 A 7/1971 Friedlander et al.
4,240,882 A 12/1980 Ang et al.
(Continued)

(72) Inventors: **Michael Edward Aumer**, Raleigh, NC
(US); **Steven Francis LeBoeuf**,
Raleigh, NC (US)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Valencell, Inc.**, Raleigh, NC (US)

AU 2015101130 10/2015
CN 101212927 A 7/2008
(Continued)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 302 days.

OTHER PUBLICATIONS

(21) Appl. No.: **15/299,684**

Han et al., "Artifacts in wearable photoplethysmographs during
daily life motions and their reduction with least mean square based
active noise cancellation method", *Computers in Biology and
Medicine*, vol. 42, Apr. 2012, pp. 387-393.

(22) Filed: **Oct. 21, 2016**

(Continued)

(65) **Prior Publication Data**

US 2017/0112447 A1 Apr. 27, 2017

Primary Examiner — Gary Jackson

Assistant Examiner — Zahed Kabir

(74) *Attorney, Agent, or Firm* — Myers Bigel, P.A.

(57)

ABSTRACT

Methods and apparatus for monitoring a subject are
described. A monitoring device configured to be attached to
a body of a subject includes a sensor that is configured to
detect and/or measure physiological information from the
subject and a motion sensor configured to detect and/or
measure subject motion information. The physiological sen-
sor and motion sensor are in communication with a proces-
sor that is configured to receive and analyze signals pro-
duced by the physiological sensor and motion sensor. The
processor is configured to process motion sensor signals to
identify an activity characteristic of the subject. Once an
activity characteristic is determined, the processor is con-
figured to select a biometric signal extraction algorithm or
circuit in response to the activity characteristic of the
subject, and then process physiological sensor signals via
the biometric signal extraction algorithm or circuit to pro-
duce physiological information about the subject.

Related U.S. Application Data


(60) Provisional application No. 62/245,919, filed on Oct.
23, 2015.

(51) **Int. Cl.**
A61B 5/00 (2006.01)
A61B 5/0205 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 5/721** (2013.01); **A61B 5/0205**
(2013.01); **A61B 5/6817** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC ... A61B 5/0205; A61B 5/6817; A61B 5/7278;
A61B 5/021; A61B 5/02405;
(Continued)

14 Claims, 10 Drawing Sheets



- (51) **Int. Cl.**
A61B 5/021 (2006.01)
A61B 5/024 (2006.01)
A61B 5/08 (2006.01)
A61B 5/11 (2006.01)
A61B 5/145 (2006.01)
- (52) **U.S. Cl.**
 CPC *A61B 5/7278* (2013.01); *A61B 5/021* (2013.01); *A61B 5/02405* (2013.01); *A61B 5/02416* (2013.01); *A61B 5/02438* (2013.01); *A61B 5/0816* (2013.01); *A61B 5/1118* (2013.01); *A61B 5/145* (2013.01); *A61B 5/6815* (2013.01); *A61B 5/6831* (2013.01); *A61B 5/7257* (2013.01); *A61B 2562/0219* (2013.01)
- (58) **Field of Classification Search**
 CPC *A61B 5/02416*; *A61B 5/02438*; *A61B 5/0816*; *A61B 5/1118*; *A61B 5/145*; *A61B 5/6815*; *A61B 5/6831*; *A61B 5/7257*; *A61B 2562/0219*; *A61B 5/721*
 USPC 600/301, 479, 519, 513, 515, 518
 See application file for complete search history.
- (56) **References Cited**
 U.S. PATENT DOCUMENTS
- | | | | | | |
|-------------|---------|-------------------|--------------|---------|--------------------|
| 4,281,645 A | 8/1981 | Jobsis | 5,807,267 A | 9/1998 | Bryars et al. |
| 4,331,154 A | 5/1982 | Broadwater et al. | 5,817,008 A | 10/1998 | Rafert et al. |
| 4,438,772 A | 3/1984 | Slavin | 5,820,560 A | 10/1998 | Sinderby et al. |
| 4,491,760 A | 1/1985 | Linville | 5,846,190 A | 12/1998 | Woehrle |
| 4,521,499 A | 6/1985 | Switzer | 5,853,005 A | 12/1998 | Scanlon |
| 4,541,905 A | 9/1985 | Kuwana et al. | 5,904,654 A | 5/1999 | Wohlmann et al. |
| 4,586,513 A | 5/1986 | Hamaguri | 5,938,593 A | 8/1999 | Quellette |
| 4,592,807 A | 6/1986 | Switzer | 5,954,644 A | 9/1999 | Dettling et al. |
| 4,655,225 A | 4/1987 | Dahne et al. | 5,964,701 A | 10/1999 | Asada et al. |
| 4,830,014 A | 5/1989 | Goodman et al. | 5,971,931 A | 10/1999 | Raff |
| 4,882,492 A | 11/1989 | Schlager | 5,974,338 A | 10/1999 | Asano et al. |
| 4,896,676 A | 1/1990 | Sasaki | 5,995,858 A | 11/1999 | Kinast |
| 4,928,704 A | 5/1990 | Hardt | 6,004,274 A | 12/1999 | Nolan et al. |
| 4,952,890 A | 8/1990 | Swanson | 6,006,119 A | 12/1999 | Soller et al. |
| 4,952,928 A | 8/1990 | Carroll et al. | 6,013,007 A | 1/2000 | Root et al. |
| 4,957,109 A | 9/1990 | Groeger et al. | 6,022,748 A | 2/2000 | Charych et al. |
| 5,002,060 A | 3/1991 | Nedivi | 6,023,541 A | 2/2000 | Merchant et al. |
| 5,022,970 A | 6/1991 | Cook et al. | 6,030,342 A | 2/2000 | Amano et al. |
| 5,025,791 A | 6/1991 | Niwa | 6,045,511 A | 4/2000 | Ott et al. |
| 5,079,421 A | 1/1992 | Knudson et al. | 6,067,006 A | 5/2000 | O'Brien |
| 5,080,098 A | 1/1992 | Willett et al. | 6,070,093 A | 5/2000 | Oosta et al. |
| 5,086,229 A | 2/1992 | Rosenthal et al. | 6,078,829 A | 6/2000 | Uchida et al. |
| 5,139,025 A | 8/1992 | Lewis et al. | 6,080,110 A | 6/2000 | Thorgersen |
| 5,143,078 A | 9/1992 | Mather et al. | 6,081,742 A | 6/2000 | Amano et al. |
| 5,226,417 A | 7/1993 | Swedlow et al. | 6,122,042 A | 9/2000 | Wunderman et al. |
| 5,237,994 A | 8/1993 | Goldberger | 6,148,229 A | 11/2000 | Morris, Sr. et al. |
| 5,299,570 A | 4/1994 | Hatschek | 6,155,983 A | 12/2000 | Kosuda et al. |
| 5,348,002 A | 9/1994 | Caro | 6,168,567 B1 | 1/2001 | Pickering et al. |
| 5,377,100 A | 12/1994 | Pope et al. | 6,186,145 B1 | 2/2001 | Brown |
| 5,386,819 A | 2/1995 | Kaneko et al. | 6,198,394 B1 | 3/2001 | Jacobsen et al. |
| 5,431,170 A | 7/1995 | Mathews | 6,198,951 B1 | 3/2001 | Kosuda et al. |
| 5,448,082 A | 9/1995 | Kim | 6,205,354 B1 | 3/2001 | Gellermann et al. |
| 5,482,036 A | 1/1996 | Diab et al. | 6,231,519 B1 | 5/2001 | Blants et al. |
| 5,492,129 A | 2/1996 | Greenberger | 6,267,721 B1 | 7/2001 | Welles |
| 5,494,043 A | 2/1996 | O'Sullivan et al. | 6,283,915 B1 | 9/2001 | Aceti et al. |
| 5,499,301 A | 3/1996 | Sudo et al. | 6,285,816 B1 | 9/2001 | Anderson et al. |
| 5,581,648 A | 12/1996 | Sahagen | 6,289,230 B1 | 9/2001 | Chaiken et al. |
| 5,596,987 A | 1/1997 | Chance | 6,298,314 B1 | 10/2001 | Blackadar et al. |
| 5,662,117 A | 9/1997 | Bittman | 6,332,868 B1 | 12/2001 | Sato et al. |
| 5,673,692 A | 10/1997 | Schulze et al. | 6,358,216 B1 | 3/2002 | Kraus et al. |
| 5,697,374 A | 12/1997 | Odagiri et al. | 6,361,660 B1 | 3/2002 | Goldstein |
| 5,711,308 A | 1/1998 | Singer | 6,371,925 B1 | 4/2002 | Imai et al. |
| 5,725,480 A | 3/1998 | Oosta et al. | 6,374,129 B1 | 4/2002 | Chin et al. |
| 5,743,260 A | 4/1998 | Chung et al. | 6,415,167 B1 | 7/2002 | Blank et al. |
| 5,779,631 A | 7/1998 | Chance | 6,443,890 B1 | 9/2002 | Schulze et al. |
| 5,797,841 A | 8/1998 | Delonzor et al. | 6,444,474 B1 | 9/2002 | Thomas et al. |
| 5,807,114 A | 9/1998 | Hodges et al. | 6,454,718 B1 | 9/2002 | Clift |
| | | | 6,458,080 B1 | 10/2002 | Brown et al. |
| | | | 6,470,893 B1 | 10/2002 | Boesen |
| | | | 6,513,532 B2 | 2/2003 | Mault et al. |
| | | | 6,514,278 B1 | 2/2003 | Hibst et al. |
| | | | 6,527,711 B1 | 3/2003 | Stivorice et al. |
| | | | 6,527,712 B1 | 3/2003 | Brown et al. |
| | | | 6,529,754 B2 | 3/2003 | Kondo |
| | | | 6,534,012 B1 | 3/2003 | Hazen et al. |
| | | | 6,556,852 B1 | 4/2003 | Schulze et al. |
| | | | 6,569,094 B2 | 5/2003 | Suzuki et al. |
| | | | 6,571,117 B1 | 5/2003 | Marbach |
| | | | 6,605,038 B1 | 8/2003 | Teller et al. |
| | | | 6,608,562 B1 | 8/2003 | Kimura et al. |
| | | | 6,616,613 B1 | 9/2003 | Goodman |
| | | | 6,631,196 B1 | 10/2003 | Taenzer et al. |
| | | | 6,647,378 B2 | 11/2003 | Kindo |
| | | | 6,656,116 B2 | 12/2003 | Kim et al. |
| | | | 6,694,180 B1 | 2/2004 | Boesen |
| | | | 6,702,752 B2 | 3/2004 | Dekker |
| | | | 6,725,072 B2 | 4/2004 | Steuer et al. |
| | | | 6,745,061 B1 | 6/2004 | Hicks et al. |
| | | | 6,748,254 B2 | 6/2004 | O'Neil et al. |
| | | | 6,760,610 B2 | 7/2004 | Tschupp et al. |
| | | | 6,783,501 B2 | 8/2004 | Takahashi et al. |
| | | | 6,808,473 B2 | 10/2004 | Hisano et al. |
| | | | 6,859,658 B1 | 2/2005 | Krug |
| | | | 6,893,396 B2 | 5/2005 | Schulze et al. |
| | | | 6,941,239 B2 | 9/2005 | Unuma et al. |
| | | | 6,953,435 B2 | 10/2005 | Kondo et al. |
| | | | 6,954,644 B2 | 10/2005 | Johansson et al. |
| | | | 6,996,427 B2 | 2/2006 | Ali et al. |
| | | | 6,997,879 B1 | 2/2006 | Turcott |

(56)

References Cited

U.S. PATENT DOCUMENTS

7,018,338 B2	3/2006	Vetter et al.	8,730,048 B2	5/2014	Shen et al.
7,024,369 B1	4/2006	Brown et al.	8,788,002 B2	7/2014	LeBoeuf et al.
7,030,359 B2	4/2006	Römhild	8,886,269 B2	11/2014	LeBoeuf et al.
7,034,694 B2	4/2006	Yamaguchi et al.	8,888,701 B2	11/2014	LeBoeuf et al.
7,039,454 B1	5/2006	Kaga et al.	8,923,941 B2	12/2014	LeBoeuf et al.
7,041,062 B2	5/2006	Friedrichs et al.	8,929,965 B2	1/2015	LeBoeuf et al.
7,043,287 B1	5/2006	Khalil et al.	8,929,966 B2	1/2015	LeBoeuf et al.
7,048,687 B1	5/2006	Reuss et al.	8,934,952 B2	1/2015	LeBoeuf et al.
7,054,674 B2	5/2006	Cane et al.	8,942,776 B2	1/2015	LeBoeuf et al.
7,088,234 B2	8/2006	Naito et al.	8,961,415 B2	2/2015	LeBoeuf et al.
7,107,088 B2	9/2006	Aceti	9,005,129 B2	4/2015	Venkatraman
7,113,815 B2	9/2006	O'Neil et al.	9,044,180 B2	6/2015	Leboeuf et al.
7,117,032 B2	10/2006	Childre et al.	9,289,175 B2	3/2016	Leboeuf et al.
7,144,375 B2	12/2006	Kosuda	9,801,552 B2	10/2017	Romesburg
7,163,512 B1	1/2007	Childre et al.	9,808,204 B2	11/2017	Leboeuf et al.
7,175,601 B2	2/2007	Verjus et al.	9,943,266 B2	4/2018	Adams et al.
7,190,986 B1	3/2007	Hannula et al.	2001/0015123 A1	8/2001	Nishitani et al.
7,209,775 B2	4/2007	Bae et al.	2001/0044588 A1	11/2001	Mault
7,217,224 B2	5/2007	Thomas	2001/0049471 A1	12/2001	Suzuki et al.
7,252,639 B2	8/2007	Kimura et al.	2002/0035340 A1	3/2002	Fraden et al.
7,263,396 B2	8/2007	Chen et al.	2002/0143242 A1	10/2002	Nemirovski
7,289,837 B2	10/2007	Mannheimer et al.	2002/0156386 A1	10/2002	Dardik et al.
7,336,982 B2	2/2008	Yoo et al.	2002/0156654 A1	10/2002	Roe et al.
7,341,559 B2	3/2008	Schulz et al.	2002/0173780 A1	11/2002	Altshuler et al.
7,376,451 B2	5/2008	Mahony et al.	2002/0186137 A1	12/2002	Skardon
7,378,954 B2	5/2008	Wendt	2002/0188210 A1	12/2002	Aizawa
7,470,234 B1	12/2008	Elhag et al.	2002/0194002 A1	12/2002	Petrushin
7,483,730 B2	1/2009	Diab et al.	2003/0002705 A1	1/2003	Boesen
7,486,988 B2	2/2009	Goodall et al.	2003/0007631 A1	1/2003	Bolognesi et al.
7,507,207 B2	3/2009	Sakai et al.	2003/0045785 A1	3/2003	Diab et al.
7,519,327 B2	4/2009	White	2003/0050563 A1	3/2003	Suribhotla et al.
7,526,327 B2	4/2009	Blondeau et al.	2003/0064712 A1	4/2003	Gaston et al.
7,583,994 B2	9/2009	Scholz	2003/0065257 A1	4/2003	Mault et al.
7,620,450 B2	11/2009	Kim et al.	2003/0065269 A1	4/2003	Vetter et al.
7,625,285 B2	12/2009	Breving	2003/0083583 A1	5/2003	Kovtun et al.
7,652,569 B2	1/2010	Kiff et al.	2003/0109030 A1	6/2003	Uchida et al.
7,689,437 B1	3/2010	Teller et al.	2003/0109791 A1	6/2003	Kondo et al.
7,695,440 B2	4/2010	Kondo et al.	2003/0130586 A1 *	7/2003	Starobin A61B 5/0464 600/515
7,725,147 B2	5/2010	Li et al.	2003/0181795 A1	9/2003	Suzuki et al.
7,756,559 B2	7/2010	Abreu	2003/0181798 A1	9/2003	Al-Ali
7,843,325 B2	11/2010	Otto	2003/0181817 A1	9/2003	Mori
7,894,869 B2	2/2011	Hoarau	2003/0212336 A1	11/2003	Lee et al.
7,914,468 B2	3/2011	Shalon et al.	2003/0220584 A1	11/2003	Honeyager et al.
7,991,448 B2	8/2011	Edgar et al.	2003/0222268 A1	12/2003	Yocom et al.
7,998,079 B2	8/2011	Nagai et al.	2003/0233051 A1	12/2003	Verjus et al.
8,050,728 B2	11/2011	Al-Ali et al.	2004/0004547 A1	1/2004	Appelt et al.
8,055,319 B2	11/2011	Oh et al.	2004/0022700 A1	2/2004	Kim et al.
8,055,330 B2	11/2011	Egozi	2004/0030581 A1	2/2004	Leven
8,059,924 B1	11/2011	Letant et al.	2004/0034289 A1	2/2004	Teller et al.
8,130,105 B2	3/2012	Al-Ali et al.	2004/0034293 A1	2/2004	Kimball
8,137,270 B2	3/2012	Keenan et al.	2004/0039254 A1	2/2004	Stivorice et al.
8,157,730 B2	4/2012	LeBoeuf et al.	2004/0054291 A1	3/2004	Schulz et al.
8,172,459 B2	5/2012	Abreu	2004/0073455 A1	4/2004	McConnochie et al.
8,175,670 B2	5/2012	Baker, Jr. et al.	2004/0075677 A1	4/2004	Loyall et al.
8,204,730 B2	6/2012	Liu et al.	2004/0077934 A1	4/2004	Marsad
8,204,786 B2	6/2012	LeBoeuf et al.	2004/0081621 A1	4/2004	Arndt et al.
8,233,955 B2	7/2012	Al-Ali et al.	2004/0082842 A1	4/2004	Lumba et al.
8,251,903 B2	8/2012	LeBoeuf et al.	2004/0097796 A1	5/2004	Berman et al.
8,255,027 B2	8/2012	Al-Ali et al.	2004/0103146 A1	5/2004	Park
8,255,029 B2	8/2012	Addison et al.	2004/0117204 A1	6/2004	Mazar et al.
8,303,512 B2	11/2012	Kosuda et al.	2004/0120844 A1	6/2004	Tribelsky et al.
8,320,982 B2	11/2012	LeBoeuf et al.	2004/0122294 A1	6/2004	Hatlestad et al.
8,323,982 B2	12/2012	LeBoeuf et al.	2004/0122702 A1	6/2004	Sabol et al.
8,328,420 B2	12/2012	Abreu	2004/0133123 A1	7/2004	Leonhardt et al.
8,416,959 B2	4/2013	Lott et al.	2004/0135571 A1	7/2004	Uutela et al.
8,491,492 B2	7/2013	Shinar et al.	2004/0138578 A1	7/2004	Pineda et al.
8,504,679 B2	8/2013	Spire et al.	2004/0158167 A1	8/2004	Smith et al.
8,506,524 B2	8/2013	Graskov et al.	2004/0186387 A1	9/2004	Kosuda et al.
8,512,242 B2	8/2013	LeBoeuf et al.	2004/0186390 A1	9/2004	Ross et al.
8,647,270 B2	2/2014	LeBoeuf et al.	2004/0219056 A1	11/2004	Tribelsky et al.
8,652,040 B2	2/2014	LeBoeuf et al.	2004/0220488 A1	11/2004	Vyshedskiy et al.
8,652,409 B2	2/2014	LeBoeuf et al.	2004/0225207 A1	11/2004	Bae et al.
8,679,008 B2	3/2014	Hughes et al.	2004/0228494 A1	11/2004	Smith
8,700,111 B2	4/2014	LeBoeuf et al.	2004/0242976 A1	12/2004	Abreu
8,702,607 B2	4/2014	LeBoeuf et al.	2004/0254501 A1	12/2004	Mault
			2005/0004458 A1	1/2005	Kanayama et al.
			2005/0007582 A1	1/2005	Villers et al.
			2005/0021519 A1	1/2005	Ghouri

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0027216 A1	2/2005	Guillemaud et al.	2007/0060800 A1	3/2007	Drinan et al.
2005/0030540 A1	2/2005	Thornton	2007/0060819 A1	3/2007	Altschuler et al.
2005/0033200 A1	2/2005	Soehren et al.	2007/0063850 A1	3/2007	Devaux et al.
2005/0036212 A1	2/2005	Saito	2007/0082789 A1	4/2007	Nissila et al.
2005/0038349 A1	2/2005	Choi et al.	2007/0083092 A1	4/2007	Rippo et al.
2005/0043600 A1	2/2005	Diab et al.	2007/0083095 A1	4/2007	Rippo et al.
2005/0043630 A1	2/2005	Buchert et al.	2007/0088221 A1	4/2007	Stahmann
2005/0058456 A1	3/2005	Yoo	2007/0093702 A1	4/2007	Yu et al.
2005/0059870 A1	3/2005	Aceti	2007/0106167 A1	5/2007	Kinast
2005/0070809 A1	3/2005	Acres	2007/0112273 A1	5/2007	Rogers
2005/0084666 A1	4/2005	Pong et al.	2007/0112598 A1	5/2007	Heckerman et al.
2005/0100866 A1	5/2005	Arnone et al.	2007/0116314 A1	5/2007	Grilliot et al.
2005/0101845 A1	5/2005	Nihtila	2007/0118043 A1	5/2007	Oliver et al.
2005/0101872 A1	5/2005	Sattler et al.	2007/0123763 A1	5/2007	Al-Ali et al.
2005/0113167 A1	5/2005	Buchner et al.	2007/0135717 A1	6/2007	Uenishi et al.
2005/0113656 A1	5/2005	Chance	2007/0165872 A1	7/2007	Bridger et al.
2005/0113703 A1	5/2005	Farrington et al.	2007/0167850 A1	7/2007	Russell et al.
2005/0116820 A1	6/2005	Goldreich	2007/0191718 A1	8/2007	Nakamura
2005/0119833 A1	6/2005	Nanikashvili	2007/0197878 A1	8/2007	Shklarski
2005/0148883 A1	7/2005	Boesen	2007/0197881 A1	8/2007	Wolf et al.
2005/0154264 A1	7/2005	Lecompte et al.	2007/0213020 A1	9/2007	Novac
2005/0177034 A1	8/2005	Beaumont	2007/0230714 A1	10/2007	Armstrong
2005/0187448 A1	8/2005	Petersen et al.	2007/0233403 A1	10/2007	Alwan et al.
2005/0187453 A1	8/2005	Petersen et al.	2007/0265097 A1	11/2007	Havukainen
2005/0192515 A1	9/2005	Givens et al.	2007/0270667 A1	11/2007	Coppi et al.
2005/0196009 A1	9/2005	Boesen	2007/0270671 A1	11/2007	Gal
2005/0203349 A1	9/2005	Nanikashvili	2007/0293781 A1	12/2007	Sims et al.
2005/0203357 A1	9/2005	Debreczeny et al.	2007/0299330 A1	12/2007	Couronne et al.
2005/0209516 A1	9/2005	Fraden	2008/0001735 A1	1/2008	Tran
2005/0212405 A1	9/2005	Negley	2008/0004536 A1	1/2008	Baxi et al.
2005/0222487 A1	10/2005	Miller et al.	2008/0015424 A1	1/2008	Bernreuter
2005/0222903 A1	10/2005	Buchheit et al.	2008/0039731 A1	2/2008	McCombie et al.
2005/0228244 A1	10/2005	Banet	2008/0076972 A1	3/2008	Dorogusker et al.
2005/0228299 A1	10/2005	Banet	2008/0081963 A1	4/2008	Naghavi et al.
2005/0228463 A1	10/2005	Mac et al.	2008/0081972 A1	4/2008	Debreczeny
2005/0240087 A1	10/2005	Keenan et al.	2008/0086533 A1	4/2008	Neuhauser et al.
2005/0245839 A1	11/2005	Stivorac et al.	2008/0096726 A1	4/2008	Riley et al.
2005/0258816 A1	11/2005	Zen et al.	2008/0114220 A1	5/2008	Banet et al.
2005/0259811 A1	11/2005	Kimm et al.	2008/0132798 A1	6/2008	Hong et al.
2006/0009685 A1	1/2006	Finarov et al.	2008/0133699 A1	6/2008	Craw et al.
2006/0012567 A1	1/2006	Sicklinger	2008/0141301 A1	6/2008	Azzaro et al.
2006/0063993 A1	3/2006	Yu et al.	2008/0146890 A1	6/2008	LeBoeuf et al.
2006/0064037 A1	3/2006	Shalon et al.	2008/0154098 A1	6/2008	Morris et al.
2006/0074333 A1*	4/2006	Huiku A61B 5/0205 600/529	2008/0154105 A1	6/2008	Lemay
2006/0084878 A1	4/2006	Banet et al.	2008/0165017 A1	7/2008	Schwartz
2006/0084879 A1	4/2006	Nazarian et al.	2008/0170600 A1	7/2008	Sattler et al.
2006/0122520 A1	6/2006	Banet et al.	2008/0171945 A1	7/2008	Dotter
2006/0123885 A1	6/2006	Yates et al.	2008/0177162 A1	7/2008	Bae et al.
2006/0140425 A1	6/2006	Berg et al.	2008/0200774 A1	8/2008	Luo
2006/0142665 A1	6/2006	Garay et al.	2008/0203144 A1	8/2008	Kim
2006/0202816 A1	9/2006	Crump et al.	2008/0221461 A1	9/2008	Zhou et al.
2006/0205083 A1	9/2006	Zhao	2008/0249594 A1	10/2008	Dietrich et al.
2006/0210058 A1	9/2006	Kock et al.	2008/0287752 A1	11/2008	Stroetz et al.
2006/0211922 A1	9/2006	Al-Ali et al.	2008/0312517 A1	12/2008	Genoe et al.
2006/0211924 A1	9/2006	Dalke et al.	2009/0005662 A1	1/2009	Petersen et al.
2006/0217598 A1	9/2006	Miyajima et al.	2009/0006457 A1	1/2009	Stivorac et al.
2006/0224059 A1	10/2006	Swedlow et al.	2009/0010461 A1	1/2009	Klinghult et al.
2006/0240558 A1	10/2006	Zhao	2009/0010556 A1	1/2009	Uchibayashi et al.
2006/0246342 A1	11/2006	MacPhee	2009/0030350 A1	1/2009	Yang et al.
2006/0251277 A1	11/2006	Cho	2009/0054751 A1	2/2009	Babashan et al.
2006/0251334 A1	11/2006	Oba et al.	2009/0054752 A1	2/2009	Jonnalagadda et al.
2006/0252999 A1	11/2006	Devaux et al.	2009/0069645 A1	3/2009	Nielsen et al.
2006/0264730 A1	11/2006	Stivorac et al.	2009/0082994 A1	3/2009	Schuler et al.
2006/0287590 A1	12/2006	McEowen	2009/0088611 A1	4/2009	Buschmann
2006/0292533 A1	12/2006	Selod	2009/0093687 A1	4/2009	Telfort et al.
2006/0293921 A1	12/2006	McCarthy et al.	2009/0105548 A1	4/2009	Bart
2007/0004449 A1	1/2007	Sham	2009/0105556 A1*	4/2009	Fricke A61B 5/0059 600/301
2007/0004969 A1	1/2007	Kong et al.	2009/0112101 A1	4/2009	Furness, III et al.
2007/0015992 A1	1/2007	Filkins et al.	2009/0131761 A1	5/2009	Moroney, III et al.
2007/0021206 A1	1/2007	Sunnen	2009/0131764 A1	5/2009	Lee et al.
2007/0027367 A1	2/2007	Oliver et al.	2009/0175456 A1	7/2009	Johnson
2007/0027399 A1	2/2007	Chou	2009/0177097 A1	7/2009	Ma et al.
2007/0036383 A1	2/2007	Romero	2009/0214060 A1	8/2009	Chuang et al.
2007/0050215 A1	3/2007	Kil et al.	2009/0221888 A1	9/2009	Wijesiriwardana
			2009/0227853 A1	9/2009	Wijesiriwardana
			2009/0240125 A1	9/2009	Such et al.
			2009/0253992 A1	10/2009	Van Der Loo
			2009/0253996 A1	10/2009	Lee et al.

(56)	References Cited			2014/0275854	A1 *	9/2014	Venkatraman	A61B 5/721 600/301
U.S. PATENT DOCUMENTS				2014/0275855	A1	9/2014	LeBoeuf et al.	
				2014/0276119	A1	9/2014	Venkatraman et al.	
2009/0264711	A1	10/2009	Schuler et al.	2014/0287833	A1	9/2014	LeBoeuf et al.	
2009/0270698	A1	10/2009	Shioi et al.	2014/0288392	A1	9/2014	Hong et al.	
2009/0281435	A1	11/2009	Ahmed et al.	2014/0288396	A1	9/2014	LeBoeuf et al.	
2009/0287067	A1	11/2009	Dorogusker et al.	2014/0288436	A1	9/2014	Venkatraman et al.	
2009/0299215	A1	12/2009	Zhang	2014/0323829	A1	10/2014	LeBoeuf et al.	
2010/0004517	A1	1/2010	Bryenton et al.	2014/0323830	A1	10/2014	LeBoeuf et al.	
2010/0022861	A1	1/2010	Cinbis et al.	2014/0323880	A1	10/2014	Ahmed et al.	
2010/0045663	A1	2/2010	Chen et al.	2014/0378844	A1	12/2014	Fei	
2010/0100013	A1	4/2010	Hu et al.	2015/0011898	A1	1/2015	Romesburg	
2010/0113948	A1	5/2010	Yang et al.	2015/0018636	A1	1/2015	Romesburg	
2010/0168531	A1	7/2010	Shaltis et al.	2015/0025393	A1 *	1/2015	Hong	A61B 5/02427 600/479
2010/0172522	A1	7/2010	Mooring et al.					
2010/0179389	A1	7/2010	Moroney et al.	2015/0031967	A1	1/2015	LeBoeuf et al.	
2010/0185105	A1	7/2010	Baldinger	2015/0032009	A1	1/2015	LeBoeuf et al.	
2010/0217100	A1	8/2010	LeBoeuf	2015/0057967	A1	2/2015	Albinali	
2010/0217102	A1	8/2010	Leboeuf et al.	2015/0080746	A1 *	3/2015	Bleich	A63B 69/0028 600/479
2010/0217103	A1	8/2010	Abdul-Hafiz et al.					
2010/0222655	A1	9/2010	Starr et al.	2015/0157269	A1	6/2015	Lisogurski et al.	
2010/0228315	A1	9/2010	Nielsen	2015/0190085	A1	7/2015	Nathan et al.	
2010/0234714	A1	9/2010	Mercier et al.	2015/0196256	A1	7/2015	Venkatraman et al.	
2010/0268056	A1	10/2010	Picard et al.	2015/0250396	A1	9/2015	Ahmed et al.	
2010/0274100	A1	10/2010	Behar et al.	2015/0265217	A1	9/2015	Penders et al.	
2010/0274109	A1	10/2010	Hu et al.	2015/0282768	A1	10/2015	Luna et al.	
2010/0292589	A1	11/2010	Goodman	2015/0289820	A1	10/2015	Miller et al.	
2010/0298653	A1	11/2010	McCombie et al.	2015/0305682	A1	10/2015	Leboeuf et al.	
2011/0028810	A1	2/2011	Van Slyke et al.	2015/0342481	A1	12/2015	Liu et al.	
2011/0028813	A1	2/2011	Watson et al.	2015/0366509	A1	12/2015	Romesburg	
2011/0066007	A1	3/2011	Banet et al.	2016/0022220	A1	1/2016	Lee et al.	
2011/0081037	A1	4/2011	Oh et al.	2016/0029964	A1	2/2016	LeBoeuf et al.	
2011/0098112	A1	4/2011	LeBoeuf	2016/0038045	A1	2/2016	Shapiro	
2011/0105869	A1	5/2011	Wilson et al.	2016/0089033	A1	3/2016	Saponas et al.	
2011/0112382	A1	5/2011	Li et al.	2016/0089086	A1	3/2016	Lin et al.	
2011/0130638	A1	6/2011	Raridan, Jr.	2016/0094899	A1 *	3/2016	Aumer	G08B 21/18 340/870.07
2011/0142371	A1	6/2011	King et al.					
2011/0178564	A1	7/2011	Keefe	2016/0120476	A1	5/2016	Liu et al.	
2011/0288379	A1	11/2011	Wu	2016/0287108	A1	10/2016	Wei et al.	
2012/0030547	A1	2/2012	Raptis et al.	2016/0361021	A1	12/2016	Salehizadeh et al.	
2012/0095303	A1	4/2012	He	2017/0034615	A1	2/2017	Mankodi et al.	
2012/0150052	A1	6/2012	Buchheim et al.	2017/0290549	A1	10/2017	Romesburg	
2012/0156933	A1	6/2012	Kreger et al.	2018/0008200	A1	1/2018	Romesburg	
2012/0179011	A1	7/2012	Moon et al.	2018/0020979	A1 *	1/2018	Wagner	A61B 5/14552 600/379
2012/0190948	A1	7/2012	Vetter et al.					
2012/0203081	A1	8/2012	LeBoeuf et al.	2018/0049645	A1	2/2018	Romesburg	
2012/0226111	A1	9/2012	LeBoeuf et al.	2018/0146926	A1	5/2018	Ishikawa	
2012/0226112	A1	9/2012	LeBoeuf et al.					
2012/0277548	A1	11/2012	Burton					
2012/0283577	A1	11/2012	LeBoeuf et al.	FOREIGN PATENT DOCUMENTS				
2012/0296184	A1	11/2012	LeBoeuf et al.					
2013/0053661	A1	2/2013	Alberth et al.	CN	201438747	U	4/2010	
2013/0072765	A1	3/2013	Kahn et al.	DE	3910749	A1	10/1990	
2013/0197377	A1	8/2013	Kishi et al.	EP	1 297 784	A1	4/2003	
2013/0245387	A1	9/2013	Patel	EP	1 480 278	A2	11/2004	
2013/0336495	A1	12/2013	Burgett et al.	EP	2 077 091	A2	7/2009	
2014/0012105	A1	1/2014	LeBoeuf et al.	EP	2 182 839	B1	10/2011	
2014/0051940	A1	2/2014	Messerschmidt	GB	2 408 209	A	5/2005	
2014/0051948	A1	2/2014	LeBoeuf et al.	GB	2 411 719	A	9/2005	
2014/0052567	A1	2/2014	Bhardwaj et al.	JP	7-241279		9/1995	
2014/0058220	A1	2/2014	LeBoeuf et al.	JP	9-253062		9/1997	
2014/0073486	A1	3/2014	Ahmed et al.	JP	9-299342		11/1997	
2014/0088433	A1	3/2014	Shan	JP	2000-116611		4/2000	
2014/0094663	A1	4/2014	LeBoeuf et al.	JP	2001-025462		1/2001	
2014/0100432	A1	4/2014	Golda et al.	JP	2003-159221		6/2003	
2014/0114147	A1	4/2014	Romesburg	JP	2004-513750	A	5/2004	
2014/0127996	A1	5/2014	Park et al.	JP	2004-283523		10/2004	
2014/0128690	A1	5/2014	LeBoeuf et al.	JP	2005-040261	A	2/2005	
2014/0135596	A1	5/2014	LeBoeuf et al.	JP	2005-270544	A	10/2005	
2014/0140567	A1	5/2014	LeBoeuf et al.	JP	2007-044203		2/2007	
2014/0171755	A1	6/2014	LeBoeuf et al.	JP	2007-185348		7/2007	
2014/0219467	A1	8/2014	Kurtz	JP	2008-136556	A	6/2008	
2014/0235967	A1	8/2014	LeBoeuf et al.	JP	2008-279061	A	11/2008	
2014/0235968	A1	8/2014	LeBoeuf et al.	JP	2009-153664	A	7/2009	
2014/0236531	A1	8/2014	Carter	JP	2010-526646		8/2010	
2014/0243617	A1	8/2014	LeBoeuf et al.	JP	2014-068733	A	4/2014	
2014/0243620	A1	8/2014	LeBoeuf et al.	KR	20-0204510	Y1	11/2000	
2014/0275852	A1	9/2014	Hong et al.	WO	WO 00/24064		4/2000	

(56) References Cited

FOREIGN PATENT DOCUMENTS

WO	WO 00/047108	A1	8/2000
WO	WO 01/08552	A1	2/2001
WO	WO 2002/017782	A2	3/2002
WO	WO 2005/010568	A2	2/2005
WO	WO 2005/020121	A1	3/2005
WO	WO 2005/036212	A2	4/2005
WO	WO 2005/110238	A1	11/2005
WO	WO 2006/009830	A2	1/2006
WO	WO 2006/067690	A2	6/2006
WO	WO 2007/012931	A2	2/2007
WO	WO 2007/023426	A2	3/2007
WO	WO 2007/038432	A2	4/2007
WO	WO 2007/053146	A1	5/2007
WO	WO 2008/141306	A2	11/2008
WO	WO 2011/127063	A1	10/2011
WO	WO 2013/019494	A2	2/2013
WO	WO 2013/038296	A1	3/2013
WO	WO 2013/109389	A1	7/2013
WO	WO 2013/109390	A1	7/2013
WO	WO 2014/092932	A1	6/2014
WO	2014196119		12/2014
WO	2015/068066		5/2015
WO	WO 2015/128226	A1	9/2015
WO	WO 2015/131065	A1	9/2015
WO	2017/027551		2/2017

OTHER PUBLICATIONS

"U.S. Army Fitness Training Handbook" by the Department of the Army, 2003, The Lyons Press. p. 17.

"Warfighter Physiological and Environmental Monitoring: A Study for the U.S. Army Research Institute in Environmental Medicine and the Soldier Systems Center", Massachusetts Institute of Technology Lincoln Laboratory, Final Report, Nov. 1, 2004, prepared for the U.S. Army under Air Force Contract F19628-00-C-0002; approved for public release.

Anpo et al. "Photocatalytic Reduction of CO₂ With H₂O on Titanium Oxides Anchored within Micropores of Zeolites: Effects of the Structure of the Active Sites and the Addition of Pt" *J. Chem. B.* 101:2632-2636 (1997).

Asada et al. "Mobile Monitoring with Wearable Photoplethysmographic Biosensors." *IEEE Engineering in Medicine and Biology Magazine*, May/Jun. 2003, pp. 28-40.

Bársan et al. "Understanding the fundamental principles of metal oxide based gas sensors; the example of CO sensing with SnO₂ sensors in the presence of humidity" *Journal of Physics: Condensed Matter* 15:R813-R839 (2003).

Bifulco et al., "Bluetooth Portable Device for Continuous ECG and Patient Motion Monitoring During Daily Life," *Medicon 2007*, IFMBE Proceedings 16, 2007, pp. 369-372.

Bott "Electrochemistry of Semiconductors" *Current Separations* 17(3):87-91 (1998).

Brodersen et al., "In-Ear Acquisition of Vital Signs Discloses New Chances for Preventive Continuous Cardiovascular Monitoring," 4th International Workshop on Wearable and Implantable Body Sensor Networks (BSN 2007), vol. 13 of the series IFMBE Proceedings, pp. 189-194.

Celka et al., "Motion Resistant Earphone Located Infrared based Heart Rate Measurement Device," *Proceedings of the Second IASTED International Conference on Biomedical Engineering*, Feb. 16-18, 2004, Innsbruck, Austria, pp. 582-585.

Colligan, M. J. et al. In "The psychological effects of indoor air pollution", *Bulletin of the New York Academy of Medicine*, vol. 57. No. 10, Dec. 1981, p. 1014-1026.

Communication pursuant to Article 94(3) EPC, European Application No. 12 739 502.8, dated Nov. 30, 2016, 6 pages.

Communication Pursuant to Article 94(3) EPC, EP 12 739 502.8, dated Jul. 19, 2016, 7 pages.

Communication pursuant to Article 94(3) EPC, EP 12 820 308.0, dated Feb. 3, 2016, 5 pages.

Communication pursuant to Article 94(3) EPC, EP 13 863 449.8, dated Nov. 5, 2015, 7 pages.

Communication pursuant to Article 94(3) EPC, EP 14 743 615.8, dated Dec. 23, 2015.

Communication Pursuant to Article 94(3) EPC, EP 14 743 615.8, dated Jul. 19, 2016, 7 pages.

Communication pursuant to Article 94(3) EPC, EP 14 743 839.4, dated Dec. 23, 2015, 6 pages.

Communication Pursuant to Article 94(3) EPC, EP 14 743 839.4, dated Jul. 20, 2016, 5 pages.

Comtois et al., "A Wearable Wireless Reflectance Pulse Oximeter for Remote Triage Applications," 2006 IEEE, pp. 53-54.

Comtois, Gary, W., "Implementation of Accelerometer-Based Adaptive Noise Cancellation in a Wireless Wearable Pulse Oximeter Platform for Remote Physiological Monitoring and Triage," Thesis, Worcester Polytechnic Institute, Aug. 31, 2007, 149 pages.

De Paula Santos, U. et al. In "Effects of air pollution on blood pressure and heart rate variability: a panel study of vehicular traffic controllers in the city of Sao Paulo, Brazil", *European Heart Journal* (2005) 26, 193-200.

Duun et al., "A Novel Ring Shaped Photodiode for Reflectance Pulse Oximetry in Wireless Applications," *IEEE Sensors 2007 Conference*, pp. 596-599.

Ebert, T et al., "Influence of Hydration Status on Thermoregulation and Cycling Hill Climbing," *Med. Sci. Sport Exerc.* vol. 39, No. 2, pp. 323-329, 2007.

Edmison et al., "E-Textile Based Automatic Activity Diary for Medical Annotation and Analysis," *Proc. BSN 2006 Int. Workshop Wearable Implantable Body Sensor Netw.* (2006), pp. 131-145, Apr. 3-5, 2006.

European Search Report corresponding to European Application No. 07862660.3 dated Apr. 25, 2012; 7 pages.

European Search Report, EP Application No. 13863449.8, dated Oct. 19, 2015, 3 pages.

European Search Report, EP Application No. 14743615.8, dated Oct. 12, 2015, 3 pages.

European Search Report, EP Application No. 14743839.4, dated Oct. 12, 2015, 3 pages.

Extended European Search Report, European Application No. 16183137.5, dated Jan. 12, 2017, 12 pages.

Extended European Search Report, European Application No. 16184560.7, dated Dec. 20, 2016, 9 pages.

Extended European Search Report, EP Application No. 16164775.5 Sep. 13, 2016, 7 pages.

Falkner et al., "Cardiovascular response to mental stress in normal adolescents with hypertensive parents. Hemodynamics and mental stress in adolescents," *Hypertension* 1979, 1:23-30.

Fittriner "The Only Trainer You Need"; <http://itami.com>; Downloaded Feb. 26, 2010; ©2008 FiTriainer™, 2 pages.

Fleming et al., "A Comparison of Signal Processing Techniques for the Extraction of Breathing Rate from the Photoplethysmogram," *World Academy of Science, Engineering and Technology*, vol. 30, Oct. 2007, pp. 276-280.

Geladas et al., "Effect of cold air inhalation on core temperature in exercising subjects under stress," *The American Physiological Society*, pp. 2381-2387, 1988.

Geun et al., "Measurement Site and Applied Pressure Consideration in Wrist Photoplethysmography," *The 23rd International Technical Conference on Circuits/Systems, Computers and Communications*, 2008, pp. 1129-1132.

Gibbs et al., "Active motion artifact cancellation for wearable health monitoring sensors using collocated MEMS accelerometers," *Smart Structures and Materials*, 2005: Sensors and Smart Structures Technologies for Civil, Mechanical and Aerospace Systems, Proc. of SPIE, vol. 5765, pp. 811-819.

Gibbs et al., "Reducing Motion Artifact in Wearable Bio-Sensors Using MEMS Accelerometers for Active Noise Cancellation," 2005 American Control Conference, Jun. 8-10, 2005, Portland, OR, USA, pp. 1581-1586.

Gold, D.R. et al. In "Ambient Pollution and Heart Rate Variability", *Circulation* 2000, 101:1267-1273.

Haahr-et al., "A Wearable "Electronic Patch" for Wireless Continuous Monitoring of the Chronically Diseased Patients," *Proceedings*

(56)

References Cited

OTHER PUBLICATIONS

of the 5th International Workshop on Wearable and Implantable Body Sensor Networks, in conjunction with The 5th International Summer School and Symposium on Medical Devices and Biosensors, The Chinese University of Hong Kong, HKSAR, China, Jun. 1-3, 2008, pp. 66-70.

International Preliminary Report on Patentability, PCT/US2014/012940, dated Jun. 17, 2015, 23 pages.

International Search Report and Written Opinion of the International Searching Authority, corresponding to International Patent Application No. PCT/US2014/012940, dated Oct. 16, 2014, 3 pages.

International Search Report and Written Opinion of the International Searching Authority, corresponding to PCT/US2012/0948079, dated Oct. 9, 2012.

International Search Report and Written Opinion of the International Searching Authority, corresponding to PCT/US2007/025114, dated May 13, 2008.

International Search Report Corresponding to International Application No. PCT/US2012/022634, dated Aug. 22, 2012, 9 pages.

International Search Report corresponding to International Patent Application No. PCT/US2014/012909, dated May 13, 2014, 3 pages.

International Search Report corresponding to International Patent Application No. PCT/US2012/046446, dated Jan. 14, 2013, 3 pages.

Jiang, Honghui, "Motion-Artifact Resistant Design of Photoplethysmograph Ring Sensor for Driver Monitoring," Thesis, Massachusetts Institute of Technology, Feb. 2004, 62 pages.

Kuzmina et al., "Compact multi-functional skin spectrometry set-up," *Advanced Optical Materials, Technologies, and Devices*, Proc. of SPIE, vol. 6596, 2007, pp. 65960T-1 to 65960T-6.

Lee et al., "Respiratory Rate Detection Algorithms by Photoplethysmography Signal Processing," 30th Annual International IEEE EMBS Conference, Vancouver, British Columbia, Canada, Aug. 20-24, 2008, pp. 1140-1143.

Lindberg et al., "Monitoring of respiratory and heart rates using a fibre-optic sensor," *Med Biol Eng Comput*, Sep. 1992, vol. 30, No. 5, pp. 533-537.

Luprano, Jean, "Sensors and Parameter Extraction by Wearable Systems: Present Situation and Future," *pHealth 2008*, May 21, 2008, 29 pages.

Lygouras et al., "Optical-Fiber Finger Photo-Plethysmograph Using Digital Techniques," *IEEE Sensors Journal*, vol. 2, No. 1, Feb. 2002, pp. 20-25.

Maguire et al., "The Design and Clinical Use of a Reflective Brachial Photoplethysmograph," Technical Report NUIM/SS-/2002/04, Submitted Apr. 2002, Signals and Systems Research Group, National University of Ireland, Maynooth, Co. Kildare, Ireland, 13 pages.

Maomao et al., "Mobile Context-Aware Game for the Next Generation," 2nd International Conference on Application and Development of Computer Games ADCOG 2003, p. 78-81.

Martins et al., "Zinc oxide as an ozone sensor" *Journal of Applied Physics* 96(3):1398-1408 (2004).

Maughan et al., "Exercise, Heat, Hydration and the Brain," *Journal of the American College of Nutrition*, vol. 26, No. 5, pp. 604S-612S, 2007.

Maughan, R.J., "Impact of mild dehydration on wellness and on exercise performance," *European Journal of Clinical Nutrition*, 57, Suppl. 2, pp. S19-S23, 2003.

Mendelson et al., "Measurement Site and Photodetector Size Considerations in Optimizing Power Consumption of a Wearable Reflectance Pulse Oximeter," *Proceedings of the 25th Annual International Conference of the IEEE EMBS*, Cancun, Mexico, Sep. 17-21, 2003, pp. 3016-3019.

Mendelson et al., "Noninvasive Pulse Oximetry Utilizing Skin Reflectance Photoplethysmography," *IEEE Transactions on Biomedical Engineering*, vol. 35, No. 10, Oct. 1988, pp. 798-805.

Mostardi, R., et al., "The effect of increased body temperature due to exercise on the heart rate and the maximal aerobic power," *Europ. J. Appl. Physiol*, 33, pp. 237-245, 1974.

Nakajima et al., "Monitoring of heart and respiratory rates by photoplethysmography using a digital filtering technique," *Med. Eng. Phys.*, vol. 18, No. 5, Jul. 1996, pp. 365-372.

Notification Concerning Transmittal of International Preliminary Report on Patentability, PCT/US2014/012909, dated Jul. 28, 2015.

Notification of Transmittal of International Preliminary Report on Patentability, PCT/US2015/041562, dated Oct. 20, 2016, 14 pages.

Notification of Transmittal of International Preliminary Report on Patentability, PCT/US2015/042636, dated Oct. 20, 2016, 7 pages.

Notification of Transmittal of International Preliminary Report on Patentability, PCT/US2015/042015, dated Oct. 20, 2016, 10 pages.

Notification of Transmittal of International Preliminary Report on Patentability, PCT/US2015/042035, dated Oct. 20, 2016, 8 pages.

Notification of Transmittal of International Preliminary Report on Patentability, PCT/US2015/046079, dated Oct. 20, 2016, 10 pages.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, PCT/US2016/046273, dated Nov. 25, 2016, 24 pages.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, PCT/US2016/041842, dated Oct. 21, 2016, 5 pages.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, PCT/US2016/058098, dated Jan. 10, 2017, 13 pages.

Notification of Transmittal of the International Search Report and Written Opinion of the International Search Authority dated May 26, 2016 by the Korean Intellectual Property Office for corresponding International Application No. PCT/US2016/019126.

Notification of Transmittal of the International Search Report and Written Opinion of the International Search Authority dated May 26, 2016 by the Korean Intellectual Property Office for corresponding International Application No. PCT/US2016/019132.

Notification of Transmittal of the International Search Report and Written Opinion of the International Search Authority dated Jul. 30, 2010 by the Korean Intellectual Property Office for corresponding International Application No. PCT/US2010/021936.

Notification of Transmittal of the International Search Report and Written Opinion of the International Search Authority dated Aug. 26, 2010 by the Korean Intellectual Property Office for corresponding International Application No. PCT/US2010/021629.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Search Authority dated Sep. 16, 2010 by the Korean Intellectual Property Office for corresponding International Application No. PCT/US2010/024922.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Search Authority dated Sep. 27, 2010 by the Korean Intellectual Property Office for corresponding International Application No. PCT/US2010/025216.

Notification of Transmittal of The International Search Report and The Written Opinion of the International Searching Authority, or the Declaration corresponding to International Application No. PCT/US2013/070271; dated Feb. 26, 2014; 13 pages.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, PCT/US2015/014562, dated Oct. 28, 2015.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, PCT/US2015/042636, dated Oct. 29, 2015.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration; PCT/US2015/042015, dated Oct. 29, 2015.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, PCT/US2015/042035, dated Oct. 29, 2015.

Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, PCT/US2015/046079, dated Dec. 29, 2015.

(56)

References Cited

OTHER PUBLICATIONS

- Poh et al., "Motion Tolerant Magnetic Earring Sensor and Wireless Earpiece for Wearable Photoplethysmography," IEEE Transactions on Information Technology in Biomedicine, vol. 14, No. 3, May 2010, pp. 786-794.
- Renevey et al., "Wrist-Located Pulse Detection Using IR Signals, Activity and Nonlinear Artifact Cancellation," IEEE EMBS, 2001, 4 pages.
- Rhee et al., "Artifact-Resistant Power-Efficient Design of Finger-Ring Plethysmographic Sensors," IEEE Transactions on Biomedical Engineering, vol. 48, No. 7, Jul. 2001, pp. 795-805.
- Saladin et al. "Photosynthesis of CH₄ at a TiO₂ Surface from Gaseous H₂O and Co₂" *J. Chem. Soc., Chem. Commun.* 533-534 (1995).
- Shaltis, Phillip Andrew, Analysis and Validation of an Artifact Resistant Design for Oxygen Saturation Measurement Using Photo Plethysmographic Ring Sensors, Thesis, Massachusetts Institute of Technology, Jun. 2004, 103 pages.
- Shin et al., "A Novel Headset with a Transmissive PPG Sensor for Heart Rate Measurement," ICBME 2008, Proceedings 23, 2009, pp. 519-522.
- Shorten et al., "Acute effect of environmental temperature during exercise on subsequent energy intake in active men," *Am. J. Clin. Nutr.* 90, pp. 1215-1221, 2009.
- Skubal et al. "Detection and identification of gaseous organics using a TiO₂ sensor" *Journal of Photochemistry and Photobiology A: Chemistry* 148:103-108 (2002).
- Skubal et al. "Monitoring the Electrical Response of Photoinduced Organic Oxidation on TiO₂ Surfaces" Manuscript submitted Oct. 2000 to SPIE Intl. Symposium on Environment & Industrial Sensing, Boston, MA, Nov. 5-8, 2000, sponsored by SPIE, 10 pp.
- Spigulis et al., "Wearable wireless photoplethysmography sensors," *Proc. of SPIE*, vol. 6991, 2008, pp. 69912O-1 to 69912O-7.
- Takatani et al., "Optical Oximetry Sensors for Whole Blood and Tissue," IEEE Engineering in Medicine and Biology, Jun./Jul. 1994, pp. 347-357.
- Thompson, M.W., "Cardiovascular drift and critical core temperature: factors limiting endurance performance in the heat?" *J. Exerc. Sci. Fit.* vol. 4, No. 1, pp. 15-24, 2006.
- Vogel et al., "A System for Assessing Motion Artifacts in the Signal of a Micro-Optic In-Ear Vital Signs Sensor," 30th Annual International IEEE EMBS Conference, Vancouver, British Columbia, Canada, Aug. 20-24, 2008.
- Vogel et al., "In-Ear Heart Rate Monitoring Using a Micro-Optic Reflective Sensor," Proceedings of the 29th Annual International Conference of the IEEE EMBS Cite Internationale, Lyon, France, Aug. 23-26, 2007, pp. 1375-1378.
- Wang et al., "Multichannel Reflective PPG Earpiece Sensor With Passive Motion Cancellation," IEEE Transactions on Biomedical Circuits and Systems, vol. 1, No. 4, Dec. 2007, pp. 235-241.
- Wang et al., "Reflective Photoplethysmograph Earpiece Sensor for Ubiquitous Heart Rate Monitoring," 4th International Workshop on Wearable and Implantable Body Sensor Networks, 2007, vol. 13 of the series IFMBE Proceedings, pp. 179-183.
- Wei et al. "A New Wristband Wearable Sensor Using Adaptive Reduction Filter to Reduce Motion Artifact," Proceedings of the 5th International Conference on Information Technology and Application in Biomedicine, in conjunction with The 2nd International Symposium & Summer School on Biomedical and Health Engineering, Shenzhen, China, May 30-31, 2008, pp. 278-281.
- Wood et al., "Active Motion Artifact Reduction for Wearable Sensors Using Laguerre Expansion and Signal Separation," Proceedings of the 2005 IEEE Engineering in Medicine and Biology, 27th Annual Conference, Shanghai, China, Sep. 1-4, 2005, pp. 3571-3574.
- Wood, Levi Benjamin, "Motion Artifact Reduction for Wearable Photoplethysmogram Sensors using Micro Accelerometers and Laguerre Series Adaptive Filters," Thesis, Massachusetts Institute of Technology, Jun. 2008, 74 pages.
- Zhang et al. "Development of Chemical Oxygen Demand On-Line Monitoring System Based on a Photoelectrochemical Degradation Principle" *Environ. Sci. Technol.*, 40(7):2363-2368 (2006).
- Comtois et al. "A Comparative Evaluation of Adaptive Noise Cancellation Algorithms for Minimizing Motion Artifacts in a Forehead-Mounted Wearable Pulse Oximeter" *Proceedings of the 29th Annual International Conference of the IEEE EMBS* (pp. 1528-1531) (Aug. 23-26, 2007).
- Han et al. "Development of a wearable health monitoring device with motion artifact reduced algorithm" *International Conference on Control, Automation and Systems 2007 (ICCAS 2007)* (pp. 1581-1584) (Oct. 17-20, 2007).
- Lee et al. "A Mobile Care System With Alert Mechanism" *IEEE Transactions on Information Technology in Biomedicine* 11(5):507-517 (Sep. 2007).
- Webster, John G. "Design of Pulse Oximeters" *Medical Science Series, Institute of Physics Publication* (143 pages) (Aug. 1997).
- Fukushima et al. "Estimating Heart Rate using Wrist-type Photoplethysmography and Acceleration sensor while running" *Conf Proc IEEE Eng Med Biol Soc.* (pp. 2901-2904) (Sep. 2012).
- Notification Concerning Transmittal of International Preliminary Report on Patentability in corresponding PCT Application No. PCT/US2016/058098 (10 pages) (dated May 3, 2018).
- Wikipedia "Least mean squares filter" Retrieved at URL: https://en.wikipedia.org/wiki/Least_mean_squares_filter (6 pages) (Retrieved on Mar. 17, 2016).

* cited by examiner




FIG. 1A

FIG. 1B




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10

1

PHYSIOLOGICAL MONITORING DEVICES AND METHODS THAT IDENTIFY SUBJECT ACTIVITY TYPE

CLAIM OF PRIORITY

This application claims priority from U.S. Provisional Patent Application No. 62/245,919 entitled "PHYSIOLOGICAL MONITORING DEVICES AND METHODS THAT IDENTIFY SUBJECT ACTIVITY TYPE," filed Oct. 23, 2015, in the United States Patent and Trademark Office, the disclosure of which is incorporated by reference herein in its entirety.

FIELD

The present invention relates generally to monitoring devices and methods, more particularly, to monitoring devices and methods for measuring physiological information.

BACKGROUND

Photoplethysmography (PPG) is based upon shining light into the human body and measuring how the scattered light intensity changes with each pulse of blood flow. The scattered light intensity will change in time with respect to changes in blood flow or blood opacity associated with heart beats, breaths, blood oxygen level (SpO_2), and the like. Such a sensing methodology may require the magnitude of light energy reaching the volume of flesh being interrogated to be steady and consistent so that small changes in the quantity of scattered photons can be attributed to varying blood flow. If the incidental and scattered photon count magnitude changes due to light coupling variation between the source or detector and the skin or other body tissue, then the signal of interest can be difficult to ascertain due to large photon count variability caused by motion artifacts. Changes in the surface area (and volume) of skin or other body tissue being impacted with photons, or varying skin surface curvature reflecting significant portions of the photons may also significantly impact optical coupling efficiency. Physical activity, such as walking, cycling, running, etc., may cause motion artifacts in the optical scatter signal from the body, and time-varying changes in photon intensity due to motion artifacts may swamp-out time-varying changes in photon intensity due to blood flow changes. Each of these changes in optical coupling can dramatically reduce the signal-to-noise ratio (S/N) of biometric PPG information to total time-varying photonic interrogation count. This can result in a much lower accuracy in metrics derived from PPG data, such as heart rate and breathing rate.

An earphone, such as a headset, earbud, etc., may be a good choice for incorporation of a photoplethysmography (PPG) device because it is a form factor that individuals are familiar with, it is a device that is commonly worn for long periods of time, and it is often used during exercise which is a time when individuals may benefit from having accurate heart rate data (or other physiological data). Unfortunately, incorporation of a photoplethysmography device into an earphone poses several challenges. For example, earphones may be uncomfortable to wear for long periods of time, particularly if they deform the ear surface. Moreover, human ear anatomy may vary significantly from person to person, so finding an earbud form that will fit comfortably in many ears may be difficult. Other form-factors for PPG devices,

2

such as wristbands, armbands, clothing, and the like may be problematic for motion artifacts as well.

Some previous efforts to reduce motion artifacts from wearable PPG devices have focused on passive filtering, adaptive filtering (U.S. Pat. No. 8,923,941), or removing noise associated with footsteps (U.S. Pat. No. 8,157,730) with harmonics associated with a subject's cadence (US 2015/0366509). Each of these methods is associated with both strengths and weaknesses, depending on the wearable PPG sensor location or the type of motion noise that is present for the subject wearing the PPG sensor.

SUMMARY

It should be appreciated that this Summary is provided to introduce a selection of concepts in a simplified form, the concepts being further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of this disclosure, nor is it intended to limit the scope of the invention.

According to some embodiments of the present invention, a monitoring device configured to be attached to a body of a subject includes a sensor that is configured to detect and/or measure physiological information from the subject (e.g., a PPG sensor, etc.), a motion sensor configured to detect and/or measure subject motion information, and at least one processor that is configured to receive and analyze physiological sensor signals produced by the physiological sensor and motion sensor signals produced by the motion sensor. The monitoring device may be configured to be positioned at or within an ear of the subject, secured to an appendage of the subject, or integrated into a form-factor that is wearable at a location of the body of the subject (for example, on a wrist). The physiological sensor may be an optical sensor that includes at least one optical emitter and at least one optical detector, although various other types of sensors may be utilized. The at least one processor is configured to process motion sensor signals to identify an activity characteristic of the subject. For example, the at least one processor is configured to determine if the subject is engaged in a periodic activity such as exercising, running, walking, etc., or if the subject is engaged in a lifestyle or non-periodic activity such as reading a book, desk work, eating, etc. A motion sensor's signal during random motion associated with lifestyle activities will be different than the signal during periodic activities. Once an activity characteristic is determined, the at least one processor is configured to select a biometric signal extraction algorithm and/or circuit in response to identification of the activity characteristic of the subject, and then process physiological sensor signals via the biometric signal extraction algorithm or circuit to produce physiological information about the subject.

In some embodiments, the at least one processor is configured to select a biometric signal extraction algorithm by choosing among multiple different biometric signal extraction algorithms, and/or modifying one or more biometric signal extraction algorithms to provide such different algorithms, based on the activity characteristic that was identified from processing the motion sensor signals. For example, once an activity characteristic is determined, the at least one processor may be configured to modify at least one parameter in a signal extraction algorithm or may be configured to modify a circuit in response to the identification of the activity characteristic of the subject, and then process physiological sensor signals via the modified biometric

signal extraction algorithm or modified circuitry to produce the physiological information about the subject.

In some embodiments, the biometric signal extraction algorithm or circuit is configured based on noise associated with the activity characteristic that was identified from processing the motion sensor signals. For example, the selected biometric signal algorithm may be configured to reduce or remove motion and/or environmental noise that is associated with the particular activity characteristic that was identified.

In some embodiments, the at least one processor is configured to process the motion sensor signals to identify the activity characteristic as periodic motion or non-periodic motion. The at least one processor is configured to select the biometric signal extraction algorithm or circuit by selecting a first biometric signal extraction algorithm or circuit in response to identification of the activity characteristic as periodic motion, and selecting a second biometric signal extraction algorithm or circuit (which is different from the first biometric signal extraction algorithm or circuit) in response to identification of the activity characteristic as non-periodic motion. The second biometric signal extraction algorithm or circuit may be based on a modification of the first biometric signal extraction algorithm or circuit.

In some embodiments, the first biometric signal extraction algorithm or circuit includes frequency domain processing and/or filtering, and the second biometric signal extraction algorithm or circuit includes time domain processing and/or filtering.

In some embodiments, responsive to identification of the activity characteristic as non-periodic motion and processing the physiological signal using the second biometric signal extraction algorithm or circuit, an accuracy of the physiological information is increased relative to processing the physiological signal using the first biometric signal extraction algorithm or circuit.

In some embodiments, the motion sensor is a multi-axis accelerometer. The at least one processor is configured to process motion sensor signals to identify an activity characteristic of the subject by filtering a signal from each axis of the accelerometer over a given time period to remove a DC component therefrom, producing an accelerometer spectrum using the filtered signals, identifying one or more frequencies in the spectrum having a magnitude above a threshold level, and/or determining if the one or more frequencies in the spectrum match a pattern associated with a known subject activity mode. In some embodiments, identifying one or more frequencies in the spectrum having a magnitude above a threshold level includes identifying first, second and third frequencies, each having a respective magnitude above the threshold level.

In some embodiments, the physiological sensor is a PPG sensor and the biometric signal extraction algorithm is configured to produce subject biometric information from signals produced by the PPG sensor. Exemplary biometric information may include one or more of the following: subject heart rate, subject respiration rate, subject RR interval (RRi), subject heart rate variability (HRV), subject blood pressure, subject blood analyte levels, subject cardiovascular properties.

Other embodiments of the present invention include methods of monitoring a subject via a monitoring device that includes a physiological sensor and a motion sensor. The monitoring device may be configured to be positioned at or within an ear of the subject, or secured to an appendage of the subject, or integrated into another wearable form-factor at a location of the body. The physiological sensor and

motion sensor are in communication with at least one processor and the method includes processing motion sensor signals received from the motion sensor by the at least one processor to identify an activity characteristic of the subject, selecting a biometric signal extraction algorithm or circuit by the at least one processor in response to the activity characteristic, and then processing physiological sensor signals by the at least one processor using the biometric signal extraction algorithm or circuit to produce physiological information about the subject.

In some embodiments, selecting a biometric signal extraction algorithm includes choosing among multiple different biometric signal extraction algorithms, and/or modifying one or more biometric signal extraction algorithms to provide such different algorithms, based on the activity characteristic that was identified from processing the motion sensor signals. For example, once an activity characteristic is determined, the processor may be configured to modify at least one parameter in a signal extraction algorithm or may be configured to modify a circuit in response to the identification of the activity characteristic of the subject, and then process physiological sensor signals via the modified biometric signal extraction algorithm or modified circuitry to produce the physiological information about the subject.

In some embodiments, the biometric signal extraction algorithm or circuit is configured based on noise associated with the activity characteristic that was identified from processing the motion sensor signals. For example, the selected biometric signal algorithm may be configured to reduce or remove motion and/or environmental noise that is associated with the particular activity characteristic that was identified.

In some embodiments, processing the motion sensor signals identifies the activity characteristic as periodic motion or non-periodic motion. Selecting the biometric signal extraction algorithm or circuit includes selecting a first biometric signal extraction algorithm or circuit; in response to identification of the activity characteristic as periodic motion, and selecting a second biometric signal extraction algorithm or circuit (which is different from the first biometric signal extraction algorithm or circuit) in response to identification of the activity characteristic as non-periodic motion. The second biometric signal extraction algorithm or circuit may be based on a modification of the first biometric signal extraction algorithm or circuit.

In some embodiments, the first biometric signal extraction algorithm or circuit includes frequency domain processing and/or filtering, and the second biometric signal extraction algorithm or circuit includes time domain processing and/or filtering.

In some embodiments, responsive to identification of the activity characteristic as non-periodic motion and processing the physiological signal using the second biometric signal extraction algorithm or circuit, an accuracy of the physiological information is increased relative to processing the physiological signal using the first biometric signal extraction algorithm or circuit.

In some embodiments, the motion sensor is a multi-axis accelerometer, and processing motion sensor signals via the at least one processor to identify an activity characteristic of the subject includes filtering a signal from each axis of the accelerometer over a given time period to remove a DC component therefrom, producing an accelerometer spectrum using the filtered signals, identifying one or more frequencies in the spectrum having a magnitude above a threshold

level, and/or determining if the one or more frequencies in the spectrum match a pattern associated with a known subject activity mode.

In some embodiments, identifying one or more frequencies in the spectrum having a magnitude above a threshold level includes identifying first, second and third frequencies, each having a respective magnitude above the threshold level.

In some embodiments, the physiological sensor is a PPG sensor, and the biometric signal extraction algorithm is configured to produce subject biometric information from signals produced by the PPG sensor. Exemplary biometric information may include one or more of the following: subject heart rate, subject respiration rate, subject RRI, subject HRV, subject blood pressure, subject blood analyte levels, subject cardiovascular properties.

Other embodiments of the present invention include methods of monitoring a subject via a monitoring device that includes a PPG sensor and a motion sensor. The monitoring device may be configured to be positioned at or within an ear of the subject, secured to an appendage of the subject, or integrated into a form-factor that is wearable at a location of the body of the subject. The PPG sensor and motion sensor are in communication with at least one processor and the method includes filtering a motion signal generated by the motion sensor to attenuate information in the motion signal to generate a filtered motion signal, generating a spectral representation of the filtered motion signal, identifying a plurality of frequencies in the spectral representation having a magnitude above a threshold level and/or matching a pattern associated with a known subject activity mode, processing information associated with the plurality of frequencies to determine a type of motion of the subject, sending information on subject motion type to a biometric tracking algorithm or circuit, and processing a PPG sensor signal using the subject motion type information. The information on subject motion type may be communicated to a biometric signal extraction algorithm or circuit.

In some embodiments, identifying the plurality of frequencies includes identifying first, second and third frequencies having a magnitude above the threshold level.

In some embodiments, processing information associated with the plurality of frequencies may include determining if a ratio of peak frequencies fit a pattern associated with periodic subject motion.

In some embodiments, processing information associated with the plurality of frequencies to determine a type of motion of the subject includes determining if the motion of the subject is periodic motion or non-periodic motion.

In some embodiments, processing the PPG sensor signal using the biometric tracking algorithm or circuit includes processing the PPG sensor signal using a first biometric signal extraction algorithm or circuit in response to determining that the type of motion is periodic motion, and processing the PPG sensor signal using a second biometric signal extraction algorithm or circuit (which is different from the first biometric signal extraction algorithm or circuit) in response to determining that the type of motion is non-periodic motion. For example, the second biometric signal extraction algorithm or circuit may be a modification of the first biometric signal extraction algorithm or circuit, and the modification is based on the type of motion of the subject.

In some embodiments, the biometric signal extraction algorithm or circuit is configured to process the PPG sensor signal to obtain one or more of the following: subject heart

rate, subject respiration rate, subject RRI, subject HRV, subject blood pressure, subject blood analyte levels, subject cardiovascular properties.

Other embodiments of the present invention include methods of monitoring a subject via a monitoring device that includes a PPG sensor. The monitoring device may be configured to be positioned at or within an ear of the subject, secured to an appendage of the subject, or integrated into a form-factor that is wearable at a location of the body of the subject. The PPG sensor is in communication with at least one processor and the method includes processing PPG sensor signals via the at least one processor to identify a statistical relationship between RR-intervals in the PPG sensor signals, selecting a biometric signal extraction algorithm or circuit via the at least one processor in response to an identified statistical relationship between the RR-intervals, and then processing PPG sensor signals via the selected biometric signal extraction algorithm to produce physiological information about the subject.

In some embodiments, prior to selecting a biometric signal extraction algorithm or circuit the method includes processing the statistical relationship between RR-intervals to determine a type of motion of the subject.

In some embodiments, processing the PPG sensor signals to identify the statistical relationship is performed using a first biometric signal extraction algorithm or circuit that is different than the selected biometric signal extraction algorithm or circuit. The selected biometric signal extraction algorithm or circuit is configured based on noise associated with the type of motion or physiological status.

Monitoring devices according to embodiments of the present invention can be advantageous over some conventional monitoring devices because, by detecting an activity characteristic of a subject, biometric extraction algorithms can be selected and/or modified so as to provide more accurate physiological information about a subject. For example, for optimal heart rate tracking accuracy, it is advantageous to have some context about the type of activity being performed by a subject (i.e., whether the subject is engaged in lifestyle activities or periodic activities).

It is noted that aspects of the invention described with respect to one embodiment may be incorporated in a different embodiment although not specifically described relative thereto. That is, all embodiments and/or features of any embodiment can be combined in any way and/or combination, even if not specifically described in that manner. These and other aspects of the present invention are explained in detail below.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which form a part of the specification, illustrate various embodiments of the present invention. The drawings and description together serve to fully explain embodiments of the present invention.

FIGS. 1A-1B illustrate a monitoring device that can be positioned within an ear of a subject, according to some embodiments of the present invention.

FIG. 2A illustrates a monitoring device that can be positioned around an appendage (such as an arm, leg, finger, toe, etc.) of the body of a subject, according to some embodiments of the present invention.

FIG. 2B is a cross sectional view of the monitoring device of FIG. 2A.

FIG. 3 is a block diagram of a monitoring device according to some embodiments of the present invention.

FIGS. 4-7 are flowcharts of operations for monitoring a subject according to embodiments of the present invention.

FIG. 8 is a graph illustrating heart rate data for a subject plotted over time compared to a benchmark for a range of activity mode settings of a monitoring device, according to some embodiments of the present invention.

FIG. 9 is a graph illustrating heart rate data for a subject plotted over time compared to a benchmark for a range of activity mode settings of a monitoring device, according to some embodiments of the present invention.

FIG. 10 is a spectrogram of accelerometer data showing the subject monitored in FIGS. 8 and 9 performing non-periodic activity and periodic activity.

DETAILED DESCRIPTION

The present invention will now be described more fully hereinafter with reference to the accompanying figures, in which embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Like numbers refer to like elements throughout. In the figures, certain layers, components or features may be exaggerated for clarity, and broken lines illustrate optional features or operations unless specified otherwise. In addition, the sequence of operations (or steps) is not limited to the order presented in the figures and/or claims unless specifically indicated otherwise. Features described with respect to one figure or embodiment can be associated with another embodiment or figure although not specifically described or shown as such.

It will be understood that when a feature or element is referred to as being “on” another feature or element, it can be directly on the other feature or element or intervening features and/or elements may also be present. In contrast, when a feature or element is referred to as being “directly on” another feature or element, there are no intervening features or elements present. It will also be understood that, when a feature or element is referred to as being “secured”, “connected”, “attached” or “coupled” to another feature or element, it can be directly secured, directly connected, attached or coupled to the other feature or element or intervening features or elements may be present. In contrast, when a feature or element is referred to as being “directly secured”, “directly connected”, “directly attached” or “directly coupled” to another feature or element, there are no intervening features or elements present. Although described or shown with respect to one embodiment, the features and elements so described or shown can apply to other embodiments.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise.

As used herein, the terms “comprise”, “comprising”, “comprises”, “include”, “including”, “includes”, “have”, “has”, “having”, or variants thereof are open-ended, and include one or more stated features, elements, steps, components or functions but does not preclude the presence or addition of one or more other features, elements, steps, components, functions or groups thereof. Furthermore, as used herein, the common abbreviation “e.g.”, which derives from the Latin phrase “exempli gratia,” may be used to introduce or specify a general example or examples of a previously mentioned item, and is not intended to be limiting of such item. The common abbreviation “i.e.”, which

derives from the Latin phrase “id est,” may be used to specify a particular item from a more general recitation.

As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items and may be abbreviated as “/”.

As used herein, phrases such as “between X and Y” and “between about X and Y” should be interpreted to include X and Y. As used herein, phrases such as “between about X and Y” mean “between about X and about Y.” As used herein, phrases such as “from about X to Y” mean “from about X to about Y.”

Spatially relative terms, such as “under”, “below”, “lower”, “over”, “upper” and the like, may be used herein for ease of description to describe one element or feature’s relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if a device in the figures is inverted, elements described as “under” or “beneath” other elements or features would then be oriented “over” the other elements or features. Thus, the exemplary term “under” can encompass both an orientation of over and under. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly. Similarly, the terms “upwardly”, “downwardly”, “vertical”, “horizontal” and the like are used herein for the purpose of explanation only unless specifically indicated otherwise.

It will be understood that although the terms first and second are used herein to describe various features or elements, these features or elements should not be limited by these terms. These terms are only used to distinguish one feature or element from another feature or element. Thus, a first feature or element discussed below could be termed a second feature or element, and similarly, a second feature or element discussed below could be termed a first feature or element without departing from the teachings of the present invention.

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the specification and relevant art and should not be interpreted in an idealized or overly formal sense unless expressly so defined herein. Well-known functions or constructions may not be described in detail for brevity and/or clarity.

The term “about”, as used herein with respect to a value or number, means that the value or number can vary more or less, for example by $\pm 20\%$, $\pm 10\%$, $\pm 5\%$, $\pm 1\%$, $\pm 0.5\%$, $\pm 0.1\%$, etc.

The terms “sensor”, “sensing element”, and “sensor module”, as used herein, are interchangeable and refer to a sensor element or group of sensor elements that may be utilized to sense information, such as information (e.g., physiological information, body motion, etc.) from the body of a subject and/or environmental information in a vicinity of the subject. A sensor/sensing element/sensor module may comprise one or more of the following: a detector element, an emitter element, a processing element, optics, mechanical support, supporting circuitry, and the like. Both a single sensor element and a collection of sensor elements may be considered a sensor, a sensing element, or a sensor module.

The term “optical emitter”, as used herein, may include a single optical emitter and/or a plurality of separate optical emitters that are associated with each other.

The term “optical detector”, as used herein, may include a single optical detector and/or a plurality of separate optical detectors that are associated with each other.

The term “wearable sensor module”, as used herein, refers to a sensor module configured to be worn on or near the body of a subject.

The terms “monitoring device” and “biometric monitoring device”, as used herein, are interchangeable and include any type of device, article, or clothing that may be worn by and/or attached to a subject and that includes at least one sensor/sensing element/sensor module. Exemplary monitoring devices may be embodied in an earpiece, a headpiece, a finger clip, a digit (finger or toe) piece, a limb band (such as an arm band or leg band), an ankle band, a wrist band, a nose piece, a sensor patch, eyewear (such as glasses or shades), apparel (such as a shirt, hat, underwear, etc.), a mouthpiece or tooth piece, contact lenses, or the like.

The term “monitoring” refers to the act of measuring, quantifying, qualifying, estimating, sensing, calculating, interpolating, extrapolating, inferring, deducing, or any combination of these actions. More generally, “monitoring” refers to a way of getting information via one or more sensing elements. For example, “blood health monitoring” includes monitoring blood gas levels, blood hydration, and metabolite/electrolyte levels.

The term “headset”, as used herein, is intended to include any type of device or earpiece that may be attached to or near the ear (or ears) of a user and may have various configurations, without limitation. Headsets incorporating optical sensor modules, as described herein, may include mono headsets (a device having only one earbud, one earpiece, etc.) and stereo headsets (a device having two earbuds, two earpieces, etc.), earbuds, hearing aids, ear jewelry, face masks, headbands, and the like. In some embodiments, the term “headset” may include broadly headset elements that are not located on the head but are associated with the headset. For example, in a “medallion” style wireless headset, where the medallion comprises the wireless electronics and the headphones are plugged into or hard-wired into the medallion, the wearable medallion would be considered part of the headset as a whole. Similarly, in some cases, if a mobile phone or other mobile device is intimately associated with a plugged-in headphone, then the term “headset” may refer to the headphone-mobile device combination. The terms “headset” and “earphone”, as used herein, are interchangeable.

The term “physiological” refers to matter or energy of or from the body of a creature (e.g., humans, animals, etc.). In embodiments of the present invention, the term “physiological” is intended to be used broadly, covering both physical and psychological matter and energy of or from the body of a creature.

The term “body” refers to the body of a subject (human or animal) that may wear a monitoring device, according to embodiments of the present invention. The term “bodily location” refers to a location of the body on which (or in which) a monitoring device may be worn.

The term “processor” is used broadly to refer to a signal processor or computing system or processing or computing method which may be localized or distributed. For example, a localized signal processor may comprise one or more signal processors or processing methods localized to a general location, such as to a wearable device. Examples of such wearable devices may comprise an earpiece, a head-

piece, a finger clip, a digit (finger or toe) piece, a limb band (such as an arm band or leg band), an ankle band, a wrist band, a nose piece, a sensor patch, eyewear (such as glasses or shades), apparel (such as a shirt, hat, underwear, etc.), a mouthpiece or tooth piece, contact lenses, or the like. Examples of a distributed processor comprise “the cloud”, the internet, a remote database, a remote processor computer, a plurality of remote processors or computers in communication with each other, or the like, or processing methods distributed amongst one or more of these elements. The key difference is that a distributed processor may include delocalized elements, whereas a localized processor may work independently of a distributed processing system. As a specific example, microprocessors, microcontrollers, ASICs (application specific integrated circuits), analog processing circuitry, or digital signal processors are a few non-limiting examples of physical signal processors that may be found in wearable devices.

The term “remote” does not necessarily mean that a remote device is a wireless device or that it is a long distance away from a device in communication therewith. Rather, the term “remote” is intended to reference a device or system that is distinct from another device or system or that is not substantially reliant on another device or system for core functionality. For example, a computer wired to a wearable device may be considered a remote device, as the two devices are distinct and/or not substantially reliant on each other for core functionality. However, any wireless device (such as a portable device, for example) or system (such as a remote database for example) is considered remote to any other wireless device or system.

The terms “signal analysis frequency” and “signal sampling rate”, as used herein, are interchangeable and refer to the number of samples per second (or per other unit) taken from a continuous sensor (i.e., physiological sensor and environmental sensor) signal to ultimately make a discrete signal.

The term “sensor module interrogation power”, as used herein, refers to the amount of electrical power required to operate one or more sensors (i.e., physiological sensors and environmental sensors) of a sensor module and/or any processing electronics or circuitry (such as microprocessors and/or analog processing circuitry) associated therewith. Examples of decreasing the sensor interrogation power may include lowering the voltage or current through a sensor element (such as lowering the voltage or current applied to a pair of electrodes), lowering the polling (or polling rate) of a sensor element (such as lowering the frequency at which an optical emitter is flashed on/off in a PPG sensor), lowering the sampling frequency of a stream of data (such as lowering the sampling frequency of the output of an optical detector in a PPG sensor), selecting a lower-power algorithm (such as selecting a power-efficient time-domain processing method for measuring heart rate vs. a more power-hungry frequency-domain processing method), or the like. Lowering the interrogation power may also include powering only one electrode, or powering fewer electrodes, in a sensor module or sensor element such that less total interrogation power is exposed to the body of a subject. For example, lowering the interrogation power of a PPG sensor may comprise illuminating only one light-emitting diode rather than a plurality of light-emitting diodes that may be present in the sensor module, and lowering the interrogation power of a bioimpedance sensor may comprise powering only one electrode pair rather than a plurality of electrodes that may be present in the bioimpedance sensor module.

The term “polling” typically refers to controlling the intensity of an energy emitter of a sensor or to the “polling rate” and/or duty cycle of an energy emitter element in a sensor, such as an optical emitter in a PPG sensor or an ultrasonic driver in an ultrasonic sensor. Polling may also refer to the process of collecting and not collecting sensor data at certain periods of time. For example, a PPG sensor may be “polled” by controlling the intensity of one or more optical emitters, i.e. by pulsing the optical emitter over time. Similarly, the detector of a PPG sensor may be polled by reading data from that sensor only at a certain point in time or at certain intervals, i.e., as in collecting data from the detector of a PPG sensor for a brief period during each optical emitter pulse. A sensor may also be polled by turning on or off one or more elements of that sensor in time, such as when a PPG sensor is polled to alternate between multiple LED wavelengths over time or when an ultrasonic sensor is polled to alternate between mechanical vibration frequencies over time.

The terms “sampling frequency”, “signal analysis frequency”, and “signal sampling rate”, as used herein, are interchangeable and refer to the number of samples per second (or per other unit) taken from a continuous sensor or sensing element (for example, the sampling rate of the thermopile output in a tympanic temperature sensor).

It should be noted that “algorithm” and “circuit” are referred to herein. An algorithm refers to an instruction set, such as an instruction set with sequential steps and logic, that may be in memory whereas a circuit refers to electronic components and/or traces that may implement such logic operations.

It should be noted that processes for managing hysteresis are implied herein. Namely, several embodiments herein for controlling sensors (and other wearable hardware) may involve a processor sending commands to a sensor element depending on the sensor readings. Thus, in some embodiments, a sensor reading (such as a reading from an optical detector or a sensing electrode) above X may result in a processor sending a command to electrically bias another sensor element (such as an optical emitter or a biasing electrode) above Y. Similarly, as soon as the sensor reading drops below X, a processor may send a command to bias another sensor element below Y. However, in borderline situations this may cause unwanted hysteresis in the biasing command, as sensor readings may rapidly toggle above/below X resulting in the toggling of the biasing of another sensor element above/below Y. As such, hysteresis management may be integrated within the algorithm(s) for controlling the execution of a processor. For example, the processor may be configured by the algorithm to delay a biasing command by a period of time Z following the timing of a prior biasing command, thereby preventing or reducing the aforementioned toggling.

In the following figures, various monitoring devices will be illustrated and described for attachment to the ear or an appendage of the human body. However, it is to be understood that embodiments of the present invention are not limited to those worn by humans.

The ear is an ideal location for wearable health and environmental monitors. The ear is a relatively immobile platform that does not obstruct a person’s movement or vision. Monitoring devices located at an ear have, for example, access to the inner-ear canal and tympanic membrane (for measuring core body temperature), muscle tissue (for monitoring muscle tension), the pinna, earlobe, and elsewhere (for monitoring blood gas levels), the region behind the ear (for measuring skin temperature and galvanic

skin response), and the internal carotid artery (for measuring cardiopulmonary functioning), etc. Virtually all areas of the ear support enough blood perfusion to enable an assessment of blood flow and blood-flow-derived metrics (such as breathing rate, heart rate, blood pressure, RR-interval, and the like) via photoplethysmography (PPG). A particularly good location for PPG may be the region covering the anti-tragus and concha regions of the ear, as the region has high perfusion, is more resistant to motion artifacts, and is in a region away from the ear canal. The ear is also at or near the point of exposure to: environmental breathable toxicants of interest (volatile organic compounds, pollution, etc.); noise pollution experienced by the ear; and lighting conditions for the eye. Furthermore, as the ear canal is naturally designed for transmitting acoustical energy, the ear provides a good location for monitoring internal sounds, such as heartbeat, breathing rate, and mouth motion.

Optical coupling into the blood vessels of the ear may vary between individuals. As used herein, the term “coupling” refers to the interaction or communication between excitation energy (such as light) entering a region and the region itself. For example, one form of optical coupling may be the interaction between excitation light generated from within an optical sensor of a wearable device—such as a wristband, armband, legband, skin-worn patch, neckband, ring, earbud, other device positioned at or within an ear, a headband, or the like—and the blood vessels. In one embodiment, this interaction may involve excitation light entering the skin and scattering from a blood vessel such that the temporal change in intensity of scattered light is proportional to a temporal change in blood flow within the blood vessel. Another form of optical coupling may be the interaction between excitation light generated by an optical emitter within a wearable device and a light-guiding region of the wearable device. Thus, a wearable device with integrated light-guiding capabilities, wherein light can be guided to multiple and/or select regions along the wearable device, can assure that each individual wearing the device will generate an optical signal related to blood flow through the blood vessels. Optical coupling of light to a particular skin region of one person may not yield photoplethysmographic signals for each person. Therefore, coupling light to multiple regions may assure that at least one blood-vessel-rich region will be interrogated for each person wearing the device. Coupling multiple regions of the body to light may also be accomplished by diffusing light from a light source in the device.

According to some embodiments of the present invention, “smart” monitoring devices including, but not limited to, wrist-worn devices, armbands, earbuds, and the like, are provided that can modify biometric signal extraction algorithms based upon a recognition of an activity level of a subject.

FIGS. 1A-1B illustrate a monitoring apparatus 20 configured to be positioned within an ear of a subject, according to some embodiments of the present invention. The illustrated apparatus 20 includes an earpiece body or housing 22, a sensor module 24, a stabilizer 25, and a sound port 26. When positioned within the ear of a subject, the sensor module 24 has a region 24a configured to contact a selected area of the ear. The illustrated sensor region 24a is contoured (i.e., is “form-fitted”) to matingly engage a portion of the ear between the anti tragus and acoustic meatus, and the stabilizer is configured to engage the anti-helix. However, monitoring devices in accordance with embodiments of the present invention can have sensor modules with one or more regions configured to engage various portions of the ear.

13

Various types of device configured to be worn at or near the ear may be utilized in conjunction with embodiments of the present invention.

FIGS. 2A-2B illustrate a monitoring apparatus 30 in the form of a sensor band 32 configured to be secured to an appendage (e.g., an arm, wrist, hand, finger, toe, leg, foot, neck, etc.) of a subject. The band 32 includes a sensor module 34 on or extending from the inside surface 32a of the band 32. The sensor module 34 is configured to detect and/or measure physiological information from the subject and includes a sensor region 34a that is contoured to contact the skin of a subject wearing the apparatus 30.

Embodiments of the present invention may be utilized in various devices and articles including, but not limited to, patches, clothing, etc. Embodiments of the present invention can be utilized wherever PPG and blood flow signals can be obtained and at any location on the body of a subject. Embodiments of the present invention are not limited to the illustrated monitoring devices 20, 30 of FIGS. 1A-1B and 2A-2B.

The sensor modules 24, 34 for the illustrated monitoring devices 20, 30 of FIGS. 1A-1B and 2A-2B are configured to detect and/or measure physiological information from a subject wearing the monitoring devices 20, 30. In some embodiments, the sensor modules 24, 34 may be configured to detect and/or measure one or more environmental conditions in a vicinity of the subject wearing the monitoring devices 20, 30.

A sensor module utilized in accordance with embodiments of the present invention may be an optical sensor module that includes at least one optical emitter and at least one optical detector. Exemplary optical emitters include, but are not limited to light-emitting diodes (LEDs), laser diodes (LDs), compact incandescent bulbs, micro-plasma emitters, IR blackbody sources, or the like. In addition, a sensor module may include various types of sensors including and/or in addition to optical sensors. For example, a sensor module may include one or more inertial sensors (e.g., an accelerometer, piezoelectric sensor, vibration sensor, photo-reflector sensor, etc.) for detecting changes in motion, one or more thermal sensors (e.g., a thermopile, thermistor, resistor, etc.) for measuring temperature of a part of the body, one or more electrical sensors for measuring changes in electrical conduction, one or more skin humidity sensors, and/or one or more acoustical sensors. Sensor modules may include physiological sensors for monitoring vital signs, blood flow properties, body fluids, muscle motion, body motion, and the like. Sensor modules may include environmental sensors for monitoring ambient light, ambient temperature, ambient humidity, airborne pollutants, wind, and the like. It should be understood that a wide variety of sensors may be incorporated into a wearable sensor module.

Referring to FIG. 3, a monitoring device (e.g., monitoring devices 20, 30), according to embodiments of the present invention, is illustrated schematically. The illustrated monitoring device includes a sensor module 24, 34 having one or more physiological sensors configured to detect and/or measure physiological information from the subject, and a motion sensor 50 (e.g., an accelerometer) configured to detect and/or measure subject motion information. The monitoring device 20, 30 also includes at least one processor 40 that is coupled to the sensor(s) of a sensor module 24, 34, to the motion sensor 50, and that is configured to receive and analyze signals produced by the sensor(s) and motion sensor 50.

According to some embodiments of the present invention, the processor 40 is configured to process motion sensor

14

signals to identify an activity characteristic (e.g., periodic or non-periodic activity) of the subject, select or modify a biometric signal extraction algorithm (implemented by computer-readable memory and/or circuit 60) in response to identification of the type of subject activity, and then process physiological sensor signals via the modified biometric signal extraction algorithm or circuit 60 to produce physiological information about the subject, such as subject heart rate, subject respiration rate, subject RRI (i.e., the time-difference between consecutive R-peaks in the ECG or PPG waveform), subject HRV, subject blood pressure, subject blood analyte levels, subject cardiovascular properties, and the like.

In some embodiments, the motion sensor 50 is an accelerometer and a filter is applied to each axis of the accelerometer data to remove the DC component therefrom. A spectral transform is performed on each axis of the DC-removed signal over a given time span. An accelerometer spectrum is then generated by taking the root of the sum of the squares of each axis of the accelerometer that is associated with that time span. Other techniques may also be used.

The 1st, 2nd, and 3rd, most intense frequencies and magnitudes in the accelerometer spectrum are identified. The relative proportion of energy within the peaks is compared to all other frequencies to determine if the criteria for periodicity is met. If so, the given segment of time is determined to represent periodic activity and an Automatic Mode Switching feature of the monitoring device is set to inform an algorithm 60 (e.g., a heart rate algorithm, etc.) of the periodic context. If not, an Automatic Mode Switching feature of the monitoring device is set to inform the HR algorithm of the non-periodic context.

Alternatively or in addition, a determination is made whether the ratio of peak frequencies fits a pattern associated with periodicity (e.g., whether peak 2 is twice the frequency of peak 1, etc.). If so, the given segment of time is determined to represent periodic activity and an Automatic Mode Switching feature of the monitoring device is set to inform an algorithm 60 (e.g., a heart rate algorithm, etc.) of the periodic context. If not, an Automatic Mode Switching feature is set to inform the HR algorithm of the non-periodic context.

Referring now to FIG. 4, a method of monitoring a subject via a monitoring device, such as monitoring devices 20, 30, according to some embodiments of the present invention, will be described. The monitoring device includes a physiological sensor configured to detect and/or measure physiological information from the subject and a motion sensor. The physiological sensor and the motion sensor are in communication with a processor that is configured to receive and analyze signals produced by the physiological sensor and motion sensor. The processor may be part of the monitoring device or may be a remotely located processor.

The subject is monitored for a change in physical activity level or type (Block 100). If a change is detected (Block 110), the processor 40 identifies an activity characteristic (e.g., determines if the activity is periodic or non-periodic) (Block 120). For example, via an algorithm stored in or implemented by memory or circuit 60, the processor determines if the subject is engaged in a non-periodic or lifestyle activity such as reading a book, desk work, eating, etc., or a periodic activity such as exercising, running, walking, etc. In response to determining the type of activity, the processing of the biometric signal extraction algorithm may be modified in one or more ways (Block 130). For example, in response to determining the type of activity, at least one

parameter of the biometric signal extraction algorithm may be modified, and this modified biometric signal extraction algorithm may be selected for processing. Some specific examples of parameters that may be modified are described in US 2015/0366509 entitled “CADENCE DETECTION BASED ON INERTIAL HARMONICS” (published Dec. 24, 2015), US 2016/0029964 entitled “PHYSIOLOGICAL MONITORING DEVICES WITH ADJUSTABLE SIGNAL ANALYSIS AND INTERROGATION POWER AND MONITORING METHODS USING THE SAME” (published Feb. 4, 2016), and US 2015/0011898 entitled “PHYSIOLOGICAL METRIC ESTIMATION RISE AND FALL LIMITING” (published Jan. 8, 2015), the disclosures of which are incorporated by reference herein. For example, parameters affecting the rise or fall time of biometric tracking (such as the tracking of heart rate, breathing rate, RRI, etc.), parameters affecting the subtraction or redaction of unwanted frequencies in the PPG signal (i.e., which frequency bands to subtract or redact (set to zero) based for example on amplitude and/or power), and/or parameters affecting which types of filters to execute (highpass, lowpass, bandpass, active, subtractive or redactive filters, or the like) may be modified. In response to determining the type of activity, the processor may thus select a biometric signal extraction algorithm (which may be all or part of algorithm stored in or implemented by memory or circuit 60) so as to be best suited for processing sensor data during such activity (Block 130) (i.e., that is best suited for removing motion or environmental noise from that particular activity).

It should be noted that, in addition to or alternatively than modifying an algorithm or selecting an algorithm, a circuit may be modified or selected. For example, the determination of periodicity in Block 120 may send a signal to one or more transistors (Block 130) to switch the analog filtering circuits to “notch out” the periodic signal; or, the determination of non-periodicity in Block 120 may send a signal to one or more transistors (Block 130) to switch the analog filtering circuits to a bandpass filter that includes the biometric signals of interest. It should also be noted that both algorithms and circuits may simultaneously be modified or selected in the embodiments described herein. Thus, as another exemplary embodiment, the determination of periodicity in Block 120, using a low-power time-domain algorithm (such as an autocorrelation function, or the like), may initiate an algorithm in Block 130 that determines which frequencies should be removed. The output of the algorithm (i.e., the output from a processor) may send a signal to a bank of analog filters in Block 130 to remove these frequencies without the need for digital removal. This may be advantageous because executing a spectral transform may be overly power-hungry in a wearable device. Physiological sensor signals are then processed via the selected biometric signal extraction algorithm to produce physiological information about the subject, such as subject heart rate, subject respiration rate, subject RRI, subject HRV, subject blood pressure, subject blood analyte levels, subject cardiovascular properties, and the like.

Identification of an activity characteristic (e.g., determining if the activity is periodic or non-periodic) may also be associated with particular metrics to be assessed. For example, detecting that periodic motion exists may be a criteria for determining that a cardiac efficiency metric is being assessed. In contrast, if the subject’s motion is aperiodic, then a cardiac efficiency score (Average Cadence/Average HR) may be meaningless. Also, one or more processors or functions may be deactivated or run in power-saving mode based on the detection of type of motion (e.g.,

a pedometer may be deactivated responsive to detection of aperiodic motion). Additionally, an energy expenditure calculation which factors both HR and footsteps into an equation for the estimation of calories burned may be tuned to detect “fidgeting” (subtle motions) rather than footsteps and update the energy expenditure model to incorporate fidgets and HR, rather than footsteps and HR. The weighting factors for fidgets and HR, for example, may be different than the weighting factors for footsteps and HR when estimating energy expenditure.

As illustrated in FIG. 5, identifying an activity characteristic of a subject (Block 120) may include filtering a signal from each axis of the accelerometer over a given time period to remove a DC component therefrom (Block 122), producing an accelerometer spectrum using the filtered signals (Block 124), identifying one or more frequencies in the spectrum having a magnitude above a threshold level (Block 126), and/or determining if the one or more frequencies in the spectrum match a pattern associated with a known subject activity mode (Block 128). It should be noted that the operations of FIG. 5 may be controlled by algorithms, circuitry, or a combination of both.

Referring now to FIG. 6, a method of monitoring a subject via a monitoring device, such as monitoring devices 20, 30, according to some embodiments of the present invention, will be described. The monitoring device includes a PPG sensor and a motion sensor which are in communication with a processor that is configured to receive and analyze signals produced by the sensor module and motion sensor. The processor may be part of the monitoring device or may be a remotely located processor. It should be noted that the operations of FIG. 6 may be controlled by algorithms, circuitry, or a combination of both.

The method includes filtering a motion signal generated by the motion sensor to attenuate DC information in the motion signal and generate a DC-filtered motion signal (Block 200). A spectral representation of the DC-filtered motion signal is generated (Block 210) and a plurality of frequencies in the spectral representation are identified having a magnitude above a threshold level (Block 220). In other words, the most intense frequencies in the spectral representation are identified. Additional operations may include filtering a step rate component from a measured heart rate component based on a function of a difference therebetween as described in US 2015/0018636 entitled “REDUCTION OF PHYSIOLOGICAL METRIC ERROR DUE TO INERTIAL CADENCE” (published Jan. 15, 2015), comparing frequency measurements from an inertial sensor with one or more thresholds as described in US 2015/0366509 entitled “CADENCE DETECTION BASED ON INERTIAL HARMONICS” (published Dec. 24, 2015), and measuring signal quality to determine how a user should adjust a monitoring device to improve biometric fit, as described in US 2016/0094899 entitled “METHODS AND APPARATUS FOR IMPROVING SIGNAL QUALITY IN WEARABLE BIOMETRIC MONITORING DEVICES” (published Mar. 31, 2016), individually or together in combination, the disclosures of which are incorporated by reference herein. Information associated with the plurality of frequencies is then processed to determine a type of motion of the subject, for example, whether the subject motion is periodic or non-periodic motion (Block 230). Information on the subject motion type is sent to a biometric tracking algorithm or circuit or is otherwise used by the processor to select a biometric tracking algorithm or circuit (Block 240), and a PPG sensor signal is processed using the biometric tracking algorithm or circuit corresponding to the subject

motion type information to generate biometric information about the subject (Block 250). Exemplary biometric information includes, but is not limited to, subject heart rate, subject respiration rate, subject RRi, subject HRV, subject blood pressure, subject blood analyte levels, subject cardiovascular properties, etc.

Referring now to FIG. 7, a method of monitoring a subject via a monitoring device, such as monitoring devices 20, 30, according to some embodiments of the present invention, will be described. The monitoring device includes a PPG sensor and a motion sensor which are in communication with a processor that is configured to receive and analyze signals produced by the sensor module and motion sensor. The processor may be part of the monitoring device or may be a remotely located processor. It should be noted that the operations of FIG. 7 may be controlled by algorithms, circuitry, or a combination of both.

The method includes processing PPG sensor signals via the at least one processor to identify a statistical relationship between RR-intervals in the PPG sensor signals (Block 300) and processing the statistical relationship between RR-intervals to determine a type of motion of the subject (e.g., periodic or non-periodic) or a physiological status of the subject (Block 310). A biometric signal extraction algorithm or circuit is modified or selected via the processor in response to an identified statistical relationship between RR-intervals (Block 320). PPG sensor signals are then processed via the selected biometric signal extraction algorithm to produce physiological information about the subject (Block 320), such as subject heart rate, subject respiration rate, subject RR-interval (RRi), subject HRV, subject blood pressure, subject blood analyte levels, subject cardiovascular properties, etc. A particular example of processing RR-intervals to determine a type of motion of the subject may include processing a series of RR-intervals to identify the existence of stress, which may be associated with aperiodic (nonperiodic) motion.

It should be noted that it is known to those skilled in the art that a series of RR-intervals may be processed to generate an assessment of fatigue, stress (particularly psychosocial stress), autonomic nervous functioning, hemodynamics, cardiac disease—such as atrial fibrillation or cardiac arrhythmia—or the like. However, the inventors have discovered that the statistical analysis alone may not be sufficient to generate sufficient physiological information for a diagnosis of a health condition or other physiological state. Thus, in one particular embodiment of FIG. 7, the RRi-intervals may be statistically processed (Block 310) to generate an assessment that a subject status of atrial fibrillation is likely. Once this status is known to be likely, the signal extraction algorithm may be modified or selected to more concretely determine a status of atrial fibrillation or to diagnose another condition (such as poor or abnormal hemodynamics or cardiac output, which may be associated with atrial fibrillation). As a specific example, Block 320 may switch to an algorithm that allows more frequencies to pass through during signal extraction, such that the extracted signal from Block 320 may be further processed by Block 330 to generate sufficient physiological information to diagnose atrial fibrillation. It should be understood that this describes a particular embodiment, and other embodiments that rely on FIG. 7 may be used with the present invention. As another specific example, Block 310 may determine that a subject may likely be in a status of fatigue. Block 320 may then modify or select a signal extraction algorithm that increases the signal resolution (i.e., the sampling rate and/or dynamic range), such that the extracted signal may be

processed by Block 330 to generate a more definitive assessment of fatigue. In yet another example, Block 310 may determine that a subject may likely be in a status of stress, Block 320 may then modify or select a signal extraction algorithm that switches from a screening spectral-based (frequency domain-based) RRi calculator to a higher resolution time-domain-based RRi calculator, the extracted RRi signal may then be processed by Block 330 to generate a more definitive assessment of stress.

FIG. 8 is a graph illustrating heart rate data 400, 402, 404 for a subject plotted over time compared to the actual heart rate (406), the heart rate determined by a validated benchmark device, for a range of activity mode settings for a monitoring device according to some embodiments of the present invention. For the illustrated duration, the subject was not walking/jogging/running (i.e., the subject was not engaged in a periodic activity), but was doing deskwork (i.e., the subject was engaged in a non-periodic activity), where arms and hands were moving as is typical for desk work. As seen, the heart rate in Mode 3 (the “lifestyle mode” indicated by 404) most closely agrees with that of the benchmark device heart rate (406), and the monitoring device correctly uses the output for Mode 3.

FIG. 9 is a graph illustrating heart rate data 400, 402, 404 for a subject plotted over time compared to the actual heart rate (406), the heart rate determined by a validated benchmark device, for a range of activity mode settings for a monitoring device according to some embodiments of the present invention. For the illustrated duration, the subject is jogging. As seen, the heart rate in Mode 1 (400) most closely agrees with that of the benchmark device heart rate (406), and the monitoring device correctly uses the output for Mode 1. Note that the heart rate reported using Lifestyle mode (404) does not match the benchmark (406) as well as Mode 1 output (400).

FIG. 10 is a spectrogram for exemplary combined accelerometer data showing the subject monitored in FIGS. 8 and 9 performing non-periodic activity from time (t)=0 to 150 seconds, and performing periodic activity (walking) after t=150 seconds. For accurate heart rate tracking, the monitoring device uses settings associated with Lifestyle Mode (Mode 3) prior to t=150 sec and Periodic Mode after t=120 seconds.

Example embodiments are described herein with reference to block diagrams and flowchart illustrations. It is understood that a block of the block diagrams and flowchart illustrations, and combinations of blocks in the block diagrams and flowchart illustrations, can be implemented by computer program instructions that are performed by one or more computer circuits. These computer program instructions may be provided to a processor circuit of a general purpose computer circuit, special purpose computer circuit, and/or other programmable data processing circuit to produce a machine, such that the instructions, which execute via the processor of the computer and/or other programmable data processing apparatus, transform and control transistors, values stored in memory locations, and other hardware components within such circuitry to implement the functions/acts specified in the block diagrams and flowchart block or blocks, and thereby create means (functionality) and/or structure for implementing the functions/acts specified in the block diagrams and flowchart blocks.

These computer program instructions may also be stored in a tangible computer-readable medium that can direct a computer or other programmable data processing apparatus to function in a particular manner, such that the instructions stored in the computer-readable medium produce an article

of manufacture including instructions which implement the functions/acts specified in the block diagrams and flowchart blocks.

A tangible, non-transitory computer-readable medium may include an electronic, magnetic, optical, electromagnetic, or semiconductor data storage system, apparatus, or device. More specific examples of the computer-readable medium would include the following: a portable computer diskette, a random access memory (RAM) circuit, a read-only memory (ROM) circuit, an erasable programmable read-only memory (EPROM or Flash memory) circuit, a portable compact disc read-only memory (CD-ROM), and a portable digital video disc read-only memory (DVD/Blu-Ray).

The computer program instructions may also be loaded onto a computer and/or other programmable data processing apparatus to cause a series of operational steps to be performed on the computer and/or other programmable apparatus to produce a computer-implemented process such that the instructions which execute on the computer or other programmable apparatus provide steps for implementing the functions/acts specified in the block diagrams and flowchart blocks. Accordingly, embodiments of the present invention may be embodied in hardware and/or in software (including firmware, resident software, micro-code, etc.) that runs on a processor such as a digital signal processor, which may collectively be referred to as "circuitry," "a module" or variants thereof.

It should also be noted that in some alternate implementations, the functions/acts noted in the blocks may occur out of the order noted in the flowcharts. For example, two blocks shown in succession may in fact be executed substantially concurrently or the blocks may sometimes be executed in the reverse order, depending upon the functionality/acts involved. Moreover, the functionality of a given block of the flowcharts and block diagrams may be separated into multiple blocks and/or the functionality of two or more blocks of the flowcharts and block diagrams may be at least partially integrated. Finally, other blocks may be added/inserted between the blocks that are illustrated. Moreover, although some of the diagrams include arrows on communication paths to show a primary direction of communication, it is to be understood that communication may occur in the opposite direction to the depicted arrows.

The foregoing is illustrative of the present invention and is not to be construed as limiting thereof. Although a few exemplary embodiments of this invention have been described, those skilled in the art will readily appreciate that many modifications are possible in the exemplary embodiments without materially departing from the teachings and advantages of this invention. Accordingly, all such modifications are intended to be included within the scope of this invention as defined in the claims. The invention is defined by the following claims, with equivalents of the claims to be included therein.

That which is claimed is:

1. A method of monitoring a subject via a monitoring device, wherein the monitoring device includes a photoplethysmography (PPG) sensor that is in communication with at least one processor, the method comprising:

processing PPG sensor signals received from the PPG sensor by the at least one processor to obtain RR-intervals and identify a statistical relationship between first and second RR-intervals of the RR-intervals obtained from the PPG sensor signals;
selecting a biometric signal extraction algorithm or circuit by the at least one processor in response to identifica-

tion of the statistical relationship between the first and second RR-intervals; and then

processing PPG sensor signals received from the PPG sensor by the at least one processor using the selected biometric signal extraction algorithm or circuit to produce physiological information about the subject.

2. The method of claim 1, wherein the physiological information that is produced includes one or more of the following: subject heart rate, subject respiration rate, subject RR interval (RRi), subject heart rate variability (HRV), subject blood pressure, subject blood analyte levels, subject cardiovascular properties.

3. The method of claim 1, wherein the monitoring device is configured to be positioned at or within an ear of the subject, secured to an appendage of the subject, or worn on a bodily location of the subject.

4. The method of claim 1, wherein the at least one processor is configured to process the PPG sensor signals using the selected biometric signal extraction algorithm or circuit to obtain one or more of the following: subject heart rate, subject respiration rate, subject RR interval (RRi), subject heart rate variability (HRV), subject blood pressure, subject blood analyte levels, subject cardiovascular properties.

5. The method of claim 1, wherein, prior to selecting a biometric signal extraction algorithm or circuit, the method comprises processing the statistical relationship between the first and second RR-intervals to determine a type of motion of the subject or a physiological status of the subject.

6. The method of claim 5, wherein the processing to determine the type of motion of the subject comprises determining that the type of motion of the subject is periodic motion or non-periodic motion.

7. The method of claim 6, wherein the processing the PPG sensor signals using the selected biometric tracking algorithm or circuit comprises:

processing the PPG sensor signals using a first biometric signal extraction algorithm or circuit in response to determining that the type of motion is periodic motion, wherein the first biometric signal extraction algorithm or circuit comprises frequency domain processing and/or filtering; and

processing the PPG sensor signals using a second biometric signal extraction algorithm or circuit, which is different from the first biometric signal extraction algorithm or circuit, in response to determining that the type of motion is non-periodic motion, wherein the second biometric signal extraction algorithm or circuit comprises time domain processing and/or filtering.

8. The method of claim 7, wherein the second biometric signal extraction algorithm or circuit comprises a modification of the first biometric signal extraction algorithm or circuit, wherein the modification is based on the type of motion of the subject.

9. The method of claim 5, wherein processing the PPG sensor signals to identify the statistical relationship between the first and second RR-intervals therein is performed using a first biometric signal extraction algorithm or circuit that is different than the selected biometric signal extraction algorithm or circuit, and wherein the selected biometric signal extraction algorithm or circuit is configured based on noise associated with the type of motion or physiological status.

10. A method of monitoring a subject via a monitoring device, wherein the monitoring device includes a photoplethysmography (PPG) sensor that is in communication with at least one processor, the method comprising:

21

processing PPG sensor signals received from the PPG sensor by the at least one processor to obtain RR-intervals and identify a statistical relationship between the RR-intervals obtained from the PPG sensor signals; processing the statistical relationship between the RR-intervals to determine a stress status for the subject; selecting a biometric signal extraction algorithm or circuit by the at least one processor in response to identification of the statistical relationship between the RR-intervals and based on the stress status determined therefrom; and then

processing PPG sensor signals received from the PPG sensor by the at least one processor using the selected biometric signal extraction algorithm or circuit to produce physiological information about the subject.

11. The method of claim 10, wherein:

the processing the statistical relationship between the RR-intervals to determine the stress status comprises determining a likelihood of a first health condition;

the selecting the biometric signal extraction algorithm or circuit is based on the likelihood of the first health condition; and

the processing the PPG sensor signals using the selected biometric signal extraction algorithm to produce the

22

physiological information indicates a diagnosis of the first health condition or a second health condition that is associated with the first health condition.

12. The method of claim 11, wherein the first health condition comprises atrial fibrillation.

13. The method of claim 10, wherein:

processing the PPG sensor signals to identify the statistical relationship between the RR-intervals therein is performed using a first biometric signal extraction algorithm or circuit that is different than the selected biometric signal extraction algorithm or circuit; and

responsive processing the PPG sensor signals using the selected biometric signal extraction algorithm or circuit, an accuracy of the physiological information is increased relative to processing the PPG sensor signals using the first biometric signal extraction algorithm or circuit.

14. The method of claim 13, wherein the first biometric signal extraction algorithm or circuit comprises frequency domain processing and/or filtering, and wherein the selected biometric signal extraction algorithm or circuit comprises time domain processing and/or filtering.

* * * * *

专利名称(译)	识别受试者活动类型的生理监测设备和方法		
公开(公告)号	US10610158	公开(公告)日	2020-04-07
申请号	US15/299684	申请日	2016-10-21
[标]申请(专利权)人(译)	瓦倫賽爾公司		
申请(专利权)人(译)	VALENCELL INC.		
当前申请(专利权)人(译)	VALENCELL INC.		
[标]发明人	AUMER MICHAEL EDWARD LEBOEUF STEVEN FRANCIS		
发明人	AUMER, MICHAEL EDWARD LEBOEUF, STEVEN FRANCIS		
IPC分类号	A61B5/00 A61B5/0205 A61B5/11 A61B5/021 A61B5/024 A61B5/08 A61B5/145		
CPC分类号	A61B5/721 A61B5/6817 A61B5/0205 A61B5/7278 A61B5/02405 A61B5/021 A61B5/145 A61B5/0816 A61B5/6815 A61B5/02438 A61B5/7257 A61B5/1118 A61B5/6831 A61B5/02416 A61B2562/0219		
审查员(译)	JACKSON , GARY		
优先权	62/245919 2015-10-23 US		
其他公开文献	US20170112447A1		
外部链接	Espacenet		

摘要(译)

描述了用于监视对象的方法和设备。被配置为附接到对象的身体的监视设备包括被配置为检测和/或测量来自对象的生理信息的传感器以及被配置为检测和/或测量对象的运动信息的运动传感器。生理传感器和运动传感器与处理器通信，该处理器被配置为接收和分析由生理传感器和运动传感器产生的信号。处理器被配置为处理运动传感器信号以识别受试者的活动特征。一旦确定了活动特征，则处理器被配置为响应于受试者的活动特征来选择生物特征信号提取算法或电路，然后经由生物特征信号提取算法或电路处理生理传感器信号以产生关于该生物特征信号的生理信息。学科。

