



US009314167B2

(12) **United States Patent**
LeBoeuf et al.

(10) **Patent No.:** **US 9,314,167 B2**
(45) **Date of Patent:** ***Apr. 19, 2016**

(54) **METHODS FOR GENERATING DATA
OUTPUT CONTAINING PHYSIOLOGICAL
AND MOTION-RELATED INFORMATION**

(71) Applicant: **Valencell, Inc.**, Raleigh, NC (US)

(72) Inventors: **Steven Francis LeBoeuf**, Raleigh, NC
(US); **Jesse Berkley Tucker**,
Youngsville, NC (US); **Michael Edward
Aumer**, Raleigh, NC (US)

(73) Assignee: **Valencell, Inc.**, Raleigh, NC (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **14/550,039**

(22) Filed: **Nov. 21, 2014**

(65) **Prior Publication Data**

US 2015/0105633 A1 Apr. 16, 2015

Related U.S. Application Data

(63) Continuation of application No. 14/184,396, filed on
Feb. 19, 2014, now Pat. No. 8,923,941, which is a
continuation of application No. 12/691,388, filed on
Jan. 21, 2010, now Pat. No. 8,700,111.

(Continued)

(51) **Int. Cl.**
A61B 5/00 (2006.01)
A61B 5/0205 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **A61B 5/0205** (2013.01); **A61B 5/00**
(2013.01); **A61B 5/0013** (2013.01);

(Continued)

(58) **Field of Classification Search**

USPC 600/310
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,595,219 A 7/1971 Friedlander et al.
4,240,882 A 12/1980 Ang et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE 3910749 A1 10/1990
EP 1 480 278 A2 11/2004

(Continued)

OTHER PUBLICATIONS

“U.S. Army Fitness Training Handbook” by the Department of the
Army, 2003, The Lyons Press. p. 17.

(Continued)


Primary Examiner — Rodney Fuller

(74) *Attorney, Agent, or Firm* — Myers Bigel & Sibley

(57) **ABSTRACT**

A method of generating a data string containing physiological and motion-related information includes sensing physical activity of a subject via at least one motion sensor attached to the subject, sensing physiological information from the subject via at least one photoplethysmography (PPG) sensor attached to the subject, and processing signals from the at least one motion sensor and signals from the at least one PPG sensor into a serial data string of physiological information and motion-related information. A plurality of subject physiological parameters can be extracted from the physiological information, and a plurality of subject physical activity parameters can be extracted from the motion-related information. The serial data string is parsed out such that an application-specific interface can utilize the physiological information and motion-related information for an application that generates statistical relationships between subject physiological parameters and subject physical activity parameters in the physiological information and motion-related information.

35 Claims, 21 Drawing Sheets



Related U.S. Application Data

- (60) Provisional application No. 61/208,567, filed on Feb. 25, 2009, provisional application No. 61/208,574, filed on Feb. 25, 2009, provisional application No. 61/212,444, filed on Apr. 13, 2009, provisional application No. 61/274,191, filed on Aug. 14, 2009.

(51) Int. Cl.

G06F 19/00 (2011.01)
A61B 5/024 (2006.01)
H04R 1/10 (2006.01)
A61B 5/11 (2006.01)
A61B 5/1455 (2006.01)
A61B 5/0476 (2006.01)
A61B 5/16 (2006.01)
F21V 8/00 (2006.01)
A61B 5/021 (2006.01)
A61B 5/08 (2006.01)
A61B 5/01 (2006.01)
A61B 5/145 (2006.01)
A61B 5/026 (2006.01)
A61B 5/0295 (2006.01)
A61B 5/091 (2006.01)

(52) U.S. Cl.

CPC **A61B 5/0022** (2013.01); **A61B 5/0024** (2013.01); **A61B 5/0059** (2013.01); **A61B 5/0082** (2013.01); **A61B 5/0084** (2013.01); **A61B 5/01** (2013.01); **A61B 5/021** (2013.01); **A61B 5/02055** (2013.01); **A61B 5/0261** (2013.01); **A61B 5/02427** (2013.01); **A61B 5/02433** (2013.01); **A61B 5/0476** (2013.01); **A61B 5/0816** (2013.01); **A61B 5/11** (2013.01); **A61B 5/1107** (2013.01); **A61B 5/1118** (2013.01); **A61B 5/1455** (2013.01); **A61B 5/14532** (2013.01); **A61B 5/14551** (2013.01); **A61B 5/165** (2013.01); **A61B 5/418** (2013.01); **A61B 5/486** (2013.01); **A61B 5/4812** (2013.01); **A61B 5/4845** (2013.01); **A61B 5/4848** (2013.01); **A61B 5/4866** (2013.01); **A61B 5/4875** (2013.01); **A61B 5/4884** (2013.01); **A61B 5/6803** (2013.01); **A61B 5/6815** (2013.01); **A61B 5/6817** (2013.01); **A61B 5/6819** (2013.01); **A61B 5/6826** (2013.01); **A61B 5/6838** (2013.01); **A61B 5/721** (2013.01); **A61B 5/7214** (2013.01); **A61B 5/7282** (2013.01); **A61B 5/742** (2013.01); **A61B 5/7475** (2013.01); **G02B 6/0001** (2013.01); **G06F 19/3418** (2013.01); **H04R 1/105** (2013.01); **H04R 1/1091** (2013.01); **A61B 5/024** (2013.01); **A61B 5/026** (2013.01); **A61B 5/0295** (2013.01); **A61B 5/02405** (2013.01); **A61B 5/02416** (2013.01); **A61B 5/091** (2013.01); **A61B 5/411** (2013.01); **A61B 5/415** (2013.01); **A61B 2560/0242** (2013.01); **A61B 2562/0233** (2013.01)

(56) References Cited

U.S. PATENT DOCUMENTS

4,331,154 A 5/1982 Broadwater et al.
 4,438,772 A 3/1984 Slavin
 4,491,760 A 1/1985 Linvill
 4,521,499 A 6/1985 Switzer
 4,541,905 A 9/1985 Kuwana et al.
 4,592,807 A 6/1986 Switzer
 4,655,225 A 4/1987 Dahne et al.

4,882,492 A 11/1989 Schlager
 4,896,676 A 1/1990 Sasaki
 4,928,704 A 5/1990 Hardt
 4,957,109 A 9/1990 Groeger et al.
 5,002,060 A 3/1991 Nedivi
 5,022,970 A 6/1991 Cook et al.
 5,079,421 A 1/1992 Knudson et al.
 5,086,229 A 2/1992 Rosenthal et al.
 5,143,078 A 9/1992 Mather et al.
 5,226,417 A 7/1993 Swedlow et al.
 5,348,002 A 9/1994 Caro
 5,377,100 A 12/1994 Pope et al.
 5,482,036 A 1/1996 Diab et al.
 5,492,129 A 2/1996 Greenberger
 5,499,301 A 3/1996 Sudo et al.
 5,581,648 A 12/1996 Sahagen
 5,596,987 A 1/1997 Chance
 5,662,117 A 9/1997 Bittman
 5,673,692 A 10/1997 Schulze et al.
 5,697,374 A 12/1997 Odagiri et al.
 5,711,308 A 1/1998 Singer
 5,725,480 A 3/1998 Oosta et al.
 5,743,260 A 4/1998 Chung et al.
 5,779,631 A 7/1998 Chance
 5,807,114 A 9/1998 Hodges et al.
 5,853,005 A 12/1998 Scanlon
 5,904,654 A 5/1999 Wohltmann et al.
 5,938,593 A 8/1999 Quellette
 5,964,701 A 10/1999 Asada et al.
 5,971,931 A 10/1999 Raff
 5,974,338 A 10/1999 Asano et al.
 5,995,858 A 11/1999 Kinast
 6,004,274 A 12/1999 Nolan et al.
 6,013,007 A 1/2000 Root et al.
 6,023,541 A 2/2000 Merchant et al.
 6,045,511 A 4/2000 Ott et al.
 6,067,006 A 5/2000 O'Brien
 6,070,093 A 5/2000 Oosta et al.
 6,078,829 A 6/2000 Uchida et al.
 6,080,110 A 6/2000 Thorgersen
 6,186,145 B1 2/2001 Brown
 6,198,394 B1 3/2001 Jacobsen et al.
 6,198,951 B1 3/2001 Kosuda et al.
 6,205,354 B1 3/2001 Gellermann et al.
 6,231,519 B1 5/2001 Blants et al.
 6,283,915 B1 9/2001 Aceti et al.
 6,285,816 B1 9/2001 Anderson et al.
 6,289,230 B1 9/2001 Chaiken et al.
 6,298,314 B1 10/2001 Blackadar et al.
 6,332,868 B1 12/2001 Sato et al.
 6,358,216 B1 3/2002 Kraus et al.
 6,361,660 B1 3/2002 Goldstein
 6,371,925 B1 4/2002 Imai et al.
 6,374,129 B1 4/2002 Chin et al.
 6,415,167 B1 7/2002 Blank et al.
 6,443,890 B1 9/2002 Schulze et al.
 6,444,474 B1 9/2002 Thomas et al.
 6,454,718 B1 9/2002 Clift
 6,458,080 B1 10/2002 Brown et al.
 6,470,893 B1 10/2002 Boesen
 6,514,278 B1 2/2003 Hibst et al.
 6,527,711 B1 3/2003 Stivoric et al.
 6,527,712 B1 3/2003 Brown et al.
 6,534,012 B1 3/2003 Hazen et al.
 6,556,852 B1 4/2003 Schulze et al.
 6,569,094 B2 5/2003 Suzuki et al.
 6,571,117 B1 5/2003 Marbach
 6,605,038 B1 8/2003 Teller et al.
 6,616,613 B1 9/2003 Goodman
 6,631,196 B1 10/2003 Taenzer et al.
 6,647,378 B2 11/2003 Kindo
 6,656,116 B2 12/2003 Kim et al.
 6,694,180 B1 2/2004 Boesen
 6,760,610 B2 7/2004 Tschupp et al.
 6,783,501 B2 8/2004 Takahashi et al.
 6,808,473 B2 10/2004 Hisano et al.
 6,859,658 B1 2/2005 Krug
 6,893,396 B2 5/2005 Schulze et al.
 6,941,239 B2 9/2005 Unuma et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,953,435	B2	10/2005	Kondo et al.	2004/0120844	A1	6/2004	Tribelsky et al.
6,996,427	B2	2/2006	Ali et al.	2004/0122294	A1	6/2004	Hatlestad et al.
6,997,879	B1	2/2006	Turcott	2004/0122702	A1	6/2004	Sabol et al.
7,018,338	B2	3/2006	Vetter et al.	2004/0133123	A1	7/2004	Leonhardt et al.
7,024,369	B1	4/2006	Brown et al.	2004/0135571	A1	7/2004	Uutela et al.
7,041,062	B2	5/2006	Friedrichs et al.	2004/0138578	A1	7/2004	Pineda et al.
7,043,287	B1	5/2006	Khalil et al.	2004/0186390	A1	9/2004	Ross et al.
7,054,674	B2	5/2006	Cane et al.	2004/0219056	A1	11/2004	Tribelsky et al.
7,088,234	B2	8/2006	Naito et al.	2004/0220488	A1	11/2004	Vyshedskiy et al.
7,107,088	B2	9/2006	Aceti	2004/0225207	A1	11/2004	Bae et al.
7,175,601	B2	2/2007	Verjus et al.	2004/0228494	A1	11/2004	Smith
7,209,775	B2	4/2007	Bae et al.	2004/0242976	A1	12/2004	Abreu
7,252,639	B2	8/2007	Kimura et al.	2005/0004458	A1	1/2005	Kanayama et al.
7,263,396	B2	8/2007	Chen et al.	2005/0027216	A1	2/2005	Guillemaud et al.
7,336,982	B2	2/2008	Yoo et al.	2005/0030540	A1	2/2005	Thornton
7,341,559	B2	3/2008	Schulz et al.	2005/0033200	A1	2/2005	Soehren et al.
7,376,451	B2	5/2008	Mahony et al.	2005/0038349	A1	2/2005	Choi et al.
7,470,234	B1	12/2008	Elhag et al.	2005/0043600	A1	2/2005	Diab et al.
7,483,730	B2	1/2009	Diab et al.	2005/0043630	A1	2/2005	Buchert
7,486,988	B2	2/2009	Goodall et al.	2005/0058456	A1	3/2005	Yoo
7,519,327	B2	4/2009	White	2005/0059870	A1	3/2005	Aceti
7,583,994	B2	9/2009	Scholz	2005/0101872	A1	5/2005	Sattler et al.
7,625,285	B2	12/2009	Breving	2005/0113167	A1	5/2005	Buchner et al.
7,652,569	B2	1/2010	Kiff et al.	2005/0113656	A1	5/2005	Chance
7,689,437	B1	3/2010	Teller et al.	2005/0113703	A1	5/2005	Farrington et al.
7,695,440	B2	4/2010	Kondo et al.	2005/0116820	A1	6/2005	Goldreich
7,725,147	B2	5/2010	Li et al.	2005/0119833	A1	6/2005	Nanikashvili
7,756,559	B2	7/2010	Abreu	2005/0148883	A1	7/2005	Boesen
7,843,325	B2	11/2010	Otto	2005/0154264	A1	7/2005	Lecompte et al.
7,894,869	B2	2/2011	Hoarau	2005/0177034	A1	8/2005	Beaumont
7,914,468	B2	3/2011	Shalon et al.	2005/0187448	A1	8/2005	Petersen et al.
7,991,448	B2	8/2011	Edgar et al.	2005/0192515	A1	9/2005	Givens et al.
8,050,728	B2	11/2011	Al-Ali et al.	2005/0196009	A1	9/2005	Boesen
8,055,319	B2	11/2011	Oh et al.	2005/0203349	A1	9/2005	Nanikashvili
8,059,924	B1	11/2011	Letant et al.	2005/0203357	A1	9/2005	Debreczeny et al.
8,130,105	B2	3/2012	Al-Ali et al.	2005/0209516	A1	9/2005	Fraden
8,137,270	B2	3/2012	Keenan et al.	2005/0222487	A1	10/2005	Miller et al.
8,172,459	B2	5/2012	Abreu	2005/0222903	A1	10/2005	Buchheit et al.
8,175,670	B2	5/2012	Baker, Jr. et al.	2005/0228244	A1	10/2005	Banet
8,251,903	B2	8/2012	LeBoeuf et al.	2005/0228299	A1	10/2005	Banet
8,255,027	B2	8/2012	Al-Ali et al.	2005/0240087	A1	10/2005	Keenan et al.
8,328,420	B2	12/2012	Abreu	2005/0258816	A1	11/2005	Zen et al.
8,416,959	B2	4/2013	Lott et al.	2005/0259811	A1	11/2005	Kimm et al.
8,504,679	B2	8/2013	Spire et al.	2006/0009685	A1	1/2006	Finarov et al.
8,506,524	B2	8/2013	Graskov et al.	2006/0063993	A1	3/2006	Yu et al.
8,512,242	B2	8/2013	LeBoeuf et al.	2006/0064037	A1	3/2006	Shalon et al.
8,730,048	B2	5/2014	Shen et al.	2006/0084878	A1	4/2006	Banet et al.
8,923,941	B2*	12/2014	LeBoeuf	2006/0122520	A1	6/2006	Banet et al.
			A61B 5/00	2006/0123885	A1	6/2006	Yates et al.
			600/310	2006/0142665	A1	6/2006	Garay et al.
				2006/0202816	A1	9/2006	Crump et al.
				2006/0205083	A1	9/2006	Zhao
				2006/0210058	A1	9/2006	Kock et al.
				2006/0211922	A1	9/2006	Al-Ali et al.
				2006/0211924	A1	9/2006	Dalke et al.
				2006/0224059	A1	10/2006	Swedlow et al.
				2006/0240558	A1	10/2006	Zhao
				2006/0246342	A1	11/2006	MacPhee
				2006/0251334	A1	11/2006	Oba et al.
				2006/0264730	A1	11/2006	Stivorac et al.
				2006/0292533	A1	12/2006	Selod
				2007/0004449	A1	1/2007	Sham
				2007/0004969	A1	1/2007	Kong et al.
				2007/0015992	A1	1/2007	Filkins et al.
				2007/0021206	A1	1/2007	Sunnen
				2007/0027367	A1	2/2007	Oliver et al.
				2007/0060800	A1	3/2007	Drinan et al.
				2007/0063850	A1	3/2007	Devaul et al.
				2007/0082789	A1	4/2007	Nissila et al.
				2007/0083092	A1	4/2007	Rippo et al.
				2007/0083095	A1	4/2007	Rippo et al.
				2007/0088221	A1	4/2007	Stahmann
				2007/0106167	A1	5/2007	Kinast
				2007/0112598	A1	5/2007	Heckerman et al.
				2007/0116314	A1	5/2007	Grilliot et al.
				2007/0118054	A1	5/2007	Pinhas et al.
				2007/0165872	A1	7/2007	Bridger et al.
				2007/0167850	A1	7/2007	Russell et al.
				2007/0197881	A1	8/2007	Wolf et al.
2001/0049471	A1	12/2001	Suzuki et al.				
2002/0143242	A1	10/2002	Nemirovski				
2002/0156386	A1	10/2002	Dardik et al.				
2002/0156654	A1	10/2002	Roe et al.				
2002/0186137	A1	12/2002	Skardon				
2003/0002705	A1	1/2003	Boesen				
2003/0007631	A1	1/2003	Bolognesi et al.				
2003/0045785	A1	3/2003	Diab et al.				
2003/0050563	A1	3/2003	Suribhotla et al.				
2003/0064712	A1	4/2003	Gaston et al.				
2003/0083583	A1	5/2003	Kovtun et al.				
2003/0109030	A1	6/2003	Uchida et al.				
2003/0181795	A1	9/2003	Suzuki et al.				
2003/0212336	A1	11/2003	Lee et al.				
2003/0220584	A1	11/2003	Honeyager et al.				
2003/0222268	A1	12/2003	Yocom et al.				
2004/0004547	A1	1/2004	Appelt et al.				
2004/0022700	A1	2/2004	Kim et al.				
2004/0030581	A1	2/2004	Leven				
2004/0034289	A1	2/2004	Teller et al.				
2004/0034293	A1	2/2004	Kimball				
2004/0054291	A1	3/2004	Schulz et al.				
2004/0075677	A1	4/2004	Loyall et al.				
2004/0077934	A1	4/2004	Massad				
2004/0103146	A1	5/2004	Park				
2004/0117204	A1	6/2004	Mazar et al.				

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0213020	A1	9/2007	Novac
2007/0233403	A1	10/2007	Alwan et al.
2007/0265097	A1	11/2007	Havukainen
2007/0270667	A1	11/2007	Coppi et al.
2007/0270671	A1	11/2007	Gal
2007/0293781	A1	12/2007	Sims et al.
2008/0004536	A1	1/2008	Baxi et al.
2008/0039731	A1	2/2008	McCombie et al.
2008/0076972	A1	3/2008	Dorogusker et al.
2008/0081963	A1	4/2008	Naghavi et al.
2008/0096726	A1	4/2008	Riley et al.
2008/0114220	A1	5/2008	Banet et al.
2008/0132798	A1	6/2008	Hong et al.
2008/0141301	A1	6/2008	Azzaro et al.
2008/0146890	A1	6/2008	LeBoeuf et al.
2008/0146892	A1	6/2008	LeBoeuf et al.
2008/0154098	A1	6/2008	Morris et al.
2008/0154105	A1	6/2008	Lemay
2008/0165017	A1	7/2008	Schwartz
2008/0170600	A1	7/2008	Sattler et al.
2008/0171945	A1	7/2008	Dotter
2008/0177162	A1	7/2008	Bae et al.
2008/0200774	A1	8/2008	Luo
2008/0203144	A1	8/2008	Kim
2008/0249594	A1	10/2008	Dietrich
2008/0287752	A1	11/2008	Stroetz et al.
2009/0005662	A1	1/2009	Petersen et al.
2009/0006457	A1	1/2009	Stivoric et al.
2009/0010461	A1	1/2009	Klinghult et al.
2009/0030350	A1	1/2009	Yang et al.
2009/0054752	A1	2/2009	Jonnalagadda et al.
2009/0069645	A1	3/2009	Nielsen et al.
2009/0082994	A1	3/2009	Schuler et al.
2009/0088611	A1	4/2009	Buschmann
2009/0093687	A1	4/2009	Telfort et al.
2009/0105548	A1	4/2009	Bart
2009/0105556	A1	4/2009	Fricke et al.
2009/0112071	A1	4/2009	LeBoeuf et al.
2009/0131761	A1	5/2009	Moroney, III et al.
2009/0131764	A1	5/2009	Lee et al.
2009/0214060	A1	8/2009	Chuang et al.
2009/0221888	A1	9/2009	Wijesiriwardana
2009/0227853	A1	9/2009	Wijesiriwardana
2009/0240125	A1	9/2009	Such et al.
2009/0253992	A1	10/2009	Van Der Loo
2009/0253996	A1	10/2009	Lee et al.
2009/0264711	A1	10/2009	Schuler et al.
2009/0270698	A1	10/2009	Shioi et al.
2009/0287067	A1*	11/2009	Dorogusker
2009/0299215	A1	12/2009	Zhang
2010/0004517	A1	1/2010	Bryenton et al.
2010/0045663	A1	2/2010	Chen et al.
2010/0100013	A1	4/2010	Hu et al.
2010/0113948	A1	5/2010	Yang et al.
2010/0168531	A1	7/2010	Shaltis et al.
2010/0172522	A1	7/2010	Mooring et al.
2010/0179389	A1	7/2010	Moroney et al.
2010/0185105	A1	7/2010	Baldinger
2010/0217102	A1	8/2010	LeBoeuf et al.
2010/0217103	A1	8/2010	Abdul-Hafiz et al.
2010/0222655	A1	9/2010	Starr et al.
2010/0228315	A1	9/2010	Nielsen
2010/0234714	A1	9/2010	Mercier et al.
2010/0268056	A1	10/2010	Picard et al.
2010/0274100	A1	10/2010	Behar et al.
2010/0274109	A1	10/2010	Hu et al.
2010/0292589	A1	11/2010	Goodman
2010/0298653	A1	11/2010	McCombie et al.
2011/0028810	A1	2/2011	Van Slyke et al.
2011/0028813	A1	2/2011	Watson et al.
2011/0081037	A1	4/2011	Oh et al.
2011/0105869	A1	5/2011	Wilson et al.
2011/0112382	A1	5/2011	Li et al.
2011/0142371	A1	6/2011	King et al.

2011/0288379	A1	11/2011	Wu
2012/0030547	A1	2/2012	Raptis et al.
2012/0095303	A1	4/2012	He
2012/0156933	A1	6/2012	Kreger et al.
2012/0179011	A1	7/2012	Moon et al.
2012/0197093	A1	8/2012	LeBoeuf et al.
2012/0277548	A1	11/2012	Burton
2013/0053661	A1	2/2013	Alberth et al.
2013/0072765	A1	3/2013	Kahn et al.
2013/0131519	A1	5/2013	LeBoeuf et al.
2013/0245387	A1	9/2013	Patel
2013/0336495	A1	12/2013	Burgett et al.
2014/0051940	A1	2/2014	Messerschmidt
2014/0052567	A1	2/2014	Bhardwaj et al.
2014/0073486	A1	3/2014	Ahmed et al.
2014/0127996	A1	5/2014	Park et al.
2014/0219467	A1	8/2014	Kurtz
2014/0236531	A1	8/2014	Carter
2014/0275852	A1	9/2014	Hong et al.

FOREIGN PATENT DOCUMENTS

EP	2 077 091	A2	7/2009
GB	2 408 209	A	5/2005
GB	2 411 719	A	9/2005
JP	7-241279		9/1995
JP	9-253062		9/1997
JP	9-299342		11/1997
JP	2000-116611		4/2000
JP	2001-025462		1/2001
JP	20030159221		6/2003
JP	2004-513750	A	5/2004
JP	2004-283523		10/2004
JP	2007-044203		2/2007
JP	2007-185348		7/2007
JP	2008-136556	A	6/2008
JP	2008-279061	A	11/2008
JP	2009-153664	A	7/2009
JP	2010-526646		8/2010
WO	WO 00/24064		4/2000
WO	WO 00/047108	A1	8/2000
WO	WO 01/08552	A1	2/2001
WO	WO 2005/020121	A1	3/2005
WO	WO 2005/110238	A1	11/2005
WO	WO 2006/009830	A2	1/2006
WO	WO 2006/067690	A2	6/2006
WO	WO 2007/012931	A2	2/2007
WO	WO 2007/053146	A1	5/2007
WO	WO 2008/141306	A2	11/2008
WO	WO 2013/038296	A1	3/2013

OTHER PUBLICATIONS

“Warfighter Physiological and Environmental Monitoring: A Study for the U.S. Army Research Institute in Environmental Medicine and the Soldier Systems Center”, Massachusetts Institute of Technology Lincoln Laboratory, Final Report, Nov. 1, 2004, prepared for the U.S. Army under Air Force Contract F19628-00-C-0002; approved for public release.

Colligan, M. J. et al. in “The psychological effects of indoor air pollution”, Bulletin of the New York Academy of Medicine, vol. 57, No. 10, Dec. 1981, p. 1014-1026.

de Paula Santos, U. et al. in “Effects of air pollution on blood pressure and heart rate variability: a panel study of vehicular traffic controllers in the city of Sao Paulo, Brazil”, European Heart Journal (2005) 26, 193-200.

Ebert, T et al., “Influence of Hydration Status on Thermoregulation and Cycling Hill Climbing,” Med. Sci. Sport Exerc. vol. 39, No. 2, pp. 323-329, 2007.

Falkner et al., “Cardiovascular response to mental stress in normal adolescents with hypertensive parents. Hemodynamics and mental stress in adolescents,” *Hypertension* 1979, 1:23-30.

Fleming et al., “A Comparison of Signal Processing Techniques for the Extraction of Breathing Rate from the Photoplethysmogram,” World Academy of Science, Engineering and Technology, vol. 30, Oct. 2007, pp. 276-280.

(56)

References Cited

OTHER PUBLICATIONS

- Geladas et al., "Effect of cold air inhalation on core temperature in exercising subjects under stress," *The American Physiological Society*, pp. 2381-2387, 1988.
- Gold, D.R. et al. in "Ambient Pollution and Heart Rate Variability", *Circulation* 2000, 101:1267-1273.
- International Search Report corresponding to International Patent Application No. PCT/US2012/046446, Date of Mailing: Jan. 14, 2013, 3 pages.
- International Search Report and Written Opinion of the International Searching Authority, corresponding to PCT/US2012/0948079, mailed Oct. 9, 2012.
- International Search Report Corresponding to International Application No. PCT/US2012/022634, Date of Mailing: Aug. 22, 2012, 9 pages.
- Maomao et al., "Mobile Context-Aware Game for the Next Generation," 2nd International Conference on Application and Development of Computer Games ADCOG 2003, p. 78-81.
- Maughan, R.J., "Impact of mild dehydration on wellness and on exercise performance," *European Journal of Clinical Nutrition*, 57, Suppl. 2, pp. S19-S23, 2003.
- Maughan et al., "Exercise, Heat, Hydration and the Brain," *Journal of the American College of Nutrition*, vol. 26, No. 5, pp. 604S-612S, 2007.
- Mostardi, R., et al., "The effect of increased body temperature due to exercise on the heart rate and the maximal aerobic power," *Europ. J. Appl. Physiol.*, 33, pp. 237-245, 1974.
- Nakajima et al., "Monitoring of heart and respiratory rates by photoplethysmography using a digital filtering technique," *Med. Eng. Phys.*, vol. 18, No. 5, Jul. 1996, pp. 365-372.
- Notification of Transmittal of the International Search Report and Written Opinion of the International Search Authority issued Jul. 30, 2010 by the Korean Intellectual Property Office for corresponding International Application No. PCT/US2010/021936.
- Notification of Transmittal of the International Search Report and the Written Opinion of the International Search Authority issued Sep. 16, 2010 by the Korean Intellectual Property Office for corresponding International Application No. PCT/US2010/024922.
- Notification of Transmittal of the International Search Report and the Written Opinion of the International Search Authority issued Sep. 27, 2010 by the Korean Intellectual Property Office for corresponding International Application No. PCT/US2010/025216.
- Shorten et al., "Acute effect of environmental temperature during exercise on subsequent energy intake in active men," *Am. J. Clin. Nutr.* 90, pp. 1215-1221, 2009.
- Thompson, M.W., "Cardiovascular drift and critical core temperature: factors limiting endurance performance in the heat?" *J. Exerc. Sci. Fit.*, vol. 4, No. 1, pp. 15-24, 2006.
- Edmison et al., "E-Textile Based Automatic Activity Diary for Medical Annotation and Analysis," *Proc. BSN 2006 Int. Workshop Wearable Implantable Body Sensor Netw.* (2006), pp. 131-145, Apr. 3-5, 2006.
- European Search Report, EP Application No. 13863449.8, Oct. 19, 2015, 3 pages.
- European Search Report, EP Application No. 14743615.8, Oct. 12, 2015, 3 pages.
- European Search Report, EP Application No. 14743839.4, Oct. 12, 2015, 3 pages.
- Gibbs et al., "Reducing Motion Artifact in Wearable Bio-Sensors Using MEMS Accelerometers for Active Noise Cancellation," 2005 American Control Conference, Jun. 8-10, 2005, Portland, OR, USA, pp. 1581-1586.
- International Preliminary Report on Patentability, PCT/US2014/012940, Jun. 17, 2015, 23 pages.
- International Search Report and Written Opinion of the International Searching Authority, corresponding to International Patent Application No. PCT/US2014/012940, Date of Mailing: Oct. 16, 2014, 13 pages.
- International Search Report corresponding to International Patent Application No. PCT/US2014/012909, Date of Mailing: May 13, 2014, 3 pages.
- Notification Concerning Transmittal of International Preliminary Report on Patentability, PCT/US2014/012909, Jul. 28, 2015.
- Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, PCT/US2015/014562, Oct. 28, 2015.
- Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, PCT/US2015/042636, Oct. 29, 2015.
- Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, PCT/US2015/042015, Oct. 29, 2015.
- Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, PCT/US2015/042035, Oct. 29, 2015.
- Wood et al., "Active Motion Artifact Reduction for Wearable Sensors Using Laguerre Expansion and Signal Separation," *Proceedings of the 2005 IEEE Engineering in Medicine and Biology, 27th Annual Conference*, Shanghai, China, Sep. 1-4, 2005, pp. 3571-3574.
- FiTrainer "The Only Trainer You Need"; <http://itami.com>; Downloaded Feb. 26, 2010; © 2008 FiTrainer™; 2 pages.
- Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration corresponding to International Application No. PCT/US2013/070271; Date of Mailing: Feb. 26, 2014; International Search Report; Written Opinion of the International Searching Authority; 13 pages.
- Notification of Transmittal of the International Search Report and Written Opinion issued Aug. 26, 2010 by the Korean Intellectual Property Office for corresponding International Application No. PCT/US2010/021629.
- Anpo et al. "Photocatalytic Reduction of Co₂ With H₂O on Titanium Oxides Anchored within Micropores of Zeolites: Effects of the Structure of the Active Sites and the Addition of Pt" *J. Phys. Chem. B*, 101:2632-2636 (1997).
- Bärsan et al. "Understanding the fundamental principles of metal oxide based gas sensors; the example of CO sensing with SnO₂ sensors in the presence of humidity" *Journal of Physics: Condensed Matter* 15:R813-R839 (2003).
- Bott "Electrochemistry of Semiconductors" *Current Separations* 17(3):87-91 (1998).
- European Search Report corresponding to European Application No. 07862660.3 dated Apr. 25, 2012; 7 pages.
- International Search Report and Written Opinion of the International Searching Authority, corresponding to PCT/US2007/025114, mailed May 13, 2008.
- Martins et al. "Zinc oxide as an ozone sensor" *Journal of Applied Physics* 96(3):1398-1408 (2004).
- Saladin et al. "Photosynthesis of CH₄ at a TiO₂ Surface from Gaseous H₂O and CO₂" *J. Chem. Soc., Chem. Commun.* 533-534 (1995).
- Skubal et al. "Detection and identification of gaseous organics using a TiO₂ sensor" *Journal of Photochemistry and Photobiology A: Chemistry* 148:103-108 (2002).
- Skubal et al. "Monitoring the Electrical Response of Photoinduced Organic Oxidation on TiO₂ Surfaces" Manuscript submitted Oct. 2000 to SPIE Intl. Symposium on Environment & Industrial Sensing, Boston, MA, Nov. 5-8, 2000, sponsored by SPIE, 10 pp.
- Zhang et al. "Development of Chemical Oxygen Demand On-Line Monitoring System Based on a Photoelectrochemical Degradation Principle" *Environ. Sci. Technol.*, 40(7):2363-2368 (2006).
- Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, PCT/US2015/046079, Dec. 29, 2015.
- Communication pursuant to Article 94(3) EPC, European Patent Application No. 13863449.8, Nov. 5, 2015, 7 pages.
- Communication pursuant to Article 94(3) EPC, European Patent Application No. 14743615.8, Dec. 23, 2015, 7 pages.
- Communication pursuant to Article 94(3) EPC, European Patent Application No. 14743839.4, Dec. 23, 2015, 6 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4A






FIG. 4B








FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 9A




FIG. 9B




FIG. 10




FIG. 9C




FIG. 9E











FIG. 9D



**FIG. 13**






FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19





FIG. 20






FIG. 22A




FIG. 22B




FIG. 23

METHODS FOR GENERATING DATA OUTPUT CONTAINING PHYSIOLOGICAL AND MOTION-RELATED INFORMATION

RELATED APPLICATIONS

This application is a continuation application of pending U.S. patent application Ser. No. 14/184,396, filed Feb. 19, 2014, which is a continuation application of U.S. patent application Ser. No. 12/691,388, filed Jan. 21, 2010, now U.S. Pat. No. 8,700,111, which claims the benefit of and priority to U.S. Provisional Patent Application No. 61/208,567 filed Feb. 25, 2009, U.S. Provisional Patent Application No. 61/208,574 filed Feb. 25, 2009, U.S. Provisional Patent Application No. 61/212,444 filed Apr. 13, 2009, and U.S. Provisional Patent Application No. 61/274,191 filed Aug. 14, 2009, the disclosures of which are incorporated herein by reference as if set forth in their entireties.

FIELD OF THE INVENTION

The present invention relates generally to headsets and, more particularly, to headset earbuds.

BACKGROUND OF THE INVENTION

There is growing market demand for personal health and environmental monitors, for example, for gauging overall health and metabolism during exercise, athletic training, dieting, daily life activities, sickness, and physical therapy. However, traditional health monitors and environmental monitors may be bulky, rigid, and uncomfortable—generally not suitable for use during daily physical activity. There is also growing interest in generating and comparing health and environmental exposure statistics of the general public and particular demographic groups. For example, collective statistics may enable the healthcare industry and medical community to direct healthcare resources to where they are most highly valued. However, methods of collecting these statistics may be expensive and laborious, often utilizing human-based recording/analysis steps at multiple sites.

As such, improved ways of collecting, storing and analyzing physiological information are needed. In addition, improved ways of seamlessly extracting physiological information from a person during everyday life activities, especially during high activity levels, may be important for enhancing fitness training and healthcare quality, promoting and facilitating prevention, and reducing healthcare costs.

SUMMARY

It should be appreciated that this Summary is provided to introduce a selection of concepts in a simplified form, the concepts being further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of this disclosure, nor is it intended to limit the scope of the invention.

According to some embodiments of the present invention, a headset configured to be attached to the ear of a person includes a base, an earbud housing extending outwardly from the base that is configured to be positioned within an ear of a subject, and a cover surrounding the earbud housing. The base includes a speaker, an optical emitter, and an optical detector. The cover includes light transmissive material that is in optical communication with the optical emitter and the optical detector and serves as a light guide to deliver light from the optical emitter into the ear canal of the subject wearing the

headset at one or more predetermined locations and to collect light external to the earbud housing and deliver the collected light to the optical detector. The optical emitter, via the light-guiding cover, directs optical energy towards a particular region of ear and the optical detector detects secondary optical energy emanating from the ear region. In some embodiments, the optical detector may include an optical filter configured to pass secondary optical energy at selective wavelengths. In some embodiments, the light transmissive material of the cover may be configured, for example via the use of cladding and/or light reflective material, such that the cover serves as a light guide that is coupled in parallel to the optical emitter and detector. In some embodiments, the light transmissive material of the cover may be configured, for example via the use of cladding and/or light reflective material, such that the cover serves as a light guide that is coupled perpendicular to the optical emitter and detector.

In some embodiments, the headset may include various electronic components secured to the base. For example, the headset may include one or more environmental sensors configured to detect and/or measure environmental conditions in a vicinity of the headset. The headset may include a signal processor configured to receive and process signals produced by the optical detector. For example, in some embodiments, a signal processor may be configured to extract secondary optical energy and remove optical noise or environmental noise. The headset may include a signal processor configured to receive and process signals produced by the one or more environmental sensors. In addition, the headset may include a transmitter configured to transmit signals processed by the signal processor to a remote device in real time. Headsets according to embodiments of the present invention may utilize, for example, Bluetooth®, Wi-Fi, ZigBee, or other wireless transmitters.

In some embodiments, a housing is secured to and overlies the base so as to enclose and protect the speaker, optical emitter and optical detector, as well as other electronic components secured to the base (e.g., sensors, processor, transmitter etc.).

The earbud housing is in acoustical communication with the speaker and has at least one aperture through which sound from the speaker can pass. The light-guiding cover surrounding the earbud housing also includes at least one aperture through which sound from the speaker can pass. The cover may be formed from a soft, resilient material, such as silicone which deforms when inserted within an ear canal of a subject. In some embodiments, the cover includes an alignment member that facilitates alignment of the earbud housing within an ear canal of a subject.

Light directed into the ear of a subject from a light emitter and the subsequent collection of light at a light detector, according to embodiments of the present invention, may be utilized for detecting and/or measuring, among other things, body temperature, skin temperature, blood gas levels, muscle tension, heart rate, blood flow, cardiopulmonary functions, etc.

In some embodiments of the present invention, the light-guiding cover may include a lens that is in optical communication with the optical emitter and/or optical detector. The lens may be configured to focus light emitted by the optical emitter and/or to focus collected light toward the optical detector. In some embodiments, multiple lenses may be incorporated into a light-guiding cover.

In some embodiments, the light-guiding cover may include a light diffusion region in optical communication with the light transmissive material that diffuses light emitted by the optical detector.

In some embodiments, the light-guiding cover may include a luminescence-generating region, such as a phosphor-containing region, that is in optical communication with the light transmissive material. The luminescence-generating region may be embedded within the light-guiding cover and/or on a surface of the light-guiding cover. The luminescence-generating region is configured to receive light emitted by the optical emitter and convert at least a portion of the received light to light having a different wavelength from that of the received light.

In some embodiments, the light-guiding cover includes one or more grooves formed therein. Each groove is configured to direct external light to the optical detector.

In some embodiments, the light transmissive material of the light-guiding cover is configured to direct light from the optical emitter to a plurality of locations at an outer surface of the cover for delivery into an ear canal of a subject.

In some embodiments, the light transmissive material of the light-guiding cover is a translucent material or includes translucent material in selected locations.

In some embodiments, a light reflective material is on at least a portion of one or both of the inner and outer surfaces of the light-guiding cover.

According to some embodiments of the present invention, a light-guiding earbud for a headset includes light transmissive material that is in optical communication with an optical emitter and optical detector associated with the headset. The light transmissive material is configured to deliver light from the optical emitter into the ear canal of a subject at one or more predetermined locations and to collect light external to the earbud housing and deliver the collected light to the optical detector. In some embodiments, the light emitter and light detector may be integral with the earbud. For example, in some embodiments, a flexible optical emitter is incorporated within the earbud and is in optical communication with the light transmissive material.

In some embodiments, an earbud includes at least one lens in optical communication with the light transmissive material. Each lens may be configured to focus light from the optical emitter onto one or more predetermined locations in the ear of a subject and/or to focus collected external light onto the optical detector.

In some embodiments of the present invention, an earbud may include luminescent material. Luminescent light is generated from optical excitation of the luminescent material by an optical emitter.

In some embodiments of the present invention, an earbud may integrate a sensor module containing a plurality of sensor elements for measuring physiological information and at least one noise source for measuring noise information. A “noise source”, as used herein, refers to a sensor, such as an optical sensor, inertial sensor, electrically conductive sensor, capacitive sensor, inductive sensor, etc., and derives its name from the fact that it is a source of input to a filter, such as an adaptive filter described below.

The physiological sensors of the sensor module may generate a signal that includes physiological information plus noise information. The noise may be removed by combining the physiological information and noise information from the sensor module with noise information from the noise source of the sensor module via an electronic filtering method, such as a signal processing technique. Specific examples of such signal processing techniques include FIR (Finite Impulse Response), IIR (Infinite Impulse Response), informatics, machine learning, and adaptive filter methods. The output of the adaptive filter may be a physiological signal that is wholly or partially free of noise. In some embodiments, motion-

related noise from a subject activity such as running may be removed from the physiological plus noise signal generated by a photoplethysmography (PPG) sensor for measuring blood constituent levels or blood flow properties, such as blood oxygen level, VO_2 , or heart rate.

In some embodiments of the present invention, the noise source input of an adaptive filter may include a “blocked channel” of optical energy, an inertial sensor, or environmental energy. In some embodiments, the environmental energy may be unwanted ambient optical noise.

In some embodiments of the present invention, a processor/multiplexor processes physiological signals and noise signals into a data string. This data string may contain information relating to physiological information and motion-related information. The processing method may include signal processing techniques such as pre-adaptive signal conditioning, adaptive filtering, and parameter extraction.

In some embodiments, an earbud includes one or more sensor modules that includes one or more sensors for sensing physiological information and environmental information, such as noise, for example. As such, the earbud may function as a physiological monitor as well as an environmental monitor. In some embodiments, the earbud may include a microprocessor that is in electrical communication with the sensor module(s). For example, a microprocessor incorporated into an earbud may be configured to execute an adaptive filter algorithm to remove noise from at least one signal generated by a sensor module in the earbud. A microprocessor may also be configured to process information from the one or more sensors to generate a digital output string, wherein the digital output string includes a plurality of physiological and motion-related information.

Physiological sensors that may be incorporated into headsets and/or earbuds, according to some embodiments of the present invention, may be configured to detect and/or measure one or more of the following types of physiological information: heart rate, pulse rate, breathing rate, blood flow, VO_2 , VO_{2max} , heartbeat signatures, cardio-pulmonary health, organ health, metabolism, electrolyte type and/or concentration, physical activity, caloric intake, caloric metabolism, blood metabolite levels or ratios, blood pH level, physical and/or psychological stress levels and/or stress level indicators, drug dosage and/or dosimetry, physiological drug reactions, drug chemistry, biochemistry, position and/or balance, body strain, neurological functioning, brain activity, brain waves, blood pressure, cranial pressure, hydration level, auscultatory information, auscultatory signals associated with pregnancy, physiological response to infection, skin and/or core body temperature, eye muscle movement, blood volume, inhaled and/or exhaled breath volume, physical exertion, exhaled breath physical and/or chemical composition, the presence and/or identity and/or concentration of viruses and/or bacteria, foreign matter in the body, internal toxins, heavy metals in the body, anxiety, fertility, ovulation, sex hormones, psychological mood, sleep patterns, hunger and/or thirst, hormone type and/or concentration, cholesterol, lipids, blood panel, bone density, organ and/or body weight, reflex response, sexual arousal, mental and/or physical alertness, sleepiness, auscultatory information, response to external stimuli, swallowing volume, swallowing rate, sickness, voice characteristics, voice tone, voice pitch, voice volume, vital signs, head tilt, allergic reactions, inflammation response, auto-immune response, mutagenic response, DNA, proteins, protein levels in the blood, water content of the blood, pheromones, internal body sounds, digestive system functioning, cellular regeneration response, healing response, stem cell regeneration response, etc.

Environmental sensors that may be incorporated into headsets and/or earbuds, according to some embodiments of the present invention, may be configured to detect and/or measure one or more of the following types of environmental information: climate, humidity, temperature, pressure, barometric pressure, soot density, airborne particle density, airborne particle size, airborne particle shape, airborne particle identity, volatile organic chemicals (VOCs), hydrocarbons, polycyclic aromatic hydrocarbons (PAHs), carcinogens, toxins, electromagnetic energy, optical radiation, X-rays, gamma rays, microwave radiation, terahertz radiation, ultraviolet radiation, infrared radiation, radio waves, atomic energy alpha particles, atomic energy beta-particles, gravity, light intensity, light frequency, light flicker, light phase, ozone, carbon monoxide, carbon dioxide, nitrous oxide, sulfides, airborne pollution, foreign material in the air, viruses, bacteria, signatures from chemical weapons, wind, air turbulence, sound and/or acoustical energy, ultrasonic energy, noise pollution, human voices, animal sounds, diseases expelled from others, exhaled breath and/or breath constituents of others, toxins from others, pheromones from others, industrial and/or transportation sounds, allergens, animal hair, pollen, exhaust from engines, vapors and/or fumes, fuel, signatures for mineral deposits and/or oil deposits, snow, rain, thermal energy, hot surfaces, hot gases, solar energy, hail, ice, vibrations, traffic, the number of people in a vicinity of the person, coughing and/or sneezing sounds from people in the vicinity of the person, loudness and/or pitch from those speaking in the vicinity of the person.

According to some embodiments of the present invention, earbuds for headsets may include a chipset having at least one sensor element, noise source element, signal processor, input/output line, digital control, and power regulator.

Light-guiding earbuds according to the various embodiments of the present invention may be utilized with mono headsets (i.e., headsets having one earbud) as well as stereo headsets (i.e., headsets having two earbuds). Additionally, the light-guiding region of earbuds, according to embodiments of the present invention, may be integrated not only into an earbud cover and earbud housing, but also into each or all components of an earbud. Moreover, light-guiding earbuds according to the various embodiments of the present invention may be utilized with hearing aids, body jewelry, or any other attachment that can be placed near the head region, such as eye glasses or shades, a headband, a cap, helmet, visor, or the like.

According to some embodiments of the present invention, a monitoring device includes a circular band capable of encircling a finger of a subject, and a base having an optical emitter and an optical detector attached to the circular band. The circular band includes light transmissive material in optical communication with the optical emitter and optical detector that is configured to deliver light from the optical emitter to one or more portions of the finger of the subject and to collect light from one or more portions of the finger of the subject and deliver the collected light to the optical detector. In some embodiments, the circular band includes first and second concentric body portions.

In some embodiments, the circular band includes a lens region in optical communication with the optical emitter that focuses light emitted by the optical emitter and/or that collects light reflected from a finger. In some embodiments the circular band includes a phosphor-containing region in optical communication with the light transmissive material, wherein the phosphor-containing region receives light emitted

by the optical emitter and converts at least a portion of the received light to light having a different wavelength from the received light.

In some embodiments, the light transmissive material of the circular band has an outer surface and an inner surface, and a cladding material, such as light reflective material, is on (or near) at least a portion of one or both of the inner and outer surfaces.

In some embodiments, the base includes one or more of the following: a signal processor configured to receive and process signals produced by the optical detector, a transmitter configured to transmit signals processed by the signal processor to a remote device.

According to some embodiments of the present invention, a monitoring device configured to be attached to the body of a subject includes a base having an optical emitter and an optical detector, and light transmissive material attached to the base. The light transmissive material is in optical communication with the optical emitter and optical detector and is configured to deliver light from the optical emitter to one or more portions of the body of the subject and to collect light from one or more portions of the body of the subject and deliver the collected light to the optical detector. The light transmissive material may include adhesive material in one or more locations that is configured to adhesively secure the device to the body of the subject.

In some embodiments, an outer body portion is attached to the base and to the light transmissive material. The outer body portion may include adhesive material in one or more locations that is configured to adhesively secure the device to the body of the subject.

In some embodiments, the light transmissive material includes a lens region that is in optical communication with the optical emitter and that focuses light emitted by the optical emitter and/or that collects light reflected from a finger. In some embodiments, the light transmissive material includes a phosphor-containing region that receives light emitted by the optical emitter and converts at least a portion of the received light to light having a different wavelength from the received light. In some embodiments, the light transmissive material has an outer surface and an inner surface, and a light reflective material is disposed on or near at least a portion of one or both of the inner and outer surfaces.

In some embodiments, the base includes one or more of the following: a signal processor configured to receive and process signals produced by the optical detector, a transmitter configured to transmit signals processed by the signal processor to a remote device.

It is noted that aspects of the invention described with respect to one embodiment may be incorporated in a different embodiment although not specifically described relative thereto. That is, all embodiments and/or features of any embodiment can be combined in any way and/or combination. Applicant reserves the right to change any originally filed claim or file any new claim accordingly, including the right to be able to amend any originally filed claim to depend from and/or incorporate any feature of any other claim although not originally claimed in that manner. These and other objects and/or aspects of the present invention are explained in detail below.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which form a part of the specification, illustrate various embodiments of the present invention. The drawings and description together serve to fully explain embodiments of the present invention.

FIG. 1 is an exploded perspective view of a headset with a light-guiding earbud, according to some embodiments of the present invention.

FIG. 2 is a perspective view of a stereo headset incorporating light-guiding earbuds, according to some embodiments of the present invention.

FIG. 3 is a side section view of a light-guiding earbud for a headset, according to some embodiments of the present invention.

FIGS. 4A-4D are side section views of light-guiding earbuds for a headset, according to some embodiments of the present invention.

FIG. 5 is a side section view of a light-guiding earbud for a headset, according to some embodiments of the present invention.

FIG. 6 is a side section view of a light-guiding earbud for a headset, according to some embodiments of the present invention.

FIG. 7A is a side section view of a light-guiding earbud for a headset, according to some embodiments of the present invention.

FIG. 7B is a perspective view of a flexible optical emitter utilized in the earbud of FIG. 7A, according to some embodiments of the present invention.

FIG. 8A is a side section view of a light-guiding earbud for a headset, according to some embodiments of the present invention.

FIG. 8B is a cross-sectional view of the earbud of FIG. 8A taken along lines 8B-8B.

FIG. 8C is a side section view of a light-guiding earbud for a headset, according to some embodiments of the present invention.

FIG. 8D is a side section view of a light-guiding earbud for a headset, according to some embodiments of the present invention.

FIG. 9A is a side section view of a light-guiding earbud for a headset, according to some embodiments of the present invention.

FIG. 9B is a cross-sectional view of the earbud of FIG. 9A taken along lines 9B-9B.

FIG. 9C illustrates luminescent particles within the earbud cover of FIGS. 9A-9B, according to some embodiments of the present invention.

FIG. 9D is a side section view of a light-guiding earbud for a headset, according to some embodiments of the present invention.

FIG. 9E is a cross-sectional view of the earbud of FIG. 9D taken along lines 9E-9E.

FIG. 10 illustrates various anatomy of a human ear.

FIG. 11A is a side section view of a light-guiding earbud for a headset, according to some embodiments of the present invention.

FIG. 11B is a cross-sectional view of the earbud of FIG. 11A taken along lines 11B-11B.

FIGS. 12A-12B illustrate respective opposite sides of a sensor module that may be located near the periphery of an earbud, according to some embodiments of the present invention.

FIG. 13 illustrates an adaptive filter and noise source for removing noise from a noisy physiological signal, according to some embodiments of the present invention.

FIGS. 14A-14D are respective graphs of time-dependent data collected from a light-guiding earbud worn by a person, according to some embodiments of the present invention.

FIG. 15 is a graph of processed physiological signal data from a headset having one or more light-guiding earbuds, according to some embodiments of the present invention.

FIG. 16 is a flow chart of operations for extracting physiological information from headset sensor signals, according to some embodiments of the present invention.

FIG. 17 is a block diagram that illustrates sensor signals being processed into a digital data string including activity data and physiological data, according to some embodiments of the present invention.

FIG. 18 illustrates a digital data string, according to some embodiments of the present invention.

FIG. 19 illustrates the optical interaction between the sensor module of FIGS. 12A-12B and the skin of a subject.

FIG. 20 illustrates a chipset for use in a headset, according to some embodiments of the present invention.

FIG. 21 illustrates a chipset for use in a stereo headset, according to some embodiments of the present invention.

FIG. 22A is a top plan view of a monitoring device configured to be attached to finger of a subject, according to some embodiments of the present invention.

FIG. 22B is a cross-sectional view of the monitoring device of FIG. 22A taken along lines 22B-22B.

FIG. 23 is a side view of a monitoring device configured to be attached to the body of a subject, according to some embodiments of the present invention.

DETAILED DESCRIPTION

The present invention will now be described more fully hereinafter with reference to the accompanying figures, in which embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Like numbers refer to like elements throughout. In the figures, certain layers, components or features may be exaggerated for clarity, and broken lines illustrate optional features or operations unless specified otherwise. In addition, the sequence of operations (or steps) is not limited to the order presented in the figures and/or claims unless specifically indicated otherwise. Features described with respect to one figure or embodiment can be associated with another embodiment or figure although not specifically described or shown as such.

It will be understood that when a feature or element is referred to as being “on” another feature or element, it can be directly on the other feature or element or intervening features and/or elements may also be present. In contrast, when a feature or element is referred to as being “directly on” another feature or element, there are no intervening features or elements present. It will also be understood that, when a feature or element is referred to as being “connected”, “attached” or “coupled” to another feature or element, it can be directly connected, attached or coupled to the other feature or element or intervening features or elements may be present. In contrast, when a feature or element is referred to as being “directly connected”, “directly attached” or “directly coupled” to another feature or element, there are no intervening features or elements present. Although described or shown with respect to one embodiment, the features and elements so described or shown can apply to other embodiments. It will also be appreciated by those of skill in the art that references to a structure or feature that is disposed “adjacent” another feature may have portions that overlap or underlie the adjacent feature.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be

further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, steps, operations, elements, components, and/or groups thereof. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

Spatially relative terms, such as “under”, “below”, “lower”, “over”, “upper” and the like, may be used herein for ease of description to describe one element or feature’s relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if a device in the figures is inverted, elements described as “under” or “beneath” other elements or features would then be oriented “over” the other elements or features. Thus, the exemplary term “under” can encompass both an orientation of over and under. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly. Similarly, the terms “upwardly”, “downwardly”, “vertical”, “horizontal” and the like are used herein for the purpose of explanation only unless specifically indicated otherwise.

It will be understood that although the terms first and second are used herein to describe various features/elements, these features/elements should not be limited by these terms. These terms are only used to distinguish one feature/element from another feature/element. Thus, a first feature/element discussed below could be termed a second feature/element, and similarly, a second feature/element discussed below could be termed a first feature/element without departing from the teachings of the present invention. Like numbers refer to like elements throughout.

Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the specification and relevant art and should not be interpreted in an idealized or overly formal sense unless expressly so defined herein. Well-known functions or constructions may not be described in detail for brevity and/or clarity.

The term “headset” includes any type of device or earpiece that may be attached to or near the ear (or ears) of a user and may have various configurations, without limitation. Headsets incorporating light-guiding earbuds as described herein may include mono headsets (one earbud) and stereo headsets (two earbuds), earbuds, hearing aids, ear jewelry, face masks, headbands, and the like.

The term “real-time” is used to describe a process of sensing, processing, or transmitting information in a time frame which is equal to or shorter than the minimum timescale at which the information is needed. For example, the real-time monitoring of pulse rate may result in a single average pulse-rate measurement every minute, averaged over 30 seconds, because an instantaneous pulse rate is often useless to the end user. Typically, averaged physiological and environmental information is more relevant than instantaneous changes. Thus, in the context of the present invention, signals may sometimes be processed over several seconds, or even minutes, in order to generate a “real-time” response.

The term “monitoring” refers to the act of measuring, quantifying, qualifying, estimating, sensing, calculating, interpolating, extrapolating, inferring, deducing, or any combination of these actions. More generally, “monitoring” refers to a way of getting information via one or more sensing elements. For example, “blood health monitoring” includes monitoring blood gas levels, blood hydration, and metabolite/electrolyte levels.

The term “physiological” refers to matter or energy of or from the body of a creature (e.g., humans, animals, etc.). In embodiments of the present invention, the term “physiological” is intended to be used broadly, covering both physical and psychological matter and energy of or from the body of a creature. However, in some cases, the term “psychological” is called-out separately to emphasize aspects of physiology that are more closely tied to conscious or subconscious brain activity rather than the activity of other organs, tissues, or cells.

The term “body” refers to the body of a subject (human or animal) that may wear a headset incorporating one or more light-guiding earbuds, according to embodiments of the present invention.

In the following figures, various headsets and light-guiding earbuds for use with headsets will be illustrated and described for attachment to the ear of the human body. However, it is to be understood that embodiments of the present invention are not limited to those worn by humans.

The ear is an ideal location for wearable health and environmental monitors. The ear is a relatively immobile platform that does not obstruct a person’s movement or vision. Headsets located at an ear have, for example, access to the inner-ear canal and tympanic membrane (for measuring core body temperature), muscle tissue (for monitoring muscle tension), the pinna and earlobe (for monitoring blood gas levels), the region behind the ear (for measuring skin temperature and galvanic skin response), and the internal carotid artery (for measuring cardiopulmonary functioning), etc. The ear is also at or near the point of exposure to: environmental breathable toxicants of interest (volatile organic compounds, pollution, etc.; noise pollution experienced by the ear; and lighting conditions for the eye. Furthermore, as the ear canal is naturally designed for transmitting acoustical energy, the ear provides a good location for monitoring internal sounds, such as heartbeat, breathing rate, and mouth motion.

Wireless, Bluetooth®-enabled, and/or other personal communication headsets may be configured to incorporate physiological and/or environmental sensors, according to some embodiments of the present invention. As a specific example, Bluetooth® headsets are typically lightweight, unobtrusive devices that have become widely accepted socially. Moreover, Bluetooth® headsets are cost effective, easy to use, and are often worn by users for most of their waking hours while attending or waiting for cell phone calls. Bluetooth® headsets configured according to embodiments of the present invention are advantageous because they provide a function for the user beyond health monitoring, such as personal communication and multimedia applications, thereby encouraging user compliance. Exemplary physiological and environmental sensors that may be incorporated into a Bluetooth® or other type of headsets include, but are not limited to accelerometers, auscultatory sensors, pressure sensors, humidity sensors, color sensors, light intensity sensors, pressure sensors, etc.

Headsets, both mono (single earbud) and stereo (dual earbuds), incorporating low-profile sensors and other electronics, according to embodiments of the present invention, offer a platform for performing near-real-time personal health and

environmental monitoring in wearable, socially acceptable devices. The capability to unobtrusively monitor an individual's physiology and/or environment, combined with improved user compliance, is expected to have significant impact on future planned health and environmental exposure studies. This is especially true for those that seek to link environmental stressors with personal stress level indicators. The large scale commercial availability of this low-cost device can enable cost-effective large scale studies. The combination of monitored data with user location via GPS data can make on-going geographic studies possible, including the tracking of infection over large geographic areas. The commercial application of the proposed platform encourages individual-driven health maintenance and promotes a healthier lifestyle through proper caloric intake and exercise.

Accordingly, some embodiments of the present invention combine a personal communications headset device with one or more physiological and/or environmental sensors. Other embodiments may combine physiological and/or environmental sensors into a headset device.

Optical coupling into the blood vessels of the ear may vary between individuals. As used herein, the term "coupling" refers to the interaction or communication between excitation light entering a region and the region itself. For example, one form of optical coupling may be the interaction between excitation light generated from within a light-guiding earbud and the blood vessels of the ear. In one embodiment, this interaction may involve excitation light entering the ear region and scattering from a blood vessel in the ear such that the intensity of scattered light is proportional to blood flow within the blood vessel. Another form of optical coupling may be the interaction between excitation light generated by an optical emitter within an earbud and the light-guiding region of the earbud. Thus, an earbud with integrated light-guiding capabilities, wherein light can be guided to multiple and/or select regions along the earbud, can assure that each individual wearing the earbud will generate an optical signal related to blood flow through the blood vessels. Optical coupling of light to a particular ear region of one person may not yield photoplethysmographic signals for each person. Therefore, coupling light to multiple regions may assure that at least one blood-vessel-rich region will be interrogated for each person wearing the light-guiding earbud. Coupling multiple regions of the ear to light may also be accomplished by diffusing light from a light source within the earbud.

Embodiments of the present invention are not limited to headsets that communicate wirelessly. In some embodiments of the present invention, headsets configured to monitor an individual's physiology and/or environment may be wired to a device that stores and/or processes data. In some embodiments, this information may be stored on the headset itself. Furthermore, embodiments of the present invention are not limited to earbuds. In some embodiments, the light-guiding structure may be molded around another part of the body, such as a digit, finger, toe, limb, around the nose or earlobe, or the like. In other embodiments, the light-guiding structure may be integrated into a patch, such as a bandage that sticks on a person's body.

Referring to FIG. 1, a headset 10 according to some embodiments of the present invention is illustrated. The illustrated headset 10 includes a base 12, a headset housing 14, an earbud housing 16, and a cover 18 that surrounds the earbud housing 16. The base 12 includes a main circuit board 20 that supports and/or is connected to various electronic components. In the illustrated embodiment, a speaker 22, optical emitter 24, optical detectors 26, and thermopile 28 (described below) are mounted onto a secondary circuit board 32 which

is secured to the main circuit board 20. The earbud housing surrounds the speaker 22, optical emitter 24, optical detectors 26, and thermopile 28. Collectively, the earbud housing 16, cover 18, and various electronic components (e.g., speaker 22, optical emitter 24, optical detectors 26, thermopile 28) located within the earbud housing 16 of the illustrated headset 10 may be referred to as an earbud 30. The headset housing 14 is secured to the base 12 and is configured to enclose and protect the various electronic components mounted to the base (e.g., main circuit board 20 and components secured thereto, etc.) from ambient interference (air, humidity, particulates, electromagnetic interference, etc.).

Each optical detector 26 may be a photodiode, photodetector, phototransistor, thyristor, solid state device, optical chipset, or the like. The optical emitter 24 may be a light-emitting diode (LED), laser diode (LD), compact incandescent bulb, micro-plasma emitter, IR blackbody source, or the like. The speaker 22 may be a compact speaker, such as an inductive speaker, piezoelectric speaker, electrostatic speaker, or the like. One or more microphones, such as electrets, MEMS, acoustic transducers, or the like, may also be located within the headset housing or earbud housing to pick up speech, physiological sounds, and/or environmental sounds.

The main circuit board 20 and secondary circuit board 32 may also support one or more sensor modules (not shown) that contain various physiological and/or environmental sensors. For example, a sensor module, such as sensor module 70 illustrated in FIGS. 12A-12B, may be attached to the circuit boards 20, 32. The circuit boards 20, 32 also may include at least one signal processor (not shown), at least one wireless module (not shown) for communicating with a remote device, and/or at least one memory storage device (not shown). An exemplary wireless module may include a wireless chip, antenna, or RFID tag. In some embodiments, the wireless module may include a low-range wireless chip or chipset, such as a Bluetooth® or ZigBee chip. These electronic components may be located on the main circuit board 20, or on another circuit board, such as the secondary circuit board 32, attached to the main circuit board.

Secondary circuit board 32 may also include a temperature sensor, such as a thermopile 28 mounted thereto. The thermopile 28 is oriented so as to point towards the tympanic membrane within the ear of a subject wearing the headset 10 through the acoustic orifices 34a, 34b in the earbud housing 16 and cover 18, respectively. The secondary circuit board 32 may be in electrical contact with the main circuit board 20 via soldering, connectors, wiring, or the like. A battery 36, such as a lithium polymer battery or other portable battery, may be mounted to the main circuit board 20 and may be charged via a USB charge port 38. Although not shown in FIG. 1, an ear hook may be attached to the base 12 or housing 14 to help stabilize the earbud 30 and headset 10 worn by a subject and such that the earbud 30 is consistently placed at the same location within the ear canal of a subject.

In the illustrated embodiment, the earbud housing 16 is in acoustical communication with the speaker 22 and includes an aperture 34a through which sound from the speaker 22 can pass. However, additional apertures may also be utilized. The cover 18 also includes at least one aperture 34b through which sound from the speaker 22 can pass. The thermopile 28 is used as a heat sensor and measures thermal radiation from the ear of a subject via the acoustic apertures 34a, 34b. Additional or other sensors may be in the location of the thermopile 28, aligned towards the tympanic membrane, to sense other forms of energy, such as acoustic, mechanical, chemical, optical, or nuclear energy from the tympanic membrane

region. For example, a photodetector may replace the thermopile 28 to measure light scattering off the tympanic membrane.

The cover 18 includes light transmissive material in a portion 19 thereof that is referred to as a light-guiding region. The light transmissive material in light-guiding region 19 is in optical communication with the optical emitter 24 and detectors 26. The light transmissive material in light-guiding region 19 is configured to deliver light from the optical emitter 24 into an ear canal of the subject at one or more predetermined locations and to collect light external to the earbud 30 and deliver the collected light to the optical detectors 26. As such, the earbud 30 of the illustrated headset 10 is referred to as a "light-guiding" earbud 30.

In some embodiments, the light transmissive material in the light-guiding region 19 may include a lens (e.g., lens 18L illustrated in FIG. 6). The lens 18L is in optical communication with the optical emitter 24 and/or with the optical detectors 26. For example, a lens 18L may be configured to focus light emitted by the optical emitter 24 onto one or more portions of an ear and/or to focus collected light on the light detectors 26. Lenses are described below with respect to FIGS. 5-6.

In some embodiments, the earbud cover 18 may integrate a transparent light-guiding layer, wherein air is utilized as a cladding layer. For example, the earbud cover 18 may include an optically transparent silicone molded layer, and the earbud housing 16 may be removed such that a cladding layer is air. In some embodiments, the earbud housing 16 may be closed, and the light-guiding region 19 may be integrated within the cover 18 or between the housing 16 and cover 18.

The illustrated cover 18 of FIG. 1 includes an alignment member 40 (also referred to as a stabilization arm) that facilitates alignment of the earbud 30 within an ear canal of a subject. The alignment member 40 may facilitate stable measurements of optical scattered light from the ear region, which can be important for PPG measurements and tympanic temperature measurements.

In some embodiments, a light-guiding cover 18 is formed from a soft, resilient material, such as silicone, which deforms when inserted within an ear canal of a subject. However, various materials may be utilized for light-guiding covers 18 and for serving as light guides depending on the type of earbud desired for a particular use case, according to embodiments of the present invention. For example, in some embodiments, a light-guiding cover 18 may be formed from a substantially rigid material such that the light-guiding earbud 30 is substantially rigid. For example, for a running use case, the runner may wish to have firm but soft earbuds, such that the earbud may deform to some extent when inserted into the ear. In such case, the light-guiding region may be silicone or other soft material and the outer cladding may be air, a polymer, plastic, or a soft material having a lower index of refraction than silicone.

FIG. 2 illustrates a stereo headset 100 that utilizes two light-guiding earbuds 130, according to some embodiments of the present invention. The headset 100 also includes various sensor elements 132 located at several regions in the stereo headset 100. A benefit of the stereo headset 100 may be that the total number of sensors measuring the ear region may be doubled; alternatively, the sensors in each earbud may be halved. Another benefit of the stereo headset is that it may enable stereo music during daily activities. Another benefit of the stereo headset is that asymmetric physiological differences can be detected in the user by measuring each side of the user in real-time. For example, differences in blood flow between right and left sides of a user may be detected, indi-

cating changes in right/left brain activity, the onset of a stroke, localized inflammation, or the like.

Light-guiding earbuds according to various embodiments of the present invention will now be described with respect to FIGS. 3, 4A-4D, 5, 6, 7A-7B, 8A-8D, 9A-9B, and 11A-11B. Referring initially to FIGS. 3-4, a light-guiding earbud 30 includes a base 50, an earbud housing 16 extending outwardly from the base 50 that is configured to be positioned within an ear E of a subject, and a cover 18 that surrounds the earbud housing 16. The earbud housing 16 is in acoustical communication with a speaker 22 and includes at least one aperture 34a through which sound from the speaker 22 can pass. The cover 18 includes at least one aperture 34b through which sound from the speaker 22 can pass, and includes light transmissive material in optical communication with an optical emitter 24 and detector 26.

The cover 18 includes cladding material 21 on an inner surface 18b thereof and on an outer surface 18a thereof, as illustrated. An end portion 18f of the cover outer surface 18a does not have cladding material. As such, the cover 18 serves as a light guide that delivers light from the optical emitter 24 through the end portion 18f and into the ear canal C of a subject at one or more predetermined locations and that collects light external to the earbud housing 16 and delivers the collected light to the optical detector 26. In the various embodiments described herein, the terms light guide and cover are intended to be interchangeable. However, it should be noted that, in other embodiments, the earbud housing 16 may also serve as a light guide without the need for cover 18.

The base 50 in all of the earbud embodiments (FIGS. 3, 4A-4D, 5, 6, 7A-7B, 8A-8D, 9A-9B, and 11A-11B) described herein may include any combination of a printed circuit board, electrical connectors, and housing component for a headset. For example, the base 50 in FIGS. 3-6, 7A-7B, 8A-8D, 9A-9B, and 11A-11B, may include, for example, the base 12 of the headset 10 of FIG. 1, the main circuit board 20 of the headset 10 of FIG. 1, the housing 14 of the headset 10 of FIG. 1, or may be a combination of the base 12, main circuit board 20, and/or housing 14 of the headset 10 of FIG. 1.

The optical emitter 24 generates inspection light 111 and the light-guiding region 19 of the light guide 18 directs the inspection light 111 towards an ear region. This light is called inspection light because it interrogates the surface of the ear, penetrates the skin of the ear, and generates a scattered light response 110 which may effectively inspect blood vessels within the ear region. The optical detector 26 detects scattered light 110 from an ear region and the light-guiding region 19 of the light guide 18 guides the light to the optical detector 26 through the light-guiding region 19, as illustrated.

In the embodiment of FIG. 3, the light-guiding earbud 30 is configured for optical coupling that is parallel to the light guide (i.e., cover 18). The optical detector 26 and optical emitter 24 are configured to detect and generate light substantially parallel to the light-guiding region 19 of the light guide 18. For example, the light guide 18 defines an axial direction A_1 . The optical emitter 24 and optical detector 26 are each oriented such that their respective primary emitting and detecting planes P_1 , P_2 are each facing a respective direction A_3 , A_2 that is substantially parallel with direction A_1 .

The light guiding region 19 of the light guide 18 in the illustrated embodiment of FIG. 3 is defined by cladding material 21 that helps confine light within the light guiding region 19. The cladding material 21 may be reflective material in some embodiments. In other embodiments, the cladding material may be optically transparent or mostly transparent with a lower index of refraction than the light transmissive material of the cover 18. The cladding 21 may be a layer of

material applied to one or more portions of the inner and/or outer surfaces **18a**, **18b** of the light guide **18**. In some embodiments, the outer surface **16a** of the earbud housing **16** may serve as cladding that confines light within the light-guiding region **19**. In some embodiments, the light transmissive material of the light guide **18** may be composed of a material having a higher index of refraction than the cladding material **21**. In some embodiments, air may serve as a cladding layer.

In the embodiment of FIG. 4A, the light-guiding earbud **30** is configured for optical coupling that is substantially perpendicular to the light guide (i.e., cover **18**). The optical detector **26** and optical emitter **24** are configured to detect and generate light substantially perpendicular to the light-guiding region **19** of the light guide **18**. For example, the light guide **18** defines an axial direction A_1 . The optical emitter **24** and optical detector **26** are each oriented such that their respective primary emitting and detecting planes P_1 , P_2 are each facing a respective direction A_3 , A_2 that is substantially perpendicular to direction A_1 . The orientation of the optical emitter **24** and optical detector **26** in FIG. 4A may be convenient for manufacturing purposes, where side-emitting LEDs and side-detecting photodetectors can couple directly to the light-guiding region **19** for generating light **111** and detecting light **110**. This may relax size constraints for an earbud **30** because the dimensions of the light-guiding region **19** may be independent of the optical emitter **24** and optical detector **26**.

FIG. 4B illustrates the light-guiding earbud **30** of FIG. 4A modified such that the earbud cover **18** and cladding material **21** are elongated to reach deeper within the ear canal C of a subject, and closer to the tympanic membrane, for example. In the illustrated embodiment of FIG. 4B, there are no apertures in the housing **16** or cover **18**. Acoustic energy **44** from/to the speaker/microphone passes through the material of the cover **18** and housing **16**. The illustrated elongated configuration serves as both an optical light-guiding region and an acoustic wave-guiding region.

FIG. 4C illustrates the light-guiding earbud **30** of FIG. 4A modified such that the earbud cover **18** and cladding material **21** are elongated to reach deeper within the ear canal C of a subject, and closer to the tympanic membrane, for example. In the illustrated embodiment of FIG. 4C, apertures **34a**, **34b** in the housing **16** and cover **18** are provided. As such, the optical light-guiding region **19** and the acoustic wave-guiding region **54** are isolated from each other. The light-guiding region **19** may be a light transmissive material, such as a dielectric material, and the acoustic wave-guiding region **54** may be air or another material, and the separation between these regions may be defined by at least part of the cladding material **21**. Embodiments of the present invention may include multiple openings **34a**, **34b** in the housing **16** and cover **18**. The separation between the light-guiding region **19** and the acoustic wave-guiding region **54** may be defined by other structures composed of a variety of possible materials. Specific examples of these materials include plastic molding, metals, polymeric structures, composite structures, or the like.

FIG. 4D illustrates the light-guiding earbud **30** of FIG. 4A modified such that the earbud cover **18** and cladding material **21** are elongated to reach deeper within the ear canal C of a subject, and closer to the tympanic membrane, for example. In the illustrated embodiment of FIG. 4D, the area within the housing **16** may be air, silicone, plastic, or any material capable of passing sound. As such, at opening **34b**, an interface exists between the material of the light-guiding region **19** and the material within the housing **16**. In some embodiments, the light-guiding region **19** and the region within the housing **16** may both be air. In other embodiments, the light-

guiding region **19** and the region within the housing **16** may be formed from the same or different materials. In some embodiments, the region within the housing **16** may be formed from an optical wave guiding material identical or similar to the material in the light-guiding region **19**.

In the embodiments of FIGS. 4B-4D, the optical energy **110** coming from the ear may include optical wavelengths, such as IR wavelengths, emitting from the tympanic membrane due to black body radiation. If the optical detector **26** is configured to measure this black body radiation, then the earbud can be used to measure tympanic temperature, blood analyte levels, neurological, electrical activity, or metabolic activity of the earbud wearer.

Referring to FIG. 5, a light-guiding earbud **30** is configured for optical coupling that is parallel to the light guide (i.e., cover **18**) as in the embodiment of FIG. 3. However, the embodiment of FIG. 5 does not include a separate earbud housing. Instead, the light guide **18** serves the function of the earbud housing. In addition, the light guide **18** includes multiple windows **18w** formed in the cladding material **21** on the outer surface **18a** of the cover and through which light **111** emitted by the light emitter **24** passes and multiple windows **18w** through which scattered light **110** passes into the light guide **18** to be directed to the light detector **26**. These openings **18w** may extend circumferentially around the light guide **18** or may partially extend circumferentially around portions of the light guide **18**. In some embodiments of this invention, the earbud housing and light guide **18** may be separated, as shown in other figures.

In addition, the illustrated light guide **18** of FIG. 5 is surrounded by a layer **29** of light transmissive material. One or more lenses **29L** are formed in this layer **29** and are in optical communication with respective windows **18w** in the light guide **18**. In the illustrated embodiment, a lens **29L** is in optical communication with a respective window **18w** through which emitted light **111** passes, and a respective window **18w** through which scattered light **110** passes. Lenses **29L** are configured to focus inspection light **111** onto a particular region of the ear. Lenses **29L** are configured to help collect scattered light **110** and direct the scattered light **110** into the light guiding region **19**. In some embodiments, these lenses **29L** may be a molded part of the light guide **18**. The illustrated location of lenses **29L** in FIG. 5 is non-limiting, and the lenses **29L** may be located wherever optical coupling between the earbud and ear is desired. Though convex lens embodiments are shown in FIG. 5, this is not meant to limit embodiments of the present invention. Depending on the desired optical coupling and configuration of the earbud against the ear, a variety of lens types and shapes may be useful, such as convex, positive or negative meniscus, plano-convex, planoconcave, biconvex, biconcave, converging, diverging, and the like.

Referring now to FIG. 6, a light guiding earbud **30**, according to some embodiments of the present invention, includes a base **50**, an earbud housing **16** extending outwardly from the base **50** that is configured to be positioned within an ear E of a subject, and a cover **18** of light transmissive material surrounding the earbud housing **16** that forms a light-guiding region **19**. The earbud housing **16** is in acoustical communication with a speaker **22** and includes at least one aperture **34a** through which sound from the speaker **22** can pass. The earbud housing **16** encloses the speaker **22**, an optical emitter **24** and an optical detector **26** as illustrated. An additional light detector **26** is located on the base **50** but is not surrounded by the earbud housing **16**.

The earbud housing **16** is formed of a cladding material. The cladding material may be reflective material in some

embodiments. In other embodiments, the cladding material may be optically transparent or mostly transparent with a lower index of refraction than the light transmissive material of the cover 18. In some embodiments, the earbud housing 16 may be replaced by air, such that the cladding region is air. Air may have a smaller index of refraction than that of the cover 18, supporting light transmission along the cover 18. In other embodiments, a cladding region exists between the earbud housing 16 and the light-guiding region 19. In another embodiment, a cladding region exists covering the outside of light-guiding region 19, with the exception of regions surrounding the lens regions 18L.

A plurality of windows 16w are formed in the earbud housing 16 at selected locations to permit light emitted by the light emitter 24 to pass therethrough. In some embodiments, the earbud housing 16 may have translucent or transparent material that serves the function of one or more windows 16w. The cover 18 includes a plurality of lenses 18L that are in optical communication with respective windows 16w in the earbud housing 16. These lenses 18L are configured to focus light 111 passing through a respective window 16w towards a particular region of the ear of a subject, and to help collect scattered light 110 and direct the scattered light 110 into the earbud housing 16 towards the light detector 26.

The earbud 30 of FIG. 6, via the locations of windows 16w, produces isotropic optical coupling, such that the light generated by the optical emitter 24 is roughly identical in all directions with respect to the earbud housing 16. The inspection light 111 generated by the optical emitter 24 passes isotropically into the light guiding region 19 through the windows 16w.

A benefit of light guiding earbud 30 of FIG. 6 is that manufacturing may not require alignment of the light-guiding region 19 with respect to the optical emitter 24 and detector 26. This may be in part because the optical energy density generated/detected by the optical emitter/detector may be the same, or relatively uniform, within the earbud housing 16 regardless of alignment of the light guide 18 with respect to the earbud housing 16 or regardless of alignment between the optical emitters/detectors and the earbud housing 16. This effect may be similar to that observed in "integrating spheres" commonly used for quantifying the lumen output of an optical source. Namely, because the light from the optical emitter 24 may be substantially isotropic and not focused, there is less restriction on the alignment of the earbud housing and earbud cover with respect to the optical emitter 24 or optical detector 26.

Referring now to FIGS. 7A-7B, a light guiding earbud 30, according to some embodiments of the present invention, includes a base 50, and an earbud housing 16 extending outwardly from the base 50 that is configured to be positioned within an ear E of a subject. The earbud housing 16 is formed from translucent material such that light can pass therethrough and forms a light-guiding region 19. The earbud housing 16 is in acoustical communication with a speaker 22 and includes at least one aperture 34a through which sound from the speaker 22 can pass. A pair of optical detectors 26 are secured to the base 50 but are not surrounded by the earbud housing 16, as illustrated.

The earbud housing 16 includes a flexible optical emitter 24 integrally formed within the housing 16, as illustrated. The optical emitter 24 is flexible such that it may be positioned around the earbud in an earbud form-factor. The flexible optical emitter 24 is configured to be conformable to an earbud shape and configuration. The flexible optical emitter 24 may be in, near, or part of the earbud housing 16, cladding

material 21, or housing 16. In some embodiments, the flexible optical emitter 24 may be part of a flexible optical circuit inserted into an earbud 30.

The optical detectors 26 positioned outside the earbud housing 16 of the earbud 30 of FIGS. 7A-7B collect scattered light from an ear originating from inspection light 111 generated by the flexible optical emitter 24. The flexible optical emitter 24 may be mounted to the earbud base 50 through one or more electrical connectors 24a. In some embodiments, these may be soldered, wired, or detachable connectors. In some embodiments, the flexible optical emitter 24 may include a flexible optical detector. In some embodiments, the flexible optical emitter 24 may be part of a flexible optical circuit comprising the form-factor of 24 shown in FIGS. 7A-7B, where the flexible optical circuit may include one or more optical emitters and detectors as well as amplifiers, microprocessors, wireless circuitry, and signal conditioning electronics. In some embodiments, the flexible optical circuit may include a complete chipset for physiological and environmental detection and for wired/wireless transfer of data to a remote location. For example, these flexible devices may include an organic LED (OLED) and an organic optical detector circuit. This embodiment may be useful for generating a diffuse light beam towards the ear region and for detecting a diffuse optical scatter response from the ear region. In some embodiments, the emitter and detector on the flexible optical emitter 24 may be a traditional light-emitting diode (LED) and photodetector (PD) integrated onto a flexible printed circuit board. In other embodiments, transparent solid state optical emitters, detectors, or switches may be used. For example, an electrically controlled liquid crystal matrix may be embedded within an earbud, covering the flexible optical emitter 24. This may allow localized control of light flow to selected areas from/to the earbud going towards/away-from the ear. Additionally, this may allow localized control of light wavelength to selected areas.

Referring now to FIGS. 8A-8B, a light guiding earbud 30, according to some embodiments of the present invention, includes a base 50, an earbud housing 16 extending outwardly from the base 50 that is configured to be positioned within an ear of a subject, and a cover 18 that surrounds the earbud housing 16. The earbud housing 16 is in acoustical communication with a speaker 22 and includes at least one aperture 34a through which sound from the speaker 22 can pass. The cover 18 includes at least one aperture 34b through which sound from the speaker 22 can pass. The cover 18 includes a cladding material 21 on the outer surface 18a thereof, except at end portion 18f, as illustrated. In the illustrated embodiment, there is no cladding material on the cover inner surface 18b. The housing 16 is in contact with the cover inner surface 18b and serves as a cladding layer to define the light guiding region 19. The cover 18 with the illustrated cladding material 18c serves as a light guide that delivers light from the optical emitters 24 into an ear canal of a subject through cover end portion 18f. The cover 18 also collects light through end portion 18f and delivers the collected light to the optical detectors 26. Various configurations and arrangements of optical emitters and detectors may be utilized in accordance with embodiments of the present invention.

In the illustrated embodiment of FIGS. 8A-8B, to reduce the risk of the inspection light 111 interrogating and saturating the optical detectors 26, a bottom portion 16a of the earbud housing 16 includes a light blocking region that blocks light from passing therethrough. This light blocking region 16a may be a black-painted region, an optically opaque region, or a material or structure that blocks light transmission. The illustrated configuration of the earbud housing 16

and bottom portion **16a** may help confine inspection light **111** generated by the optical emitters **24** within the light-guiding layer (i.e., **19**), guiding this light towards the ear region through the end portion **18f** of the earbud **30**.

In some embodiments, as illustrated in FIG. **8C**, the earbud housing **16** may be at least partially reflective to scatter light within the cavity defined by the earbud housing **16**. In such case, the optical energy **111** may exit the earbud **30** through apertures **34a**, **34b** in the housing **16** and cover **18**. An advantage of this configuration is that light **111** can be focused on a particular region of the ear where a particular physiological activity may be located. Also, this configuration may reduce unwanted optical signals from regions that may not be relevant to the physiological activity of interest. Although FIG. **8C** shows the apertures **34a**, **34b** positioned toward the tympanic membrane, the apertures **34a**, **34b** may be located at one or more other locations about the earbud **30**. For example, an aperture may be formed in the housing **16** and cover **18** at the location where the earbud **30** contacts the antitragus of an ear to allow optical energy **111** to interrogate the antitragus region of the ear.

In some embodiments, as illustrated in FIG. **8D**, the earbud housing **16** may contain a material that reflects one or more wavelengths of light and transmits one or more wavelengths of light. For example, the earbud housing **16** may be comprised of a polymer, plastic, glass, composite material, or resin that reflects visible wavelengths and transmits IR wavelengths. Exemplary materials include color absorbing materials, such as organic dyes, found in photographic film. Alternatively, the earbud housing **16** may include an optical filter region, such as a Bragg filter or other optical filter layer deposited on one or more sides of the housing region. If an optical detector **26'** is configured to measure visible wavelengths only, then the optical energy detected by optical detector **26'** may consist primarily of optical energy scattered from the earbud housing **16**, and the optical energy detected by the optical detectors **26** may consist of optical energy scattered from the ear region. This configuration may be useful because the signal from the optical detector **26'** may represent motion noise which may be removed from the signal derived from the optical detectors **26**, which may contain physiological information and motion noise.

Referring now to FIGS. **9A-9B**, a light guiding earbud **30**, according to some embodiments of the present invention, includes a base **50**, an earbud housing **16** extending outwardly from the base **50** that is configured to be positioned within an ear of a subject, and a cover **18** surrounding the earbud housing **16**. The earbud housing **16** is in acoustical communication with a speaker **22** and includes at least one aperture **34a** through which sound from the speaker **22** can pass. The cover **18** includes at least one aperture **34b** through which sound from the speaker **22** can pass. A pair of optical emitters **24** are secured to the base **50** and are surrounded by the earbud housing **16**, as illustrated. An optical detector **26** is secured to the base **50** and is not surrounded by the earbud housing **16**, as illustrated. The cover **18** serves as a light guide that delivers light from the optical emitters **24** into an ear canal of a subject.

The light-guiding region **19** of the cover **18** is designed to diffuse light and/or to generate luminescence. In this embodiment, the light-guiding region **19** includes at least one optical scatter or luminescence region. The optical scatter or luminescence region may be located anywhere within the earbud in the optical path of the optical emitters **24**, but preferably within or about the cladding layer itself. When inspection light **111** generated by the optical emitters **24** is scattered or by an optical scatter region, this light may form a more diffuse optical beam **111a** that is more uniform across the earbud **30**

than the inspection light **111** generated by the optical emitters **24**. This diffused beam, having an intensity distribution being less sensitive to motion of the ear, may be useful in alleviating motion artifacts in the scattered light coming from the ear, such that the scattered light coming from the ear, measured by the optical detector **26**, is more indicative of blood flow changes within blood vessels and less indicative of mouth movements and body motion. The optical scatter region within the light-guiding region **19** may be at least partially comprised of impurities or morphological differences within the light-guiding region. An example of such impurities may include point defects, volume defects, native defects, metallics, polymers, microspheres, phosphors, luminescent particles, air pockets, particles, particulate matter, and the like. An example of morphological differences may include density variations, roughness, air pockets, stoichiometry variations, and the like. As a specific example, the light-guiding region **19** may comprise a transparent material, such as glass, a polymer, or silicone, and a luminescent impurity, such as a phosphor or luminescent polymer or molecule, may be integrated within the light-guiding region. This configuration may generate luminescence within the light-guiding region **19** in response to optical excitation from the optical emitters **24**. In other embodiments, nanoscale fluctuations or impurities may be used to diffuse or manipulate light through the earbud. Examples of nanoscale fluctuations or impurities may include quantum dots, rods, wires, doughnuts, or the like.

FIG. **9C** illustrates an exemplary homogeneous distribution of luminescent particles **44**, such as phosphors, embedded within the earbud cover **18**, according to some embodiments of the present invention. FIGS. **9D-9E** illustrate an exemplary distribution of luminescent particles **44**, such as phosphors, where the particles are distributed near one or more surfaces of the earbud cover **18**, according to some embodiments of the present invention.

In another embodiment, an optical scatter or luminescent region may be at least partially located in a separate region from the light-guiding region **19**, such as a coating, that may be in physical contact with the light-guiding region **19**.

In another embodiment, the optical scatter region or luminescent region may include multiple layers of light-guiding material having at least one dissimilar optical property, such as a dissimilar index of refraction, transparency, reflectivity, or the like. In another embodiment, the optical scatter region may include one or more patterned regions having at least one dissimilar optical property.

In another embodiment, the optical scatter or luminescent region may be distributed at select locations throughout the earbud.

FIG. **10** illustrates relevant anatomy of a human ear **E**. Blood vessels are located across the ear, but it has been discovered that photoplethysmography (PPG) signals are the strongest near the antitragus, tragus, lobule, and portions of the acoustic meatus, and the ear canal. The antitragus is a particularly attractive location for photoplethysmography because a strong PPG signal can be derived with minimal motion artifacts associated with running and mouth motion.

Referring now to FIGS. **11A-11B**, a light guiding earbud **30**, according to some embodiments of the present invention, includes a base **50**, an earbud housing **16** extending outwardly from the base **50** that is configured to be positioned within an ear of a subject, and a cover **18** surrounding the earbud housing **16**. The earbud housing **16** is in acoustical communication with a speaker **22** and includes at least one aperture **34a** through which sound from the speaker **22** can pass. The cover **18** includes at least one aperture **34b** through which sound from the speaker **22** can pass. The cover **18** serves as a light

guide for directing light into an ear of a subject and defines a light-guiding region 19. The illustrated earbud 30 is configured to focus light towards the antitragus of the ear of a human. In the illustrated embodiment, there is no cladding material on the outer surface 18a or inner surface 18b of the cover 18. Air serves as a cladding layer at the outer surface 18a and the housing 16 serves as a cladding layer at the inner surface 18b. Air may serve as a sufficient cladding layer due to the index of refraction difference between air and the light guiding layer. Namely, the index of refraction of the light-guiding layer 19 may be more than that of air.

A sensor module 70 is located near the earbud periphery, as illustrated. This sensor module 70 is shown in more detail in FIGS. 12A-12B, and is described below. Three benefits of locating the sensor module 70 near the periphery of the light-guiding earbud 30 are: 1) PPG signals near the antitragus are less corrupted by motion artifacts than are PPG signals in other blood-vessel-rich regions of the ear; 2) the sensor module 70 may be designed somewhat independently of the earbud 30, liberating earbud comfort maximization from PPG signal maximization; and 3) because design constraints may be liberated, sensors need not be located in the acoustic cavity (i.e., within the earbud housing 16), allowing sound to pass through the acoustic orifices 34a, 34b with minimal interference. In this embodiment, it may be beneficial to incorporate lenses within the cover 18, similar to the lenses 18L of FIG. 6. It may be beneficial to extend the light-guiding region 19 of the cover 18 near the location where the earbud 30 rests near the antitragus. This light-guide extension 19a serves as an additional light-coupling region and may improve optical coupling from the light-guiding region 19 to an ear region and/or improve optical coupling from an ear region to the light-guiding region 19, including the antitragus and portions of the acoustic meatus. This is because this extended light-guiding region 19a may provide skin contact between the light guiding layer 19 and the skin, providing better optomechanical stability and optical coupling. In this embodiment, light may couple into the extended light-guiding region 19a, from an optical emitter 24, and into the ear region. Similarly, light may couple from the ear region, into the extended light-guiding region 19a, and to the optical detector 26. This extended light-guiding region 19a may appear as a bulb or lens near the bottom of the earbud cover 18.

FIGS. 12A-12B illustrate respective opposite sides of a sensor module 70 that may be located near the periphery of an earbud 30, for example as illustrated in FIGS. 11A-11B, according to some embodiments of the present invention. Sensor module 70 may include a number of electronic components capable of converting various forms of energy into an electrical signal and digitizing the signal. For example, the sensor module 70 may include light-emitting diodes, optical sensors, accelerometers, capacitive sensors, inertial sensors, mechanical sensors, electromagnetic sensors, thermal sensors, nuclear radiation sensors, biological sensors, and the like. In some embodiments, the optical emitters of this invention may be a combination of side-emitting, edge-emitting, or surface-emitting light-emitting diodes (LEDs) or laser diodes (LDs).

In the illustrated embodiment of FIGS. 12A-12B, the sensor module 70 includes two sets of optical emitters 24a, 24b. The first set of optical emitters 24a may be side-emitters (or edge-emitters) that are located at the top of the module 70 and direct light towards the earbud tip (e.g., cover end portion 18f; FIG. 8A) and towards the acoustic meatus and/or ear canal of the ear. The second set of optical emitters 24b may be located near the middle of the module 70 and may direct light in a beam that is largely perpendicular to that of the side-emitters

24a. In this particular embodiment, a single optical emitter 24b is shown mounted on a circuit board 70c such that this optical emitter 24b directs light towards the antitragus, which is located largely perpendicular to the acoustic meatus.

The optical energy generated by these optical emitters 24a, 24b may be scattered by blood vessels in the ear. This scattered light may be at least partially captured by the optical detectors 26. This light may be digitized by an optical detector 26 itself or with other circuitry on the sensor module circuit board 70c. The light-guiding design of the aforementioned light-guiding earbuds 30 may direct light towards each of these detectors 26. For example, this may be accomplished via the light-guiding earbud 30, wherein a lens (e.g., 18L, FIG. 6) facilitates inspection light coupling from the optical emitters 24 into the ear region and facilitates scattered light coupling to the optical detectors 26 from the ear region. Additional sensor components 27a, 27b may be used to measure an orthogonal energy component, facilitate sensor analysis, and thus help generate physiological assessments. For example, sensor components 27a, 27b may be thermal sensors for measuring the temperature of the inner ear (using the thermal sensors 27a facing the ear region) with respect to the outer ear (using the thermal sensor 27b facing away from the ear region). By subtracting the two measured digitized temperatures from these two sensors 27a, 27b, an indication of heat flow from the ear can be generated. This temperature differential may be mathematically related to metabolic rate. For example, this temperature differential may be directly proportional to metabolic rate. These temperature sensors may include thermistors, thermopiles, thermocouples, solid state sensors, or the like. They may be designed to measure thermal conduction, convection, radiation, or a combination of these temperature components.

The earbud-facing side (FIG. 12B) of the sensor module 70 may include sensors that do not need to be located on the antitragus-facing side of the sensor module. For example, one or more inertial sensors 27c may be located on the earbud-facing side (FIG. 12B) of the sensor module 70. In a particular embodiment, the inertial sensor 27c may be a 3-axis accelerometer, and because this sensor does not need to optically couple with the ear region, a better use of sensor real estate may be to locate this sensor on the earbud-facing side of the sensor module 70. Additional optical emitters 24a, 24b may be located on the earbud-facing side to facilitate an optical noise reference. Namely, as the person wearing the earbud module 30 moves around, the interrogation light generated by the optical emitters 24a, 24b may be scattered off the earbud and be detected by optical detectors 27d. This scattered light intensity, phase, and/or frequency due to body motion may be proportional to the motion-related component of the scattered light intensity from the ear region. The motion-related component is the component due to the physical motion of the ear and not the component related to blood flow. Thus, the optical scatter signal collected by the detectors 27d may provide a suitable noise reference for an adaptive filter to remove motion artifacts from the scattered light from the ear region, generating an output signal that is primarily related to blood flow (which may be the desired signal). In the same token, the scattered light reaching the optical detectors 27d may be used to generate a measure of activity. The intensity, phase, and frequency of this scattered light may be related to physical activity. Sinusoidal variations of the heart rate waveform may be counted digitally, by identifying and counting crests and peaks in the waveform, to generate an effective step count. Embodiments of the present invention, however, are not limited to the illustrated location of components in the sensor

module **70**. Various types and orientations of components may be utilized without limitation.

FIG. **19** illustrates the optical interaction between the sensor module **70** of FIGS. **12A-12B** and the skin of a subject. The sensor module **70** is shown in a reflective pulse oximetry setup **80** where reflected wavelengths **110** are measured, as opposed to measuring transmitted wavelengths. The optical emitter and optical detector wavelengths for pulse oximetry and photoplethysmography may include ultraviolet, visible, and infrared wavelengths. In the illustrated embodiment, an optical source-detector assembly **71** is integrated into sensor module **70** to generate optical wavelengths **111** and monitor the resulting scattered optical energy **110**. The optical source-detector assembly **71** contains one or more optical sources emitting one or more optical wavelengths, as well as one or more optical detectors detecting one or more optical wavelengths.

The epidermis **90**, dermis **91**, and subcutaneous **92** layers of skin tissue are shown in FIG. **19** for reference. The scattered optical energy **110** may be modulated in intensity by changes in blood flow in the blood vessels, changes in physical motion of the body, respiration, heart rate, and other physiological changes. In some cases, the scattered optical energy may be luminescent energy from the skin, blood, blood analytes, drugs, or other materials in the body.

As previously described, the optical scatter signal collected by the detectors **27d** may provide a suitable noise reference for an adaptive filter to remove motion artifacts from the scattered light from the ear region, generating an output signal that is primarily related to blood flow (which may be the desired signal). This is because light detected by these detectors would come from light that has not been scattered by a physiological region but rather light that has been scattered from a region of the associated earpiece that may move along with the ear. Thus, the scattered light reaching the optical detectors **27d** may be used to generate a measure of activity.

FIG. **13** illustrates the basic configuration of an adaptive noise cancellation scheme **200** for extracting a physiological signal from noise. The two types of sensor inputs are represented by the terms “Channel A” and “Channel B”. Channel A refers to inputs from sensors that collect physiological information plus noise information, and Channel B refers to inputs from sensors that collect primarily (or substantially) noise information. Channel B information is passed through an electronic filter **203** whose properties are updated adaptively and dynamically. The filter **203** properties are updated to minimize the difference between Channel A and the post-processed Channel B, denoted as $B^{\wedge}$. In this way, noise is removed from Channel A and Channel C contains predominantly physiological information from which parameters such as blood flow, heart rate, blood analyte levels, breathing rate or volume, blood oxygen levels, and the like may be calculated. It is important to note that the Channel A information can still be useful despite the presence of noise, and the noise information may still be utilized for the computation of relevant parameters. For instance, the residual noise information in Channel A may be extracted by a parameter estimator **201** and the output in Channel D may be one or more activity assessments or the like. Similarly, the raw noise channel, Channel B, may be post-processed by a parameter estimator **205** to extract activity assessments for Channel E. Activity assessments may include exertion, activity level, distance traveled, speed, step count, pace, limb motion, poise, performance of an activity, mastication rate, intensity, or volume, and the like. The noise cancellation scheme **200** may be integrated into the firmware of a microprocessor or the like.

Although the embodiment of FIG. **13** for cancelling motion noise has been presented for an earbud configuration, this does not limit the invention to earbuds. An element of the adaptive noise cancellation scheme **200** for cancelling motion noise with an optical noise source may be that the optical detectors (such as **27d**) are configured such that they do not receive scattered light from a physiological region while the detectors are simultaneously receiving scattered light from a region that is moving in synchronization with the physiological region. Even the slightest physiological signal existing in the optical noise reference of Channel B may prevent the adaptive filter from working properly such that the physiological signal may inadvertently be removed altogether by the filter **203**. Furthermore, although the noise source Channel B is described as an optical noise source, other forms of energy may be used in this invention. Namely, any inertial sensor input may constitute the input for Channel B. More specifically, a sensor for measuring changes in capacitance along the earbud with respect to the ear may provide an inertial noise reference without also measuring physiological information. Similarly, an accelerometer may provide an inertial noise reference without also measuring physiological information. An inductive sensor may also provide an inertial noise reference without also measuring physiological information. For each noise source, a defining element may be that the noise source may be configured to measure physical motion only (or mostly) and not physiological information (such as blood flow, blood oxygen, blood pressure, and the like). The utility of an optical noise source is that because the optical signal Channel A and the optical noise Channel B have the same linearity response, the adaptive filter scheme **200** may be more effective than the case where the signal and noise channels operate via different forms of sensed energy. For example, the response linearity characteristics of an accelerometer sensor in response to inertial changes may not be the same as the response linearity characteristics of an optical sensor.

The adaptive noise cancellation scheme **200** for cancelling motion noise with an optical source (specifically an infrared LED) has been demonstrated in the laboratory, with a human wearing a light-guiding earbud while resting, jogging, and running over a treadmill, and various data summaries **300a-300d** are presented in FIGS. **14A-14D**. The data was recorded by a chip and memory card embedded in an earbud **30**, having electrical connectivity with the sensor module **70** within the earbud **30**. The raw signal in low motion **300a** and raw signal in high motion **300c** may be equated with the signal of Channel A of FIG. **13**. Similarly, the “blocked channel” in low motion **300b** and “blocked channel” in high motion **300d** may be equated with Channel B of FIG. **13**. In this experiment, the “block channel” consisted of an optical noise source, wherein the optical noise source included an optical emitter-detector module such as **70** of FIGS. **12A-12B**. However, instead of being exposed to the ear, the optical emitter-detector module was covered with a layer of clear silicone that was then covered by black tape to prevent light from the emitter (such as **24a** and **24b**) from reaching the ear. Thus, scatter from the black tape was scattered back to the emitter-detector module through the silicone and sensed as motion noise by the detectors (such as **26** and **27d**). In a sense, for this configuration, the optical channel to the human ear is “blocked”, hence the term “blocked channel”. The purpose of the clear silicone below the black tape was to: 1) provide an unobstructed, transparent optical scatter path for the IR light and 2) provide motion sensitivity similar to that of human skin, as silicone has a vibration response that may be similar to that of human skin.

FIGS. 14A-14D show that the raw signal in low motion 300a indicates blood flow pulses which can be translated as heart rate. This is because each blood flow pulse represents one heart beat. However, the raw signal in high motion 300c indicates measured mostly physical activity. This is evident by the fact that the high motion signal 300c matches the corresponding blocked channel signal 300d, and the blocked channel in high motion 300d was found to have a substantially identical beat profile with the measured steps/second of the runner.

FIG. 15 is a graph of processed physiological signal data from a headset having one or more light-guiding earbuds 30, according to some embodiments of the present invention. Specifically, FIG. 15 shows the analysis results 400 of the data summaries 300a-300d presented in FIGS. 14A-14D of blood flow (y-axis) versus time (x-axis) following two data processing sequences to extract heart rate. One sequence incorporated the adaptive filtering process 200 of FIG. 13 as well as a beat finder processing step. The second sequence incorporated the beat finder processing step without the adaptive filtering process 200 of FIG. 13. The beat finder process counts each heart beat by monitoring the peaks and valleys of each pulse, such as the peaks and valleys shown in the graph 300a of FIG. 14A. As shown in FIG. 15, the beat finder was effective at measuring heart rate during resting and jogging. However, the beat finder alone was not sufficient for monitoring heart rate during running. This is because at high motion, the signal 300d (FIG. 14D) associated with footsteps is strong enough to overwhelm the smaller signal associated with heart rate, and so the motion-related contribution dominated the overall signal 300d. Thus, the beat finder cannot distinguish heart beats from footsteps. By employing the adaptive filtering process 200 (FIG. 13) before the beat finder process, the footstep motion artifacts during running were effectively removed from the sensor signal (Channel A of FIG. 13) such that the output signal (Channel C of FIG. 13) contained blood flow information with minimal motion artifacts. Thus, this output signal contained blood flow pulse signals that could then be "counted" by the beat finder to generate an accurate heart rate assessment.

In the specific analysis results 400 of FIG. 15, a beat finder was employed, following the adaptive filter process 200 of FIG. 13, to count heart beats. A more general method 500 for extracting physiological information from sensor signals in the midst of noise is illustrated in FIG. 16. The first block (block 510) represents the pre-adaptive signal conditioning stage. This process may utilize a combination of filters to remove frequency bands outside the range of interest. For example, a combination of band-pass, low-pass, and/or high-pass filters (such as digital filters) may be used. The second block (block 520) represents an adaptive filtering process such as the process 200 described in FIG. 13. This process may utilize the pre-conditioned signals from block 510 as inputs into an adaptive filter that reduces motion or environmental artifacts and noise in the primary data channel. The third block (block 530) represents the parameter extraction stage. This process may utilize a combination of signal conditioning filters in addition to peak finding (such as beat finding) algorithms to calculate properties of interest (e.g. heart rate, blood flow, heart rate variability, respiration rate, blood gas/analyte level, and the like). The method 500 of FIG. 16 may be encoded in the firmware of a microprocessor (or similar electronics) to facilitate real-time processing of physiological information.

FIG. 17 is a block diagram that illustrates sensor signals being processed into a digital data string including activity data and physiological data using the method 500 of FIG. 16,

according to some embodiments of the present invention. Optical detectors 26 and optical emitters 24 may include digitizing circuitry such that they may be connected serially to a digital bus 600. Data from the detectors 26 may be processed by a processor/multiplexer 602 to generate multiple data outputs 604 in a serial format at the output 606 of the processor 602. In some embodiments, the processing methods may involve one or more of the methods described in FIGS. 13, 14A-14D, 15 and 16. The multiple data outputs 604 may be generated by the processor/multiplexer 602 by time division multiplexing or the like. The processor 602 may execute one or more serial processing methods, wherein the outputs of a plurality of processing steps may provide information that is fed into the multiplexed data outputs 604.

The multiplexed data outputs 604 may be a serial data string of activity and physiological information 700 (FIG. 18) parsed out specifically such that an application-specific interface (API) can utilize the data as required for a particular application. The applications may use this data to generate high-level assessments, such as overall fitness or overall health. Furthermore, the individual data elements of the data string can be used to facilitate better assessments of other individual data elements of the data string. As a specific example, the Blood Flow data string may contain information on the first and second derivatives of each blood pulse. This information may be processed from a PPG signal by running the adaptively filtered heart rate signal through a slope-finder algorithm (such as a differentiator circuit). In another example, the filtered PPG signal may be run through an integration circuit to estimate blood volume over each blood pulse. This information may then be used to assess blood pressure and blood oxygen levels more accurately than a direct measurement of blood pressure or blood oxygen levels.

In some embodiments of the invention, new methods of generating physiological assessment algorithms are enabled. These new methods may be achieved by measuring each data output of the data output string 604 in real time while an earbud user is also wearing one or more benchmark sensors. Principal component analysis, multiple linear regression, or other statistical or machine learning techniques can then be used to generate statistical relationships between the data outputs 604 and high level assessments measured simultaneously by the benchmark sensors. These benchmark sensors may measure aerobic fitness level, VO₂max, blood pressure, blood analyte levels, and the like. The relationships between the earbud sensor and benchmark sensor readings may be translated as algorithms embedded in the earbud, wherein each algorithm generates at least one assessment for the earbud user. In some cases, Bland-Altman plots of the earbud-derived assessment value versus the benchmark value may be used to judge the effectiveness of the algorithm, and this information may then feedback into improving the said earbud-derived assessment algorithm. Examples of these assessments may include aerobic fitness level, VO₂max, blood pressure, blood analyte levels (such as blood glucose, oxygen, carbon monoxide, etc.), and the like.

In some cases, it may be important to remove the effects of ambient optical noise from the physiological signal of a light-guiding earbud 30. In such cases, one or more optical detectors 26 may be configured to measure outdoor or ambient lighting, and this information may be fed back into the processor 602 (FIG. 17) to extract external optical noise from the physiological signal. For example, some optical detectors may be configured to measure light from the ear, whereas others may be configured to measure light from the ambient environment, such as sunlight, room light, headlights, or the like. This may be achieved by directing the optical detectors

towards and away from the ear, respectively. In a specific example, the ambient light reaching the optical detectors **26** may generate an undesirable sinusoidal response on an optical detector that is configured to measure light from the ear. This undesirable sinusoidal noise response may be generated as an earbud user moves their head from side to side while running. Thus, Channel A of the adaptive filter **200** (FIG. **13**) may include physiological information plus undesired ambient optical noise information. To remove this noise from the final output Channel C, the output of the optical detector configured to measure ambient optical noise may be an input (Channel B of FIG. **13**) into the adaptive filter **200**. In this way, ambient noise from Channel A may be removed to generate a mostly physiological signal in Channel C.

The optical detectors **26** and emitters **24** may be of multiple wavelengths, with the goal of providing specialized physiological information for each wavelength. Referring to FIG. **19**, for example, violet or UV light may be used to measure motion-related aspects of the ear, as violet and UV light may not penetrate greatly through the skin of the ear. Green, red, and IR wavelengths may have deeper penetration and provide information on the blood vessels and blood analyte levels. Blue wavelengths may be particularly useful for gauging changes in the size of the blood vessels.

Embodiments of the present invention may be more generally applied to non-optical or mix-optical configurations. For example, one or more of the detectors **26** and emitters **24** may be mechanical, acoustical, electrical, gravimetric, or nuclear detectors and emitters, all providing physiological information to the processor **602** (FIG. **17**). For example, an accelerometer or capacitor may be used as a detector **26** for the noise reference (Channel B) input of an adaptive filter running in real-time on the processor **602**.

Referring to FIG. **20**, a chipset **800** for use in light-guiding earbuds **30**, according to some embodiments of the present invention, may include optical emitters, optical detectors, mechanical, acoustical, electrical, gravimetric, nuclear detectors, additional sensors, signal processing, power regulation, digital control, and input/output lines. The chipset **800** may include firmware for signal extraction and for generating physiological assessments from information derived from the sensors and noise sources. One benefit of the chipset configuration is that the chipset **800** may be fully or partially integrated and hence compact and scalable to a wide range of products. To be integrated with a light-guiding earbud **30**, the chipset **800** may be aligned such that the sensor region has an exposed window to a subject's ear. For example, the chipset **800** may be attached to the earbud base **50** or an earbud sensor module **70** and aligned line-of-sight through an acoustic orifice of an earbud and/or through a transparent end portion of an earbud **30** (e.g., through end portion **18** of the earbud **30** of FIGS. **8A-8B** or **18w** of FIGS. **4** & **5**).

A specific embodiment of a chipset **800** for a stereo headset, according to some embodiments of the present invention, is illustrated in FIG. **21**. This stereo chipset **800** may be integrated into an electronic module that may be attached to a printed circuit board. In another configuration, this stereo chipset **800** may be integrated into 3 modules, wherein the right and left earbud sensors comprise two separate modules, embedded in right and left earbuds respectively, and wherein the remaining circuit elements comprise the main module.

According to other embodiments of the present invention, monitoring devices with light-guiding regions may be configured to be attached to earlobes, fingers, toes, other digits, etc. For example, FIGS. **22A-22B** illustrate a monitoring device **70** that is configured to fit over a finger F, for example, as a finger ring, according to some embodiments of the

present invention. The illustrated monitoring device **70** includes a generally circular band capable of encircling a finger F of a subject, with a cylindrical outer body portion **72** and a generally cylindrical inner body portion **74** secured together in concentric relationship. The outer body portion may be formed from virtually any type of material and may have an ornamental configuration. In some embodiments, the outer body portion **72** may include a flex circuit containing various electronic components, such as a microprocessor, D/A converter, power source, power regulator, and the like. However, in some embodiments, the outer body portion **72** may not be required and the circular band of the monitoring device **70** includes only the inner body portion **74** secured to the base **50** (described below).

A base **50** is secured to the inner and outer body portions **74**, **72** of the illustrated embodiment and may be similar to the base **50** described above with respect to FIGS. **3**, **4A-4D**, **5**, **6**, **7A-7B**, **8A-8D**, **9A-9B**, and **11A-11B**. The base **50** provides support for one or more sensors. In the illustrated embodiment, the base **50** supports an optical emitter **24**, an optical detector **26**, and an optical noise detector **26'**.

The inner body portion **74** includes light transmissive material similar to that of the cover **18** described above with respect to FIGS. **3**, **4A-4D**, **5**, **6**, **7A-7B**, **8A-8D**, **9A-9B**, and **11A-11B**. In some embodiments, the inner body portion **74** is formed from a soft, resilient material, such as silicone, which deforms when a finger of a subject is inserted therethrough. However, various types of light transmissive materials may be utilized, without limitation.

A layer of cladding material **21** is applied to (or near) the outer surface **74a** of the inner body portion **74** and a layer of cladding material **21** is applied to (or near) the inner surface **74b** of the inner body portion **74**, as illustrated, to define a light-guiding region **19**. As such, the inner body portion **74** serves as a light guide that delivers light from the optical emitter **24** to the finger F of a subject at one or more predetermined locations and that collects light from the finger F and delivers the collected light to the optical detectors **26**, **26'**. In some embodiments, the cladding material **21** may be embedded within the inner body portion **74** adjacent to the outer surface **74a** and inner surface **74b**. In some embodiments, the outer body portion **72** may serve as a cladding layer adjacent to the inner body portion outer surface **74a**.

In the illustrated embodiment, windows **74w** are formed in the cladding material **21** and serve as light-guiding interfaces to the finger F. There may be any number of these windows, as may be required for sufficient optical coupling, and the windows **74w** may include lenses such as those described above (e.g., lens **18L** illustrated in FIG. **6**), to focus light emitted by the optical emitter **24** onto one or more portions of a finger F and/or to focus collected light on the light detectors **26**, **26'**. Similarly, the windows **74w** may include optical filters to selectively pass one or more optical wavelengths and reflect and/or absorb other optical wavelengths.

In the illustrated embodiment, the light-guiding region **19** includes light blocking members **80** that isolate light emitter **24** and light detector **26** from each other. In some embodiments, only a single light blocking member **80** may be utilized. For example, a single light blocking member **80** may be positioned between the light emitter **24** and light detector **26**. By adding an additional blocking member **80**, as illustrated, the only light reaching the optical detector **26** may be light passing through at least one portion of the finger.

In some embodiments, multiple light emitters **24** may be utilized. For example, light emitters of different wavelengths may be utilized. In some embodiments, multiple light detectors may be utilized that are configured to measure light at

different wavelengths (e.g., light detectors **26** and **26'** may be configured to measure light at different wavelengths). In this way, either optical detector may be configured to measure light mostly due to motion (such as finger motion) or to measure light mostly due to physiological processes and motion. For example, if the windows **74w** incorporate IR-pass filters, visible light will not pass through the windows **74w** and the light will be scattered to the photodetectors **26** and **26'**. Or, if the two illustrated blocking regions **80** are in place, and if photodetector **26'** is configured to measure only visible light and photodetector **26** is configured to measure only IR light, then only the photodetector **26'** will detect scattered visible light. As this visible scattered light cannot reach the finger, the scatter intensity measured by optical detector **26'** may be indicative of motion and not physiological activity.

Referring now to FIG. **23**, a monitoring device **70'**, according to some embodiments of the present invention, may be configured to be attached to a body of a subject as a bandage or "band-aid". The illustrated monitoring device **70'** includes an outer layer or body portion **72** and an inner layer or body portion **74** secured together, as illustrated. The outer body portion may be formed from virtually any type of material and may have an ornamental configuration. In some embodiments, the outer body portion **72** may include a flex circuit containing various electronic components, such as a micro-processor, D/A converter, power source, power regulator, and the like. However, in some embodiments, the outer body portion **72** may not be required and the monitoring device **70'** includes only the inner body portion **74** secured to the base **50** (described below).

A base **50** is secured to the inner and outer body portions **74**, **72** and may be similar to the base **50** described above with respect to FIGS. **3**, **4A-4D**, **5**, **6**, **7A-7B**, **8A-8D**, **9A-9B**, and **11A-11B**. The base **50** provides support for one or more sensors. In the illustrated embodiment, the base **50** supports an optical emitter **24**, an optical detector **26**, and an optical noise detector **26'**.

The inner body portion **74** is formed of light transmissive material similar to that of the cover **18** described above with respect to FIGS. **3**, **4A-4D**, **5**, **6**, **7A-7B**, **8A-8D**, **9A-9B**, and **11A-11B**. In some embodiments, the inner body portion **74** is formed from a soft, resilient material, such as silicone, which deforms when the device is attached to the body of a subject. However, various types of light transmissive materials may be utilized, without limitation.

A layer of cladding material **21** is applied to (or near) the outer surface **74a** of the inner body portion **74** and a layer of cladding material **21** is applied to (or near) the inner surface **74b** of the inner body portion **74**, as illustrated, to define a light-guiding region **19**. As such, the inner body portion **74** serves as a light guide that delivers light from the optical emitter **24** to the body of a subject at one or more predetermined locations and that collects light from the body and delivers the collected light to the optical detectors **26**, **26'**. In some embodiments, the cladding material **21** may be embedded within the inner body portion **74** adjacent to the outer surface **74a** and inner surface **74b**. In some embodiments, the outer body portion **72** may serve as a cladding layer adjacent to the inner body portion outer surface **74a**.

In the illustrated embodiment, windows **74w** are formed in the cladding material **21** and serve as light-guiding interfaces to the body of a subject. There may be any number of these windows, as may be required for sufficient optical coupling, and the windows **74w** may include lenses such as those described above (e.g., lens **18L** illustrated in FIG. **6**), to focus light emitted by the optical emitter **24** onto one or more portions of the body of a subject and/or to focus collected

light on the light detectors **26**, **26'**. Similarly, the windows **74w** may include optical filters to selectively pass one or more optical wavelengths and reflect and/or absorb other optical wavelengths.

In the illustrated embodiment, the light-guiding region **19** includes a light blocking member **80** that isolates light emitter **24** and light detector **26** from each other. In some embodiments, multiple light emitters **24** may be utilized. For example, light emitters of different wavelengths may be utilized. In some embodiments, multiple light detectors may be utilized that are configured to measure light at different wavelengths (e.g., light detectors **26** and **26'** may be configured to measure light at different wavelengths).

The illustrated monitoring device **70'** may be removably attached to the body of a subject via adhesive on one or more portions of the device **70'**. In some embodiments, adhesive may be on the inner body portion **74**. In embodiments where the outer body portion is utilized, the adhesive may be on the outer body portion **74**. In some embodiments, the illustrated device **70'** may be removably attached to the body of a subject via tape or other known devices.

The foregoing is illustrative of the present invention and is not to be construed as limiting thereof. Although a few exemplary embodiments of this invention have been described, those skilled in the art will readily appreciate that many modifications are possible in the exemplary embodiments without materially departing from the teachings and advantages of this invention. Accordingly, all such modifications are intended to be included within the scope of this invention as defined in the claims. The invention is defined by the following claims, with equivalents of the claims to be included therein.

That which is claimed is:

1. A method of generating data output containing physiological and motion-related information, the method comprising:

sensing physical activity and physiological information from a subject via a single monitoring device attached to the subject, wherein the monitoring device comprises at least one motion sensor for sensing the physical activity and at least one photoplethysmography (PPG) sensor for sensing the physiological information; and

processing signals from the at least one motion sensor and signals from the at least one PPG sensor, via at least one processor, into a serial data output of physiological information and motion-related information,

wherein the serial data output is configured such that a plurality of subject physiological parameters comprising subject heart rate and at least one of subject heart rate variability, subject blood gas level, subject blood flow, subject blood pulse volume, subject blood analyte levels, subject breathing rate, subject breathing volume, subject blood oxygen levels, subject blood pressure, subject VO_2max , the 1st derivative of at least one subject blood pulse, and the 2nd derivative of at least one subject blood pulse can be extracted from the physiological information, and such that a plurality of subject physical activity parameters can be extracted from the motion-related information.

2. The method of claim 1, wherein the serial data output is parsed out such that an application-specific interface (API) can utilize the physiological information and motion-related information for an application.

3. The method of claim 1, wherein the application is configured to generate statistical relationships between subject

31

physiological parameters and subject physical activity parameters in the physiological information and motion-related information.

4. The method of claim 3, wherein the application is configured to generate statistical relationships between subject physiological parameters and subject physical activity parameters via at least one of the following: principal component analysis, multiple linear regression, machine learning, and Bland-Altman plots.

5. The method of claim 1, further comprising, prior to processing signals from the at least one motion sensor and signals from the at least one PPG sensor into the serial data output, removing frequency bands from the PPG signals that are outside of a range of interest using at least one band-pass filter to produce pre-conditioned PPG signals, and filtering the pre-conditioned PPG signals to reduce motion artifacts and noise artifacts from the pre-conditioned PPG signals to produce cleaner physiological information.

6. The method of claim 5, wherein the subject motion noise comprises subject footsteps noise.

7. The method of claim 5, wherein filtering the pre-conditioned PPG signals comprises at least one of the following: FIR (Finite Impulse Response) filtering, IIR (Infinite Impulse Response) filtering, adaptive filtering, phase filtering, and frequency filtering.

8. The method of claim 1, wherein the at least one motion sensor comprises at least one of the following: an optical sensor, an inertial sensor, an electrically conductive sensor, a capacitive sensor, an inductive sensor, an accelerometer, and a blocked channel sensor.

9. The method of claim 1, wherein the at least one PPG sensor comprises at least one optical emitter, at least one optical detector, and at least one light guide.

10. The method of claim 1, wherein the at least one motion sensor and the at least one PPG sensor are integrated into a wearable device.

11. The method of claim 10, wherein the wearable device is configured to be attached to the subject at one or more of the following body locations: an ear, a limb, the nose, and a digit.

12. The method of claim 1, wherein the at least one motion sensor and the at least one PPG sensor are integrated into a chipset.

13. The method of claim 1 wherein the physiological information and/or motion-related information comprises information on data integrity.

14. A method of monitoring a subject via a monitoring device attached to a body of the subject, the device comprising at least one optical emitter and at least one optical detector, the method comprising:

directing light having a plurality of optical wavelengths at the body of the subject via the at least one optical emitter;

measuring body motion of the subject by detecting, via the at least one optical detector, light scattered by the body that is within a first wavelength range, wherein the first wavelength range comprises violet light or ultraviolet (UV) light; and

measuring blood vessel changes or blood analyte levels of the subject by detecting, via the at least one optical detector, light scattered by the body that is within a second wavelength range different from the first range, wherein the second wavelength range comprises green light, red light, infrared (IR) light or blue light.

15. The method of claim 14, wherein the monitoring device is configured to be attached to the subject at one or more of the following body locations: an ear, a limb, the nose, and a digit.

32

16. A method of monitoring a subject via a monitoring device attached to a body of the subject, the device comprising at least one motion sensor and at least one photoplethysmography (PPG) sensor, the method comprising:

directing light having a plurality of optical wavelengths at the body of the subject via the at least one PPG sensor; measuring body motion of the subject by detecting, via the at least one motion sensor, light scattered by the body that is within a first wavelength range, wherein the first wavelength range comprises violet light or ultraviolet (UV) light; and

measuring blood vessel changes or blood analyte levels of the subject by detecting, via the at least one PPG sensor, light scattered by the body that is within a second wavelength range different from the first range, wherein the second wavelength range comprises green light, red light, infrared (IR) light or blue light.

17. The method of claim 16, wherein the monitoring device is configured to be attached to the subject at one or more of the following body locations: an ear, a limb, the nose, and a digit.

18. A method of generating data output containing physiological and motion-related information, the method comprising:

sensing physical activity and physiological information from a subject via a single monitoring device attached to the subject, wherein the monitoring device comprises at least one motion sensor for sensing the physical activity and at least one photoplethysmography (PPG) sensor for sensing the physiological information; and

processing signals from the at least one motion sensor and signals from the at least one PPG sensor via at least one processor, into a serial data output of physiological information and motion-related information,

wherein the serial data output is configured such that subject heart rate can be extracted from the physiological information, and such that a plurality of subject physical activity parameters can be extracted from the motion-related information, and such that data integrity can be extracted from the physiological information and/or the motion-related information.

19. A method of generating data output containing physiological information, the method comprising:

sensing physical activity and physiological information from a subject via a single monitoring device attached to the subject, wherein the monitoring device comprises a motion sensor and a photoplethysmography (PPG) sensor;

removing, via a first filter stage, one or more frequency bands from a PPG signal generated by the PPG sensor to produce a pre-conditioned PPG signal;

processing, via a second filter stage, the pre-conditioned PPG signal and a signal generated by the motion sensor to remove motion noise from the pre-conditioned PPG signal and produce a cleaner PPG signal; and

processing, via a third filter stage, the cleaner PPG signal to extract at least one physiological parameter.

20. The method of claim 19, wherein the first and third filter stages each comprise a plurality of digital filters.

21. The method of claim 19, wherein the second filter stage comprises an adaptive filter.

22. The method of claim 19, wherein the at least one physiological parameter comprises heart rate.

23. The method of claim 19, wherein the at least one physiological parameter comprises heart rate, and wherein a heart rate signal is extracted from PPG signal output from the third filter stage via a beat finding algorithm.

33

24. The method of claim 19, wherein the PPG sensor comprises at least one light guide configured to couple light to or from the body of a subject.

25. The method of claim 19, wherein the motion sensor comprises an accelerometer or an optical scatter detector.

26. The method of claim 19, wherein the motion sensor signal is further processed to generate a plurality of physical activity parameters.

27. The method of claim 19, wherein processing the cleaner PPG signal via the third filter stage comprises extracting a plurality of physiological parameters and producing a serial data output of the plurality of physiological parameters.

28. A method of generating data output containing physiological information, the method comprising:

sensing physical activity and physiological information from a subject via a single monitoring device attached to the subject, wherein the monitoring device comprises a motion sensor and a photoplethysmography (PPG) sensor;

processing, via a first filter stage, a PPG signal produced by the PPG sensor and a signal generated by the motion sensor to remove motion noise from the PPG signal and produce a cleaner PPG signal;

34

removing, via a second filter stage, one or more frequency bands from the cleaner PPG signal to produce a processed PPG signal; and

processing, via a third filter stage, the processed PPG signal to extract at least one physiological parameter.

29. The method of claim 28, wherein the second and third filter stages each comprise a plurality of digital filters.

30. The method of claim 28, wherein the first filter stage comprises an adaptive filter.

31. The method of claim 28, wherein the at least one physiological parameter comprises heart rate.

32. The method of claim 28, wherein the at least one physiological parameter comprises heart rate, and wherein a heart rate signal is extracted from PPG signal output from the third filter stage via a beat finding algorithm.

33. The method of claim 28, wherein the PPG sensor comprises at least one light guide configured to couple light to or from the body of a subject.

34. The method of claim 28, wherein the motion sensor comprises an accelerometer or an optical scatter detector.

35. The method of claim 28, wherein the motion sensor signal is further processed to generate a plurality of physical activity parameters.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,314,167 B2
APPLICATION NO. : 14/550039
DATED : April 19, 2016
INVENTOR(S) : LeBoeuf et al.


Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims:

Column 32, Claim 18, Line 31: Please correct "sensor via"
to read -- sensor, via --

Signed and Sealed this
Eighth Day of November, 2016

A handwritten signature in black ink, reading "Michelle K. Lee". The signature is written in a cursive style with a long horizontal flourish at the end.

Michelle K. Lee
Director of the United States Patent and Trademark Office

专利名称(译)	用于生成包含生理和运动相关信息的数据输出的方法		
公开(公告)号	US9314167	公开(公告)日	2016-04-19
申请号	US14/550039	申请日	2014-11-21
[标]申请(专利权)人(译)	瓦倫賽爾公司		
申请(专利权)人(译)	VALENCELL INC.		
当前申请(专利权)人(译)	VALENCELL INC.		
[标]发明人	LEBOEUF STEVEN FRANCIS TUCKER JESSE BERKLEY AUMER MICHAEL EDWARD		
发明人	LEBOEUF, STEVEN FRANCIS TUCKER, JESSE BERKLEY AUMER, MICHAEL EDWARD		
IPC分类号	A61B5/00 A61B5/145 A61B5/01 A61B5/021 A61B5/08 F21V8/00 A61B5/16 A61B5/0476 A61B5/1455 A61B5/11 H04R1/10 A61B5/024 G06F19/00 A61B5/0205 A61B5/026 A61B5/091 A61B5/0295		
CPC分类号	A61B5/0205 A61B5/0024 A61B5/0059 A61B5/0082 A61B5/0084 A61B5/01 A61B5/021 A61B5/02055 A61B5/0261 A61B5/02427 A61B5/02433 A61B5/0476 A61B5/0816 A61B5/11 A61B5/1107 A61B5/1118 A61B5/1455 A61B5/14532 A61B5/14551 A61B5/165 A61B5/418 A61B5/486 A61B5/4812 A61B5/4845 A61B5/4848 A61B5/4866 A61B5/4875 A61B5/4884 A61B5/6803 A61B5/6815 A61B5/6817 A61B5/6819 A61B5/6826 A61B5/6838 A61B5/721 A61B5/7214 A61B5/7282 A61B5/742 A61B5/7475 G02B6/0001 G06F19/3418 H04R1/105 H04R1/1091 A61B5/00 A61B5/0013 A61B5/0022 A61B5/024 A61B5/026 A61B5/0295 A61B5/02405 A61B5/02416 A61B5/091 A61B5/411 A61B5/415 A61B2560/0242 A61B2562/0233 A61B5/6816 A61B5/7207 A61B2560/0425 A61B2560/0443 G16H20/30 G16H40/67 Y02A90/26 A61B5/002 A61B5/7221 A61B5/725 A61B5/7278 A61B2562/0219 G16H30/40 G16H40/63 G16H50/20 H04R1/028		
优先权	12/691388 2014-04-15 US 61/208567 2009-02-25 US 61/208574 2009-02-25 US 61/212444 2009-04-13 US 61/274191 2009-08-14 US		
其他公开文献	US20150105633A1		
外部链接	Espacenet USPTO		

摘要(译)

一种生成包含生理和运动相关信息的数据串的方法包括：经由附接到对象的至少一个运动传感器感测对象的身体活动;通过附接到对象的至少一个光电容积脉搏波描记术（PPG）传感器以及将来自所述至少一个运动传感器的信号和来自所述至少一个PPG传感器的信号处理成生理信息和运动相关信息的串行数据串。可以从生理信息中提取多个对象生理参数，并且可以从运动相关信息中提取多个对象身体活动参数。解析串行数据串，使得应用特定接口可以利用生理信息和运动相关信息用于在生理信息和运动相关信息中生成对象生理参数和对象身体活动参数之间的统计关系的应用。

