

(19)



(11)

**EP 3 338 643 B1**

(12)

**EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention  
of the grant of the patent:  
**30.10.2019 Bulletin 2019/44**

(51) Int Cl.:  
**A61B 8/14** (2006.01) **A61B 8/08** (2006.01)  
**A61B 8/00** (2006.01)

(21) Application number: **16838850.2**

(86) International application number:  
**PCT/JP2016/063873**

(22) Date of filing: **10.05.2016**

(87) International publication number:  
**WO 2017/033503 (02.03.2017 Gazette 2017/09)**

**(54) ULTRASONIC DIAGNOSTIC DEVICE AND METHOD FOR CONTROLLING ULTRASONIC  
DIAGNOSTIC DEVICE**

ULTRASCHALLDIAGNOSEVORRICHTUNG UND VERFAHREN ZUR STEUERUNG DER  
ULTRASCHALLDIAGNOSEVORRICHTUNG

DISPOSITIF DE DIAGNOSTIC PAR ULTRASONS ET PROCÉDÉ DE COMMANDE DUDIT  
DISPOSITIF DE DIAGNOSTIC PAR ULTRASONS

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB  
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO  
PL PT RO RS SE SI SK SM TR**

(30) Priority: **21.08.2015 JP 2015164045**

(43) Date of publication of application:  
**27.06.2018 Bulletin 2018/26**

(73) Proprietor: **FUJIFILM Corporation**  
**Tokyo 106-8620 (JP)**

(72) Inventor: **IMAI Yoshiro**  
**Ashigara-kami-gun**  
**Kanagawa 258-8538 (JP)**

(74) Representative: **Klunker IP**  
**Patentanwälte PartG mbB**  
**Destouchesstraße 68**  
**80796 München (DE)**

(56) References cited:  
**JP-A- H04 224 738 JP-A- 2010 259 662**  
**JP-A- 2012 205 610 JP-A- 2014 061 291**

**EP 3 338 643 B1**

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

## Description

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

**[0001]** The present invention relates to an ultrasound diagnostic apparatus and a method for controlling the ultrasound diagnostic apparatus, and more particularly, to an ultrasound diagnostic apparatus that determines an imaging part of a subject on the basis of an ultrasound image.

#### 2. Description of the Related Art

**[0002]** In the related art, an ultrasound diagnostic apparatus using an ultrasound image has been put to practical use in the medical field. In general, in this type of ultrasound diagnostic apparatus, an ultrasound probe provided with an array transducer scans a subject with an ultrasound beam and receives ultrasound echoes from the subject and the received signal is electrically processed to generate an ultrasound image.

**[0003]** In a case in which the ultrasound diagnostic apparatus is used to diagnose a plurality of imaging parts of the subject, appropriate imaging conditions vary depending on imaging parts in order to obtain ultrasound images suitable for diagnosis for each imaging part. Therefore, for example, JP1992-224738A (JP-H04-224738A) discloses an ultrasound diagnostic apparatus which automatically determines an imaging part from a generated ultrasound image, using a pattern matching process, and sets a scanning parameter most suitable for the imaging part on the basis of the determination result.

**[0004]** JPH04224738A discloses a diagnosis part discriminator and scan parameter setting apparatus. An image data of a frame memory of an ultrasonic diagnostic apparatus is compressed to be written into a compression data memory and an image pattern is extracted from a compression data to be collated with a pattern data stored previously in a pattern memory. A diagnosis part corresponding to a similar pattern data is obtained and outputted. A scan parameter stored previously in a system memory corresponding to the pattern data is taken out to be fed back to a beam former of the ultrasonic diagnostic device.

### SUMMARY OF THE INVENTION

**[0005]** However, the shape of the same imaging part changes depending on the person. In addition, for example, brightness or a dynamic range varies depending on the difference between transmission characteristics and reflection characteristics for ultrasound beams. Therefore, in a case in which an imaging part is automatically determined by the apparatus disclosed in JP1992-224738A (JP-H04-224738A), there is a concern

that an error in the determination result will occur. In a case in which erroneous determination is performed, a scanning parameter that is not suitable for the imaging part is set, which makes it difficult to obtain a good ultrasound image.

**[0006]** In a case in which erroneous part determination is performed during scanning with the ultrasound beam, the scanning parameter is instantaneously changed and the quality of an ultrasound image is changed. As a result, there is a concern that diagnosis will be hindered.

**[0007]** The invention has been made in order to solve the problems of the related art and an object of the invention is to provide an ultrasound diagnostic apparatus and a method for controlling the ultrasound diagnostic apparatus that can improve the reliability of part determination.

**[0008]** According to one aspect, there is provided an ultrasound diagnostic apparatus according to claim 1 of the appended claims.

**[0009]** Preferably, the ultrasound diagnostic apparatus further comprises: an imaging condition memory that stores a plurality of imaging conditions set for each of a plurality of imaging parts in advance; and an apparatus control unit that selects an imaging condition corresponding to the integrated determination result from the plurality of imaging conditions stored in the imaging condition memory and controls the imaging unit such that the ultrasound image is generated under the selected imaging condition.

**[0010]** The imaging unit may include a transmitting/receiving unit that transmits and receives the ultrasound beam according to ultrasound beam scanning conditions and an image generation unit that generates the ultrasound image from the received signal according to ultrasound image generation conditions. The imaging conditions may include the ultrasound beam scanning conditions and the ultrasound image generation conditions.

**[0011]** In this case, the determination result integration unit may give a weight to a determination result corresponding to the latest frame among the determination results corresponding to the plurality of frames stored in the determination result storage unit and integrate the determination results under the majority rule.

**[0012]** The part determination unit may output the determination result and a similarity score for each of the plurality of frames. The determination result integration unit may give weights to the determination results corresponding to the plurality of frames stored in the determination result storage unit according to the similarity scores output from the part determination unit and integrate the determination results under the majority rule.

**[0013]** The ultrasound diagnostic apparatus may further comprise an examined part storage unit that stores the integrated determination result. In a case in which a plurality of imaging parts of the subject are sequentially examined, the apparatus control unit may exclude the imaging part indicated by the integrated determination result stored in the examined part storage unit from the

subsequent imaging parts to be determined by the part determination unit.

**[0014]** In this case, the ultrasound diagnostic apparatus may further comprise a probe state determination unit that determines whether the ultrasound probe is in an aerial emission state or a contact state with the subject. In a case in which the probe state determination unit determines that the ultrasound probe has been changed from the contact state with the subject to the aerial emission state, the apparatus control unit may store the integrated determination result in the examined part storage unit.

**[0015]** According to another aspect, there is provided a method for controlling an ultrasound diagnostic apparatus including an ultrasound probe, according to claim 8 of the appended claims.

**[0016]** According to the invention, the determination results corresponding to a plurality of frames for an imaging part of the subject are stored. The stored determination results corresponding to the plurality of frames are integrated and the integrated determination result is output. Therefore, it is possible to improve the reliability of part determination.

## BRIEF DESCRIPTION OF THE DRAWINGS

### [0017]

Fig. 1 is a block diagram illustrating the configuration of an ultrasound diagnostic apparatus according to Embodiment 1 of the invention.

Fig. 2 is a block diagram illustrating the internal configuration of a receiving unit.

Fig. 3 is a block diagram illustrating the internal configuration of a B-mode processing unit.

Fig. 4 is a flowchart illustrating the operation of Embodiment 1.

Fig. 5 is a block diagram illustrating the configuration of an ultrasound diagnostic apparatus according to Embodiment 2.

Fig. 6 is a diagram illustrating a B-mode image in Embodiment 2.

Fig. 7 is a diagram illustrating a B-mode image in which a plurality of regions of interest are set.

Fig. 8 a diagram illustrating a B-mode image in which a plurality of observation points are set.

Fig. 9 is a flowchart illustrating the operation of Embodiment 2.

## DESCRIPTION OF THE PREFERRED EMBODIMENTS

**[0018]** Hereinafter, embodiments of the invention will be described with reference to the accompanying drawings.

### Embodiment 1

**[0019]** Fig. 1 illustrates the configuration of an ultrasound diagnostic apparatus according to Embodiment 1 of the invention. The ultrasound diagnostic apparatus includes an ultrasound probe 1 provided with an array transducer 1A. An image generation unit 3 is connected to the ultrasound probe 1 through a transmitting/receiving unit 2 and a display unit 5 is connected to the image generation unit 3 through a display control unit 4.

**[0020]** The transmitting/receiving unit 2 includes a transmitting unit 6 and a receiving unit 7 that are connected to the array transducer 1A of the ultrasound probe 1 and a transmission/reception control unit 8 that is connected to the transmitting unit 6 and the receiving unit 7. The image generation unit 3 includes a B-mode processing unit 9 that is connected to the receiving unit 7 of the transmitting/receiving unit 2 and a digital scan converter (DSC) 10 that is connected to the B-mode processing unit 9. The display control unit 4 is connected to the DSC 10.

**[0021]** A part determination unit 11 is connected to the DSC 10 of the image generation unit 3. A determination result storage unit 12 is connected to the part determination unit 11. In addition, a determination result integration unit 13 is connected to the determination result storage unit 12.

**[0022]** An apparatus control unit 14 is connected to the transmission/reception control unit 8 of the transmitting/receiving unit 2, the B-mode processing unit 9 and the DSC 10 of the image generation unit 3, the display control unit 4, the part determination unit 11, and the determination result integration unit 13. An imaging condition memory 15, an operation unit 16, and a storage unit 17 are connected to the apparatus control unit 14.

**[0023]** The array transducer 1A of the ultrasound probe 1 includes a plurality of ultrasound transducers that are one-dimensionally or two-dimensionally arranged. Each of the ultrasound transducers transmits ultrasonic waves in response to a driving signal supplied from the transmitting unit 6. In addition, each of the ultrasound transducers receives ultrasound echoes from a subject and outputs a received signal. Each ultrasound transducer is, for example, a transducer in which electrodes are formed on both sides of a piezoelectric body made of piezoelectric ceramic typified by lead zirconate titanate (PZT), a polymer piezoelectric element typified by polyvinylidene difluoride (PVDF), or piezoelectric single crystal typified by lead magnesium niobate-lead titanate (PMN-PT).

**[0024]** In a case in which a pulsed voltage or a continuous-wave voltage is applied to the electrodes of the transducer, the piezoelectric body is expanded and contracted, and pulsed or continuous ultrasonic waves are generated from each transducer. The ultrasonic waves are combined to form an ultrasound beam. In addition, each transducer receives propagated ultrasonic waves, is expanded and contracted, and generates an electric

signal. The electric signal is output as a received ultrasound signal.

**[0025]** The transmitting/receiving unit 2 transmits and receives an ultrasound beam according to the set ultrasound beam scanning conditions and the image generation unit 3 generates a B-mode image signal according to the set ultrasound image generation conditions. Therefore, the transmitting/receiving unit 2 and the image generation unit 3 form an imaging unit. In addition, imaging conditions for the imaging unit include the ultrasound beam scanning conditions for the transmitting/receiving unit 2 and the ultrasound image generation conditions for the image generation unit 3.

**[0026]** The transmitting unit 6 of the transmitting/receiving unit 2 includes, for example, a plurality of pulse generators, adjusts the amount of delay of each driving signal such that the ultrasonic waves transmitted from a plurality of ultrasound transducers in the array transducer 1A form an ultrasound beam on the basis of a transmission delay pattern selected according to a control signal from the transmission/reception control unit 8, and supplies the driving signals to the plurality of ultrasound transducers.

**[0027]** As illustrated in Fig. 2, the receiving unit 7 has a configuration in which an amplification unit 18 and an analog/digital (A/D) conversion unit 19 are sequentially connected in series. The receiving unit 7 amplifies the received signals transmitted from each ultrasound transducer of the array transducer 1A with the amplification unit 18 and performs A/D conversion for the received signals with the A/D conversion unit 19 to generate digital received data.

**[0028]** The transmission/reception control unit 8 controls the transmitting unit 6 and the receiving unit 7 on the basis of various control signals transmitted from the apparatus control unit 14 such that the transmission of an ultrasound pulse to a subject and the reception of an ultrasound echo from the subject are repeated at a pulse repetition frequency (PRF) interval.

**[0029]** The B-mode processing unit 9 of the image generation unit 3 has a configuration in which a beam former 20 and a signal processing unit 21 are sequentially connected in series, as illustrated in Fig. 3. The beam former 20 applies a delay to each received data item output from the receiving unit 7 of the transmitting/receiving unit 2 according to a sound speed or a sound speed distribution set on the basis of a reception delay pattern selected according to a control signal from the apparatus control unit 14 and adds the received data to perform a reception focusing process. A sound ray signal in which the focus of an ultrasound echo subjected to phasing addition is narrowed is generated by the reception focusing process.

**[0030]** The signal processing unit 21 corrects the attenuation of the sound ray signal generated by the beam former 20 depending on a distance according to the depth of the reflection position of ultrasonic waves and then performs an envelope detection process. In addition, the signal processing unit 21 performs various types of nec-

essary image processing including a gradation process to generate a B-mode image signal which is tomographic image information about the issues of the subject.

**[0031]** The DSC 10 of the image generation unit 3 converts the B-mode image signal generated by the signal processing unit 21 into an image signal based on a general television signal scanning system (raster conversion).

**[0032]** The display control unit 4 displays a B-mode image on the display unit 5 on the basis of the B-mode image signal generated by the image generation unit 3.

**[0033]** The display unit 5 includes a display device, such as a liquid crystal display (LCD), and displays the B-mode image under the control of the display control unit 4.

**[0034]** The part determination unit 11 determines an imaging part of the subject on the basis of the B-mode image signal generated by the image generation unit 3.

**[0035]** The determination result storage unit 12 stores the determination results corresponding to a plurality of frames obtained by the part determination unit 11.

**[0036]** The determination result integration unit 13 integrates the determination results corresponding to the plurality of frames stored in the determination result storage unit 12 and outputs an integrated determination result.

**[0037]** The apparatus control unit 14 controls the transmission/reception control unit 8, the B-mode processing unit 9, the DSC 10, the display control unit 4, the part determination unit 11, and the determination result integration unit 13 on the basis of commands input by the operator through the operation unit 16.

**[0038]** The imaging condition memory 15 stores a plurality of imaging conditions which are set for a plurality of imaging parts of the subject in advance. The imaging conditions are used to acquire the B-mode images suitable for diagnosing each corresponding imaging part.

**[0039]** The operation unit 16 is used by the operator to perform an input operation and may include, for example, a keyboard, a mouse, a trackball, and a touch panel.

**[0040]** The storage unit 17 stores, for example, an operation program. For example, a recording medium, such as a hard disk, a flexible disk, an MO, an MT, a RAM, a CD-ROM, a DVD-ROM, an SD card, a CF card, or a USB memory, or a server may be used as the storage unit 17.

**[0041]** Here, a part determination method in the part determination unit 11 will be described.

**[0042]** Examples of the imaging part of the subject can include the heart, the right abdomen, the left abdomen, and the urinary bladder. Of course, the part determination unit 11 may be configured so as to determine various other imaging parts.

**[0043]** The part determination unit 11 stores the typical pattern data of a plurality of imaging parts in advance and calculates the similarity between the B-mode image signal of the imaging part output from the DSC 10 of the image generation unit 3 and each of a plurality of pattern

data items stored in advance. A known matching technique can be used to calculate the similarity. In addition to the matching technique, for example, the following method may be used to calculate the similarity: a machine learning method disclosed in Csurka et al.: Visual Categorization with Bags of Keypoints, Proc. of ECCV Workshop on Statistical Learning in Computer Vision, pp. 59-74 (2004); or a general image recognition method using deep learning disclosed in Krizhevsk et al.: ImageNet Classification with Deep Convolutional Neural Networks, Advances in Neural Information Processing Systems 25, pp. 1106-1114 (2012).

**[0044]** The part determination unit 11 calculates similarity scores between the B-mode image signal of the imaging part and a plurality of imaging parts, using these methods, and uses an imaging part with the highest similarity score as the determination result. For example, in a case in which the similarity score for the heart is 5, the similarity score for the right abdomen is 10, the similarity score for the left abdomen is 6, and the similarity score for the urinary bladder is 3, the determination result indicating that the captured imaging part is the right abdomen with the highest similarity score is obtained.

**[0045]** In this case, the following configuration may be used: before the part is determined, the operator inputs subject information (for example, a body type and sex) through the operation unit 16 and pattern data used to determine the part is changed according to the subject information. That is, a plurality of pattern data items corresponding to, for example, a difference in body size and sex are stored for each imaging part and the part is determined on the basis of pattern data corresponding to the input subject information. With this configuration, it is possible to prevent an error in determination caused by the difference in the body size and sex of the subject and to improve the accuracy of determining the part.

**[0046]** The determination of the part by the part determination unit 11 may be performed for each display frame of the B-mode image or may be performed for every several frames for one imaging part.

**[0047]** As such, the determination results corresponding to a plurality of frames obtained by the part determination unit 11 are stored for one imaging part in the determination result storage unit 12.

**[0048]** The determination result integration unit 13 integrates the determination results corresponding to a plurality of frames stored in the determination result storage unit 12 and outputs an integrated determination result. However, a majority rule may be used as the method for integrating the determination results. For example, in a case in which Nf determination results corresponding to Nf frames are stored for one imaging part in the determination result storage unit 12, an imaging part indicated by the largest number of determination results among the Nf determination results, that is, an imaging part with the highest score is output as the integrated determination result. As such, since the determination results corresponding to a plurality of frames are integrated under

the majority rule to obtain the integrated determination result, it is possible to effectively prevent an error in determination.

**[0049]** In addition, in this embodiment, the determination results corresponding to a plurality of frames stored in the determination result storage unit 12 are simply integrated under the majority rule. However, a weight may be given to the latest frame and the determination results may be integrated under the majority rule. That is, weights may be given to the determination results corresponding to a predetermined number of frames stored in the determination result storage unit 12 in reverse chronological order among the determination results corresponding to a plurality of frames stored in the determination result storage unit 12 and the determination results may be integrated under the majority rule. The weight given to the determination result corresponding to a new frame stored in the determination result storage unit 12 may be greater than the weight given to the determination result corresponding to an old frame among the determination results corresponding to a plurality of frames stored in the determination result storage unit 12.

**[0050]** For example, Nf is 90 and, among 90 determination results, a weight of 3 is given to the determination results corresponding to 30 new frames, a weight of 2 is given to the determination results corresponding to 30 intermediate frames, and a weight of 1 is given to the determination results corresponding to 30 old frames. Then, an imaging part with the highest score is output as the integrated determination result. In a case in which the imaging part is changed, the position of the ultrasound probe 1 is not determined immediately after the change and the quality of the B-mode image is unstable. For this reason, a weight is given to the latest frame. Therefore, it is possible to reduce a time lag in a case in which the imaging part is changed and to more rapidly perform accurate part determination.

**[0051]** In addition, weighting may be performed according to the similarity score during part determination and the determination results may be integrated under the majority rule. For example, in a case in which Nf is 90, the number of determination results indicating an imaging part A among 90 determination results is 45, the number of determination results indicating an imaging part B is 45, the average value of the similarity scores in 45 determination results indicating the imaging part A is 10, the average value of the similarity scores in 45 determination results indicating the imaging part B is 5, and the number of determination results is multiplied by the average value of the similarity scores to calculate a score, the score of the imaging part A is  $10 \times 45 = 450$  and the score of the imaging part B is  $5 \times 45 = 225$ . Therefore, the imaging part A with a higher score is output as the integrated determination result. As such, since weighting is performed according to the similarity score, it is possible to further increase the accuracy of determining the part.

**[0052]** Next, the operation of Embodiment 1 will be de-

scribed with reference to the flowchart illustrated in Fig. 4.

**[0053]** First, in Step S1, the transmitting/receiving unit 2 performs the transmission and reception of an ultrasound beam and scanning, using the plurality of ultrasound transducers in the array transducer 1A of the ultrasound probe 1. A received signal from each ultrasound transducer that has received ultrasound echoes from the subject is output to the receiving unit 7. The receiving unit 7 performs amplification and A/D conversion for the received signal to generate received data.

**[0054]** In Step S2, the received data is input to the image generation unit 3. The B-mode processing unit 9 performs the reception focusing process for the received data and the DSC 10 converts signal conversion to generate a B-mode image signal. The B-mode image signal is output from the image generation unit 3 to the display control unit 4. The B-mode image is displayed on the display unit 5.

**[0055]** The B-mode image signal output from the DSC 10 of the image generation unit 3 is input to the part determination unit 11. After the part is determined by the part determination unit 11 in Step S3, the determination results are stored in the determination result storage unit 12 in Step S4.

**[0056]** Then, in Step S5, it is determined whether the number of frames storing the determination results for one imaging part in the determination result storage unit 12 reaches a predetermined number of frames Nf. In a case in which the number of frames does not reach the number of frames Nf, the process returns to Step S1. In this way, Steps S1 to S5 are repeated until the number of frames storing the determination results reaches Nf.

**[0057]** Here, the number of frames Nf is predetermined. However, the operator may input the number of frames Nf through the operation unit 16.

**[0058]** In addition, instead of directly setting the number of frames Nf, the time for which the determination results are stored may be set to automatically determine the number of frames Nf according to a frame rate. For example, in a case in which the determination results corresponding to three seconds are stored and the frame rate is 30 frames/second, Nf is  $30 \times 3 = 90$ . In a case in which the frame rate is 40 frames/second, Nf is  $40 \times 3 = 120$ .

**[0059]** In a case in which it is determined in Step S5 that the number of frames storing the determination results reaches Nf, the process proceeds to Step S6 and the determination result integration unit 13 integrates the determination results corresponding to Nf frames stored in the determination result storage unit 12 and outputs an integrated determination result.

**[0060]** In a case in which the integrated determination result is output from the determination result integration unit 13 in this way, the apparatus control unit 14 adjusts imaging conditions in Step S7. That is, the apparatus control unit 14 selects imaging conditions corresponding to the integrated determination result from a plurality of imaging conditions which are stored in the imaging con-

dition memory 15 in advance, on the basis of the integrated determination result output from the determination result integration unit 13, and controls the transmitting/receiving unit 2 and the image generation unit 3 such that imaging is performed for the subsequent frames under the selected imaging conditions. Specifically, the transmission/reception control unit 8 of the transmitting/receiving unit 2 is controlled such that an ultrasound beam is transmitted and received according to an ultrasound beam scanning condition included in the imaging conditions selected from the imaging condition memory 15 and the image generation unit 3 is controlled such that a B-mode image is generated from the received signal according to an ultrasound image generation condition included in the selected imaging conditions.

**[0061]** Among the imaging conditions, the ultrasound beam scanning condition can include an ultrasound beam transmission frequency, a focal position, and a display depth and the ultrasound image generation condition can include a sound speed, detection conditions, a gain, a dynamic range, a gradation curve, speckle reduction intensity, and the degree of edge enhancement. Appropriate conditions for each imaging part are in the imaging condition memory 15 in advance.

## Embodiment 2

**[0062]** Fig. 5 illustrates the configuration of an ultrasound diagnostic apparatus according to Embodiment 2. The ultrasound diagnostic apparatus differs from the ultrasound diagnostic apparatus according to Embodiment 1 illustrated in Fig. 1 in that an apparatus control unit 14A is provided instead of the apparatus control unit 14, a probe state determination unit 31 is connected to the DSC 10 of the image generation unit 3 and the apparatus control unit 14A, and an examined part storage unit 32 is connected to the apparatus control unit 14A.

**[0063]** The probe state determination unit 31 determines whether the ultrasound probe 1 is in a contact state in which the ultrasound probe 1 comes into contact with the body surface of a subject and emits ultrasonic waves into the body of the subject or an aerial emission state in which the ultrasound probe 1 is separated from the body surface of the subject and emits ultrasonic waves to the air, on the basis of the B-mode image generated by the image generation unit 3.

**[0064]** The examined part storage unit 32 stores an examined imaging part among a plurality of imaging parts.

**[0065]** The apparatus control unit 14A has a function that stores an imaging part indicated by the integrated determination result output from the determination result integration unit 13 as the examined part in the examined part storage unit 32 in a case in which the probe state determination unit 31 determines that the state of the ultrasound probe 1 has been changed and excludes the imaging part from the next part determination targets, in addition to the functions of the apparatus control unit 14

according to Embodiment 1.

**[0066]** The probe state determination unit 31 may analyze the B-mode image generated by the image generation unit 3 to determine whether the ultrasound probe 1 is in the contact state with the subject or the aerial emission state. In general, in a case in which the ultrasound probe 1 comes into contact with the body surface of the subject and emits ultrasonic waves into the body of the subject, a certain structure, that is, a tissue of the subject is visualized in a B-mode image 33 as illustrated in Fig. 6. However, in a case in which the ultrasound probe 1 is separated from the body surface of the subject and emits ultrasonic waves to the air, no structure is visualized in the B-mode image 33.

**[0067]** Therefore, it is detected whether a structure is present or absent in the B-mode image 33 on the basis of a brightness distribution of the B-mode image 33. In a case in which a structure is detected in the B-mode image 33, it can be determined that the ultrasound probe 1 is in the contact state with the subject. In a case in which no structure is detected in the B-mode image 33, it can be determined that the ultrasound probe 1 is in the aerial emission state.

**[0068]** Specifically, as illustrated in Fig. 7, the B-mode image 33 is divided into a plurality of regions 34. The variance of the brightness of each region 34 or the difference between the maximum brightness and the minimum brightness is calculated as an index value. In a case in which the number of regions 34 with an index value that is equal to or greater than a predetermined set value is equal to or greater than a predetermined threshold value, the probe state determination unit 31 determines that the ultrasound probe 1 is in the contact state with the subject. On the other hand, in a case in which the number of regions 34 with an index value that is equal to or greater than the predetermined set value is less than the predetermined threshold value, the probe state determination unit 31 determines that the ultrasound probe 1 is in the aerial emission state.

**[0069]** In addition to the analysis based on the index value of the brightness of each region 34, a plurality of observation points 35 may be set in the B-mode image 33 as illustrated in Fig. 8 and the amount of movement of each observation point 35 between frames may be detected to determine the state of the ultrasound probe 1.

**[0070]** In a case in which the number of observation points 35 of which the amount of movement between frames is equal to or less than a set value is equal to or greater than a predetermined threshold value, the probe state determination unit 31 may determine that the movement of the ultrasound probe 1 is stable and may determine whether the ultrasound probe 1 is in the contact state with the subject or the aerial emission state on the basis of the index value of the brightness of each region 34.

**[0071]** In a case in which the ultrasound probe 1 is in the aerial emission state, it is considered that almost the same B-mode image is acquired. Therefore, the B-mode

image in a case in which the ultrasound probe 1 is in the aerial emission state may be stored in advance and the probe state determination unit 31 may determine the state of the ultrasound probe 1, using a matching technique such as template matching.

**[0072]** Next, the operation of Embodiment 2 will be described with reference to the flowchart illustrated in Fig. 9. As in Embodiment 1, in Steps S1 to S7, the determination of the part by the part determination unit 11, the integration of the determination results by the determination result integration unit 13, and the adjustment of the imaging conditions by the apparatus control unit 14A are performed. Then, in Step S8, the probe state determination unit 31 determines whether the ultrasound probe 1 has been changed from the contact state with the subject to the aerial emission state.

**[0073]** Then, in a case in which it is determined that the ultrasound probe 1 has been changed from the contact state with the subject to the aerial emission state, the process proceeds to Step S9 and the apparatus control unit 14A detects that the image part to be examined has been changed to the next imaging part, recognizes the imaging part indicated by the integrated determination result output from the determination result integration unit 13 in Step S6 as an examined part, stores the imaging part in the examined part storage unit 32, and excludes the stored integrated determination result (That is, the examined part) from the subsequent part determination targets.

**[0074]** Similarity determination may not be performed for the examined part stored in the examined part storage unit 32 in the subsequent part determination process. Alternatively, similarity determination may be performed for the examined part. In a case in which the determination result integration unit 13 reads out the determination results from the determination result storage unit 12 and integrates the determination results, a weight given to the examined part may be reduced and the determination results may be integrated under the majority rule.

**[0075]** In addition, the operator may designate an imaging part to be excluded from the part determination targets through the operation unit 16.

**[0076]** As such, the ultrasound diagnostic apparatus according to Embodiment 2 recognizes the examined part and excludes the examined part from the subsequent part determination targets. Therefore, in a case in which a plurality of imaging parts are sequentially examined in a predetermined order as in a focused assessment with sonography for trauma (FAST) examination in critical care, it is possible to rapidly perform part determination for the subsequent imaging parts with high accuracy.

#### Explanation of References

**[0077]**

1: ultrasound probe

1A: array transducer  
 2: transmitting/receiving unit  
 3: image generation unit  
 4: display control unit  
 5: display unit  
 6: transmitting unit  
 7: receiving unit  
 8: transmission/reception control unit  
 9: B-mode processing unit  
 10: DSC  
 11: part determination unit  
 12: determination result storage unit  
 13: determination result integration unit  
 14, 14A: apparatus control unit  
 15: imaging condition memory  
 16: operation unit  
 17: storage unit  
 18: amplification unit  
 19: A/D conversion unit  
 20: beam former  
 21: signal processing unit  
 31: probe state determination unit  
 32: examined part storage unit  
 33: B-mode image  
 34: region  
 35: observation point

## Claims

### 1. An ultrasound diagnostic apparatus comprising:

an ultrasound probe (1);  
 an imaging unit configured to transmit and receive an ultrasound beam to and from a subject using the ultrasound probe and convert a received signal output from the ultrasound probe into an image to generate an ultrasound image of the subject, according to set imaging conditions, the ultrasound image comprising a frame;  
 a part determination unit (11) configured to determine an imaging part of the subject using the ultrasound image generated by the imaging unit, thereby obtaining determination result indicative of the imaging part that has been captured in the frame;  
 a determination result storage unit (12) configured to store determination results obtained by the part determination unit, the determination results corresponding to a plurality of frames, whereby Nf determination results corresponding to Nf frames are stored for one imaging part in the determination result storage unit; and  
 a determination result integration unit (13) configured to integrate the determination results corresponding to the plurality of frames stored in the determination result storage unit and output an integrated determination result, whereby

an imaging part indicated by the largest number of determination results among the Nf determination results is output as the integrated determination result.

### 2. The ultrasound diagnostic apparatus according to claim 1, further comprising:

an imaging condition memory (15) configured to store a plurality of imaging conditions set for each of a plurality of imaging parts in advance; and  
 an apparatus control unit (14, 14A) configured to select an imaging condition corresponding to the integrated determination result from the plurality of imaging conditions stored in the imaging condition memory and control the imaging unit such that the ultrasound image is generated under the selected imaging condition.

### 3. The ultrasound diagnostic apparatus according to claim 1 or 2,

wherein the imaging unit includes a transmitting/receiving unit (2) configured to transmit and receive the ultrasound beam according to ultrasound beam scanning conditions and an image generation unit (3) configured to generate the ultrasound image from the received signal according to ultrasound image generation conditions, and  
 the imaging conditions include the ultrasound beam scanning conditions and the ultrasound image generation conditions.

### 4. The ultrasound diagnostic apparatus according to claim 1, wherein the determination result integration unit (13) is configured to give a weight to a determination result corresponding to the latest frame among the determination results corresponding to the plurality of frames stored in the determination result storage unit.

### 5. The ultrasound diagnostic apparatus according to claim 1,

wherein the part determination unit (11) is configured to output the determination result and a similarity score for each of the plurality of frames, and  
 the determination result integration unit (13) is configured to give weights to the determination results corresponding to the plurality of frames stored in the determination result storage unit according to the similarity scores output from the part determination unit.

6. The ultrasound diagnostic apparatus according to any one of claims 1 to 5, further comprising:

an examined part storage unit (32) configured to store the integrated determination result, wherein, in a case in which a plurality of imaging parts of the subject are sequentially examined, the apparatus control unit (14, 14A) is configured to exclude the imaging part indicated by the integrated determination result stored in the examined part storage unit from the subsequent imaging parts to be determined by the part determination unit.

7. The ultrasound diagnostic apparatus according to claim 6, further comprising:

a probe state determination unit (31) configured to determine whether the ultrasound probe is in an aerial emission state or a contact state with the subject, wherein, in a case in which the probe state determination unit (31) is configured to determine that the ultrasound probe (1) has been changed from the contact state with the subject to the aerial emission state, the apparatus control unit (14, 14A) is configured to store the integrated determination result in the examined part storage unit (32).

8. A method for controlling an ultrasound diagnostic apparatus including an ultrasound probe, the method comprising:

a step (S1) of transmitting and receiving an ultrasound beam to and from a subject using the ultrasound probe and converting a received signal output from the ultrasound probe into an image to generate an ultrasound image of the subject, according to set imaging conditions, the ultrasound image comprising a frame; a step of determining (S3) an imaging part of the subject using the generated ultrasound image, thereby obtaining determination result indicative of the imaging part that has been captured in the frame; a step of storing (S4) determination results obtained by determining an imaging part, the determination results corresponding to a plurality of frames, whereby Nf determination results corresponding to Nf frames are stored for one imaging part; and a step of integrating (S6) the stored determination results corresponding to the plurality of frames and outputting an integrated determination result, whereby an imaging part indicated by the largest number of determination results among the Nf determination results is output as

the integrated determination result.

9. The method for controlling an ultrasound diagnostic apparatus according to claim 8,

wherein a plurality of imaging conditions set for each of a plurality of imaging parts are stored in advance, and an imaging condition corresponding to the integrated determination result are selected from the plurality of imaging conditions stored and the ultrasound image is generated under the selected imaging condition.

10. The method for controlling an ultrasound diagnostic apparatus according to claim 8 or 9, wherein the imaging conditions include ultrasound beam scanning conditions used to transmit and receive the ultrasound beam and ultrasound image generation conditions used to generate the ultrasound image from the received signal.

11. The method for controlling an ultrasound diagnostic apparatus according to claim 8, wherein a weight is given to a determination result corresponding to the latest frame among the determination results corresponding to the plurality of frames stored.

12. The method for controlling an ultrasound diagnostic apparatus according to claim 8,

wherein the determination result and a similarity score are output for each of the plurality of frames, and weights are given to the determination results corresponding to the plurality of frames stored according to the similarity scores output.

13. The method for controlling an ultrasound diagnostic apparatus according to any one of claims 8-12,

wherein the integrated determination result is stored, and in a case in which a plurality of imaging parts of the subject are sequentially examined, the imaging part indicated by the integrated determination result stored is excluded from the subsequent imaging parts to be determined.

## Patentansprüche

1. Ultraschall Diagnosevorrichtung, umfassend:

eine Ultraschallsonde (1);  
eine Bildeinheit, die konfiguriert ist, um einen Ultraschallstrahl zu und von einem Subjekt unter

- Verwendung der Ultraschallsonde zu senden und zu empfangen und ein von der Ultraschallsonde ausgegebenes, empfangenes Signal in ein Bild umzuwandeln, um ein Ultraschallbild des Subjekts gemäß den eingestellten Bildbedingungen zu erzeugen, wobei das Ultraschallbild einen Frame umfasst;
- eine Teilbestimmungseinheit (11), die konfiguriert ist, um einen Bildteil des Subjekts unter Verwendung des von der Bildeinheit erzeugten Ultraschallbildes zu bestimmen, wodurch ein Bestimmungsergebnis erhalten wird, das den Bildteil angibt, der im Frame erfasst wurde;
- eine Bestimmungsergebnis-Speichereinheit (12), die konfiguriert ist, um die von der Teilbestimmungseinheit erhaltenen Bestimmungsergebnisse zu speichern, wobei die Bestimmungsergebnisse einer Vielzahl von Frames entsprechen, wobei die Nf-Bestimmungsergebnisse, die Nf-Frames entsprechen, für einen Bildteil in der Bestimmungsergebnis-Speichereinheit gespeichert werden; und
- eine Bestimmungsergebnis-Integrationseinheit (13), die konfiguriert ist, um die Bestimmungsergebnisse entsprechend der Vielzahl von Frames, die in der Bestimmungsergebnis-Speichereinheit gespeichert sind, zu integrieren und ein integriertes Bestimmungsergebnis auszugeben, wobei ein Bildteil, der durch die größte Anzahl von Bestimmungsergebnissen unter den Nf-Bestimmungsergebnissen angegeben ist, als integriertes Bestimmungsergebnis ausgegeben wird.
2. Ultraschalldiagnosevorrichtung nach Anspruch 1, weiterhin umfassend:
- einen Bildbedingungsspeicher (15), der dazu konfiguriert ist, eine Vielzahl von Bildbedingungen, die für jedes der Vielzahl von Bildteilen im Voraus festgelegt wurden, zu speichern; und
- eine Vorrichtungssteuereinheit (14, 14A), die dazu konfiguriert ist, eine Bildbedingung auszuwählen, die dem integrierten Bestimmungsergebnis aus der Vielzahl der im Bildbedingungsspeicher gespeicherten Bildbedingungen entspricht, und die Bildeinheit so zu steuern, dass das Ultraschallbild unter der ausgewählten Bildbedingung erzeugt wird.
3. Ultraschalldiagnosevorrichtung nach Anspruch 1 oder 2,
- wobei die Bildeinheit eine Sende-/Empfangeinheit (2) umfasst, die dazu konfiguriert ist, den Ultraschallstrahl gemäß Ultraschallstrahl-Abtastbedingungen zu senden und zu empfangen, und eine Bilderzeugungseinheit (3), die konfiguriert ist, um das Ultraschallbild aus dem empfangenen Signal gemäß Ultraschallbild-Erzeugungsbedingungen zu erzeugen, und die Bildbedingungen die Ultraschallstrahl-Abtastbedingungen und die Ultraschallbild-Erzeugungsbedingungen beinhalten.
4. Ultraschalldiagnosevorrichtung nach Anspruch 1, wobei die Bestimmungsergebnis-Integrationseinheit (13) dazu konfiguriert ist, einem Bestimmungsergebnis, das dem neuesten Frame entspricht, eine Gewichtung unter den Bestimmungsergebnissen zu verleihen, die der Vielzahl von Frames entsprechen, die in der Bestimmungsergebnis-Speichereinheit gespeichert sind.
5. Ultraschalldiagnosevorrichtung nach Anspruch 1, wobei die Teilbestimmungseinheit (11) dazu konfiguriert ist, das Bestimmungsergebnis und einen Ähnlichkeitswert für jeden der Vielzahl von Bildern auszugeben, und die Bestimmungsergebnis-Integrationseinheit (13) dazu konfiguriert ist, den Bestimmungsergebnissen Gewichtungen zu verleihen, die der Vielzahl von Frames entsprechen, die in der Bestimmungsergebnis-Speichereinheit gemäß von der Teilbestimmungseinheit ausgegebenen Ähnlichkeitswerten gespeichert sind.
6. Ultraschalldiagnosevorrichtung nach einem der Ansprüche 1 bis 5, ferner umfassend:
- eine Speichereinheit (32) für untersuchte Teile, die dazu konfiguriert ist, das integrierte Bestimmungsergebnis zu speichern, wobei in dem Fall, dass eine Vielzahl von Bildteilen des Subjekts sequentiell untersucht werden, die Vorrichtungssteuereinheit (14, 14A) dazu konfiguriert ist, den Bildteil, der durch das in der untersuchten Teilespeichereinheit gespeicherte integrierte Bestimmungsergebnis angegeben ist, von den nachfolgenden, durch die Teilebestimmungseinheit zu bestimmenden Bildteilen auszuschließen.
7. Ultraschalldiagnosevorrichtung nach Anspruch 6, ferner umfassend:
- eine Sondenzustandsbestimmungseinheit (31), die dazu konfiguriert ist, zu bestimmen, ob sich die Ultraschallsonde in einem Luftemissionszustand oder einem Kontaktzustand mit dem Subjekt befindet, wobei in dem Fall, dass die Sondenzustandsbestimmungseinheit (31) dazu konfiguriert ist, zu bestimmen, dass die Ultraschallsonde (1) aus dem Kontaktzustand mit dem Subjekt in den

Luftemissionszustand geändert wurde, die Vorrichtungsteuereinheit (14,14A) dazu konfiguriert ist, das integrierte Bestimmungsergebnis in der Speichereinheit (32) für untersuchte Teile zu speichern.

8. Verfahren zum Steuern einer Ultraschall Diagnosevorrichtung umfassend eine Ultraschallsonde, wobei das Verfahren umfasst:

einen Schritt (S1) des Sendens und Empfangens eines Ultraschallstrahls zu und von einem Subjekt unter Verwendung der Ultraschallsonde und des Umwandels eines von der Ultraschallsonde ausgehenden, empfangenen Signals in ein Bild, um ein Ultraschallbild des Subjekts gemäß den eingestellten Bildbedingungen zu erzeugen, wobei das Ultraschallbild einen Frame umfasst;

einen Schritt des Bestimmens (S3) eines Bildteils des Subjekts unter Verwendung des erzeugten Ultraschallbildes, wodurch ein Bestimmungsergebnis erhalten wird, das den Bildteil angibt, der in dem Frame erfasst wurde;

einen Schritt des Speicherns (S4) von Bestimmungsergebnissen, die durch das Bestimmen eines Bildteils erhalten werden, wobei die Bestimmungsergebnisse einer Vielzahl von Frames entsprechen, wobei Nf-Bestimmungsergebnisse, die Nf-Frames entsprechen, für einen Bildteil gespeichert werden; und

einen Schritt des Integrierens (S6) der gespeicherten Bestimmungsergebnisse, die der Vielzahl von Frames entsprechen, und des Ausgebens eines integrierten Bestimmungsergebnisses, wobei ein Bildteil, der durch die größte Anzahl von Bestimmungsergebnissen unter den Nf-Bestimmungsergebnissen angegeben ist, als das integrierte Bestimmungsergebnis ausgegeben wird.

9. Verfahren zum Steuern einer Ultraschall Diagnosevorrichtung nach Anspruch 8,

wobei eine Vielzahl von Bildbedingungen, die für jedes der Vielzahl von Bildteilen im Voraus festgelegt wurden, gespeichert werden, und eine dem integrierten Bestimmungsergebnis entsprechende Bildbedingung aus der Vielzahl der gespeicherten Bildbedingungen ausgewählt wird und das Ultraschallbild unter der ausgewählten Bildbedingung erzeugt wird.

10. Verfahren zum Steuern einer Ultraschall Diagnosevorrichtung nach Anspruch 8 oder 9, wobei die Bildbedingungen Ultraschallstrahl-Abtastbedingungen, die zum Senden und Empfangen des Ultraschallstrahls verwendet werden, und Ultra-

schallbild-Erzeugungsbedingungen, die zum Erzeugen des Ultraschallbildes aus dem empfangenen Signal verwendet werden, beinhalten.

11. Verfahren zum Steuern einer Ultraschall Diagnosevorrichtung nach Anspruch 8, wobei einem Bestimmungsergebnis eine Gewichtung verliehen wird, die dem letzten Frame der Bestimmungsergebnisse entspricht, die der Vielzahl der gespeicherten Frames entsprechen.

12. Verfahren zum Steuern einer Ultraschall Diagnosevorrichtung nach Anspruch 8,

wobei das Bestimmungsergebnis und ein Ähnlichkeitswert für jeden der Vielzahl von Frames ausgegeben werden, und den Bestimmungsergebnissen Gewichtungen gegeben werden, die der Vielzahl von Frames entsprechen, die entsprechend der Ausgabe der Ähnlichkeitswerte gespeichert sind.

13. Verfahren zum Steuern einer Ultraschall Diagnosevorrichtung nach einem der Ansprüche 8-12,

wobei das integrierte Bestimmungsergebnis gespeichert wird, und in dem Fall, dass eine Vielzahl von Bildteilen des Subjekts sequentiell untersucht wird, der durch das gespeicherte integrierte Bestimmungsergebnis angezeigte Bildteil von den nachfolgend zu bestimmenden Bildteilen ausgeschlossen wird.

## Revendications

1. Appareil de diagnostic à ultrasons (1), comprenant :

une sonde à ultrasons (1) ;  
une unité d'imagerie configurée pour transmettre et recevoir un faisceau ultrasonore en direction et en provenance d'un sujet à l'aide de la sonde à ultrasons et pour convertir un signal reçu produit à partir de la sonde à ultrasons en une image afin de générer une image ultrasonore du sujet, conformément à des conditions d'imagerie fixées, l'image ultrasonore comprenant une trame ;

une unité de détermination de partie (11) configurée pour déterminer une partie d'imagerie du sujet à l'aide de l'image ultrasonore générée par l'unité d'imagerie, ceci permettant d'obtenir un résultat de détermination indiquant la partie d'imagerie capturée dans la trame ;

une unité de stockage de résultat de détermination (12) configurée pour stocker des résultats de détermination obtenus par l'unité de déter-

- mination de partie, les résultats de détermination correspondant à une pluralité de trames, en sachant que Nf résultats de détermination correspondant à Nf trames sont stockés pour une partie d'imagerie dans l'unité de stockage de résultat de détermination, et  
 5 une unité d'intégration de résultat de détermination (13) configurée pour intégrer les résultats de détermination correspondant à la pluralité de trames stockées dans l'unité de stockage de résultat de détermination, et produire un résultat de détermination intégré, en sachant qu'une partie d'imagerie indiquée par le nombre le plus grand de résultats de détermination parmi les Nf résultats de détermination est produite sous la forme du résultat de détermination intégré.
2. Appareil de diagnostic à ultrasons selon la revendication 1, comprenant en outre :
- 20 une mémoire de condition d'imagerie (15) configurée pour stocker une pluralité de conditions d'imagerie fixées pour chacune d'une pluralité de parties d'imagerie au préalable, et  
 25 une unité de commande d'appareil (14, 14A) configurée pour sélectionner une condition d'imagerie correspondant au résultat de détermination intégré parmi la pluralité de conditions d'imagerie stockées dans la mémoire de condition d'imagerie et pour commander l'unité d'imagerie de telle sorte que l'image ultrasonore soit générée sous la condition d'imagerie sélectionnée.
3. Appareil de diagnostic à ultrasons selon la revendication 1 ou 2,  
 35 dans lequel l'unité d'imagerie inclut une unité de transmission/réception (2) configurée pour transmettre et recevoir le faisceau ultrasonore conformément à des conditions de balayage de faisceau ultrasonore, et une unité de génération d'image (3) configurée pour générer l'image ultrasonore à partir du signal reçu conformément à des conditions de génération d'image ultrasonore, et  
 40 les conditions d'imagerie incluent les conditions de balayage de faisceau ultrasonore et les conditions de génération d'image ultrasonore.
4. Appareil de diagnostic à ultrasons selon la revendication 1,  
 50 dans lequel l'unité d'intégration de résultat de détermination (13) est configurée pour attribuer une pondération à un résultat de détermination correspondant à la dernière trame parmi les résultats de détermination correspondant à la pluralité de trames stockées dans l'unité de stockage de résultat de détermination.
5. Appareil de diagnostic à ultrasons selon la revendication 1,  
 dans lequel l'unité de détermination de partie (11) est configurée pour produire le résultat de détermination et un score de similarité pour chacune de la pluralité de trames, et  
 l'unité d'intégration de résultat de détermination (13) est configurée pour attribuer des pondérations aux résultats de détermination correspondant à la pluralité de trames stockées dans l'unité de stockage de résultat de détermination conformément aux scores de similarité produits à partir de l'unité de détermination de partie.
6. Appareil de diagnostic à ultrasons selon l'une quelconque des revendications 1 à 5, comprenant en outre :
- 20 une unité de stockage de partie examinée (32) configurée pour stocker le résultat de détermination intégré,  
 dans lequel dans un cas où une pluralité de parties d'imagerie du sujet sont examinées séquentiellement, l'unité de commande d'appareil (14, 14A) est configurée pour exclure la partie d'imagerie, indiquée par le résultat de détermination intégré et stockée dans l'unité de stockage de partie examinée, des parties d'imagerie subséquentes devant être déterminées par l'unité de détermination de partie.
7. Appareil de diagnostic à ultrasons selon la revendication 6, comprenant en outre :
- 35 une unité de détermination d'état de sonde (31), configurée pour déterminer si oui ou non la sonde à ultrasons est dans un état d'émission aérienne ou un état de contact avec le patient, dans lequel dans un cas où l'unité de détermination d'état de sonde (31) est configurée pour déterminer que la sonde à ultrasons (1) a été modifiée d'un état de contact avec le sujet vers l'état d'émission aérienne, l'unité de commande d'appareil (14, 14A) est configurée pour stocker le résultat de détermination intégré dans l'unité de stockage de partie examinée (32).
8. Procédé destiné à commander un appareil de diagnostic à ultrasons incluant une sonde à ultrasons, le procédé comprenant les étapes suivantes :
- 50 une étape (S1) pour transmettre et recevoir un faisceau ultrasonore en direction et en provenance d'un sujet à l'aide de la sonde à ultrasons et pour convertir un signal reçu produit à partir de la sonde à ultrasons en une image afin de générer une image ultrasonore du sujet, conformément à des conditions d'imagerie fixées,

- l'image ultrasonore comprenant une trame ;  
 une étape pour déterminer (S3) une partie d'imagerie du sujet à l'aide de l'image ultrasonore générée, ceci permettant d'obtenir un résultat de détermination indiquant la partie d'imagerie capturée dans la trame ;  
 une étape pour stocker (S4) des résultats de détermination obtenus en déterminant une partie d'imagerie, les résultats de détermination correspondant à une pluralité de trames, en sachant que Nf résultats de détermination correspondant à Nf trames sont stockés pour une partie d'imagerie, et  
 une étape pour intégrer (S6) les résultats de détermination stockés correspondant à la pluralité de trames et produire un résultat de détermination intégré, en sachant qu'une partie d'imagerie indiquée par le nombre le plus grand de résultats de détermination parmi les Nf résultats de détermination est produite sous la forme du résultat de détermination intégré.
- 5 10 15 20
9. Procédé destiné à commander un appareil de diagnostic à ultrasons selon la revendication 8, dans lequel une pluralité de conditions d'imagerie fixées pour chacune d'une pluralité de parties d'imagerie sont stockées au préalable, et une condition d'imagerie correspondant au résultat de détermination intégré est sélectionnée parmi la pluralité de conditions d'imagerie stockées, et l'image ultrasonore est générée sous la condition d'imagerie sélectionnée.
- 25 30
10. Procédé destiné à commander un appareil de diagnostic à ultrasons selon la revendication 8 ou 9, dans lequel les conditions d'imagerie incluent des conditions de balayage de faisceau ultrasonore utilisées pour transmettre et recevoir le faisceau ultrasonore et des conditions de génération d'image ultrasonore utilisées pour générer l'image ultrasonore à partir du signal reçu.
- 35 40
11. Procédé destiné à commander un appareil de diagnostic à ultrasons selon la revendication 8, dans lequel une pondération est attribuée à un résultat de détermination correspondant à la dernière trame parmi les résultats de détermination correspondant à la pluralité de trames stockées.
- 45
12. Procédé destiné à commander un appareil de diagnostic à ultrasons selon la revendication 8, dans lequel le résultat de détermination et un score de similarité sont produits pour chacune de la pluralité de trames, et des pondérations sont attribuées aux résultats de détermination correspondant à la pluralité de trames stockées conformément aux scores de similarité produits.
- 50 55
13. Procédé destiné à commander un appareil de diagnostic à ultrasons selon l'une quelconque des revendications 8 à 12, dans lequel le résultat de détermination intégré est stocké, et dans un cas où une pluralité de parties d'imagerie du sujet sont examinées séquentiellement, la partie d'imagerie indiquée par le résultat de détermination intégré et stockée est exclue des parties d'imagerie subséquentes à déterminer.

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9



REFERENCES CITED IN THE DESCRIPTION

*This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.*

Patent documents cited in the description

- JP 4224738 A [0003] [0005]
- JP H04224738 A [0003] [0005]

Non-patent literature cited in the description

- **CSURKA et al.** Visual Categorization with Bags of Keypoints. *Proc. of ECCV Workshop on Statistical Learning in Computer Vision*, 2004, 59-74 [0043]
- **KRIZHEVSK et al.** ImageNet Classification with Deep Convolutional Neural Networks. *Advances in Neural Information Processing Systems*, 2012, vol. 25, 1106-1114 [0043]

|                |                             |         |            |
|----------------|-----------------------------|---------|------------|
| 专利名称(译)        | 超声波诊断装置及超声波诊断装置的控制方法        |         |            |
| 公开(公告)号        | <a href="#">EP3338643B1</a> | 公开(公告)日 | 2019-10-30 |
| 申请号            | EP2016838850                | 申请日     | 2016-05-10 |
| [标]申请(专利权)人(译) | 富士胶片株式会社                    |         |            |
| 申请(专利权)人(译)    | 富士胶片株式会社                    |         |            |
| 当前申请(专利权)人(译)  | 富士胶片株式会社                    |         |            |
| [标]发明人         | IMAI YOSHIRO                |         |            |
| 发明人            | IMAI YOSHIRO                |         |            |
| IPC分类号         | A61B8/14 A61B8/08 A61B8/00  |         |            |
| 优先权            | 2015164045 2015-08-21 JP    |         |            |
| 其他公开文献         | EP3338643A1<br>EP3338643A4  |         |            |
| 外部链接           | <a href="#">Espacenet</a>   |         |            |

#### 摘要(译)

一种超声波诊断装置，包括：超声波探头；和成像单元，其根据设置的成像条件，使用超声探头向对象发射超声波束并从对象接收超声束，并且将从超声探头输出的接收信号转换成图像以生成对象的超声图像；部分确定单元，其使用由所述成像单元生成的超声图像来确定所述对象的成像部分；确定结果存储单元，其存储与由部分确定单元获得的多个帧相对应的确定结果；确定结果整合单元，将与存储在确定结果存储单元中的多个帧相对应的确定结果进行整合，并输出合并后的确定结果。

