

(19)



(11)

EP 3 143 612 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
11.09.2019 Bulletin 2019/37

(51) Int Cl.:
G10K 11/30 (2006.01) **G01N 29/24** (2006.01)
A61B 8/00 (2006.01)

(21) Application number: **15718923.4**

(86) International application number:
PCT/EP2015/059439

(22) Date of filing: **30.04.2015**

(87) International publication number:
WO 2015/173027 (19.11.2015 Gazette 2015/46)

(54) ACOUSTICAL LENS AND ULTRASOUND TRANSDUCER PROBE

AKUSTISCHE LINSE UND ULTRASCHALLWANDLERSONDE

LENTILLE ACOUSTIQUE ET SONDE DE TRANSDUCTEUR ULTRASONORE

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(30) Priority: **14.05.2014 EP 14168372**

(43) Date of publication of application:
22.03.2017 Bulletin 2017/12

(73) Proprietor: **Koninklijke Philips N.V.
5656 AE Eindhoven (NL)**

(72) Inventors:
• **BECKERS, Lucas Johannes Anna Maria
NL-5656 AE Eindhoven (NL)**

- **DIRKSEN, Peter
NL-5656AE Eindhoven (NL)**
- **DE WILD, Nico Maris Adriaan
NL-5656AE Eindhoven (NL)**
- **HAKKENS, Franciscus Johannes Gerardus
NL-5656AE Eindhoven (NL)**

(74) Representative: **Philips Intellectual Property &
Standards
High Tech Campus 5
5656 AE Eindhoven (NL)**

(56) References cited:
**EP-A1- 2 289 419 EP-A1- 2 308 397
JP-A- 2004 105 741 US-A- 4 659 956
US-A- 4 699 150 US-A- 5 976 091**

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 3 143 612 B1

Description

FIELD OF THE INVENTION

[0001] The present invention relates to an acoustical lens for an ultrasound probe including an ultrasound transducer for emitting ultrasound waves. The present invention further relates to an ultrasound transducer probe comprising an ultrasound transducer for emitting ultrasound waves.

BACKGROUND OF THE INVENTION

[0002] Ultrasound probes are typically formed by an ultrasound transducer comprising one or more transducer elements and an acoustical lens for providing the ultrasound waves from the transducer to an outer concave surface which can be brought into contact e.g. with a human body for an ultrasound examination. The ultrasound transducers are usually molded with a connection mold or a glue to the acoustical lens in order to provide a good acoustical contact between the transducer elements and the outer surface of the acoustical lens, however, the connection mold usually comprise air bubbles while mounting the ultrasound transducer to the acoustical lens, which lead to acoustical reflections and an attenuation of the acoustical waves emitted from the transducer so that the efficiency of the ultrasound probe is reduced.

[0003] Further, the typically used connection molds or glues are susceptible for fluid incrust so that the acoustical stack, in particular the connection mold has to be protected against moisture from the outside of the acoustical lens.

[0004] In order to reduce the acoustical reflections between the transducer and the acoustical lens WO 2013/046080 proposes to scatter the acoustical waves in different spatial directions by means of a scattering surface, however, air bubbles included in the connection mold may still attenuate the emitted ultrasound waves.

[0005] US 4,699,150 A discloses an ultrasonic transducer for medical diagnostic examination which comprises a transducer element having one surface through which acoustic waves are emitted, an acoustic impedance matcher, and a contact member brought into contact with an object being examined and formed on the one surface of the ultrasonic transducer element.

[0006] US 4,659,956 A discloses a compound focus ultrasonic transducer for nondestructive evaluation and material characterization applications comprising a piezoelectric ceramic element having a first radius of curvature and a combination lens and a cover layer on its front having a second radius of curvature which is less than the first radius of the piezoelectric ceramic element.

[0007] Further ultrasound transducers are known from JP 2004 105741 A, US 5,976,091 A, and EP 2 289 419 A1.

SUMMARY OF THE INVENTION

[0008] It is an object of the present invention to provide an acoustical lens for an ultrasound probe and an ultrasound probe including an acoustical lens having an improved ultrasound emission.

[0009] In a first aspect of the present invention, an acoustical lens for an ultrasound probe according to claim 1 is provided.

[0010] In a further aspect of the present invention, an ultrasound transducer probe according to claim 9 is provided.

[0011] Preferred embodiments of the invention are defined in the dependent claims. It shall be understood that the claimed ultrasound transducer probe has similar and/or identical preferred embodiments as the claimed acoustical lens and as defined in the dependent claims.

[0012] The present invention is based on the idea to achieve an air bubble free mold connection between the emission surface of the ultrasound transducer and the inner surface of the acoustical lens to improve the acoustical connection between the emission surface and the inner surface in the main emission direction of the ultrasound waves. Since the inner surface is formed as a convexly curved surface, the thickness of the connection mold layer is reduced in a central portion which corresponds to the main direction of the ultrasound waves. While connecting the ultrasound transducer to the inner surface, the connection mold is moved or driven by the convexly curved surface to peripheral parts of the inner surface so that the included air bubbles are also driven to the peripheral part and the central part of the connection mold which corresponds to the main direction of the ultrasound waves is air bubble free and the thickness of the mold is reduced compared to the peripheral parts. Further, the recess can serve as a cavity for capturing excessive connection mold when the emission surface is brought into contact with the inner surface and to capture the air bubbles and the voids within the contact mold. Hence, the acoustical reflections at the air bubbles in the main direction of the ultrasound waves and the corresponding attenuation of the ultrasound waves can be reduced so that the ultrasound wave emission efficiency is increased.

[0013] According to a preferred embodiment, the inner surface is formed as a single convexly curved portion. This is a possibility to reduce the thickness of the contact mold at a central portion of the inner surface corresponding to the main direction of the ultrasound waves so that the attenuation of the ultrasound waves in the main emission direction is reduced and the efficiency of the ultrasound wave emission is improved. Further, the single convexly curved portion can multiple reflections so that the main direction of the ultrasound waves induced by the ultrasound transducer is not disturbed.

[0014] In a preferred embodiment, the recess has a concave shape. This is a possibility to provide the recess within the acoustical lens with low technical effort.

[0015] In a preferred embodiment, the recess is formed as a notch surrounding the inner surface at least partially. This is a possibility to capture the air bubbles in the connection mold and to receive the excessive material with high efficiency since the excessive material can be pushed to the sides of the convexly curved surface by pressing the emission surface to the inner surface.

[0016] The side walls are associated to the inner surface forming a cavity together with the inner surface for receiving the ultrasound transducer. This is a possibility to form a reliable connection between the ultrasound transducer and the acoustical lens, since the acoustical lens, since the acoustical lens forms a cavity for receiving the ultrasound transducer and supports the ultrasound transducer laterally.

[0017] In a preferred embodiment, the recess is formed as a notch separating the inner surface from inner surfaces of the side walls. This is a possibility to provide a cavity for excessive material of the connection mold which can receive the excessive connection mold easily, since the recess is formed as an edge between the side walls and the inner surface.

[0018] In a preferred embodiment, the inner surface is covered by a coating forming a moisture barrier. This is a possibility to protect the connection mold against moisture so that the probe can be used in a wet environment and the reliability of the mechanical connection between the ultrasound transducer and the acoustical lens is improved.

[0019] In a preferred embodiment, the inner surfaces of the side wall and a surface of the recess are covered by a coating forming the moisture barrier. This is a possibility to further improve the reliability of the mechanical connection, since the connection mold is entirely surrounded and protected against moisture.

[0020] In a preferred embodiment, the coating is formed as a metal layer. This is a possibility to provide the moisture barrier with high efficiency and low technical effort.

[0021] In a preferred embodiment of the ultrasound probe, the emission surface is connected to an inner surface by means of a connection mold. This is a possibility to improve the mechanical connection between the ultrasound transducer and the acoustical lens and to improve the efficiency of the ultrasound wave emission, since the connection mold reduces the ultrasound wave reflection at the inner surface of the acoustical lens.

[0022] In a preferred embodiment, the emission surface is a planar surface. This is a possibility to manufacture the ultrasound transducer with low technical effort, since the transducer can be formed e.g. as a capacitive micromachined ultrasound transducer on a silicon wafer and connected to the acoustical lens with an improved ultrasound wave emission efficiency.

[0023] As mentioned above, the present invention can reduce the reflection of the ultrasound waves at the interface between the emission surface and the inner surface of the acoustical lens, since air bubbles can be driven

from a middle portion of the inner surface to a peripheral side portion of the inner surface when the emission surface and the inner surface are connected by means of a connection mold and the two surfaces are pressed to each other. Since the air bubbles are removed from the central portion of the emission surface, which is the main emission direction of the ultrasound waves and since the thickness of the connection mold can be reduced at this central portion, the reflections and the attenuation of the ultrasound waves is reduced and the efficiency of the ultrasound wave emission is improved.

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] These and other aspects of the invention will be apparent from and elucidated with reference to the embodiments described hereinafter. In the following drawings

Fig. 1 shows a schematic representation of an ultrasound imaging system in use to scan a volume of a patient's body;

Fig. 2 shows a schematic cross sectional view of an acoustical lens for an ultrasound probe;

Fig. 3 shows a schematic cross sectional view of an ultrasound probe including an acoustical lens shown in fig. 2, and

Fig. 4 shows single steps for connecting an ultrasound transducer to an acoustical lens shown in fig. 2 in order to form the ultrasound probe shown in fig. 3.

DETAILED DESCRIPTION OF THE INVENTION

[0025] Fig. 1 shows a schematic illustration of an ultrasound system 10, in particular a medical three-dimensional (3D) ultrasound imaging system. The ultrasound imaging system 10 is applied to inspect the volume of an anatomical side, in particular an anatomical side of a patient 12. The ultrasound system comprises an ultrasound probe 14 having at least one ultrasound transducer, in particular an ultrasound transducer array having a multitude of transducer elements for transmitting and/or receiving ultrasound waves. The ultrasound probe 14 comprises an acoustical lens connected to the ultrasound transducer forming a contact surface of the ultrasound probe 14 for connecting the ultrasound probe 14 to the patient 12.

[0026] Further, the ultrasound system 10 may comprise a controlling unit 16 that controls the provision of a 3D image via the ultrasound system 10. The controlling unit 16 controls not only the acquisition of data via the transducer array of the ultrasound probe 14, but also signal and image processing that form the 3D images out of the echoes of the ultrasound beams received by the transducer array of the ultrasound probe.

[0027] The ultrasound system may further comprise a display 18 for displaying the 3D images to the user and may comprise an input device including keys or a key-

boards as a user interface.

[0028] Fig. 2 shows a schematic sectional view of an acoustical lens for the ultrasound probe 14 generally denoted by 20. The acoustical lens 20 comprises a main body 22 that may be formed of a thermoplastic elastomer, which is capable of submitting ultrasound waves. The main body comprises an outer surface 24 and an inner surface 26. The inner surface 26 is generally adapted to face an emission surface of an ultrasound transducer and for receiving ultrasound waves from the ultrasound transducer. The outer surface 24 is generally adapted to emit the ultrasound waves received at the inner surface and submitted via the main body 22. The outer surface 24 is also adapted to receive ultrasound waves and to provide the received ultrasound waves to the ultrasound transducer. The outer surface 24 has a convexly curved shape in order to emit the ultrasound waves correspondingly in a radial direction. The inner surface 26 is formed as a convexly curved surface having a curvature opposite to the curvature of the outer surface.

[0029] The main body 22 further comprises one or a plurality of side walls 28 extending in this sectional view in a direction opposite to the outer surface 24. The side walls 28 comprise an inner surface 30, which form a cavity 32 for receiving the ultrasound transducer as described in the following. The main body 22 is formed as an integral part in one piece.

[0030] Between the inner surface 26 and the inner surface 30 of the side walls 28, one or more recesses 34 are formed for capturing excessive connection mold which is used for connecting the ultrasound transducer to the acoustical lens 20 as described in the following. The recesses 34 may be formed as separate recesses between the inner surface 26 and the inner surface 30 of the side walls 28 or may be a continuous notch at the edge between the inner surface 26 and the inner surface 30 of the side walls 28. The recess 34 is formed as a cavity or a blind hole or blind notch.

[0031] The main body 22 may have a circular shape and is symmetrical to an axis of symmetry 36. The sectional view of fig. 2 has to be understood that the inner surface 26 and the outer surface 24 are both two dimensional planes which expand orthogonally from the paper plane. Thereby, both surfaces 24, 26 are arranged at opposite sides of the main body 22. The side walls 28 are preferably formed as a cylindrical portion extending coaxially in a direction of the axis of symmetry 36.

[0032] The inner surface 26, the inner surfaces 30 of the side walls 28 and an inner surface of the cavity 34 are covered by a moisture barrier layer 38. The moisture barrier layer 38 is provided to protect the cavity 32 in general against moisture from the outside. The moisture barrier layer 38 is preferably formed as a metal layer.

[0033] The main body 22 is preferably formed by the polyether block amide PEBAX 2533, which is a thermoplastic elastomer, made of flexible polyether and writhed polyamide.

[0034] Fig. 3 shows a schematic sectional view of the

ultrasound probe 14 comprising the acoustical lens 20 and an ultrasound transducer which is generally denoted by 40. The ultrasound transducer 40 comprises an ultrasound transducer element 42 or an ultrasound transducer array 42 for transmitting and/or receiving ultrasound waves. The ultrasound transducer element 42 or the ultrasound transducer array 42 is formed as a ceramic micromachined ultrasound transducer on wafer level and attached to a support portion 44, which is provided for mechanically supporting the transducer element or array 42 and for electrically connecting the transducer elements 42. The support portion 44 may be a flexible mount structure having an underfill for the transducer element 42 or the transducer array 42. The transducer element 42 or the transducer array 42 comprises an emission surface 46 for emitting and/or receiving the ultrasound waves.

[0035] The ultrasound transducer 40 is disposed at least partially within the cavity 32 and attached to the inner surfaces 26, 30 of the cavity 32 by means of a connection mold or a glue 48. The glue 48 is formed as a PDMS (Polydimethylsiloxan) or a Polybutadine in order to fix the ultrasound transducer 40 in the cavity 32 and to form a good acoustic connection to the inner surface 26.

[0036] The ultrasound transducer 40 is disposed within the cavity 32 so that the emission surface 46 faces the inner surface 26 and the side walls 28 support the ultrasound transducer 40 laterally. In this position, the ultrasound waves emitted from the emission surface 46 can be provided to the inner surface 26 and further submitted to the outer surface 24 via the main body 22. Due to the convexly curved shape of the inner surface 26, a central portion of the emission surface 46, which forms the main emission direction of the ultrasound transducer element 42 or the transducer array 42 along the axis of symmetry 36, is in close contact to the inner surface 26 so that the attenuation and the reflections at this central portion are reduced. During the manufacturing process, an ultrasound transducer 40 is pressed into the cavity 32, so that the glue 48 is driven from the central portion of the emission surface 46 to the peripheral portion and also avoids or air bubbles included in the mold 48 are driven to the peripheral portion as described in the following.

[0037] The moisture barrier layer 38 protects the glue 32, which is hydrophilic, from the outside, so that the ultrasound probe 14 can be used in wet environments without damaging the glue 48 by intruding moisture.

[0038] The recesses 34 serve as a cavity for excessive glue 48, which is pressed during the manufacturing process to the sides into the recesses 34 so that the emission surface 46 can be brought into close contact to the inner surface 26.

[0039] Figs. 4a-d show process steps to manufacture the ultrasound probe 14 including the acoustical lens 20 and the ultrasound transducer 40. In other words, fig. 4a-d show process steps to connect the ultrasound transducer 40 into the cavity 32 of the acoustical lens 20.

[0040] The ultrasound transducer 40 comprises the transducer element 42 or the transducer array 42 attached to the support portion 44 and having the emission surface 46 as described above. The transducer elements 42 can be the capacitive micromachined ultrasound transducers (CMUTs) manufactured by the available microfabrication techniques, such as sacrificial layer etching or wafer-bonding. The transducer elements 42 can be also piezoelectric based ultrasound transducers (PZTs).

[0041] The upper portion of the support portion 40 including the transducer element 42 or the transducer array 42 is coated with the glue 48 by means of dip-coating or spray-coating as shown in fig. 4b.

[0042] As shown in fig. 4c, the ultrasound transducer 40 and the attached glue 48 are introduced into the cavity 32 as indicated by an arrow 50. The ultrasound transducer 40 is introduced into the cavity 32 so that the emission surface 46 faces the inner surface 26 and that the ultrasound transducer 40 is introduced coaxially to the axis of symmetry 36 into the cavity 32. When the emission surface 46 is introduced into the cavity 32 and still disposed in a distance to the inner surface 26, the ultrasound transducer 40 is pressed into the cavity 32 as shown in fig. 4d by an arrow 52. In this certain step, the glue 48 disposed between the emission surface 46 and the inner surface 26 is moved or driven to the peripheral parts of the emission surface 46 and into the recesses 34 as shown by arrows 54. This is achieved by the convex curvature of the inner surface 26 so that the excessive glue 48 is driven into the recesses 34 including air bubbles so that finally the distance between the emission surface 46 and the inner surface 26 at the central part of the emission surface 26 is low and the air bubbles in the glue 48 are removed to the peripheral parts and in particular into the recesses 34. Hence, the reflections and the attenuation for the ultrasound waves in the central part of the emission surface 46 are reduced and the efficiency of the ultrasound wave emission of the probe 14 is improved.

[0043] While the invention has been illustrated and described in detail in the drawings and foregoing description, such illustration and description are to be considered illustrative or exemplary and not restrictive; the invention is not limited to the disclosed embodiments. Other variations to the disclosed embodiments can be understood and effected by those skilled in the art in practicing the claimed invention, from a study of the drawings and the disclosure, the scope of protection is defined by the appended claims.

[0044] In the claims, the word "comprising" does not exclude other elements or steps, and the indefinite article "a" or "an" does not exclude a plurality.

[0045] Any reference signs in the claims should not be construed as limiting the scope.

Claims

1. Acoustical lens (20) for an ultrasound probe (14), comprising:

- an inner surface (26) for facing an emission surface (46) of an ultrasound transducer (40) and for receiving ultrasound waves from the ultrasound transducer,
- an outer surface (24) for emitting the ultrasound waves received at the inner surface,

wherein the inner surface is formed as a convexly curved surface, and

characterized in that :

- at least one recess (34) is associated to an edge of the inner surface for capturing mold material, and
- wherein sidewalls (28) are associated to the inner surface forming a cavity together with the inner surface for receiving the ultrasound transducer, and
- wherein the recess is formed between the sidewalls and the inner surface.

2. Acoustical lens as claimed in claim 1, wherein the inner surface is formed as a single convexly curved portion.

3. Acoustical lens as claimed in claim 1, wherein the recess has a concave shape.

4. Acoustical lens as claimed in claim 1, wherein the recess is formed as a notch surrounding the inner surface at least partially.

5. Acoustical lens as claimed in claim 1, wherein the recess is formed as a notch separating the inner surface from inner surfaces (30) of the sidewalls.

6. Acoustical lens as claimed in claim 1, wherein the inner surface is covered by a coating (38) forming a moisture barrier.

7. Acoustical lens as claimed in claim 6, wherein inner surfaces of side walls and a surface of the recess are covered by the coating forming the moisture barrier.

8. Acoustical lens as claimed in claim 6, wherein the coating is formed as a metal layer.

9. Ultrasound transducer probe (14) comprising:

- an ultrasound transducer (40) including an emission surface (46) for emitting ultrasound waves, and

- the acoustical lens of claim 1, having the inner surface (26) facing the emission surface of the ultrasound transducer for receiving the ultrasound waves from the emission surface, and the outer surface (24) for emitting the ultrasound waves received at the inner surface, wherein the sidewalls (28) are associated to the inner surface forming a cavity together with the inner surface for receiving the ultrasound transducer.

10. Ultrasound transducer probe as claimed in claim 9, wherein the emission surface is connected to the inner surface by means of a connection mold (48).

11. Ultrasound transducer probe as claimed in claim 9, wherein the emission surface is a planar surface.

Patentansprüche

1. Akustische Linse (20) für eine Ultraschallsonde (14), umfassend:

- eine Innenfläche (26) zum Verkleiden einer Emissionsfläche (46) eines Ultraschallwandlers (40) und zum Empfangen von Ultraschallwellen vom Ultraschallwandler,
- eine Außenfläche (24) zum Aussenden der Ultraschallwellen, die an der Innenfläche empfangen wurden,

wobei die Innenfläche als eine konvex gekrümmte Fläche gebildet ist und

dadurch gekennzeichnet, dass:

mindestens eine Vertiefung (34) mit einem Rand der Innenfläche zum Erfassen von Formungsmaterial verbunden ist, und wobei Seitenwände (28) mit der Innenfläche verbunden sind, die gemeinsam mit der Innenfläche einen Hohlraum zum Aufnehmen des Ultraschallwandlers bilden, und wobei die Vertiefung zwischen den Seitenwänden und der Innenfläche gebildet ist.

2. Akustische Linse nach Anspruch 1, wobei die Innenfläche als ein einzelner konvex gekrümmter Abschnitt gebildet ist.

3. Akustische Linse nach Anspruch 1, wobei die Vertiefung eine konkave Form hat.

4. Akustische Linse nach Anspruch 1, wobei die Vertiefung als eine Kerbe gebildet ist, die die Innenfläche zumindest teilweise umgibt.

5. Akustische Linse nach Anspruch 1, wobei die Vertiefung als eine Kerbe gebildet ist, die die Innenfläche

che von Innenflächen (30) der Seitenwände trennt.

6. Akustische Linse nach Anspruch 1, wobei die Innenfläche von einer Beschichtung (38) bedeckt ist, die eine Feuchtigkeitsbarriere bildet.

7. Akustische Linse nach Anspruch 6, wobei Innenflächen von Seitenwänden und eine Fläche der Vertiefung von der Beschichtung bedeckt sind, die eine Feuchtigkeitsbarriere bildet.

8. Akustische Linse nach Anspruch 6, wobei die Beschichtung als Metallschicht gebildet ist.

9. Ultraschallwandlersonde (14), umfassend:

- einen Ultraschallwandler (40), der eine Emissionsfläche (46) zum Aussenden von Ultraschallwellen enthält, und

- die akustische Linse nach Anspruch 1 mit der Innenfläche (26), die die Emissionsfläche des Ultraschallwandlers verkleidet, um die Ultraschallwellen von der Emissionsfläche zu empfangen, und der Außenfläche (24) zum Aussenden der Ultraschallwellen, die an der Innenfläche empfangen wurden, wobei die Seitenwände (28) mit der Innenfläche verbunden sind, um gemeinsam mit der Innenfläche einen Hohlraum zum Aufnehmen des Ultraschallwandlers zu bilden.

10. Ultraschallwandlersonde nach Anspruch 9, wobei die Emissionsfläche mit der Innenfläche durch eine Verbindungsform (48) verbunden ist.

11. Ultraschallwandlersonde nach Anspruch 9, wobei die Emissionsfläche eine ebene Fläche ist.

Revendications

1. Lentille acoustique (20) pour une sonde ultrasonore (14) comprenant :

- une surface interne (26) pour faire face à une surface d'émission (46) d'un transducteur ultrasonore (40) et pour recevoir des ondes ultrasonores du transducteur ultrasonore,
- une surface externe (24) pour émettre les ondes ultrasonores reçues sur la surface interne,

dans laquelle la surface interne est conformée en surface à courbure convexe, et

caractérisée en ce que :

au moins un évidement (34) est associé à un bord de la surface interne pour capturer un matériau de moulage et

- dans laquelle les parois latérales (28) sont associées à la surface interne en formant une cavité conjointement avec la surface interne pour recevoir le transducteur ultrasonore, et dans lequel l'évidement est formé entre les parois latérales et la surface interne. 5
2. Lentille acoustique selon la revendication 1, dans laquelle la surface interne est conformée en partie unique à courbure convexe. 10
3. Lentille acoustique selon la revendication 1, dans laquelle l'évidement à une forme concave.
4. Lentille acoustique selon la revendication 1, dans laquelle l'évidement est conformé en encoche entourant la surface interne au moins en partie. 15
5. Lentille acoustique selon la revendication 1, dans laquelle l'évidement est conformé en encoche séparant la surface interne des surfaces internes (30) des parois latérales. 20
6. Lentille acoustique selon la revendication 1, dans laquelle la surface interne est recouverte d'un revêtement (38) formant une barrière à l'humidité. 25
7. Lentille acoustique selon la revendication 6, dans laquelle les surfaces internes des parois latérales et une surface de l'évidement sont recouvertes par le revêtement formant la barrière à l'humidité. 30
8. Lentille acoustique selon la revendication 6, dans laquelle le revêtement est conformé en couche métallique. 35
9. Sonde de transducteur ultrasonore (14) comprenant :
- un transducteur ultrasonore (40) comprenant une surface d'émission (46) pour émettre des ondes ultrasonores et 40
 - la lentille acoustique de la revendication 1 ayant la surface interne (26) faisant face à la surface d'émission du transducteur ultrasonore pour recevoir les ondes ultrasonores de la surface d'émission et la surface externe (24) pour émettre les ondes ultrasonores reçues sur la surface interne, dans laquelle les parois latérales (28) sont associées à la surface interne en formant une cavité conjointement avec la surface interne pour recevoir le transducteur ultrasonore. 45 50
10. Sonde de transducteur ultrasonore selon la revendication 9, dans laquelle la surface d'émission est raccordée à la surface interne au moyen d'un moule de liaison (48). 55
11. Sonde de transducteur ultrasonore selon la revendication 9, dans laquelle la surface d'émission est une surface plane.




FIG. 1




FIG. 2




FIG. 3




FIG. 4

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO 2013046080 A [0004]
- US 4699150 A [0005]
- US 4659956 A [0006]
- JP 2004105741 A [0007]
- US 5976091 A [0007]
- EP 2289419 A1 [0007]

专利名称(译)	声学镜头和超声波发射器		
公开(公告)号	EP3143612B1	公开(公告)日	2019-09-11
申请号	EP2015718923	申请日	2015-04-30
[标]申请(专利权)人(译)	皇家飞利浦电子股份有限公司		
申请(专利权)人(译)	皇家飞利浦N.V.		
当前申请(专利权)人(译)	皇家飞利浦N.V.		
[标]发明人	BECKERS LUCAS JOHANNES ANNA MARIA DIRKSEN PETER DE WILD NICO MARIS ADRIAAN HAKKENS FRANCISCUS JOHANNES GERARDUS		
发明人	BECKERS, LUCAS JOHANNES ANNA MARIA DIRKSEN, PETER DE WILD, NICO MARIS ADRIAAN HAKKENS, FRANCISCUS JOHANNES GERARDUS		
IPC分类号	G10K11/30 G01N29/24 A61B8/00		
CPC分类号	A61B8/4281 A61B8/4444 A61B8/483 G01N29/2456 G10K11/30 A61B8/4483		
代理机构(译)	飞利浦知识产权及标准		
优先权	2014168372 2014-05-14 EP		
其他公开文献	EP3143612A1		
外部链接	Espacenet		

摘要(译)

公开了一种用于超声探头 (14) 的声透镜 (20)。声透镜包括内表面 (26)，该内表面 (26) 面向超声换能器 (40) 的发射表面 (46) 并用于接收来自超声换能器的超声波。该声透镜还包括用于发射在该内表面处接收的超声波的外表面 (24)，其中该内表面形成为凸曲面，并且其中至少一个凹部 (34) 与该内表面的边缘相关联。用于捕获模具材料的表面。




FIG. 1