



(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 158(3) EPC

(43) Date of publication:
01.08.2007 Bulletin 2007/31

(51) Int Cl.:
A61B 8/12 (2006.01)

(21) Application number: **05790499.7**

(86) International application number:
PCT/JP2005/018317

(22) Date of filing: **04.10.2005**

(87) International publication number:
WO 2006/051659 (18.05.2006 Gazette 2006/20)

(84) Designated Contracting States:
DE FR GB

(30) Priority: **09.11.2004 JP 2004325248**

(71) Applicant: **Olympus Corporation**
Tokyo 151-0072 (JP)

(72) Inventors:
• **IMAHASHI, Takuya**
Olympus Medical Systems Corp.
Tokyo 151-0072 (JP)
• **MIZUNUMA, Akiko**
Olympus Medical Systems Corp.
Tokyo 1510072 (JP)

• **SAWADA, Yukihiro**
Olympus Medical Systems Corp.
Tokyo 151-0072 (JP)
• **WAKABAYASHI, Katsuhiro**
Olympus Medical Systems Corp.
Tokyo 151-0072 (JP)
• **SATO, Sunao**
Olympus Medical Systems Corp.
Tokyo 1510072 (JP)

(74) Representative: **von Hellfeld, Axel**
Wuesthoff & Wuesthoff
Patent- und Rechtsanwälte
Schweigerstrasse 2
81541 München (DE)

(54) **ULTRASONIC ENDOSCOPE**

(57) The present invention provides an ultrasonic endoscope, comprising: an ultrasonic transducer in a cylindrical shape including a plurality of piezoelectric devices, an acoustic matching layer stacked on a principal plane on a sound emitting plane side, an acoustic lens on a plane of the acoustic matching layer opposite to a plane facing the piezoelectric devices, and a backing material stacked on another principal planes of the piezoelectric devices; an endoscopic observation and endo-therapy unit provided, for performing endoscopic image observation, at a proximal end side of the ultrasonic transducer; a cable ass'y including a plurality of cables for transmitting signals to and from the ultrasonic transducer. In the above configuration, the cable ass'y is arranged in such a manner that the cable ass'y passes through an inside portion of the ultrasonic transducer, and is connected to the ultrasonic transducer at a distal end side of the ultrasonic transducer. Thereby, an ultrasonic endoscope is provided that has an ultrasonic transducer in which the ultrasonic transducer and coaxial cables will not be disconnected even under thermal or mechanical loads.




FIG. 4

Description

Technical Field

[0001] The present invention relates to an electronic radial scanning ultrasonic endoscope, and particularly to a method of connecting coaxial cables for transmitting signals and an ultrasonic transducer in which a plurality of transducer elements are arranged in such a manner that the arranged transducer elements to the cylindrical shape along the periphery of the ultrasonic transducer.

Background Art

[0002] There are two conventional methods of radial scanning ultrasonic endoscopes, the electronic scanning method that performs electronic scans and the mechanical scanning method that performs mechanical scans. In the ultrasonic endoscopes of the electronic scanning-method, the configuration is generally employed in which the ultrasonic transducer formed in a cylindrical shape for performing the radial scan and the endoscopic observation and endo-therapy units for performing endoscopic image observation are arranged in very close proximity to each other and are fixed as one piece, and a plurality of flexible printed circuit (FPC) boards are used as cables for transmitting electric signals to and from the ultrasonic transducer.

[0003] In addition, a plurality of FPC boards connected to the transducer elements are arranged in such a manner that an arch is formed by the plurality of FPC boards in order to avoid being close to the endoscopic observation and endo-therapy units such as its instrument channel port and the like, and thereafter the plurality of FPC boards are connected to signal cables (coaxial cables) at a spot closer to the proximal end than the bending section of the endoscope (on the side of the control section of the ultrasonic endoscope body) (see Patent Document 1, for example).

[0004] In the ultrasonic endoscopes of the mechanical scanning method, a scan is performed by turning one ultrasonic transducer in the insertion axis direction using an electric motor or the like provided at the proximal end. Accordingly, the ultrasonic transducer is attached by means of a shaft bearing structure such as ball bearings provided in the vicinity of the ultrasonic transducer (see Patent Document 2, for example).

Patent Document 1

Japanese Patent Application Publication No. 2001-314406

Patent Document 2

Japanese Patent Application Publication No. 2-116358

Disclosure of the Invention

[0005] The ultrasonic endoscope of the electronic

scanning method has the problem that when the FPC boards and the coaxial cables are connected and the components for the cables are inserted into the insertion tube, tensile force applied in the direction of the control section tends to break the connection between the ultrasonic transducer and the FPC boards, which results in disconnection.

[0006] Also, because the FPC boards, which are naturally flat shaped, are curved to form an arch, the residual stress of the FPC boards varies with thermal variations and variations in atmospheric pressure during sterilization and disinfection, and the FPC boards tend to change their shape, causing an increased likelihood of disconnection between the ultrasonic transducer and the connection portions in the FPC boards and between the cables and the connection portions in the FPC boards, which is problematic.

[0007] Also, the cross section of the FPC board is rectangular while the cross section of the ultrasonic endoscope is circular; accordingly, there is the problem that spatial losses result, requiring larger diameter of the ultrasonic endoscope even when the FPC boards are packed together into the insertion tube.

[0008] Also, there is the problem that, because the connection portions are at a place that is closer to the control section than to the bending section, it is difficult to repair when a disconnection is caused in this configuration.

[0009] Also, in the ultrasonic endoscope of the mechanical scanning method, the interval between the axis of an endoscopic image and the acoustic axis emitted from the ultrasonic transducer is determined by the dimension (diameter) of the ultrasonic transducer and the structure of the shaft bearing in the vicinity of the ultrasonic transducer. The diameter of the ultrasonic transducer influences the penetration, which in turn influences ultrasonic images; thus, the diameter of the ultrasonic transducer is required to be at least approximately 10 mm. Additionally, the structure is conventionally required to be the bearing structure; accordingly, the interval between the endoscopic image and the acoustic axis is approximately 10 mm. Thus, it is difficult to make images of surfaces of the body cavities that are in endoscopic images correspond to ultrasonic images (cross section images) or inside portions or the corresponding area on the endoscopic surfaces of the body cavities, which is problematic.

[0010] The present invention is achieved in view of the above problems, and it is an object of the present invention to provide an ultrasonic endoscope having an ultrasonic transducer in which the ultrasonic transducer and coaxial cables will not become disconnected even under thermal or mechanical loads.

[0011] In addition, it is another object of the present invention to provide an ultrasonic endoscope in which the length of the rigid portion required as a space for wiring is shortened as much as possible.

[0012] The present invention employs the configura-

tions as described below in order to solve the above problems.

[0013] According to one aspect of the present invention, an ultrasonic endoscope according to the present invention is an ultrasonic endoscope comprising: an ultrasonic transducer in a cylindrical shape including a plurality of piezoelectric devices, an acoustic matching layer stacked on a principal plane on a sound emitting plane side, an acoustic lens on a plane of the acoustic matching layer opposite to a plane facing the piezoelectric devices, and a backing material stacked on another principal planes of the piezoelectric devices; an endoscopic observation and endo-therapy units provided, for performing endoscopic image observation, at the proximal end side of the ultrasonic transducer; a cable ass'y (a bundle of cable) including a plurality of cables for transmitting signals to and from the ultrasonic transducer, in which: the cable ass'y is arranged in such a manner that the cable ass'y passes through an inside portion of the ultrasonic transducer and is connected to the ultrasonic transducer at the distal end side of the ultrasonic transducer.

[0014] Also, it is desirable in an ultrasonic endoscope according to the present invention that the ultrasonic transducer includes a ring-shaped frame member in an inside portion of the distal end side for forming the cylindrical shape; the ultrasonic endoscope further includes a ring-shaped circuit board having an outer diameter that is greater than the inner diameter of the frame member and that is smaller than the inner diameter of the ultrasonic transducer, the ring-shaped circuit board being for connecting respective cables included in the cable ass'y to the ultrasonic transducer; and the circuit board be locked in the frame member at the distal end side of the ultrasonic transducer.

[0015] Also, it is desirable in an ultrasonic endoscope according to the present invention that the ultrasonic transducer includes a ring-shaped frame member in an inside portion of the distal end side for forming the cylindrical shape; and the ultrasonic endoscope further comprises: a ring-shaped circuit board having an outer diameter that is smaller than the inner diameter of the frame member, the ring-shaped circuit board being for connecting respective cables included in the cable ass'y to the ultrasonic transducer; and a locking member for locking the circuit board in the frame member at the distal end side of the ultrasonic transducer.

[0016] Also, it is desirable in an ultrasonic endoscope according to the present invention that, for the ultrasonic endoscope according to claim 1, the ultrasonic endoscope further comprises a balloon unit for covering the ultrasonic transducer; and the balloon unit or the acoustic lens be arranged in such a manner that the acoustic axis of ultrasound emitted from the acoustic lens and the balloon unit are not orthogonal to each other.

Brief Description of the Drawings

[0017]

Fig. 1 shows a configuration of the entire ultrasonic endoscope;

Fig. 2 shows a configuration of the rigid tip portion;

Fig. 3 shows a configuration of the ultrasonic transducer;

Fig. 4 shows an internal configuration of the ultrasonic transducer;

Fig. 5 is a first view showing processes of manufacturing the ultrasonic transducer;

Fig. 6 is a second view showing processes of manufacturing the ultrasonic transducer;

Fig. 7 is a first view showing processes of manufacturing the ultrasonic transducer in an example of a variation;

Fig. 8 shows locking members in an example of a variation of the ultrasonic transducer;

Fig. 9 is a second view showing processes of manufacturing the ultrasonic transducer in an example of a variation;

Fig. 10 shows a positional relationship between the objective lens and the acoustic axis; and

Fig. 11 shows a positional relationship between a balloon unit and the acoustic axis.

Best Modes for Carrying Out the Invention

[0018] Hereinafter, embodiments of the present invention will be described by referring to the drawings.

[0019] Fig. 1 shows a configuration of an entire ultrasonic endoscope.

[0020] In Fig. 1, an ultrasonic endoscope 1 comprises an insertion section 11 that is to be inserted into body cavities, a control section 12 connected to a proximal end side of the insertion section 11, and a universal code 13 that extends from a side surface of the control section 12.

[0021] A scope connector 14 that is connected to a light source unit (not shown) for providing illumination light is connected to the proximal end of the universal code 13. An ultrasonic code 15 has an ultrasonic connector 16 that is electrically connected to a diagnostic ultrasound system (not shown) and that is for driving an ultrasonic transducer and creating ultrasonic diagnosis images by performing various signal processes on received signals. The ultrasonic code 15 extends from the scope connector 14.

[0022] The insertion section 11 comprises, in the order starting from the distal end side thereof and in a connected state, a rigid tip portion 17 made of a stiff material, a bending section 18 that is at the proximal end side of the rigid tip portion 17 and that can arbitrarily bend, and an insertion tube 19 that is at the proximal end side of the bending section 18, is connected to the distal end side of the control section 12, and is elongate and flexible.

[0023] Fig. 2 shows a configuration of the rigid tip portion.

[0024] In Fig. 2, the rigid tip portion 17 comprises an endoscopic observation and endo-therapy unit 22 for directly performing endoscopic image observation of sur-

faces of tissues of diseased area, and an ultrasonic transducer 21 for emitting ultrasound in order to receive the ultrasound that have been reflected from the acoustic impedance boundary in the tissues of diseased area that are the observation area.

[0025] The endoscopic observation and endo-therapy unit 22 comprises an illumination lens 23 for guiding the illumination light to the surfaces of the tissues of diseased area, an objective lens 24 for condensing the light reflected from the surfaces of the tissues of diseased area, an nozzle 25 for feeding gas or liquid to body cavities, and an instrument channel outlet 26 for suction the gas or liquid in the body cavities and accepting an instrument.

[0026] Fig. 3 shows a configuration of the ultrasonic transducer.

[0027] In Fig. 3, the ultrasonic transducer 21 comprises circuit boards 32 connected to a cable ass'y 31 that includes a plurality of cables for the transmission of electric signals to and from an ultrasonic endoscope body via the bending section 18 and the insertion tube 19, boards 33 connected to the circuit boards 32 and linked to a cylindrical piezoelectric device for emitting ultrasound (see Fig. 4), an acoustic matching layer 34 formed on the outer surfaces of the piezoelectric devices for protecting the piezoelectric devices and for performing acoustic matching with an external environment, an acoustic lens 35 formed on the outer surface of the acoustic matching layer 34 for condensing the ultrasound transmitted from the piezoelectric devices, and a backing material (see Fig. 4) on the inner surfaces of the piezoelectric devices. The ultrasonic transducer 21 is cylindrical.

[0028] Fig. 4 shows an internal configuration of the ultrasonic transducer.

[0029] In Fig. 4, the ultrasonic transducer 21 comprises the circuit boards 32 connected to the cable ass'y 31, the boards 33, piezoelectric devices 36, the acoustic matching layer 34 stacked on the outer surface of the piezoelectric devices 36, the acoustic lens 35 stacked on the outer surface of the acoustic matching layer 34, and a backing material 38 on the inner surfaces of the piezoelectric devices 36.

[0030] The cable ass'y 31 and the circuit boards 32 are connected to each other via cables 43, and the connection spots between them are covered by a potting material 44. The circuit boards 32 and the boards 33 are connected to each other via wires 45 at soldered portions 46, and the boards 33 are connected to the piezoelectric devices 36 via connection units 37. Thereby, electric signals are transmitted to the piezoelectric devices 36.

[0031] A cylindrical nose piece 42 surrounding the cable ass'y 31 is provided to the circuit boards 32, and the circuit boards 32 are partially grounded via a ground line 47 in the cylindrical nose piece 42. The circuit boards 32 are locked in ring-shaped frame members 41 in such a way that the piezoelectric devices 36, the boards 33, the acoustic matching layer 34, the acoustic lens 35, and the backing material 38 form a cylindrical shape.

[0032] Next, processes of manufacturing the ultrason-

ic transducer 21 are explained.

[0033] First, as shown in Fig. 5, the cable ass'y 31 and the circuit boards 32 are connected to each other, and the portion of the cable ass'y 31 closer to the circuit boards 32 is surrounded by the nose piece 42. The portion of the cable ass'y 31 closer to the ultrasonic endoscope body is inserted, from the distal end side of the ultrasonic endoscope, into a cylinder made by stacking the backing material 38, the boards 33, the piezoelectric devices 36, the acoustic matching layer 34, and the acoustic lens 35.

[0034] Then, as shown in Fig. 6, the circuit boards 32 are fixed to the frame member 41 that is closer to the distal end of the ultrasonic endoscope. In this configuration, the outer diameter of the entire set of circuit boards 32 arranged in a ring shape is greater than the inner diameter of the frame members 41, and is smaller than the inner diameter of the ultrasonic transducer 21, i.e., is smaller than the inner diameter of the backing material 38.

[0035] Next, variations in the ultrasonic transducer and its manufacturing processes will be explained.

[0036] In this present variation example, the circuit boards 32 are not locked in the ring-shaped frame member 41, but are locked by using the members that are used for locking the circuit boards 32. This contrasts with the above embodiment.

[0037] First, as shown in Fig. 7, the cable ass'y 31 and a circuit board 73 are connected to each other, and the portion of the cable ass'y 31 closer to the circuit board 73 is surrounded by a nose piece 72. This nose piece 72 has a trench 71. Next, in a similar manner to the above embodiment, the portion of the cable ass'y 31 closer to the ultrasonic endoscope body is inserted, from the distal end side of the ultrasonic endoscope, into a cylinder made by stacking the backing material 38, the boards 33, the piezoelectric devices 36, the acoustic matching layer 34, and the acoustic lens 35.

[0038] Then, as shown in Fig. 8, locking members 81 are fitted into the trench 71, and the circuit board 73 is fixed to the frame member 41 that is closer to the distal end of the ultrasonic endoscope by using the locking members 81 as shown in Fig. 9. In this configuration, the outer diameter of the circuit board 73, which has a ring shape, is smaller than the inner diameter of the above ultrasonic transducer 21, i.e., is smaller than the inner diameter of the backing material 38, and is smaller than the inner diameter of the frame members 41. However, the circuit board 73 is fixed to the ring-shaped frame members 41 by the locking members 81 that are fitted into the trench 71.

[0039] As described above, the cable ass'y 31 is formed by grouping a plurality of cables for the transmission of electric signals via the bending section 18 and the insertion tube 19; accordingly, the sectional area of the cable ass'y 31 can be minimized. Further, the cable ass'y 31 is inserted, from the distal end side of the ultrasonic endoscope, into the inside portion of the backing

material 38 that is one of the materials stacked in a cylindrical shape, and is connected to the circuit boards 32 at the distal end side of the ultrasonic endoscope. Accordingly, the cable ass'y 31 can be thinner on the portion closer to the control section 12 than on the portion closer to the distal end of the ultrasonic endoscope. In addition, there will not be an unnecessary load on the connection point between the cable ass'y 31 and the circuit boards 32 when manufacturing the ultrasonic transducer 21.

[0040] Because the cable ass'y 31 is connected to the circuit boards 32 at a position closer to the distal end of the ultrasonic endoscope and inside the backing material 38, which is one of the materials stacked in a cylindrical shape so that bearing members can be dispensed with, the interval 102 between an acoustic axis 101 representing the direction in which the ultrasound emitted from the ultrasonic transducer 21 travel and the objective lens 24 can be shortened. Further, it is also possible to shorten rigid length of the rigid tip portion 17 that is inserted into body cavities.

[0041] Also, the cable ass'y 31 is connected to the circuit board 32 inside the backing material 38, which is one of the materials stacked in a cylindrical shape, and at the distal end side of the ultrasonic endoscope when a balloon unit 111 for covering the ultrasonic transducer 21 is attached to balloon attachment grooves 112a and 112b; accordingly, it is possible, as shown in Fig. 11, to prevent an acoustic axis 101 from being at the midpoint of the interval 113 between the balloon attachment grooves 112a and 112b, and to prevent the acoustic axis 101 from being orthogonal to the wall of the balloon unit 111 when the balloon unit 111 is in an inflated state. This configuration contributes to the reduction of multiple echoes.

[0042] In the above, the embodiments of the present invention have been explained by referring to the drawings. However, the scope of the present invention is not limited to the above embodiments, and various alterations, modifications, and the like are allowed without departing from the spirit of the present invention.

[0043] According to the present invention, a bearing structure is dispensed with, and the ultrasonic transducer and the coaxial cables are connected at the tip portion of the insertion tube of the ultrasonic endoscope. Accordingly, it is also possible to shorten the length of the rigid portion of the ultrasonic endoscope's tip portion, which is inserted into body cavities, thus realizing an ultrasonic endoscope that causes less discomfort in patients.

[0044] In addition, according to the present invention, the ultrasonic transducer and the coaxial cables are connected to each other at the tip portion of the insertion tube of the ultrasonic endoscope; accordingly, an acoustic lens for converting ultrasound can be arranged on the control section side of the tip portion of the ultrasonic endoscope, and thus it is possible to prevent the directions of the ultrasound transmitted and received from and by the acoustic lens from being orthogonal to the balloon unit. Thereby, multiple reflection caused by the balloon

unit can be reduced.

Claims

1. An ultrasonic endoscope, comprising:

an ultrasonic transducer in a cylindrical shape including a plurality of piezoelectric devices, an acoustic matching layer stacked on a principal plane on a sound emitting plane side, an acoustic lens on a plane of the acoustic matching layer opposite to a plane facing the piezoelectric devices, and a backing material stacked on another principal planes of the piezoelectric devices; an endoscopic observation and endo-therapy unit provided, for performing endoscopic image observation, at a proximal end side of the ultrasonic transducer;

a cable ass'y including a plurality of cables for transmitting signals to and from the ultrasonic transducer, wherein:

the cable ass'y is arranged in such a manner that the cable ass'y passes through an inside portion of the ultrasonic transducer and is connected to the ultrasonic transducer at a distal end side of the ultrasonic transducer.

2. The ultrasonic endoscope according to claim 1, wherein:

the ultrasonic transducer includes a ring-shaped frame member in an inside portion of the distal end side for forming the cylindrical shape; the ultrasonic endoscope further includes a ring-shaped circuit board having an outer diameter that is greater than an inner diameter of the frame member and that is smaller than an inner diameter of the ultrasonic transducer, for connecting respective cables included in the cable ass'y to the ultrasonic transducer; and the circuit board is locked in the frame member at the distal end side of the ultrasonic transducer.

3. The ultrasonic endoscope according to claim 1, wherein:

the ultrasonic transducer includes a ring-shaped frame member in an inside portion of the distal end side for forming the cylindrical shape; and the ultrasonic endoscope further comprises:

a ring-shaped circuit board having an outer diameter that is smaller than an inner diameter of the frame member, for connecting respective cables included in the cable ass'y to the ultrasonic transducer; and

a locking member for locking the circuit board in the frame member at the distal end side of the ultrasonic transducer.

4. The ultrasonic endoscope according to claim 1, 5
wherein:

the ultrasonic endoscope further comprises a
balloon unit for covering the ultrasonic transduc- 10
er; and
the balloon unit or the acoustic lens is arranged
in such a manner that the acoustic axis of ultra-
sound emitted from the acoustic lens and the
balloon unit are not orthogonal to each other. 15

5. The ultrasonic endoscope according to claim 2,
wherein:

the ultrasonic endoscope further comprises a
balloon unit for covering the ultrasonic transduc- 20
er; and
the balloon unit or the acoustic lens is arranged
in such a manner that the acoustic axis of ultra-
sound emitted from the acoustic lens and the
balloon unit are not orthogonal to each other. 25

6. The ultrasonic endoscope according to claim 3,
wherein:


the ultrasonic endoscope further comprises a 30
balloon unit for covering the ultrasonic transduc-
er; and
the balloon unit or the acoustic lens is arranged
in such a manner that the acoustic axis of ultra- 35
sound emitted from the acoustic lens and the
balloon unit are not orthogonal to each other.

40

45

50

55



F I G. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5



F I G. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP2005/018317

A. CLASSIFICATION OF SUBJECT MATTER A61B8/12 (2006.01)		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols) A61B8/12 (2006.01)		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Jitsuyo Shinan Koho 1922-1996 Jitsuyo Shinan Toroku Koho 1996-2005 Kokai Jitsuyo Shinan Koho 1971-2005 Toroku Jitsuyo Shinan Koho 1994-2005		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y	JP 2004-298240 A (Olympus Corp.), 28 October, 2004 (28.10.04), Full text; all drawings (Family: none)	1 2, 3
Y	JP 10-192281 A (Endosonics Corp.), 28 July, 1998 (28.07.98), Full text; all drawings & US 5857974 A & EP 0853919 A2	2, 3
A	JP 2003-33353 A (Olympus Optical Co., Ltd.), 04 February, 2003 (04.02.03), Full text; all drawings (Family: none)	1-3
☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 08 December, 2005 (08.12.05)		Date of mailing of the international search report 20 December, 2005 (20.12.05)
Name and mailing address of the ISA/ Japanese Patent Office		Authorized officer
Facsimile No.		Telephone No.

Form PCT/ISA/210 (second sheet) (April 2005)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP2005/018317

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:

2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:

3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

The matter common to the inventions of claim 1-6 is the one stated in claim 1. However, the international search has revealed that the above constitution is not novel since it is disclosed in document JP 2004-298240 A (Olympus Corp.), 28 October, 2004 (28.10.04), the full text, all the drawings.

Consequently, the constitution cannot be considered as a special technical feature within the meaning of PCT Rule 13.2, second sentence.

Therefore, the inventions of claims 1-3 and the inventions of claims 4-6 obviously do not satisfy the requirement of unity of invention.

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:

4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.: 1-3

Remark on Protest
the

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, payment of a protest fee..
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.

Form PCT/ISA/210 (continuation of first sheet (2)) (April 2005)

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JP 2001314406 A [0004]
- JP 2116358 A [0004]

专利名称(译)	超声波内窥镜		
公开(公告)号	EP1813195A1	公开(公告)日	2007-08-01
申请号	EP2005790499	申请日	2005-10-04
[标]申请(专利权)人(译)	奥林巴斯株式会社		
申请(专利权)人(译)	OLYMPUS CORPORATION		
当前申请(专利权)人(译)	OLYMPUS CORPORATION		
发明人	IMAHASHI, TAKUYA OLYMPUS MEDICAL SYSTEMS CORP. MIZUNUMA, AKIKO OLYMPUS MEDICAL SYSTEMS CORP. SAWADA, YUKIHIKO OLYMPUS MEDICAL SYSTEMS CORP. WAKABAYASHI, KATSUHIRO OLYMPUS MEDICAL SYSTEMS CORP. SATO, SUNAO OLYMPUS MEDICAL SYSTEMS CORP.		
IPC分类号	A61B8/12		
CPC分类号	A61B8/12 A61B8/445 A61B8/4483 B06B1/0633		
优先权	2004325248 2004-11-09 JP		
其他公开文献	EP1813195B1 EP1813195A4		
外部链接	Espacenet		

摘要(译)

本发明提供一种超声波内窥镜，包括：包括多个压电装置的圆柱形超声波换能器，堆叠在发声平面侧的主平面上的声学匹配层，声学匹配平面上的声学透镜与面对压电器件的平面相对的层，和堆叠在压电器件的另一主面上的背衬材料；内窥镜观察和/或治疗单元，用于在超声换能器的近端侧进行内窥镜图像观察；电缆组件包括多个电缆，用于向超声换能器发送信号和从超声换能器发送信号。在上述结构中，电缆组件以电缆组件穿过超声波换能器的内部的方式布置，并且在超声波换能器的远端侧连接到超声波换能器。因此，提供了一种超声波内窥镜，其具有超声波换能器，其中超声波换能器和同轴电缆即使在热负荷或机械负荷下也不会断开。




FIG. 4