



(11)

EP 2 995 943 A1

(12)

EUROPEAN PATENT APPLICATION
published in accordance with Art. 153(4) EPC

(43) Date of publication:
16.03.2016 Bulletin 2016/11

(51) Int Cl.:
G01N 29/24 (2006.01) A61B 8/00 (2006.01)

(21) Application number: **14794112.4**

(86) International application number:
PCT/KR2014/002386

(22) Date of filing: **21.03.2014**

(87) International publication number:
WO 2014/181961 (13.11.2014 Gazette 2014/46)

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME

(71) Applicant: **Humanscan Co., Ltd.**
Ansan-si, Gyeonggi-do 425-836 (KR)

(72) Inventor: **PARK, Wonseop**
Seoul 152-797 (KR)


(30) Priority: **09.05.2013 KR 20130052553**

(74) Representative: **TBK**
Bavariaring 4-6
80336 München (DE)

(54) **DETACHABLY JOINED ULTRASONIC PROBE DEVICE**

(57) The present invention relates to a detachably joined ultrasonic probe device, including modular ultrasonic probe and a case for detachably joining with the modular ultrasonic probes, which enables the user to select a suitable ultrasonic probe according to desired performance and diagnosis frequency region. The device according to the present invention includes: a plurality of ultrasonic probe modules horizontally arranged in the direction of generating an ultrasonic wave; a case consisting of an outer housing with one open side for receiving and enclosing the plurality of ultrasonic probe modules, and a separation housing provided between the plurality of ultrasonic probe modules for separating the ultrasonic modules from one another, so as to detachably join with the ultrasonic modules; and a control module installed in the case for controlling the plurality of ultrasonic probe modules.

FIG1.



EP 2 995 943 A1

Description**[Disclosure]****[Technical Field]****[Technical Problem]**

[0001] The present invention relates to an ultrasonic probe, and more particularly, a detachably joined ultrasonic probe device in which probes are modularized and various types of the probes are detachably joined and used to one ultrasonic probe apparatus

5 **[0009]** Therefore, in a purpose of the present invention, an embodiment includes a modular ultrasonic probe and a case detachably coupled with the modular ultrasonic probe and provides a detachably joined ultrasonic probe device in which a user selects and uses an appropriate
10 ultrasonic probe according to a performance and diagnosis frequency range which a user desires.

[Background Art]**[Technical Solution]**

[0002] An ultrasonic wave is an acoustic wave having a frequency above the range of human audibility, and a sound wave having a frequency which is between about 20 kHz and 100 kHz.

[0003] Ultrasonic waves are used for inspecting inner parts of a human body or animal or for measuring, in a non-destructive manner, the thicknesses or inside combinations of solid matters such as a metal or a plastic. In these cases, ultrasonic waves are implemented in the form of a probe (hereinafter, referred to as "an ultrasonic probe") for easy handling by users.

15 **[0010]** To embody the above, one embodiment of the present invention provides a detachably joined ultrasonic probe device including a plurality of ultrasonic probe modules horizontally arranged in a direction ultrasonic wave generation, a case with an open portion in one side
20 accommodating the plurality of ultrasonic probe modules through the open portion, an outer housing configured to enclose an exterior of the plurality of ultrasonic probe modules, and having a separation housing provided between the plurality of ultrasonic probe modules to separate each of the plurality of ultrasonic probe modules and
25 configured to be detachably coupled with the ultrasonic probe modules, and a control module installed in the case and configured to control the plurality of ultrasonic probe modules.

[0004] This ultrasonic probe includes a piezoelectric ceramic to interchangeably convert an electrical signal to an acoustic signal by vibration of a piezoelectric material, an acoustic matching layer configured to decrease an acoustic impedance difference between the piezoelectric ceramic and an object so that ultrasonic waves generated in the piezoelectric ceramic can be fully delivered to the object, and a lens layer to focus ultrasonic waves propagating in a forward direction of the piezoelectric ceramic at a certain position, and a rear-side block to exclude ultrasonic waves propagating in a rearward direction of a piezoelectric layer to prevent image distortion.

30 **[0011]** In the detachably joined ultrasonic probe device according to the present invention, the ultrasonic probe module may be a linear array ultrasonic probe module in which ultrasonic waves propagate in a fixed direction or a phased array ultrasonic probe module in which the ultrasonic waves are steered and proceed in propagating
35 according to a propagation direction and a depth.

[0005] Ultrasonic probes formed as these configurations have been widely used in medical field. An ultrasonic diagnosis apparatus using an ultrasonic probe applies ultrasonic waves to an organism, converts reflected ultrasonic waves to electrical signals, transmits the electrical signals to an image processing unit, and generates an image through the signals received by the image processing unit.

[0012] In the detachably joined ultrasonic probe device according to the present invention, the control module may be electrically connected to the ultrasonic probe module to operate at least one of the linear array ultrasonic probe module and the phased array ultrasonic probe module.
40

[0006] Through the above-described process, the ultrasonic probes have been advantageously used for detecting a foreign material in an organism, measuring the degree of injury, observing a tumor, and observing a fetus.

[0013] In the detachably joined ultrasonic probe device according to the present invention, the case may accommodate the pair of phased array ultrasonic probe modules, and the linear array ultrasonic probe module disposed between the pair of phased array ultrasonic probe modules. The control module may operate the pair of the phased array ultrasonic probe module, and the linear array ultrasonic probe module to generate three dimensional image data.
45

[0007] Since ultrasonic waves have various frequency areas, in ultrasonic diagnosis using ultrasonic probes, the range of diagnosis is limited based on the frequency areas.

[0014] In the detachably joined ultrasonic probe device according to the present invention, the ultrasonic probe device module may include a rear-side block, a piezoelectric ceramic formed on top of the rear-side block, an acoustic matching layer formed on top of the piezoelectric ceramic, an acoustic lens formed on top of the acoustic matching layer, a flexible printed circuit board disposed
50

[0008] Therefore, since an appropriate probe is used for a diagnosis desired by a user, there are inconveniences in that different probes should be used according to intended use.

55

between the rear-side block and the piezoelectric ceramic, and a module case surrounding the rear-side block, the piezoelectric ceramic, the acoustic matching layer, the acoustic lens, and an exterior of the flexible printed circuit board excluding an upper portion of the acoustic lens, wherein the flexible printed circuit board is connected to the control module and the control module r controls the ultrasonic probe module.

[0015] In the detachably joined ultrasonic probe device according to the present invention, the ultrasonic probe module may further include a ground plate formed between the acoustic matching layer and the piezoelectric ceramic.

[Advantageous Effects]

[0016] A detachably joined ultrasonic probe device according to the present invention includes a modular ultrasonic probe and a case to accommodate the modular ultrasonic probe, which allows a user to select and use an appropriate ultrasonic probe based on a performance and diagnosis frequency range which a user desires so that the user uses probes of various types in one ultrasonic probe device without needing a plurality of ultrasonic probe devices.

[Description of Drawings]

[0017]

FIG. 1 is a view illustrating a configuration of a plurality of ultrasonic probe modules coupled with a case according to an embodiment of the present invention.

FIG. 2 is a view illustrating a detachably joined ultrasonic probe device according to the embodiment of the present invention.

FIG. 3 is a block diagram for describing the detachably joined ultrasonic probe device according to the embodiment of the present invention.

FIG. 4 is a view illustrating an ultrasonic probe module excluding a module case according to the embodiment of the present invention.

FIG. 5 is a view illustrating an ultrasonic probe module except a module case according to a second embodiment of the present invention.

[Modes of the Invention]

[0018] In the following description, only the parts necessary to understand an exemplary embodiment of the present invention will be described, the omission of descriptions of other parts is not intended to obscure the spirit of the present invention.

[0019] It should be understood that the terms used in the specification and claims set forth below are not to be construed as limited to typical or dictionary meanings, but were simply interpreted by the inventor as terms ap-

propriately defining and explaining the invention properly on the basis of the principle that can be interpreted based on the meanings and concepts corresponding to technical aspects of the present invention. Therefore, the configurations shown in the embodiments and drawings set forth herein are merely preferable embodiments of the present invention, because they are representative of all of the technical features of the present invention, and not intended to limit the scope of the present application. In the present application it should be understood that that equivalents and modifications may be made thereto.

[0020] Hereinafter, a detachably joined ultrasonic probe device according to the present invention will be described in detail with reference to the accompanying drawings.

[0021] An ultrasonic probe is implemented in a probe shape to easily handle ultrasonic waves for inspecting inner parts of a human body or animal or for measuring, in a non-destructive manner, the thickness or inside combinations of solid matters such as a metal or a plastic.

[0022] In an ultrasonic probe, ultrasonic waves may be generated with a piezoelectric ceramic in a configuration of the ultrasonic probe, a rear-side block may absorb the ultrasonic waves which propagate toward the rear-side block, the ultrasonic waves which propagate toward an acoustic matching layer may be transferred to an object to be examined through the acoustic matching layer and an acoustic lens. This description will be described below.

[0023] FIG. 1 is a view illustrating a configuration of a plurality of ultrasonic probe modules coupled with a case according to one embodiment of the present invention. FIG. 2 is a view illustrating the detachably joined ultrasonic probe device according to one embodiment of the present invention. FIG. 3 is a block diagram for describing the detachably joined ultrasonic probe device according to one embodiment of the present invention.

[0024] Referring to FIGS. 1 to 3, a detachably joined ultrasonic probe device 100 according to the embodiment of the present invention includes a plurality of ultrasonic probe modules 10, a case 20 and a control module 30.

[0025] The ultrasonic probe modules 10 are modular ultrasonic probes which can be detachably coupled through open portion 22 of the case 20. That is, the ultrasonic probe modules 10 are formed for the ultrasonic probe to be accommodated and used in receiving portions formed inside the case 20 through the open portion 22 of the case 20.

[0026] The detachably joined ultrasonic probe device 100 according to one embodiment of the present invention includes the plurality of ultrasonic probe modules 10. The plurality of ultrasonic probe modules 10 is arranged in a horizontal direction with respect to a direction in which ultrasonic waves are generated and are coupled to be accommodated in the receiving portions through the open portion 22 of the case 20. The ultrasonic probe module 10 accommodated in the case 20 may be a linear array ultrasonic probe module 40 or a phased array ul-

trasonic probe module 50, descriptions which relate to the above modules will be described below.

[0027] The case 20 has open portion 22 formed in one side thereof, accommodates the plurality of ultrasonic probe modules 10 through the open portion 22, and includes an outer housing 24 and a separation housing 26.

[0028] The outer housing 24 encloses the exterior of the plurality of ultrasonic probe modules 10 accommodated in the open portion 22. That is, the outer housing 24 protects the plurality of ultrasonic probe modules 10 from external shocks by enclosing the exterior of the plurality of ultrasonic probe modules 10 accommodated inside the case 20.

[0029] The separation housing 26 is disposed between the plurality of ultrasonic probe modules 10 to separate each of the ultrasonic probe modules 10. That is, the separation housing 26 serves a partition role to divide the inside of the case 20 into a plurality of open portions 22, separates each of the ultrasonic probe modules 10 so that the ultrasonic probe modules 10 do not come in contact with each other and are not affected by vibrations of each other.

[0030] Materials of the case 20 may be plastic materials such as polyethylene (PE), polypropylene (PP), or polyethylene terephthalate (PET), but an aspect of the present invention is not limited thereto, and a material having a lightweight, an excellent durability, and non-conductivity may be used.

[0031] A control module 30 is installed inside the case 20 to control the plurality of ultrasonic probe modules 10. That is, the control module 30 may be electrically connected to the plurality of ultrasonic probe modules 10 which are coupled with the open portion 22 of the case 20 to operate or halt each of the ultrasonic probe modules 10.

[0032] The detachably joined ultrasonic probe device 100 according to one embodiment of the present invention may accommodate in the case 20 a pair of the phased array ultrasonic probe modules 50, and the linear array ultrasonic probe module 40 disposed between the pair of the phased array ultrasonic probe modules 50. The control module 30 is electrically connected to the pair of the phased array ultrasonic probe modules 50 and the linear array ultrasonic probe module 40 and controls each operation thereof. For example, when a user desire to use only the linear array ultrasonic probe module 40, the control module 30 halts the pair of phased array ultrasonic probe modules 50 and operates only the linear array ultrasonic probe module 40 to generate ultrasonic waves.

[0033] As described above, the ultrasonic probe module 10 according to the embodiment of the present invention may be a linear array ultrasonic probe module 40 or a phased array ultrasonic probe module 50. In connection with the above, the description made with reference to FIG. 4 is as follows.

[0034] FIG. 4 is a view illustrating the ultrasonic probe module excluding a module case according to the em-

bodiment of the present invention.

[0035] Referring to FIG. 4, the ultrasonic probe module 10 according to one embodiment of the present invention includes a rear-side block 12, a piezoelectric ceramic 14, an acoustic matching layer 16, an acoustic lens 18, a flexible circuit board 13, and the module case.

[0036] The rear-side block 12 serves to absorb ultrasonic waves among ultrasonic waves which is generated in the piezoelectric ceramic 14 and is propagating toward the rear-side block 12. An acoustic characteristic of the ultrasonic probe module 10 may be controlled through the rear-side block 12.

[0037] The piezoelectric ceramic 14 is formed on top of the rear-side block 10, converts an electrical signal into an acoustic signal to transmit it to air, and changes an ultrasonic wave reflected and returned in air back into an electrical signal again to deliver it to the device.

[0038] A ceramic material such as lead-zirconate titanate (PZT) or a single crystal material such as lead magnesium niobate-lead titanate (PMN-PT) may be used as a material of the piezoelectric ceramic 14.

[0039] The acoustic matching layer 16 may be formed on top of the piezoelectric ceramic 14, that is, on an electrode of a transceiver surface of the piezoelectric ceramic 14, to increase a reflection rate and efficiency of an ultrasonic wave. Further, the acoustic matching layer 16 may be formed to have one or more layer so as to increase the reflection rate and efficiency of an ultrasonic wave.

[0040] The acoustic lens 18 is formed on top of the acoustic matching layer 16, focuses and applies an ultrasonic wave transmitted to the object to be examined so as to increase a resolution of an ultrasonic image.

[0041] As a material of the acoustic lens 18, for example, a silicone similar to living tissue may be used.

[0042] The flexible circuit board 13 is formed between the rear-side block 12 and the piezoelectric ceramic 14 and is electrically connected to the piezoelectric ceramic 30 and the rear-side block 10. That is, interconnection patterns formed in the flexible circuit board 13 are electrically connected to electrodes formed in a rear surface of the piezoelectric ceramic 14, for example, signal electrodes, ground electrodes, and the rear-side block 12.

[0043] Furthermore, since the flexible circuit board 13 is electrically connected to the control module 30, the control module 30 may control the ultrasonic probe module 10.

[0044] The flexible circuit board 13 is electrically connected to the electrodes of the piezoelectric ceramic 14, and grounded to the rear-side block 10, and a tape circuit board of a polyimide material in which interconnection patterns are formed in the front surface may be used. Further, according to need, a tape circuit board which has both sides in which interconnection patterns are formed may be used as the flexible circuit board 13.

[0045] Since the module case encloses the exterior of the rear-side block 12, the piezoelectric ceramic 14, the acoustic matching layer 16, the acoustic lens 18 and the

flexible circuit board 13 excluding the top of the acoustic lens 18, the module case protects the ultrasonic probe module 10 excluding the top of the acoustic lens 18 from external shocks.

[0046] As described above, the ultrasonic probe module 10 according to one embodiment of the present invention may be one of a linear array ultrasonic probe module 40 and a phased array ultrasonic probe module 50.

[0047] The linear array ultrasonic probe module 40 may include the piezoelectric ceramic 14 in which the ultrasonic waves propagate in a fixed direction. Here, the piezoelectric ceramic 14 is divided into a plurality of piezoelectric devices. The linear array ultrasonic probe module 40 may be used on superficial organs such as the breast, the thyroid gland, the musculoskeletal system and the like.

[0048] The phased array ultrasonic probe module 50 may steerably generate ultrasonic waves according to a propagation direction and a depth. That is, the piezoelectric ceramic 14 of the phased array ultrasonic probe module 50 may include a plurality of piezoelectric devices and each of the piezoelectric devices may generate and propagate acoustic pulses which have phase differences. In other words, the phased array ultrasonic probe module 50 may generate ultrasonic waves having phase differences by arranging every piezoelectric device in phase and steering a propagation direction of the ultrasonic waves to obtain an image. An organ such as the heart between the ribs may be tested through scanning using the phased array ultrasonic probe 90.

[0049] As described above, the detachably joined ultrasonic probe device 100 according to the embodiment of the present invention may accommodate the pair of phased array ultrasonic probe modules 50 in the case 20 and the linear array ultrasonic probe module 40 between the pair of phased array ultrasonic probe modules 50. The control module 30 may be electrically connected to and control the pair of the phased array ultrasonic probe modules 50 and the linear array ultrasonic probe module 40, respectively.

[0050] When the control module 30 operates the linear array ultrasonic probe module 40 to generate ultrasonic waves, the ultrasonic waves may be used to diagnose superficial organs such as the breast, the thyroid gland, the musculoskeletal system and the like.

[0051] When the control module 30 operates both or one of the pair of the phased array ultrasonic probe modules 50 to generate ultrasonic waves, the ultrasonic waves may be used to diagnose an organ such as the heart and/or the like through scanning. When both of the pair of phased array ultrasonic probe modules 50 are operated, ultrasonic waves may be generated to have a lower frequency than one of the pair thereof.

[0052] When the control module 30 simultaneously operates the pair of phased array ultrasonic probe modules 50 and the linear array ultrasonic probe module 40 to generate ultrasonic waves, the detachably joined ultra-

sonic probe device 100 according to the embodiment of the present invention may arrange each of the piezoelectric ceramics 14 in the form of a matrix array and generate a three dimensional image data.

[0053] As described above, the detachably joined ultrasonic probe device 100 according to one embodiment of the present invention may detachably couple the ultrasonic probe module 10 with the case 20 and use the ultrasonic probe module 10 having an appropriate diagnosis range and performance which a user desires.

[0054] As shown in FIG. 5, an ultrasonic probe module 10 according to a second embodiment of the present invention may further include a ground plate 15.

[0055] Here, FIG. 5 is a view illustrating an ultrasonic probe module excluding a module case according to the second embodiment of the present invention.

[0056] Referring to FIG. 5, since an ultrasonic probe module 60 according to the second embodiment of the present invention may have the same configuration comparatively as the ultrasonic probe module 10 in FIG. 4 except that a ground plate 15 is further provided, the following description will be focused on a structure in which the ground plate 15 is formed.

[0057] The ground plate 15 is formed between an acoustic matching layer 16 and a piezoelectric ceramic 14, and both end portions thereof are in contact with interconnection patterns of a flexible circuit board 13. That is, the ground plate 15 is in contact with the ground patterns of interconnection patterns in the flexible circuit board 13.

[0058] Since the ground plate 15 is included, the ultrasonic probe module 60 according to the second embodiment of the present invention may improve an acoustic characteristic.

[0059] On the other hand, the embodiments of the invention disclosed in the specification and drawings are merely presented as specific example for clarity and are not intended to limit the scope of the invention. It will be apparent to those of ordinary skill in the art that other modifications based on the technical concept of the present invention, in addition to the embodiments disclosed herein, can be carried out.

Claims

1. A detachably joined ultrasonic probe device comprising:

a plurality of ultrasonic probe modules horizontally arranged in a direction of ultrasonic wave generation;
a case configured to accommodate the plurality of ultrasonic probe modules through an open portion formed in one side thereof and detachably couple the ultrasonic probe modules, the case including an outer housing configured to enclose an exterior of the plurality of ultrasonic

- probe modules and a separation housing provided between the plurality of ultrasonic probe modules to separate the plurality of ultrasonic probe modules from each other; and
a control module installed in the case and configured to control the plurality of ultrasonic probe modules. 5
2. The device of claim 1, wherein the ultrasonic probe module is a linear array ultrasonic probe module in which ultrasonic wave propagates in a fixed direction or a phased array ultrasonic probe module in which the ultrasonic wave is steerably propagates according to a propagation direction and a depth. 10 15
3. The device of claim 2, wherein the control module is electrically connected to the ultrasonic probe module to operate at least one of the linear array ultrasonic probe module and the phased array ultrasonic probe module. 20
4. The device of claim 3, wherein the case accommodates the pair of phased array ultrasonic probe modules, and the linear array ultrasonic probe module disposed between the pair of the phased array ultrasonic probe modules, and wherein the control module operates the pair of phased array ultrasonic probe modules, and the linear array ultrasonic probe module to generate three dimensional image data. 25 30
5. The device of claim 1, wherein the ultrasonic probe module includes:
- a rear-side block;
 - a piezoelectric ceramic formed on top of the rear-side block; 35
 - an acoustic matching layer formed on top of the piezoelectric ceramic;
 - an acoustic lens formed on top of the acoustic matching layer; 40
 - a flexible printed circuit board formed between the rear-side block and the piezoelectric ceramic; and
 - a module case configured to enclose the rear-side block, the piezoelectric ceramic, the acoustic matching layer, the acoustic lens, and an exterior of the flexible printed circuit board excluding an upper portion of the acoustic lens, wherein the flexible printed circuit board is connected to the control module and the control module controls the ultrasonic probe module. 45 50
6. The probe of claim 5, wherein the ultrasonic probe module further includes a ground plate formed between the acoustic matching layer and the piezoelectric ceramic. 55

FIG1.




FIG2.




FIG3.




FIG4.





FIG5.



INTERNATIONAL SEARCH REPORT

International application No.

PCT/KR2014/002386

A. CLASSIFICATION OF SUBJECT MATTER

G01N 29/24(2006.01)i; A61B 8/00(2006.01)i

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

G01N 29/24; A61B 8/12; A61B 8/14; A61B 3/00; A61B 8/00

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean Utility models and applications for Utility models: IPC as above

Japanese Utility models and applications for Utility models: IPC as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKOMPASS (KIPO internal) & Keywords: linear, phased, linear, phase, ultrasonic waves, ultrasound, probe, and transducer

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2003-0055337 A1 (LIN, Gregory Sharat) 20 May 2003 See paragraphs 12-36 and figures 1A-5B.	1
Y		2-6
Y	US 6045508 A (HOSSACK et al.) 04 April 2000 See column 3, line 55 - column 7, line 30 and claim 28.	2-4
Y	US 5976090 A (HANAFY et al.) 02 November 1999 See column 9, line 42 - column 12, line 65 and figures 8, 12, 18.	5-6
A	US 6059728 A (RITTER, Jonh Alan) 09 May 2000 See column 3, line 41 - column 7, line 35 and figures 1-5.	1-6
A	KR 10-2010-0047393 A (SAMSUNG MEDISON CO.,LTD.) 10 May 2010 See paragraphs 18-59 and figures 1-8.	1-6

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

25 JUNE 2014 (25.06.2014)

Date of mailing of the international search report

26 JUNE 2014 (26.06.2014)

Name and mailing address of the ISA/KR



Korean Intellectual Property Office
Government Complex-Daejeon, 189 Seonsa-ro, Daejeon 302-701,
Republic of Korea

Facsimile No. 82-42-472-7140

Authorized officer

Telephone No.

EP 2 995 943 A1

INTERNATIONAL SEARCH REPORT Information on patent family members

International application No.

PCT/KR2014/002386

Patent document cited in search report	Publication date	Patent family member	Publication date
US 2003-0055337 A1	20/03/2003	US 6540683 B1	01/04/2003
US 06045508 A	04/04/2000	US 6171248 B1	09/01/2001
		US 6171248 B2	09/01/2001
		WO 1998-38486 A2	03/09/1998
US 05976090 A	02/11/1999	EP 0641606 A2	08/03/1995
		EP 0641606 A3	12/06/1996
		EP 0641606 B1	02/02/2000
		JP 07-107595 A	21/04/1995
		JP 3478874 B2	15/12/2003
		US 05415175 A	16/05/1995
		US 05438998 A	08/08/1995
		US 05582177 A	10/12/1996
		US 05743855 A	28/04/1998
		US 05792058 A	11/08/1998
US 06059728 A	09/05/2000	NONE	
KR 10-2010-0047393 A	10/05/2010	KR 10-1023658 B1	25/03/2011

Form PCT/ISA/210 (patent family annex) (July 2009)

专利名称(译)	可拆卸地连接超声波探头装置		
公开(公告)号	EP2995943A4	公开(公告)日	2016-12-28
申请号	EP2014794112	申请日	2014-03-21
申请(专利权)人(译)	HUMANSCAN CO. , LTD.		
当前申请(专利权)人(译)	HUMANSCAN CO. , LTD.		
[标]发明人	PARK WONSEOP		
发明人	PARK, WONSEOP		
IPC分类号	G01N29/24 A61B8/00 G10K11/00		
CPC分类号	A61B8/4411 A61B8/4444 A61B8/4455 A61B8/4477 A61B8/4488 A61B8/4494 G01N29/226 G01N2291/02475 G01N2291/106 G10K11/004 G10K11/34		
代理机构(译)	TBK		
优先权	1020130052553 2013-05-09 KR		
其他公开文献	EP2995943A1 EP2995943B1		
外部链接	Espacenet		

摘要(译)

可拆卸地连接的超声波探头装置本发明涉及一种可拆卸地连接的超声波探头装置，包括模块化超声波探头和用于与模块化超声波探头可拆卸地连接的壳体，使用户能够根据所需的性能和诊断频率区域选择合适的超声波探头。根据本发明的装置包括：多个超声波探头模块，其在产生超声波的方向上水平布置；壳体包括：外壳，具有一个开口侧，用于容纳和封闭多个超声波探头模块；以及分离壳体，设置在多个超声波探头模块之间，用于将超声波模块彼此分离，以便可拆卸地与所述超声波探头模块连接。超声波模块；控制模块安装在壳体中，用于控制多个超声波探头模块。