



US010401493B2

(12) **United States Patent**
Call et al.

(10) **Patent No.: US 10,401,493 B2**
(45) **Date of Patent: Sep. 3, 2019**

(54) **NETWORK-BASED ULTRASOUND IMAGING SYSTEM**

(51) **Int. Cl.**
A61B 8/14 (2006.01)
G01S 15/89 (2006.01)

(71) Applicant: **MAUI IMAGING, INC.**, San Jose, CA (US)

(Continued)

(72) Inventors: **Josef R. Call**, Campbell, CA (US);
Henry A. Davis, Ash Fork, AZ (US);
David M. Smith, Lodi, CA (US);
David J. Specht, San Jose, CA (US);
Viet Nam Le, San Jose, CA (US);
Lang J. McHardy, San Jose, CA (US);
Joseph James Digiovanni, II, Los Altos Hills, CA (US); **Nathan W. Osborn**, Palo Alto, CA (US); **Bruce R. Ritzi**, Sunnyvale, CA (US)

(52) **U.S. Cl.**
CPC **G01S 15/8929** (2013.01); **A61B 8/14** (2013.01); **A61B 8/483** (2013.01); **A61B 8/523** (2013.01);

(Continued)

(58) **Field of Classification Search**
CPC G01S 15/8929
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,174,286 A 3/1965 Erickson
3,895,381 A 7/1975 Kock
(Continued)

FOREIGN PATENT DOCUMENTS

CN 1781460 A 6/2006
CN 101116622 A 2/2008
(Continued)

(21) Appl. No.: **15/500,933**

(22) PCT Filed: **Aug. 18, 2015**

(86) PCT No.: **PCT/US2015/045703**

§ 371 (c)(1),

(2) Date: **Feb. 1, 2017**

(87) PCT Pub. No.: **WO2016/028787**

PCT Pub. Date: **Feb. 25, 2016**

(65) **Prior Publication Data**

US 2017/0219704 A1 Aug. 3, 2017

Related U.S. Application Data

(60) Provisional application No. 62/038,602, filed on Aug. 18, 2014.

OTHER PUBLICATIONS

Call et al.; U.S. Appl. No. 15/495,591 entitled "Systems and methods for improving ultrasound image quality by applying weighting factors," filed Apr. 24, 2017.

(Continued)


Primary Examiner — Chikaodili E Anyikire

(74) *Attorney, Agent, or Firm* — Shay Glenn LLP

(57) **ABSTRACT**

Systems and methods for network-based ultrasound imaging are provided, which can include a number of features. In some embodiments, an ultrasound imaging system images an object with three-dimensional unfocused pings and obtains digital sample sets from a plurality of receiver elements. A sub-set of the digital sample sets can be elec-

(Continued)



tronically transferred to a remote server, where the sub-set can be beamformed to produce a series of two-dimensional image frames. A video stream made up of the series of two-dimensional images frames can then be transferred from the remote server to a display device.

16 Claims, 9 Drawing Sheets

(51) Int. Cl.

A61B 8/08 (2006.01)

A61B 8/00 (2006.01)

G01S 7/52 (2006.01)

G06F 3/14 (2006.01)

(52) U.S. Cl.

CPC *A61B 8/5207* (2013.01); *A61B 8/565* (2013.01); *G01S 7/52053* (2013.01); *G01S 15/89* (2013.01); *G01S 15/8925* (2013.01); *G01S 15/8993* (2013.01); *G06F 3/14* (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

3,974,692 A	8/1976	Hassler	5,442,462 A	8/1995	Guissin
4,055,988 A	11/1977	Dutton	5,454,372 A	10/1995	Banjanin et al.
4,072,922 A	2/1978	Taner et al.	5,503,152 A	4/1996	Oakley et al.
4,097,835 A	6/1978	Green	5,515,853 A	5/1996	Smith et al.
4,105,018 A	8/1978	Greenleaf et al.	5,515,856 A	5/1996	Olstad et al.
4,180,792 A	12/1979	Lederman et al.	5,522,393 A	6/1996	Phillips
4,259,733 A	3/1981	Taner et al.	5,526,815 A	6/1996	Granz et al.
4,265,126 A	5/1981	Papadofrangakis et al.	5,544,659 A	8/1996	Banjanin
4,271,842 A	6/1981	Specht et al.	5,558,092 A	9/1996	Unger
4,325,257 A	4/1982	Kino et al.	5,564,423 A	10/1996	Mele et al.
4,327,738 A	5/1982	Green et al.	5,568,812 A	10/1996	Murashita et al.
4,333,474 A	6/1982	Nigam	5,570,691 A	11/1996	Wright et al.
4,339,952 A	7/1982	Foster	5,581,517 A	12/1996	Gee et al.
4,452,084 A	6/1984	Taenzer	5,625,149 A	4/1997	Gururaja et al.
4,501,279 A	2/1985	Seo	5,628,320 A	5/1997	Teo
4,511,998 A	4/1985	Kanda et al.	5,673,697 A	10/1997	Bryan et al.
4,539,847 A	9/1985	Paap	5,675,550 A	10/1997	Ekhaus
4,566,459 A	1/1986	Umemura et al.	5,720,291 A	2/1998	Schwartz
4,567,768 A	2/1986	Satoh et al.	5,720,708 A	2/1998	Lu et al.
4,604,697 A	8/1986	Luthra et al.	5,744,898 A	4/1998	Smith et al.
4,662,222 A	5/1987	Johnson	5,769,079 A	6/1998	Hossack
4,669,482 A	6/1987	Ophir	5,784,334 A	7/1998	Sena et al.
4,682,497 A	7/1987	Sasaki	5,785,654 A	7/1998	Iinuma et al.
4,781,199 A	11/1988	Hirama et al.	5,795,297 A	8/1998	Daigle
4,817,434 A	4/1989	Anderson	5,797,845 A	8/1998	Barabash et al.
4,831,601 A	5/1989	Breimesser et al.	5,798,459 A	8/1998	Ohba et al.
4,893,284 A	1/1990	Magrane	5,820,561 A	10/1998	Olstad et al.
4,893,628 A	1/1990	Angelsen	5,838,564 A	11/1998	Bahorich et al.
5,050,588 A	9/1991	Grey et al.	5,850,622 A	12/1998	Vassiliou et al.
5,141,738 A	8/1992	Rasor et al.	5,862,100 A	1/1999	VerWest
5,161,536 A	11/1992	Vilkomerson et al.	5,870,691 A	2/1999	Partyka et al.
5,197,475 A	3/1993	Antich et al.	5,876,342 A	3/1999	Chen et al.
5,226,019 A	7/1993	Bahorich	5,891,038 A	4/1999	Seyed-Bolorforosh et al.
5,230,339 A	7/1993	Charlebois	5,892,732 A	4/1999	Gersztenkorn
5,269,309 A	12/1993	Fort et al.	5,916,169 A	6/1999	Hanafy et al.
5,278,757 A	1/1994	Hocor et al.	5,919,139 A	7/1999	Lin
5,293,871 A	3/1994	Reinstein et al.	5,920,285 A	7/1999	Benjamin
5,299,576 A	4/1994	Shiba	5,930,730 A	7/1999	Marfurt et al.
5,301,674 A	4/1994	Erikson et al.	5,940,778 A	8/1999	Marfurt et al.
5,305,756 A	4/1994	Entrekin et al.	5,951,479 A	9/1999	Holm et al.
5,339,282 A	8/1994	Kuhn et al.	5,964,707 A	10/1999	Fenster et al.
5,340,510 A	8/1994	Bowen	5,969,661 A	10/1999	Benjamin
5,345,426 A	9/1994	Lipschutz	5,999,836 A	12/1999	Nelson et al.
5,349,960 A	9/1994	Gondo	6,007,499 A	12/1999	Martin et al.
5,355,888 A	10/1994	Kendall	6,013,032 A	1/2000	Savord
5,381,794 A	1/1995	Tei et al.	6,014,473 A	1/2000	Hossack et al.
5,398,216 A	3/1995	Hall et al.	6,048,315 A	4/2000	Chiao et al.
5,409,010 A	4/1995	Beach et al.	6,049,509 A	4/2000	Sonneland et al.
			6,050,943 A	4/2000	Slayton et al.
			6,056,693 A	5/2000	Haider
			6,058,074 A	5/2000	Swan et al.
			6,077,224 A	6/2000	Lang et al.
			6,092,026 A	7/2000	Bahorich et al.
			6,122,538 A	9/2000	Sliwa, Jr. et al.
			6,123,670 A	9/2000	Mo
			6,129,672 A	10/2000	Seward et al.
			6,135,960 A	10/2000	Holmberg
			6,138,075 A	10/2000	Yost
			6,148,095 A	11/2000	Prause et al.
			6,162,175 A	12/2000	Marian, Jr. et al.
			6,166,384 A	12/2000	Dentinger et al.
			6,166,853 A	12/2000	Sapia et al.
			6,193,665 B1	2/2001	Hall et al.
			6,196,739 B1	3/2001	Silverbrook
			6,200,266 B1	3/2001	Shokrollahi et al.
			6,210,335 B1	4/2001	Miller
			6,213,958 B1	4/2001	Winder
			6,221,019 B1	4/2001	Kantorovich
			6,231,511 B1	5/2001	Bae
			6,238,342 B1	5/2001	Feleppa et al.
			6,246,901 B1	6/2001	Benaron
			6,251,073 B1	6/2001	Imran et al.
			6,264,609 B1	7/2001	Herrington et al.
			6,266,551 B1	7/2001	Osadchy et al.
			6,278,949 B1	8/2001	Alam
			6,289,230 B1	9/2001	Chaiken et al.
			6,299,580 B1	10/2001	Asafusa
			6,304,684 B1	10/2001	Niczyporuk et al.
			6,309,356 B1	10/2001	Ustuner et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,324,453	B1	11/2001	Breed et al.	7,510,529	B2	3/2009	Chou et al.
6,345,539	B1	2/2002	Rawes et al.	7,514,851	B2	4/2009	Wilser et al.
6,361,500	B1	3/2002	Masters	7,549,962	B2	6/2009	Dreschel et al.
6,363,033	B1	3/2002	Cole et al.	7,574,026	B2	8/2009	Rasche et al.
6,370,480	B1	4/2002	Gupta et al.	7,625,343	B2	12/2009	Cao et al.
6,374,185	B1	4/2002	Taner et al.	7,637,869	B2	12/2009	Sudol
6,394,955	B1	5/2002	Perlitz	7,668,583	B2	2/2010	Fegert et al.
6,423,002	B1	7/2002	Hossack	7,674,228	B2	3/2010	Williams et al.
6,436,046	B1	8/2002	Napolitano et al.	7,682,311	B2	3/2010	Simopoulos et al.
6,449,821	B1	9/2002	Sudol et al.	7,699,776	B2	4/2010	Walker et al.
6,450,965	B2	9/2002	Williams et al.	7,722,541	B2	5/2010	Cai
6,468,216	B1	10/2002	Powers et al.	7,744,532	B2	6/2010	Ustuner et al.
6,471,650	B2	10/2002	Powers et al.	7,750,311	B2	7/2010	Daghighian
6,475,150	B2	11/2002	Haddad	7,785,260	B2	8/2010	Umemura et al.
6,480,790	B1	11/2002	Calvert et al.	7,787,680	B2	8/2010	Ahn et al.
6,487,502	B1	11/2002	Taner	7,806,828	B2	10/2010	Stringer
6,499,536	B1	12/2002	Ellingsen	7,819,810	B2	10/2010	Stringer et al.
6,508,768	B1	1/2003	Hall et al.	7,822,250	B2	10/2010	Yao et al.
6,508,770	B1	1/2003	Cai	7,824,337	B2	11/2010	Abe et al.
6,517,484	B1	2/2003	Wilk et al.	7,833,163	B2	11/2010	Cai
6,526,163	B1	2/2003	Halmann et al.	7,837,624	B1	11/2010	Hossack et al.
6,543,272	B1	4/2003	Vitek	7,846,097	B2	12/2010	Jones et al.
6,547,732	B2	4/2003	Jago	7,850,613	B2	12/2010	Stribling
6,551,246	B1	4/2003	Ustuner et al.	7,862,508	B2	1/2011	Davies et al.
6,565,510	B1	5/2003	Haider	7,876,945	B2	1/2011	Lötjönen
6,585,647	B1	7/2003	Winder	7,887,486	B2	2/2011	Ustuner et al.
6,604,421	B1	8/2003	Li	7,901,358	B2	3/2011	Mehi et al.
6,614,560	B1	9/2003	Silverbrook	7,914,451	B2	3/2011	Davies
6,620,101	B2	9/2003	Azzam et al.	7,919,906	B2	4/2011	Cerofolini
6,652,461	B1	11/2003	Levkovitz	7,926,350	B2	4/2011	Kröning et al.
6,668,654	B2	12/2003	Dubois et al.	7,927,280	B2	4/2011	Davidson
6,672,165	B2	1/2004	Rather et al.	7,972,271	B2	7/2011	Johnson et al.
6,681,185	B1	1/2004	Young et al.	7,984,637	B2	7/2011	Ao et al.
6,690,816	B2	2/2004	Aylward et al.	7,984,651	B2	7/2011	Randall et al.
6,692,450	B1	2/2004	Coleman	8,002,705	B1	8/2011	Napolitano et al.
6,695,778	B2	2/2004	Golland et al.	8,007,439	B2	8/2011	Specht
6,702,745	B1	3/2004	Smythe	8,057,392	B2	11/2011	Hossack et al.
6,719,693	B2	4/2004	Richard	8,057,393	B2	11/2011	Yao et al.
6,728,567	B2	4/2004	Rather et al.	8,079,263	B2	12/2011	Randall et al.
6,752,762	B1	6/2004	DeJong et al.	8,079,956	B2	12/2011	Azuma et al.
6,755,787	B2	6/2004	Hossack et al.	8,088,067	B2	1/2012	Vortman et al.
6,780,152	B2	8/2004	Ustuner et al.	8,088,068	B2	1/2012	Yao et al.
6,790,182	B2	9/2004	Eck et al.	8,088,071	B2	1/2012	Hwang et al.
6,837,853	B2	1/2005	Marian	8,105,239	B2	1/2012	Specht
6,843,770	B2	1/2005	Sumanaweera	8,135,190	B2	3/2012	Bae et al.
6,847,737	B1	1/2005	Kouri et al.	8,157,737	B2	4/2012	Zhang et al.
6,854,332	B2	2/2005	Alleyne	8,182,427	B2	5/2012	Wu et al.
6,865,140	B2	3/2005	Thomenius et al.	8,202,219	B2	6/2012	Luo et al.
6,932,767	B2	8/2005	Landry et al.	8,277,383	B2	10/2012	Specht
7,033,320	B2	4/2006	Von Behren et al.	8,279,705	B2	10/2012	Choi et al.
7,087,023	B2	8/2006	Daft et al.	8,412,307	B2	4/2013	Willis et al.
7,104,956	B1	9/2006	Christopher	8,419,642	B2	4/2013	Sandrin et al.
7,217,243	B2	5/2007	Takeuchi	8,473,239	B2	6/2013	Specht et al.
7,221,867	B2	5/2007	Silverbrook	8,478,382	B2	7/2013	Burnside et al.
7,231,072	B2	6/2007	Yamano et al.	8,532,951	B2	9/2013	Roy et al.
7,269,299	B2	9/2007	Schroeder	8,582,848	B2	11/2013	Funka-Lea et al.
7,283,652	B2	10/2007	Mendonca et al.	8,602,993	B2	12/2013	Specht et al.
7,285,094	B2	10/2007	Nohara et al.	8,627,724	B2	1/2014	Papadopoulos et al.
7,293,462	B2	11/2007	Lee et al.	8,634,615	B2	1/2014	Brabec
7,313,053	B2	12/2007	Wodnicki	8,672,846	B2	3/2014	Napolitano et al.
7,366,704	B2	4/2008	Reading et al.	8,684,936	B2	4/2014	Specht
7,402,136	B2	7/2008	Hossack et al.	9,072,495	B2	7/2015	Specht
7,410,469	B1	8/2008	Talish et al.	9,146,313	B2	9/2015	Specht et al.
7,415,880	B2	8/2008	Renzel	9,192,355	B2	11/2015	Specht et al.
7,443,765	B2	10/2008	Thomenius et al.	9,220,478	B2	12/2015	Smith et al.
7,444,875	B1	11/2008	Wu et al.	9,247,926	B2	2/2016	Smith et al.
7,447,535	B2	11/2008	Lavi	9,265,484	B2	2/2016	Brewer et al.
7,448,998	B2	11/2008	Robinson	9,282,945	B2	3/2016	Specht et al.
7,466,848	B2	12/2008	Metaxas et al.	9,339,256	B2	5/2016	Specht et al.
7,469,096	B2	12/2008	Silverbrook	9,420,994	B2	8/2016	Specht
7,474,778	B2	1/2009	Shinomura et al.	9,510,806	B2	12/2016	Smith et al.
7,481,577	B2	1/2009	Ramamurthy et al.	9,526,475	B2	12/2016	Specht et al.
7,491,171	B2	2/2009	Barthe et al.	9,572,549	B2	2/2017	Belevich et al.
7,497,828	B1	3/2009	Wilk et al.	9,582,876	B2	2/2017	Specht
7,497,830	B2	3/2009	Li	2002/0035864	A1	3/2002	Paltiel et al.
				2002/0087071	A1	7/2002	Schmitz et al.
				2002/0111568	A1	8/2002	Bukshpan
				2002/0138003	A1	9/2002	Bukshpan
				2002/0161299	A1	10/2002	Prater et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2003/0013962	A1	1/2003	Bjaerum et al.	2008/0114253	A1	5/2008	Randall et al.
2003/0028111	A1	2/2003	Vaezy et al.	2008/0114255	A1	5/2008	Schwartz et al.
2003/0040669	A1	2/2003	Grass et al.	2008/0125659	A1	5/2008	Wilser et al.
2003/0228053	A1	12/2003	Li et al.	2008/0181479	A1	7/2008	Yang et al.
2004/0015079	A1*	1/2004	Berger A61B 8/546 600/437	2008/0183075	A1	7/2008	Govari et al.
2004/0054283	A1	3/2004	Corey et al.	2008/0188747	A1	8/2008	Randall et al.
2004/0068184	A1	4/2004	Trahey et al.	2008/0188750	A1	8/2008	Randall et al.
2004/0100163	A1	5/2004	Baumgartner et al.	2008/0194957	A1	8/2008	Hector et al.
2004/0111028	A1	6/2004	Abe et al.	2008/0194958	A1	8/2008	Lee et al.
2004/0122313	A1	6/2004	Moore et al.	2008/0194959	A1	8/2008	Wang et al.
2004/0122322	A1	6/2004	Moore et al.	2008/0208061	A1	8/2008	Halmann
2004/0127793	A1	7/2004	Mendlein et al.	2008/0242996	A1	10/2008	Hall et al.
2004/0138565	A1	7/2004	Trucco	2008/0249408	A1	10/2008	Palmeri et al.
2004/0144176	A1	7/2004	Yoden	2008/0255452	A1	10/2008	Entrekin
2004/0236217	A1	11/2004	Cerwin et al.	2008/0269604	A1	10/2008	Boctor et al.
2004/0236223	A1	11/2004	Barnes et al.	2008/0269613	A1	10/2008	Summers et al.
2005/0004449	A1	1/2005	Mitschke et al.	2008/0275344	A1	11/2008	Glide-Hurst et al.
2005/0053305	A1	3/2005	Li et al.	2008/0285819	A1	11/2008	Konofagou et al.
2005/0054910	A1	3/2005	Tremblay et al.	2008/0287787	A1	11/2008	Sauer et al.
2005/0090743	A1	4/2005	Kawashima et al.	2008/0294045	A1	11/2008	Ellington et al.
2005/0090745	A1	4/2005	Steen	2008/0294050	A1	11/2008	Shinomura et al.
2005/0111846	A1	5/2005	Steinbacher et al.	2008/0294052	A1	11/2008	Wilser et al.
2005/0113689	A1	5/2005	Gritzky	2008/0306382	A1	12/2008	Guracar et al.
2005/0113694	A1	5/2005	Haugen et al.	2008/0306386	A1	12/2008	Baba et al.
2005/0124883	A1	6/2005	Hunt	2008/0319317	A1	12/2008	Kamiyama et al.
2005/0131300	A1	6/2005	Bakircioglu et al.	2009/0010459	A1	1/2009	Garbini et al.
2005/0147297	A1	7/2005	McLaughlin et al.	2009/0012393	A1	1/2009	Choi
2005/0165312	A1	7/2005	Knowles et al.	2009/0016163	A1	1/2009	Freeman et al.
2005/0203404	A1	9/2005	Freiburger	2009/0018445	A1	1/2009	Schers et al.
2005/0215883	A1	9/2005	Hundley et al.	2009/0024039	A1	1/2009	Wang et al.
2005/0240125	A1	10/2005	Makin et al.	2009/0036780	A1	2/2009	Abraham
2005/0252295	A1	11/2005	Fink et al.	2009/0043206	A1	2/2009	Towfiq et al.
2005/0281447	A1	12/2005	Moreau-Gobard et al.	2009/0048519	A1	2/2009	Hossack et al.
2005/0288588	A1	12/2005	Weber et al.	2009/0069681	A1	3/2009	Lundberg et al.
2006/0062447	A1	3/2006	Rinck et al.	2009/0069686	A1	3/2009	Daft et al.
2006/0074313	A1	4/2006	Slayton et al.	2009/0069692	A1	3/2009	Cooley et al.
2006/0074315	A1	4/2006	Liang et al.	2009/0099483	A1	4/2009	Rybyanets
2006/0074320	A1	4/2006	Yoo et al.	2009/0112095	A1	4/2009	Daigle
2006/0079759	A1	4/2006	Vaillant et al.	2009/0131797	A1	5/2009	Jeong et al.
2006/0079778	A1	4/2006	Mo et al.	2009/0143680	A1	6/2009	Yao et al.
2006/0079782	A1	4/2006	Beach et al.	2009/0148012	A1	6/2009	Altmann et al.
2006/0094962	A1	5/2006	Clark	2009/0150094	A1	6/2009	Van Velsor et al.
2006/0111634	A1	5/2006	Wu	2009/0182233	A1	7/2009	Wodnicki
2006/0122506	A1	6/2006	Davies et al.	2009/0182237	A1	7/2009	Angelsen et al.
2006/0173327	A1	8/2006	Kim	2009/0198134	A1	8/2009	Hashimoto et al.
2006/0262961	A1	11/2006	Holsing et al.	2009/0203997	A1	8/2009	Ustuner
2006/0270934	A1	11/2006	Savord et al.	2009/0208080	A1	8/2009	Grau et al.
2007/0016022	A1	1/2007	Blalock et al.	2009/0259128	A1	10/2009	Stribling
2007/0016044	A1	1/2007	Blalock et al.	2009/0264760	A1	10/2009	Lazebnik et al.
2007/0036414	A1	2/2007	Georgescu et al.	2009/0306510	A1	12/2009	Hashiba et al.
2007/0055155	A1	3/2007	Owen et al.	2009/0326379	A1	12/2009	Daigle et al.
2007/0078345	A1	4/2007	Mo et al.	2010/0010354	A1	1/2010	Skerl et al.
2007/0088213	A1	4/2007	Poland	2010/0016725	A1	1/2010	Thiele
2007/0138157	A1	6/2007	Dane et al.	2010/0063397	A1	3/2010	Wagner
2007/0161898	A1	7/2007	Hao et al.	2010/0063399	A1	3/2010	Walker et al.
2007/0161904	A1	7/2007	Urbano	2010/0069751	A1	3/2010	Hazard et al.
2007/0167752	A1	7/2007	Proulx et al.	2010/0069756	A1	3/2010	Ogasawara et al.
2007/0167824	A1	7/2007	Lee et al.	2010/0106431	A1	4/2010	Baba et al.
2007/0232914	A1	10/2007	Chen et al.	2010/0109481	A1	5/2010	Buccafusca
2007/0238985	A1	10/2007	Smith et al.	2010/0121193	A1	5/2010	Fukukita et al.
2007/0242567	A1	10/2007	Daft et al.	2010/0121196	A1	5/2010	Hwang et al.
2008/0110261	A1	5/2008	Randall et al.	2010/0130855	A1	5/2010	Lundberg et al.
2008/0110263	A1	5/2008	Klessel et al.	2010/0168566	A1	7/2010	Bercoff et al.
2008/0112265	A1	5/2008	Urbano et al.	2010/0168578	A1	7/2010	Garson, Jr. et al.
2008/0114241	A1	5/2008	Randall et al.	2010/0174194	A1	7/2010	Chiang et al.
2008/0114245	A1	5/2008	Randall et al.	2010/0191110	A1	7/2010	Insana et al.
2008/0114246	A1	5/2008	Randall et al.	2010/0217124	A1	8/2010	Cooley
2008/0114247	A1	5/2008	Urbano et al.	2010/0228126	A1	9/2010	Emery et al.
2008/0114248	A1	5/2008	Urbano et al.	2010/0240994	A1	9/2010	Zheng
2008/0114249	A1	5/2008	Randall et al.	2010/0249570	A1	9/2010	Carson et al.
2008/0114250	A1*	5/2008	Urbano G01S 7/52028 600/447	2010/0249596	A1	9/2010	Magee
2008/0114251	A1	5/2008	Weymer et al.	2010/0256488	A1	10/2010	Kim et al.
2008/0114252	A1	5/2008	Randall et al.	2010/0262013	A1	10/2010	Smith et al.
				2010/0266176	A1	10/2010	Masumoto et al.
				2010/0286525	A1	11/2010	Osumi
				2010/0286527	A1	11/2010	Cannon et al.
				2010/0310143	A1	12/2010	Rao et al.
				2010/0324418	A1	12/2010	El-Aklouk et al.
				2010/0324423	A1	12/2010	El-Aklouk et al.

(56)	References Cited			CN	102018533	A	4/2011
	U.S. PATENT DOCUMENTS			CN	102123668	A	7/2011
				EP	1949856	A1	7/2008
				EP	2058796	A2	5/2009
2010/0329521	A1	12/2010	Beymer et al.	EP	2101191	A2	9/2009
2011/0005322	A1	1/2011	Ustuner	EP	2182352	A2	5/2010
2011/0016977	A1	1/2011	Guracar	EP	2187813	A1	5/2010
2011/0021920	A1	1/2011	Shafir et al.	EP	2198785	A1	6/2010
2011/0021923	A1	1/2011	Daft et al.	EP	1757955	B1	11/2010
2011/0033098	A1	2/2011	Richter et al.	EP	2325672	A1	5/2011
2011/0044133	A1	2/2011	Tokita	EP	1462819	B1	7/2011
2011/0066030	A1	3/2011	Yao	EP	2356941	A1	8/2011
2011/0098565	A1	4/2011	Masuzawa	EP	1979739	B1	10/2011
2011/0112400	A1	5/2011	Emery et al.	EP	2385391	A2	11/2011
2011/0112404	A1	5/2011	Gourevitch	EP	2294400	B1	2/2012
2011/0125017	A1	5/2011	Ramamurthy et al.	EP	2453256	A2	5/2012
2011/0178441	A1 *	7/2011	Tyler A61N 7/00	EP	1840594	B1	6/2012
			601/2	EP	2514368	A1	10/2012
2011/0270088	A1	11/2011	Shiina	EP	1850743	B1	12/2012
2011/0301470	A1	12/2011	Sato et al.	EP	1594404	B1	9/2013
2011/0306886	A1	12/2011	Daft et al.	EP	2026280	B1	10/2013
2011/0319764	A1	12/2011	Okada et al.	FR	2851662	A1	8/2004
2012/0004545	A1	1/2012	Ziv-Ari et al.	JP	49-11189	A	1/1974
2012/0035482	A1	2/2012	Kim et al.	JP	54-44375	A	4/1979
2012/0036934	A1	2/2012	Kröning et al.	JP	55-103839	A	8/1980
2012/0085173	A1	4/2012	Papadopoulos et al.	JP	57-31848	A	2/1982
2012/0095347	A1	4/2012	Adam et al.	JP	58-223059	A	12/1983
2012/0101378	A1	4/2012	Lee	JP	59-101143	A	6/1984
2012/0114210	A1	5/2012	Kim et al.	JP	59-174151	A	10/1984
2012/0121150	A1	5/2012	Murashita	JP	60-13109	A	1/1985
2012/0137778	A1	6/2012	Kitazawa et al.	JP	60-13109	U	1/1985
2012/0141002	A1	6/2012	Urbano et al.	JP	60-68836	A	4/1985
2012/0165670	A1	6/2012	Shi et al.	JP	02501431	A	5/1990
2012/0179044	A1	7/2012	Chiang et al.	JP	03015455	A	1/1991
2012/0226201	A1	9/2012	Clark et al.	JP	03126443	A	5/1991
2012/0235998	A1	9/2012	Smith-Casem et al.	JP	04017842	A	1/1992
2012/0243763	A1	9/2012	Wen et al.	JP	04067856	A	3/1992
2012/0253194	A1	10/2012	Tamura	JP	05042138	A	2/1993
2012/0265075	A1	10/2012	Pedrizzi et al.	JP	06125908	A	5/1994
2012/0277585	A1	11/2012	Koenig et al.	JP	07051266	A	2/1995
2013/0070062	A1	3/2013	Fouras et al.	JP	070204201	A	8/1995
2013/0076207	A1	3/2013	Krohn et al.	JP	08154930	A	6/1996
2013/0079639	A1	3/2013	Hector et al.	JP	08252253	A	10/1996
2013/0083628	A1	4/2013	Qiao et al.	JP	09103429	A	4/1997
2013/0088122	A1	4/2013	Krohn et al.	JP	09201361	A	8/1997
2013/0116561	A1	5/2013	Rothberg et al.	JP	2777197	B	5/1998
2013/0131516	A1	5/2013	Katsuyama	JP	10216128	A	8/1998
2013/0144165	A1	6/2013	Ebbini et al.	JP	11089833	A	4/1999
2013/0144166	A1 *	6/2013	Specht G01S 15/8913	JP	11239578	A	9/1999
			600/441	JP	2001507794	A	6/2001
2013/0172743	A1 *	7/2013	Brewer A61B 8/486	JP	2001245884	A	9/2001
			600/440	JP	2002209894	A	7/2002
2013/0204136	A1	8/2013	Duric et al.	JP	2002253548	A	9/2002
2013/0204137	A1	8/2013	Roy et al.	JP	2002253549	A	9/2002
2013/0253325	A1	9/2013	Call et al.	JP	2004167092	A	6/2004
2013/0258805	A1	10/2013	Hansen et al.	JP	2004215987	A	8/2004
2013/0261463	A1	10/2013	Chiang et al.	JP	2004337457	A	12/2004
2014/0058266	A1	2/2014	Call et al.	JP	2004351214	A	12/2004
2014/0073921	A1	3/2014	Specht et al.	JP	2005046192	A	2/2005
2014/0086014	A1	3/2014	Kobayashi	JP	2005152187	A	6/2005
2014/0243673	A1	8/2014	Anand et al.	JP	2005523792	A	8/2005
2015/0045668	A1	2/2015	Smith et al.	JP	2005526539	A	9/2005
2015/0080727	A1	3/2015	Specht et al.	JP	2006051356	A	2/2006
2015/0172878	A1 *	6/2015	Luna H04W 4/12	JP	200661203	A	3/2006
			455/412.2	JP	2006122657	A	5/2006
2016/0095579	A1	4/2016	Smith et al.	JP	2006130313	A	5/2006
2016/0135783	A1	5/2016	Brewer et al.	JP	2007325937	A	12/2007
2016/0157833	A1	6/2016	Smith et al.	JP	2008122209	A	5/2008
2016/0256134	A1	9/2016	Specht et al.	JP	2008513763	A	5/2008
2016/0354059	A1	12/2016	Specht	JP	2008132342	A	6/2008
2017/0074982	A1	3/2017	Smith et al.	JP	2008522642	A	7/2008
2017/0079621	A1	3/2017	Specht et al.	JP	2008259541	A	10/2008
				JP	2008279274	A	11/2008
				JP	2009240667	A	10/2009
				JP	2010005375	A	1/2010
				JP	2010124842	A	6/2010
CN	101190134	A	6/2008	JP	2010526626	A	8/2010
CN	101453955	A	6/2009	KR	100715132	B	4/2007
CN	101843501	A	9/2010	KR	1020090103408	A	10/2009
	FOREIGN PATENT DOCUMENTS						

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO92/18054	A1	10/1992
WO	WO98/00719	A2	1/1998
WO	WO01/64109	A1	9/2001
WO	WO02/08459	A2	10/2002
WO	WO2005/009245	A1	2/2005
WO	WO2006/114735	A1	11/2006
WO	WO2007/127147	A2	11/2007
WO	WO2009/060182	A2	5/2009
WO	WO2010/095094	A1	8/2010
WO	WO2010/139519	A1	12/2010
WO	WO2011/004661	A1	1/2011
WO	WO2011/057252	A1	5/2011
WO	WO2011/064688	A1	6/2011
WO	WO2011/100697	A1	8/2011
WO	WO2011/123529	A1	10/2011
WO	WO2012/028896	A1	3/2012
WO	WO2012/049124	A2	4/2012
WO	WO2012/049612	A2	4/2012
WO	WO2012/078639	A1	6/2012
WO	WO2012/091280	A1	7/2012
WO	WO2012/112540	A2	8/2012
WO	WO2012/131340	A2	10/2012
WO	WO2012/160541	A2	11/2012
WO	WO2013/059358	A2	4/2013
WO	WO2013/109965	A1	7/2013
WO	WO2013/116807	A1	8/2013
WO	WO2013/116809	A1	8/2013
WO	WO2013/116851	A1	8/2013
WO	WO2013/116854	A1	8/2013
WO	WO2013/116866	A1	8/2013
WO	WO2013/128301	A2	9/2013

OTHER PUBLICATIONS

Abeysekera et al.; Alignment and calibration of dual ultrasound transducers using a wedge phantom; *Ultrasound in Medicine and Biology*; 37(2); pp. 271-279; Feb. 2011.

Arigovindan et al.; Full motion and flow field recovery from echo doppler data; *IEEE Transactions on Medical Imaging*; 26(1); pp. 31-45; Jan. 2007.

Capineri et al.; A doppler system for dynamic vector velocity maps; *Ultrasound in Medicine & Biology*; 28(2); pp. 237-248; Feb. 28, 2002.

Carson et al.; Measurement of photoacoustic transducer position by robotic source placement and nonlinear parameter estimation; *Biomedical Optics (BIOS)*; International Society for Optics and Photonics (9th Conf. on Biomedical Thermoacoustics, Optoacoustics, and Acousto-optics; vol. 6856; 9 pages; Feb. 28, 2008.

Chen et al.; Maximum-likelihood source localization and unknown sensor location estimation for wideband signals in the near-field; *IEEE Transactions on Signal Processing*; 50(8); pp. 1843-1854; Aug. 2002.

Chen et al.; Source localization and tracking of a wideband source using a randomly distributed beamforming sensor array; *International Journal of High Performance Computing Applications*; 16(3); pp. 259-272; Fall 2002.

Cristianini et al.; *An Introduction to Support Vector Machines*; Cambridge University Press; pp. 93-111; Mar. 2000.

Dunmire et al.; A brief history of vector doppler; *Medical Imaging 2001*; International Society for Optics and Photonics; pp. 200-214; May 30, 2001.

Du et al.; User parameter free approaches to multistatic adaptive ultrasound imaging; *5th IEEE International Symposium*; pp. 1287-1290, May 2008.

Feigenbaum, Harvey, M.D.; *Echocardiography*; Lippincott Williams & Wilkins; Philadelphia; 5th Ed.; pp. 482, 484; Feb. 1994.

Fernandez et al.; High resolution ultrasound beamforming using synthetic and adaptive imaging techniques; *Proceedings IEEE International Symposium on Biomedical Imaging*; Washington, D.C.; pp. 433-436; Jul. 7-10, 2002.

Gazor et al.; Wideband multi-source beamforming with array location calibration and direction finding; *Conference on Acoustics, Speech and Signal Processing ICASSP-95*; Detroit, MI; vol. 3 IEEE; pp. 1904-1907; May 9-12, 1995.

Haykin, Simon; *Neural Networks: A Comprehensive Foundation* (2nd Ed.); Prentice Hall; pp. 156-187; Jul. 16, 1998.

Heikkila et al.; A four-step camera calibration procedure with implicit image correction; *Proceedings IEEE Computer Society Conference on Computer Vision and Pattern Recognition*; San Juan; pp. 1106-1112; Jun. 17-19, 1997.

Hendee et al.; *Medical Imaging Physics*; Wiley-Liss, Inc. 4th Edition; Chap. 19-22; pp. 303-353; (year of pub. sufficiently earlier than effective US filing date and any foreign priority date) © 2002.

Hsu et al.; Real-time freehand 3D ultrasound calibration; *CUED/F-INFENG/TR 565*; Department of Engineering, University of Cambridge, United Kingdom; 14 pages; Sep. 2006.

Jeffs; *Beamforming: a brief introduction*; Brigham Young University; 14 pages; retrieved from the internet (<http://ens.ewi.tudelft.nl/Education/courses/et4235/Beamforming.pdf>); Oct. 2004.

Khamene et al.; A novel phantom-less spatial and temporal ultrasound calibration method; *Medical Image Computing and Computer-Assisted Intervention—MICCAI (Proceedings 8th Int. Conf.)*; Springer Berlin Heidelberg; Palm Springs, CA; pp. 65-72; Oct. 26-29, 2005.

Kramb et al.; Considerations for using phased array ultrasonics in a fully automated inspection system. *Review of Quantitative Non-destructive Evaluation*, 2004 Edition, ed. D. O. Thompson and D. E. Chimenti, American Inst. of Physics, pp. 817-825, Mar. 2004.

Ledesma-Carbayo et al.; Spatio-temporal nonrigid registration for ultrasound cardiac motion estimation; *IEEE Trans. on Medical Imaging*; vol. 24; No. 9; Sep. 2005.

Leotta et al.; Quantitative three-dimensional echocardiography by rapid imaging . . . ; *J American Society of Echocardiography*; vol. 10; No. 8; pp. 830-839; Oct. 1997.

Li et al.; An efficient speckle tracking algorithm for ultrasonic imaging; 24; pp. 215-228; Oct. 1, 2002.

Morrison et al.; A probabilistic neural network based image segmentation network for magnetic resonance images; *Proc. Conf. Neural Networks*; Baltimore, MD; vol. 3; pp. 60-65; Jun. 1992.

Nadkarni et al.; Cardiac motion synchronization for 3D cardiac ultrasound imaging; *Ph.D. Dissertation*, University of Western Ontario; Jun. 2002.

Opretzka et al.; A high-frequency ultrasound imaging system combining limited-angle spatial compounding and model-based synthetic aperture focusing; *IEEE Transactions on Ultrasonics, Ferroelectrics and Frequency Control*, IEEE, US; 58(7); pp. 1355-1365; Jul. 2, 2011.

Press et al.; Cubic spline interpolation; §3.3 in "Numerical Recipes in FORTRAN: The Art of Scientific Computing", 2nd Ed.; Cambridge, England; Cambridge University Press; pp. 107-110; Sep. 1992.

Saad et al.; Computer vision approach for ultrasound doppler angle estimation; *Journal of Digital Imaging*; 22(6); pp. 681-688; Dec. 1, 2009.

Sakas et al.; Preprocessing and volume rendering of 3D ultrasonic data; *IEEE Computer Graphics and Applications*; pp. 47-54, Jul. 1995.

Sapia et al.; Deconvolution of ultrasonic waveforms using an adaptive wiener filter; *Review of Progress in Quantitative Nondestructive Evaluation*; vol. 13A; Plenum Press; pp. 855-862; Jan. 1994.

Sapia et al.; Ultrasound image deconvolution using adaptive inverse filtering; *12 IEEE Symposium on Computer-Based Medical Systems*, CBMS, pp. 248-253; Jun. 1999.

Sapia, Mark Angelo; Multi-dimensional deconvolution of optical microscope and ultrasound imaging using adaptive least-mean-square (LMS) inverse filtering; *Ph.D. Dissertation*; University of Connecticut; Jan. 2000.

Slavine et al.; Construction, calibration and evaluation of a tissue phantom with reproducible optical properties for investigations in light emission tomography; *Engineering in Medicine and Biology Workshop*; Dallas, TX; IEEE pp. 122-125; Nov. 11-12, 2007.

(56)

References Cited

OTHER PUBLICATIONS

- Smith et al.; High-speed ultrasound volumetric imaging system. 1. Transducer design and beam steering; IEEE Trans. Ultrason., Ferroelect., Freq. Contr.; vol. 38; pp. 100-108; Mar. 1991.
- Specht et al.; Deconvolution techniques for digital longitudinal tomography; SPIE; vol. 454; presented at Application of Optical Instrumentation in Medicine XII; pp. 319-325; Jun. 1984.
- Specht et al.; Experience with adaptive PNN and adaptive GRNN; Proc. IEEE International Joint Conf. on Neural Networks; vol. 2; pp. 1203-1208; Orlando, FL; Jun. 1994.
- Specht, D.F.; A general regression neural network; IEEE Trans. on Neural Networks; vol. 2.; No. 6; Nov. 1991.
- Specht, D.F.; Blind deconvolution of motion blur using LMS inverse filtering; Lockheed Independent Research (unpublished); Jun. 23, 1975.
- Specht, D.F.; Enhancements to probabilistic neural networks; Proc. IEEE International Joint Conf. on Neural Networks; Baltimore, MD; Jun. 1992.
- Specht, D.F.; GRNN with double clustering; Proc. IEEE International Joint Conf. Neural Networks; Vancouver, Canada; Jul. 16-21, 2006.
- Specht, D.F.; Probabilistic neural networks; Pergamon Press; Neural Networks; vol. 3; pp. 109-118; Feb. 1990.
- UCLA Academic Technology; SPSS learning module: How can I analyze a subset of my data; 6 pages; retrieved from the internet (http://www.ats.ucla.edu/stat/spss/modules/subset_analyze.htm) Nov. 26, 2001.
- Urban et al.; Implementation of vibro-acoustography on a clinical ultrasound system; IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control; 58(6); pp. 1169-1181 (Author Manuscript, 25 pgs.); Jun. 2011.
- Urban et al.; Implementation of vibro-acoustography on a clinical ultrasound system; IEEE Ultrasonics Symposium (IUS); pp. 326-329; Oct. 14, 2010.
- Von Ramm et al.; High-speed ultrasound volumetric imaging-System. 2. Parallel processing and image display; IEEE Trans. Ultrason., Ferroelect., Freq. Contr.; vol. 38; pp. 109-115; Mar. 1991.
- Wang et al.; Photoacoustic tomography of biological tissues with high cross-section resolution: reconstruction and experiment; Medical Physics; 29(12); pp. 2799-2805; Dec. 2002.
- Wells, P.N.T.; Biomedical ultrasonics; Academic Press; London, New York, San Francisco; pp. 124-125; Mar. 1977.
- Widrow et al.; Adaptive signal processing; Prentice-Hall; Englewood Cliffs, NJ; pp. 99-116; Mar. 1985.
- Wikipedia; Point cloud; 2 pages; retrieved Nov. 24, 2014 from the internet (https://en.wikipedia.org/w/index.php?title=Point_cloud&oldid=472583138).
- Wikipedia; Curve fitting; 5 pages; retrieved from the internet (http://en.wikipedia.org/wiki/Curve_fitting) Dec. 19, 2010.
- Wikipedia; Speed of sound; 17 pages; retrieved from the internet (http://en.wikipedia.org/wiki/Speed_of_sound) Feb. 15, 2011.
- Yang et al.; Time-of-arrival calibration for improving the microwave breast cancer imaging; 2011 IEEE Topical Conf. on Biomedical Wireless Technologies, Networks, and sensing Systems (BioWireless); Phoenix, AZ; pp. 67-70; Jan. 16-19, 2011.
- Zang et al.; A high-frequency high frame rate duplex ultrasound linear array imaging system for small animal imaging; IEEE transactions on ultrasound, ferroelectrics, and frequency control; 57(7); pp. 1548-1567; Jul. 2010.
- Belevich et al.; U.S. Appl. No. 15/400,826 entitled "Calibration of multiple aperture ultrasound probes," filed Jan. 6, 2017.
- Davies et al.; U.S. Appl. No. 15/418,534 entitled "Ultrasound imaging with sparse array probes," filed Jan. 27, 2017.

* cited by examiner


FIG. 1


FIG. 2

FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7

FIG. 8





FIG. 9

NETWORK-BASED ULTRASOUND IMAGING SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Patent Application No. 62/038,602, filed on Aug. 18, 2014, titled "Network-Based Ultrasound Imaging System", the contents of which are incorporated by reference herein.

INCORPORATION BY REFERENCE

All publications and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication or patent application was specifically and individually indicated to be incorporated by reference.

FIELD

This application relates generally to the field of ultrasound imaging, and more particularly to a network-based ultrasound imaging system.

BACKGROUND

Ultrasound imaging provides for relatively low cost medical and non-medical imaging without the risks associated with ionizing radiation, or the complications of MRI imaging. Improvements to ultrasound imaging techniques combined with improvements to client-server networking architecture may provide additional opportunities for the use of ultrasound imaging to solve imaging challenges.

SUMMARY OF THE DISCLOSURE

A method of ultrasound imaging is provided, comprising transmitting an unfocused three-dimensional ping into an object from a transmitter element of a transducer array in a probe of a data capture device, receiving echoes of the unfocused three-dimensional ping with a plurality of receiver elements of the transducer array, converting analog signals from each of the plurality of receiver elements into a full dataset of digital sample sets, wherein the full dataset comprises digital sample sets from all the receiver elements, electronically transferring a sub-set of the digital sample sets to a remote server, wherein the sub-set comprises fewer digital samples than the full dataset, beamforming the sub-set of digital samples in the remote server to produce a series of two-dimensional image frames, and transferring a video stream made up of the series of two-dimensional image frames from the remote server to a display device.

In some embodiments, the method further comprises, in response to a control signal, transferring the full dataset from the data capture device to the remote server and storing the full dataset at the remote server.

In another embodiment, the method further comprises determining digital samples to include in the sub-set of digital samples by identifying digital samples associated with a selected imaging window from among the full dataset of digital sample sets.

In some embodiments, the display device is physically attached to the data capture device. In other embodiments, the display device is not physically attached to the data capture device. In further embodiments, the display device is a mobile device.

In some embodiments, the method further comprises selecting digital samples to include in the sub-set of digital samples by selecting only data samples corresponding to less than all pings transmitted from the probe.

In one embodiment, the method further comprises selecting digital samples to include in the sub-set of digital samples by selecting only data samples corresponding to less than all receive elements of the array.

In other embodiments, the method further comprises selecting digital samples to include in the sub-set of digital samples by selecting only data samples corresponding to less than all receive apertures of the array.

A network-based imaging system is provided, comprising a data capture device comprising a housing containing transmit control electronics configured to transmit ultrasound signals from a first plurality of transducer elements, receiver electronics configured to receive echoes of the transmitted ultrasound signals, the receiver electronics being further configured to digitize and store the received echoes as a full dataset in a first memory device physically located within a common housing of the data capture device, and communication electronics configured to communicate the full dataset. The system further comprises a remote server device comprising server communication electronics configured to receive the digitized echoes communicated by the communication electronics of the data capture device, beamforming software executed by the remote server device and configured to convert the received digitized echoes into a video stream of consecutive image frames, video streaming software executed by the remote server device and configured to stream the video to a display device.

In some embodiments, the display device further comprises user interface software executed by the display device and configured to receive user inputs to control one or more beamforming or video streaming parameters, and further configured to transfer user inputs to the beamforming software at the remote server device, the user interface software further comprising a user input control configured to transfer the full dataset to the remote server, and video display software executed by the display device and configured to receive the video stream from the remote server device and to display the video stream.

In some embodiments, the system further comprises a plurality of data capture devices in communication with the remote server device.

A method of collecting volumetric data representing a target object is provided, the method comprising transmitting an unfocused three-dimensional ping into the target object from a transmitter element of a transducer array in a probe, receiving echoes of the unfocused three-dimensional ping with a plurality of receiver elements of the transducer array, converting analog signals from each of the plurality of receiver elements into a full dataset of digital sample sets, wherein the full dataset comprises digital sample sets from all the receiver elements, electronically transferring a sub-set of the digital sample sets to a remote server, wherein the sub-set comprises fewer digital samples than the full dataset, beamforming the sub-set of digital samples in the remote server to produce a series of two-dimensional image frames, transferring a video stream made up of the series of two-dimensional image frames from the remote server to a mobile display device.

In some embodiments, the method further comprises, in response to a control signal, transferring the full dataset to the remote server and storing the full dataset at the remote server.

A method of ultrasound imaging is also provided comprising transmitting a plurality of unfocused three-dimensional pings into a three-dimensional target volume from a plurality of transmitter elements of a transducer array in a probe, receiving echoes of the unfocused three-dimensional pings with a plurality of receiver elements of the transducer array, converting analog signals from each of the plurality of receiver elements into a full dataset of digital sample sets, wherein the full dataset comprises digital sample sets from all the receiver elements, selecting a two-dimensional plane intersecting the three-dimensional target volume, identifying three-dimensional voxels intersecting the selected two-dimensional plane, identifying a sub-set of data samples corresponding to the selected two-dimensional plane, communicating only the sub-set of data samples over a computer network to a remote server, receiving, from the remote server, a video stream of two-dimensional images representing the selected two-dimensional plane, and displaying the video stream on a display device adjacent to the probe.

In some embodiments, the method further comprises, in response to a user command, communicating the full dataset to a remote data storage device.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a process flow diagram illustrating an example process for directly beamforming a two-dimensional image plane from raw echo data obtained from a three-dimensional volume.

FIG. 2 is a schematic perspective illustration of a multiple aperture imaging system for imaging a three-dimensional volume.

FIG. 3 is a schematic perspective illustration of a multiple aperture imaging system imaging a two-dimensional plane within a three-dimensional volume.

FIG. 4 is a schematic illustration of an embodiment of an imaging system incorporating a raw data memory.

FIG. 5 is a schematic illustration of an embodiment of a network-based imaging system.

FIG. 6 is a schematic illustration of another embodiment of a network-based imaging system.

FIG. 7 is a process flow diagram illustrating an example embodiment network-based imaging process.

FIG. 8 is a schematic illustration of another embodiment of a network-based imaging system.

FIG. 9 is a process flow diagram illustrating an example embodiment network-based imaging process.

DETAILED DESCRIPTION

Introduction and Definitions

Although the various embodiments are described herein with reference to ultrasound imaging of various anatomic structures, it will be understood that many of the methods and devices shown and described herein may also be used in other applications, such as imaging and evaluating non-anatomic structures and objects. For example, the probes, systems and methods described herein may be used in non-destructive testing, inspection or evaluation of various mechanical objects, structural objects or materials, such as welds, pipes, beams, plates, pressure vessels, layered structures, etc. The various embodiments below include systems and methods for using an ultrasound imaging system that is configured to store raw, un-beamformed ultrasound data for

subsequent beamforming and processing into image data. Such a system enables many unique methods of using ultrasound imaging systems.

Although examples are described herein with reference to transmission of ultrasound impulses into a medium to be imaged and reception of echoes of the transmitted ultrasound impulses. However, the skilled artisan will recognize that many of the techniques and systems described herein may be equally applicable to transmission and reception of other forms of energy, such as electromagnetic radiation including radio frequency signals, microwave signals, X-rays, or any other part of the electromagnetic spectrum.

As used herein the terms “ultrasound transducer” and “transducer” may carry their ordinary meanings as understood by those skilled in the art of ultrasound imaging technologies, and may refer without limitation to any single component capable of converting an electrical signal into an ultrasonic signal and/or vice versa. For example, in some embodiments, an ultrasound transducer may comprise a piezoelectric device. In some other embodiments, ultrasound transducers may comprise capacitive micromachined ultrasound transducers (CMUT) or any other electro-acoustic transducer device. In some embodiments, transducers may comprise components for the transduction of other energy forms, such as electromagnetic radiation.

Transducers are often configured in arrays of multiple individual transducer elements. As used herein, the terms “transducer array” or “array” generally refers to a collection of transducer elements mounted to a common backing block. Such arrays may have one dimension (1D), two dimensions (2D), 1.X dimensions (1.XD) or three dimensions (3D). Other dimensioned arrays as understood by those skilled in the art may also be used. Annular arrays, such as concentric circular arrays and elliptical arrays may also be used. An element of a transducer array may be the smallest discretely functional component of an array. For example, in the case of an array of piezoelectric transducer elements, each element may be a single piezoelectric crystal or a single machined section of a piezoelectric crystal.

As used herein, the terms “transmit element” and “receive element” may carry their ordinary meanings as understood by those skilled in the art of ultrasound imaging technologies. The term “transmit element” may refer without limitation to an ultrasound transducer element which at least momentarily performs a transmit function in which an electrical signal is converted into an ultrasound signal. Similarly, the term “receive element” may refer without limitation to an ultrasound transducer element which at least momentarily performs a receive function in which an ultrasound signal impinging on the element is converted into an electrical signal. Transmission of ultrasound into a medium may also be referred to herein as “insonifying.” An object or structure which reflects ultrasound waves may be referred to as a “reflector” or a “scatterer.”

As used herein, the term “aperture” may refer to a conceptual “opening” through which ultrasound signals may be sent and/or received. In actual practice, an aperture is simply a single transducer element or a group of transducer elements that are collectively managed as a common group by imaging control electronics or by beamforming electronics or software. For example, in some embodiments an aperture may be a physical grouping of elements which may be physically separated from elements of an adjacent aperture. However, adjacent apertures need not necessarily be physically separated.

It should be noted that the terms “receive aperture,” “insonifying aperture,” and/or “transmit aperture” are used

herein to mean an individual element, a group of elements within an array, or even entire arrays within a common housing, or groups of elements in multiple separate arrays, that perform the desired transmit or receive function from a desired physical viewpoint or aperture. In some embodiments, such transmit and receive apertures may be created as physically separate components with dedicated functionality. In other embodiments, any number of send and/or receive apertures may be dynamically defined electronically as needed. In other embodiments, a multiple aperture ultrasound imaging system may use a combination of dedicated-function and dynamic-function apertures.

As used herein, the term "total aperture" refers to the total cumulative size of all imaging apertures. In other words, the term "total aperture" may refer to one or more dimensions defined by a maximum distance between the furthest-most transducer elements of any combination of send and/or receive elements used for a particular imaging cycle. Thus, the total aperture is made up of any number of sub-apertures designated as send or receive apertures for a particular cycle. In the case of a single-aperture imaging arrangement, the total aperture, sub-aperture, transmit aperture, and receive aperture will all have the same dimensions. In the case of a multiple array probe, the dimensions of the total aperture may include the sum of the dimensions of all of the arrays.

As used herein, the term "ping cycle" may refer to a cycle beginning with a ping signal being transmitted from a transmit aperture and echoes of that ping being received by receiver transducer elements. In some cases, echoes from two or more pings may be combined to form a single image frame, and multiple frames may be displayed in sequence to form a video. Thus, an "image cycle" may contain echoes from multiple ping cycles. In other cases, a single ping cycle may correspond to a single image cycle.

In some embodiments, two apertures may be located adjacent one another on a continuous array. In still other embodiments, two apertures may overlap one another on a continuous array, such that at least one element functions as part of two separate apertures. The location, function, number of elements and physical size of an aperture may be defined dynamically in any manner needed for a particular application. Constraints on these parameters for a particular application will be discussed below and/or will be clear to the skilled artisan.

Elements and arrays described herein may also be multi-function. That is, the designation of transducer elements or arrays as transmitters in one instance does not preclude their immediate redesignation as receivers in the next instance. Moreover, embodiments of the control system herein include the capabilities for making such designations electronically based on user inputs, pre-set scan or resolution criteria, or other automatically determined criteria.

As used herein the term "point source transmission" or "ping" may refer to an introduction of transmitted ultrasound energy into a medium from a single spatial location. This may be accomplished using a single ultrasound transducer element or combination of adjacent transducer elements transmitting together as a single transmit aperture. A single transmission from a point source transmit aperture approximates a uniform spherical wave front, or in the case of imaging a 2D slice, a uniform circular wave front within the 2D slice. In some cases, a single transmission of a circular or spherical wave front from a point source transmit aperture may be referred to herein as a "ping" or a "point source pulse."

As used herein, the phrase "pixel resolution" refers to a measure of a number of pixels in an image, and may be

expressed with two positive integers, the first referring to a number of pixel columns (image width) and the second referring to a number of pixel rows (image height). Alternatively, pixel resolution may be expressed in terms of a total number of pixels (e.g., the product of the number of rows and the number of columns), a number of pixels per unit length, or a number of pixels per unit area. "Pixel resolution" as used herein is distinct from other uses of the term "resolution" which refers to the level of detail visible in an image. For example, "lateral resolution" may refer to the level of detail that may be discerned along a horizontal axis in an ultrasound image plane, independent of how an image of such a plane may be represented as a digital image made up of pixels.

15 Ping-Based Ultrasound Imaging

In various embodiments, point-source transmission ultrasound imaging, otherwise referred to as ping-based ultrasound imaging, provides several advantages over traditional scanline-based imaging. Point source transmission differs in its spatial characteristics from a "phased array transmission" which focuses energy in a particular direction from the transducer element array along a directed scanline. An un-focused point source pulse (ping) may be transmitted so as to insonify as wide an area as possible with an un-focused wavefront.

In some cases, an un-focused "circular" wavefront may be transmitted into a single image plane or "scanning plane." Such two-dimensional focusing may be achieved by providing a lensing material between a transducer element and an object to be imaged. A ping focused into a single plane may be referred to as a two-dimensional ping.

For volumetric imaging, an un-focused three-dimensional ping may be transmitted to form a substantially spherical wavefront which may be referred to as a three-dimensional ping.

Echoes of a transmitted ping will be returned from scatterers in the region of interest and may be received by all of the receiver elements of a probe. The receiver elements may be grouped into "receive apertures" as will be further described below. Those echo signals may be filtered, amplified, digitized and stored in short term or long term memory (depending on the needs or capabilities of a particular system).

Images may then be reconstructed from received echoes by assuming that the wavefronts emitted from the point source are physically circular (for 2D imaging) or spherical (for 3D imaging) in the region of interest. In actuality, a two-dimensionally focused wavefront may also have some penetration in the dimension normal to the 2D image plane. That is, some energy may essentially "leak" into the dimension perpendicular to the desired two-dimensional imaging plane.

Additionally, a "circular" wavefront may be limited to a semicircle or a fraction of a circle less than 180 degrees ahead of the front face of the transducer according to the unique off-axis properties of a transducing material. Similarly, when transmitting three-dimensional "spherical" pings, the corresponding wavefronts may have a shape of a semi-sphere or a smaller fractional sphere section (e.g., a "cone" shape), depending on the off-axis characteristics of the transmit element(s) used.

The process of forming an image from received echoes is generally referred to herein as "beamforming." In ping-based imaging, beamforming may generally involve determining an echo sample corresponding to each pixel or voxel position within an image window. Alternately, beamforming may involve the reverse, that is determining a pixel display

location for each received echo sample. Because each ping insonifies an entire imaged region, a “complete” (albeit low quality) image may be formed with the echoes of a single transducer element. An image that may be formed from echoes received by a single receive transducer element may be referred to as a sub-image. The image quality may be improved by combining sub-images formed from echoes received at a plurality of transducer elements. Transducer elements may be grouped into “apertures,” and sub-images from elements of a common aperture may be combined to form an image layer.

Beamforming of ping-based echoes may be performed using a software-based or hardware-based dynamic beamforming technique, in which a beamformer’s focus may be continuously changed to focus at a particular pixel position as that pixel is being imaged. Such a beamformer may be used to plot the position of echoes received from a point source pulse. In some embodiments, a dynamic beamformer may plot the locus of each echo signal based on a round-trip travel time of the signal from the transmitter to an individual receive transducer element.

When beamforming echoes of a transmitted two-dimensionally focused ping, the locus of a single reflector will lie along an ellipse with a first elliptical focus at the position of the transmit transducer element(s) and the second elliptical focus at the position of the receive transducer element. Although several other possible reflectors lie along the same ellipse, echoes of the same reflector will also be received by each of the other receive transducer elements of a receive aperture. The slightly different positions of each receive transducer element means that each receive element will define a slightly different ellipse for a given reflector. Accumulating the results by coherently summing the ellipses for all elements of a common receive aperture will indicate an intersection of the ellipses for the reflector, thereby converging towards a point at which to display a pixel representing the reflector. The echo amplitudes received by any number of receive elements may thereby be combined into each pixel value. In other embodiments the computation can be organized differently to arrive at substantially the same image.

When beamforming echoes of a transmitted three-dimensional ping, substantially the same process may be followed, but the possible locus of each reflector lies on a three-dimensional ellipsoid with a first ellipsoidal focus at the position of the transmit transducer element, and a second ellipsoidal focus at the position of the receiving transducer element. Therefore, combining impressions of a particular reflector obtained with multiple receive elements may produce a voxel point at the three-dimensional intersection of the multiple ellipsoids.

Errors in information describing the relative three-dimensional position of transmitting and receiving elements may substantially degrade image quality. Therefore, a calibration process may be used to minimize error in element position information.

Various algorithms may be used for combining echo signals received by separate receive elements. For example, some embodiments may process echo signals individually, plotting each echo signal at all possible locations along its ellipse, then proceeding to the next echo signal. Alternatively, each pixel location may be processed individually, identifying and processing all echoes potentially contributing to that pixel location before proceeding to the next 2D pixel or 3D voxel location.

Image quality may be further improved by combining images formed by the beamformer from one or more sub-

sequent transmitted pings, transmitted from the same or a different point source (or multiple different point sources). Improvements to image quality may be obtained by combining images formed by more than one receive aperture. The process of combining separately beamformed images, pixels or voxels may be referred to herein as “image layer combining.” Combining images from echoes received at multiple, separate apertures of a multiple aperture ultrasound probe may further improve image quality. The term “image layer combining” may refer to the combination of two or more overlapping pixel values, voxel values, or complete images (i.e., arrays of pixel and/or voxel values), where the overlapping values are obtained using different transmitted pings, different transmit apertures, and/or different receive apertures. Examples of image layer combining processes are described in Applicants’ prior applications referenced and incorporated by reference herein.

In some embodiments, ping-based multiple aperture imaging may operate by transmitting a point-source ping (e.g., a 2D ping or a 3D ping) from a first transmit aperture and receiving echoes with elements of two or more receive apertures, one or more of which may include some or all elements of a transmit aperture. An image may be formed by triangulating the position of scatterers based on delay times between ping transmission and reception of echoes, the speed of sound, and the relative positions of transmit and receive transducer elements. As a result, a sub-image of the entire insonified region may be formed from echoes of each transmitted ping received by each receive element. Coherently combining sub-images from echoes received by multiple elements grouped into a first receive aperture may produce the improvement described above with reference to intersecting ellipses. Sub-images from echoes received by multiple elements grouped into a second receive aperture may also be coherently combined with one another, and then the first-aperture image and the second-aperture image may be combined coherently or incoherently.

In some embodiments, a single time domain frame may be formed by combining images formed from echoes received at two or more receive apertures from a single transmitted ping. In other embodiments, a single time domain frame may be formed by combining images formed from echoes received at one or more receive apertures from two or more transmitted pings. In some such embodiments, the multiple transmitted pings may originate from different transmit apertures.

The same ping-based imaging techniques may be applied to 3D volumetric data by transmitting ping signals that are not constrained to a single plane (e.g., three-dimensional semi-spherical or near-semi-spherical ultrasound signals), and receiving echoes with receive elements displaced from one another in two dimensions perpendicular a line extending into the imaged medium, as described herein and in Applicants’ previous applications. Multiple aperture ultrasound probes configured for ping-based 3D volumetric imaging may have large total apertures, which may be substantially greater than any expected coherence width for an intended imaging application. Examples of multiple aperture ultrasound probes are shown and described in Applicants’ co-pending U.S. patent application Ser. No. 13/272,105, published as US 2012/0095343 and U.S. patent application Ser. No. 14/279,052, both of which are incorporated by reference herein.

3D volumetric data may be captured and stored using substantially the same systems and methods described above. Typically, a multiple aperture probe for 3D imaging may have substantially more transducer elements than a

probe intended primarily for 2D imaging. As such, an imaging system for capturing and storing 3D volumetric data during a ping-based imaging process may include substantially more receive channels and may also include a larger capacity raw data memory device. The raw echo data obtained with a probe for 3D volumetric imaging may be stored in the memory device. Such volumetric raw data may be structured similarly to data captured with a probe configured for 2D imaging, such that echoes may be distinguished based on the particular receive element that received them and the particular transmitted ping that generated the echoes.

Beamforming 3D ping-based echo data may also be performed using similar systems and methods to those used for beamforming 2D ping-based echo data. Each digitized sample value may represent a scatterer from theinsonified region of interest. As in the 2D case, the amplitude of each received sample along with its time of arrival and the exact three-dimensional positions of the transmitting and receiving transducers may be analyzed to define a locus of points identifying potential positions of the scatterer. In the 3D case, such a locus is a three-dimensional ellipsoid having as its foci the positions of the transmitting and receiving transducer elements. Each unique combination of transmitting and receiving transducer elements may define a separate view of the same reflector. Thus, by combining information from multiple transmit-receive transducer element combinations, the actual three-dimensional location of each reflector may be more accurately represented as a three-dimensional point or voxel in a three-dimensional volume.

For example, in some embodiments a 3D array of voxels representing reflectors in a 3D volume may be assembled in computer memory by beginning with an evaluation of a selected digital sample. The selected digitized sample value may be written into every voxel indicated by the corresponding ellipsoid as described above. Proceeding to do the same with every other collected sample value, and then combining all resulting ellipsoids may produce a more refined image. Real scatterers may be indicated by the intersection of many ellipsoids whereas parts of the ellipsoids not reinforced by other ellipsoids may have low levels of signal and may be eliminated or reduced by filters or other image processing steps.

In other embodiments, the order of computation may be changed by beginning with a selected voxel in a final 3D volume representation to be produced. For example, for a selected voxel, the closest stored sample may be identified for each transmitter/receiver pair. All samples corresponding to the selected voxel (i.e., all samples with an ellipsoid that intersects the voxel) may then be evaluated and summed (or averaged) to produce a final representation of the voxel. Closeness of a sample to a selected voxel may be determined by calculating the vector distance from the three-dimensional position of a transmitter (i.e., the transmitter from which the ping signal was transmitted to produce the echo sample) to the selected voxel position plus the vector distance from the selected voxel position to the position of a receiver at which the sample was received. Such a linear distance may be related to the time-divided sample values by dividing the total path length by speed of sound through the imaged object. If received data samples are stored and/or indexed based on the time after a transmitted ping at which they were received, then samples corresponding to a particular voxel may be identified based on the element position data and speed-of-sound data as described above. Using such methods, the samples corresponding to a calculated time may be associated with the selected voxel.

In some embodiments, a voxel of a final 3D volume representation may be made up of combined data from multiple receive elements, from multiple receive apertures, from multiple pings, or various combinations of these. An example will now be described with reference to an arbitrarily selected voxel. A first ping signal may be transmitted from a first transmit element, and the echoes received by each receive elements may be digitized and stored separately (e.g., one echo string per receive element per ping). A first set of echo data may be identified as representing energy from the first ping corresponding to the selected voxel received by elements of a first receive aperture. A second set of echo data generated from the first ping may also be identified as corresponding to the selected voxel received by elements of a second receive aperture.

A second ping signal may then be transmitted from a second, different transmit element. A third set of echo data representing energy from the second ping may be identified as corresponding to the selected voxel received by elements of the first receive aperture. A fourth set of echo data of the second ping may be identified as corresponding to the selected voxel received by elements of the second receive aperture.

As will be clear in view of the present disclosure, data received each element of the first receive aperture may provide a separate representation of each voxel in the imaged volume. Thus, the first data set may contain multiple data points representing the selected voxel as received by the individual elements of the first receive aperture. The data points of the first data set may be coherently combined with one another to produce a first impression of the selected voxel. The data points of the second data set representing signals from the first ping received by elements of the second receive aperture may be coherently combined with one another to produce a second impression of the selected voxel. The data points of the third data set representing signals from the second ping received by elements of the first receive aperture may be coherently combined with one another to produce a third impression of the example. The data points of the fourth data set representing signals from the second ping received by elements of the second receive aperture may be coherently combined with one another to produce a fourth impression of the selected voxel.

The first selected voxel impression may be coherently combined with the third selected voxel impression to form a first combined voxel impression of the selected voxel. Because both the first impression and the third impression were obtained with the same receive aperture, they may be combined coherently without risking phase cancellation (assuming the first receive aperture is sized to be less than a maximum coherent width for an intended imaging application).

The second impression of the selected voxel may be coherently combined with the fourth impression to form a second combined voxel impression of the selected voxel.

In some embodiments the step of coherently combining data from the first ping received by the elements of the first aperture with the data from the second ping received by the same elements of the same first receive aperture may be performed before any other combining steps. In some embodiments, combination of signals from two separate pings received by the same receive elements may be performed before or simultaneously with combining signals received by elements of a common receive aperture. In some embodiments, some coherent combinations of received signals may be performed electronically (i.e., by combining analog signals) before digitizing the received signals.

The first combined voxel impression may be combined with the second combined voxel impression. If the total aperture defined by the first receive aperture and the second receive aperture is greater than a total coherent width for the imaging application, then the first combined voxel impression may be combined incoherently with the second combined voxel impression to obtain a final representation of the selected voxel.

These steps of combining impressions of a selected voxel may be repeated or performed in parallel for each voxel of the imaged three-dimensional volume to obtain a final representation of the entire volume. In other embodiments, the steps may be performed in any other sequence, with any number of transmitted pings, and with any number of receive apertures. Various other combinations of coherent and incoherent summation techniques may also be used when combining signals from multiple receive elements, receive apertures, and/or pings.

In some embodiments, after the above example process or another process has been used to form a complete representation of the 3D volume, a single plane may be selected for display by identifying a collection of voxels making up the selected plane, and displaying the data from those voxel on a two-dimensional display.

In other embodiments, a selected two-dimensional plane may be beamformed directly from volumetric raw data instead of beamforming a complete 3D volume. This may be desirable in order to reduce a quantity of processing needed to produce an image of a selected plane.

FIG. 1 illustrates an example embodiment of a process 10 for beamforming a two-dimensional plane from three-dimensional data obtained by a ping-based multiple aperture imaging system. As shown at block 12, imaging signals may be transmitted into a three-dimensional volume. At block 14, signals from the transmitted signals may be received by receive elements of the imaging probe. Block 16 may comprise digitizing signals received by each receive transducer element of the probe as element-specific raw data sets (i.e., complete echo strings corresponding to each receive channel as described elsewhere herein). At block 18, a two-dimensional image plane within the insonified three-dimensional volume may be identified manually by a user or automatically by an imaging device or other system. At block 20, three-dimensional voxels intersecting the selected image plane may be identified. At block 22, the process may include identifying portions of each of the complete element-specific raw data sets corresponding to the identified voxels. The portions of the data sets may comprise complete samples and/or interpolated positions between samples. Identifying data samples corresponding to specified voxels may be performed based on known positions of transmit and receive elements and a speed-of-sound value (which may be based on an ultrasound frequency and the composition of an imaged medium) as described above. At block 24, the process may proceed by selecting only the identified samples for beamforming to determine display values for each pixel of the selected two-dimensional image plane.

FIG. 2 illustrates a schematic representation of an example three-dimensional multiple aperture ultrasound imaging probe array 100 (probe housing and support structures are omitted from the drawing for simplicity) comprising an array of transducer elements and a region of interest 120 to be imaged represented as a rectangular block (an actual shape and size of an insonified region may depend on details of the probe being used). The probe arrays 100 of FIG. 2 and FIG. 3 are shown as having curvature about two orthogonal axes, thereby forming a three-dimensional array

with all elements spaced from one another in at least two dimensions. In alternative embodiments, a probe array may be substantially flat with all elements lying in substantially the same two-dimensional plane. In further embodiments, any other configuration is also possible. For example, some elements may lie on a common plane while others may be angled inwards or outwards relative to an object to be imaged. As will be clear in view of the disclosure herein, as long as the position of each element is known to a desired degree of precision and accuracy, any array shape may be used, though some array configurations may be more optimally configured for a particular imaging application.

The probe array 100 is shown with a plurality of transmit elements T_1 , T_2 , and T_n highlighted. In some cases transmit elements may be dedicated for transmit only, while in other cases, any of the transducer elements may be temporarily designated as a transmit element for a particular image cycle or ping cycle. In some embodiments, any element of the array may be temporarily or permanently designated and used as a transmit element. In other embodiments, transmit elements may be configured differently than receive elements and/or may be used exclusively for transmitting. Transmit elements may be located at any position within a two-dimensional or three-dimensional array.

In some embodiments, some or all elements of the array 10 may be configured to receive echoes of transmitted signals. Such receive elements may be grouped into a plurality of receive apertures, each receive aperture comprising one or more receive elements as described herein. Grouping of elements into receive apertures may be performed at any time before or after imaging is performed. Furthermore, using stored raw echo data, receive apertures may be re-defined after collecting echo data, as described in further detail below.

FIG. 2 shows two receive apertures R_1 , R_2 , and R_3 . As shown, R_1 is made up of more elements than R_2 . It should be understood that each of the receive apertures may include any number of transducer elements which may be spaced from one another in one, two or three dimensions. The elements of the probe array may be grouped into any number of receive apertures as needed. Because echoes of each ping may be received by all or substantially all of the receive elements, and raw echo data from echoes received by each element may be digitized and stored in a raw data memory, the grouping of receive elements into receive apertures may be established or adjusted prior to imaging, during live imaging, or during subsequent review of stored raw data in order to optimize the arrangement of apertures for a given imaging scenario.

In some embodiments, the size of a receive aperture may be limited by the assumption that the speed of sound is the same for every path from a scatterer to each element of the receive aperture. In a narrow enough receive aperture this simplifying assumption is acceptable. However, as receive aperture width increases, an inflection point is reached (referred to herein as the "maximum coherent aperture width," "maximum coherent width" or "coherence width") at which the echo return paths will necessarily pass through different types of tissue having different speeds of sound. When this aggregate difference results in phase shifts approaching 180 degrees, additional receive elements beyond the maximum coherent receive aperture width will tend to degrade the image rather than improve it.

Therefore, in order to make use of a wide probe with a total aperture width greater than the maximum coherent width, the full probe width may be physically or logically divided into multiple apertures, each of which may be

limited to a maximum width (e.g., a circular diameter, an ellipse major axis length, or a rectangular/square aperture's diagonal length) no greater than the maximum coherent aperture width for an intended imaging application (that is, small enough to avoid phase cancellation of received signals). The maximum coherent width can be different for different patients and for different probe positions on the same patient. In some embodiments, a compromise width may be determined for a given imaging scenario. In other embodiments, a multiple aperture ultrasound imaging control system may be configured with a dynamic control mechanism to subdivide the available elements in multiple apertures into groups that are small enough to avoid destructive phase cancellation. Determining such a maximum aperture width may be achieved by sequentially evaluating images, image data, or other data produced using incrementally larger apertures until phase cancellation is detected, and then backing up by one or more aperture size increments.

In some embodiments, it may be more difficult to meet design constraints while grouping elements into apertures with a width less than the maximum coherent width. For example, if the material being examined is too heterogeneous over very small areas, it may be impractical or too costly to form apertures small enough to be less than the maximum coherent width. Similarly, if a system is designed to image a very small target at a substantial depth, an aperture with a width greater than the accepted maximum coherent width may be needed. In such cases, a receive aperture with a width greater than the maximum coherent width can be accommodated by making additional adjustments, or corrections may be made to account for differences in the speed-of-sound along different paths, allowing the region just enveloping the very small, very deep target to be brought into precise focus while other regions may be slightly defocused. Some examples of such speed-of-sound adjustments are provided here, while other methods may also be known.

Because ping signals insonify an entire region to be imaged, volumetric echo data obtained via three-dimensional ping-based imaging is seamless. By contrast, volumetric data assembled from a series of 2D planar slices tend to require some amount of interpolation of image data in the spaces between adjacent planar slices. Similarly, individual 2D images assembled from a series of scanlines typically require some amount of interpolation of image data in the spaces between adjacent scanlines.

The seamless nature of ping-based volumetric echo data means that any arbitrary 2D slices taken through any portion of a 3D volume may be beamformed and displayed without the need for interpolation. In some cases, non-planar or curved slices may also be taken through a section of volumetric data. The result of such a non-planar or curved-path slice may be displayed on a two-dimensional display, either as a flattened planar image or as a perspective rendering. Volumetric information may also be presented via a three-dimensional display such as a holographic display or a stereoscopic display. Therefore, in some embodiments, raw echo data from a volumetric imaging session may be retrieved from a memory device, some or all of the volume may be beamformed and displayed as an image, a desired region of the volume may be selected (automatically by software or manually by an operator), and the selected region may be re-beamformed and presented as a new image. Volumetric raw echo data may also be used in a wide range of other ways, as described below.

FIG. 3 illustrates a schematic probe array 100 highlighting a plurality of transmit elements T1, T2, T3, T4, T5, and

two receive aperture groups of elements R3 and R4. FIG. 3 also shows ray lines indicating paths traveled by ultrasound energy transmitted by each transmit element T1, T2, T3, T4, T5, to a reflector 140 within a single 2D plane 150 and dashed ray lines representing the paths traveled by echoes reflected by the reflector 140 and received at each of the receive apertures R3 and R4. As can be seen, although the transmit elements and the receiver elements do not all lie along a common plane, reflectors lying within the indicated 2D plane 150 can be illuminated with ultrasound energy from any of the transmit elements, and echoes may be received by receive elements located anywhere in the probe array 100.

Thus, even using a volumetric probe, reflectors lying along a single two-dimensional plane (e.g., plane 150) may be selected for beamforming and display from within an insonified three-dimensional volume. The use of transmitters and receivers not on the image plane makes possible point spread functions that are much smaller in the dimension perpendicular to the image plane than point spread functions in the same plane obtained with a 2D probe (i.e., a probe configured to transmit and receive energy focused within the image plane).

As will be described in further detail below, beamforming of received echo data may be performed in real-time during a live imaging session, and/or at a later time by retrieving raw echo data of an imaging session. Depending on a probe used, and the needs of a particular application, raw echo data sets may be collected and stored for imaging sessions covering one or more individual two-dimensional planes, or for complete three-dimensional volumes.

Raw Echo Data

FIG. 4 is a block diagram illustrating components that may be included in some embodiments of an ultrasound imaging system 200. The diagram of FIG. 4 includes several subsystems: a transmit control subsystem 204, a probe subsystem 202, a receive subsystem 210, an image generation subsystem 230, and a video subsystem 240. Unlike most ultrasound systems, the system of FIG. 4 provides a memory device configured to store raw, un-beamformed echo data for later retrieval and processing. In some embodiments, the various subsystems may be physically and logically contained within a single device. In other embodiments, some or all of the subsystems may be contained in physically separate devices or systems that may be in communication with other devices containing some or all of the other subsystems. Additional details of the elements of FIG. 4 are described in Applicants' co-pending U.S. patent application Ser. No. 13/971,689, published as US Patent Application Publication No. 2014/0058266, the entirety of which is incorporated by reference herein.

The transmit control subsystem may generally comprise control electronics for determining the shape, timing, frequency or other characteristics of transmitted ultrasound pulses. The probe subsystem may include any probe configured to transmit ultrasound energy into a medium to be imaged and to receive echoes of the transmitted energy from within the medium. In some cases, transmit and receive functions may be divided into physically, electronically, and/or logically separate devices, and in some cases, a receive probe may receive directly-transmitted energy in addition to reflected energy. In some cases, one or more elements of the imaging system 200 of FIG. 4 may be omitted.

The receive subsystem 210 may generally include a plurality of separate channels (e.g., one channel per receive transducer element, in some embodiments), each channel

having an Analog Front End (AFE) **212** configured to perform various amplifying, filtering and other handling of analog signals from the probe subsystem's receive transducer elements. The AFE may be connected to an Analog-to-Digital conversion device/system (ADC) **214** which may be configured to convert received analog signals into digital signals. Such digital signals may be stored in a digital memory device such as a raw data memory device **220** as described below, and/or optionally transmitted directly **250** to elements of an image generation subsystem **230**.

The image generation subsystem **230** may include a beamformer block **232** and, in some cases, may also include an image-layer combining block **234** and/or other processing blocks. The image generation subsystem **230** may generally be configured to convert the digital raw echo data received from the receive sub-system **210** or the raw data memory device **220** into a series of displayable images. In some embodiments, the displayable images produced by the image generation subsystem **230** may be stored in an image buffer storage device **236**. The video/image display subsystem **240** may include components such as a video processor block **242** configured to convert the series of displayable images from the image generation subsystem **230** into an analog or digital video stream that may be displayed on an output display device **244**. The video/image display subsystem **240** may also include an analog or digital memory device configured to store video streams for display at a different time and/or at a different location. The image generation subsystem may also include a video memory device **246** configured to store beamformed and processed digital video files.

Any of the digital storage devices described herein, such as raw data memory devices, video memory devices, image memory devices, data warehouses and others may include any number of any suitable non-volatile digital memory device or combinations thereof. Examples of digital storage devices may include hard disk drives, solid state disk drives, flash memory devices, other solid state removable non-volatile storage devices such as SD cards or USB flash memory devices, optical storage devices such as CDs, DVDs, or Blu-Ray, magnetic tape, or any non-volatile digital memory device. In some cases, analog storage devices may also be used for data storage.

As used herein, the phrases "echo data," "raw echo data" and "raw data" may refer to stored echo information describing received ultrasound echoes at any level of processing prior to beamforming. In various embodiments, received echo data may be stored at various stages between pure analog echo signals to fully processed digital images or even digital video. For example, a raw analog signal may be stored using an analog recording medium such as analog magnetic tape. At a slightly higher level of processing, digital data may be stored immediately after passing the analog signal through an analog-to-digital converter. Further incremental processing, such as band-pass filtering, interpolation, down-sampling, up-sampling, other filtering, etc., may be performed on the digitized echo data, and "raw" output data may be stored after such additional filtering or processing steps. Such raw data may then be beamformed to determine a pixel location for each received echo, thereby forming an image. Individual still images may be combined as frames to form motion video. In some embodiments of the systems and methods described herein, it may be desirable to store digitized raw echo data after performing very little processing e.g., after some filtering and conditioning of digital echo data, but before performing any beamforming or image processing.

Although the term "echo data" is generally used herein to refer to data received by receive elements, the term "echo data" is also intended to include data generated by digitizing received signals resulting from direct transmission of ultrasound or other transmitted energy signals without necessarily being reflected. Therefore, the phrase "echo data" may generally have the same meaning as "receive data."

In addition to received echo data, it may also be desirable to store information about one or more transmitted ultrasound signals that generated a particular set of echo data. For example, when imaging with a multiple aperture ping-based ultrasound method as described above, it is desirable to know information about a transmitted ping that produced a particular set of echoes. Such information may include the identity and/or position of one or more transmit elements, as well as frequency, amplitude (magnitude), pulse length (duration), waveform (shape), or other information describing a transmitted ultrasound signal.

Transmit data may be collectively referred herein to as "TX data". In some embodiments, such TX data may be stored explicitly in the same raw data memory device in which raw echo data is stored. For example, TX data describing a transmitted signal may be stored as a header before or as a footer after a set of raw echo data generated by the transmitted signal. In other embodiments, TX data may be stored explicitly in a separate memory device that is also accessible to any system performing a beamforming process (e.g., a PC, laptop, tablet, mobile device, server, imaging system, or other suitably configured device). In embodiments in which transmit data is stored explicitly, the phrases "raw echo data" or "raw data" may also include such explicitly stored TX data.

TX data may also be stored implicitly. For example, if an imaging system is configured to transmit consistently defined ultrasound signals (e.g., consistent amplitude, waveform shape, frequency, pulse length, etc.) in a consistent or known sequence, then such information may be assumed during a beamforming process. In such cases, the only information that needs to be associated with the echo data is the position (or identity) of the transmit transducer(s). In some embodiments, such information may be implicitly stored and extracted based on the organization of raw echo data in a raw data memory.

For example, a system may be configured to store a fixed number of echo records following each ping. In such embodiments, echoes from a first ping may be stored at memory positions 0 through 'n-1' (where 'n' is the number of records stored for each ping), and echoes from a second ping may be stored at memory positions n through 2n-1. In other embodiments, one or more empty or specially encoded records may be left in between echo sets. In some embodiments received echo data may be stored using any of various memory interleaving techniques to imply a relationship between a transmitted ping and a received echo data point (or a group of echoes). In general, a collection of data records corresponding to echoes or other signals resulting from a single transmitted ping received by a single receive element may be referred to herein as a single "echo string."

A "complete echo string" may refer to substantially all data resulting from a single ping received by a receive element, whereas a "partial string" or a "partial echo string" may refer to a sub-set of all echoes of the single ping received by the receive element.

Similarly, a "complete data set" may refer to substantially all raw data (e.g., echoes or directly-received signals) resulting from a defined set of transmitted signals. A set of transmitted signals may be defined as an identifiable set of

transmitted pings, as all pings or other signals transmitted within a defined period of time, or otherwise. A “partial data set” may refer to a sub-set of all raw data resulting from the defined set of transmitted signals.

In some cases, a complete echo string or a complete data set may comprise less than all theoretically available data, because some data may be discarded as undesirable. For example, data representing a first few milliseconds following transmission of a ping may contain substantial cross-talk or other noise that may not meaningfully contribute to a desired dataset, and may therefore be ignored. Nonetheless, the resulting dataset may still be considered a “complete echo string” or a “complete data set” if it contains all of the desired data resulting from a transmitted ping (or a set of pings). Partial echo strings or partial data sets may be obtained by selecting a sub-set of records from a complete echo string or data set in order to limit a data set for the purposes of faster data communication or limiting processing resources, for example.

Similarly, assuming data is sampled at a consistent, known sampling rate, the time at which each echo data point was received may be inferred from the position of that data point in memory. In some embodiments, the same techniques may also be used to implicitly store and organize/interpret data from multiple receive channels in a single raw data memory device.

In other embodiments, the raw echo data stored in the raw data memory device **220** may be physically or logically located in any other structure as desired, provided that the system retrieving the echo data is able to determine which echo signals correspond to which receive transducer element and to which transmitted ping. In some embodiments, position data describing the exact physical location of each receive transducer element relative to a common coordinate system may be stored in the calibration memory device **238** along with information that may be linked to the echo data received by that same element. Similarly, position data describing the exact physical location of each transmit transducer element may be stored in the calibration memory device **238** along with information that may be linked to TX data describing each ping transmitted from that transmit element.

In general, calibration data describing position and/or performance information about each transducer element may be physically located in any device electronically accessible by the device performing beamforming operations. For example, calibration data may be located in a probe device itself, in an imaging system connected by a wired or wireless connection to the probe, in a network-accessible database accessible by an imaging system, or by a server or other computing device configured to perform beamforming operations.

In some embodiments, calibration data may also include performance information. Performance information may include information identifying elements that have become damaged to the point that they provide response data that does not accurately describe the echoes impinging on the element. Depending on the nature of the inaccurate information, data from damaged elements may be ignored or weighted to minimize detrimental effects on resulting images.

In some embodiments, additional information useful in beamforming images based on stored echo data may also be stored in a digital storage device accessible to a device performing beamforming operations. Examples of such additional information may include speed-of-sound values, such as average speed-of-sound values, path-specific speed-

of-sound values (e.g., a speed of sound along a ray path from a transmit aperture to a pixel/voxel location to a receive aperture), receive-aperture-specific speed-of-sound values, or others. Additional stored information may also include weighting factors or user-controllable settings used during a data-capture session.

In some embodiments, each echo string in the raw data memory device **220** may be associated with position data describing the position of the receive transducer element that received the echoes and with data describing the position of one or more transmit elements of a transmit aperture that transmitted the ping that produced the echoes. Each echo string may also be associated with TX data describing characteristics of the transmitted ping such as power level, frequency, pulse length/signal shape, emitter efficiency, etc. Such associations may be made using any suitable data structures.

In some cases, raw echo data may also be associated with various “meta-data,” including information allowing a clinician or service provider to associate the raw echo data with a patient, imaging date/time, imaging location, imaging environment (ambient temperature, humidity, barometric pressure, etc.), imaging system settings used during image capture, object surface temperature, or other information that may be useful in using the raw data. Any other meta-data may also be associated with raw echo data records.

One benefit of storing raw echo data is that the information may be retrieved, processed, and reviewed at a later time, allowing a far greater degree of control and flexibility than if only a video stream (e.g., a cine loop) were saved from an imaging session. For example, in one embodiment, a patient may visit a technician and the technician may conduct an ultrasound examination during which raw echo data is captured and stored. Hours, days, weeks, or even months later (in other words, any time after the patient’s original session), a trained professional such as a physician may use a personal computer, laptop, tablet or an imaging system to re-examine a wide range of images derivable from data generated during the examination session and to create new images (that is, images that were not produced during the imaging session with the patient) by manipulating the raw data without re-examining or re-imaging the patient. In some embodiments, such re-examination of stored data may include several processes that are only possible with access to raw echo data.

In some embodiments, raw data from an imaging session may be stored along with raw echo data captured while imaging a calibration phantom. For example, raw echo data obtained while imaging a calibration phantom may be used for later calibration of the imaging session data by correcting transducer element position assumptions made during live beamforming.

Information describing the position of each transducer element may be obtained by a calibration process as described in Applicants’ prior applications. Such element position data may be stored in a calibration memory device **220**, which may be physically located with other electronics, or may be located in a remote, network-accessible server. However, in some embodiments, the element-position information may change between performing a calibration operation and capturing raw ultrasound data. For example, a probe may have been dropped, damaged or otherwise altered before or during a raw echo data capture session.

In some embodiments, the ability to re-process stored raw echo data means that a probe may actually be retroactively

re-calibrated after raw echo data is captured, and the data may be re-beamformed using the updated element position information.

In other embodiments, raw echo data stored in a raw data memory device may be analyzed to determine whether a probe is actually out of calibration.

Raw Data Capture Devices

In various embodiments, a network-based imaging system may provide the advantage of de-coupling the collection of raw echo data from formation and display of images derived from the collected raw echo data. As a result, systems operating as components in a network-based imaging system may be configured to operate in two broadly-defined modes. In a “live imaging” or “real-time imaging” mode, the system may be configured to process and display images based on echo data with as little latency as possible. Latency may be defined as the time delay between when an action (such as moving the probe relative to the object being imaged) occurs and when the imaging system displays a result of the action. Various examples of live-imaging modes are described below.

A second broad mode may be described as a “high quality data capture” mode. When a “high quality data capture” mode is initiated, a data capture component of a network-based imaging system may collect and store raw echo data (along with TX data, and other data as described herein) from a pre-determined time period, number of ping cycles, or number of image cycles. During a high quality data capture mode, the full data set need not be beamformed or otherwise processed in real time. In some embodiments, the data capture device may store the raw data in an external (e.g., network-connected) storage device in real-time as it is captured. In other embodiments, such as when real-time network communication resources are limited, the data capture device may store the raw data in a local storage device in real-time, and may subsequently transfer the captured data to an external (e.g., network-connected) storage device at a later time when network resources are less constrained. A single remote data storage device or a collection of remote data storage devices may be referred to herein as a “data warehouse,” which may include any number of network-connected data storage devices as needed.

Embodiments of network-based imaging systems may generally include data capture devices having lower cost and limited-performance hardware for performing transmitting, receiving and data storage functions. Data capture devices may be physically de-coupled from and located physically remotely from image generation devices which may have higher cost and higher performance hardware and/or software for performing beamforming and image processing functions. Some embodiments of network-based imaging systems may also include end-use viewer terminals in network-communication with the image generation devices and/or in communication directly with one or more data capture devices. Such viewer terminals may be used for real-time or time-shifted viewing of images generated from captured raw data. In some embodiments, data capture devices may be configured for operation by relatively minimally-trained technicians who may be guided by one or more highly trained professionals via network communications or by a software or artificial intelligence agent.

In some embodiments, raw echo data that is captured and stored in a raw data memory device as described above may subsequently be copied, forwarded, or otherwise electronically communicated to an external (e.g., a backup) memory storage device. Such data communications may take place

over any available wired or wireless data transfer system, such as Bluetooth, IR/Infra-Red, USB, IEEE 1394 Firewire, Thunderbolt, Ethernet/Intranet/Internet (TCP/IP, FTP, etc.) or others.

In some embodiments, the raw data may be loaded back onto an ultrasound imaging system (e.g., the same system originally used forinsonification and raw echo data capture), or a similarly-configured ultrasound imaging system for re-processing, re-beamforming, and image generation/viewing. In other embodiments, a personal computer, laptop, tablet, mobile device, network-connected server, or other digital computing device may be configured with software and/or hardware to beamform and/or process the raw echo data into images without the use of a dedicated ultrasound imaging system.

In other embodiments, raw echo data may be beamformed, processed and displayed by software on any other suitably configured computational device or system, such as a tablet or smart phone. In other embodiments, raw echo data may be uploaded over a network to a network-accessible server which may store and process image data remotely.

FIG. 5 illustrates an embodiment of an imaging system **201** divided into an energy (e.g. ultrasound) data capture and communication device **260** and a remote image generation and display system **262**. The data capture and communication device **260** may be configured with minimal hardware components for communication of raw echo data to the remote imaging system **262** via a communications device **264** and a wired or wireless network **266**.

The data capture device **260** of FIG. 5 may include a probe **202**, a transmit controller **204**, an AFE **212** and an ADC **214** as described above. In place of any beamforming or image processing components, the data capture device **260** may instead include a communications device **264** configured to communicate raw echo data to a remote system **262** via a network **266**. The remote system **262** may include hardware, firmware and/or software configured to beamform and process the raw echo data captured by the device **260**.

In some embodiments, the probe **202** may be an ultrasound probe with ultrasound transducer elements spaced from one another in two or three dimensions and configured for capturing 3D volumetric ultrasound data as described herein.

In some embodiments, the communications device **264** may be configured to stream raw echo data in real time to the remote system **262**. In other embodiments, the data capture device **260** may include an internal memory device **220** for short term storage of raw echo data (e.g., as a communication buffer). In other embodiments, an internal memory device **220** within the data capture and communication device **260** may be configured for longer term storage of raw echo data within the capture device **260**. In further embodiments, a data capture device may contain one, two or more memory devices **220** configured for various uses.

For example, a data capture and communication device **260** may include a first memory device **220** configured to operate as a circular buffer for storing real-time data immediately prior to communicating the real-time data over a network **266**. After data has been communicated from the device **260**, the data may be deleted or overwritten with newly acquired data. The data capture device **260** may also contain a second memory device configured to operate as a circular buffer for a full set of raw echo data to be communicated over the network in response to a command from an operator.

In some embodiments, a system **201** such as that shown in FIG. **5** may be used in an environment in which an operator of the data capture device **260** does not require a display, such as when using a probe configured to be placed in a stationary position on a patient during a data capture session. In some cases, a third party (e.g., in addition to the patient and the data capture device operator) may view real-time images produced from the raw echo data obtained by the data capture device **260** and communicated over the data network **266**. The third party reviewing the images may then provide real-time instructions relating to the placement of the probe on a patient or other object to be imaged. In some embodiments, such positioning instructions may be delivered verbally, such as over a telephone or other audio connection. Alternatively, probe placement instructions may be communicated to the operator by way of indicators on the probe itself or by an external device such as a display screen or other device.

For example, a tablet device with an integrated camera may be used to produce an optical image of the patient or other object with the probe **202** in place. The tablet may include an application configured to indicate a direction and distance of movement of the probe on the patient (or other object) to a more ideal location. Such movement instructions may be provided by a third-party viewing images at a remote image generation and display system **262**. Alternatively, probe positioning instructions may be provided to the operator by an artificial intelligence application on the tablet or by directional indicators on an image being displayed on a tablet or other display screen.

In some embodiments, some or all elements of a remote image generation and display system **262** may be implemented in a tablet, personal computer, laptop, mobile device, or a combination of such elements, collectively referred to herein as a “control surface”. For example, in some embodiments, image generation, raw data storage and image buffering functions may be performed in a computing device which may be in wired or wireless communication with a control surface such as a handheld tablet device which may be configured to perform the display and video processing functions along with user interface functions.

FIG. **6** illustrates another example of an imaging system **300** comprising a limited function data capture and communication device **310**, a network-based beamforming and video processing device **320**, and one or more viewer terminals **330** connected to one another via a wired or wireless data network. As shown in the illustrated example, the data capture and communication device **310** may include a probe **202**, a transmit controller **204**, an AFE, **212**, an ADC **214**, a raw-data memory device **220**, a communications device **264**, and a display **244**. In some embodiments, the probe **202** may be an ultrasound probe with ultrasound transducer elements spaced from one another in two or three dimensions and configured for capturing 3D volumetric ultrasound data as described herein.

The network-based beamforming and video processing device **320** may include one or more digital storage devices comprising a raw data warehouse **221**, an image generation subsystem **230** which may include hardware and/or software for performing beamforming, image layer combining (as described above, for example) and other image generation processes. The beamforming and video processing device **320** may also include a calibration memory **238**, an image buffer **236**, a video processor **242**, and a video memory **246**.

In operation, the imaging system **300** may be used for live real-time imaging of a patient or object to be imaged. An example of a real-time imaging process is described below

with reference to FIG. **7**. Live real-time imaging may be performed using the limited function data capture and communication device **310** by using the probe **202** to transmit ultrasound pulses into the region of interest (such as unfocused three-dimensional pings) and receive echo signals from the region of interest. The received signals and other information (e.g., calibration information, TX data, device identifier, etc.) may be communicated from the data capture and communication device **310** to the beamforming and video processing device **320** over the network **266**. The beamforming and video processing device **320** may beamform the echo data to generate images and may produce data representing a video stream that may be electronically communicated over the network **266** back to the data capture and communication device **310** for display to an operator on the display **244** of the device **310**.

The data capture and communication device **310** of FIG. **6** may include a probe configured to transmit into and receive energy from an entire three-dimensional volume to be imaged. Alternatively, the data capture and communication device **310** of FIG. **6** may include a probe configured to insonify and receive echoes from only a single imaging plane. In some embodiments, the data capture and communication device **310** of FIG. **6** may be configured with beamforming hardware and software omitted. This may allow for the data capture and communication device **310** to be constructed at relatively lower cost, and utilize components with relatively lower power demand. In some embodiments, several such low-cost data capture and communication devices **310** may be deployed within a local network (such as a hospital, medical center, imaging center, or other facility in which imaging may be performed). All such devices may utilize the same beamforming and video processing device **320** over the local network. In some embodiments, the beamforming and video processing device **320** may comprise several servers in order to manage a load of several simultaneous live imaging sessions.

In order to conduct live, real-time imaging sessions using a network-based imaging system, it may be desirable to limit the quantity of raw echo data to be processed to form real-time images. The quantity of raw echo data to be processed and/or communicated over a network may be reduced by using one or more of various data reduction methods. Some examples of which are provided below.

In the case of a network-based beamformer such as that illustrated in FIG. **5** and FIG. **6**, various data reduction methods may be used to reduce the quantity of data communicated over the data network **266** from each data capture and communication device **310** to the beamforming and video processing device **320**.

One example data reduction approach may involve identifying a reduced set of data samples to be processed into images by defining a limited image window. In some embodiments, the quantity of raw echo data to be processed and/or communicated over a network can be greatly reduced by determining a minimum sample window necessary to generate images of a defined image window.

An image window may be defined as a particular two-dimensional plane (possibly as a portion of a three-dimensional volume), qualified by zoom level, and further constrained by left-right pan and up-down elevation within the insonified object's region of interest. An image window may be selected automatically by the data capture and communication device **310**, manually by an operator of the device, or a combination of manually and automatically.

As used herein, the term “sample window” may refer to a range or list of sample index values identifying a set of

stored data samples meeting some criteria. For example, a sample window may be defined as the set of data samples corresponding to pixels of a two-dimensional image window which may be defined in terms of size, position, and orientation within an insonified volume.

In some embodiments, a process for reducing a data set by image window sample selection may comprise the steps of (1) defining an image window, (2) identifying receive data samples corresponding to the defined image window, and (3) selecting only those samples corresponding to the defined image window for processing or communication over a network.

In some embodiments, an optimum set of raw data samples (earliest through latest per ping for each receive element) needed for generating a particular image window may be determined by calculating the sample numbers (or other sample-identifying indices) corresponding to the top and bottom rows of image window pixels, and communicating only those reduced ranges of samples to the remote beamforming and video processing device **320**; all raw data samples outside of these ranges will not be used for beamforming that particular image window, so need not be communicated to the remote beamforming and video processing device **320**. Typically, and depending on zoom level selected, only a quarter or fewer of the total samples collected per ping for each receive element may be used during the beamforming process. Each TX-RX pair may generate a slightly different range of necessary samples for a given image window, but the variation among all pairs may be small enough to simply use the minimum 'early' sample number/index through the maximum 'late' sample number/index across all pings and receive elements.

One data reduction technique may include using a process for directly beamforming a two-dimensional image from raw data produced by insonifying a three-dimensional volume, as described above with reference to FIG. 1. In such embodiments, a reduced data set may comprise only the data corresponding to the selected two-dimensional image plane, while a "complete" raw data set may comprise echo data received from the entire three-dimensional volume.

A set of data samples to be processed or communicated over a network may be further reduced by effectively reducing a frame rate of a displayed video stream. Frame rate reduction may be performed in multiple ways. For example, in some embodiments a frame rate may be reduced by selecting only echoes of selected pings for processing into image frames. In other words, a size of a raw data set may be reduced by using the data produced by less-than-all transmitted pings. For example, if only the echoes of every-other transmitted ping are selected for processing, then the data set may be reduced by half. In other examples, selected data may be limited to data received from every third ping, every fourth ping, every fifth ping, etc.

In another example, raw data may be selected based on the position and/or identity of transmit elements that produced the data. For example, if a probe contains X transmit apertures (or transmit elements where each transmit aperture has only one element), each of which transmits a ping during a typical imaging cycle, then a data set to be processed or communicated over a network may be reduced by selecting only echo data samples corresponding to pings transmitted by X/2, X/3, X/4, X/5, etc. of the transmit elements. In some embodiments, the transmit elements from which echo data is to be selected may be chosen based on position of the elements in the probe. For example, if only a small region under the probe is of interest, then chosen transmit elements may be limited to those above the small region of interest.

In other embodiments, a data set may be reduced by pre-combining echo data before processing or communicating the data over a network. For example, receive data received by the same receive element in response to two separate pings may be combined with one another coherently, thereby reducing two data points to one. In some embodiments, a first echo string received by a first receive element resulting from a first ping may be coherently combined with a second echo string received by the first receive element resulting from a second ping. In some embodiments echoes of two or more pings received by the same element may be combined before performing other data reduction methods.

Many other methods may be used for reducing the set of raw echo data to be transferred when conducting live, real-time imaging sessions using a network-based beamformer and image generation device **320**. In one example, the real precision of the A/D Converter **214** may be closely measured, and the LSB (Least Significant Bit) bits that correspond most closely to sampling noise, conversion noise, or quantization error may be stripped or removed from the data to be transferred. For example, for a 16-bit ADC with sufficiently high statistical error probabilities in bits **0** through **2**, it may be sufficient to only communicate bits **3** through **15** and pack sequential samples accordingly, reducing bandwidth needs by nearly 20%.

Another data reduction method may include reducing the frame rate of communicated data to a small fraction of the full frame rate supported by the Analog Front End (AFE) or other electronics, with a corresponding linear reduction in bandwidth needs.

Another data reduction method may include, prior to communicating a reduced set of data samples over the network **266**, compressing the raw data samples of the set using a lossless or lossy compression algorithm as requirements dictate, allowing for another potential 25% to 75% or greater reduction in bandwidth needs.

Another data reduction method may include reducing a total number of receive elements for which data is selected. For example, a subset of all receive elements may be selected, and receive data from only those selected elements may be selected for beamforming or communication over a network. In some cases, a subset of receive elements may be selected based on position of the receive elements relative to a particular feature of interest within an insonified volume. In other cases, the number of elements assigned to an aperture may be reduced, such as by ignoring some receive elements in between selected elements, using only data from the selected elements.

In other embodiments, entire apertures may be ignored, such as by selecting some apertures to be included in a reduced data set, while removing data from one or more apertures. In some embodiments, data received by a group of elements between selected apertures may be removed from a data set to form a reduced data set.

In some cases, several data reduction techniques may be applied concurrently, yielding compounded reductions in total communicated data.

In some cases, a level of data reduction to be applied may be based on a desired image quality level for a particular imaging application. For example, if a user or an automated system determines that a particular imaging application requires a high quality real-time image, then data reduction methods may be selected based on their impact on image quality in order to preserve image quality at a minimum level needed for the identified application. On the other hand, if a lower image quality is acceptable for an identified

imaging application, then data reduction methods that may tend to reduce image quality may be used.

In some embodiments, the data capture and communication device **310** may include a user interface with controls allowing an operator to select an image window, adjust imaging parameters, and capture raw echo data to local and/or remote storage for later review and analysis. Capturing raw data may comprise storing raw echo data received by the transducer elements during several seconds (or more) of imaging. The raw data captured may be stored in the raw data memory device **220** in the data capture and communication block **310**, and may be communicated to the remote beamforming and video processing block **320** over the network **266** and stored in the raw data warehouse **221**.

In some cases, in addition to data reduction, various processing-reduction adjustments may be made to beamforming, image layer combining, or image processing methods. For example, performing fewer data combining (image layer combining) steps may reduce a quantity of processing needed to produce each image frame. Similarly, by adjusting a balance of coherent vs incoherent summation of image layers, a number of processing cycles to produce an image frame may be increased or decreased. In other embodiments, any other processing-reduction methods may be used.

The raw data captured and stored by the data capture and communication device **310** may include substantially all of the received data, without reducing or reducing the data using the techniques described above. This allows the raw data set to be used for more detailed review and analysis than might be available for real-time imaging with a limited-function data capture and communication device **310**.

In some embodiments, the system of FIG. **6** may be used in combination with a viewer terminal **330**, such as a laptop computer, a desktop computer, a tablet, a smartphone, or other computing device configured to connect to the remote image generation system. For example, an operator controlling the probe **202** may view a video stream produced by the video processing block **320** on a terminal device **330** instead of (or in addition to) the display **244**.

FIG. **7** illustrates an example of a network-based imaging process **400** that may be performed by a raw data capture device, such as those described herein (e.g., the device **260** of FIG. **5**, the device **310** of FIG. **6**, the device **312** of FIG. **8**, or any other suitably configured device). In various embodiments, the steps of the process **400** of FIG. **7** may be performed by two or more devices.

The process **400** of FIG. **7** may generally be configured to perform a live imaging process while communicating a limited data set to a remote server (e.g., **262** of FIG. **5**, **320** of FIG. **6**, or **322** of FIG. **8**) which may perform beamforming operations and communicate a video stream back to the data capture device and/or an adjacent display device (such as a laptop, PC, tablet, mobile device, or other control surface). In various embodiments, user interface elements may be provided in the data capture device, in a separate control surface device, or in another device.

The process **400** of FIG. **7** may include transmitting and receiving signals with an imaging probe as shown in block **410**. In some embodiments, the operations of block **410** may include transmitting and receiving steps as described herein with reference to ping-based multiple aperture imaging. Alternatively, transmitting and receiving signals may include any other suitable imaging process. Any suitable probe device may be used.

At block **412**, the process **400** may include digitizing received signals as raw data sets and storing complete raw data sets in a local memory device. As described herein,

digitizing received signals may be performed with any suitable analog front end, analog-to-digital conversion, and/or other hardware and software components. The local memory device may be any suitable volatile or non-volatile memory device.

As described above, a “complete data set” may refer to substantially all raw data (e.g., echoes or directly-received signals) resulting from a defined set of transmitted signals. A set of transmitted signals may be defined as an identifiable set of transmitted pings, as all pings or other signals transmitted within a defined period of time, or otherwise. Thus, for example, a complete data set may include all digitized received signals resulting from a set of X transmitted pings, where X is any number from 1 to 1 million or more (practical systems may define sets of pings based on a number of transmit elements of a probe, for example).

At block **414**, the process **400** may include selecting portions of the complete stored raw data set for communication over the network. Selecting portions of the data sets may include any one or more of the data reduction methods described above. For example, in some embodiments, a selected reduced data set may comprise only data corresponding to a selected two-dimensional image plane, while a “complete” raw data set may comprise echo data received from the entire insonified three-dimensional volume.

At block **416**, the process **400** may include communicating the selected raw data set portions over a network to a remote server. As described herein, the network may include any data network, and the remote server may include any suitable server device. In some embodiments, the remote server may be physically located a distance of several miles or more from the probe, while in other embodiments, the remote server may be located in the same room. The server may only be “remote” in the sense that it is not housed in the same device as the data capture device.

The remote server may process the received information and beamform the raw data set portions to produce images which may be combined to form a video stream. The methods used by the remote server may include any beamforming, image layer combining, and/or other image processing techniques appropriate for the received data, including the various example methods described herein.

At block **418**, the process **400** may include receiving a video stream from the remote server over the network. The video stream may be communicated using any suitable digital video communication protocols or methods. At block **420**, the received video stream may be displayed to an operator of the imaging probe (who may also be operating the data capture device).

At block **422**, the process **400** may include, in response to a user command to initiate a “high quality data capture mode” as described herein, communicating a complete raw data set over a network to a remote data storage device. As described in various examples above, the remote data storage device may be integral with or separate from the same remote server used to perform beamforming and image processing. The network used for communicating the complete raw data set may be the same network or a different network than the one used to communicate the selected raw data set portions. In various embodiments, the complete data set may be retrieved from the remote data storage device, beamformed and processed into images in near-real-time (e.g., within second or milliseconds of it being received at the remote data storage device) or at any longer time delay.

In various embodiments, each viewer terminal **330** may include independent user interface controls configured to independently control imaging parameters. Independently-

controlled imaging parameters may include any items of user-controllable information affecting an image displayed to the user. For example, imaging parameters may include beamforming parameters such as speed-of-sound and image window selection, or video processing parameters such as brightness, contrast, video filters, etc.

FIG. 8 illustrates an example of an alternate configuration of an imaging system 302 with a limited-function data capture and communication device 312 in communication with a network-based remote image generation system 322. The data capture and communication device 312 may optionally include hardware and software elements to enable the device to perform some or all beamforming and image generation operations locally and to display a limited-quality (and/or lower frame rate) real-time image to an operator. The data capture and communication device 312 may also be configured to communicate full-quality raw echo data from the full insonified 3D volume or 2D plane to the network-based image generation system 322 for real-time and/or time-shifted manipulation and viewing by one or more remote professionals (e.g., physicians, sonographers, or other trained professionals) using a viewer terminal 330.

The data capture and communication device 312 may include a probe 202 (e.g., a 3D imaging probe or a 2D imaging probe as described above), a transmit controller 204, an AFE 212, an ADC 214, a raw data memory device 220, a communication device 264, an image generation block 231 which may perform beamforming and image layer combining operations, a video processor 242, and a display 244. In some embodiments, the data capture and communication device 312 may include components with relatively low processing power and low power requirements in order to allow an operator to see a limited-quality real-time image, while allowing for full-quality data to be captured, stored and communicated to a raw data warehouse 221.

The data capture and communication device 312 of FIG. 8 may include a probe configured to transmit and receive energy in an entire three-dimensional volume to be imaged. In some embodiments, the image generation block 231 may be configured to beamform echoes received from a single plane within a three-dimensional insonified volume, while optionally (e.g., on an operator's command) storing several seconds worth of raw echo data from the full 3D volume in the on-board raw data memory 220 and/or communicating the 3D volumetric raw data to the raw data warehouse 221.

In order to limit the hardware requirements for the data capture and communication device 312, on-board real-time beamforming and image generation and display hardware may be limited to generating and processing images for one or more two-dimensional slices within an insonified 3D volume. In some embodiments, the 2D slice (or slices) to be beamformed and displayed may be selected manually by an operator. In other embodiments, the displayed image planes may be fixed for a particular probe, or may be automatically selected by software. Fixed planes, for example, may include a pair of orthogonal planes intersecting at the center of a probe array (e.g., the plane 150 in FIG. 3 and a vertical plane orthogonal to plane 150), plus a horizontal plane orthogonal to the two vertical planes. Fixed planes may include axial, coronal, sagittal, transverse and other planes commonly used in anatomical imaging. These two or more planes may be displayed side-by-side on the display 244. Alternatively, two, three, four or more user-selectable (and not necessarily orthogonal) planes may also be displayed simultaneously.

Additionally, the amount of processing to be performed by the image generation block 231 may be limited by

utilizing any of the data reduction methods described above, such as producing images at a frame rate substantially lower than a maximum frame rate that may be achievable with ping-based multiple aperture imaging.

The system of FIG. 8 may also be used in combination with a viewer terminal 330, such as a laptop computer, a desktop computer, a tablet, a smartphone, or other computing device configured to connect to the remote image generation system in order to allow the full-quality image data to be viewed by the operator either in real-time or after the imaging session has been completed.

In some embodiments all or a substantial portion of the raw data collected by a data capture device may be communicated to the remote image generation system 322 in real-time (or as close to real-time as possible). In such embodiments, one or more remote users may view near real-time images of the imaging session via a network-connected viewer terminal 330.

The remote image generation system 322 may include a calibration memory device 238, a raw data warehouse 221, and an image processing server 324. The image processing server may include hardware and software elements suitable for performing any of the sub-processes described herein, such as beamforming, image layer combining, image process, video processing, etc. The image processing server 324 may also be configured to retrieve raw data from the raw data warehouse and corresponding calibration data from the calibration memory based on a request from a user operating a viewer terminal or a data capture and communication device 312 for an identified imaging session.

In some embodiments, the remote user may select one or more image windows entirely independent of an image window (if any) being viewed by an operator of the data capture and communication device 312. Similarly, the remote user may adjust beamforming and image generation parameters independently of settings used by an operator of the data capture and communication devices 312 without necessarily changing an image displayed to the operator. Variables that may be adjusted by the remote viewer user may include speed-of-sound values, zoom level, pan window, weighting factors, image layer combining algorithms, etc.

In addition to ping-based beamforming, beamformer technology may be separately packaged for embedding into a scanline-based imaging system or installed on a server and made available to scanline-based imaging systems through a network connection. In some embodiments, a data capture device may comprise a tap configured to intercept electrical signals sent to and received from a conventional ultrasound (or other) imaging probe.

FIG. 9 illustrates an example of a network-based imaging process 450 that may be performed by a raw data capture device that includes at least some beamforming and imaging processing electronics, such as the device 312 described herein with reference to FIG. 8. In various embodiments, the steps of the process 450 of FIG. 9 may be performed by two or more devices.

The process 450 of FIG. 9 may generally be configured to perform a live imaging process using a built-in processor to beamform and process a limited data set and display a limited-quality video stream while capturing and storing a complete data set from which a full-quality video stream may be produced. On command, the complete data set may be communicated over a network to a remote storage device. In various embodiments, user interface elements may be provided in the data capture device, in a separate control surface device, or in another device.

The process **450** of FIG. **9** may include transmitting and receiving signals with an imaging probe as shown in block **452**. In some embodiments, the operations of block **452** may include transmitting and receiving steps as described herein with reference to ping-based multiple aperture imaging. Alternatively, transmitting and receiving signals may include any other suitable imaging process. Any suitable probe device may be used.

At block **454**, the process **450** may include digitizing received signals as raw data sets and storing complete raw data sets in a local memory device. As described herein, digitizing received signals may be performed with any suitable analog front end, analog-to-digital conversion, and/or other hardware and software components. The local memory device may be any suitable volatile or non-volatile memory device.

As described above, a “complete data set” may refer to substantially all raw data (e.g., echoes or directly-received signals) resulting from a defined set of transmitted signals. A set of transmitted signals may be defined as an identifiable set of transmitted pings, as all pings or other signals transmitted within a defined period of time, or otherwise. Thus, for example, a complete data set may include all digitized received signals resulting from a set of X transmitted pings, where X is any number from 1 to 1 million or more (practical systems may define sets of pings based on a number of transmit elements of a probe, for example).

At block **456**, the process **450** may include selecting portions of the complete stored raw data set for real-time beamforming and image processing. Selecting portions of the data sets may include any one or more of the data reduction methods described above. For example, in some embodiments, a selected reduced data set may comprise only data corresponding to a selected two-dimensional image plane, while a “complete” raw data set may comprise echo data received from the entire insonified three-dimensional volume.

At block **458**, the selected raw data set portions may be processed and beamformed to produce a limited-quality video stream. The image processing block **231** and the video processing block **242** within the data capture and communications device **312** may beamform and process the selected raw data portions to produce images which may be combined to form a limited quality video stream. The methods used by the image processing block **231** may include any beam forming, image layer combining, and/or other image processing techniques appropriate for the selected data, including the various example methods described herein.

At block **460**, the limited quality video stream may be displayed to an operator of the imaging probe (who may also be operating the data capture and communications device **312**).

At block **462**, the process **450** may include, in response to a user command to initiate a “high quality data capture mode” as described herein, communicating a complete raw data set over a network to a remote data storage device. As described in various examples above, the remote data storage device may be integral with or separate from the same remote server used to perform beamforming and image processing. The network used for communicating the complete raw data set may be the same network or a different network than the one used to communicate the selected raw data set portions. In various embodiments, the complete data set may be retrieved from the remote data storage device, beamformed and processed into images in near-real-time

(e.g., within second or milliseconds of it being received at the remote data storage device) or at any longer time delay.

The retrieved complete data set may be processed by the image processing server **324** to produce a video stream of higher quality than the limited quality video stream. The retrieved complete data set may also be processed by the image processing server **324** to produce entirely different images and/or video than what was viewed in real-time by the operator of the data capture device.

10 Remote-Guided Imaging

In some embodiments, an operator of a limited-function data capture and communication device such as those described above may be remotely guided in positioning the probe on a patient or other object by a more-skilled operator.

15 Alternatively, or in addition, probe-positioning guidance may also be provided by an automated system.

In various embodiments, automatic guidance may be provided by an artificial intelligence system utilizing computer aided detection techniques to recognize features within an image and suggesting probe movements to more fully capture a desired target object. Alternatively, automatic guidance may be provided by obtaining optical images of the probe as positioned on a patient (or other object). Such optical images may be obtained with a web-cam or other computer-connected digital camera. Artificial Intelligence software configured to recognize anatomical features may be used to guide the user to place the probe in an ideal position for imaging a target organ or other object. In some embodiments, a laser pointer or other indicator may be used to indicate probe movement instructions to the operator.

Alternatively, the operator may be guided by a static or dynamic image of a mannequin mock-up of a patient with illustrations of where to place the probe in order to image a desired organ or other object.

35 Data Communications and Storage

In various embodiments, the systems of FIG. **5**-FIG. **8** may be configured to communicate information in addition to the raw echo data to a network-based storage device. For example, the systems may communicate various annotations and/or header information along with the raw echo data. Such annotation/header data may include information allowing a clinician or service provider to associate the raw echo data with a patient, such as an anonymized patient ID number. Additionally, information such as a date/time of the data capture session, a location of the data capture session, imaging system settings used during image capture, a probe identifier, calibration data, environmental data, or other information that may be useful in beamforming or otherwise using the raw data.

50 Some examples of data reduction procedures are described above. In addition to those methods, additional processes may be performed to package, compress, annotate or otherwise modify raw echo data prior to transmission to the data warehouse.

55 In some embodiments, each probe may be provided with its own hard-coded globally unique identifier (GUID). The GUID, combined with the numerical representation of the current date and time may be used as a basis for creating a unique identifier for each data capture session. The unique identifier may then be associated with the header data associated with and stored with the raw echo data from the data capture session. The header data may include elements such as: the date and time of the data capture, the geographic location of the data capture, an ID number identifying the patient (or other object to be imaged), the settings of the probe, user interface settings used during live imaging, and any other pertinent information. The unique identifier and

header information may be associated with the raw data set and stored locally and/or in a data warehouse. The stored information may be referenced at any point in the future for an unlimited amount of accesses.

Although this invention has been disclosed in the context of certain preferred embodiments and examples, it will be understood by those skilled in the art that the present invention extends beyond the specifically disclosed embodiments to other alternative embodiments and/or uses of the invention and obvious modifications and equivalents thereof. Various modifications to the above embodiments will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other embodiments without departing from the spirit or scope of the invention. Thus, it is intended that the scope of the present invention herein disclosed should not be limited by the particular disclosed embodiments described above, but should be determined only by a fair reading of the claims that follow.

In particular, materials and manufacturing techniques may be employed as within the level of those with skill in the relevant art. Furthermore, reference to a singular item, includes the possibility that there are plural of the same items present. More specifically, as used herein and in the appended claims, the singular forms “a,” “and,” “said,” and “the” include plural referents unless the context clearly dictates otherwise. Also as used herein, unless explicitly stated otherwise, the term “or” is inclusive of all presented alternatives, and means essentially the same as the commonly used phrase “and/or.” It is further noted that the claims may be drafted to exclude any optional element. As such, this statement is intended to serve as antecedent basis for use of such exclusive terminology as “solely,” “only” and the like in connection with the recitation of claim elements, or use of a “negative” limitation. Unless defined otherwise herein, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs.

What is claimed is:

1. A method of ultrasound imaging comprising:
transmitting an unfocused three-dimensional ping into an object from a transmitter element of a transducer array in a probe of a data capture device;
receiving echoes of the unfocused three-dimensional ping with a plurality of receiver elements of the transducer array;
converting analog signals from each of the plurality of receiver elements into a full dataset of digital sample sets, wherein the full dataset comprises digital sample sets from all the receiver elements;
electronically transferring a sub-set of the digital sample sets to a remote server, wherein the sub-set comprises fewer digital samples than the full dataset;
beamforming the sub-set of digital samples in the remote server to produce a series of two-dimensional image frames;
combining the series of two-dimensional image frames to form a limited quality video stream; and
transferring the limited quality video stream made up of the series of two-dimensional image frames from the remote server to a display device.

2. The method of claim 1 wherein, in response to a control signal, transferring the full dataset from the data capture device to the remote server and storing the full dataset at the remote server.

3. The method of claim 1, further comprising determining digital samples to include in the sub-set of digital samples by identifying digital samples associated with a selected imaging window from among the full dataset of digital sample sets.

4. The method of claim 1, wherein the display device is physically attached to the data capture device.

5. The method of claim 1, wherein the display device is not physically attached to the data capture device.

6. The method of claim 4, wherein the display device is a mobile device.

7. The method of claim 1, further comprising selecting digital samples to include in the sub-set of digital samples by selecting only data samples corresponding to less than all pings transmitted from the probe.

8. The method of claim 1, further comprising selecting digital samples to include in the sub-set of digital samples by selecting only data samples corresponding to less than all receive elements of the array.

9. The method of claim 1, further comprising selecting digital samples to include in the sub-set of digital samples by selecting only data samples corresponding to less than all receive apertures of the array.

10. A network-based imaging system, comprising:

a data capture device comprising:

a housing containing transmit control electronics configured to transmit ultrasound signals from a first plurality of transducer elements;

receiver electronics configured to receive echoes of the transmitted ultrasound signals, the receiver electronics being further configured to digitize and store the received echoes as a full dataset in a first memory device physically located within a common housing of the data capture device; and

communication electronics configured to communicate a sub-set of digital samples of the full dataset;

a remote server device comprising:

server communication electronics configured to receive the sub-set of digital samples communicated by the communication electronics of the data capture device;

beamforming software executed by the remote server device and configured to convert the received sub-set of digital samples into a limited quality video stream of consecutive image frames;

video streaming software executed by the remote server device and configured to stream the limited quality video stream to a display device.

11. The imaging system of claim 10, the display device further comprising:

user interface software executed by the display device and configured to receive user inputs to control one or more beamforming or video streaming parameters, and further configured to transfer user inputs to the beamforming software at the remote server device, the user interface software further comprising a user input control configured to transfer the full dataset to the remote server;

video display software executed by the display device and configured to receive the video stream from the remote server device and to display the video stream.

12. The system of claim 10, further comprising a plurality of data capture devices in communication with the remote server device.

13. A method of collecting volumetric data representing a target object, the method comprising:

33

transmitting an unfocused three-dimensional ping into the target object from a transmitter element of a transducer array in a probe;

receiving echoes of the unfocused three-dimensional ping with a plurality of receiver elements of the transducer array;

converting analog signals from each of the plurality of receiver elements into a full dataset of digital sample sets, wherein the full dataset comprises digital sample sets from all the receiver elements;

electronically transferring a sub-set of the digital sample sets to a remote server, wherein the sub-set comprises fewer digital samples than the full dataset;

beamforming the sub-set of digital samples in the remote server to produce a series of two-dimensional image frames;

combining the series of two-dimensional image frames to form a limited quality video stream; and

transferring the limited quality video stream made up of the series of two-dimensional image frames from the remote server to a mobile display device.

14. The method of claim **13** wherein, in response to a control signal, transferring the full dataset to the remote server and storing the full dataset at the remote server.

34

15. A method of ultrasound imaging comprising:

transmitting a plurality of unfocused three-dimensional pings into a three-dimensional target volume from a plurality of transmitter elements of a transducer array in a probe;

receiving echoes of the unfocused three-dimensional pings with a plurality of receiver elements of the transducer array;

converting analog signals from each of the plurality of receiver elements into a full dataset of digital sample sets, wherein the full dataset comprises digital sample sets from all the receiver elements;

selecting a two-dimensional plane intersecting the three-dimensional target volume;

identifying three-dimensional voxels intersecting the selected two-dimensional plane;

identifying a sub-set of data samples corresponding to the selected two-dimensional plane;

communicating only the sub-set of data samples over a computer network to a remote server;

receiving, from the remote server, a limited quality video stream of two-dimensional images representing the selected two-dimensional plane; and

displaying the limited quality video stream on a display device adjacent to the probe.

16. The method of claim **15**, further comprising, in response to a user command, communicating the full dataset to a remote data storage device.

* * * * *

专利名称(译)	基于网络的超声成像系统		
公开(公告)号	US10401493	公开(公告)日	2019-09-03
申请号	US15/500933	申请日	2015-08-18
[标]申请(专利权)人(译)	茂伊成像股份有限公司		
申请(专利权)人(译)	MAUI IMAGING , INC.		
当前申请(专利权)人(译)	MAUI IMAGING , INC.		
[标]发明人	CALL JOSEF R DAVIS HENRY A SMITH DAVID M SPECHT DAVID J LE VIET NAM MCHARDY LANG J DIGIOVANNI II JOSEPH JAMES OSBORN NATHAN W RITZI BRUCE R		
发明人	CALL, JOSEF R. DAVIS, HENRY A. SMITH, DAVID M. SPECHT, DAVID J. LE, VIET NAM MCHARDY, LANG J. DIGIOVANNI, II, JOSEPH JAMES OSBORN, NATHAN W. RITZI, BRUCE R.		
IPC分类号	A61B8/14 A61B8/00 A61B8/08 G06F3/14 G01S15/89 G01S7/52		
CPC分类号	G01S15/89 G01S15/8993 G01S7/52053 G01S15/8925 G01S15/8929 G06F3/14 A61B8/14 A61B8/5207 A61B8/523 A61B8/565 A61B8/483		
优先权	62/038602 2014-08-18 US		
其他公开文献	US20170219704A1		
外部链接	Espacenet		

摘要(译)

提供了用于基于网络的超声成像的系统和方法，其可以包括许多特征。在一些实施例中，超声成像系统利用三维未聚焦的瞳孔对物体成像，并从多个接收器元件获得数字样本集。可以将数字样本集的子集电子地传送到远程服务器，其中可以对子集进行波束成形以产生一系列二维图像帧。然后可以将由一系列二维图像帧组成的视频流从远程服务器传送到显示设备。

