




US 20140364731A1

(19) **United States**(12) **Patent Application Publication**
Kann(10) **Pub. No.: US 2014/0364731 A1**(43) **Pub. Date: Dec. 11, 2014**(54) **ULTRASOUND IMAGING SYSTEM IMAGE IDENTIFICATION AND DISPLAY**(71) Applicant: **B-K MEDICAL APS**, Herlev (DK)(72) Inventor: **Peter Ulrik Kann**, Farum (DK)(21) Appl. No.: **13/913,580**(22) Filed: **Jun. 10, 2013****Publication Classification**(51) **Int. Cl.**
A61B 8/00 (2006.01)
A61B 8/08 (2006.01)(52) **U.S. CL.**CPC **A61B 8/463** (2013.01); **A61B 8/4472**
(2013.01); **A61B 8/469** (2013.01); **A61B**
8/5207 (2013.01); **A61B 8/4483** (2013.01);
A61B 8/54 (2013.01)
USPC **600/440**(57) **ABSTRACT**

An ultrasound imaging system includes at least one transducer element. The ultrasound imaging system further includes a console with a transducer controller that controls the at least one element, a transducer processor that processes information detected by the at least one element, and a display controller that controls display of the processed information. The ultrasound imaging system further includes a display monitor with a first image display region. The ultrasound imaging system further includes a touch screen keyboard with a second image display region, wherein the display monitor and the touch screen keyboard are separate devices.






FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7




FIGURE 8




FIGURE 9




FIGURE 10




FIGURE 11

ULTRASOUND IMAGING SYSTEM IMAGE IDENTIFICATION AND DISPLAY

TECHNICAL FIELD

[0001] The following generally relates to ultrasound and more particular to identification of one or more images to display and the display of the identified one or more images, and is described with particular application to an ultrasound imaging system.

BACKGROUND

[0002] An ultrasound imaging system has included an ultrasound probe with a transducer, a console with an internal or external display monitor, and a keyboard. The transducer transmits an ultrasound signal into a field of view and receives echoes produced in response to the signal interacting with structure therein. The echoes are conveyed to the console via a cable or the like and are processed, producing images of the scanned structure, which may be visually presented in a display region of the display monitor.

[0003] The display monitor has included a cathode ray tube (CRT), a liquid crystal display (LCD), light emitting diode (LED), and/or other monitor. Furthermore, the display monitor has been a monitor with no processor or processing capabilities and that is simply an output device that accepts and displays data from a processor of the console. With such display monitors, generally, the display monitor faces the clinician operating the ultrasound imaging system. In this manner, the clinician can visually observe rendered images and readily access controls for invoking visualization and non-visualization features.

[0004] To show a patient and/or other person a rendered image, the clinician would have to turn the display monitor so that the display region is in the line of sight of the patient and/or the other person. Unfortunately, this may make it difficult for the clinician to concurrently observe the rendered image. Furthermore, with an integrated console/monitor, the clinician may have to turn the console and thus may no longer have easy access to the visualization and non-visualization controls of the console. Moreover, displayed text, graphics, etc. also displayed may clutter the display region and limit the size of the rendered image.

SUMMARY

[0005] Aspects of the application address the above matters, and others.

[0006] In one aspect, an ultrasound imaging system includes at least one transducer element. The ultrasound imaging system further includes a console with a transducer controller that controls the at least one element, a transducer processor that processes information detected by the at least one element, and a display controller that controls display of the processed information. The ultrasound imaging system further includes a display monitor with a first image display region. The ultrasound imaging system further includes a touch screen keyboard with a second image display region, wherein the display monitor and the touch screen keyboard are separate devices.

[0007] In another aspect, a method includes receiving a first signal from a touch screen keyboard of an ultrasound imaging system indicating one of a plurality of images to display with a display monitor of the ultrasound imaging system, wherein

the touch screen keyboard and the display monitor are separate devices, and displaying the one of the plurality of images with the display monitor.

[0008] In another aspect, a computer readable storage medium is encoded with computer readable instructions which, when executed by a computer processor, cause the computer process to: display, in an image display region of a display monitor of an ultrasound imaging system, an image from a set of images displayed in an image display region of a touch screen keyboard based on a signal from the touch screen keyboard indicative of an image of interest, wherein the touch screen keyboard and the display monitor are separate devices.

[0009] Those skilled in the art will recognize still other aspects of the present application upon reading and understanding the attached description.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] The application is illustrated by way of example and not limitation in the figures of the accompanying drawings, in which like references indicate similar elements and in which:

[0011] FIG. 1 schematically illustrates an example ultrasound imaging system, including a touch screen keyboard (with an image display region) and a display monitor (with an image display region) that is a separate device relative to the touch screen keyboard;

[0012] FIGS. 2 and 3 illustrate an example in which an image of interest is identified in the touch screen keyboard and displayed in the display monitor;

[0013] FIG. 4 illustrates an example in which a pointer is created and manipulated in the display monitor through interaction with the touch screen keyboard;

[0014] FIG. 5 illustrates an example in which the display monitor is rotated with respect to the touch screen keyboard;

[0015] FIG. 6 illustrates an example in which the touch screen keyboard includes an image save active region and an image delete active region;

[0016] FIG. 7 illustrates an example of saving an image displayed in the touch screen keyboard using the image save active region;

[0017] FIG. 8 illustrates an example of deleting an image displayed in the touch screen keyboard using the image delete active region;

[0018] FIG. 9 illustrates a method for displaying an image in an image display region of a display monitor via identifying the image in an image display region of a touch screen keyboard;

[0019] FIG. 10 illustrates a method for manipulating an image displayed in an image display region of a display monitor via an image display region of a touch screen keyboard; and

[0020] FIG. 11 illustrates a method for saving or deleting an image displayed in an image display region of a touch screen keyboard.

DETAILED DESCRIPTION

[0021] FIG. 1 schematically illustrates an ultrasound (US) imaging system **102**.

[0022] The ultrasound imaging system **102** includes a probe **104** with a one-dimensional (1D) or two-dimensional (2D) transducer array **106** with at least one transducer element **108**. Suitable configurations include, but are not limited to, linear, curved (e.g., concave, convex, etc.), circular, etc.,

full populated or sparse, etc. The probe **104** further includes an interface **110**. The interface **110** may include a connector (e.g., an electro-mechanical device for joining electrical circuits) and/or wireless transceiver.

[0023] The ultrasound imaging system **102** further includes a console **112**. The console **112** includes an interface **114**, which is complementary to the interface **110**. With physical connectors, a communication device **116** such as a cable, a wire, an optical fiber, etc. electrically interfaces the interfaces **110** and **114**. For example, the interface **110** may include a female connector and the communication device **116** may include a male connector, wherein the connectors physically engage and physically connect electrodes.

[0024] The console **112** further includes a transducer controller **118**. The transducer controller **118** controls excitation of the at least one transducer element **108**. The transducer controller **118** also controls detection of echoes with the at least one transducer element **108**. The console **118** further includes an ultrasound processor **120** that processes detected echoes. Such processing may include generating an image, estimating flow velocity, and/or processing. A memory device **121** stores saved images.

[0025] The console **112** further includes an interface **124**, which is a unidirectional interface in the illustrated embodiment. The console **112** utilizes the interface **124** to transmit information to an apparatus. For example, the console **112** can transmit images through the interface **124**. In a variation, the interface **124** can be a bidirectional interface in that the interface **124** can receive information from the apparatus. Generally, the apparatus is a remote or separate apparatus (such as a display monitor) that is not part of the console **112**.

[0026] The console **112** further includes an interface **126**, which is a bidirectional interface. The console **112** utilizes the interface **126** to interact with an input/output (I/O) device, including transmitting information to and receiving information from the I/O device. In one instance, this includes transmitting one or more images to the I/O device and receiving control information from the I/O device. Generally, the I/O device can be part of the console **112** and includes a user interface with controls and a display that allows an operator to control the scanner **102** and view images.

[0027] The ultrasound imaging system **102** further includes a display monitor **122**. The display monitor **122** can be a cathode ray tube (CRT), a liquid crystal display (LCD), a light emitting diode (LED), and/or other display monitor. The display monitor **122** includes a display region **124**, which can visually present images and/or flow velocity information generated by the ultrasound processor **120**. The display monitor **122** includes an interface **128**, which is complementary to the interface **124**. The interfaces **128** can include physical connectors and/or a wireless receiver.

[0028] In the illustrated embodiment, the display monitor **122** is affixed to a support **123**. The support can be, for example, a stand that rests on a surface and holds the display monitor **122** in a generally upright position such that an observer can view images displayed thereby. In another instance, the support **123** can be a wall bracket that mounts to a wall, thereby indirectly mounting the display monitor **122** to a wall. Other supports are also contemplated herein. The support **123** may be configured to rotate, tilt, translate, and/or otherwise move, which selectively allows for spatially orienting the region **124**.

[0029] The ultrasound imaging system **102** further includes a touch screen keyboard **130**. The touch screen keyboard **130**

includes at least controls **132**, indicators **134**, and an image display region **136**. The touch screen keyboard **130** further includes an interface **138**, which is complementary to the interface **126**. The interfaces can include physical connectors and/or a wireless transceiver. In a configuration in which the touch screen keyboard **130** is part of the console **112**, the interfaces **138** and **126** may alternatively be an internal connection such as a backplane, etc., and/or other connection.

[0030] In the illustrated embodiment, at least a sub-portion of the touch screen keyboard **130** includes a touch panel, in which predetermined active regions thereof evoke actions (e.g., through control signals) in response to being actuated by simple or multi-touch gestures of the screen with one or more fingers, a stylus, a glove, etc. The sub-portion may include sub-portions of one or more of the controls **132**, the indicators **134**, and the image display region **136**. For example, sliding of two fingers together across the touch screen keyboard **130** over an image displayed in the image display region **136** may invoke generation of a zoom out control signal in connection with the displayed image.

[0031] An example of a suitable touch panel is described in application Ser. No. 13/748,653, filed on Jan. 24, 2013, and entitled "Ultrasound Imaging System," which is incorporated herein by reference in its entirety. As such the touch panel may include a resistive, capacitive, acoustic, infrared, optical, piezoelectric, and/or other panel. Furthermore, the touch panel may include a liquid crystal display (LCD), thin film transistor liquid crystal display (TFT LCD), organic light-emitting diode (OLED), and/or other display.

[0032] A display controller **140** at least controls the information visually presented on with display monitor **122**. By way of example, in one non-limiting instance, actuation of one of the predetermined regions of the touch panel sub-regions of the touch screen keyboard **130** sends controls signals to the display controller **140**, and the display controller **140** displays and/or controls display of an image displayed in the image display region **124** of the display monitor **122**. As described in greater detail below, this may include presenting an initial image for display, removing a displayed image, replacing a displayed image with a different image, and/or other visualization based feature.

[0033] One or more of the components of FIG. 1 can be implemented via a computer processor executing computer readable instructions stored on computer readable storage medium (which exclude transitory medium). Additionally or alternatively, at least one of the computer readable instructions is carried by a signal, a carrier wave and/or other transitory medium.

[0034] FIGS. 2 and 3 show an example in which one of a plurality images displayed in the image display region **136** of the touch screen keyboard **130** is identified and displayed in the image display region **124** of the display monitor **122**.

[0035] Initially referring to FIG. 2, a plurality of images **202** are displayed, for example, as thumb nails, with an image of the plurality of images **202** at a position **204** displayed in a larger size relative to the other positions. The plurality of images **202** can be scrolled through by moving the plurality of images **202** one or more positions to the right or to the left. This can be achieved through swiping a suitable object (e.g., a stylus, a finger, etc.) across the plurality of images **202** in a direction of interest (left or right).

[0036] In another instance, this can be achieved by tapping or pressing an active region of the touch screen keyboard **130** in which each tap or press moves the plurality of images **202**

one or more positions to the left or one or more positions to the right. In yet another example, this can be achieved by actuating an active region of the touch screen keyboard **130** that invokes automatic scrolling (left or right). Other approaches for scrolling through the images **202** are contemplated herein.

[0037] In a variation, more than one of the plurality of images **202** is displayed at a larger size relative to the other positions. In another variation, all of the plurality of images **202** is displayed at a same size. In another variation, the plurality of images **202** is displayed in a vertical manner, a diagonal manner, or otherwise instead of a horizontal manner, as shown in FIG. 2. Six images are shown in the illustrated example. It is to be understood that more or less images can be displayed.

[0038] Turning to FIG. 3, an object **302** (a finger in this example) identifies an image **202_i** of the plurality of images **202** for display in the image display region **124** of the display monitor **122**. In the illustrated embodiment, this is achieved by dragging the image **202_i** in a direction of the image display region **124** of the display monitor **122**, e.g., from a border region of the image **202_i**. Although the bottom border is shown, the image **202_i** can be dragged from a side or top border. Other approaches are also contemplated herein.

[0039] The particular image displayed in the image display region **124** of the display monitor **122** can be changed by dragging another image to the image display region **124** of the display monitor **122**. In a variation, the displayed image **202_i** can be removed by dragging the image in the touch screen keyboard in the opposite direction, or away from the image display region **124**. Similar to the initial display, the object **302** drags the image from a border region of the image **202**.

[0040] In FIG. 4, a pointer **402** is created for the image display region **124** of the display monitor **122** by pressing with the object **302** within the border of the image displayed in the image display region **136** of the touch screen keyboard **130**. The pointer **402** can be moved, for example, to point to a particular part of the image, by moving the object **302** over the image display region **136** of the touch screen keyboard **130** while maintaining depression of the object within the border.

[0041] Other visualization features can be activated using a similar approach. For example, to zoom in or zoom out of the image displayed in the image display region **124** of the display monitor **122**, the user, respectively, places two fingers on the touch screen keyboard **130** and slides the fingers within the border across the touch screen keyboard **130** away from each other or slides the fingers across the touch screen keyboard **130** towards each other.

[0042] For rotating the image, the user places two fingers on the touch screen keyboard **130** and slides their fingers through an arc in the direction of rotation of interest. For panning the image, the user places a finger on the touch screen keyboard **130** and slides their finger within the border along a line in the direction of interest. Other image manipulation features are also contemplated herein. Furthermore, two or more of these features can be concurrently activated.

[0043] As described herein, the display monitor **122** is affixed to the support **123** and can rotate, tilt, translate, and/or otherwise move with respect thereto. In FIG. 5, the display monitor **122** is rotated 90 degrees. Such motion is well-suited for turning the display monitor **122** so that the image displayed via the display monitor **122** is viewable to one or more observers, other than or including the person operating the ultrasound imaging system **102**, who can additionally or

alternatively see and manipulate the image via the image display region **136** of the touch screen keyboard **130**.

[0044] In FIG. 6, a plurality of images **602** are displayed, e.g., as thumb nails and can be scrolled through by moving the plurality of images **602** to the right or one position to the left by swiping the object (not shown for clarity) across the plurality of images **602** in a direction of interest, as described herein and/or otherwise. In this example, the touch screen keyboard **130** also includes an image save active region **604** and an image delete active region **606**.

[0045] With respect to FIGS. 6 and 7, the object (not shown for clarity) is used to identify an image **702_i** to be saved, similar to identifying an image for display. In the illustrated embodiment, this is achieved by dragging, via swiping (indicated by arrow **704**), the image **702_i** from its border to the image save active region **604** of the touch screen keyboard **130** and then removing the object from the touch screen keyboard **130**. Other approaches are also contemplated herein.

[0046] With respect to FIGS. 6 and 8, the object (not shown for clarity) is used to identify an image **802_i** to be saved, similar to identifying an image for display and/or saving. In the illustrated embodiment, this is achieved by dragging, via swiping (indicated by arrow **804**), the image **802_i** from its border to the image delete active region **606** of the touch screen keyboard **130** and then removing the object from the touch screen keyboard **130**. Other approaches are also contemplated herein.

[0047] FIGS. 9, 10 and 11 illustrate example methods in accordance with the embodiments described herein.

[0048] It is to be appreciated that the order of the following acts is provided for explanatory purposes and is not limiting. As such, one or more of the following acts may occur in a different order. Furthermore, one or more of the following acts may be omitted and/or one or more additional acts may be added.

[0049] FIG. 9 illustrates a method for displaying an image in an image display region of a display monitor via identifying the image in an image display region of a touch screen keyboard, which is a separate device with respect to the display monitor.

[0050] At **902**, a sub-set of a plurality of images is displayed in an image display region of a touch screen keyboard of an ultrasound imaging system.

[0051] At **904**, optionally, one or more different sub-sets of the plurality of images are successively displayed by scrolling through the plurality of images, as described herein and/or otherwise.

[0052] At **906**, an image of interest of the plurality of images is identified for display in an image display region of a display monitor, which is a separate device, relative to the touch screen keyboard.

[0053] At **908**, the identified image of interest is displayed in the image display region of the display monitor, as described herein, for example, by swiping across the image displayed on the touch screen keyboard in a direction toward the display monitor.

[0054] At **910**, optionally, the identified image of interest is removed from image display region of the display monitor, as described herein, for example, by swiping across the image displayed on the touch screen keyboard in a direction away from the display monitor.

[0055] At 912, optionally, another image is identified via the touch screen keyboard and displayed in the image display region of the display monitor.

[0056] At 914, optionally, the displayed image of interest is replace with another image of interest, as described herein, for example, by swiping across the image displayed on the touch screen keyboard in the direction of the display monitor.

[0057] FIG. 10 illustrates a method for manipulating an image displayed in an image display region of a display monitor via an image display region of a touch screen keyboard, which is a separate device with respect to the display monitor.

[0058] At 1002, a sub-set of a plurality of images is displayed in an image display region of a touch screen keyboard of an ultrasound imaging system.

[0059] At 1004, optionally, one or more different sub-sets of the plurality of images are successively displayed by scrolling through the plurality of images.

[0060] At 1006, an image of interest of the plurality of images is identified for display in an image display region of a display monitor, which is a separate device with respect to the touch screen keyboard.

[0061] At 1008, the identified image of interest is displayed in the image display region of the display monitor, as described herein.

[0062] At 1010, the identified image of interest is manipulated (e.g., rotated, panned, zoomed, etc.) in the image display region of the display monitor, as described herein, for example, by manipulating the corresponding image displayed on the touch screen keyboard.

[0063] FIG. 11 illustrates a method for saving or deleting an image displayed in an image display region of a touch screen keyboard.

[0064] At 1102, a sub-set of a plurality of images is displayed in an image display region of a touch screen keyboard of an ultrasound imaging system.

[0065] At 1104, optionally, one or more different sub-sets of the plurality of images are successively displayed by scrolling through the plurality of images.

[0066] At 1106, an image of interest of the plurality of images is identified. At 1108, the identified image of interest is saved or deleted by swiping across the image displayed on the touch screen keyboard in a direction towards a save active region of the touch screen keyboard or a delete active region of the touch screen keyboard.

[0067] At least a portion of the methods discussed herein may be implemented by way of computer readable instructions, encoded or embedded on computer readable storage medium (which excludes transitory medium), which, when executed by a computer processor(s), causes the processor(s) to carry out the described acts. Additionally or alternatively, at least one of the computer readable instructions is carried by a signal, carrier wave or other transitory medium.

[0068] The application has been described with reference to various embodiments. Modifications and alterations will occur to others upon reading the application. It is intended that the invention be construed as including all such modifications and alterations, including insofar as they come within the scope of the appended claims and the equivalents thereof.

What is claimed is:

1. An ultrasound imaging system, comprising:

at least one transducer element;

a console, including: a transducer controller that controls the at least one element; a transducer processor that

processes information detected by the at least one element, and a display controller that controls display of the processed information;

a display monitor, including: a first image display region; and

a touch screen keyboard, including: at least a second image display region, wherein the display monitor and the touch screen keyboard are separate devices.

2. The ultrasound imaging system of claim 1, wherein the display controller displays a sub-set of a plurality of images in the second image display region.

3. The ultrasound imaging system of claim 2, wherein the display controller displays a different sub-set of the plurality of images in the second image display region.

4. The ultrasound imaging system of claim 3, wherein the display controller displays the different sub-set of the plurality of images in the second image display region in response to receiving a first signal from the touch screen keyboard.

5. The ultrasound imaging system of claim 1, wherein the display controller displays an identified one of the plurality of images in the first image display region.

6. The ultrasound imaging system of claim 5, wherein the display controller displays the identified one of the plurality of images in the first image display region in response to receiving a second signal indicating activation of an active region of the touch screen keyboard by an object moving across the identified one of the plurality of images in a first direction over the second image display region.

7. The ultrasound imaging system of claim 6, wherein the display controller removes the displayed identified one of the plurality of images from the first image display region.

8. The ultrasound imaging system of claim 7, wherein the display controller removes the displayed identified one of the plurality of images in the first image display region in response to receiving a third signal indicating activation of an active region of the touch screen keyboard by the object moving across the identified one of the plurality of images in an opposite direction.

9. The ultrasound imaging system of claim 6, wherein the display controller replaces the displayed identified one of the plurality of images with a second identified one of the plurality of images.

10. The ultrasound imaging system of claim 7, wherein the display controller displays the replaced identified one of the plurality of images in response to receiving a fourth signal indicating activation of the active region of the touch screen keyboard by the object moving across the second identified one of the plurality of images in the first direction over the second image display region.

11. A method, comprising:

receiving a first signal from a touch screen keyboard of an ultrasound imaging system indicating one of a plurality of images to display with a display monitor of the ultrasound imaging system, wherein the touch screen keyboard and the display monitor are separate devices; and displaying the one of the plurality of images with the display monitor.

12. The method of claim 11, further comprising:

moving an object from a boundary of the one of the plurality of images displayed with the touch screen keyboard in a first direction, thereby generating the first signal.

13. The method of claim **11**, further comprising:
receiving a second signal from the touch screen keyboard indicating removal of the one of the plurality of images from the display monitor; and
removing the one of the plurality of images from the display monitor.

14. The method of claim **13**, further comprising:
moving the object from the boundary of the one of the plurality of images displayed with the touch screen keyboard in a second different direction, thereby generating the second signal.

15. The method of claim **11**, further comprising:
receiving a third signal from the touch screen keyboard indicating replacing the one of the plurality of images displayed with the display monitor with another one of the plurality of images; and
replacing the one of the plurality of images with the other one of the plurality of images in the display monitor.

16. The method of claim **15**, further comprising:
moving the object from the boundary of the one of the plurality of images displayed with the touch screen keyboard in the first direction, thereby generating the third signal.

17. The method of claim **11**, further comprising:
receiving a fourth signal from the touch screen keyboard indicating rotating the one of the plurality of images displayed with the display monitor; and
rotating the one of the plurality of images based on the fourth signal.

18. The method of claim **17**, further comprising:
rotating the object over the one of the plurality of images displayed with the touch screen keyboard in a rotation direction of interest, thereby generating the fourth signal.

19. The method of claim **11**, further comprising:
receiving a fifth signal from the touch screen keyboard indicating a zoom factor for the one of the plurality of images displayed with the display monitor; and
zooming the one of the plurality of images based on the fifth signal.

20. The method of claim **19**, further comprising:
moving the object over the one of the plurality of images displayed with the touch screen keyboard to identify a zoom factor of interest, thereby generating the fifth signal.

21. The method of claim **11**, further comprising:
receiving a sixth signal from the touch screen keyboard indicating panning the one of the plurality of images displayed with the display monitor; and
panning the one of the plurality of images based on the sixth signal.

22. The method of claim **21**, further comprising:
moving the object over the one of the plurality of images displayed with the touch screen keyboard to identify a pan direction of interest, thereby generating the sixth signal.

23. The method of claim **11**, further comprising:
receiving a seventh signal from the touch screen keyboard indicating a location of a moveable pointer for the one of the plurality of images displayed with the display monitor; and
placing the moveable pointer at the location based on the seventh signal.

24. The method of claim **23**, further comprising:
depressing, with the object, within a border of the one of the plurality of images displayed with the touch screen keyboard to identify the location, thereby generating the seventh signal.

25. The method of claim **24**, further comprising:
translating, with the object, over the object and within the border, to identify a next location, thereby updating the seventh signal.

26. A computer readable storage medium encoded with computer readable instructions which, when executed by a computer processor, cause the computer processor to:
display, in an image display region of a display monitor of an ultrasound imaging system, an image from a set of images displayed in an image display region of a touch screen keyboard based on a signal from the touch screen keyboard indicative of an image of interest, wherein the touch screen keyboard and the display monitor are separate devices.

* * * * *

专利名称(译)	超声成像系统图像识别和显示		
公开(公告)号	US20140364731A1	公开(公告)日	2014-12-11
申请号	US13/913580	申请日	2013-06-10
[标]申请(专利权)人(译)	B-K医疗公司		
申请(专利权)人(译)	B-k医疗APS		
当前申请(专利权)人(译)	B-k医疗APS		
[标]发明人	KANN PETER ULRIK		
发明人	KANN, PETER ULRIK		
IPC分类号	A61B8/00 A61B8/08		
CPC分类号	A61B8/463 A61B8/4472 A61B8/54 A61B8/5207 A61B8/4483 A61B8/469 A61B8/4455 A61B8/461 A61B8/467		
其他公开文献	US10226230		
外部链接	Espacenet USPTO		

摘要(译)

超声成像系统包括至少一个换能器元件。超声成像系统还包括控制台，其具有控制至少一个元件的换能器控制器，处理由至少一个元件检测的信息的换能器处理器，以及控制处理的信息的显示的显示控制器。超声成像系统还包括具有第一图像显示区域的显示监视器。超声成像系统还包括具有第二图像显示区域的触摸屏键盘，其中显示监视器和触摸屏键盘是单独的设备。

