




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7

METHOD AND APPARATUS FOR PERFORMING ULTRASOUND ELEVATION COMPOUNDING

BACKGROUND OF THE INVENTION

[0001] The subject matter disclosed herein relates generally to ultrasound systems, and more particularly, to methods and systems for performing spatial and elevation compounding using an ultrasound system.

[0002] Ultrasound imaging is a medical imaging technique for imaging organs and soft tissues in a human body. Ultrasound imaging uses real time, non-invasive high frequency sound waves to produce a two-dimensional (2D) image and/or a three-dimensional (3D) image. In conventional ultrasound imaging, the image is acquired by a series of scan lines. This results in an image in which some anatomical structures may be “shadowed” by objects closer to the transducer and diagonal structures may not be optimally imaged. Typically, when the boundaries of anatomical structures are parallel to the transducer, the acoustic waves reflect directly back to the transducer with less dispersion and a clear image is obtained. However, diagonal or vertical structures are sub-optimally imaged using conventional ultrasound because of the lower percentage of acoustic energy that reflects back to the transducer. Furthermore, structures that are hidden beneath strong reflectors are also sub-optimally imaged. For example, a small breast cyst may be hidden behind muscular tissue (e.g., tendons), which is a strong superficial reflector.

[0003] In addition, another disadvantage of conventional ultrasound imaging is speckle noise. Speckle noise is a result of interference of scattered echo signals reflected from an object, such as an organ. The speckle appears as a granular grayscale pattern on an image. The speckle noise degrades image quality (e.g., speckles obtained from different angles are incoherent) and increases the difficulty of discriminating fine details in images during diagnostic examinations.

[0004] At least some known ultrasound systems are capable of spatially compounding a plurality of ultrasound images of a given target into a compound image. The term “compounding” generally refers to non-coherently combining multiple data sets to create a new single data set. The plurality of data sets may each be obtained from imaging the object from different angles, using different imaging properties (such as e.g. aperture, frequency) and/or imaging nearby objects (such as slightly out of the plane steering). These compounding techniques can be used independently or in combination to reduce speckle and improve image quality.

[0005] The plurality of data sets or steering frames are combined to generate a single view or compound image by combining the data received from each point in the compound image target that has been received from each compound frame. A transducer array may be utilized to implement electronic beam steering and/or electronic translation of the component frames. The component frames are combined into a compound image by summation, averaging, peak detection, or other combinational means. The compounded image may display relatively lower speckle and better specular reflector delineation than a non-spatially compounded ultrasound image.

BRIEF DESCRIPTION OF THE INVENTION

[0006] In one embodiment, a method for generating a spatially compounded image is provided. The method includes

acquiring ultrasound image information from a first scan plane, acquiring ultrasound information from a second scan plane where the offset between the scan planes is varied as a function of depth, and combining the information from the first and second scan planes to generate a two-dimensional (2D) compounded image.

[0007] In another embodiment, an ultrasound system for generating a spatially compounded image is provided. The system includes an ultrasound probe for transmitting and receiving ultrasound signals to and from an area of interest, a receiver for receiving the ultrasound signals, and a processing unit coupled to the ultrasound probe. The processing unit is programmed to acquire ultrasound image information from a first scan plane, acquire ultrasound information from a second scan plane where the offset between the planes is varied as a function of depth, and combine the information from the first and second scan planes to generate a two-dimensional (2D) compounded image.

[0008] In a further embodiment, a non-transitory computer readable medium for generating a spatially compounded image is provided. The computer readable medium is programmed to instruct a processing unit to acquire ultrasound image information from a first scan plane, acquire ultrasound information from a second scan plane where the offset between the planes is varied as a function of depth, and combine the information from the first and second non-linear scan planes to generate a two-dimensional (2D) compounded image.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1 is a block diagram of an exemplary ultrasound system formed in accordance with various embodiments.

[0010] FIG. 2 illustrates a block diagram of an exemplary method of generating an image in accordance with various embodiments.

[0011] FIG. 3 is an exemplary set of scan planes formed in accordance with various embodiments.

[0012] FIG. 4 is a side view of the scan planes shown in FIG. 3.

[0013] FIG. 5 is another exemplary set of scan planes formed in accordance with various embodiments.

[0014] FIG. 6 is a side view of the scan planes shown in FIG. 5.

[0015] FIG. 7 illustrates a plurality of exemplary scan planes formed in accordance with various embodiments.

DETAILED DESCRIPTION OF THE INVENTION

[0016] In the following detailed description, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration specific embodiments in which the present invention may be practiced. It is to be understood that the embodiments may be combined, or that other embodiments may be utilized and that structural, logical and electrical changes may be made without departing from the scope of the various embodiments of the present invention. The following detailed description is, therefore, not to be taken in a limiting sense, and the scope of the present invention is defined by the appended claims and their equivalents.

[0017] In this document, the terms “a” or “an” are used, to include one or more than one. In this document, the term “or” is used to refer to a nonexclusive or, unless otherwise indi-

cated. In addition, as used herein, the phrase “pixel” also includes embodiments of the present invention where the data is represented by a “voxel”. Thus, both the terms “pixel” and “voxel” may be used interchangeably throughout this document.

[0018] Also as used herein, the phrase “reconstructing an image” is not intended to exclude embodiments of the present invention in which data representing an image is generated, but a viewable image is not generated. Therefore, as used herein, the term “image” broadly refers to both viewable images and data representing a viewable image. However, many embodiments generate (or are configured to generate) at least one viewable image. In addition, as used herein, the phrase “image” is used to refer to an ultrasound mode such as B-mode, CF-mode and/or sub-modes of CF such as TVI, Angio, B-flow, BMI, BMI_Angio, and in some cases also MM, CM, PW, TVD, CW where the “image” and/or “plane” includes a single beam or multiple beams.

[0019] Further, the term processor or processing unit, as used herein, refers to any type of processing unit that can carry out the required calculations needed for the invention, such as single or multicore: CPU, Graphics Board, DSP, FPGA or a combination.

[0020] FIG. 1 illustrates a block diagram of an ultrasound system **100** formed in accordance with various embodiments. The ultrasound system **100** includes a transmitter **102** which drives an ultrasound probe **104**. The probe **104** may include a 1.75D array, a 2D array and the like. In operation, the probe **104** has the ability to do some degree of steering perpendicular to the scan plane direction. In the exemplary embodiment, the probe **104** is embodied as a two dimensional (2D) array of elements that can steer a beam in the desired spatial direction. The probe **104** includes a transmit group of elements **106** and a receive group of elements **108**, that normally constitute the same elements. A transmit beamformer **110** controls the transmitter **102** which, through a transmit sub-aperture beamformer **114**, drives the group of transmit elements **106** to emit ultrasonic transmit signals into a region of interest (e.g., human, animal, underground cavity, physical structure and the like). The transmitted ultrasonic signals are back-scattered from structures in the object of interest, like blood cells, to produce echoes which return to the group of receive elements **108**. The echoes are received by the receive elements **108** and may include undesirable speckle (e.g., interference caused by scattered echo signals reflected from the region of interest).

[0021] The receive group of elements **108** convert the received echoes into analog signals, undergo sub-aperture beamforming by a receive sub-aperture beamformer **116** and are then passed to a receiver **118**. The output of the receiver **118** is communicated to a receive beamformer **120**, which performs additional beamforming operations and outputs an RF signal. The ultrasound system **100** may include a plurality of A/D converters **122** that are disposed between the receiver **118** and the receive beamformer **120** to illustrate that the incoming received signals may be converted from analog to digital form at the front end of the receive beamformer **120** (such as in analog beamformer).

[0022] The receiver **118** and the beamformer **120** may be combined into a single beamformer which may be digital. The RF signals are then provided to an RF processor **124**. The RF processor **124** may include a complex demodulator (not shown) that demodulates the RF signals to form IQ data pairs representative of the echo signals. The RF or IQ signal data

may then be routed directly to an RF/IQ buffer **126** for temporary storage. A user input **130** may be used to input patient data, scan parameters, a change of scan mode, and the like. The herein described transmit and receive beam forming is an example and it can be differently distributed between the system part (**102**, **110**, **118**, **120**, **122**, **124**) and the probe (**104**).

[0023] The ultrasound system **100** also includes a processing unit **132** to process the acquired ultrasound information (i.e., RF signal data or IQ data pairs) for presentation on a display system **134**. The processing unit **132** is adapted to perform one or more processing operations (e.g., compounding) according to a plurality of selectable ultrasound modalities on the acquired ultrasound information. Acquired ultrasound information may be processed in real-time during a scanning session as the echo signals are received. Additionally or alternatively, the ultrasound information may be stored temporarily in the RF/IQ buffer **126** during a scanning session and processed in less than real-time in a live or off-line operation.

[0024] The ultrasound system **100** may continuously acquire ultrasound information at a frame rate that is suitable for the imaging situation in question. Typical frame rates range from 20-70 but can be lower or higher. The acquired ultrasound information is displayed on the display system **134** at a display-rate that can be the same as the frame rate, or slower or faster. An image buffer **136** is included for storing processed frames of acquired ultrasound information that are not scheduled to be displayed immediately. Preferably, the image buffer **136** is of sufficient capacity to store at least several seconds worth of frames of ultrasound information. The frames of ultrasound information are stored in a manner to facilitate retrieval thereof according to its order or time of acquisition. The image buffer **136** may be embodied as any known data storage medium.

[0025] In the exemplary embodiment, the processing unit **132** may include a spatial compounding module **140**. The spatial compounding module **140** is configured to combine a plurality of steering frames corresponding to a plurality of different angles to produce a compound image. The spatial compounding module **140** is configured to control the steering of the ultrasound signals generated by the plurality of transducer elements **106/108** to multiple angles, and may also control the steering of the ultrasound signals generated by the plurality of transducer elements **106/108** to a plurality of angles as discussed in more detail below.

[0026] FIG. 2 is a flowchart of an exemplary method **200** of generating a spatially compounded image using a plurality of images acquired at different imaging planes. Spatial compounding is an imaging technique in which a number of echo signals from a number of adjacent imaging planes are combined. Elevation compounding is discussed in more detail below. The multiple directions help achieve speckle decorrelation. It should be noted that although the method **200** is described in connection with ultrasound imaging having particular characteristics, the various embodiments are not limited to ultrasound imaging or to any particular imaging characteristics.

[0027] At **202**, and also with reference to FIGS. 3 and 4, the probe **104** is utilized to scan a first scan plane **250**. In the exemplary embodiment, the scan planes, such as the first scan plane **250**, are acquired based on scan parameters that are entered by the operator, from the system, or a combination of the two. The scan parameters may include, for example, a

quantity of scan planes to be collected and the degree of spacing between the scan planes as a function of depth. In operation, the scan planes are collected for a thickness, such as from a group or set of adjacent scan planes that are mutually separated by a distance that varies with depth.

[0028] In the exemplary embodiment, the probe 104 is utilized to perform a sector scan by scanning the fan-shaped plane 250. The sector scan can have any spatial direction that can be realized with the probe 104. The sector scan scans a region 260 along a direction of the angle θ and along an acoustic beam 262 extending from an emission point 264 to a depth 266, the emission point 264 representing the proximal end of the scan plane and the depth 266 representing the distal end of the scan plane. Beam 262 is drawn as the edge beam of the sector scan, but may represent any beam within the plane 250. Further a scan plane 252 is a sector scan that scans a region 260 along a direction of the angle θ and along an acoustic beam 272 that are drawn as the edge beam of the scan sector, but which may represent any beam within the plane 252. The difference between plane 250 and 252 is that they have an offset in a direction that is mainly perpendicular to the main plane direction and the reference plane 270 which illustrates the result plane from compounding the planes 250 and 252. If the planes 250 and 252 had been planar, e.g. straight two dimensional planes with a fixed angular offset, the result would have been what is known as standard elevation compounding.

[0029] In the exemplary embodiment, elevation compounding is improved by optimizing the distance, or angular offset, between the pluralities of planes that are compounded, as a function of depth. This is illustrated for two planes by D_1 at 280, D_2 at 282 and D_3 at 284 that show how the plane spacing may vary as a function of depth. Variation of depth, in this context, means that they are not all identical and they are not related by their depth times a fixed angle between the planes (which would be the case for straight planes with an fixed angular offset). To obtain such a variation in the plane spacing as a function of depth the transmit and/or receive elements 106/108 must be steered to acquire non-straight beams. The planes 250/252 are non-planar as they are built up from the non-straight beams 262/272.

[0030] In this exemplary embodiment two mirror symmetrical planes 250/252 are shown. With symmetrical compounding weights the resulting plane 270 will be planar, but this is not a requirement for the scope of various embodiments. In other embodiments three, four, five or more planes can be used. For odd numbers of planes, the center plane is preferably kept planar and other planes are non-planar to realize the mutual distances that vary with depth, but also a non-planar center plane is within the scope of various embodiments.

[0031] In the preferred embodiment the adjacent beams in the plurality of adjacent planes are acquired using multiline acquisition. The corresponding beams 262/272 in the adjacent planes 250/252 are acquired with the same shot to increase frame rate. In another embodiment the adjacent planes are acquired independently or a combination of multiline and independent acquisition.

[0032] Various embodiments may be used in conjunction with all probes that can do some degree of steering in a direction that is perpendicular to the scan plane. This steering can be realized electronically and/or mechanically. This applies for phased arrays, curved arrays, linear arrays and is independent of the application in question. It can further be

used in conjunction with sector scans, curved scans, linear scans, virtual apex scans and any other scan geometry as long as out-of-the plane steering is utilized to acquire the plurality of compound planes.

[0033] At 204, the probe 104 is utilized to scan the second scan plane 252. At 206, the images derived at 202 and 204 are spatially combined to form a first 2D or 3D image. In the exemplary embodiment, the second scan plane 252 is also a non-linear scan plane such as the first scan plane 250. The second scan plane 252 is also acquired based on scan parameters that are entered by the operator. The scan parameters may include, for example, a quantity of scan planes to be collected, and/or an angular distance between scan planes. As such, various embodiments can be "repeated" for multiple planes. In a preferred embodiment it is used for each of the planes in multi plane acquisition in 3D. Here a plurality of planes are acquired for a set of spatial directions in space and a plurality of compound planes are acquired for each of these in accordance with the described embodiments. In another embodiment the elevational compounding is used to enhance each of the planes in standard spatial compounding, where each of the planes with different imaging angles are acquired as a plurality of planes in accordance with the described embodiment.

[0034] As discussed above, the distance between the elevation planes 300 and 302 is varied with depth to optimize image quality. More specifically, the probe 104 is configured to acquire the acoustic beams 262 such that the resulting scan plane 250 is non-planar due to variable steering respect to the common axis 254. More specifically, while the scan plane 250 is generally fan shaped, the surface of the scan plane 250 is non-planar, between the emission point 264 and the depth 266 of the scan plane 250, referred to herein as the elevation of the scan plane. The acoustic beams 262 may be steered by controlling the shape of the ultrasound signals generated by the transmit and receive elements 106/108. Specifically, the transmit and receive elements 106/108 may be electronically steered at different angles to transmit and receive the non-straight acoustic beams 262.

[0035] FIG. 4 is a side view of the first scan plane 250 and the second scan plane 252. In the exemplary embodiment, the spatial and elevation compounding module 140 identifies the thickness, i.e. elevation, of a slice to be created from the scan planes 250 and 252. The slice thickness defines the distance between the scan planes 250 and 252. In the exemplary embodiment, because the planes 250 and 252 are normally non-linear, there is a slight elevational offset between the planes 250 and 252, in a direction 276 that is perpendicular to the main imaging direction of the planes 250 and 252, which is varied in some embodiments. For example, as shown in FIG. 4, the planes 250 and 252 are offset from each other by a distance D_1 at an elevation point 280 that is proximate to the emission point 264. The planes 250 and 252 are offset from each other by a distance D_2 that is larger than D_1 , at an elevation point 282 that is midway between the emission point 264 and the point of depth 266. Moreover, the planes 250 and 252 are offset from each other by a distance D_3 , that is less than D_2 , at an elevation point 284 that is proximate to the point of depth 266. Accordingly, in some embodiments, the thickness of the slab defined by the planes 250 and 252 diverges from the point 280 to the point 282 and converges from the point 282 to the point 284 such that the planes 250 and 252 are non-planar between the emission point 264 and

the depth 266, to enable a thicker, and/or thinner, slab of the region of interest to be used to generate a 2D image.

[0036] In the exemplary embodiment, the offset or distance between the planes 250 and 250 are therefore controlled as a function of the depth 266 of the imaging plane which affects the correlation between the acquired images. More specifically, a smaller distance between the planes 250 and 252, such as D1 and D3, provides a relatively high degree of correlation for specular reflectors. The distances D1 and D3 may be for example, on the order of one-half of the beam width to achieve significant speckle decorrelation between the planes 250 and 252. Whereas, a larger distance between the planes 250 and 252, such as D3, provides a lower degree of correlation for speckle and noise. Specifically, correlation of specular reflectors are desired, while speckle and noise should be de-correlated. Accordingly, the offset between the planes 250 and 252 may be tuned to enhance the imaged structures and suppress noise and speckle. In the exemplary embodiment, the beam width is varied as a function of depth to control the spacing between the planes 250 and 252. Moreover, in the case where the vectors of adjacent planes are acquired during a single transmit event, using multiline acquisition (MLA) for example, large spacing facilitates reducing penetration due to reduced overlap between the transmit and receive beams. Therefore, the planes 250 and 252 may be positioned closer together to regain penetration.

[0037] FIG. 5 is another exemplary set of scan planes formed in accordance with various embodiments. In the exemplary embodiment, the offset or distance between the planes 300 and 302 are controlled as a function of the depth of the imaging plane which affects the correlation between the acquired images. The scan parameters also include a spatial offset that defines a spatial distance between two adjacent scan planes, such as scan planes 250 and 252. In the exemplary embodiment, to form the spatial offset the transmit and receive elements 106/108 may be steered at different angles. The first plane 300 is spatially offset from the second plane 302 by an angle α . More specifically, the first plane 300 is scanned at a first angular direction and the second plane 203 is scanned at a second different angle but along a same axis 274. The difference between the angles represents the angle α . It should be realized that although the exemplary embodiment illustrates two scan planes 300 and 302, various embodiments may utilize more than two scan planes to form a spatially compounded image. The sector scan used to scan the planes 300 and 302 may be performed, for example, by steering the receive elements 106 as discussed above. When the offset between the compounding planes are controlled as a function of depth and will affect the correlation between the acquired images. Small spacing will give high degree of correlation while large spacing will give lower degree of correlation. Correlations of specular reflectors are desired, while one wants speckle and noise to de-correlate. The spatial offset must be properly tuned to enhance the imaged structures and suppress noise and speckle. Since beam width vary with depth it is important to control the plane spacing as a function of depth to get an optimal result. Further, in the case where the vectors of adjacent planes are acquired during a single transmit event using multiline acquisition, spacing between the beams and/or planes will reduce penetration due to reduced overlap between the transmit beam and the receive beams. In this case one can reduce the offset between the planes to regain penetration.

[0038] FIG. 6 is a side view of the scan planes 300 and 302. In the exemplary embodiment, the spatial and elevation compounding module 140 identifies the thickness, i.e. elevation, of a slice to be created from the scan planes 300 and 302. In the exemplary embodiment, because the planes 300 and 302 are non-planar there is a slight elevational offset between the planes 300 and 302, in a direction 306 that is perpendicular to the main imaging direction of the planes 300 and 302. For example, as shown in FIG. 6, the planes 300 and 302 are offset from each other by a distance D4 at an elevation point 310 that is proximate to the emission point 264. The planes 300 and 302 are offset from each other by a distance D5, that is larger than D4, at an elevation point 312. The planes 300 and 302 are offset from each other by a distance D6, that is smaller than D5, at an elevation point 314. The planes 300 and 302 are offset from each other by a distance D7, that is larger than D6, at an elevation point 316. Moreover, the planes 300 and 302 are offset from each other by a distance D8, that is less than D7, at an elevation point 318. Accordingly, in some embodiments, the thickness of the slab defined by the planes 300 and 302 diverges from the point 310 to the point 312, converges from the point 312 to the point 314, converges from the point 314 to 316, and diverges from the point 316 to 318 to enable a thicker slab of the region of interest to be used to generate a 2D image.

[0039] The invention, as described herein, can be used for any imaging mode and a combination of imaging modes. The phrase "image" is thus used to refer to an ultrasound mode such as B-mode, CF-mode and/or sub-modes of CF such as TVI, Angio, B-flow, BMI, BMI Angio, and for other embodiments also MM, CM, PW, TVD, CW. Further, for B-mode the invention can be used in conjunction with any B-mode acquisition methods such as harmonic imaging, contrast imaging, pulse inversion, power modulation and coded excitation.

[0040] In the exemplary embodiment, the compounding of the plurality of planes can be done with fixed weights. In other embodiments one can use adaptive weights (for example based on a quality measure or image analysis) and/or on transformed data.

[0041] Referring again to FIG. 2, at 208, the ultrasound system 100 generates at least a second spatially and elevationally combined 2D image as described above in steps 202-206. In the exemplary embodiment, the ultrasound system 100 may acquire a series of spatially and elevationally combined 2D images using a multiplane acquisition scanning technique. More specifically, multiplane acquisition may be embodied as a biplane, a tri-plane, or N-plane scan that is specified by the user. The system 100 sets the angles, orientation, tilt, and the like for a given type of multiplane scan for the planes with respect to one another based on predefined default values or the user entered parameter values. For example, if the user designates bi-plane imaging, the user may then set parameter values for the angles of the planes to be 0 degrees and 90 degrees with respect to a base reference plane. Optionally, if the user designates tri-plane imaging, the user may then set parameter values for the angles of the planes to be 0 degrees, 60 degrees and 120 degrees with respect to a base reference plane.

[0042] For example, FIG. 7 illustrates a multi-plane image acquisition that may be performed by the imaging system 100. In the exemplary embodiment, the multi-plane image data shown in FIG. 7 includes two, sets of the scan planes 250 and 252 described above. However, it should be realized that the multi-plane image data may include two or more sets of

the scan planes **250** and **252**, two or more sets of the scan planes **300** and **302**, or two or more sets of any scan planes having a non-linear elevational profile. The multi-plane image data may be obtained from a current image scan or from previously obtained and stored data. In the exemplary embodiment, the multi-plane image data is acquired from a 3D ultrasound scan using two or more image planes. For example, as shown in FIG. 7, the image data may be obtained from a bi-plane image scan using two-planes **250** and **252**. In another embodiment, the image data may be obtained from a tri-plane image scan using three-planes (not shown). It should be noted that each of the scan planes **250** and **252** is a 2D scan plane. Additionally, it should be noted that the multi-plane image acquisition may be performed using any type of ultrasound probe and/or ultrasound imaging system as appropriate.

[0043] In some embodiments, such as in a bi-plane image acquisition implementation, the ultrasound information is acquired substantially simultaneously or consecutively within a short period of time (e.g. $\frac{1}{20}$ second) for the two differently oriented scan planes **250** and **252** or views. It should be noted that the spacing (e.g., angular rotation) between a first set **350** of scan planes **250** and **252** and a second set **352** of scan planes **250** and **252** may be the same or varied. For example, one data slice associated with the first set **350** of scan planes may correspond to an angle of 0 degrees, another data slice associated with the second set of scan planes **352** may correspond to an angle of 60 degrees, and a third set of scan planes (not shown) may correspond to an angle of 120 degrees, etc.

[0044] At **210**, a 2D combined image, a 3D combined image or other image may be formed from the image planes (e.g., individual planes of a multi-plane dataset). The sets of scan planes **350** and **352** may intersect at a common rotational axis **354** or, alternatively, intersect at different axes. Two slice images (e.g., 2D slices cut through a full volume 3D dataset) may be generated by image data acquired at the two sets of scan plane **350** and **352**, which are two views of the scan object at about the same point in time due to simultaneous acquisition of the scan data for the two sets of scan planes **350** and **352**. The two slice images may be, for example, of a patient's heart at a specific point in time of the heart beat or cycle. Alternatively, the three slice images may show continuous motion of a patient's heart while the heart beats. It should be noted that one or more of the sets of scan planes **350** and **352** may be tilted relative to a scanning surface of the ultrasound probe **104** (shown in FIG. 1). Additionally, the angular rotation between the sets of scan planes **350** and **352** may be changed or varied. It also should be noted that the sets of scan planes **350** and **352** may be acquired by mechanical or electronic steering of the ultrasound probe **104**. For example, in some embodiments, the ultrasound probe may include electronic steering means as is known that electronically steers a matrix array, as shown in FIG. 1, to acquire the image data corresponding to the sets of scan planes **350** and **352**. In another embodiment, the ultrasound probe **104** may include a mechanically movable scan head as is known that moves the array of elements **106/108** (shown in FIG. 1) to acquire image data (e.g., image planes) corresponding to the sets of scan planes **350** and **352**. In still other embodiments, a combination of mechanical and electronic steering as is known may be used. It should be noted that during acquisition of the sets of

scan planes **350** and **352**, the probe housing in various embodiments is not moved relative to the object being examined.

[0045] It also should be noted that more than two scan planes may be used to acquire image information. For example, three, four, five, six images (e.g., six image planes) may be generated at the six planes, which may be located, for example, equidistance from each other. However, the angular spacing between each of the scan planes may be varied. Accordingly, the number of apical planes may be increased using, for example, sequentially acquired multi-plane scan data by electronically rotating the scan angles. In some embodiments, multiple tri-plane acquisitions may be performed that are angularly rotated with respect to each other or a single acquisition having more than three scan planes may be performed. Thus, increased image resolution of, for example, the left ventricle of an imaged heart may be provided.

[0046] In the exemplary embodiment, at **212**, a weighting factor may be applied to the image formed at **210**. In the exemplary embodiment, relative weights are assigned to the areas where the planes overlap and do not overlap. For example, the same weighting factor may be applied to areas that overlap. Optionally, different weights may be assigned to each of the areas that do not overlap. By weighting the acquired scan data differently, speckle interference may be decreased, thereby improving image quality. In addition, weighting eliminates any detected motion prior to combining the plurality of steering frames into a compound image. Optionally, different levels of compounding may be used. For example, a high level of compounding (e.g., five or more image frames steered at large angles) may be used. Optionally, other applications may require no compounding or a lower level of compounding (e.g., three frame images and transducer elements steered at smaller angles). Therefore, in an embodiment, a plurality of default preset choices for different levels of compounding may be provided (e.g., no compounding, low compounding, high compounding).

[0047] In addition, the ultrasound system **100** provides for reducing interference caused by speckle noise. Speckle noise is an intrinsic property of ultrasound imaging, the existence of speckle noise in ultrasound imaging reduces image contrast and resolution. Accordingly at **214**, a speckle reduction filter is used to reduce speckle noise. The speckle reduction filter usually does not create motion artifacts, preserves acoustic shadowing, and enhancement. However, the speckle reduction filter may cause a loss of spatial resolution and reduce processing power of an ultrasound imaging system.

[0048] A speckle reduction filter (not shown), such as a low pass filter, may be utilized to reduce speckle noise in an image generated the ultrasound system **100**. An example of a low pass filter is a finite impulse response (FIR) filter. In an alternative embodiment, the speckle reduction filter is a mathematical algorithm that is executed by the processor **132** and that is used on a single image frame to identify and reduce speckle noise content. In yet another embodiment, the speckle reduction filter is a median filter, a Wiener filter, an anisotropic diffusion filter, or a wavelet transformation filter, which are mathematical algorithms executed by the processor **132**. In still another alternative embodiment, the speckle reduction filter is a high pass filter that performs structural and feature enhancement. An example of a high pass filter is an infinite impulse response (IIR) filter. In the median filter, a pixel value of an image generated using the ultrasound system

100 is replaced by a median value of neighboring pixels. The Wiener filter can be implemented using a least mean square (LMS) algorithm. The anisotropic diffusion filter uses heat diffusion equation and finite elements schemes. The wavelet transformation filter decomposes echo signals into a wavelet domain and obtained wavelet coefficients are soft-thresholded. In the soft-thresholding, wavelets with absolute values below a certain threshold are replaced by zero, while those above the threshold are modified by shrinking them towards zero. A modification of the soft thresholding is to apply non-linear soft thresholding within finer levels of scales to suppress speckle noise.

[0049] A technical effect of at least one embodiment is to utilize a spatial compounding technique to improve imaging by averaging different ultrasound images of different targets. The averaging is done to improve imaging of specular reflectors and to reduce speckle and noise in the resulting image. Additionally, the spatial compounding is done in combination with variable spacing (or angle) between the planes as a function of depth, referred to herein as elevation compounding. More specifically, when the spacing between planes is varied as a function of depth, the planes that are averaged are not planar any more. The control of the spacing allows optimization of the tradeoff between the overall thickness of the slice (determined by the region spanned by the planes), the degree of decorrelation of speckle and noise between the planes, and the degree of penetration at large depths for planes that are acquired as multi-line acquisitions (MLAs) for the same shot.

[0050] In some embodiments, the spacing between planes is controlled as a function of the beamwidth of the ultrasound probe such that less spacing may be used when the beamwidth is narrow, or if the vectors of adjacent planes are acquired from the same transmit event, using for example, parallel beamforming.

[0051] Thus, in various embodiments, the compounding described herein is based on planes with a slight spatial offset that is accurately controlled to optimize the quality of the resulting image. An offset on the order of one-half of the slice thickness is required, in some embodiments, to obtain significant speckle decorrelation between adjacent planes. Various embodiments, combine two or more ultrasound sector scans with a slight offset in a direction that is perpendicular to the main imaging direction of the planes. In this manner, information from a thicker slab of the imaging object is combined.

[0052] It should be noted that although the various embodiments may be described in connection with an ultrasound system, the methods and systems described herein are not limited to ultrasound imaging or a particular configuration thereof. For example, the various embodiments may be implemented in other non-medical imaging systems, for example, non-destructive testing systems.

[0053] The various embodiments and/or components, for example, the modules, or components and controllers therein, also may be implemented as part of one or more computers or processors. The computer or processor may include a computing device, an input device, a display unit and an interface, for example, for accessing the Internet. The computer or processor may include a microprocessor. The microprocessor may be connected to a communication bus. The computer or processor may also include a memory. The memory may include Random Access Memory (RAM) and Read Only Memory (ROM). The computer or processor further may include a storage device, which may be a hard disk drive or a

removable storage drive such as a floppy disk drive, optical disk drive, and the like. The storage device may also be other similar means for loading computer programs or other instructions into the computer or processor.

[0054] As used herein, the term “computer” may include any processor-based or microprocessor-based system including systems using micro controllers, reduced instruction set computers (RISC), graphics board, application specific integrated circuits (ASICs), logic circuits, and any other circuit or processor capable of executing the functions described herein. The above examples are exemplary only, and are thus not intended to limit in any way the definition and/or meaning of the term “computer”.

[0055] The computer or processor executes a set of instructions that are stored in one or more storage elements, in order to process input data. The storage elements may also store data or other information as desired or needed. The storage element may be in the form of an information source or a physical memory element within a processing machine.

[0056] The set of instructions may include various commands that instruct the computer or processor as a processing machine to perform specific operations such as the methods and processes of the various embodiments of the invention. The set of instructions may be in the form of a software program. The software may be in various forms such as system software or application software. Further, the software may be in the form of a collection of separate programs, a program module within a larger program or a portion of a program module. The software also may include modular programming in the form of object-oriented programming. The processing of input data by the processing machine may be in response to user commands, or in response to results of previous processing, or in response to a request made by another processing machine.

[0057] As used herein, the terms “software” and “firmware” are interchangeable, and include any computer program stored in memory for execution by a computer, including RAM memory, ROM memory, EPROM memory, EEPROM memory, and non-volatile RAM (NVRAM) memory. The above memory types are exemplary only, and are thus not limiting as to the types of memory usable for storage of a computer program.

[0058] It is to be understood that the above description is intended to be illustrative, and not restrictive. For example, the above-described embodiments (and/or aspects thereof) may be used in combination with each other. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the various embodiments of the invention without departing from their scope. While the dimensions and types of materials described herein are intended to define the parameters of the various embodiments of the invention, the embodiments are by no means limiting and are exemplary embodiments. Many other embodiments will be apparent to those of skill in the art upon reviewing the above description. The scope of the various embodiments of the invention should, therefore, be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled. In the appended claims, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.” Moreover, in the following claims, the terms “first,” “second,” and “third,” etc. are used merely as labels, and are not intended to impose numerical requirements on their objects. Further, the limitations of the follow-

ing claims are not written in means-plus-function format and are not intended to be interpreted based on 35 U.S.C. §112, sixth paragraph, unless and until such claim limitations expressly use the phrase “means for” followed by a statement of function void of further structure.

[0059] This written description uses examples to disclose the various embodiments of the invention, including the best mode, and also to enable any person skilled in the art to practice the various embodiments of the invention, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the various embodiments of the invention is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if the examples have structural elements that do not differ from the literal language of the claims, or if the examples include equivalent structural elements with insubstantial differences from the literal languages of the claims.

What is claimed is:

1. A method for generating a spatially compounded image, said method comprising:

acquiring ultrasound information from two or more scan planes, wherein the scan planes are mutually offset by a spatial distance, and wherein at least one of the scan planes is non-planar such that the spatial distance between the scan planes is a function of depth; and combining the information from the scan planes to generate a compounded image.

2. The method of claim 1, wherein the scan planes are offset in a direction that is perpendicular to the resulting compounded image.

3. The method of claim 1, wherein one of the scan planes is defined as a base plane, said method further comprising acquiring beams in at least one adjacent scan plane using multiline acquisition to increase framerate.

4. The method of claim 1, wherein the scan planes are acquired so that the resulting compounded image has any spatial direction.

5. The method of claim 1, wherein the method is used for each of the scan planes in multiplane acquisition to generate a plurality of two-dimensional scan planes.

6. The method in claim 1, wherein the method is used for each of the scan planes in standard compounding that images the imaging target from different spatial angles.

7. The method of claim 1, wherein the scan planes are acquired using B-Mode imaging, Colorflow Imaging and sub-modes of colorflow such as Tissue Velocity Imaging, Angio Imaging, B-flow Imaging, F-flow Angio imaging, and M-Mode Imaging, Color M-Mode Imaging, Pulse Wave Imaging, TVD Imaging or Continuous Wave Imaging.

8. The method of claim 7, wherein B-mode comprises fundamental imaging, harmonic imaging, pulse inversion imaging, power modulation imaging, or coded excitation imaging.

9. The method of claim 1 wherein combining the information from the scan planes further comprises combining the information from the scan planes using fixed weights, adaptive weights, or transformed data.

10. An ultrasound system for generating a compounded image, said system comprising:

an ultrasound probe for transmitting and receiving ultrasound signals to and from an area of interest; a receiver for receiving the ultrasound signals; and a processor coupled to the ultrasound probe, the processor programmed to:

acquire ultrasound information from two or more scan planes, wherein the scan planes are mutually offset by a spatial distance, and wherein at least one of the scan planes is non-planar such that the spatial distance between the scan planes is a function of depth; and combine the information from the scan planes to generate a compounded image.

11. The ultrasound system of claim 10, wherein the scan planes are offset in a direction that is perpendicular to the resulting compounded image.

12. The ultrasound system of claim 10, wherein one of the scan planes is defined as a base plane, said method further comprising acquiring beams in at least one adjacent scan plane using multiline acquisition to increase framerate.

13. The ultrasound system of claim 10, wherein the scan planes are acquired so that the resulting compounded image has any spatial direction.

14. The ultrasound system of claim 10, wherein the processor is further programmed to use each of the scan planes in multiplane acquisition to generate a plurality of two-dimensional scan planes.

15. The ultrasound system of claim 10, wherein the processor is further programmed to use each of the scan planes in standard compounding that images the imaging target from different spatial angles.

16. The ultrasound system of claim 10, wherein the scan planes are acquired using B-Mode imaging, Colorflow Imaging, Tissue Velocity Imaging, B-flow Imaging, M-Mode Imaging, Pulse Wave Imaging, or Continuous Wave Imaging.

17. The ultrasound system of claim 16, wherein B-mode imaging comprises fundamental imaging, harmonic imaging, pulse inversion imaging, power modulation imaging, or coded excitation imaging.

18. The ultrasound system of claim 10, wherein combining the information from the scan planes further comprises combining the information from the scan planes using fixed weights, adaptive weights, or transformed data.

19. A non-transitory computer readable medium for generating a compounded image, the computer readable medium instructing a processor to:

acquire ultrasound information from two or more scan planes, wherein the scan planes are mutually offset by a spatial distance, and wherein at least one of the scan planes is non-planar such that the spatial distance between the scan planes is a function of depth; and combine the information from the scan planes to generate a compounded image.

20. The non-transitory computer readable medium of claim 18 wherein the scan planes are offset in a direction that is perpendicular to the resulting compounded image.

* * * * *

专利名称(译)	用于执行超声波高度复合的方法和设备		
公开(公告)号	US20130012819A1	公开(公告)日	2013-01-10
申请号	US13/179212	申请日	2011-07-08
[标]申请(专利权)人(译)	通用电气公司		
申请(专利权)人(译)	通用电气公司		
当前申请(专利权)人(译)	通用电气公司		
[标]发明人	HAUGEN GEIR ULTVEIT KRISTOFFERSEN KJELL SORNES ANDERS R		
发明人	HAUGEN, GEIR ULTVEIT KRISTOFFERSEN, KJELL SORNES, ANDERS R.		
IPC分类号	A61B8/13		
CPC分类号	A61B8/5269 A61B8/5246 G01S15/8995		
其他公开文献	US9204862		
外部链接	Espacenet USPTO		

摘要(译)

用于生成空间复合图像的方法包括从两个或更多个扫描平面获取超声信息，其中扫描平面相互偏移空间距离，并且其中至少一个扫描平面是非平面的，使得它们之间的空间距离扫描平面是深度的函数，并且组合来自扫描平面的信息以生成复合图像。本文还描述了系统和非暂时性计算机可读介质。

