



US006572551B1

(12) **United States Patent**
Smith et al.

(10) **Patent No.:** **US 6,572,551 B1**
(45) **Date of Patent:** **Jun. 3, 2003**

(54) **IMAGING CATHETERS FOR VOLUMETRIC INTRALUMINAL ULTRASOUND IMAGING**

(75) Inventors: **Stephen W. Smith**, Durham, NC (US);
Edward D. Light, Durham, NC (US);
Jason O. Fiering, Durham, NC (US)

(73) Assignee: **Duke University**, Durham, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/546,721**

(22) Filed: **Apr. 11, 2000**

Related U.S. Application Data

(62) Division of application No. 09/074,907, filed on May 8, 1998, now Pat. No. 6,066,096.

(51) **Int. Cl.**⁷ **A61B 8/00**

(52) **U.S. Cl.** **600/459**

(58) **Field of Search** 29/25.35; 367/153; 600/459; 310/334-336

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,671,293 A	6/1987	Shaulov	128/660
4,747,192 A *	5/1988	Rokurota	29/25.35
4,802,487 A	2/1989	Martin et al.	128/662.06
4,870,867 A	10/1989	Shaulov	73/625
4,887,605 A	12/1989	Angelsen et al.	128/660.03
5,091,893 A *	2/1992	Smith et al.	367/153
5,178,150 A	1/1993	Silverstein et al.	128/662.06
5,273,045 A	12/1993	Chihara et al.	128/662.06
5,287,330 A	2/1994	Gilmour	367/103
5,335,663 A	8/1994	Oakley et al.	128/662
5,373,845 A	12/1994	Gardineer et al.	128/660.09
5,421,338 A	6/1995	Crowley et al.	128/662.06
5,437,283 A	8/1995	Ranalletta et al.	128/662.06
5,488,954 A	2/1996	Sleva et al.	128/662.03
5,493,541 A *	2/1996	Snyder	367/155
5,522,393 A	6/1996	Phillips et al.	128/661.09
5,617,565 A *	4/1997	Polczewska et al.	600/459

5,644,085 A *	7/1997	Lorraine et al.	73/641
5,651,366 A	7/1997	Liang et al.	128/662.06
5,655,276 A *	8/1997	Pattanyak et al.	29/25.35
5,704,361 A	1/1998	Seward et al.	128/662.06
5,715,825 A	2/1998	Crowley	128/602.06
5,744,898 A *	4/1998	Smith et al.	310/334
5,749,833 A	5/1998	Hakki et al.	600/380
5,774,960 A *	7/1998	De Fraguier et al.	29/25.35
5,829,439 A	11/1998	Yokosawa et al.	128/662.06
5,840,031 A	11/1998	Crowley	600/440
5,938,612 A *	8/1999	Kline-Schroder et al.	600/459
6,019,727 A *	2/2000	Koger et al.	600/459
6,066,096 A *	5/2000	Smith et al.	600/463

OTHER PUBLICATIONS

Davidson et al., "Two-Dimensional Arrays for Medical Ultrasound Using Multilayer Flexible Circuit Interconnection," *IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control*, vol. 45, No. 2, Mar. 1998.

(List continued on next page.)


Primary Examiner—Francis J. Jaworski

(74) *Attorney, Agent, or Firm*—Myers Bigel Sibley & Sajovec

(57) **ABSTRACT**

A real time three dimensional ultrasound imaging probe apparatus is configured to be placed inside a body. The apparatus comprises an elongated body having proximal and distal ends with an ultrasonic transducer phased array connected to and positioned on the distal end of the elongated body. The ultrasonic transducer phased array is positioned to emit and receive ultrasonic energy for volumetric forward scanning from the distal end of the elongated body. The ultrasonic transducer phased array includes a plurality of sites occupied by ultrasonic transducer elements. At least one ultrasonic transducer element is absent from at least one of the sites, thereby defining an interstitial site. A tool is positioned at the interstitial site. In particular, the tool can be a fiber optic lead, a suction tool, a guide wire, an electrophysiological electrode, or an ablation electrode. Related systems are also discussed.

18 Claims, 11 Drawing Sheets



OTHER PUBLICATIONS

Davidsen et al., "Two-Dimensional Random Arrays for Real Time Volumetric Imaging," *Ultrason. Imag.*, vol. 16, pp. 143-163, 1994.

Evans et al., "Arterial Imaging with a New Forward-Viewing Intravascular Ultrasound Catheter, I, Initial Studies," *Circulation*, vol. 89, No. 2, pp. 712-717, Feb. 1994.

Light et al., "Advances in Two Dimensional Arrays for Real Time Volumetric Imaging," *1997 IEEE Ultrasonics Symposium*, pp. 1619-1623, 1997.

Ng et al., "Arterial Imaging With a New Forward-Viewing Intravascular Ultrasound Catheter, II, Three-Dimensional

Reconstruction and Display of Data," *Circulation*, vol. 89, No. 2, pp. 718-723, Feb. 1994.

Piel, Jr., "7.5 MHz Pediatric Phased Array Transesophageal Endoscope," *1994 Ultrasonics Symposium*, pp. 1527-1530, 1994.

Seward et al., "Ultrasound Cardioscopy: Embarking on a New Journey," *Mayo Clin. Proc.*, vol. 71, No. 7, pp. 629-635, Jul. 1996.

Smith, et al., "Two-Dimensional Arrays for Medical Ultrasound," *Ultrasonic Imaging*, vol. 14, pp. 213-233, 1992.

* cited by examiner







FIG. 1.






FIG. 2D.




FIG. 2E.




FIG. 2F.




FIG. 2G.




FIG. 3A.




FIG. 3B.




FIG. 4A.




FIG. 4B.




FIG. 5A.




FIG. 5B.




FIG. 6A.




FIG. 6B.




FIG. 7A.






FIG. 7B.



IMAGING CATHETERS FOR VOLUMETRIC INTRALUMINAL ULTRASOUND IMAGING

This is a division of Ser. No. 09/074,907 filed May 8, 1998 and now U.S. Pat. No. 6,066,096.

This invention was made with Government support under grant number CA56475 from the National Institute of Health. The Government has certain rights to this invention.

FIELD OF THE INVENTION

The present invention relates to the field of imaging in general and to ultrasound imaging in particular.

BACKGROUND OF THE INVENTION

Ultrasonic imaging has been applied in many two dimensional systems using pulse echo B-mode tomography or B-scans. These systems display echoes returning to an ultrasonic transducer as brightness levels proportional to echo amplitude. The brightness levels may be used to create cross-sectional images of the object in the plane perpendicular to the transducer aperture.

Examination of objects in three dimensions has evolved using a number of modalities including x-ray, ultrasound, and nuclear magnetic resonance. In particular, improvements have been made in spatial resolution, dynamic range, display methods and data analysis. For example, ultrasound scanning of three-dimensional objects by sequential B-scans followed by off-line reconstruction and display of rendered images has progressed in recent years with the introduction of commercial three-dimensional systems. Off-line rendering, however, may take several minutes to produce a single three-dimensional scan.

In the area of high-speed three-dimensional ultrasound imaging, U.S. Pat. No. 4,596,145 to Smith and von Ramm discloses an acoustic imaging system capable of producing high-speed projection orthoscopic images, as well as a single high-speed C-scan image using a two-dimensional array transducer and receive mode parallel processing. The C-scan image may be defined as a planar section of the object parallel to the effective transducer aperture. In 1987, U.S. Pat. No. 4,694,434 to von Ramm and Smith disclosed a steered array acoustic imaging scanner capable of producing a high-speed pyramidal scan to obtain a volumetric (three-dimensional) image using a two-dimensional array transducer and receive mode parallel processing.

High frequency intraluminal ultrasound imaging probes have been developed, including circular arrays and mechanically steered transducers. The circular arrays and mechanically steered transducers produce B-mode circular side scan geometries in which the ultrasound beam is swept through a 360° arc. The 360° arc may create a high-speed circular image within a vessel or lumen with a maximum range of approximately one centimeter. For example, U.S. Pat. No. 3,938,502 to Bom and U.S. Pat. No. 4,917,097 to Proudian, et al. disclose circular arrays of transducer elements within a catheter to produce a circular side scanning intraluminal B-mode image. U.S. Pat. No. 4,794,931 to Yock and U.S. Pat. No. 5,243,988 to Sieben, et al. disclose motor-driven piston transducers at the end of the catheters to produce circular side scanning intravascular imaging.

Catheters may be used in conjunction with the systems described above to provide intraluminal imaging. Intraluminal imaging may involve inserting a catheter, that includes an ultrasonic transducer phased array, into coronary vessels, pulmonary arteries, the aorta, or venous structures. For example, U.S. Pat. No. 5,704,361 to Seward, et al. discloses

a volumetric imaging ultrasound transducer under-fluid catheter system. The advantages of Seward may, however, be limited by the quality of the imaging provided therein. In particular, the catheter probes disclosed in Seward show the therapeutic tools adjacent to the transducer array on the catheter tip, thereby reducing the area available for the transducer array. Such an array may provide images having reduced spatial resolution. Moreover, the applications described in Seward may be limited to procedures involving catheters.

The catheters described above may be combined with electrodes or tools to locate (cardiac electrophysiological mapping) and perform therapy on (radiofrequency ablation) or monitor tissue. For example, a three-dimensional ultrasound imaging device using a catheter may be combined with an ablation electrode to provide therapy to particular tissue. The therapy provided by the electrode, however, may be limited by the registration between the image provided by the catheter and the electrodes associated with the catheter. For example, a user may have difficulty translating the image produced by the catheter to the position of the electrode, thereby possibly creating difficulty in applying the electrode to the intended tissue. Moreover, the electrode may obscure the three dimensional ultrasound image when the electrode is within the field of view of the image.

In view of the above discussion, there exists a need to improve the quality of real-time three-dimensional imaging in intraluminal ultrasound applications.

SUMMARY OF THE INVENTION

In view of the above discussion, it is an object of the present invention to provide improved ultrasonic imaging probes.

It is another object of the present invention to provide improved therapy in conjunction with ultrasonic imaging.

These and other objects are provided by a real time three dimensional ultrasound imaging probe configured to be placed inside a body. The imaging probe includes an elongated body having proximal and distal ends. An ultrasonic transducer phased array is connected to and positioned on the distal end of the elongated body. The ultrasonic transducer phased array is configured to emit ultrasonic energy for volumetric scanning from the distal end of the elongated body and receive reflected ultrasonic energy. The ultrasonic transducer phased array includes a plurality of sites occupied by ultrasonic transducer elements. At least one ultrasonic transducer element is absent from at least one of the sites, thereby defining an interstitial site. A tool is positioned at the interstitial site. In particular, the tool can be a fiber optic lead, a suction tool, a scalpel, a guide wire, an electrophysiological electrode, or an ablation electrode. Positioning the tool at an interstitial site allows a large ultrasonic transducer phased array aperture, thereby producing superior image resolution and sensitivity as compared to the prior art. Conventional probes may include tools, positioned outside the ultrasonic transducer phased array, that reduce the aperture size of the ultrasonic transducer phased array. A reduced aperture size provides lower image resolution and sensitivity. Positioning the tool within the ultrasonic transducer phased array allows the user to accurately align the tool with the tissue to be treated more accurately, thereby making the probe easier to use and more effective.

In one aspect, a plurality of ultrasonic transducer elements are absent from a plurality of sites, defining a plurality of interstitial sites. The plurality of interstitial sites have a circular arrangement within the ultrasonic transducer phased

array. The circular arrangement allows a larger aperture size while limiting side lobe effects on the imaging.

In another aspect, the ultrasonic transducer elements are arranged in a row of ultrasonic transducer elements and a column of ultrasonic transducer elements, defining four quadrants of interstitial sites within the ultrasonic transducer phased array. The row of ultrasonic transducer elements is substantially perpendicular to the column of ultrasonic transducer elements. A tool can be positioned at an interstitial site within each quadrant of the ultrasonic transducer phased array.

In still another aspect, a real time three dimensional ultrasound imaging probe apparatus is configured to be placed inside a body. The apparatus includes an elongated body having proximal and distal ends with an ultrasonic transducer phased array connected to and positioned on the distal end of the elongated body. The ultrasonic transducer phased array is configured to emit either forward or side scanning ultrasonic energy for volumetric scanning from the distal end of the elongated body and receive reflected ultrasonic energy. An electrode assembly is connected to and overlies the ultrasonic transducer phased array, wherein the electrode assembly is transparent to ultrasonic energy.

The ultrasonically transparent electrode assembly allows the user to more accurately apply the electrode to tissue within a region of interest, thereby allowing a reduction in the complexity associated with the prior art. For example, the present invention allows the user to apply the electrode to the tissue by locating the tissue within the region of interest using the real time three dimensional images. In contrast, users of some conventional imaging probes locate the tissue and then manipulate an electrode to the tissue by understanding the registration between the image and the physical location of the electrode on the probe.

The present invention also provides increased image resolution and sensitivity (signal to noise ratio) by increasing the aperture size of the ultrasonic transducer phased array to include a majority of the surface area of the distal end of elongated body. In particular, conventional ultrasonic transducer phased arrays cover a minority of the distal end of the elongated body described therein. Moreover, the prior art generally discloses an ultrasonic transducer phased array in conjunction with conventional tools and electrodes positioned in close proximity to the ultrasonic transducer phased array, thereby limiting the size of the ultrasonic transducer phased array. As a result, images produced by conventional imaging probes have less spatial resolution and sensitivity relative to those produced by the present invention.

The present invention also provides improved imaging over the prior art as applied to biopsy procedures. In particular, a real time three dimensional imaging biopsy apparatus configured to be inserted into a body includes an elongated body, having proximal and distal ends, that is configured to be extended through a biopsy needle into the body. An ultrasonic transducer phased array is connected to and positioned on the distal end of the elongated body. The ultrasonic transducer phased array is configured to emit and receive ultrasonic energy for volumetric scanning from the distal end of the elongated body.

The present invention also provides improved imaging over the prior art as applied to minimally invasive surgical procedures. In particular, a real time three dimensional ultrasonic imaging probe apparatus configured to be placed into a body, includes a cannula configured to provide access to a cavity inside the body. An elongated body, having proximal and distal ends, is configured to extend into the

body via the cannula. An ultrasonic transducer phased array is connected to and is positioned on the distal end of the elongated body. The ultrasonic transducer phased array is configured to emit ultrasonic energy for volumetric scanning from the distal end of the elongated body and receive reflected ultrasonic energy.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a block diagram of a real time three dimensional ultrasonic imaging system;

FIG. 2A is an enlarged partial perspective view an imaging probe configured to emit and receive ultrasonic energy for volumetric forward scanning according to the present invention;

FIG. 2B is an enlarged side view of an imaging probe of FIG. 2A;

FIG. 2C is an enlarged partial perspective view an imaging probe configured to emit and receive ultrasonic energy for volumetric side scanning according to the present invention;

FIG. 2D is an enlarged side view of an imaging probe of FIG. 2C;

FIG. 2E is an enlarged view of elements of an ultrasonic transducer phased array according to the present invention;

FIG. 2F is an enlarged view of elements of a sparsely populated periodic ultrasonic transducer phased array with tools according to the present invention;

FIG. 2G is an enlarged view of a row of ultrasonic transducer elements and a column of ultrasonic transducer elements with tools according to the present invention;

FIG. 3A is an enlarged cross-sectional view of a real time three dimensional imaging probe apparatus configured to emit and receive ultrasonic energy for volumetric forward scanning according to the present invention;

FIG. 3B is an enlarged cross-sectional view of a real time three dimensional imaging probe apparatus configured to emit and receive ultrasonic energy for volumetric side scanning according to the present invention;

FIG. 4A is an enlarged cross-sectional view of an ultrasonic transducer phased array and electrode according to the present invention;

FIG. 4B is an enlarged view of a distal end of an ultrasonic transducer phased array and electrode partially overlying the ultrasonic transducer phased array according to the present invention;

FIG. 5A is a cross-sectional view of a real time three dimensional imaging probe apparatus configured to emit and receive ultrasonic energy for volumetric forward scanning according to the present invention;

FIG. 5B is a cross-sectional view of a real time three dimensional imaging probe apparatus configured to emit and receive ultrasonic energy for volumetric side scanning according to the present invention;

FIG. 6A is a cross-sectional view of a real time three dimensional imaging biopsy apparatus configured to emit volumetric forward scanning ultrasonic energy according to the present invention;

FIG. 6B is a cross-sectional view of a real time three dimensional imaging biopsy apparatus configured to emit volumetric side scanning ultrasonic energy according to the present invention;

FIG. 7A is an enlarged cross-sectional view of a real time three dimensional catheter apparatus configured to emit and receive ultrasonic energy for volumetric forward scanning and electrodes according to the present invention;

FIG. 7B is an enlarged cross-sectional view of a real time three dimensional catheter apparatus configured to provide side scanning and electrodes according to the present invention; and

FIGS. 7C and 7D illustrate the use of a real time three dimensional imaging catheter and electrode apparatus of FIG. 7A.

DETAILED DESCRIPTION OF THE INVENTION

The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which a preferred embodiment of the invention is shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout.

FIG. 1 is a block diagram of an ultrasonic imaging system that provides real time three dimensional ultrasonic images. The imaging probe **110** is a real time three dimensional imaging catheter, biopsy probe, surgical or endoluminal probe (such as arectal, prostrate, transurethral, or intravaginal probe) that can be configured to provide either forward or side scanning volumetric scanning ultrasonic energy via an ultrasonic transducer phased array under the control of the controller/signal processor **105**. The imaging probe **110** can be inserted into a region of interest (such as a inside the body of a patient) to provide real time three dimensional ultrasonic imaging of objects within the region of interest. For example, the imaging probe **110** can be a real time three dimensional imaging catheter used to provide imaging during cardiac or prostrate procedures. Accordingly, the imaging catheter probe **110** would have a diameter in the range between about 3 French and 20 French. Alternately, the imaging probe **110** can provide imaging during needle biopsy or minimally invasive surgical procedures (such as in conjunction with a trocar during knee or abdominal surgery). Accordingly, the imaging probe would have a diameter in the range between about 1 millimeter (mm) and 20 mm. The imaging probe can include mechanical, surgical, and therapeutic tools (such as a suction tool, an optical fiber, a guide wire, or a scalpel blade) and electrodes to monitor or treat a particular tissue (such as electrophysiological or ablation electrodes). As described herein, a configuration for the emission of ultrasonic energy for volumetric scanning includes a configuration for the emission of volumetric forward scanning ultrasonic energy and a configuration for the emission of volumetric side scanning ultrasonic energy.

The controller/signal processor **105** transmits/receives electrical pulses to/from imaging probe **110**. For example, the controller/signal processor **105** transmits electrical pulses to the imaging probe **110** that cause the ultrasonic transducer phased array to emit ultrasonic energy. The controller/signal processor also receives electrical pulses from the imaging probe **110** caused by the incidence of ultrasonic energy reflected from objects within the region of interest upon the ultrasonic transducer phased array. The controller/signal processor **105** provides a volumetric image on the display **100** of the object within the region of interest based on the electrical pulses received from the imaging probe **110**. For example, the image may be formed using the systems and techniques disclosed in U.S. Pat. No. 5,546,807 to Oxaal et al. entitled High Speed Volumetric Ultrasound

Imaging System. The display can be a cathode ray tube, liquid crystal display, or other device with suitable dynamic range for the display of volumetric images.

FIGS. 2A and 2B are enlarged partial perspective and side views of an imaging probe **110** configured to emit and receive ultrasonic energy for volumetric forward scanning according to the present invention. The imaging probe includes an elongated body **200** having proximal and distal ends. The ultrasonic transducer phased array **205** is connected to and positioned on the distal end of the elongated body **200**, and positioned to emit and receive ultrasonic energy for volumetric forward scanning from the distal end of the elongated body **200**. Imaging is provided by inserting the imaging probe into the region of interest (such as the body of a patient) so that the ultrasonic energy emitted from the ultrasonic transducer phased array is incident upon and is reflected from an object within the region of interest (such as tissue). The term body, as used herein, includes a biological entity, such as a human body, animal body, or vessel or container filled with fluid or airborne media subject to non-destructive evaluation (such as a nuclear reactor vessel).

The cable **210** provides a plurality of conductors (such as wires or optical fibers) for transmission of signals to/from the controller/signal processor **105**. In one embodiment, the cable **210** includes 70 conductors.

FIGS. 2C and 2D are enlarged partial perspective and side views of an imaging probe **110** configured to emit and receive ultrasonic energy for volumetric side scanning according to the present invention. Side scanning can provide a real time three dimensional image of objects located such that rotation of a forward scanning probe described above is less practical (such as a cardiac ventricular wall). The ultrasonic transducer phased array **206** is positioned substantially parallel to the longitudinal axis **211** of the elongated body **200** to provide side scanning ultrasonic energy. It should be understood that substantially parallel includes an orientation of the ultrasonic transducer phased array that is within ± 45 degrees of a completely parallel orientation.

FIG. 2E is an illustration of a preferred embodiment of an ultrasonic transducer phased array **205** connected to and positioned on the distal end of the elongated body **200** to emit volumetric forward or side scanning ultrasonic energy wherein the ultrasonic transducer phased array **205** covers a major portion of the distal end of the elongated body **200** (more than 50% of the distal end of the elongated body). The ultrasonic transducer phased array **205** is formed in an octagonal shape so as to increase the number of ultrasonic transducer elements included in the ultrasonic transducer phased array **205** positioned on the distal end of the elongated body. The ultrasonic transducer phased array operates at about 5 megahertz (MHz), includes 70 elements spaced about 0.2 mm apart, and is about 3 mm in diameter.

The ultrasonic transducer phased array **205** includes a plurality of ultrasonic transducer transmit and receive elements (elements) **215** arranged in row and column configuration. The elements can be arranged as a sparse array, a fully populated array (such as 10×10 , 20×20 , 60×60 , 80×80), a Mills Cross array, a random distribution array, or a periodic distribution array. The ultrasonic transducer elements **215** receive electrical pulses from the controller/signal processor **105**, as described above, causing the ultrasonic transducer elements **215** to emit ultrasonic energy. Furthermore, the ultrasonic transducer elements are provided with electrical pulses according to a phase sequence in the row and column direction as described in U.S. Pat. No.

5,546,807 to Oxaal et al. to produce the volumetric image described therein. The emitted ultrasonic energy is reflected from an object within the region of interest and is incident upon the elements **215** and thereby causing a corresponding electrical pulse to be transmitted to the controller/signal processor **105**. The ultrasonic transducer phased array is made from a piezoelectric material.

The ultrasonic transducer phased array **205** is configured to cover a majority of the distal end of the elongated body **200** to provide a large aperture relative to the prior art. In particular, an ultrasonic transducer phased array **205** may provide superior resolution, θ_A (resolution in the azimuth dimension) and θ_E (resolution in the elevation dimension), by increasing the azimuth and elevation dimensions of the elongated body **200** allocated to the ultrasonic transducer phased array **205** according to:

$$\theta_E = \sin^{-1}\left(\frac{\lambda}{L}\right) \quad \theta_A = \sin^{-1}\left(\frac{\lambda}{D}\right)$$

where λ is the wavelength of the ultrasonic energy and where L is the aperture size of the ultrasonic transducer phased array **205** in the elevation dimension and where D is the aperture size of the ultrasonic transducer phase array in the azimuth dimension. A larger aperture size also provides increased sensitivity (signal to noise ratio) in proportion to the improved resolution described above. For example, in contrast to the ultrasonic transducer phased arrays described herein, the ultrasonic transducer phased arrays disclosed in Seward cover a minority of the elongated body described therein. Moreover, Seward discloses an ultrasonic transducer phased array in conjunction with conventional tools and electrodes positioned in close proximity to and outside of the ultrasonic transducer phased array, thereby limiting the size of the ultrasonic transducer phased array. As a result, the images produced by the prior art may have low spatial resolution and sensitivity relative to those produced by the present invention. Moreover, the three dimensional ultrasound imaging of the prior art may be obscured when conventional tools are used within the field of view of the ultrasonic transducer phased array.

FIG. 2F is an enlarged view of elements of a sparsely populated periodic ultrasonic transducer phased array with tools according to the present invention. The ultrasonic transducer phased array includes a plurality of sites occupied by ultrasonic transducer elements **215**. The ultrasonic transducer phased array **205** is divided into four quadrants: quadrant **1**, quadrant **2**, quadrant **3**, and quadrant **4**. At least one of the ultrasonic transducer elements is absent from the ultrasonic transducer phased array, thereby defining an interstitial site. A tool can be positioned at the interstitial site to provide therapy to or monitoring of tissue. In a preferred embodiment, a plurality of ultrasonic transducer elements **215** are absent, thereby defining a plurality of interstitial sites having a circular arrangement **224** in which a plurality of tools can be positioned.

The circular arrangement **224** allows tools **222**, **226**, **228**, and **230** to be positioned within the ultrasonic transducer phased array **205** and provides improved image resolution and sensitivity and reduces the effect of side lobes produced by smaller array dimensions as described above. The plurality of tools are distributed among the quadrants to reduce the side lobe effects caused by the presence of the tools. For example, tool **222** is positioned in quadrant **1**, tool **226** is positioned in quadrant **2**, tool **228** is positioned in quadrant **3**, and tool **230** is positioned in quadrant **4**. The tools may be a fiber optic lead, an ablation electrode, an electrophysi-

ological electrode, a suction tool, or a guide wire. The inclusion of tools within the ultrasonic transducer phased array **205** allows the user to align the tool with the tissue more accurately, thereby making the imaging probe easier to use and more effective.

FIG. 2G is an enlarged view of a row of ultrasonic transducer elements and a column of ultrasonic transducer elements (a Mills cross array) with tools according to the present invention. The combination of the row of ultrasonic transducer elements and the column of ultrasonic transducer elements define four quadrants of the ultrasonic transducer phased array: quadrant **1**, quadrant **2**, quadrant **3**, and quadrant **4**. The quadrants include a plurality of interstitial sites **221** from which ultrasonic transducer elements **215** are absent.

The sparse array may be implemented by selectively connecting a sub-set of conductors included in the cable **210** to corresponding elements **215**. For example, a sparse array may be implemented using a single row and column of ultrasonic transducer elements in combination. The row and column ultrasonic transducer elements are provided with electrical pulses and receive mode delays according to the phasing described above. Alternately, the elements **215** within the ultrasonic transducer phased array **205** may be arranged according to a periodic distribution in which the spacing between transmit and receive elements is different so as to reduce grating lobe and side lobe effects. Another alternative distribution includes a random array geometry with a gaussian sampling of the transmit elements and a uniform sampling of the receive elements.

In one embodiment, tools **222**, **226**, **228**, and **230** are positioned at interstitial sites in the quadrants **1**, **2**, **3**, and **4** defined by the row and column of ultrasonic transducers. In a preferred embodiment, a single tool is positioned in each quadrant so as to minimize the effects of side lobes on the imaging. The tools may be a fiber optic lead, an ablation electrode, an electrophysiological electrode, a suction tool, or a guide wire. The inclusion of tool within the ultrasonic transducer phased array allows the user to align the tool with the tissue more accurately, thereby making the imaging probe easier to use and more effective.

FIG. 3A is an enlarged cross-sectional view of a real time three dimensional imaging probe apparatus configured to emit volumetric forward scanning ultrasonic energy according to the present invention. A plurality of conductors **300** within the cable **210**, having proximal and distal ends, are suitable for conducting electrical impulses to and from the corresponding elements **215** of the ultrasonic transducer phased array **205**. The plurality of conductors **300** pass through a plurality of spaced holes **315** in the mounting plate **305** having a first and second side. The plurality of conductors **300** are connected to corresponding elements **215** within the ultrasonic transducer phased array **205** that is connected to and overlying the second side of the mounting plate **305**.

A backing material **335** is positioned between the mounting plate **305** and the distal end of the cable **210**. The acoustic impedance of the backing material **335** is matched to the acoustic impedance of the mounting plate **305** to reduce the amount of acoustic energy reflected back to the ultrasonic transducer phased array **205**. The mounting plate **305** is made from a material which is acoustically transparent to ultrasonic energy at the resonant frequency of the ultrasonic transducer phased array **205**. The term acoustically transparent, in the frequency band, includes materials that reflect a portion of an incident ultrasonic energy in the range between about 50% and 0% of the incident ultrasonic energy. For example, the mounting plate **305** can be a soft

polymer material such as polyimide. In a preferred embodiment, the impedance of the mounting plate **305** is in the range between about 2 MRaysl and 5 MRaysl.

The plurality of holes **315** in the mounting plate **305** are spaced to accommodate the spacing of the elements **215** within the ultrasonic transducer phased array **205**. In a preferred embodiment, the hole spacing **320** is about 0.2 mm on center and the hole diameter **325** is about 0.1 mm. In a preferred embodiment, the holes **315** are created using a CO₂ or excimer laser. The CO₂ or excimer laser can avoid over-stressing the mounting plate while the holes **315** are created and may be controlled with greater precision than can mechanical drilling. In one embodiment, the holes **315** are filled with a conductive epoxy. The plurality of conductors **300** are connected to the conductive epoxy. In another embodiment, the plurality of conductors **300** pass through the holes **315** and are connected to the plurality of corresponding elements **215**. The holes **315** are then filled with the conductive epoxy.

In the prior art, mechanical drilling of holes with a diameter and spacing described above may over-stress the mounting plate material, thereby causing a failure of the mounting plate. Moreover, control and accuracy of a mechanical drilling process may be difficult at the dimensions described above. Furthermore, a drill bit capable of drilling a hole having a diameter of about 0.1 mm may be difficult to obtain and may be prone to failure.

The mounting plate **305** is formed to a thickness, D, that does not exceed

$$D=\lambda$$

where λ is the wavelength of the ultrasonic energy emitted by the ultrasonic transducer phased array. For example, for ultrasonic energy emitted at 5 MHz, the thickness of the mounting plate **305** should not exceed 0.075 mm. The thickness described above may provide additional structural integrity to the mounting plate **305**. Consequently, the mounting plate **305** may be better suited to the creation of the holes **315** having the hole diameter **325** and the hole spacing **320** described above.

FIG. **3B** is an enlarged cross-sectional view of a real time three dimensional imaging probe apparatus configured to emit volumetric side scanning ultrasonic energy according to the present invention. A conduit **330** having proximal and distal ends includes a plurality of conductors **337** having proximal and distal ends. The distal end of the conduit **330** is positioned substantially parallel to the ultrasonic transducer phased array **205** to allow a plurality of pads **339**, positioned at the distal end of the plurality of conductors **337**, to be directly connected to a plurality of corresponding elements of the ultrasonic transducer phased array **205**. A backing material **335** is positioned between the conduit **330** and the distal end of the elongated body **200**. The backing material **335** is acoustically matched to the mounting plate **305** to reduce the reflection of acoustic energy emitted from the ultrasonic transducer phased array **205**. A glue is positioned between the conduit **300** and the ultrasonic transducer phased array **205** to maintain the position of the conduit **300** with respect to the ultrasonic transducer phased array **205**. It will be understood that the phrase directly connect, as used herein, includes in contact with and having layers positioned between the mounting plate **305** and the conduit **330**.

The conduit **330** can be a Multilayer Flexible Circuit (MFC) that includes the conductors **337** and the pads **339**. The conductors **337** can be on the outer surface and the interior of the MFC. The MFC can be oriented within the elongated body to provide a direct connection to the mount-

ing sheet **305**. The pads **339** of the MFC are aligned with the elements of the ultrasonic transducer phased array.

FIG. **4A** is an enlarged cross-sectional view of an ultrasonic transducer phased array **205** and electrode assembly **400** according to the present invention. The ultrasonic transducer phased array **205** is connected to and positioned on the distal end of the elongated body **200** and positioned to emit and receive ultrasonic energy for volumetric forward scanning of objects within the region of interest. The electrode assembly **400** is connected to and overlying the ultrasonic transducer phased array **205**. The electrode assembly **400** includes a first ground layer **405** connected to and overlying the ultrasonic transducer phased array **205**. The first ground layer **405** can be implemented with a metal layer having a thickness in the range between about 0.02 μm and 20 μm . The first ground layer **405** is formed by sputter deposition, plating, a bonded foil, a screen print, or vapor deposition. The first insulator layer **410** is connected to and overlying the first ground layer **405**. The first insulator layer **410** is formed from polyimide to a thickness in the range between about 0.02 μm and 20 μm . The second ground layer **415** is connected to and overlying the first insulator layer **410** and can be implemented with a metal layer having a thickness in the range between about 0.02 μm and 20 μm . The second insulator layer **420** is connected to and overlying the second ground layer **415** and can be implemented using polyimide formed to a thickness in the range between about 0.02 μm and 20 μm . The electrode **425** is connected to and overlying the second insulator layer **420**.

As described above, the electrode assembly is transparent to ultrasonic energy. Consequently, the thickness, D, of the electrode assembly **400** does not exceed:

$$D=\lambda$$

where λ is the wavelength of the ultrasound energy emitted by the ultrasonic transducer phased array. For example, for ultrasonic energy of 5 MHz, the thickness, D, of the electrode assembly **400** is less than about 0.075 mm.

It should be understood that the phrase connected to, as used herein, includes an arrangement wherein the a first component is physically contacting a second component and an arrangement wherein at least a third component is positioned between the first and second components. Accordingly, the above description includes an arrangement wherein other components are positioned between the ultrasonic transducer phased array **205** and the electrode **425**.

The electrode **425** can be used to perform therapy on or monitoring of tissue within the region of interest. For example, the electrode **405** may be an electrocardiogram electrode or electrophysiological mapping electrode used to monitor the activity of heart tissue. Alternately, the electrode **425** can be an ablation electrode used to deliver a stimulus to the tissue within the region of interest. For example, the electrode may be used to deliver a radiofrequency thermal ablation in the range between about 5 Watts to 30 Watts at a frequency in the range between about 300 Hz to 750 kHz.

The position of the electrode **425** connected to and overlying the ultrasonic transducer phased array **205** may provide, in combination with the ultrasonic transparency of the electrode assembly, improved guidance of the electrode to the targeted tissue within the region of interest. The electrode **425** can be positioned by aligning the image with the tissue, thereby possibly reducing complications associated with the alignment of the electrode **425** and the image presented to the user in the prior art. The function of the electrode **425** may be controlled by the controller/signal processor **105** via a guide wire **440** extending through the

elongated body **200**, through the ultrasonic transducer phased array **205**, and through the electrode assembly **400**. Alternately, the electrode **425** may be controlled via a wire **435** that is connected to the electrode **425** without passing through the electrode assembly **400**. In another embodiment, a fiber optic lead **450** extends through the ultrasonic transducer phased array and the electrode assembly **400**. Laser light is emitted from the fiber optic lead to provide therapy to a particular tissue.

FIG. **4B** is an enlarged view of the distal end of an ultrasonic transducer phased array and electrode partially overlying the ultrasonic transducer phased array and tools according to the present invention. The electrode **425** described above, can be used in combination with the tools described herein. The electrode **425** is connected to and overlying the ultrasonic transducer phased array **205**. The ultrasonic transducer phased array **205** includes a plurality of sites occupied by ultrasonic transducer elements **215**. At least one of the ultrasonic transducer elements **215** is absent from a site, defining an interstitial site **480**. A tool **455** is positioned at the interstitial site **480**. The electrode **425** does not overlie the tool **455** positioned at the interstitial site **480**. The electrode **425**, thereby, may not interfere with the operation of the tool. In another embodiment, a plurality of tools **455**, **460**, **465**, and **470** are positioned at a plurality of interstitial sites.

FIG. **5A** is a cross-sectional view of a real time three dimensional imaging probe apparatus configured to emit and receive ultrasonic energy for volumetric forward scanning according to the present invention. The apparatus shown in FIG. **5A** may be used for minimally invasive surgical procedures such as laparoscopic surgery. Laparoscopic surgery may involve the insertion of the cannula **500** through an incision to provide access to a cavity within the body. The cannula **500** provides a surgical port through which tools may access the cavity. The distal end of the elongated body **505** extends through the cannula **500** into the cavity. The ultrasonic transducer phased array **205** is connected to the distal end of the elongated body **505** and is configured to emit volumetric forward scanning ultrasonic energy from the distal end of the elongated body **505** and receive reflected ultrasonic energy.

The present invention provides a three dimensional ultrasonic image of the region of interest to the user, thereby possibly allowing less complicated manipulation of the imaging probe in relation to the tissue. In contrast, the prior art may include a B-mode or slice scanner for surgical procedures of the type described above. The user may therefore need to mentally re-orient the B-mode image to aid in locating and applying the imaging probe.

In one embodiment, tools are combined with the volumetric forward scanning imaging probe as described herein. The ultrasonic transducer phased array **205** includes a plurality sites occupied by a plurality of ultrasonic transducer elements. At least one of the ultrasonic transducer elements is absent from a site, thereby defining an interstitial site. A tool is positioned at the interstitial site.

FIG. **5B** is a cross-sectional view of a real time three dimensional imaging probe apparatus configured to provide side scanning ultrasonic energy according to the present invention. Side scanning can provide a real time three dimensional image of objects located such that rotation of a forward scanning probe described above is less practical (such as a cardiac ventricular wall). The ultrasonic transducer phased array **205** is positioned substantially parallel to a longitudinal axis of the elongated body **400** and configured to emit volumetric side scanning ultrasonic energy and receive reflected ultrasonic energy.

In one embodiment, tools are combined with the volumetric side scanning imaging probe described above. The ultrasonic transducer phased array **206** includes a plurality sites occupied by a plurality of ultrasonic transducer elements. At least one of the ultrasonic transducer elements is absent from a site, thereby defining an interstitial site. A tool is positioned at the interstitial site.

FIG. **6A** is a cross-sectional view of a real time three dimensional imaging biopsy apparatus configured to emit volumetric forward scanning ultrasonic energy according to the present invention. The apparatus shown in FIG. **6A** may be used for biopsy procedures wherein the biopsy needle **600**, having a proximal and distal end, is pointed at the distal end and is configured for insertion into a body. For example, the biopsy needle may have a core element that is removed after insertion into the body. After the core element is removed, the distal end of the elongated body **610** is inserted into the hollow core of the biopsy needle **600** and extended into the body. The ultrasonic transducer phased array **205** is connected to and overlies the distal end of the elongated body **610** and is configured to emit volumetric forward scanning ultrasonic energy.

In one embodiment, tools are combined with the volumetric forward scanning imaging biopsy apparatus as described herein. The ultrasonic transducer phased array **205** includes a plurality sites occupied by a plurality of ultrasonic transducer elements. At least one of the ultrasonic transducer elements is absent from a site, thereby defining an interstitial site.

The present invention provides an ultrasonic transducer phased array **205** to provide the user with images of the region of interest, thereby allowing less complicated manipulation of the biopsy apparatus in relation to the tissue. In contrast, the prior art may include a B-mode or slice scanner for surgical procedures of the type described above. The user, therefore, may need to mentally re-orient the B-mode image to perform the biopsy.

FIG. **6B** is a cross-sectional view of a real time three dimensional imaging biopsy apparatus configured to provide volumetric side scanning ultrasonic energy according to the present invention. After the core element is removed, the distal end of the elongated body **610** is inserted into the hollow core of the biopsy needle **606** and extended into the body. The ultrasonic transducer phased array **205** is positioned substantially parallel to a longitudinal axis of the elongated body **610** to emit volumetric side scanning ultrasonic energy.

In one embodiment, tools are combined with the volumetric side scanning imaging biopsy apparatus described herein. The ultrasonic transducer phased array **205** includes a plurality sites occupied by a plurality of ultrasonic transducer elements. At least one of the ultrasonic transducer elements is absent from a site, thereby defining an interstitial site. A tool is positioned at the interstitial site. Side scanning can provide a real time three dimensional image of objects located such that rotation of a forward scanning probe described above is less practical (such as a breast tumor).

The imaging probes for biopsy and minimally invasive surgical procedures described herein can exist as unit wherein the components are connected. Alternately, the components may be available as a kit wherein the components are assembled for use. For example, the components can be available as a sterile kit that includes each of the components.

FIG. **7A** is an enlarged cross-sectional view of a real time three dimensional imaging catheter apparatus configured to emit volumetric forward scanning ultrasonic energy and an

electrode according to the present invention. The catheter shown in FIG. 7A can be used for cardiac diagnosis and treatment by positioning the elongated body 200, having proximal and distal ends, using the three dimensional imaging provided by the ultrasonic transducer phased array 205 that is connected to and overlies the distal end of the elongated body 200. The ultrasonic transducer phased array 205 is positioned to emit volumetric forward scanning ultrasonic energy from the distal end of the elongated body 200. A plurality of electrodes 700 and 701 are connected to and positioned around a perimeter of the elongated body 200 substantially perpendicular to a longitudinal axis of the elongated body 200. Electrodes 700 and 701 can be electrophysiological mapping electrodes used to monitor the tissue in contact with the electrodes 700 and 701. In a preferred embodiment, the electrodes 700 and 701 are positioned around the perimeter of the elongated body 200 so as to provide contact with the tissue regardless of the rotation of the elongated body 200. The electrodes 700 and 701 may also be ablation electrodes that provide therapy to the contacted tissue as described herein.

FIG. 7B is an enlarged cross-sectional view of a real time three dimensional imaging catheter apparatus configured to provide side scanning and an electrode according to the present invention. Side scanning can provide a real time three dimensional image of objects located such that rotation of a forward scanning catheter described above is less practical (such as a cardiac ventricular wall). The apparatus shown in FIG. 7B may be used to locate tissue and apply the electrodes 700 and 701 in areas where the rotation of the imaging catheter of FIG. 7A is impractical.

In FIG. 7C, the real time three dimensional imaging catheter apparatus is used locate tissue within the region of interest. In FIG. 7D, the real time three dimensional imaging catheter apparatus is used to monitor the tissue as described above. For example, the volumetric forward scanning ultrasonic catheter may be used to image the endocardium. When the desired tissue is located, the catheter is positioned parallel to the endocardium and the plurality of electrodes are used to treat the located tissue.

The present invention provides volumetric scanning ultrasonic imaging probes and catheters in combination with tools to provide therapy to tissue of interest. In particular, the tool can be a fiber optic lead, a suction tool, a guide wire, an electrophysiological electrode, or an ablation electrode. Positioning the tool at an interstitial site allows a large ultrasonic transducer phased array aperture, thereby producing superior image resolution and sensitivity as compared to the prior art. Positioning the tool within the ultrasonic transducer phased array allows the user to align the tool with the tissue to be treated more accurately, thereby making the probe easier to use and more effective. Conventional probes may include tools, positioned outside the ultrasonic transducer phased array, reducing the aperture size of the ultrasonic transducer phased array. A reduced aperture size provides lower image resolution and sensitivity.

The present invention also provides increased image resolution by increasing the aperture size of the ultrasonic transducer phased array to include a majority of the surface area of the distal end of elongated body. In particular, in contrast to the ultrasonic transducer phased arrays described herein, the ultrasonic transducer phased arrays disclosed in Seward cover a minority of the elongated body described therein. Moreover, Seward discloses an ultrasonic transducer phased array in conjunction with conventional tools and electrodes positioned in close proximity to the ultrasonic transducer phased array, thereby limiting the size of the

ultrasonic transducer phased array. As a result, the images produced by the prior art may have low spatial resolution and sensitivity relative to those produced by the present invention.

The present invention also provides improved imaging over the prior art as applied to biopsy and minimally invasive surgical procedures. In particular, the present invention provides a three dimensional ultrasonic image of the region of interest to the user, thereby possibly allowing less complicated manipulation of the electrode assembly in relation to the tissue. In contrast, the prior art may include a B-mode or slice scanner for surgical procedures of the type described above. The user may therefore need to mentally re-orient the B-mode image to aid in locating and applying the electrode assembly.

The present invention also provides real time three dimensional imaging probes with ultrasonically transparent electrodes for use with catheters. The ultrasonically transparent electrode may enable the user to more easily apply the electrode to tissue within a region of interest, thereby allowing a reduction in the complexity associated with the prior art. For example, the present invention may enable the user to apply the electrode to the tissue by locating the tissue within the region of interest using the real time three dimensional images. In contrast, users of imaging probes in the prior art may locate the tissue and then manipulate a tool to the tissue by understanding the registration between the image and the physical location of the electrode on the probe. Moreover, the ultrasonically transparent electrode may reduce the occlusion of the tissue.

In the drawings and specification, there have been disclosed typical preferred embodiments of the invention and, although specific terms are employed, they are used in a generic and descriptive sense only and not for purposes of limitation, the scope of the invention being set forth in the following claims.

What is claimed is:

1. A real time three dimensional imaging catheter apparatus configured to emit ultrasonic energy for volumetric scanning and receive reflected ultrasonic energy, the apparatus comprising:

a mounting plate having a first and a second side wherein the mounting plate is transparent to ultrasonic energy and acoustically matched to a backing material overlying the first side of the mounting plate;

a plurality of spaced holes formed through the mounting plate, wherein a spacing between the holes is in a range between about 0.01 mm and 0.2 mm and wherein a diameter of the holes is in a range between about 0.01 mm and 0.2 mm;

a plurality of conductors, having proximal and distal ends, wherein the distal ends of the plurality of conductors are associated with corresponding holes in the first side of the mounting plate wherein the plurality of conductors are positioned so as to be substantially perpendicular to the mounting plate; and

an ultrasonic transducer phased array connected to and overlying the second side of the mounting plate wherein an element of the ultrasonic transducer phased array is operably responsive to a corresponding conductor associated with a corresponding hole in the mounting plate.

2. The apparatus of claim 1, further comprising an electrode assembly connected to and overlying the ultrasonic transducer phased array wherein the electrode assembly is transparent to ultrasonic energy.

3. The apparatus of claim 2, wherein the electrode assembly has a thickness that does not exceed about a wavelength of the ultrasonic energy emitted by the ultrasonic transducer phased array.

15

4. The apparatus of claim 2, wherein the electrode assembly comprises:

- a first ground layer connected to and overlying the ultrasonic transducer phased array having a thickness in a range between about 0.02 μm and 20 μm ;
- a first insulator layer connected to and overlying the first ground layer having a thickness in the range between about 0.02 μm and 20 μm ;
- a second ground layer connected to and overlying the first insulator having a thickness in the range between about 0.02 μm and 20 μm ;
- a second insulator layer connected to and overlying the second ground layer having a thickness in the range between about 0.02 μm and 20 μm ; and
- an electrode connected to and overlying the second insulator.

5. The apparatus of claim 1, wherein the ultrasonic transducer phased array comprises a plurality of sites occupied by ultrasonic transducer elements, wherein at least one ultrasonic transducer element is absent from at least one of the sites to define an interstitial site; and the apparatus further comprising a tool, positioned at said interstitial site.

6. The apparatus of claim 5, wherein the tool comprises a guide wire, a suction tool, an ablation electrode, a fiber optic lead, or an electrophysiological mapping electrode.

7. The apparatus of claim 5, wherein a plurality of elements are absent from a plurality of sites to define a plurality of interstitial sites, wherein the plurality of interstitial sites have a circular arrangement within the ultrasonic transducer phased array.

8. A real time three dimensional imaging probe apparatus configured to emit ultrasonic energy for volumetric scanning and receive reflected ultrasonic energy, the apparatus comprising:

- a mounting plate having a first and a second side and having a plurality of spaced holes therethrough;
- a backing material on the first side of the mounting plate, wherein the backing material is acoustically matched to the mounting plate;
- a plurality of conductors, having proximal and distal ends, wherein the distal ends of the plurality of conductors are associated with corresponding holes in the mounting plate; and
- an ultrasonic transducer phased array on the second side of the mounting plate wherein an element of the ultrasonic transducer phased array is operably responsive to a corresponding conductor associated with a corresponding hole in the mounting plate.

9. An apparatus according to claim 8, further comprising: an electrode assembly on the ultrasonic transducer phased array opposite the mounting plate.

10. An apparatus according to claim 9, wherein the electrode assembly is transparent to ultrasonic energy.

11. An apparatus according to claim 10, wherein the electrode assembly has a thickness that does not exceed about a wavelength of the ultrasonic energy emitted by the ultrasonic transducer phased array.

12. An apparatus according to claim 9, wherein the electrode assembly comprises:

- at least one ground layer on the ultrasonic transducer phased array;
- at least one insulator layer on the at least one ground layer; and
- an electrode on the at least one insulator layer.

16

13. An apparatus according to claim 8, wherein the electrode assembly comprises:

- a first ground layer connected to and overlying the ultrasonic transducer phased array having a thickness in a range between about 0.02 μm and 20 μm ;
- a first insulator layer connected to and overlying the first ground layer having a thickness in the range between about 0.02 μm and 20 μm ;
- a second ground layer connected to and overlying the first insulator having a thickness in the range between about 0.02 μm and 20 μm ;
- a second insulator layer connected to and overlying the second ground layer having a thickness in the range between about 0.02 μm and 20 μm ; and
- an electrode connected to and overlying the second insulator.

14. An apparatus according to claim 13, wherein the electrode assembly is transparent to ultrasonic energy.

15. A real time three dimensional imaging probe apparatus configured to emit ultrasonic energy for volumetric scanning and receive reflected ultrasonic energy, the apparatus comprising:

- a mounting plate having a first and a second side and having a plurality of spaced holes therethrough;
- a plurality of conductors, having proximal and distal ends, wherein the distal ends of the plurality of conductors are associated with corresponding holes in the mounting plate;
- an ultrasonic transducer phased array on the second side of the mounting plate wherein an element of the ultrasonic transducer phased array is operably responsive to a corresponding conductor associated with a corresponding hole in the mounting plate; and
- an electrode assembly on the ultrasonic transducer phased array opposite the mounting plate.

16. An apparatus according to claim 15, wherein the electrode assembly has a thickness that does not exceed about a wavelength of the ultrasonic energy emitted by the ultrasonic transducer phased array.

17. An apparatus according to claim 15, wherein the electrode assembly comprises:

- at least one ground layer on the ultrasonic transducer phased array;
- at least one insulator layer on the at least one ground layer; and
- an electrode on the at least one insulator layer.

18. An apparatus according to claim 15, wherein the electrode assembly comprises:

- a first ground layer connected to and overlying the ultrasonic transducer phased array having a thickness in a range between about 0.02 μm and 20 μm ;
- a first insulator layer connected to and overlying the first ground layer having a thickness in the range between about 0.02 μm and 20 μm ;
- a second ground layer connected to and overlying the first insulator having a thickness in the range between about 0.02 μm and 20 μm ;
- a second insulator layer connected to and overlying the second ground layer having a thickness in the range between about 0.02 μm and 20 μm ; and
- an electrode connected to and on the second insulator.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,572,551 B1
DATED : June 3, 2003
INVENTOR(S) : Smith et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 15,

Line 56, should read -- An apparatus according to claim 9, wherein the --

Column 16,

Line 1, should read -- An apparatus according to claim 9, wherein the --

Signed and Sealed this

Sixteenth Day of December, 2003

A handwritten signature in black ink, appearing to read "James E. Rogan", with a horizontal line underneath it.

JAMES E. ROGAN
Director of the United States Patent and Trademark Office

专利名称(译)	用于体积腔内超声成像的成像导管		
公开(公告)号	US6572551	公开(公告)日	2003-06-03
申请号	US09/546721	申请日	2000-04-11
[标]申请(专利权)人(译)	杜克大学		
申请(专利权)人(译)	杜克大学		
当前申请(专利权)人(译)	皇家飞利浦N.V.		
[标]发明人	SMITH STEPHEN W LIGHT EDWARD D FIERING JASON O		
发明人	SMITH, STEPHEN W. LIGHT, EDWARD D. FIERING, JASON O.		
IPC分类号	A61B8/12 A61B19/00 A61B5/0408 A61B5/042 A61B8/08 A61B8/00		
CPC分类号	A61B8/4488 A61B8/12 A61B5/0422 A61B8/0833 Y10S128/916 A61B19/52 A61B90/36		
外部链接	Espacenet USPTO		

摘要(译)

实时三维超声成像探头装置被配置为放置在身体内。该装置包括具有近端和远端的细长主体，超声换能器相控阵列连接到细长主体的远端并定位在细长主体的远端上。超声换能器相控阵列定位成发射和接收超声能量，用于从细长主体的远端进行体积正向扫描。超声换能器相控阵列包括由超声换能器元件占据的多个位置。至少一个超声换能器元件不存在于至少一个位置，从而限定间隙位置。工具位于插页式网站上。特别地，该工具可以是光纤引线，抽吸工具，导丝，电生理学电极或消融电极。还讨论了相关系统。

