



US 20140107492A1

(19) **United States**

(12) **Patent Application Publication**

Zhou et al.

(10) **Pub. No.: US 2014/0107492 A1**

(43) **Pub. Date: Apr. 17, 2014**

(54) **MECHANICAL SCANNING ULTRASOUND
TRANSDUCER WITH MICROMOTOR**

Publication Classification

(71) Applicant: **Muffin Incorporated**, West Lafayette,
IN (US)

(51) **Int. Cl.**
A61B 8/00 (2006.01)
A61B 8/12 (2006.01)

(72) Inventors: **Yun Zhou**, West Lafayette, IN (US);
Peter S. McKinnis, West Lafayette, IN
(US); **Neal E. Fearnot**, West Lafayette,
IN (US)

(52) **U.S. Cl.**
CPC *A61B 8/4461* (2013.01); *A61B 8/12*
(2013.01); *A61B 8/445* (2013.01); *A61B*
8/4494 (2013.01)

USPC 600/467; 600/462; 600/459

(21) Appl. No.: **14/051,812**


(57) **ABSTRACT**

(22) Filed: **Oct. 11, 2013**

A system for use with ultrasound procedures including an ultrasound control and/or imaging system which has a micro-miniature motor, a rotatable reflector and a stationary ultrasound transducer. The transducer may be placed between the motor and the reflector, so as to eliminate the need for placement of wires or other artifact-creating items in the path of ultrasound signals. In particular embodiments, such systems can be incorporated in or retrofitted to commercially standard diagnostic and therapeutic catheters or other housings. Examples can be used in variety of ultrasound procedures, e.g. to perform intravascular ultrasound (IVUS) imaging.

Related U.S. Application Data

(60) Provisional application No. 61/713,186, filed on Oct. 12, 2012.






Fig. 1




Fig. 2

MECHANICAL SCANNING ULTRASOUND TRANSDUCER WITH MICROMOTOR

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims the benefit of U.S. Provisional Application No. 61/713,186 filed Oct. 12, 2012, which is hereby incorporated by reference.

BACKGROUND

[0002] Intravascular ultrasound (IVUS) allows the use of ultrasound technology to gather images from within portions of a body. In recent years, IVUS technology has provided physicians with the ability to obtain important diagnostic information that is not available from traditional x-ray techniques or other ultrasound techniques, thereby increasing the effectiveness of diagnosis and treatment. For example, IVUS can help to determine plaque volume and the degree of stenosis within an artery lumen. That information is often difficult to obtain through angiographic imaging and exterior ultrasound imaging, particularly in regions having multiple overlapping arterial segments.

[0003] One type of ultrasound transducer includes a stationary ultrasound array which can image the full slice of the body tissue due to the particular positioning of the ultrasound elements in the array. Other configurations include a single, rotating ultrasound element, which obtains imaging data by mechanically rotating the ultrasound element during imaging. In that case, a cross-sectional image of the body tissue is obtained by the ultrasound element emitting sequential ultrasound pulses at changing rotational positions. Advantages of the single-element rotational design when compared to an array design include smaller size, better image quality, possible higher center frequency, lower cost for the ultrasound imaging console, and less ring down artifacts (dead zone).

[0004] Single element designs can also include certain disadvantages, such as non-uniform rotational distortion (NURD). During imaging procedures including a single element design, the ultrasound element is typically rotated with a torque cable. Ultrasound pulses are emitted in an even-spaced time-sequential manner under the expectation of a uniform rotation rate of the ultrasound element. Each reflected ultrasound pulse represents a portion of a cross-sectional image. An image processor assembles the data based on the assumption that the data points represent images from evenly-spaced pulses. However, it can be difficult to achieve a uniform rotation rate for the ultrasound element when using a torque cable as a driving means. The ultrasound element can be one to two meters from the driving end of the torque cable. The torque cable must follow all the bends along the path of a blood vessel to reach the region to be imaged and there can be a lag (a delay in transfer) in the rotation of the torque cable from the handle end to the distal or operational end which causes the ultrasound element to rotate at a non-uniform rate even when the rotation source rotates at a uniform rate. The non-uniform rate causes the resulting images to be distorted.

[0005] Other problems exist in current designs. Typically, IVUS elements are mounted to a dedicated catheter. The IVUS catheter usually shares the same utility lumen as other therapeutic catheters preventing a physician from performing IVUS imaging monitoring simultaneously with or during a

single procedure with other intravascular procedures, such as, for example, deploying a stent or graft or performing a biopsy. [0006] Attempts to create single element IVUS imaging systems without torque cables present further problems. Current commercialized designs use costly rotary transformers to connect stationary electrical wires from a console to a rotating ultrasound transducer. However, the rotary transformer is among the most expensive parts of a mechanical scanning IVUS catheter. Alternative designs place a rotary transformer on a console (proximal) side of the reflector. However, the cost of the coaxial connector that couples both mechanical movement and an electrical signal is comparable to the cost of the rotary transformer, further increasing overall cost.

[0007] Thus, there is a need to have an ultrasound emission design that could be integrated to a general catheter or other device for internal use in a patient, that is cost effective, and which produces images free from NURD artifacts.

SUMMARY

[0008] Among other things, there are disclosed embodiments of a system for use with ultrasound procedures including an ultrasound control or imaging system which has a microminiature motor, a rotatable reflector and a stationary ultrasound transducer which is mountable to or incorporated in internal medical devices such as commercially standard diagnostic and therapeutic catheters, and in particular examples can perform two-dimensional (2D) IVUS imaging.

[0009] In particular embodiments, the system is a stand alone device which is configured to be adaptable to existing medical devices such as catheters and other devices which are used internally (e.g. intravascularly, per- or subcutaneously, or through insertion into a bodily orifice). The reflector is positioned distally relative to the transducer and is connected to a rotary shaft of the microminiature motor. The transducer is connected to a support which is positioned concentric relative to the shaft of the motor. The housing of the microminiature motor is connected to a housing of the system. The support of the ultrasound element is also connected to the housing of the system. In that way the reflector is rotatable about an axis while the transducer remains stationary relative to the housing.

[0010] The system is capable of creating an image as a two-dimensional slice, a cone shape slice, or a toroidal section shape of a portion of body tissue. The image is obtained through use of a single element ultrasound transducer which emits an ultrasound signal along the axial direction of the ultrasound transducer. The reflector reflects the ultrasound signal in a direction non-parallel, and in particular embodiments perpendicular, to the ultrasound transducer axial direction. As the reflector rotates through a 360 degree arc, an image is created of a section of body tissue.

[0011] Embodiments of the ultrasound element can include wire(s) configured to run along or through the support. Because the reflector is located distally relative to the ultrasound element and the wires connecting the ultrasound element run towards an ultrasound system console or proximal end of the system, the imaging plane is free from any wires which would otherwise cross the imaging plane and create an artifact or blocked portion of the ultrasound image.

[0012] The system is configured, in some embodiments, to be attachable to existing medical devices, such as, for example, a catheter. The system may be placed within an existing lumen or alternatively could be attached externally to a medical device. Wires connecting the ultrasound element

and the microminiature motor could be routed through a dedicated lumen which can be attached externally to a medical device or alternatively it could be routed within the medical device such as through an existing lumen within a catheter.

[0013] In specific embodiments, a system for use with ultrasound procedures includes an ultrasound element connected to a support for maintaining the transducer in position, the transducer adapted to emit and receive ultrasound signals substantially along an axis, and a reflector connected to a shaft, the reflector positioned with respect to the ultrasound element to reflect in a direction non-parallel to the axis ultrasound waves emitted from the transducer. The shaft and support are positioned concentrically and the shaft is rotatable relative to the support about the axis. A housing around the transducer and the reflector may be provided, with the support fixed in a stationary position relative to the housing. At least one electrical wire may be connected to the transducer, with the reflector angled with respect to the axis of the transducer so that a reflection direction from the reflector is non-parallel to the axis, and so that the wire does not cross the reflection direction. Particular embodiments have a reflector that forms an angle between 10 and 84 degrees with respect to the axis.

[0014] Examples of a microminiature motor rotatably connected to the shaft include a piezoelectric or electromagnetic motor. Part of the support for the transducer may be positioned concentrically inward relative to the motor, and the motor, reflector, and transducer are configured to be positioned in a medical device, and configured for internal use (e.g. sized and configured for intravascular usage). One or more electrical wires connected to the transducer and one or more electrical wires connected to the microminiature motor are provided in specific embodiments, for example wherein at least one electrical wire is housed within the support. A housing containing the reflector and transducer may be provided, with the housing having a leading end, and wherein the reflector is positioned between the leading end and the transducer. An example of a transducer is a single element transducer.

[0015] In further examples, an internal ultrasound system includes a transducer connected to a support, a reflector positioned distally of the ultrasound element to reflect a signal from the ultrasound element, the reflector connected to a shaft, and a microminiature motor connected to the shaft and configured to cause the shaft to rotate. The motor, reflector, and transducer are configured to be positioned in a medical device having a leading end and adapted for internal medical use, and wherein the reflector is closer to the leading end than the transducer is to the leading end. The motor may be a piezoelectric or an electromagnetic motor, as noted above, with a size of approximately 0.3 mm to 4 mm. The shaft and support can be positioned concentrically, and the shaft may be rotatable about an axis relative to the support. A housing may be provided so that the support is fixed in a stationary position relative to the housing. Particular embodiments include the support being positioned concentrically inward relative to the motor, and/or the use of a single element transducer. One or more electrical wires may be connected to the transducer and one or more electrical wires may be connected to the motor, for example with at least one electrical wire housed within the support. The shaft is rotatable about an axis coaxial with the support in some embodiments, with the reflector generating a viewing angle approximately perpendicular to the axis, and at each angular position of the reflector the viewing angle does not cross any electrical conductors.

[0016] Embodiments of ultrasound systems may have a motor with a drive shaft, a stationary transducer positioned coaxially with the motor and configured to emit and receive ultrasound signals, and a mirror positioned to reflect an ultrasound signal between the transducer and a viewing window and operatively disposed to rotate in response to with the drive shaft. The viewing window is free from any echo-opaque members (i.e. members having an acoustic impedance such that all or a substantial fraction of ultrasound striking them will be reflected).

[0017] The system described herein can be used with existing ultrasound imaging equipment and procedures. For example, the system can be used with an ultrasound imaging system which includes a console portion having a user interface and controls for a physician as well as a display for displaying an ultrasound image. The console portion can be connected to commercially available ultrasound probes or catheters with compatible pinout or other medical devices which are configured for internal procedures. The system as described herein can be attached to a catheter or other medical device such that ultrasound procedures can be performed simultaneously or sequentially with other procedures. Accordingly, the system described herein will allow a physician to retrofit existing medical devices such as catheters or biopsy needles with an ultrasound system such that ultrasound procedures can be performed simultaneously along with other medical procedures such as deploying a stent or graft obtaining a biopsy sample, tissue resection, making or closing holes in tissue, ablation, cauterizing, stone removal, drug delivery, cell delivery, filter delivery, lasing, aspiration, device deployment or removal, stimulation of tissue, lavage, fluid drainage, centesis, treating conditions such as pneumothorax, PCI, or thrombolysis, and other medical procedures.

[0018] Further forms, objects, features, aspects, benefits, advantages, and embodiments of the present disclosure will become apparent from a detailed description and drawings provided herewith.

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] FIG. 1 is a partial cross-sectional illustrative view of an IVUS imaging system.

[0020] FIG. 2 is a partial cross-sectional illustrative view of the IVUS imaging system of FIG. 1, taken along the line 2-2 in FIG. 1.

DESCRIPTION OF THE SELECTED EMBODIMENTS

[0021] For the purpose of promoting an understanding of the principles of the disclosure, reference will now be made to the embodiments illustrated in the drawings and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the claims is thereby intended. Any alterations and further modifications in the described embodiments, and any further applications of the principles of the disclosure as described herein are contemplated as would normally occur to one skilled in the art to which the disclosure relates.

[0022] FIG. 1 is an illustrative view of device or system 100 useful in internal ultrasound procedures. Such devices may be diagnostic or therapeutic (including interventional) in application, and include devices inserted percutaneously, subcutaneously or endoluminally into the patient. Examples of such

devices include embodiments designed for intravascular ultrasound (IVUS) imaging or treatment of deep vein thrombosis (DVT).

[0023] Device **100** is usable with an ultrasonic control or analytical (e.g. imaging) system which includes an ultrasound console connected to device **100**. The ultrasound console generally includes controls usable by a physician during an ultrasound procedure, and in cases of imaging systems, can include a graphic display which displays graphical images obtained during ultrasound procedures. For example, the ultrasound console can be of a type generally used for medical ultrasonic imaging. Embodiments of device **100** can be used at various locations of a body such as a blood vessel (e.g. IVUS), gastrointestinal tract, urogenital passages (e.g. urethra, ureter, vagina, rectum), throat, nose, ear, or through an artificial opening by percutaneous puncture for example. Device **100** is configured to be used in conjunction with another medical device, such as a catheter, and is capable of emitting and receiving ultrasound signals and then transferring electronic signals (e.g. RF signals) representing the ultrasound signals to the console. The console is configured to extract information from such electronic signals and provides data to the user (e.g. by creating an image viewable on a display). Device **100** when used as an imaging device is configured to create an image of a section of body tissue which may be a two-dimensional slice, a conical slice, or a toroidal-shaped section which is taken from a section which is rotationally symmetric.

[0024] The illustrated embodiment of device **100** includes an ultrasound transducer **102** and a reflector **104**. Transducer **102** and reflector **104** are indicated schematically in the drawings, positioned within a housing **106**. The term “transducer” should be understood to include an assembly of two or more parts as well as a single piece. It will further be understood that “transducer” as used herein includes devices that transmit ultrasound (i.e. transform an electrical (RF) signal to ultrasound), receive ultrasound (i.e. transform ultrasound to an electrical (RF) signal), or both. If multiple transducers or pieces are provided, transmission of ultrasound may occur at one and reception at another. Transducer(s) as described herein may have one or more piezoelectric elements as respective transducers, and may operate in combination with other transducers within or outside the body. As examples, “transducer” as used herein includes a single element transducer on a rotating and pivoting member, a one-dimensional array of elements on a rotating and pivoting member, and a stationary single element transducer generally aimed at a mirror on a rotating and pivoting member. Transducer **102** in a specific embodiment is capable of emitting and receiving ultrasound signals or waves in a range of frequencies which are typically used in therapeutic, imaging or other medical ultrasound procedures, such as, for example, in the range from 20 KHz to 100 MHz.

[0025] The reflector **104** is configured to reflect or otherwise redirect an ultrasound signal from element **102** in a new direction. The reflector **104** can be constructed of any of a variety of materials. The reflector **104** includes a reflection surface **108**. The reflection surface **108** is preferably constructed as a smooth surface in order to minimize any scattering of the ultrasound signal that would occur during reflection. In the present example, the reflection surface is an elliptical disc which appears circular when viewed at an angle offset from axis **120** as shown in FIG. 2. The elliptical design could maximize reflection of the ultrasound beam (i.e. reflect

the all or a substantial portion of the ultrasound beam) and minimize the distortion of ultrasound beam from transducer **102**, providing improved image quality in imaging applications. The reflection surface **108** can be integral to a frame **109** of reflector **104**. Alternatively, the reflector **104** can include a structure portion or substrate part of frame **109** which includes a coated surface or layered material comprising the reflection surface **108**. For example, the reflection surface **108** could include a metal or mirror material applied to frame **109** of reflector **104** in order to create the reflection surface **108**. With that understanding, the reflector **104** can be generally comprised of any of a variety of materials such as metal, ceramic, or a polymer or any other material which provides adequate reflection characteristics due to sufficiently varied acoustic impedance between the reflection surface **108** and the acoustic impedance of the surrounding environment.

[0026] In the illustrated embodiment, transducer **102** is oriented so that it emits and receives ultrasound generally along the central longitudinal axis **120** of device **100**. In such cases, reflector **104** is arranged so that reflection surface **108** forms an angle of approximately 45 degrees with axis **120**. In that configuration, ultrasound waves emitted from ultrasound element **102** along axis **120** will be redirected by reflection surface **108** substantially perpendicularly to axis **120**, or along a radius of housing **106**. In other embodiments, reflection surface **108** may form a larger angle with respect to axis **120**, redirecting waves more distal or forward of reflector **104**, or reflection surface **108** may form a smaller angle with respect to axis **120**, redirecting waves more proximal or behind reflector **104**. In particular, it has been determined that a slightly forward-looking embodiment may be preferred for reducing undesired effects, for example one in which the reflection surface forms an angle of approximately 42 degrees with axis **120**.

[0027] The housing **106** is configured to contain the ultrasound element **102**, the reflector **104** and other components which make up the IVUS imaging system **100**. The housing **106** provides structural support for the components of the IVUS imaging system **100**. The housing **106** is illustrated in FIG. 1 as a generally cylindrical shape. The housing **106** can be a stand-alone structure for the IVUS imaging system **100** or it can be part of an additional medical device. For example, the housing **106** could be a portion of a catheter which includes the IVUS imaging system **100**. The housing **106** is sealed such that it provides protection to the components of the IVUS imaging system **100** from intrusion of unwanted substances, such as, for example blood. The housing **106** is constructed of a material which is relatively echolucent, i.e. providing a small difference in acoustic impedance compared to the working environment. For example, when used within a blood vessel containing body tissues and blood, housing **106** may be constructed of a structurally rigid polymer material such as polymethylpentene (PMP), polyethylene (PE), or acrylonitrile butadiene styrene (ABS), which have acoustic impedances similar to that of body fluids such as blood. At least the portion of housing **106** and/or a catheter wall which serves as an ultrasound window will have optimal transmission of ultrasound when its thickness is approximately a positive integer multiple of $\frac{1}{2}$ of the wavelength corresponding to center frequency of the ultrasound beam.

[0028] The immediate interior of device **100** (which includes transducer **102** and reflector **104**) can be completely filled with a fluid that presents ultrasound-carrying characteristics that are similar to the fluid outside of chamber **26**. In

embodiments used for IVUS procedures, the fluid can be a saline solution, mineral oil, castor oil, alcohol, or other substance providing ultrasound characteristics (e.g. acoustic impedance) around reflector **104** similar to those outside housing **106** (e.g. blood in a blood vessel). A port (not shown) may be placed in the wall **24** bounding chamber **26** to allow a user to inject the fluid into housing **106** just prior to use of device **20**. One or more seals may be placed in device **20** to separate the fluid from motor **100**, discussed below. Saline and/or alcohol have very good acoustic transmission and low viscosity (low friction), but they are corrosive and must be injected or otherwise placed in chamber **26** at the time of use. Oils (e.g. mineral or castor oil) have slightly worse acoustic properties and much higher viscosity (higher friction), but may be placed in chamber **26** well before using device **20**. The fluid is lubricious so as to allow rotation of reflector **104** with minimal interference from frictional torque forces acting against reflector **104** during rotation. The similar acoustic impedances of the exterior environment, housing **106**, and interior of device **100** provides a pathway for ultrasound signals to travel from transducer **102** to body tissue with minimal signal loss from undesired scattering and absorption. In this way, acoustic matching can be achieved between body fluids, a catheter wall or housing **106**, and the medium immediately surrounding ultrasound element **102** and reflector **104**. Acoustic matching ensures that minimal signal losses occur when transmitting and receiving ultrasound signals between ultrasound element **102** and body tissue which enhances the clarity of the resulting image.

[0029] Device **100** includes a microminiature motor **110** in this embodiment, for example a piezoelectric motor or an electromagnetic motor. The microminiature motor **110** is configured to impart a rotational motion to the reflector **104**. Motor **110** is preferably of a small size, such as a diameter in the range from 0.3 mm to 4 mm. An advantage of a piezoelectric motor **110** compared to other motors such as electromagnetic motors is that the efficiency of the piezoelectric motor is independent of size and piezoelectric motor usually has a high torque-to-size ratio.

[0030] Microminiature motor **110** includes a stator portion **116** which is fixed to or with respect to housing **106** such that it does not move relative to the housing **106**. The motor **110** also includes a rotor portion or shaft **118** which is rotatable relative to the stator portion **116**. The rotor portion **118** is concentric relative to the stator portion **116**. The motor **110** in this embodiment is capable of using continuous or pulsed ultrasonic vibrations to provide movement of the rotor portion **118** relative to the stator portion **116** such that the rotor portion **118** rotates relative to the stator portion **116**.

[0031] An arm **112** connects to reflector **104** to provide an extension and support for the reflection surface **108**. Arm **112** is fixedly attached to a shaft **114**, with shaft **114** being a part of or fixedly attached to rotor portion **118** of motor **110**, so that when the rotor portion **118** rotates (i.e. relative to the stator portion **116** and correspondingly to the housing **106**), the shaft **114** also rotates relative to the stator portion **116** and the housing **106**. In particular embodiments, one or both of shaft **114**, **118** are hollow and/or have an irregular (e.g. non-cylindrical) configuration. The shaft **114** is positioned in a concentric arrangement with the rotor portion **118** and the stator portion **116** relative to the axis **120**. The arm **112** provides a radial offset so that arm **112** can bypass the ultrasound element **102** while providing that the reflector **104** can rotate coaxially relative to an axis **120**. The shaft **114** is

generally configured as a cylinder in this embodiment. According to this arrangement, the motor **110** is capable of imparting a rotational motion to the reflector **104** such that the reflector **104** rotates about the axis **120**.

[0032] Transducer **102** is fixedly supported by a support **122**. The support **122** is a generally cylindrical structure which is positioned concentrically relative to the shaft **114** and also relative to the stator portion **116** and the rotor portion **118**. In one example, the support **122** is linked to shaft **114** through the use of bearings **124** such that shaft **114** is rotatable around fixed support **122**. The support **122** is fixed with respect to the housing **106** and the stator portion **116**. The support **122** can be fixed to the housing **106** at a location of device **100** which is not shown in FIG. 1. In this configuration, transducer **102** is held stationary relative to the housing **106** while the reflector **104** is rotatable about the axis **120** relative to transducer **102** and the housing **106**. According to this configuration, the support **122** is positioned concentric with the shaft **114**, **118** and the motor **110** such that the support **122** is positioned concentrically inward of the motor **110** or alternatively follows a path through a central lumen existing within the motor **110** or rotor shaft **118**. The illustrated embodiment of device **100** eliminates the need for and problems associated with a rotating ultrasound transducer. Additionally, the design eliminates the need for an ultrasound array.

[0033] Device **100** includes one or more connection wires which are connected to transducer **102** and which run through or along the support **122**. Accordingly, the connection wires for transducer **102** also run through the center portion of the microminiature motor **110** in this embodiment. Device **100** also includes one or more wires which connect to the microminiature motor **110** and which provide control signals and/or electric energy to the microminiature motor **110**. Connections in this respect may be maintained via slip ring connection(s) and/or capacitive coupler(s).

[0034] During operation of device **100**, a physician can position device **100** within the patient using a positioning device such as a catheter, sheath or a wire guide, e.g. placed on or in a catheter or sheath or over a wire guide. As previously noted, embodiments of device **100** may be used in any of a number of locations within a patient, including within the vasculature, and examples reflecting use in the vasculature are noted below. Once system **100** is properly positioned in or near the desired area of body tissue (e.g. tissue to be imaged), microminiature motor **110** is powered such that the rotor portion **118** rotates, e.g. at a uniform angular velocity. Correspondingly, the reflector **104** rotates about the axis **120** in the same manner. Transducer **102** is energized through the connection wire which runs partially through the support **122** and continues to the console of the ultrasound system. Transducer **102** transmits an ultrasound signal substantially in an axial direction relative to the support **122** in this embodiment, i.e. substantially parallel to the axis **120**. Almost all of the ultrasound signal encounters the reflective surface **108** and is substantially reflected in a direction away from (e.g. perpendicular) to the axis **120** as denoted by reflection direction **126**.

[0035] The ultrasound signal (e.g. beam or pulse(s)) passes through the housing **106** until it encounters body tissue, plaque, or other material which has acoustic impedance sufficiently different from surrounding environment (e.g. bodily fluids) to form an acoustic impedance boundary, as at a vascular tissue/blood boundary. At such a boundary, the ultrasound signal is at least partially reflected or otherwise at least

partially scattered. As an example, a portion of the ultrasound signal is reflected back towards the reflection surface **108**. Upon encountering the reflection surface **108**, the ultrasound signal is substantially reflected back towards transducer **102**. Simultaneously or subsequently transducer **102** continues to transmit further ultrasound signals and the process is repeated, continuously in certain embodiments over a desired period of time.

[0036] During this process, the reflector **104** is rotated about the axis **120** such that the reflection surface **108** causes the reflection direction **126** to move in a sweeping direction which takes the form of a slice, cone shape, or toroidal shape. In this manner, while the reflector **104** rotates about the axis **120**, transducer **102** is able to emit and receive ultrasound signals sufficient for the ultrasound system to create or analyze data (e.g. an image) of surrounding body tissue. According to the specifics of the ultrasound procedure or the desires of the physician performing the procedure, device **100** can be moved in an axial direction so that multiple two-dimensional images (or other sets of data) are created at different locations. In this way, the two-dimensional data or images can be processed into a three-dimensional data set or image or alternatively the physician can gain a three dimensional conceptual understanding of the physical characteristics of the adjacent body tissue.

[0037] In embodiments used for imaging, device **100** facilitates capture of an image which is free from unnecessary artifacts, obstructions or errors within the image. For example, the arrangement of transducer **102** and the reflector **104** (whereby the support **122** is positioned coaxial with the shaft **114**) does not require any wires or other echogenic (i.e. prone to scattering) materials to be positioned within or across the reflection direction **126**, even as the reflection direction sweeps around the circumference of housing **106**. In this way, there are no wires or other echogenic materials which could cause artifacts within the image or block portions of the redirected ultrasound waves, allowing the physician a clear view of the entirety of the image. Additionally, the microminiature motor **110** which is positioned proximal to the rotating reflector **104** allows a uniform angular velocity to be achieved by the reflector **104**. This uniform angular velocity results in an ultrasound image which is free from non-uniform rotational defects (NURD) which can otherwise be a problem with the designs using torque cables and relatively remote motors or rotational power sources.

[0038] Device **100** is configured to be used with existing medical devices which are designed for percutaneous, intraluminal, or interstitial procedures. For example, device **100** can be used with a variety of commercially available catheters, e.g. positioned on or within a distal portion or end of a catheter depending on the particular configuration. Device **100** can be positioned within an existing lumen within the catheter. Additionally, device **100** could be mounted externally to the catheter using a variety of mounting devices, glues or other types of arrangements, or could be fashioned with a catheter such that the catheter outer diameter is substantially the same as that of housing **106** (e.g., housing **106** substantially forms a part of the catheter or is sandwiched between catheter parts). Embodiments of device **100** can permit a physician to perform procedures (such as placing or moving stents, grafts, balloons or other structures, administering therapeutics, or other tasks) while simultaneously or sequentially imaging body tissue.

[0039] Device **100** includes one or more wires which are routed from the portion of device **100** containing transducer **102** and microminiature motor **110** along the length of the catheter or other medical device to the ultrasound control system console. These wires are connected to transducer **102** and the microminiature motor **110** and transfer radio frequency (RF) signals as well as electrical energy to transducer **102** and the microminiature motor **110**. In the case of retrofitting a catheter with device **100**, the wires can be routed through a dedicated lumen which can be attached externally to the catheter or alternatively could be routed through an existing lumen within the catheter. Additionally, the microminiature motor **110** could be powered by a battery which is located at a distal portion of device **100** (i.e. the end within the patient, distant from the user) near the microminiature motor **110**.

[0040] Device **100** could also be used for a variety of other medical procedures and with a variety of other medical devices. The versatility of the embodiments described herein allows ultrasound to be used to guide percutaneous therapeutic interventions such as for example placement of embolism coils, stents, filters, grafts, or balloons via IVUS, performance of biopsies, administering therapeutics, etc. Device **100** can be used to locate various anatomical landmarks that will be used to correctly place or guided therapy. Typical landmarks in the vascular context include confluences, bifurcations, side branches, nearby vessels, nearby nerves, the heart, and other tissues adjacent to vessels or other orifices in which transducer **102** is placed. Device **100** can also be used to locate diseased tissue that will be treated or avoided, such as use during a biopsy to provide an image of a needle being deployed into tissue. During a TIPS procedure an image can be produced to allow a physician to watch a needle being placed into the portal vein. For AAA delivery device **100** can allow a physician to place a guide wire into a contralateral leg. Device **100** could also be used to image the location of a deployed implantable device both during and after deployment.

[0041] It will be understood by those skilled in the art that the particular type of mounting procedure for device **100** to an existing medical device can include a variety of different types of mounting methods. Accordingly, the particular methods described herein are not indicative of any limiting aspects of the use capabilities of device **100**.

[0042] Although particular materials were highlighted herein for some components of device **100**, those materials are not intended to be limiting of the types of materials which are suitable to be used in device **100**. Additionally, where materials were not highlighted, a variety of materials could be used such as certain types of metals, polymers, ceramics or other types of materials which are suitable for use in devices for subcutaneous use as well as in imaging or other ultrasound procedures.

[0043] While the disclosure has been illustrated and described in detail in the drawings and foregoing description, the same is to be considered as illustrative and not restrictive in character, it being understood that only particular embodiments have been shown and described and that all changes, equivalents, and modifications that come within the spirit of the claims are desired to be protected. Features particularly described with respect to one embodiment or structure may be used with or incorporated into other embodiments or structures. All publications, patents, and patent applications cited in this specification are herein incorporated by reference as if

each individual publication, patent, or patent application were specifically and individually indicated to be incorporated by reference and set forth in its entirety herein. In particular, Application Ser. No. 61/713,135 and filed Oct. 12, 2012; Ser. No. 61/713,172 and filed Oct. 12, 2012; Ser. No. 61/713,142 and filed Oct. 12, 2012, are each incorporated herein by reference in their entireties.

1. A system for use with ultrasound procedures comprising:

an transducer connected to a support for maintaining the transducer in position, the transducer adapted to emit and/or receive ultrasound signals substantially along an axis;

a reflector connected to a shaft, the reflector positioned with respect to the ultrasound element to reflect in a direction non-parallel to the axis ultrasound waves emitted from the transducer; and

wherein the shaft and support are positioned concentrically and at least a part of the support is positioned concentrically inward relative to the microminiature motor, so that the shaft is rotatable relative to the support about the axis.

2. The system of claim 1, further including a housing around the transducer and the reflector, wherein the support is fixed in a stationary position relative to the housing.

3. The system of claim 1, further comprising at least one electrical wire connected to the transducer, wherein the reflector is angled with respect to the axis of the transducer so that a reflection direction from the reflector is non-parallel to the axis, and wherein the wire does not cross the reflection direction.

4. The system of claim 3, wherein the reflector forms an angle of between about 10 and 84 degrees with respect to the axis.

5. The system of claim 1, further comprising a microminiature motor rotatably connected to the shaft.

6. The system of claim 5, wherein the microminiature motor is a piezoelectric motor.

7. The system of claim 5, wherein the microminiature motor is an electromagnetic motor.

8. The system of claim 5, wherein the microminiature motor, reflector, and transducer are configured to be positioned in a medical device, configured for internal use.

9. The system of claim 8, further comprising one or more electrical wires connected to the transducer and one or more electrical wires connected to the microminiature motor.

10. The system of claim 9, wherein at least one electrical wire is housed within the support.

11. The system of claim 1, further comprising a housing containing the reflector and transducer, the housing having a leading end, wherein the reflector is positioned between the leading end and the transducer.

12. The system of claim 1, wherein the transducer is a single element transducer.

13. The system of claim 1, sized and configured for intravascular usage.

14. An internal ultrasound system comprising:

an transducer connected to a support;

a reflector to reflect a signal from and/or to the ultrasound element, wherein the reflector is connected to a shaft; and

a microminiature motor connected to the shaft and configured to cause the shaft to rotate;

wherein the microminiature motor, reflector, and transducer are configured to be positioned in a medical device having a leading end and adapted for internal medical use, and wherein the reflector is closer to the leading end than the transducer is to the leading end.

15. The system of claim 14, wherein the microminiature motor is a piezoelectric motor having a size of approximately 0.3 mm to 4 mm.

16. The system of claim 14, wherein the microminiature motor is an electromagnetic motor having a size of approximately 0.3 mm to 4 mm.

17. The system of claim 14, wherein the shaft and support are positioned concentrically and wherein the shaft is rotatable about an axis relative to the support.

18. The system of claim 17, further comprising a housing, wherein the support is fixed in a stationary position relative to the housing.

19. The system of claim 14, wherein at least a part of the support is positioned concentrically inward relative to the microminiature motor.

20. The system of claim 14, wherein the transducer is a single element transducer.

21. The system of claim 14, further comprising one or more electrical wires connected to the transducer and one or more electrical wires connected to the microminiature motor.

22. The system of claim 21, wherein at least one electrical wire is housed within the support.

23. The system of claim 21, wherein the shaft is rotatable about an axis coaxial with the support, wherein the reflector generates a viewing angle approximately perpendicular to the axis, and wherein at each angular position of the reflector the viewing angle does not cross any electrical conductors.

* * * * *

专利名称(译)	机械扫描超声换能器与微电机		
公开(公告)号	US20140107492A1	公开(公告)日	2014-04-17
申请号	US14/051812	申请日	2013-10-11
[标]申请(专利权)人(译)	玛芬股份有限公司		
申请(专利权)人(译)	MUFFIN INCORPORATED		
当前申请(专利权)人(译)	MUFFIN INCORPORATED		
[标]发明人	ZHOU YUN MCKINNIS PETER S FEARNOT NEAL E		
发明人	ZHOU, YUN MCKINNIS, PETER S. FEARNOT, NEAL E.		
IPC分类号	A61B8/00 A61B8/12		
CPC分类号	A61B8/445 A61B8/12 A61B8/4461 A61B8/4494 A61B8/4483 A61B8/483 F04C2270/041 G01S15/8943 G10K11/357		
优先权	61/713186 2012-10-12 US		
其他公开文献	US9456802		
外部链接	Espacenet USPTO		

摘要(译)

一种用于超声程序的系统，包括超声控制和/或成像系统，其具有微小型马达，可旋转反射器和固定超声换能器。换能器可以放置在电动机和反射器之间，以便消除在超声信号的路径中放置导线或其他伪影产生物的需要。在特定的实施方案中，此类系统可以并入或改装到商业标准的诊断和治疗导管或其他外壳中。实例可用于各种超声程序，例如，进行血管内超声 (IVUS) 成像。

