



US006306096B1

(12) **United States Patent**
Seward et al.

(10) **Patent No.:** **US 6,306,096 B1**
(45) **Date of Patent:** **Oct. 23, 2001**

(54) **VOLUMETRIC IMAGE ULTRASOUND
TRANSDUCER UNDERFLUID CATHETER
SYSTEM**

4,110,723 8/1978 Hetz et al. .

(List continued on next page.)

(75) Inventors: **James Bernard Seward; Abdul Jamil
Tajik**, both of Rochester, MN (US)

44 23 808 A1 1/1995 (DE) .
0 234 951 9/1987 (EP) .
0 600 568 A1 6/1994 (EP) .

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Mayo Foundation for Medical
Education and Research**, Rochester,
MN (US)

(List continued on next page.)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

(21) Appl. No.: **09/586,193**

Belohlavek, M. et al., "Three- and Four-Dimensional Cardiovascular Ultrasound Imaging: A New Era for Echocardiography", *Mayo Clin Proc.*, 68:221-240 (Mar. 1993).
Bom, N. et al., "Early and Recent Intraluminal Ultrasound Devices", *International Journal of Cardiac Imaging*, 4:79-88 (1989).

(22) Filed: **Jun. 2, 2000**

(List continued on next page.)

Related U.S. Application Data

Primary Examiner—Francis J. Jaworski

(63) Continuation of application No. 09/087,520, filed on May 29, 1998, now Pat. No. 6,099,475, which is a continuation of application No. 09/003,248, filed on Jan. 6, 1998, now Pat. No. 6,129,672, which is a continuation of application No. 08/678,380, filed on Jun. 28, 1996, now Pat. No. 5,704,361, which is a continuation-in-part of application No. 08/305,138, filed on Sep. 13, 1994, now abandoned, which is a continuation of application No. 07/972,626, filed on Nov. 6, 1992, now Pat. No. 5,345,940, which is a continuation-in-part of application No. 07/790,580, filed on Nov. 8, 1991, now Pat. No. 5,325,860.

(74) *Attorney, Agent, or Firm*—Merchant & Gould P.C.

(57)

ABSTRACT

(51) **Int. Cl.**⁷ **A61B 8/12**
(52) **U.S. Cl.** **600/463; 600/467**
(58) **Field of Search** 600/439, 443-446,
600/447, 462-463, 471, 128, 916, 606,
159, 169


An underfluid ultrasound imaging catheter system includes a catheter having a distal end inserted into an underfluid structure, an ultrasonic transducer array mounted proximate the distal end of the catheter wherein the array has a row of individual transducer crystals, a lens mounted on the array for defocusing ultrasound beams in a direction perpendicular to an axis of the array so as to provide a volumetric field of view within which the underfluid features are imaged. Alternatively, the single row of transducer crystals is replaced by multiple rows of transducer crystals so as to provide a volumetric field of view. This imaging catheter system helps an operator see 3-dimensional images of an underfluid environment, such as the 3-dimensional images of fluid-filled cavities of heart, blood vessel, urinary bladder, etc. Features in such wide volumetric field of view can be imaged, measured, or intervened by an underfluid therapeutic device with an aid of the real-time image.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,789,833 2/1974 Bom .
3,817,089 6/1974 Eggleton et al. .
3,938,502 2/1976 Bom .
4,028,934 6/1977 Sollish .

2 Claims, 14 Drawing Sheets



U.S. PATENT DOCUMENTS

4,327,738	5/1982	Green et al. .	5,285,788	2/1994	Arenson et al. .
4,354,502	10/1982	Colley et al. .	5,291,893	3/1994	Slayton .
4,374,525	2/1983	Baba .	5,295,486	3/1994	Wollschlager et al. .
4,391,282	7/1983	Ando et al. .	5,297,553	3/1994	Silwa, Jr. et al. .
4,462,408	* 7/1984	Silverstein et al. 600/146	5,299,578	4/1994	Rotteveel et al. .
4,466,444	8/1984	Baba .	5,305,755	4/1994	Nakao .
4,543,960	10/1985	Harui et al. .	5,305,756	4/1994	Entrekin et al. .
4,546,771	* 10/1985	Eggleton et al. 600/437	5,311,871	5/1994	Yock .
4,550,607	11/1985	Maslak et al. .	5,313,949	5/1994	Yock .
4,561,446	* 12/1985	Hetz 600/452	5,320,104	6/1994	Fearnside et al. .
4,582,067	4/1986	Silverstein et al. .	5,325,860	7/1994	Seward et al. .
4,699,009	10/1987	Maslak et al. .	5,329,496	7/1994	Smith .
4,748,985	6/1988	Nagasaki .	5,329,927	7/1994	Gardineer et al. .
4,756,313	7/1988	Terwilliger .	5,343,865	9/1994	Gardineer et al. .
4,757,821	7/1988	Snyder .	5,345,940	9/1994	Seward et al. .
4,771,788	9/1988	Millar .	5,351,691	10/1994	Brommersma .
4,794,931	1/1989	Yock .	5,360,007	11/1994	Shinomura et al. .
4,802,487	* 2/1989	Martin et al. 600/109	5,373,845	12/1994	Gardineer et al. .
4,841,977	6/1989	Griffith et al. .	5,373,849	12/1994	Maroney et al. .
4,841,979	6/1989	Dow et al. .	5,377,685	1/1995	Kazi et al. .
4,869,256	9/1989	Kanno et al. .	5,385,148	1/1995	Lesh et al. .
4,869,258	9/1989	Hetz .	5,398,689	3/1995	Connor et al. .
4,887,605	12/1989	Angelsen et al. .	5,402,793	4/1995	Gruner et al. .
4,911,170	3/1990	Thomas, III et al. .	5,415,175	5/1995	Hanafy et al. .
4,917,097	4/1990	Proudian et al. .	5,421,336	6/1995	De Bernardis .
4,930,515	6/1990	Terwilliger .	5,425,370	6/1995	Vilkomerson .
4,936,281	6/1990	Stasz .	5,437,283	8/1995	Ranalletta et al. .
4,947,852	8/1990	Nassi et al. .	5,438,997	8/1995	Sieben et al. .
4,951,677	8/1990	Crowley et al. .	5,438,998	8/1995	Hanafy .
4,957,111	9/1990	Millar .	5,460,181	10/1995	Seyed-Bolorforosh .
5,000,185	3/1991	Yock .	5,464,016	11/1995	Nicholas et al. .
5,002,059	3/1991	Crowley et al. .	5,465,724	11/1995	Sliwa, Jr. et al. .
5,010,886	4/1991	Passafaro et al. .	5,467,779	11/1995	Smith et al. .
5,014,710	5/1991	Maslak et al. .	5,469,852	11/1995	Nakamura et al. .
5,022,399	6/1991	Biegeleisen .	5,474,075	12/1995	Goldberg et al. .
5,029,588	7/1991	Yock et al. .	5,479,929	1/1996	Cooper et al. .
5,038,789	8/1991	Frazin .	5,479,930	1/1996	Gruner et al. .
5,070,879	12/1991	Herres .	5,485,846	1/1996	Webler et al. .
5,076,278	12/1991	Vilkomerson et al. .	5,487,388	1/1996	Rello et al. .
5,076,279	12/1991	Arenson et al. .	5,499,630	3/1996	Hiki et al. .
5,081,993	1/1992	Kitney et al. .	5,503,152	4/1996	Oakley et al. .
5,085,221	2/1992	Ingebrigtsen et al. .	5,549,111	8/1996	Wright et al. .
5,105,819	4/1992	Wollschläger et al. .	5,562,095	10/1996	Downey et al. .
5,107,844	4/1992	Kami et al. .	5,569,276	10/1996	Jang et al. .
5,115,814	5/1992	Griffith et al. .	5,630,416	5/1997	Uchikura et al. .
5,125,410	6/1992	Misono et al. .	5,634,464	6/1997	Jang et al. .
5,135,001	8/1992	Sinofsky et al. .	5,697,377	12/1997	Wittkampff .
5,140,558	8/1992	Harrison, Jr. et al. .	5,699,805	12/1997	Seward et al. .
5,148,810	9/1992	Maslak et al. .	5,704,361	1/1998	Seward et al. .
5,152,294	10/1992	Mochizuki et al. .	5,713,363	2/1998	Seward et al. .
5,159,931	11/1992	Pini .	5,749,833	5/1998	Hakki et al. .
5,161,537	11/1992	Hashimoto et al. .	5,876,345	3/1999	Eaton et al. .
5,165,413	11/1992	Maslak et al. .	5,904,651	5/1999	Swanson et al. .
5,174,296	12/1992	Watanabe et al. .			
5,181,514	1/1993	Solomon et al. .			
5,183,048	2/1993	Eberle et al. .			
5,186,175	2/1993	Hirama et al. .			
5,186,177	2/1993	O'Donnell et al. .			
5,193,546	3/1993	Shaknovich .			
5,199,433	4/1993	Metzger et al. .			
5,199,437	4/1993	Langberg .			
5,211,168	5/1993	Mason et al. .			
5,215,002	6/1993	Wray .			
5,222,501	6/1993	Ideker et al. .			
5,226,422	7/1993	McKeighen et al. .			
5,235,986	8/1993	Maslak et al. .			
5,243,988	9/1993	Sieben et al. .			
5,257,629	11/1993	Kitney et al. .			
5,261,408	11/1993	Maslak et al. .			
5,269,307	* 12/1993	Fife et al. 73/626			

FOREIGN PATENT DOCUMENTS

0 642 762 A2	3/1995	(EP) .
WO 90/13260	11/1990	(WO) .
WO 91/04707	4/1991	(WO) .
WO 93/08738	5/1993	(WO) .
WO 94/16625	8/1994	(WO) .
WO 95/13111	5/1995	(WO) .
WO 95/19143	7/1995	(WO) .
WO 96/00522	1/1996	(WO) .
WO 96/03918	2/1996	(WO) .
WO 96/03921	2/1996	(WO) .
WO 96/03922	2/1996	(WO) .
WO 96/04588	2/1996	(WO) .

OTHER PUBLICATIONS

Bom, N. et al., "Intravascular Ultrasound: Newest Branch of the Echo-Tree", *Cardiovascular Imaging*, 4:55-59 (1992).

- Devonald, K.J. et al., "Volume Imaging: Three-Dimensional Appreciation of the Fetal Head and Face", *J. Ultrasound Med.*, 14:919-925 (1995).
- Entrekin, R. et al., "Real-Time 3-D Ultrasound Imaging with a 1-D 'Fan Beam' Transducer Array", *SPIE*, 1733:264-272 (1992).
- F-D-C Reports, Inc., "Cardiovascular Imaging System' Intracardiac Imaging Catheter", *M-D-D-I Reports*, pp. I&W-6 and I&W-7 (Mar. 30, 1992).
- Hung, J. et al., "Usefulness of Intracardiac Echocardiography in Transseptal Puncture During Percutaneous Transvenous Mitral Commissurotomy", *Section of Cardiology, Chang Gung Medical College and Chang Gung Memorial Hospital*, p. 853 (May 10, 1993).
- Kossoff, G. et al., "Real-Time Quasi-Three Dimensional Viewing in Sonography, with Conventional, Gray-Scale Volume Imaging", *Ultrasound Obstet. Gynecol.*, 4:211-216 (1994).
- Kremkau, F.W., "AAPM Tutorial. Multiple-Element Transducers", *RadioGraphics*, pp. 1163-1176 (Sep. 1993).
- Moriuchi, M. et al., "Transvenous Echocardiography: Experimental Feasibility Study" *Jpn J Med Ultrasonics*, 19(3):228-235 (1992).
- Nishimura, R.A. et al., "Intravascular Ultrasound Imaging: In Vitro Validation and Pathologic Correlation", *JACC*, 16(1):145-154 (Jul. 1990).
- Pandian, N.G. et al., "Intracardiac, Intravascular, Two-Dimensional, High-Frequency Ultrasound Imaging of Pulmonary Artery and Its Branches in Humans and Animals", *Circulation*, 81(6):2007-2012 (Jun. 1990).
- Pandian, N.G. et al., "Intracardiac Echocardiography. Experimental Observations on Intracavitary Imaging of Cardiac Structures with 20-MHz Ultrasound Catheters", *Echocardiography*, 8:127-134 (Jan. 1991).
- Pandian, N.G. et al., "Real-Time, Intracardiac, Two-Dimensional Echocardiography. Enhanced Depth of Field with a Low-Frequency (12.5 MHz) Ultrasound Catheter", *Echocardiography*, 8(4):407-422 (1991).
- Rothman, A. et al., "Intraluminal Ultrasound Imaging Through a Balloon Dilatation Catheter in an Animal Model of Coarctation of the Aorta", *Circulation*, 85(6):2291-2295 (Jun. 1992).
- Schwartz, S. et al., "Intracardiac Echocardiographic Guidance and Monitoring During Aortic and Mitral Balloon Valvuloplasty: In Vivo Experimental Studies", Abstract, *JACC*, 15(2):104A (Feb. 1990).
- Schwartz, S.L. et al., "Real-Time Intracardiac Two-Dimensional Echocardiography: An Experimental Study of In Vivo Feasibility, Imaging Planes, and Echocardiographic Anatomy", *Echocardiography*, 7(4):443-455 (Jul. 1990).
- Schwartz, S.L. et al., "Intracardiac Echocardiography During Simulated Aortic and Mitral Balloon Valvuloplasty: In Vivo Experimental Studies", *Am. Heart Journal*, 123(3):665-674 (Mar. 1992).
- Schwartz, S.L. et al., "Intracardiac Echocardiography in Humans Using a Small-Sized (6F), Low Frequency (12.5 MHz) Ultrasound Catheter", *JACC*, 21(1):189-198 (Jan. 1993).
- Schwartz, S.L. et al., "Intracardiac Echocardiographic Imaging of Cardiac Abnormalities, Ischemic Myocardial Dysfunction, and Myocardial Perfusion: Studies With a 10 MHz Ultrasound Catheter", *Journal Am. Soc. of Echocardiography*, 6(4):345-355 (Jul.-Aug. 1993).
- Schwartz, S.L. et al., "Intracardiac Echocardiography Without Fluoroscopy: Potential of a Balloon-Tipped, Flow-Directed Ultrasound Catheter", *Am. Heart Journal*, 129(3):598-603 (Mar. 1995).
- Seward, J.B. et al., "Transvascular and Intracardiac Two-Dimensional Echocardiography", *Echocardiography*, 7(4):457-464 (Jul. 1990).
- Seward, J.B., et al., "Muliplane Transesophageal Echocardiography: Image Orientation, Examination Technique, Anatomic Correlations, and Clinical Applications", *Mayo Clin Proc.*, 68:523-551 (Jun. 1993).
- Seward, J.B. et al., "Ultrasound Cardioscopy: Embarking on a New Journey", *Mayo Clin Proc.*, 71(7):629-635 (Jul. 1996).
- Smith, S.W. et al., "High-Speed Ultrasound Volumetric Imaging System—Part I: Transducer Design and Beam Steering", *IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control*, 38(2):100-108 (Mar. 1991).
- Talbert, D.G., "An 'Add-On' Modification for Linear Array Real Time Ultrasound Scanners to Produce 3 Dimensional Displays", Conference: Ultrasonics International 1977. Brighton, England, pp. 52-67 (Jun. 28-30 1997).
- Tardif, J., et al., "Intracardiac Echocardiography With a Steerable Low-Frequency Linear-Array Probe for Left-Sided Heart Imaging From the Right Side; Experimental Studies" *Journal Am. Soc. of Echocardiography*, 8(2):132-138 (Mar.-Apr. 1995).
- von Ramm, O.T. et al., "High Speed Ultrasound Volumetric Imaging System—Part II: Parallel Processing and Image Display", *IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control*, 38(2):109-115 (Mar. 1991).
- Weintraub, A. et al., "Realtime Intracardiac Two-Dimensional Echocardiography in the Catheterization Laboratory in Humans". Abstract *JACC*, 15(2):16A (Feb. 1990).
- Weintraub, A.R. et al., "Intracardiac Two-Dimensional Echocardiography in Patients with Pericardial Effusion and Cardiac Tamponade", *Journal Am. Soc. of Echocardiography*, 4(6):571-576 (Nov.-Dec. 1991).
- Belohlavek, M. et al., "Toroidal Geometry: Novel Three-Dimensional Intracardiac Imaging with a Phased-Array Transducer", *Journal Am. Soc. of Echocardiography*, 10(5):493-498 (Jun. 1997).
- Lam, J. et al., "Transesophageal Echocardiography with the Use of a Four-Millimeter Probe", *Journal Am. Soc. of Echocardiography*, 10(5):499-504 (Jun. 1997).
- McCann, H.A. et al., "Multidimensional Ultrasonic Imaging for Cardiology", *Proc IEEE*. 76(9):1063-1074 (Sep. 1988).

* cited by examiner

FIG. 1





FIG. 2







FIG. 3







FIG. 4B

FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 8C





FIG. 9A




FIG. 9B

FIG. 10




FIG. 11






FIG. 12








FIG. 14




FIG. 15

FIG. 16





FIG. 17






FIG. 18

1

VOLUMETRIC IMAGE ULTRASOUND TRANSDUCER UNDERFLUID CATHETER SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a Continuation of application Ser. No. 09/087,520, filed May 29, 1998 and now U.S. Pat. No. 6,099,475, which is a Continuation of application Ser. No. 09/003,248, filed Jan. 6, 1998 now U.S. Pat. No. 6,129,672, which is a Continuation of application Ser. No. 08/678,380, filed Jun. 28, 1996 (now issued as U.S. Pat. No. 5,704,361), which is a Continuation-in-Part of application Ser. No. 08/305,138, filed Sep. 13, 1994 (now abandoned), which is a Continuation of application Ser. No. 07/972,626, filed Nov. 6, 1992 (now issued as U.S. Pat. No. 5,345,940), which is a Continuation-in-Part of application Ser. No. 07/790,580, filed Nov. 8, 1991 (now issued as U.S. Pat. No. 5,325,860), which application(s) are incorporated herein by reference.

BACKGROUND OF THE INVENTION

Noninvasive ultrasonic imaging systems are widely used for performing ultrasonic imaging and taking measurements. Such systems typically use scan heads which are placed against a patient's skin. Exemplary uses for such systems include heart and internal organ examinations as well as examinations of developing fetuses. These systems operate by transmitting ultrasonic waves into the body, receiving echoes returned from tissue interfaces upon which the waves impinge, and translating the received echo information into a structural representation of the planar slice of the body through which the ultrasonic waves are directed.

Catheter based invasive ultrasound imaging systems, typically used for intracardiac or transvascular imaging, are a relatively new addition to ultrasound armamentarium. Conventional underfluid transducers for use on catheters are comprised of crystal arrays (e.g. linear phased array) or a single crystal translated over a surface, producing a tomographic field of view in an azimuthal plane of the array. Typical arrays include: 1) linear array (linear sequential array), usually producing a rectangular or rhomboidal picture; 2) cylindrical array or rotating crystal, producing a round pie-shaped tomographic cut of structures; and 3) sector array (linear phased array), producing a triangular shaped image emanating from a small transducer source. All images are tomographic in nature and are focused in the azimuthal and elevation plane. The intent of having these conventional transducer configurations is to produce a thin ultrasound cut of the insonated structures. Such tomographic planes by nature are thin and of high resolution.

The narrow field of view provided by conventional catheter transducer configurations is problematic because structures lying outside of the plane of view can only be visualized by reorienting or manipulating the catheter. Due to the tortuous and confined nature of a typical catheter pathway, catheter manipulation is impractical and often impossible. Consequently, the localization of specific targets is difficult and at times can be disorienting because of an inability to appreciate contiguous anatomic landmarks.

Advances in 3-dimensional imaging capabilities have been made with respect to non-catheter related ultrasonic imaging systems. For example, U.S. Pat. No. 5,305,756, issued to Entekin et al., which is hereby incorporated by reference, discloses general 3-dimensional imaging techniques in a non-catheter based context. What is needed is a catheter based imaging system that utilizes 3-dimensional

2

imaging techniques to provide a wide field of view so as to improve anatomic localization for precision underfluid diagnostics and interventions.

SUMMARY OF THE INVENTION

The present invention relates generally to a volumetric, 3-dimensional image ultrasound transducer underfluid catheter system.

The present invention also relates to an ultrasonic and interventional catheter device operated in an intracardiac or transvascular system, with the aid of a volumetric 3-dimensional imaging capability.

In one particular embodiment, the present invention relates to a catheter apparatus comprising an underfluid catheter body having proximal and distal ends. An ultrasonic transducer array is mounted longitudinally along the catheter body proximate the distal end. The transducer array has a volumetric field of view that projects radially/laterally outward from the catheter. Features in such wide volumetric field of view can be imaged, measured, or intervened by an underfluid therapeutic device with an aid of the real-time image.

It is significant that the transducer array described in the previous paragraph has a 3-dimensional field of view. A first dimension; referred to as an azimuthal direction, is aligned with the length of the transducer array. A second dimension, referred to as a depth direction, is the depth into the body which an ultrasonic signal is transmitted and from which an echo return. A third dimension, referred to as an elevation direction, is perpendicular to both the azimuthal and the depth directions.

If the transducer array comprises a linear phased array having a single row of piezoelectric crystals, a 3-dimensional field of view can be generated by focusing the ultrasound signals in the azimuthal direction (parallel to the longitudinal axis of the catheter) and diverging the ultrasound signals in the elevational direction (transverse to the longitudinal axis of the catheter). The ultrasonic signals can be diverged in the elevational direction through the use of lenses. For example, the signals can be diverged by mounting a silicone rubber concave lens or a plastic convex lens in front of the transducer array.

If the transducer array comprises multiple rows of piezoelectric crystals, a 3-dimensional field of view can be generated by electronically phasing the ultrasound signals in both the azimuthal and elevational directions. Of course, lenses can be used in association with multiple row arrays to further widen the field of view.

It will be appreciated that catheters constructed in accordance with the principles of the present invention can optionally include one or more ports that extend longitudinally through the catheter bodies. The ports are preferably adapted for guiding therapeutic instruments through the catheter and preferably have exit ends adjacent to the field of view of the catheter imaging system. In operation, the ports guide the therapeutic instruments such that the operative ends of a therapeutic instruments are directed toward the 3-dimensional field of view of the imaging system.

It will also be appreciated that catheters constructed in accordance with the principles of the present invention can include one or more guidewire ports which extend longitudinally through the catheters and are adapted for receiving guidewires.

One advantage of the present invention is to provide real-time 3-dimensional images of underfluid features so as

to visualize contiguous anatomy, such as a large volume of tissues without frequently rotating, flexing, or extending the catheter.

Another advantage is that the present invention provides a much better underfluid “eye”—a 3-dimensional “motion picture”—for an operator when he/she intervenes the underfluid features by using an underfluid therapeutic device. These images provide the operator a direct aid without opening a large area of a body.

A further advantage is that the present invention have numerous clinical applications. One is related to underfluid imaging: There is a considerable need to increase the field of view when imaging from within chambers or blood vessels. The physical space of the chambers or blood vessels is small, and the anatomy in question is closed approximated and usually totally surrounds the transducer. A conventional tomographic presentation provides only a limited slice, thus requiring frequent manipulation of transducer in order to visualize contiguous anatomy. The present invention is a solution to visualizing larger volumes of tissue. The underfluid defocusing transducer array does not appreciably affect the electronics and does not require alteration in the display format. The catheter apparatus is immersed in fluid, a homogeneous, low scattering medium, which is an ideal environment for this particular transducer modification.

Another main clinical application is related to underfluid intervention: In diagnostic and therapeutic procedures, there is an increasing need for volumetric 3-dimensional visualization which would improve anatomic localization and recognition of continuous structures and events.

A further advantage of the present invention is that by using such a catheter system, major surgical procedures can be avoided. It dramatically reduces the patient’s physical pain in operation and mental distress after operation due to any large visible scars, etc.

These and various other advantages and features of novelty which characterize the invention are pointed out with particularity in the claims annexed hereto and forming a part hereof. However, for a better understanding of the invention, its advantages and objects obtained by its use, reference should be made to the drawings which form a further part hereof, and to the accompanying descriptive matter, in which there is illustrated and described a preferred embodiment of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

A better understanding of the construction and operational characteristics of a preferred embodiment(s) can be realized from a reading of the following detailed description, especially in light of the accompanying drawings in which like reference numerals in the several views generally refer to corresponding parts.

FIG. 1 is a partial perspective view of an embodiment of a catheter in accordance with the principles of the present invention;

FIG. 2 is an enlarged cross-sectional view taken proximate the distal end of the catheter shown in FIG. 1;

FIG. 3 is a block diagram in part and sectional diagram in part illustrating an embodiment of a system utilizing the catheter shown in FIG. 1;

FIG. 4A is an illustration illustrating an application of a catheter in accordance with the principles of the present invention;

FIG. 4B is a partially enlarged illustration of the catheter shown in FIG. 4A.

FIG. 5A shows a partial perspective and cross-sectional view of a first alternate embodiment of a catheter in accordance with the principles of the present invention;

FIG. 5B shows a view of the distal end of the embodiment of the catheter shown in FIG. 5A;

FIG. 6A shows a partial perspective and cross-sectional view of a second alternate embodiment of a catheter in accordance with the principles of the present invention;

FIG. 6B shows a view of the distal end of the catheter shown in FIG. 6A;

FIG. 7A shows a partial perspective and cross-sectional view of a variation of the second alternate embodiment of the catheter shown in FIG. 6A;

FIG. 7B shows a view of the distal end of the embodiment of the catheter shown in FIG. 7A;

FIG. 8A shows a partial perspective and cross-sectional view of a third alternate embodiment of a catheter in accordance with the principles of the present invention;

FIG. 8B shows a view of the distal end of the catheter shown in FIG. 8A;

FIG. 8C shows a view of the distal end of the catheter shown in FIG. 8A having an alternatively shaped secondary port;

FIG. 9A shows partial perspective and cross-sectional view of a fourth alternate embodiment of a catheter in accordance with the principles of the present invention; and

FIG. 9B shows a view of the distal end of the catheter shown in FIG. 9A.

FIG. 10 is a partial schematic view of an embodiment of an underfluid catheter system in accordance with the principles of the present invention.

FIG. 11 is an enlarged view illustrating the catheter system operated underfluid with an aid of a volumetric field of view.

FIG. 12 is an enlarged perspective view illustrating the catheter system providing a volumetric field of view.

FIG. 13 is an enlarged perspective view of an ultrasonic transducer array having a single row of crystals covered by a lens which provides a volumetric field of view.

FIG. 14 is an enlarged perspective view of an alternative ultrasonic transducer array having multiple rows of crystals which provides a volumetric field of view.

FIG. 15 is an enlarged perspective view of a second alternative ultrasonic transducer array having equal number of rows and columns of crystals which provides a volumetric field of view.

FIG. 16 is an enlarged schematic cross-sectional view of a concave silicone rubber lens being placed on the ultrasonic transducer array, providing an outwardly defocused ultrasound beam.

FIG. 17 is an enlarged schematic cross-sectional view of a convex plastic lens being placed on the ultrasonic transducer array, providing an outwardly defocused ultrasound beam.

FIG. 18 is an enlarged schematic cross-sectional view of a convex silicone rubber lens being placed on the ultrasonic transducer array, providing an inwardly focused ultrasound beam.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to FIG. 1–3, there is, generally illustrated by reference numeral 20, a catheter in accordance with the

principles of the present invention. As shown, catheter 20 includes an elongated flexible or rigid tubular catheter body 22 having a proximal end 24 and a distal end 26. Catheter 20 includes proximate its longitudinal distal end 26 a phased array ultrasonic transducer 30 which is used to transmit ultrasound and receive resultant echoes so as to provide a field of view within which Doppler flow rates can be measured and features imaged. It is appreciated that the other types of ultrasonic transducers can be used in the present invention, such as any mechanical types, or any dynamic array types, or any offset stereoscopic imaging types, or any multidimensional imaging types incorporated into a virtual reality environment for underblood operation, etc. An electrical conductor is disposed in the catheter body 22 for electrically connecting transducer 30 to control circuitry 34 external of catheter body 22. An access port 40 is disposed in catheter body 22 and extends from proximate the proximal end 24 of catheter body 22 to proximate the distal end 26 of catheter body 22. Access port 40 is configured to receive a therapeutic device, such as a catheter, medication, sensors, etc., so as to enable such items to be delivered via access port 40 to distal end 26 of catheter body 22 for operation within the ultrasonic transducer field of view. Such items might be used for intervention; e.g., ablation catheter, surgical device, etc., monitoring blood pressure, sampling blood, etc. A guide wire access port 42 is also disposed within catheter body 22 and extends from proximate proximal end 24 of the catheter body 22 to proximate distal end 26 of catheter body 22 for receiving a guide wire 44.

In the preferred embodiment of the present invention, the ultrasonic transducer preferably has a frequency of 5 to 30 megahertz (MHz) and more preferably a frequency of 7 to 10 MHz. Intracardiac imaging in an adult will require image penetration of up to 2 to 10 centimeters (cm). In the preferred embodiment, catheter body 22 preferably has a diameter of 4 to 24 French (one French divided by Pi equals one millimeter (mm)) and, more preferably, a diameter of 6 to 12 French. In the preferred embodiment, access port 40 has a diameter of 7 to 8 French and guide wire port 42 has a diameter of 0.025 to 0.038 inches.

As generally illustrated in FIG. 3, catheter 20 of the present invention can be utilized in a medical system including the appropriate control circuitry 34 for controlling operation of the ultrasonic transducer. As illustrated in FIG. 3, control circuitry 34 is electrically interconnected to transceiver circuitry 35 (T/R) for receiving and transmitting signals via a cable 36 to ultrasonic transducer 30. In turn, transceiver circuitry 35 is electrically interconnected to Doppler circuitry 37 and an appropriate display device 38 for displaying hemodynamics or blood flow. In addition, transceiver circuitry 35 is electrically interconnected to suitable imaging circuitry 39 which is interconnected to a display 41 for displaying images.

During operation, control circuitry 34 might be designed to cause ultrasonic transducer 30 to vibrate so as to cause an appropriate ultrasound wave to project from proximate the distal end 26 of catheter body 22. The ultrasound wave, represented by lines 50 in FIG. 2, will propagate through the blood surrounding distal end 26 and a portion of the body structure. A portion of the ultrasound wave so transmitted will be reflected back from both the moving red blood cells and the like and the body structures to impinge upon transducer 30. An electrical signal is thereby generated and transmitted by the cable 36 to the input of transceiver 35. A signal might then be transmitted to Doppler circuitry 37 which will include conventional amplifying and filtering circuitry commonly used in Doppler flow metering equip-

ment. Doppler circuitry 37 will analyze the Doppler shift between the transmitted frequency and the receive frequency to thereby derive an output proportional to flow rate. This output may then be conveniently displayed at display 38 which might be a conventional display terminal. Accordingly, the user will be able to obtain a readout of blood flow rates or hemodynamic information.

In order to obtain imaging information, control circuitry 34 will likewise trigger ultrasonic transducer 30 via transceiver 35 to vibrate and produce an ultrasound wave. Once again, a portion of the wave or energy will be reflected back to ultrasonic transducer 30 by the body features. A corresponding signal will then be sent by cable 36 to transceiver circuitry 35. A corresponding signal is then sent to the imaging circuitry 39 which will analyze the incoming signal to provide, at display 41, which also might be a conventional display apparatus, an image of the body features.

This imaging can occur while a therapeutic or surgical device is being used at distal end 26 of catheter 20 within the field of view provided by ultrasonic transducer 30. Accordingly, the user will be able to monitor his/her actions and the result thereof.

As illustrated in FIG. 3, catheter body 22 might include proximate its proximal end 24 a suitable mounting structure 52 to the access port 40. A therapeutic or surgical device structure 53 might be suitably attached to structure 52 by suitable means, e.g., threaded, etc. As illustrated, an elongated cable-like member 54 will extend along access port 40 and slightly beyond distal end 26 of catheter body 22 wherein an operative portion 56 of the surgical tool might be interconnected.

Additional detail of distal end 26 of catheter body 22 is illustrated in FIGS. 2, 4A, and 4B. As illustrated in FIGS. 2, 4A, and 4B, ultrasonic transducer 30 might include a piezoelectric polymer, such as Polyvinylidenedifluoride (PVDF) 60, which is bonded by an epoxy layer 62 to a depression 64 approximate distal end 26. Although some detail is provided with respect to an embodiment of an ultrasonic transducer which might be used, it will be appreciated that various types of transducers having various configurations and orientations might be utilized in keeping with the present invention.

As illustrated in FIGS. 4A and 4B, the operational portion 56 of the therapeutic device is illustrated as generally being capable of operation in the field of view of ultrasonic transducer 30. Accordingly, it is possible for the user to monitor operation of the therapeutic device by use of the ultrasonic transducer. Moreover, it is possible for the user to monitor the features of the body within the field of view before, during and after interventional activity. It is appreciated that the other types of ultrasonic transducers can be used in the present invention, such as any mechanical types, or any dynamic array types, or any offset stereoscopic imaging types, or any multidimensional imaging types incorporated into a virtual reality environment for underblood operation, etc., so that all forms of field of views, such as 1) tomographic (slices), 2) stereoscopic, 3) three-dimensional, 4) virtual reality (multidimensional) can be provided in the present invention. In addition, it is appreciated that the orientations of the scan array on the catheter can be include side-view, end-view, multiview (two or more views that are moveable or imminently directional transducer referred to in the literature as "omnidirectional"), etc.

FIG. 5A shows a partial cross-sectional view of a first alternative embodiment 70 of the catheter apparatus. The catheter apparatus has an elongated flexible or rigid body 72

having a longitudinal axis and a proximal end **74** and a distal end **76**. Disposed proximate a second side of body **72** is a port **78** extending through body **72** from proximate proximal end **74** to proximate distal end **76** of body **72**. Port **78** is for receiving and delivering to distal end **76** of body **72** a working tool **84**. Working tool **84** shown in the Figures is illustrative only, others types of tools now known or later developed may also be delivered to distal end **76** through port **78**. Proximate a first side of body **72** is a guide wire port **80** extending through body **72** from proximate proximal end **74** to proximate distal end **76**. Shown in guide port **80** is a guide wire **86**.

Distal end **76** is disposed at an oblique angle to the longitudinal axis of body **72**, the first side of body **72** extending further in the direction of the distal end than the second side of body **72**. An ultrasonic transducer **82**, having a first side and a second side, is disposed at an oblique angle to the longitudinal axis of body **72** approximately corresponding to the oblique angle of distal end **76** of body **72**. The first side of ultrasonic transducer **82** is disposed proximate the first side of body **72** and the second side of transducer **82** is disposed proximate the second side of body **72**. Extending from transducer **82** to proximate proximal end **74** of body **72** is an electrical conductor **83** connecting transducer **82** to control circuitry external of catheter **70**, as described with respect to catheter **20** above. Having transducer **82** disposed on an oblique angle toward port **78** allows for easy visualization of tools, such as tool **84**, extending beyond distal end **76** of body **72**.

FIG. **5B** shows a view of distal end **76** of body **72**, showing guide wire port means **80**, transducer **82**, and port means **78**.

FIG. **6A** shows a partial cross-sectional view of a second alternative embodiment of the catheter in accordance with the present invention, generally referred to as **88**. Like first alternative embodiment **70**, catheter **88** has an elongated flexible or rigid body **90** having a proximal end **92** and a distal end **94**. Catheter **88** also has a port **96** extending through body **90** from proximate proximal end **92** to proximate distal end **94**. Port **96** has a distal end **97** proximal distal end **94** of body **90**. Distal end **97** of port **96** exits body **90** at an acute angle to a first side of body **90** toward distal end **94**. Port **96** is for receiving and delivering to distal end **94** a working tool, such as working tool **84**. Catheter **88** also has a guide wire port **98** extending through body **90** from proximate proximal end **92** to proximate distal end **94**. Guide wire port **98** is for receiving a guide wire **86**.

Also shown in FIG. **6A** is a transducer **100** disposed to a first side of body **90** between distal end **94** and distal end **97** of port **96**. Extending from transducer **100** to proximate proximal end **92** of body **90** is an electrical conductor **102** disposed in the catheter body **90** for electrically connecting transducer **100** to control circuitry external of the catheter. With transducer **100** disposed to the first side of body **90** and distal end **97** of port **96** exiting body **90** at an acute angle relative to the first side of body **90** toward distal end **94**, working tools extending from distal end **97** of port **96** will be within the field of view of transducer **100**.

FIG. **6B** shows a view of distal end **94** of catheter **88**, as shown in FIG. **6A**.

FIG. **7A** shows second alternative embodiment **104**, as shown in FIG. **6A**, except instead of having a guide wire port **98**, this variation of the second alternative embodiment **104** has a deflection wire guidance system **106** for manipulating distal end **94**. FIG. **7B** shows a view of distal end **94** of the catheter shown in FIG. **7A**.

FIG. **8A** shows a third alternative embodiment **110** of the catheter in accordance with the present invention. Third alternative embodiment **110** has a body **112** having a distal end **114** and proximal end. Disposed proximate a first side of body **112** is a primary port **118** extending through body **112** from proximate proximal end **116** to proximate distal end **114**. Primary port **118** has a distal end **119** proximate distal end **114** of body **112**. Oppositely disposed from primary port **118**, proximate a second side of body **112** is a secondary port **120** extending through body **112** from proximate proximal end **116** to proximate distal end **114**. Secondary port **120** has a distal end **121** proximate distal end **114** of body **112**.

Mounted proximate distal end **114** of body **112** is a transducer **122**. Extending from transducer **122** through body **112** to proximate proximal end is an electrical conductor for electrically connecting the transducer **122** to control circuitry external of the catheter. Transducer **122** is disposed between distal ends of primary and secondary ports **119** and **121**, respectively. With working ports **118** and **120** oppositely disposed on either side of transducer **122**, it is possible to conduct two simultaneous applications, such as holding an object with a first tool disposed through one port and operating on the object held by the first tool with a second tool disposed through the other port. A typical working tool **123** and working tool **84** are shown disposed within ports **118** and **120**.

Although the third alternative embodiment of the catheter **110** of the present invention does not include a guide wire port means, a guide wire could be used in primary port **118** or secondary port **120** to initially position catheter **110**. Then the guide wire could be retracted from port **118** or **120** and a working tool introduced. FIG. **8B** shows a view of distal end **114** of catheter **110**.

FIG. **8C** shows a view of a distal end **124** of a catheter **126** substantially like catheter **110** shown in FIG. **8A** and FIG. **8B**, except that catheter **126** has a primary port **128** having an arc-like shaped cross-section, rather than a circular shaped cross-section. Although a circular cross-section has been shown in the Figures for the various ports described herein, the size and shape of the ports can be varied without departing from the principals of the present invention.

FIG. **9A** shows a fourth alternative embodiment of a catheter **130** of the present invention. Catheter **130** is similar to catheter **70** shown in FIG. **5A** and FIG. **5B** except that a plurality of ports **132** are disposed proximate a second side of flexible body **131**, rather than one port **78**, as shown in FIG. **5A**. With a plurality of ports, it is possible, for example, to use a therapeutic tool through one port while simultaneously suctioning and removing debris through another port; or a therapeutic tool can be used through one port while simultaneously electrophysiologically monitoring, suctioning and/or biopsying through a second port, third or fourth port.

The use of the catheter of the present invention is described with respect to the preferred embodiment **20**. It is understood that the use of alternative embodiments **70**, **88**, **110**, **126** and **130** is analogous. In use, the user would insert flexible catheter body **22** into the body via the appropriate vascular access to the desired location in the body, such as selected venous locations, heart chamber, etc. In one approach, a guide wire might be first inserted into place and then the catheter body fed along the guide wire. The user might then insert a surgical device into the body through access port **40** and feed the surgical device to proximate distal end **26** of catheter body **22**. Prior to, during and after

operation of the surgical device, the user might obtain both hemodynamic measurements and images from the ultrasonic transducer field of view. By operation of the surgical device within the field of view of transducer, the user can monitor operation of the surgical device at all times.

I. Detailed Features of the Disclosed Catheters:

- A. Frequency agility Ultrasound frequency: Frequency agility refers to the ability of a transducer to send and receive at various frequencies, most commonly 3, 5, and 7 MHz. It is also appreciated that a single frequency from a single transducer device can be sent and received. In general, higher frequencies are used to image fine detail of more proximal or closely related objects while lower frequency transducers scan more remote objects with less detail. The proposed device optimally uses a 5 to 20 mHz transducer with the most optimally applied frequency of 7 to 10 mHz. The lower frequency used in the UIHC reflects the need to image larger objects such as the cardiac septa, valves, and extravascular anatomy.
- B. Catheter size: Catheter diameters will generally be larger than intravascular catheters and will range 4 to 24 French with the optimal catheter diameter 6 to 12 French (French size =French divided by Pi plus millimeter diameter).
- C. Intervention: One primary function of this catheter system is to guide the logical and safe use of various a) ablation, b) laser, c) cutting, occluding, e) etc., catheter-based interventional tools. The invention has the access port through which other technologies (devices) can be passed. Once the interventional tool exits the catheter tip, it can be directed repeatedly and selectively to specific site for controlled intervention.
- D. Imaging: The invention is also an imaging system capable of visualizing intracardiac, intravascular, and extravascular structures. Because the transducer frequencies utilized are usually lower than intravascular systems, the catheter **20** can see multiple cardiac cavities and visualize structures outside the vascular system. The imaging capability is basically two-fold: 1) diagnostic and 2) application.
 1. Diagnostic imaging: The catheter **20** can effectively perform diagnostic intracardiac and transvascular imaging. This application will more than likely be performed just prior to an interventional application. The intervention then will follow using the same catheter system and its unique delivery capability. Some examples of diagnostic imaging include 1) accurate visualization and measurement of an intracardiac defect, 2) characterization of valve orifice, 3) localization of a tumor and its connections, 4) etc. Extravascular diagnoses would include 1) visualize pancreatic mass/pathology, 2) retroperitoneal pathology, 3) intracranial imaging, 4) recognition of perivascular pathology, and 5) imaging of other fluid containing space such as urinary bladder, bile system, fluid filled orifice or cavity (e.g. filled saline), etc.
 2. Application imaging refers to the use of the catheter and its imaging capability to deliver and then apply another technology such as 1) occlusion device for closure of a septal defect, 2) ablation catheters for treatment of bypass tracts, 3) creation of a defect such as that with the blade septostomy catheter or laser-based catheter system, and 4) directing of valvuloplasty (such as prostrate surgery, placement of stents, gallstone removal etc.), etc. By direct imaging

of an application, such as ablation, the procedure will be able to be performed more safely and repeatedly, and the result can be better assessed.

- E. Hemodynamics: The catheter **20** is a truly combined ultrasound Doppler and conventional hemodynamic catheter. There are Doppler catheters, and there are catheters capable of imaging and measuring hemodynamic pressure. However, the catheter **20** is capable of Doppler hemodynamics (continuous and pulsed wave Doppler) as well as high-fidelity hemodynamic pressure recording while simultaneously imaging the heart and blood vessel. The catheter **20** provides a combination of imaging, hemodynamic, and interventional delivery catheter.

II. Analogy with Other Existing Therapeutic Technologies:

Like interventional peritoneoscopy, intracardiac ultrasound is capable of 1) imaging, 2) delivering a therapeutic device, and 3) obtaining simultaneous hemodynamics which can be used to develop less invasive cardiac surgical techniques. This simultaneous use of one or more devices within the heart or vascular tree opens up the potential to develop less invasive surgical therapies. Examples would include 1) removal of a cardiac tumor by visually grasping the tumor with one device and visually cutting its attachment with a second device, thus allowing less invasive extraction of intracardiac mass lesions, 2) visually placing an electrophysiologic catheter on a bypass tract and then with direct ultrasound visualization ablate the underlying tract with the second device, 3) visually performing laser surgery such as creating an intra-atrial defect, vaporization of obstructing thrombus such as is seen in pseudointimal occlusion of conduits, 4) visually removing a foreign body from the heart or vascular tree, and 5) directing intravascular surgery from within a blood vessel or monitoring concomitant hemodynamic changes.

III. Selected Applications Include the Following:

- A. Radio-frequency ablation: Presently a bypass tract is localized by an electrophysiologic study which systematically maps the atrioventricular valve annulus. Positioning of the ablation catheter is determined by x-ray fluoroscopy and certain electrical measurements which relate the distance of the ablation catheter from a reference catheter. The catheter **20** will allow an operator to map the atrioventricular valve under direct ultrasound visualization. Thus, increased accuracy of catheter placement, precision of the applied therapy, and immediate assessment of outcome would result.

The above ablation technique would be particularly applicable for right-sided bypass tracts (in and around the tricuspid valve annulus). This would be accomplished by placement of the catheter **20** through the superior vena cava above the tricuspid annulus.

For left-sided bypass tracts, the catheter **20** could be placed across the atrial septum under direct ultrasound visualization. The mitral annulus could thus be mapped directly and the localized bypass tract precisely ablated under visual ultrasonic and hemodynamic direction. Complications such as valve perforation, multiple imprecise applications of ablation energy, and inadvertent ablation of normal conduction tissue would be substantially reduced.

Ablation of bypass tracts would be an ideal utilization of the proposed ultrasonic interventional catheter system.

- B. Cardiac biopsy: In the era of safe cardiac biopsy, there is a need for precision biopsy. Ultrasound direction of the biopsy device to an intracardiac tumor, avoidance of scar, and selective biopsy of suspect tissue are feasible with the catheter **20** device. One of the more

frequently life-threatening complications in the cardiac catheterization laboratory is catheter perforation of the heart. Such complications most commonly accompany cardiac biopsy, electrophysiologic catheter manipulation, and valvuloplasty. Use of an intracardiac ultrasound imaging, hemodynamics, and delivery catheter should substantially increase or improve safety of these procedures.

C. Transvascular diagnoses: The catheter **20** will allow visualization of perivascular and extravascular pathology. Transvascular or transorgan imaging and localization of pathology out of the immediate vascular tree will result in a substantial step forward in the diagnosis and possible treatment of difficult to reach pathology. The catheter **20** cannot only diagnose but guide a biopsy needle and therapeutic device to an extravascular lesion in question. The retroperitoneum, mediastinum, and basal cerebrovascular pathology are logical areas of interest. Accurate characterization of various pathologies will be more feasible. Every organ has its own vascular system, and the proposed ultrasound transvascular system is an ideal tool to assess difficult to reach areas of the body. The vascular system is a conduit to each organ, and the catheter **20** can be delivered to each organ. Characterization of the underlying parenchyma and possible transvascular biopsy or treatment will ultimately be developed.

D. Ultrasound manipulation of therapeutic devices within the heart and blood vessels: The catheter **20** opens the potential not only to visualize but to directly intervene with the same catheter system. There are numerous intraoperative catheter-based systems which to date use conventional x-ray to accomplish their goal of placement and application of a specified therapy. There is a need for a device which can more precisely guide such catheter-based systems. It is too expensive and technically impractical to incorporate ultrasound into every catheter based technology. The catheter **20** has all the prerequisites of an ideal imaging and interventional instrument and has the ability to 1) image, 2) obtain hemodynamics by multiple means (pressure dynamics and Doppler), 3) function as a diagnostic as well as therapeutic device, and 4) accommodate other unique technologies which would enhance the application of both systems.

E. General applications: It is anticipated that intravascular, transvascular, and intracardiac devices could be delivered through the port means described above within or about the heart and blood vessels of the body. The catheters described above, however, could also be used in any ectogenic tissue, such as liver, parenchyma, bile ducts, ureters, urinary bladder, and intracranial—i.e., any place in the body which is echogenic which would allow passage of a catheter for either diagnostic or therapeutic applications using ultrasound visualization.

F. Expanding applications of technologies: The catheter **20** is a new and exciting innovation to invasive medicine. There are multiple other and yet-to-be determined applications. However, the new concept described opens the potential development of less expensive, more precise, and safe intravascular and transvascular diagnostic and surgical devices.

IV. Summary:

The catheter **20** is very much different from any conventional ultrasound catheter-based system. The catheter **20** incorporates image and hemodynamic capability as well as

the ability to deliver other diverse technologies to specified sites within the cardiovascular system (heart and blood vessels). The catheter **20** is seen as an ideal diagnostic and therapeutic tool for future development. The proposed applications foster greater preciseness, adaptability, and safety. Ultrasound permits visualization from within blood-filled spaces as well as through blood-filled spaces into other water-or fluid-filled tissue. The catheter **20** will evolve into the ultimate interventional system.

FIG. **4A** is an illustration showing one potential use of the ultrasound imaging and hemodynamic catheter (UIHC). In this particular example, the UIHC is advanced from the superior vena cava to the tricuspid valve annulus. Simultaneously visualized in the annulus, electrophysiologic and ultimately an ablation procedure are performed. The ability to directly visualize and direct therapeutic catheter devices highlights only one of the many applications of the UIHC.

Another embodiment of the catheter system, generally in accordance with the principles of the present invention is shown in FIG. **10**, which is designated as reference numeral **200**. The catheter system **200** has a catheter body **202** and an ultrasonic transducer array **204** mounted on proximate the distal end of the catheter body **202**. It is appreciated that other parts of the catheter system can be similar to those in the catheter systems **20**, **70**, **88**, **104**, **110**, and **130** as shown in FIGS. **1**, **5A**, **6A**, **7A**, **8A**, and **9A**, respectively. For the purpose of illustration and explanation, FIG. **10** shows a partial schematic view of the catheter system **200**.

In FIG. **11**, the catheter body **202** of the catheter system **200** is inserted into an underfluid cavity of a body **206**. In FIG. **12**, a therapeutic device **208** projects from the catheter system **200** proximate the distal end of the catheter system **200** and manipulates features in the cavity of the body **208**. This manipulation is under observation of a 3-dimensional image shown on a display, which can be similarly connected to the ultrasound, transducer array as shown in FIG. **3**, outside the body **208** proximate the proximal end of the catheter system **200**.

Likewise, the underfluid catheter body **202** has tool port **210** disposed in the catheter body **202** extending from proximate the proximal end to proximate the distal end of the catheter body **202** for receiving the therapeutic device **208**, such as a catheter, medication, sensor, surgical device, etc., so as to enable such items to be delivered via the tool port to proximate the distal end of the catheter body **202**. It will be appreciated that the tool port is optional. It will also be appreciated that additional tool ports can be disposed in the catheter body **202**. The therapeutic device **208** is projected into an underfluid environment, as shown in FIGS. **11–12**, and operated therein with the aid of a volumetric 3-dimensional image of the underfluid environment and the therapeutic device **208**.

Further, the catheter system **200** can also optionally include a guidewire port **212** disposed in the catheter body **202** extending from proximate the proximal end to proximate the distal end of the catheter body **202** for receiving a guide wire **214**. The guide wire **214** guides the catheter body **202** when inserting into a body, such as the body **206**.

Further, the catheter system **200** includes a control circuit which can be similar to the control circuitry **34** shown in FIG. **3**. The control circuitry **34** is used to control the operation of the ultrasonic transducer array **204**. The control circuitry **34** is electrically interconnected to a transceiver circuitry **35** (T/R) for receiving and transmitting signals via a cable **36** to ultrasonic transducer array **204**. In turn, the transceiver circuitry **35** is electrically interconnected to a measuring circuitry, such as the Doppler circuitry **37**, which

is interconnected to a first display **38** for displaying hemodynamics, blood flow, etc. In addition, the transceiver circuitry **35** is electrically interconnected to an imaging circuitry **39** which is interconnected to a second display **41** for displaying a 3-dimensional image of the underfluid environment.

As shown in FIG. **10**, the catheter body **202** can also house some encased electronics **216**.

In the preferred embodiment of the present invention, the ultrasonic transducer array **204** is mounted on a side of the catheter body **202**. The array **204** can also be mounted on the tip of the catheter body **202**. The catheter body **202** is a flexible catheter capable of manual or electronic interactive flexible tip. The guidewire port **212** has a diameter of 0.035 inches. It is appreciated that the range of the diameter of the guidewire port **212** can be varied from 0.025 to 0.038 inches. The tool port **210** for transporting the therapeutic device **208** is a 7 French port. It is appreciated that the range of the tool port **210** can be varied from 3 French to 20 French.

As shown in FIG. **13**, the ultrasonic transducer array **204** is comprised of a single row of individual crystals **218**. Each crystal **218** is arranged side by side. A field of view generated by the ultrasonic transducer array **204** has a primary tomographic plane **220** in azimuthal dimension along an AZ axis. The row of the array **204** is parallel to the AZ axis. An elevation axis (EL) is perpendicular to the AZ axis. A primary beam from the ultrasonic transducer array **204** lies in the primary tomographic plane **220**. The primary beam has usually a sector configuration (generally a fan or triangle shape) or a linear configuration (generally rectangular shape).

The volumetric field of view can be produced by defocusing the primary tomographic plane **220** such that a plurality of elevation planes **222** spread laterally outward from the primary tomographic plane **220**. The primary tomographic plane **220** and the elevation planes **222** together form a volumetric field of view. To defocus the primary tomographic plane **220** as shown in FIG. **13**, a lens **224** is placed on the top of the ultrasonic transducer array **204**. The ultrasound beams which are usually collimated are defocused along the elevation direction (EL) after the beams go through the lens **224** (or other lenses **226,228** as shown in FIGS. **16** and **17**).

The lenses **224**, **226**, or **228** are preferred to be made from materials such as a plastic material or silicone rubber. It is appreciated that other types materials can be used to make the lens.

In FIG. **16**, the lens **226** is a concave lens, preferably made of silicone rubber, which transmits ultrasound waves slower than the surrounding environment, such as body tissues. The ultrasound waves pass through the lens **226** and then impact on the body tissues. The speed of the ultrasound waves is slower in the lens but faster in tissue (e.g. 1,540 m/sec). Accordingly, the transmitted ultrasound waves, after passing through more slowly transmitted lens **226** and striking faster transmitted body tissues, will be directed outward. As a result, the collimated ultrasound beams are defocused in the elevation dimension.

The defocusing can also be achieved by placing a convex lens **228** on the ultrasonic transducer array as shown in FIG. **17**. The convex lens **228**, preferably made of plastic, transmits ultrasound waves faster than the surrounding environment, such as body tissues. The ultrasound waves pass through the convex lens **228** and then impact on the body tissues. The ultrasound beams are pulled outward due to the faster velocity in the convex lens **228**. As a result, the ultrasound beams are defocused in the elevation dimension.

FIG. **18**, on the other hand, demonstrates a way of using a lens **230** to, in fact, focus the beams from the transducer array. The collimated ultrasound beams are generated from the ultrasonic transducer array. The convex lens **230** transmits ultrasound waves slower than the surrounding environment, such as body tissues, do. Accordingly, the ultrasound beams are pulled inward due to the faster velocity in body tissues. As a result, the ultrasound beams are focused toward the primary tomographic plane **220**.

FIG. **14** shows an alternative embodiment of ultrasonic transducer array **204'** which is comprised of multiple rows of individual piezoelectric crystals **218**. The rows of the array **204'** are parallel to the AZ axis. The columns of the array **204'** are parallel to the elevation dimension along the EL axis, which is perpendicular to AZ axis. This type of array is also called volumetric one and one-half (1 and ½) dimensional array. The "elevation" image and the ultimate 3-dimensional image are the result of phasing the crystals in the elevation direction as well as in the azimuthal direction.

FIG. **15** shows a second alternative embodiment of ultrasonic transducer array **204''** which is comprised of equal number of crystals **218** in all dimensions. Similar to the one and one-half (1 and ½) dimensional array **204'**, the rows of the array **204''** are parallel to the AZ axis, and the columns of the array **204''** are parallel to the EL axis. This type of array is also called a two (2) dimensional array. The "elevation" image and the ultimate 3-dimensional image are the result of phasing the crystals in the EL direction as well as the AZ direction.

Accordingly, the volumetric field of view as shown in FIGS. **14–15** provides 3-dimensional images of structures under observation. Further, the volumetric field of view not only shows, for example, a primary tomographic cut, but also volumes of features, such as tissue.

In the embodiments of FIGS. **14** and **15**, it will be appreciated that no lens is required to generate a volumetric image. Consequently, the ultrasonic beams are focused in both the azimuthal and elevational directions. The volumetric image is generated because the arrays of FIGS. **14** and **15** are 2 dimensional. As a result, a volumetric image can be generated by electronically phasing and steering the ultrasonic impulses in both the azimuthal and the elevational directions.

In the preferred embodiment, the ultrasound transducer is a 7–10 MHz sector array transducer. It is appreciated that the range of the sector array transducer can be varied from 3.7 MHz to 30 MHz.

It is also appreciated that the lenses **224**, **226**, **228**, **230** can be made of different materials which will have variable effects on the transmitted ultrasound beams. By using such defocusing lens, a 3-dimensional image can be seen on a 2-dimensional display outside the body **206** in a real-time operation. Elevation defocusing in using a lens does not interfere with the inherent frame rate or adversely affect conventional echo data.

The lens can also be fabricated to reduce the strength of the dominant tomographic plane (AZ plane). One means of accomplishing this is by changing the attenuation characteristics of the lens so as to reduce the tomographic effect and enhance the volumetric effect of the insonated and displayed object.

The lens is optional, for example, as shown in FIGS. **14** and **15** whereby the beams are phased in both the azimuthal and elevational planes.

The present invention has numerous clinical applications. One of which is the underfluid imaging when imaging from within chambers, cavities or blood vessels. Since the physi-

cal space is small, and the anatomy in question is closely approximated and usually totally surrounds the transducer, a 3-dimensional imaging is a solution to visualizing larger volumes of underfluid tissue. In this imaging application, the defocusing lens or electronically controlled phasing in both the azimuthal and elevational directions (i.e., using multi-dimensional arrays such as 1-½dimensional or 2-dimensional arrays) produces volumetric images. Working port(s) and guidewire(s) are optional. Further, catheter lengths and transducer frequencies are variable.

Another application, when the working port is optionally used in the catheter, is to intervene or manipulate an underfluid structure, such as cutting an underfluid tissue, etc., by a therapeutic device, such as the therapeutic devices **50, 84, 123, 208** shown in FIGS. **4E, 5A, 8A, and 12**, respectively. Under such direct volumetric visual guidance, diagnostic and therapeutic procedures can be performed with better spatial orientation.

Another application, when the guidewire is optionally used in the catheter, is to measure some underfluid features, such as blood flow, etc. The measurement can also be performed under direct volumetric visual guidance in the present invention.

Other generic applications include Doppler blood flow determination, color flow imaging, etc.

Thus, the preferred embodiment of the present invention has been described in detail. It is to be understood, however, that even though numerous characteristics and advantages of the present invention have been set forth in the foregoing description, together with details of the structure and function of the invention, the disclosure is illustrative only, and changes may be made in detail, especially in matters of shape, size and arrangement of parts within the principles of the invention to the full extent indicated by the broad general meaning of the terms in which the appended claims are expressed.

What is claimed is:

1. A method of viewing a cardiovascular underfluid structure, comprising:
 - disposing a catheter in the cardiovascular underfluid structure, the catheter comprising:
 - an elongated body having proximal and distal ends;
 - a linear phased-array ultrasonic transducer mounted proximate the distal end of the elongated body to transmit ultrasound and receive resultant echoes so as to provide a field of view within which features can be imaged; and
 - an electrical conductor disposed in the elongated body for electrically connecting the linear phased-array ultrasonic transducer to control circuitry external of the catheter;
 - transmitting ultrasound from the linear phased-array ultrasonic transducer;
 - receiving resultant echoes of the ultrasound using the linear phased-array ultrasonic transducer; and
 - analyzing the echoes to image features.
2. A method of viewing a cardiovascular underfluid structure, comprising:
 - disposing a catheter in the cardiovascular underfluid structure, the catheter comprising:
 - an elongated body having proximal and distal ends; and
 - a linear phased-array ultrasonic transducer mounted proximate the distal end of the elongated body to transmit ultrasound and receive resultant echoes so as to provide a field of view within which features can be imaged;
 - transmitting ultrasound from the linear phased-array ultrasonic transducer;
 - receiving resultant echoes of the ultrasound using the linear phased-array ultrasonic transducer; and
 - analyzing the echoes to image features.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,306,096 B1
DATED : October 23, 2001
INVENTOR(S) : Seward et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title page,

Item [56], **References Cited**, under U.S. PATENT DOCUMENTS, "5,215,002" should read -- 5,215,092 --

Signed and Sealed this

Twenty-seventh Day of August, 2002

Attest:

A handwritten signature in black ink, appearing to read "James E. Rogan", written over a horizontal line.

Attesting Officer

JAMES E. ROGAN
Director of the United States Patent and Trademark Office

专利名称(译)	体积图像超声换能器流体导管系统		
公开(公告)号	US6306096	公开(公告)日	2001-10-23
申请号	US09/586193	申请日	2000-06-02
[标]申请(专利权)人(译)	梅约医学教育与研究基金会		
申请(专利权)人(译)	梅奥基金会的医学教育和研究		
当前申请(专利权)人(译)	梅奥基金会的医学教育和研究		
[标]发明人	SEWARD JAMES BERNARD TAJIK ABDUL JAMIL		
发明人	SEWARD, JAMES BERNARD TAJIK, ABDUL JAMIL		
IPC分类号	A61B8/12 A61B8/00 A61B8/06 A61B8/14 A61B17/00 A61B17/22 A61B17/32 A61B19/00 A61M25/00		
CPC分类号	A61B8/06 A61B8/12 A61B8/4488 A61B17/320758 A61B2017/00243 A61B2019/5276 A61B2019/528 A61B8/445 A61B2090/378 A61B2090/3784		
代理机构(译)	商户德律P.C.		
外部链接	Espacenet USPTO		

摘要(译)

一种流体下超声成像导管系统，包括导管，其远端插入流体下结构，超声换能器阵列安装在导管的远端附近，其中阵列具有一排单独的换能器晶体，安装在阵列上的透镜用于散焦超声波束在垂直于阵列轴的方向上射束，以便提供体积视场，在该视场内对流体下特征进行成像。或者，单排换能器晶体由多行换能器晶体代替，以便提供体积视场。该成像导管系统帮助操作者看到流体不足环境的三维图像，例如心脏，血管，膀胱等充满液体的腔体的三维图像。这种宽体积视野中的特征可以是借助于实时图像，由流体不足的治疗设备成像，测量或干预。

