



US 20090131787A1

(19) **United States**(12) **Patent Application Publication****Lee et al.**(10) **Pub. No.: US 2009/0131787 A1**(43) **Pub. Date: May 21, 2009**(54) **ADAPTIVE IMAGE FILTERING IN AN
ULTRASOUND IMAGING DEVICE****Publication Classification**(51) **Int. Cl.**
A61B 8/00 (2006.01)(52) **U.S. Cl.** 600/437(57) **ABSTRACT**

The present invention relates to an ultrasound imaging device. The ultrasound imaging device includes: a data acquiring unit for acquiring 3-dimensional ultrasound image data based on receive signals formed based on ultrasound echoes reflected from a target object; a filtering unit for determining a size of a filtering mask of a filter, said size being adaptively determined according to an amount of the 3-dimensional ultrasound image data in data acquisition directions, the filtering unit being further configured to filter the 3-dimensional ultrasound image data by using the filtering mask; a scan converting unit for scan-converting the filtered 3-dimensional ultrasound image data; and a 3-dimensional rendering unit for performing 3-dimensional rendering upon the scan-converted 3-dimensional ultrasound image data to form a 3-dimensional ultrasound image.

(76) Inventors: **Jae Keun Lee**, Seoul (KR); **Suk Jin Lee**, Seoul (KR)

Correspondence Address:

JONES DAY**222 EAST 41ST ST****NEW YORK, NY 10017 (US)**(21) Appl. No.: **12/274,269**(22) Filed: **Nov. 19, 2008**(30) **Foreign Application Priority Data**

Nov. 20, 2007 (KR) 10-2007-0118600




FIG. 1




FIG. 2




FIG. 3





FIG. 4



ADAPTIVE IMAGE FILTERING IN AN ULTRASOUND IMAGING DEVICE

[0001] The present application claims priority from Korean Patent Application No. 10-2007-0118600 filed on Nov. 20, 2007, the entire subject matter of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] 1. Technical Field

[0003] The present invention generally relates to an ultrasound imaging device, and more particularly to an ultrasound imaging device and a method of forming a 3-dimensional ultrasound image using an adaptive filter.

[0004] 2. Background Art

[0005] An ultrasound imaging device has become an important and popular diagnostic tool due to its non-invasive and non-destructive nature. The ultrasound imaging device may form an ultrasound image by using ultrasound characteristics such as reflection, scattering and absorption when the ultrasound signals are propagated into tissues of a human body. Since the reflection and scattering of the ultrasound signals simultaneously occur in the target object, speckle noises may be included in forming ultrasound image data. The speckle noises may degrade a 3-dimensional ultrasound image. Also, boundaries between the organs and a background, which are important portions for diagnosis, may not be correctly displayed due to the speckle noises. Thus, the speckle noises may be burdensome in analyzing the 3-dimensional ultrasound image and examining the organs in the 3-dimensional ultrasound image.

[0006] Recently, various types of filters have been introduced to reduce the speckle noises in the 3-dimensional ultrasound image. However, the conventional filters may filter the 3-dimensional ultrasound data without considering an amount of data in data acquisition directions (i.e., axial, lateral and elevation directions) to reduce the speckle noises. As such, a loss of the ultrasound image data may occur during the filtering. Thus, the 3-dimensional ultrasound image may be distorted due to the data loss.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] FIG. 1 is a block diagram showing one embodiment of the ultrasound imaging device.

[0008] FIG. 2 is a schematic diagram showing an example of 3-dimensional ultrasound image data acquired in axial, lateral and elevation directions.

[0009] FIG. 3 is a schematic diagram showing an example of a filtering mask set in 3-dimensional ultrasound image data.

[0010] FIG. 4 is a flowchart showing an example of mixing ultrasound images filtered by filters with different filtering masks.

DETAILED DESCRIPTION OF THE INVENTION

[0011] FIG. 1 is a block diagram of an illustrative embodiment of an ultrasound imaging device. Referring to FIG. 1, a probe 100 may include a plurality of elements 112. The elements 112 may transmit ultrasound signals along scan lines set in a target object in response to transmit pulse signals

applied thereto. The elements 112 may then output electrical receive signals based on ultrasound echoes reflected from the target object.

[0012] A data acquiring unit 120 may perform signal processing upon the receive signals to thereby form ultrasound image data. The ultrasound image data may include a 3-dimensional ultrasound image data such as volume data, as illustrated in FIG. 2. Reference planes A, B and C may be set in the volume data. The reference planes A, B and C may be determined based on a scanning direction. A resolution of reference plane images may depend on the amount of ultrasound image data, which are acquired during the scanning. Generally, a larger amount of ultrasound image data may be acquired in the order of an axial direction, a lateral direction and an elevation direction.

[0013] A filtering unit 130 may filter the ultrasound image data to reduce speckle noises in the ultrasound image data. In one embodiment, the filtering unit 130 may adopt an adaptive 3-dimensional filter. The adaptive 3-dimensional filter may use a filtering mask, the size of which is determined according to a data acquisition ratio of the ultrasound image data in data acquisition directions. The filter unit 130 may calculate a data acquisition ratio of amounts of the ultrasound image data in axial, lateral and elevation directions. The filtering unit 130 may determine a size of the filtering mask of the adaptive 3-dimensional filter in the axial, lateral and elevation directions to obtain the same ratio as the data acquisition ratio. For example, assuming that the data acquisition ratio is 7:5:3 in the axial, lateral and elevation directions, the filtering unit 130 may determine the filtering mask having a size of 7×5×3.

[0014] FIG. 3 is a schematic diagram showing an example of a filtering mask set on the 3-dimensional ultrasound image data 300. As shown in FIG. 3, a length of the filtering mask 310 in an axial direction, for which a relatively more amount of ultrasound image data may be obtained, may be set to be relatively long. Also, a length of the filtering mask 310 in an elevation direction, for which a relatively less amount of ultrasound image data may be obtained, may be set to be relatively short. Thus, data loss may be reduced during the filtering. In one embodiment, the filter may be an average filter or a Gaussian filter. That is, the filtering unit 130 may be configured to smooth the ultrasound image through the filtering to thereby reduce the speckle noises.

[0015] A user input unit 140 may receive an instruction from a user. The user input unit 140 may be an input device such as a keyboard, a mouse, a track ball and the like. As mentioned above, the size of the filtering mask may be determined according to the amount of the ultrasound data for the respective data acquisition directions in accordance with one embodiment. Also, in another embodiment, the size of the filtering mask may be determined by the instruction inputted through the user input unit 140. That is, the user may adjust the size of the filtering mask so that a desirable ultrasound image may be obtained.

[0016] The scan converting unit 150 may scan-convert the filtered ultrasound image data into a data format suitable for display. The scan converting unit 150 may perform 3-dimensional scan conversion. A 3-dimensional rendering unit 160 may perform volume rendering upon the scan-converted ultrasound image data to thereby form a 3-dimensional ultrasound image. The volume rendering may be carried out with a ray casting method. The 3-dimensional ultrasound image data obtained through the volume rendering may be interpo-

lated to form a 3-dimensional ultrasound image. The 3-dimensional ultrasound image may be displayed on a display unit (not shown).

[0017] In another embodiment, the 3-dimensional ultrasound image data may be filtered at least twice with the filtering masks having different sizes. The filtered 3-dimensional ultrasound image data may be scan-converted and rendered. This is so that a plurality of 3-dimensional ultrasound images obtained by using different filtering masks may be obtained. The plurality of 3-dimensional ultrasound images may be mixed to obtain a desirably smoothened 3-dimensional ultrasound image. To this end, the ultrasound imaging device 100 may further comprise a mixing unit 170 for mixing the 3-dimensional ultrasound images produced by the 3-dimensional rendering unit 160.

[0018] FIG. 4 is a flowchart showing a procedure of forming an ultrasound image by mixing ultrasound images filtered with different sizes of the filtering masks. Referring to FIG. 4, the data acquiring unit 120 may acquire the ultrasound image data based on the receive signals outputted from the probe 110. The filtering unit 130 may filter the ultrasound image data with a first filtering mask to thereby output a first filtered ultrasound image data at step S420. In such a case, the size of the first filtering mask may be determined according to a ratio of amounts of the ultrasound image data in the axial, lateral and elevation directions. That is, the size of the first filtering mask may be determined to have the same ratio as the data acquisition ratio in the axial, lateral and elevation directions. Also, in another embodiment, the size of the filtering mask may be determined by the user instruction inputted through the user input unit 140.

[0019] The scan converting unit 150 may scan-convert the first filtered ultrasound image data to output a first scan-converted ultrasound image data at step S430. The 3-dimensional rendering unit 160 may perform the volume rendering upon the first scan-converted ultrasound image data to thereby form a first ultrasound image data at step S440.

[0020] Subsequently, the filtering unit 130 may filter the ultrasound image data with a second filtering mask to thereby output a second filtered ultrasound image data at step S450. In such a case, the size of the filtering mask may be determined to have a larger size than the first filtering mask. The size of the second mark filter may also be determined to have the same ratio as the data acquisition ratio in the axial, lateral and elevation directions. Moreover, the size of the second filtering mask may be determined by the user instruction inputted through the user input unit 140.

[0021] The scan converting unit 150 may scan-convert the second filtered ultrasound image data to output a second scan-converted ultrasound image data at step S460. The 3-dimensional rendering unit 160 may perform the volume rendering upon the second scan-converted ultrasound image data to thereby form a second ultrasound image at step S470.

[0022] The mixing unit 170 may mix the first and second ultrasound images to thereby form a final 3-dimensional ultrasound image at step S480. A mixing ratio of the first and second ultrasound images may be determined by a user instruction inputted through the user input unit 140. For example, if the mixing ratio of the first ultrasound image is higher, then a relatively sharper ultrasound image may be obtained. Also, if the mixing ratio of the second ultrasound image is higher, then a relatively more smoothened ultrasound image may be obtained. The mixed 3-dimensional ultrasound image may be displayed through the display unit

at step S490. According to another embodiment, the more smoothened 3-dimensional ultrasound image may be obtained.

[0023] As mentioned above, since the size of the filtering mask is adaptively adjusted according to the data acquisition ratio in the axial, lateral and elevation directions, the data loss may be reduced with a reduction of the speckle noise. Thus, an enhanced 3-dimensional ultrasound image may be obtained. Further, as the adaptive filtering mask is adopted, filtering calculation may be reduced.

[0024] In accordance with one embodiment of the present invention, there is provided an ultrasound imaging device, comprising: a data acquiring unit for acquiring 3-dimensional ultrasound image data based on receive signals formed based on ultrasound echoes reflected from a target object; a filtering unit for determining a size of a filtering mask of a filter, said size being adaptively determined according to an amount of the 3-dimensional ultrasound image data in data acquisition directions, the filtering unit being further configured to filter the 3-dimensional ultrasound image data by using the filtering mask; a scan converting unit for scan-converting the filtered 3-dimensional ultrasound image data; and a 3-dimensional rendering unit for performing 3-dimensional rendering upon the scan-converted 3-dimensional ultrasound image data to form a 3-dimensional ultrasound image.

[0025] In accordance with another embodiment of the present invention, there is provided a method of forming an ultrasound image, comprising: a) acquiring 3-dimensional ultrasound image data based on ultrasound echoes reflected from a target object; b) adaptively determining a size of a filtering mask of a filter according to an amount of the 3-dimensional ultrasound image data in data acquisition directions and filtering the 3-dimensional ultrasound image data by using the filtering mask; c) scan-converting the filtered 3-dimensional ultrasound image data; and d) performing 3-dimensional rendering upon the scan-converted 3-dimensional ultrasound image data to form a 3-dimensional ultrasound image.

[0026] Any reference in this specification to “one embodiment,” “an embodiment,” “example embodiment,” etc. means that a particular feature, structure or characteristic described in connection with the embodiment is included in at least one embodiment of the present invention. The appearances of such phrases in various places in the specification are not necessarily all referring to the same embodiment. Further, when a particular feature, structure or characteristic is described in connection with any embodiment, it is submitted that it is within the purview of one skilled in the art to effect such feature, structure or characteristic in connection with other ones of the embodiments.

[0027] Although embodiments have been described with reference to a number of illustrative embodiments thereof, it should be understood that numerous other modifications and embodiments can be devised by those skilled in the art that will fall within the spirit and scope of the principles of this disclosure. More particularly, numerous variations and modifications are possible in the component parts and/or arrangements of the subject combination arrangement within the scope of the disclosure, the drawings and the appended claims. In addition to variations and modifications in the component parts and/or arrangements, alternative uses will also be apparent to those skilled in the art.

What is claimed is:

1. An ultrasound imaging device, comprising:
 - a data acquiring unit for acquiring 3-dimensional ultrasound image data based on receive signals formed based on ultrasound echoes reflected from a target object;
 - a filtering unit for determining a size of a filtering mask of a filter, said size being adaptively determined according to an amount of the 3-dimensional ultrasound image data in data acquisition directions, the filtering unit being further configured to filter the 3-dimensional ultrasound image data by using the filtering mask;
 - a scan converting unit for scan-converting the filtered 3-dimensional ultrasound image data; and
 - a 3-dimensional rendering unit for performing 3-dimensional rendering upon the scan-converted 3-dimensional ultrasound image data to form a 3-dimensional ultrasound image.
2. The ultrasound imaging device of claim 1, wherein the filtering unit determines the size of the filtering mask according to a data acquisition ratio of an amount of the 3-dimensional data in data acquisition directions.
3. The ultrasound imaging device of claim 1, further comprising a user input unit operable to an instruction for setting the size of the filtering mask.
4. The ultrasound imaging device of claim 2, wherein the size of the filtering mask is determined to have different lengths in at least two acquisition directions.
5. The ultrasound imaging device of claim 1, further comprising a mixing unit for mixing a plurality of ultrasound images.
6. The ultrasound imaging device of claim 5, wherein the filtering unit filters the 3-dimensional ultrasound image data with a first filtering mask to thereby output a first filtered ultrasound image data and a second filtering mask having a different size from the first filtering mask to thereby output a second filtered ultrasound image data,
 - the scan converting unit scan-converts the first and second filtered ultrasound image data to output first and second scan-converted ultrasound image data,
 - the 3-dimensional rendering unit performs rendering upon the first and second scan-converted ultrasound image data to thereby form first and second 3-dimensional ultrasound images, and
 - the mixing unit mixes the first and second 3-dimensional ultrasound images to form a single 3-dimensional ultrasound image.
7. The ultrasound imaging device of claim 6, wherein the second filtering mask is larger than the first filtering mask.
8. A method of forming an ultrasound image, comprising:
 - a) acquiring 3-dimensional ultrasound image data based on ultrasound echoes reflected from a target object;
 - b) adaptively determining a size of a filtering mask of a filter according to an amount of the 3-dimensional ultrasound image data in data acquisition directions and filtering the 3-dimensional ultrasound image data by using the filtering mask;
 - c) scan-converting the filtered 3-dimensional ultrasound image data; and
 - d) performing 3-dimensional rendering upon the scan-converted 3-dimensional ultrasound image data to form a 3-dimensional ultrasound image.
9. The method of claim 8, wherein the size of the filtering mask is determined according to a ratio of amount of the 3-dimensional data in data acquisition directions.
10. The method of claim 9, wherein the size of the filtering mask is determined to have a different length in at least two acquisition directions.
11. The method of claim 10, wherein the step b) includes filtering the 3-dimensional ultrasound image data with a first filtering mask to thereby output a first filtered ultrasound image data and a second filtering mask having a different size from the first filtering mask to thereby output a second filtered ultrasound image data,
 - the step c) includes scan-converting the first and second filtered ultrasound image data to output first and second scan-converted ultrasound image data, and
 - the step d) includes performing rendering upon the first and second scan-converted ultrasound image data to thereby form first and second 3-dimensional ultrasound images, the method further comprising mixing the first and second 3-dimensional ultrasound images to form a single 3-dimensional ultrasound image.
12. The method of claim 11, wherein the second filtering mask is larger than the first filtering mask.

* * * * *

专利名称(译)	超声成像装置中的自适应图像滤波		
公开(公告)号	US20090131787A1	公开(公告)日	2009-05-21
申请号	US12/274269	申请日	2008-11-19
[标]申请(专利权)人(译)	李宰瑾 LEE SUK金		
申请(专利权)人(译)	李宰瑾 LEE SUK金		
当前申请(专利权)人(译)	李宰瑾 LEE SUK金		
[标]发明人	LEE JAE KEUN LEE SUK JIN		
发明人	LEE, JAE KEUN LEE, SUK JIN		
IPC分类号	A61B8/00		
CPC分类号	A61B8/14 A61B8/483 A61B8/5269 G01S7/52026 G06T2207/20221 G01S15/8993 G06T5/50 G06T2207/10136 G01S7/52077		
优先权	1020070118600 2007-11-20 KR		
其他公开文献	US8282552		
外部链接	Espacenet USPTO		

摘要(译)

超声波成像装置技术领域超声成像装置包括：数据获取单元，用于基于从目标对象反射的超声回波形成的接收信号来获取三维超声图像数据；滤波单元，用于确定滤波器的滤波掩模的大小，所述大小根据数据采集方向上的三维超声图像数据的量自适应地确定，所述滤波单元还被配置为对三维超声进行滤波使用过滤掩码的图像数据；扫描转换单元，用于对滤波的三维超声图像数据进行扫描转换；和3维渲染单元，用于对扫描转换的3维超声图像数据进行3维渲染，以形成3维超声图像。

