



US006764450B2

(12) **United States Patent**  
**Yock**

(10) **Patent No.:** **US 6,764,450 B2**  
(45) **Date of Patent:** **Jul. 20, 2004**

(54) **METHOD AND APPARATUS FOR  
INTRAVASCULAR TWO-DIMENSIONAL  
ULTRASONOGRAPHY**

(75) **Inventor:** **Paul G. Yock**, Hillsborough, CA (US)

(73) **Assignee:** **SciMed Life Systems, Inc.**, Maple Grove, MN (US)

(\*) **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 155 days.

(21) **Appl. No.:** **10/438,111**

(22) **Filed:** **May 13, 2003**

(65) **Prior Publication Data**

US 2003/0199761 A1 Oct. 23, 2003

**Related U.S. Application Data**

(63) Continuation of application No. 10/177,897, filed on Jun. 20, 2002, now Pat. No. 6,572,554, which is a continuation of application No. 09/816,586, filed on Mar. 23, 2001, now Pat. No. 6,409,673, which is a continuation of application No. 09/300,168, filed on Apr. 27, 1999, now Pat. No. 6,221,015, which is a continuation of application No. 08/911,635, filed on Aug. 15, 1997, now Pat. No. 5,902,245, which is a continuation of application No. 08/467,178, filed on Jun. 6, 1995, now Pat. No. 5,865,178, which is a continuation of application No. 08/162,412, filed on Dec. 3, 1993, now Pat. No. 5,676,151, which is a division of application No. 08/014,906, filed on Feb. 1, 1993, now Pat. No. 5,313,949, which is a continuation of application No. 07/826,260, filed on Jan. 24, 1992, now abandoned, which is a continuation of application No. 07/649,048, filed on Feb. 1, 1991, now abandoned, which is a continuation of application No. 07/290,533, filed on Dec. 23, 1998, now Pat. No. 5,000,185, which is a continuation-in-part of application No. 06/834,893, filed on Feb. 28, 1986, now Pat. No. 4,794,931.

(51) **Int. Cl.<sup>7</sup>** ..... **A61B 8/12**

(52) **U.S. Cl.** ..... **600/466; 600/471**

(58) **Field of Search** ..... 600/459-471,  
600/110, 137, 139-140; 128/901; 604/96,  
264; 606/159, 167-171

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,779,234 A 12/1973 Eggleton et al.  
3,817,089 A 6/1974 Eggleton et al.  
3,938,502 A 2/1976 Bom

(List continued on next page.)

**FOREIGN PATENT DOCUMENTS**

DE 2305501 8/1974  
EP 0088620 9/1983  
EP 0163502 12/1985  
EP 0234951 9/1987  
FR 2424733 11/1979  
WO 8301893 6/1983

**OTHER PUBLICATIONS**

Bertini et al., "Rotating Probe for Trans-Esophageal Cross-Sectional Echocardiography," J. Nuc. Med. Allied Sci. 28(2):115-121.

Bom et al., "Early and Recent Intraluminal Ultrasound Devices," International Journal of Cardia: Imaging, 4:79-88, (1989).

Bom et al., "Ein Weg sur Intraluminaren Echoateriographie" Untraschall 8 pp. 233-236 (Oct. 1987) (translation attached).

(List continued on next page.)


*Primary Examiner*—Francis J. Jaworski

(74) *Attorney, Agent, or Firm*—Orrick, Herrington & Sutcliffe LLP

(57) **ABSTRACT**

A catheter is provided for insertion in the he blood vessel of a patient for ultrasonically imaging the vessel wall. The catheter includes a tubular element and an internally housed drive cable for effective circumferential scan about the catheter of an ultrasonic generating means. Both the tubular element and the drive cable are of a size and flexibility sufficient to permit their introduction into the vessel and subsequent advancement through the vessel to the location of the vessel wall where imaging is desired.

**8 Claims, 4 Drawing Sheets**



## U.S. PATENT DOCUMENTS


3,942,530 A 3/1976 Northeved  
 4,020,847 A 5/1977 Clark, III  
 4,034,744 A 7/1977 Goldberg  
 4,175,566 A \* 11/1979 Millar et al. .... 73/861.12  
 4,259,970 A 4/1981 Green, Jr.  
 4,275,597 A 6/1981 Quedens et al.  
 4,319,580 A 3/1982 Colley et al.  
 4,354,501 A 10/1982 Colley et al.  
 4,374,525 A 2/1983 Baba  
 4,391,282 A 7/1983 Ando et al.  
 4,402,223 A 9/1983 Nauman, Jr. et al.  
 4,408,612 A 10/1983 Utsugi  
 4,442,842 A 4/1984 Baba  
 4,466,443 A 8/1984 Utsugi  
 4,466,444 A 8/1984 Baba  
 4,475,553 A 10/1984 Yamaguchi et al.  
 4,489,727 A 12/1984 Matsuo et al.  
 4,489,728 A 12/1984 Matsuo et al.  
 4,494,549 A 1/1985 Namba et al.  
 4,546,771 A 10/1985 Eggleton et al.  
 4,558,706 A 12/1985 Nakada et al.  
 4,561,446 A 12/1985 Hetz  
 4,572,201 A 2/1986 Kondo et al.  
 4,572,203 A 2/1986 Feinstein  
 4,576,177 A 3/1986 Webster, Jr.  
 4,582,067 A 4/1986 Silverstein et al.  
 4,587,972 A 5/1986 Morantte, Jr.  
 4,615,330 A \* 10/1986 Nagasaki et al. .... 128/901  
 4,633,882 A 1/1987 Matsuo et al.  
 4,641,657 A 2/1987 Ellis  
 4,669,465 A 6/1987 Moore et al.  
 4,669,469 A 6/1987 Gifford, III et al.  
 4,732,156 A 3/1988 Nakamura  
 4,748,982 A 6/1988 Horzewski et al.  
 4,771,788 A 9/1988 Millar  
 4,794,931 A 1/1989 Yock  
 4,841,977 A 6/1989 Griffith et al.  
 4,887,605 A 12/1989 Angelsen et al.  
 4,887,606 A 12/1989 Yock et al.  
 4,899,757 A 2/1990 Pope, Jr. et al.  
 4,911,170 A 3/1990 Thomas, III et al.  
 4,917,097 A 4/1990 Proudian et al.  
 4,917,104 A 4/1990 Rebell  
 4,920,967 A 5/1990 Cottonaro et al.  
 4,928,699 A 5/1990 Sasai  
 4,951,677 A 8/1990 Crowley et al.  
 4,967,753 A 11/1990 Haase et al.  
 4,991,588 A 2/1991 Pflueger et al.  
 4,998,916 A 3/1991 Hammerslag et al.  
 5,000,185 A 3/1991 Yock  
 5,002,059 A 3/1991 Crowley et al.  
 5,007,434 A 4/1991 Doyle et al.  
 5,029,588 A 7/1991 Yock et al.  
 5,040,548 A 8/1991 Yock  
 5,049,130 A 9/1991 Powell  
 5,061,273 A 10/1991 Yock  
 5,115,814 A 5/1992 Griffith  
 5,300,085 A 4/1994 Yock  
 5,311,871 A 5/1994 Yock  
 5,313,949 A 5/1994 Yock  
 5,350,395 A 9/1994 Yock  
 5,451,207 A 9/1995 Yock  
 5,451,233 A 9/1995 Yock  
 5,496,346 A 3/1996 Horzewski et al.  
 5,501,227 A 3/1996 Yock  
 5,582,178 A 12/1996 Yock  
 5,596,990 A 1/1997 Yock et al.  
 5,651,364 A 7/1997 Yock  
 5,865,178 A 2/1999 Yock  
 6,221,015 B1 4/2001 Yock

6,409,673 B2 6/2002 Yock

## OTHER PUBLICATIONS

Crowley et al., "Optimized Ultrasound Imaging Catheters for Use in the Vascular System," *Int. J. Car. Imag.* 4:145-151, (1989).  
 Ebina et al., "The Diagnostic Application of Ultrasound to the Disease in Mediastinal Organs," *Sci. Rep. Res. Inst. Tohoku U.* 12:199-212.  
 Eggleton et al., "Computerized Ultrasonic Visualization of Dynamic Ventricular Configurations," 8<sup>th</sup> ICMBE, Chicago, Ill. (Jul. 1969).  
 Engin., pp. 168-171.  
 Fukuda, M., "Endoscopic Ultrasonography," In: Gill, R.W., Dadd, M.J. eds., *WFUMB '85*, 13-16 (1985).  
 Garret, L., "A Catheter Assembly," PCT Application No. PCT/US82/01669, Published as WO83/01893 on Jun 9, 1983.  
 Gichard et al., "Development of the Mechanically Scanned Doppler Blood Flow Catheter," *Ultrasonics Symposium Proc.* 75, CHO-994-4SU, pp. 18-21 (1975).  
 Handley et al., Abstract, "The Development of an Ultrasonic Endoscope for the Assessment of Arterial Wall Disease," *Proceedings of the British Medical Ultrasound Society*, p. 689, Jul. 1985.  
 Hartley et al., "A Single-Crystal Ultrasonic Catheter-Tip Velocity Probe," *Medical Instrumentation* 8:241-243.  
 Hisanaga et al., "A New Real-Time Sector Scanning System of Ultra-Wide Angle . . .," *Proc. of the 22<sup>nd</sup> Annual Mtg. of the AIUM* (1978).  
 Hisanaga et al., "Transesophageal Cross-Sectional Echocardiography," *American Heart Journal*, pp. 607-609, (Nov. 1980).  
 Hisanaga et al., *Proc. Jap. Soc. Ultrasonics Med.*, 32:43-44, (1977).  
 Isner, et al., "Percutaneous Intravascular US as Adjunct to Catheter-Based Interventions: . . . Radiology," 175(1):61-70, (1990).  
 Kossoff, G., "Diagnostic Applications of Ultrasound in Cardiology," *Aust. Radiol.*, X:101-6 (1966).  
 Olson et al., *IEEE Transactions on Biomed.* (1974).  
 Omoto, *Jap. Heart J.*, 8:569-581, (1967).  
 Omoto, R., "Intracardiac Scanning of the Heart with the Aid of Ultrasonic Intravenous Probe," *Jap. Heart J.*, 8:569-581, (1967).  
 Omoto, R., "Ultrasonic Tomography of the Heart: An Intracardiac Scan Method," *Ultrasonics*, pp. 80-83, (Apr. 1967).  
 Serruys et al., *Am. J. Cardiol.*, 61:253-259, (1988).  
 Simpson, J.B., "Atherectomy Device & Method," *European Patent Application No. 0 163 502*, Published Apr. 12, 1985.  
 Slager et al., *JACC*, vol. 5, No. 6, pp. 1382-1386 (1985).  
 Wells et al., "Ultrasonic Transesophageal Measurement of Cardia Output," *Conference: Advances in Bioengineering*, San Francisco, California, (Dec. 1978).  
 Wells, P.N.T., "Developments in Medical Ultrasonics," *European Symposium on Medical Electronics*, pp. 272-276 (Oct. 1975).  
 Wells, *World Medical Electronics*, pp. 272-276 (1966).  
 Wild et al., "Ultrasonic Ranging," *Electronics*, pp. 174-180 (Mar. 1955).  
 Wild et al., *Am. Inst. Ultrasonics Med.*, pp. 47-72, (Aug. 1955).

\* cited by examiner






FIG. 2A.




FIG. 10A.




FIG. 2B.




FIG. 10B.




FIG. -5




FIG. -6




FIG. -7




FIG. 8.




FIG. 9.




FIG. 10.

FIG. 11.

## METHOD AND APPARATUS FOR INTRAVASCULAR TWO-DIMENSIONAL ULTRASONOGRAPHY

This application is a continuation of co-pending U.S. patent application Ser. No. 10/177,897, filed on Jun. 20, 2002 and now U.S. Pat. No. 6,572,554, which is a continuation of U.S. patent application Ser. No. 09/816,586, filed on Mar. 23, 2001 (now U.S. Pat. No. 6,409,673), which is a continuation of U.S. patent application Ser. No. 09/300,168, filed on Apr. 27, 1999 (now U.S. Pat. No. 6,221,015), which is a continuation of U.S. patent application Ser. No. 08/911,635, filed on Aug. 15, 1997 (now U.S. Pat. No. 5,902,245), which is a continuation of U.S. patent application Ser. No. 08/467,178, filed on Jun. 6, 1995 (now U.S. Pat. No. 5,865,178), which is a continuation of U.S. patent application Ser. No. 08/162,412, filed on Dec. 3, 1993 (now U.S. Pat. No. 5,676,151), which is a divisional of U.S. patent application Ser. No. 08/014,906, filed on Feb. 1, 1993 (now U.S. Pat. No. 5,313,949), which is a continuation of U.S. patent application Ser. No. 07/826,260, filed on Jan. 24, 1992 (now abandoned), which is a continuation of U.S. patent application Ser. No. 07/649,048, filed on Feb. 1, 1991 (now abandoned), which is a continuation of U.S. patent application Ser. No. 07/290,533, filed on Dec. 23, 1988 (now U.S. Pat. No. 5,000,185), which is a continuation-in-part of U.S. Patent Application Serial No. 06/834,893, filed on Feb. 28, 1986 (now U.S. Pat. No. 4,794,931). The entire disclosures of all of the aforementioned applications are incorporated herein by reference. The present application is related to U.S. patent application Ser. No. 07/290,217, filed on Dec. 23, 1988, commonly assigned herewith, the disclosure of which is incorporated herein by reference.

### BACKGROUND OF THE INVENTION

This invention relates to a catheter apparatus, system, and method for intravascular two-dimensional ultrasonographic imaging, and more particularly to such an apparatus, system, and method for guiding and monitoring interventional therapy to reduce vascular stenosis.

Ultrasonic two-dimensional imaging apparatus and systems have heretofore been provided for use in endoscopy for examining the gastrointestinal tract. Such a device is disclosed in U.S. Pat. No. 4,494,549. Such devices, however, have been relatively large and inflexible and are completely unsuitable for use within the vascular system of the human body. In addition, there is no provision for guiding such devices into specific branches of blood vessels.

There is, therefore, a need for a new and improved catheter apparatus, systems, and methods which can be utilized for performing intravascular two-dimensional ultrasonographic imaging. It would be particularly desirable if such imaging apparatus and methods could be combined with a variety of intravascular therapeutic modalities, such as angioplasty atherectomy, laser ablation, and the like, in order to provide simultaneous imaging and recanalization procedures.

### SUMMARY OF THE INVENTION

According to the present invention, a method for imaging the interior of a blood vessel comprises scanning an ultrasonic signal in a preselected pattern about said interior. By receiving ultrasonic energy reflected from the interior surface of the vessel, including any stenosis or occlusion present, an image or profile of the blood vessel may be produced. Conveniently, the ultrasonic signal is generated

by a transducer located at the distal end of a vascular catheter comprising a flexible tubular member. The transducer may be manipulated directly to sweep the ultrasonic signal in a desired pattern, including radial, planar, and conical. Alternatively, the transducer may be fixed within the catheter and a reflective surface manipulated to sweep the ultrasonic signal in a desired pattern. The imaging method of the present invention is advantageously combined with interventional therapeutic techniques to reduce vascular stenosis, where the stenosis may be imagined prior to, during, and after intervention to help direct the interventional activity to where it will be most effective.

In general, it is an object of the present invention to provide a catheter apparatus, system, and method for intravascular two-dimensional ultrasonography.

Another object of the invention is to provide an apparatus, system, and method of the above character which has a high resolution capability.

Another object of the invention is to provide an apparatus, system, and method of the above character which can be utilized for assessing endovascular lesions.

Another object of the invention is to provide an apparatus, system, and method of the above character which can be utilized for monitoring the results of interventional therapy.

Another object of the invention is to provide an apparatus, system, and method of the above character which can be used with angioplasty, atherectomy, laser ablation, drug deliver, and similar vascular interventional methods and devices.

Another object is to provide an apparatus, system, and method capable of selective cannulation of branch vessels.

Additional objects and features of the invention will appear from the following description in which the preferred embodiments are set forth in detail in conjunction with the accompanying drawings.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side elevational view partially in cross-section of a catheter apparatus incorporating the present invention.

FIG. 2 is an enlarged cross-sectional view of the distal extremity of the apparatus shown in FIG. 1.

FIG. 2A is a detail view illustrating an alternate mounting of a crystal transducer to provide a conical sweep pattern.

FIG. 2B is an alternate embodiment of the distal extremity of the apparatus shown in FIG. 1, modified to be inserted over a movable guidewire and with the cutting direction reversed.

FIG. 3 is an enlarged cross-sectional view of an intermediate portion of the apparatus shown in FIG. 1.

FIG. 4 is an enlarged cross-sectional view taken along the line of 4—4 of FIG. 1.

FIG. 5 is an isometric view of the crystal assembly which forms a part of the apparatus shown in FIG. 1.

FIG. 6 is a schematic block diagram of the electrical and electronic apparatus utilized in the system.

FIG. 7 is a two-dimensional display of an ultrasonogram which can be obtained with the apparatus and system shown in FIGS. 1—6.

FIG. 8 is an enlarged cross-sectional view of another embodiment of a catheter apparatus incorporating the present invention.

FIG. 9 is a cross-sectional view taken along the liens of 9—9 of FIG. 8.

FIG. 10 is an enlarged cross-sectional view of still another embodiment of a catheter apparatus incorporating the present invention.

FIG. 10A is a detail view illustrating an alternate configuration of a reflective surface to provide a conical sweep pattern.

FIG. 10B is an alternate embodiment of the distal extremity of the catheter apparatus of FIG. 10, modified to provide a fixed ultrasonic transducer located proximally of a reflective surface on a cutter.

FIG. 11 is an enlarged cross-sectional view of another embodiment of the catheter apparatus incorporating the present invention.

#### DESCRIPTION OF THE SPECIFIC EMBODIMENTS

In general, the catheter apparatus of the present invention includes a flexible tubular element which is adapted to be inserted into a blood vessel in the vascular system and a flexible rotatable elongate element which is disposed in the tubular element. In a first embodiment, an ultrasonic transducer is carried at the distal end of the flexible rotatable elongate element, and electrical circuitry carried at the distal end of the flexible tubular element is connected to the ultrasonic transducer for supplying signals to and receiving signals from the transducer. In a second embodiment, a reflective surface is carried by the distal end of the flexible rotatable elongate element, and the ultrasonic transducer is mounted in the distal tip of the flexible tubular element so that signals generated by the transducer will be reflected by the reflective surface. In both embodiments, a transmitter is provided for supplying signals to the ultrasonic transducer and a receiver is provided for receiving signals from the ultrasonic transducer. A motor drive is usually provided for rotating the flexible elongate element along manual rotation may also be employed. By rotating the flexible elongate element, the transducer signal can be swept in a desired pattern, either directly by the transducer in the first embodiment, or indirectly by the reflective surface in the second embodiment. Timing and control circuitry is provided for controlling the operation of the transmitter and receiver and optionally the motor drive. A display is provided which is operated under the control of the timing and control circuitry for displaying the image information that is received by the receiver.

The catheters of the present invention may further include interventional capability for recanalization of occluded regions within the imaged blood vessel. Recanalization is intended to refer to both the opening of total occlusions, as well as broadening of the vessel lumen in partial occlusions. Catheters combining ultrasonic imaging capability with atherectomy devices for severing of stenotic material are described in detail hereinafter. The methods of the present invention, however, are not limited to atherectomy and include a wide variety of other interventional techniques that may be performed with vascular catheters. Suitable interventional techniques include balloon angioplasty, laser ablation angioplasty, balloon embolectomy, aspiration embolectomy, heat probe ablation, abrasion, drilling, therapeutic ultrasound, and the like. Also, the catheters may be adapted for introducing clot-dissolving drugs, such as tissue plasminogen activator, streptokinase, urokinase, and the like, in order to reduce the stenosis, as well as platelet receptor blockers and drugs which limit cell multiplication in order to inhibit restenosis. Conveniently, perfusion lumens and ports may be provided in the catheter to provide for the administration of such drugs.

A first exemplary construction of a catheter apparatus 11 constructed in accordance with the principles of the present

invention comprises an elongate tubular assembly 12 includes an elongate flexible tubular element 13 which is provided with four lumens 14, 16, 17, and 18 with the lumen 14 serving as a torque tube, lumen 16 serving as a balloon tube, and lumens 17 and 18 serving as infusion tubes or lumens as hereinafter described. The tubular element 13 may conveniently be formed as a single extrusion which provides the four lumens, with the lumens 14 and 16 being substantially circular in cross-section, and the lumens 17 and 18 being arcuate in shape with the configuration of each being determined by three arcs with one of the arcs being concentric with the outer diameter of the tubular element 13 and with the two smaller arcs being concentric with lumens 14 and 16, respectively.

A braided shield 21 is provided on the exterior of the tubular element 13 and takes the form of one or more layers of braided strands 22 formed of suitable magnetic material, such as an electrical shield. A cover tube 23 covers the braided shield 21 and extends the length of the tubular element 13. The cover tube 23 can be formed of a suitable material such as a heat shrinkable plastic which is shrunk tightly onto the braided shield 21 and provides a smooth outer surface so the tubular assembly 12 can readily enter a vessel of the vascular system of a patient.

A work performing device such as an atherectomy or cutting device of the type described in European patent application 163 502 may be provided in the distal extremity of the tubular assembly 12. A suitable cutting device is described in said European application and consists of a housing 27 that is provided with a cutout 28. A rotary cutter 29 is rotatably disposed within the housing 27 and is provided with a hub 31 that is secured to a flexible rotatable torque cable 32. The cable 32 is disposed in and extends through the torque tube lumen 14. The torque cable 32 is formed of a suitable material such as stainless steel. The housing 27 is provided with a rounded tip 33 having a recess 34 which is adapted to receive material which is removed by the rotary cutter 29 as the cutter 29 is advanced as hereinafter described. A spring tip guide or guidewire 36 capable of being shaped is secured to the rounded tip 33 and extends forwardly therefrom and serves to guide or steer the housing 27 as the tubular assembly 12 with the cutting device 26 secured thereto is introduced into the vessel of the vascular system of the patient. As shown, the spring tip guide 36 can be secured to the rounded tip 33 by suitable means, such as solder 37. It thus can be seen that the guidewire 36 is associated with the housing 27. Alternatively, a movable guidewire 38 (FIG. 2B) can be utilized to facilitate steering of the catheter 11 into the desired vessel of the patient.

A balloon 41 of an expandable type is optionally secured to the housing in a region opposite the cutout 28 and has its distal extremity bonded around the tip 33 by suitable means, such as an adhesive 42. As shown in FIG. 2, the balloon 41 underlies substantially the entire length of the housing 27. The balloon 41 is in communication with a balloon tube 43 that extends through the balloon tube lumen 16 in the tubular element 13. The balloon tube 43 is provided with a lumen 44 through which a medium can be introduced for inflating the balloon 41 and removed for deflating the balloon 41. The proximal extremity of the balloon 41 and the proximal extremity of the housing 27 are secured to the distal extremity of the tubular assembly 12 by suitable means, such as heat shrinkable tubing 46.

A system 49 is provided at the distal end 49 of catheter 11 for imaging the region in which the work performing device is located, said system usually being a two-dimensional ultrasound image system. The system 49 includes an ultra-



sonic transducer, such as a single crystal **51** (see FIG. 5), which is mounted on the hub **31** and is secured thereto by suitable means such as an adhesive. The crystal **51** is part of an assembly **52**. The crystal **51** should be capable of operating at a frequency range of 5 to 50 megahertz and typically can be formed of a suitable material such as barium titanate or cinnabar. As can be seen from FIG. 5, the crystal **51** has a rectangular block-like configuration and has two opposed surfaces covered by metallic conducting films **53** and **54** formed of a suitable material such as chrome or gold. The material of the films can be formed of a foil or can be in the form of films evaporated or sputtered onto the opposite surfaces of the crystal **51**. The films **53** and **54** serve as electrodes and are connected to connecting wires **56** and **57** by suitable means, such as solder. Means is provided for damping out the oscillations from the backside of the crystal **51** and takes the form of a rectangular block **58** formed of a suitable backing material. The backing material can be formed in a conventional manner so as to cancel out oscillations from the side of a crystal in which the backing material is disposed.

The present invention, however, is not limited to the use of piezoelectric crystal oscillators as the ultrasonic transducer, and organic electrets such as polyvinylidene difluoride (PVDF) and vinylidene fluoride-trifluoroethylene copolymers may also find use. PVDF is particularly suitable as a transducer at higher frequencies, typically at or above 40 MHz.

The wires **56** and **57** are braided onto the torque cable **32** and rotate with the torque cable. The wires **56** and **57** extend towards the proximal extremity of the tubular assembly **12** and extend into a fitting **61** (see FIG. 3) formed of a suitable material such as plastic. A pair of spaced-apart slip rings **62** and **63** formed of a conducting material such as copper are secured to the torque cable **32**. The wire **56** is bonded to the slip ring **62**, and the wire **57** is bonded to the slip ring **63**. A fitting **66** is provided which has a threaded bore **67**. The tubular assembly **12** extends through the fitting **66** and a reinforcing sleeve **68** extends over the portion of the tubular assembly **12** extending therethrough. A pair of spring urged contacts **71** and **72** are carried by the fitting **66** and are adapted to slidably engage the slip rings **62** and **63**. The contacts **71** and **72** are connected to conductors **73** and **74**. A grounding lug **76** is provided on the fitting **66** and makes electrical contact with the braided shield **21**. A conductor **77** is connected to the grounding lug **76**.

A male fitting **78** (see FIG. 1) is threaded into the threaded bore **67**. A single arm adapter **81** is mounted in the male fitting **78** and carries an arm **82** having thereon a balloon inflation port **83** that is in communication with the lumen **44** in the balloon tube **43** disposed in the tubular assembly **12**. The single arm adapter **81** is secured to a rotating adapter **86** of a conventional type and through which the tubular assembly **12** extends. Another single arm adapter **87** is mounted in the rotating adapter and is provided with a side arm **88** having an infusion port **89** disposed therein which is in communication with the infusion lumens **17** and **18** provided in the tubular assembly **12**. A tapered fitting **91** is mounted in the single arm adapter **87** and is provided with a threaded bore **92** which carries an O-ring **93** that is adapted to be engaged by a male type fitting **94** to form a liquid-tight seal between the tubular assembly **12** and the torque cable **32** which extends therethrough. The torque cable **32** is secured to a suitable drive member such as a clutch member **98** of the type described in European application 163 502 and U.S. Pat. No. 4,771,774, the disclosures of which are incorporated herein by reference. The clutch member **98** is adapted

to be secured to a motor drive means of the type described in U.S. Pat. No. 4,771,774 consisting of a motor drive unit which in the present application is identified as a motor **99** (see FIG. 6). The motor **99** is driven by and is under the control of electronic circuitry forming a part of system **49**. The part of the system **49**, shown in block diagram form is substantially conventional and can be of a suitable type such as certain equipment identified as Model 851B manufactured by Advanced Technology Laboratories, Inc., of Bothel, Wash. As shown in FIG. 6, such apparatus includes a timing and control block **102** that supplies pulses to a transmitter **103**. The output of the transmitter **103** is supplied through a transmit receive switch **104** which supplies the signals on the conductors **73** and **74** through the slip rings **62** and **63** onto the conductors **56** and **57** connected to the crystal **51**. During the time that the transmitter **103** is supplying high frequency energy to the crystal, the crystal **52** is being rotated by the motor driving the torque cable **32** with the motor **99** being under the control of the timing and control block **102**. The motor **99** is of a type such as an open loop stepping motor or a closed loop servo controlled motor which can be driven by the timing and control block **102**.

As an alternative to the use of an external motor **99** connected to the cutter **29** by torque cable **32**, it would be possible to construct catheters according to the present invention utilizing micromotors within the distal extremity of the catheter. The micromotors could be attached to directly rotate the cutter and transducer (or reflective surface as described hereinafter) typically by mounting at the end of a nonrotating cable analogous to torque cable **32**.

The transmitter generates a voltage pulse, typically in the 10 to 50 volt range, for excitation of the transducer crystal **51**. Supplying such voltage pulses to the crystal causes the transducer to produce sonic waves which emanate therefrom into the surrounding tissue structure. Portions of the sonic energy wave are reflected by the tissue structure back to the transducer and the transducer **51** acts as a receiver and picks up the sonic vibrations and converts them into electrical signals which are supplied by the conducting wires **56** and **57** back to the slip rings **62** and **63** through the conductors **73** and **74** and through the transmit receive switch **104** to a receiver **106**. These signals are amplified and supplied to a display unit **107** which includes a CRT screen **108** under the control of the timing and control block **102** to supply an image **109** on the display **108** which can be of the type shown in FIG. 7. As can be seen from FIG. 7, as viewed through 360°, the vessel wall **111** of the image **109** is shown as indicated, having different cross sections depending upon the buildup of plaque therein. A central region **112** of the image is eclipsed because of the imaging catheter. Alternatively, if desired, only a sector of a lesser angle than 360° can be viewed.

The catheter apparatus of the present invention can be constructed in various sizes. For example, in a 9 French size, the balloon can have a length of approximately 3 centimeters. Sizes down to 3 French and below can be accomplished with the construction of the present invention. These particular dimensions are exemplary only and not intended to limit the scope of the present invention in any way.

Operation and use of the catheter apparatus, system and method during intravascular ultrasonography can now be briefly described as follows. Let it be assumed that it is desired to utilize the apparatus, system and method of the present invention to remove the atheroma in a blood vessel of a patient. The catheter of the catheter apparatus of the present invention is introduced into a vessel of the patient as, for example, into the femoral artery and introducing the

catheter into the artery by the use of the guidewire 36. The progress of the catheter into the vessel of the patient can be observed under x-ray fluoroscopy. As soon as the cutting device has entered into a region which is desired to remove certain material from the vessel and before a cutting operation is commenced, the atheroma itself can be viewed by operation of the ultrasonic imaging system 49. This can be accomplished by operating the timing control block 102 to cause operation of the motor 99 which in turn causes rotation of the torque cable 32 and the crystal assembly 52 to scan the interior of the vessel in which the crystal 51 is disposed, usually at a rotation rate in the range from about 100 to 20,000 rpm, more usually from about 500 to 2,000 rpm. An image of what is being scanned will appear on the screen 108 of the display device 107. Alternatively, the torque cable 32 may be manually rotated (or aimed without rotation) to provide a desired image. Generally, however, motorized rotation will provide a higher definition image. During the time this rotary scanning is taking place, the cable 32 can be advanced to advance the cutter so that the entire region in which the material is to be removed can be scanned. Usually, the cable 32 is advanced incrementally so that distinct cross-sectional images will be successively produced, allowing the operator to determine the length and topography of the region. Alternatively, the entire catheter apparatus 11 may be axially advanced or retracted within the blood vessel lumen to provide a plurality of cross-sectional images to allow assessment of the entire length of the atheroma.

After the scan, the cable 32 can be retracted slightly (or the catheter 11 repositioned) so that the proximal extremity of the cutout 28 lies at the proximal extremity of the atheroma. In order to stabilize the cutting device, the balloon 41 can be inflated so as to urge the cutout 28 of the housing 27 towards the portion of the atheroma it is desired to remove. The motor 99 can then be energized to rotate the cutter 29. As the cutter 29 is rotated, it can be advanced to progressively remove the material which is disposed within the cutout 28 of the housing 27. As this material is removed it is pushed forwardly and eventually moves into the recess 34. The balloon 41 can then be deflated and the catheter apparatus removed from the vessel after which the material which has been deposited in the recess 34 can be removed and the cutting device cleaned for reinsertion into the vessel of the patient for removal of additional material from the vessel if required.

During the time that the cutting operation is taking place, the cutting operation can be viewed ultrasonically by the rotating crystal 51 that places an image on the screen 108. From this image it can be ascertained how well the cutter is performing in removing the material and whether or not an additional pass of the cutter is required. It should be appreciated that, if necessary, several passes of the cutter can be made and, if necessary, the catheter assembly can be removed from the vessel of the patient to clean out material which has been removed and deposited in a recess 34.

As illustrated in FIG. 2, the ultrasonic transducer 51 is oriented to direct the ultrasonic signal in a direction substantially radially outward relative to the axis of the flexible tubular element 13. It will sometimes be desirable, however, to incline the ultrasonic transducer relative to the tubular axis, as illustrated at 51' in FIG. 2A. By inclining the transducer 51', the ultrasonic signal is directed at a forward angle  $\alpha$  relative to the tubular axis. By rotating the inclined transducer 51', the ultrasonic signal will sweep a conical pattern directed forward of said transducer. The angle  $\alpha$  may be in the range from about 10° to 85°, usually being in the range from 20° to 60°. Scanning with a conical sweep is

desirable because it can provide forward viewing at or in front of the location where the cut is being made.

An alternate embodiment 11' of catheter 11 is illustrated in FIG. 2B. The catheter 11' is similar to that of catheter 11, except that it is modified to permit insertion of the catheter 11' over a movable guidewire 38 and the cutter 29' is reversed to provide cutting when the cutter is translated in the proximal (rearward) direction. The modifications include providing a penetration 39 in the distal tip of housing 27 and an axially aligned penetration 40 in the cutter 29'. The ultrasonic transducer 52' is mounted on the distal end of cutter 29', and torque cable 32' includes an axial lumen. In this way, the catheter 11' is inserted by conventional techniques over guidewire 38, with the guidewire passing through penetrations 39 and 40 and the lumen of torque cable 32'.

Another embodiment of the catheter apparatus of the present invention is shown in FIGS. 8 and 9. Many of the parts are very similar to the parts utilized in the embodiment of the invention shown in FIG. 1 and have been given the corresponding numerals. The ultrasonic transducer 52 is mounted in a cavity 53 formed to the rear of the rotary cutter 29. The distal extremity of the catheter apparatus shown in FIG. 8, (i.e., to the left) differs from the apparatus shown in FIG. 1 in that the conducting wires or leads connected to the ultrasonic crystal 52 are connected to the outside world at a point which is proximal of an adapter 122 whereas in the embodiment shown in FIG. 1, the connectors are connected at a point which is distal of the adapters 82 and 88. Thus, there is shown an adapter 122 which is provided with an arm 123 through which dye injection and pressure measurements can be made and another fitting 124 which can be utilized in inflating and deflating the balloon 41. Another adapter 126 is provided which is threaded into the proximal end of the adapter 122 and forms a sealing engagement with an O-ring 127 carried by the adapter 122. The torque cable 32 extends through the adapter 126 and is connected to a clutch member 128. The clutch member 128 which carries a finger operated member 129 is adapted to be secured to motorized drive means of the type hereinbefore described for causing rotation of the torque cable 32.

As hereinbefore explained, the conducting wires connected to the ultrasonic transducer 52 are braided into the guidewire 32. Means is carried by the adapter 126 which is adapted to make contact with the conducting wires connected to the crystal 52 and consists of brushes 131 and 132 which are yieldably urged by springs 133 towards the torque cable 32 so as to make contact with the conducting wires or leads carried by guidewire 32. The springs 133 are held in place by pins 134 which are frictionally seated within the adapter 126. Conducting wires 136 and 137 are connected to the pins 134. These wires 136 and 137 are connected into the system in a manner hereinbefore described with the previous embodiments. The operation of this embodiment is very similar to that described in conjunction with the operation of the embodiment shown in FIG. 1.

Operation of this embodiment of the invention is very similar to that hereinbefore described with the principal advantage being that leads which are connected to the crystal and for receiving signals from the crystal are disposed proximally of the two arm adapter 122.

As a modification of catheter 121, cutter 29 could be provided with an abrasive external surface, either in place of or in addition to the forward cutting edge. Such an abrasive surface would be useful to remove atheroma and plaque by contact abrasion.

Still another embodiment **151** of the catheter apparatus of the present invention is shown in FIG. **10**. Certain parts of this catheter apparatus **151** are very similar to those hereinbefore described and are identified by the same numbers. Thus there has been provided a housing **27** which has an outwardly facing cutout **28**. A coil spring guide wire **36** is secured to the distal extremity of the housing **27** as shown (although the catheter **151** could easily be adapted to receive a movable guidewire as described above in connection with the embodiment of FIGS. 1-4). The balloon **41** is carried by the housing and has its distal extremity secured to the housing by a band **92**. The balloon **41** is disposed outside of the housing **27** on the side opposite the cutout **28**. A flexible tubular assembly **154** is secured to the proximal end of the housing **27**. A three-arm adapter **152** is mounted on the proximal extremity of the tubular assembly **154**. The tubular assembly **154** comprises a flexible tubular element formed of a suitable material, such as plastic which is provided with a balloon inflation lumen **155** that is in communication with the interior of the balloon **41** and extends into a balloon inflation port **156** provided as a part of the three-arm adapter **152**.

A crystal **157** is carried by the housing **27** in a stationary position. As shown, the crystal **157** is mounted vertically or in a direction that is at right angles to the longitudinal axis of the housing **27**. It can be mounted in the distal extremity of the housing **27** in a suitable manner such as by an adhesive. A suitable sound absorbing material **158** is provided behind the ultrasonic crystal **157** and fills the space between the crystal **157** and the distal extremity of the housing **27**. A pair of conducting wires **161** are connected to the ultrasonic crystal **157** and extend rearwardly through the housing **27** and are connected into sockets **162** provided in a side arm **163** forming a part of the adapter **152**.

The flexible tubular element **154** is provided with a large lumen **164** extending the length thereof and which has a rotatable flexible drive cable **166** disposed therein. The flexible torque cable **166** is formed in the manner hereinbefore described and is secured to a generally cylindrical member **167** which as hereinafter described, serves as a reflector mount and also serves to carry a rear-facing rotary cutter **169**. Thus, as shown, the member **167** is provided with a reflective surface **168** which is inclined at an angle of approximately  $45^\circ$  and faces the transducer **157** in such a manner so that sound waves propagated by the transducer impinge upon the surface **168** and are propagated outwardly in a direction substantially transverse, i.e., at right angles, to the longitudinal axis of the housing **27**. A circular cutting edge **169** is provided on the member **167** at the proximal extremity thereof. A truncated conical recess **171** is provided in the proximal extremity of the member **167**. The conical recess **171** can be used as a reservoir for collecting material as it is severed by the circular cutting edge **169**.

The angle of inclination of the reflective surface **168** relative to the axis of housing **27** may be varied, particularly being increased, as illustrated in FIG. **10A**, where angle  $P$  may be in the range from  $10^\circ$  to  $85^\circ$ , usually being in the range from  $10^\circ$  to  $40^\circ$ . By inclining the reflective surface by an angle  $\beta$  less than  $45^\circ$ , the reflected ultrasonic signal will sweep in a rearward conical pattern which allows viewing at or in front of, (i.e., to the right in FIG. **10**), the cutting edge **169** of member **167**.

The three-arm adapter **152** is provided with another arm **173** which serves as an infusion port and which is in communication with the lumen **164** through which the drive cable **166** extends. This lumen **164** opens into the interior of the housing **27** and is in communication with the cutout **28**.

Another adapter **176** is threaded into the proximal extremity of the adapter **162** and engages an O-ring **177**. The drive cable **166** extends through the adapter **176** and has its distal extremity secured to the clutch member **128**. As hereinbefore explained, the clutch member **128** can be secured to a motorized drive means (or may be manually rotated) for causing rotational movement of the cutter and mirror member **167**.

An alternate embodiment **151'** of catheter **151** is illustrated in FIG. **10B**. The catheter employs a fixed ultrasonic transducer **157'**, but cutter **169'** is reversed to provide for forward cutting. Forward cutting is often advantageous in that severed stenotic material is less likely to become entangled with the torque cable **166'**. Ultrasonic transducer **157'** will be provided with a central penetration to allow passage of the torque cable **166'**, and said transducer will be located at the proximal end of housing **27'**, but otherwise the construction of catheter **151'** will be the same as catheter **151**.

In a further modification, it is possible to secure the ultrasonic transducer **157'** onto the torque cable **166'**. Wires connecting the transducer **157'** to the external receiver and transmitter would then be attached to the torque cable **166'** and coupled to the outside in a manner similar to that illustrated in FIGS. 1-4. The transducer **157'** would then translate axially in tandem with the cutter **169'** and the mirror **168'**. By maintaining a fixed distance between the cutter **169'** and transducer **157'**, signal processing to produce an image is simplified.

Operation of the catheter apparatus **151** shown in FIG. **10** may now be described as follows. The operation of this device in many respects is very similar to that hereinbefore described with respect to the placement of the catheter in the vessel. The housing **27** can be positioned in the stenosis hereinbefore described and ultrasonic imaging can be carried out by supplying pulses of electrical energy to the ultrasonic transducer **157** which emanates ultrasonic energy and directs the same onto the reflector **168** which reflects the ultrasonic energy up into the tissue surrounding the housing. Rotation of the mirror **168** causes an image to be formed that can be viewed in the manner hereinbefore described. This imaging can be carried out by rotating the cable **166** and at the same time advancing the drive cable **166** throughout the length of the cutout **28** to view the stenosis. After the viewing operation has been accomplished and it is ascertained that it is desirable to remove the material creating the stenosis by use of the work performing device in the form of the cutter member **167**, the cutter member **167** can be advanced to the distal extremity of the cutout **28**. With the cutout **28** in the proper location, the balloon **41** can then be inflated through the balloon inflation port **156** to urge the housing **27** in a direction so that the stenosis enters the cutout. As soon as this has been accomplished, the cutter member **157** can be rotated at a high rate of speed and gradually retracted, (i.e., translated to the right in FIG. **10**), to cause the material forming the stenosis to be severed by the blade **169** on cutter member **167** and collected within the recess **171**. This cutting and collecting operation can be continued until the cutter member **167** has been advanced to the extreme proximal position. At this time, the catheter apparatus **151** can be removed and the tissue collected within the recess **171** can be removed. Thereafter, additional insertions of the catheter apparatus can be made and the same cutting operations performed until desired amount of material has been removed from the area of the stenosis to provide for increased blood flow through the vessel.

Another embodiment of a catheter apparatus **180** incorporating the present invention is shown in FIG. **11**. The

catheter apparatus **180** is utilized solely for imaging purposes and employs a fixed ultrasonic transducer **182** which transmits its signal against a rotating reflective surface **204**. The catheter apparatus **180** is constructed very similar to the catheter apparatus **151** shown in FIG. **10** with the exception that the cutting mechanism has been eliminated. The use of such a catheter apparatus **180** is desirable where it is unnecessary to provide a cutting function (or other interventional treatment modality). The catheter apparatus **180** also has many parts that are similar to the catheter apparatuses heretofore described. Thus there is provided a housing **27** which carries on its distal extremity a coil spring guide **36**. As before, however, the catheter **180** can also be adapted to be inserted over a movable guidewire within the scope of the present invention. The ultrasonic transducer **182** is provided in the distal extremity of the housing **27** and is disposed vertically or in a direction that is perpendicular to the longitudinal axis of the housing. A sound absorbing backing material **183** is provided in the distal extremity of the housing behind the transducer **182**. Conducting wires or leads **184** are connected to the transducer **182**. The proximal extremity of the housing **27** is connected to the distal extremity of flexible elongate tubular element **186** that is connected to a two-arm adapter **187**. The leads **184** extend through the tubular element **186** and are connected to sockets **188** provided in the arm **189** of the two-arm adapter **187**. The tubular element **186** is provided with a large lumen **191** that carries the drive cable **192**. The drive cable **192** is connected to a clutch member **193** of the type hereinbefore described which is adapted to be driven by motive means in the manner hereinbefore described. The clutch member **193** is provided with a flange **194** that cooperates with a flange **196** on the adapter **187**. The adapter **187** carries an O-ring **197** seated against another flange **198** forming a part of the adapter **187**. The O-ring **197** forms a liquid-tight seal with respect to the drive cable **192**. The clutch member **193** is thus held in a fixed longitudinal position while still permitting rotation of the same. The adapter **187** is provided with a tapered surface **199** adapted to fit into a motor drive means. Alternatively, the clutch member **193** can be adapted for manual rotation. Alternatively, the clutch member **193** can be adapted for manual rotation.

The drive cable **192** has its distal extremity secured to a rotating member **203** which is provided with an inclined reflective surface **204** which serves as a reflector for reflecting ultrasonic energy generated by the transducer **182** in a transverse direction relative to the longitudinal axis of the housing **27**. The angle of inclination of surface **204** may vary, typically between **450** and **850** provide for forward viewing as described above, depending on the sweep geometry desired. As illustrated, the torque cable **192** is unable to axially translate within the lumen **191**. Thus, the reflective surface **204** on rotating member **203** remains in a fixed longitudinal position relative to the housing **27** and cannot be advanced or retracted with respect to the ultrasonic transducer **182**. The reflective surface **204** can, of course, be axially translated within a blood vessel by movement of the catheter **180** as a whole. Also, the catheter **180** could be modified to permit axial translation of the rotating member **203** within the housing **27** (in a manner similar to the previous catheter embodiments), but generally this will be unnecessary.

The large lumen **191** in flexible elongate tubular element **186** is in communication with a side arm port **206** that forms a part of the two-arm adapter **187**. The housing **27** should be formed of a material that causes minimal attenuation of the ultrasonic signal which is transmitted and received by trans-

ducer **182**. Suitable materials include polyethylene, silicone rubber, polyvinyl chloride, polyurethanes, polyesters, natural rubbers, and the like. Alternatively, the housing may be formed of acoustically opaque materials if a cutout **207** (shown by the dashed lines) is provided through which the ultrasonic energy can pass.

The operation of the catheter apparatus **180** shown in FIG. **11** is very similar to that hereinbefore described with the exception that the cutting operation is omitted. With this catheter apparatus, the device can be inserted in the same manner as with respect to the other devices hereinbefore described. When the device is in the desired location, as for example, in the stenosis, the stenosis can be imaged ultrasonically by causing the rotating member **203** to be rotated with respect to the crystal **182** to cause ultrasonic energy to be directed upwardly and outwardly through the housing **181** to impinge upon the sidewalls of the vessel in which the catheter apparatus **180** is positioned. If a different longitudinal position is desired to be scanned, the entire catheter apparatus **181** can be shifted longitudinally in the vessel to the desired location. After the ultrasonic imaging has been completed, the catheter apparatus **180** can be removed and other operations performed if desired with other instruments.

It should be appreciated that if desired, another embodiment of catheter apparatus used solely for imaging can be provided by mounting the crystal at the end of the torque cable as illustrated in FIG. **8** so that the crystal is rotated about an axis parallel to the longitudinal axis of the housing.

From the foregoing, it can be seen that a two-dimensional ultrasound image is generated by rotating a crystal or a mirror that is located at the tip of the catheter. Good resolution is obtained because of the relatively high frequency, i.e., 5 to 50 megahertz, that is used. The image that is created is generally perpendicular to the longitudinal axis of the catheter, but may also be in a forward conical pattern, depending on the precise geometry of the transducer and/or mirror. The motor or manual drive means that is utilized for rotating the transducer is external to the patient. Rotation, of the transducer is made possible because of the electrical connection made with the brush contacts. The use of the balloon stabilizes the housing so that the cutting operation can be readily accomplished.

The apparatus and system of the present invention makes it possible to obtain images in very small vessels and has made it possible to accomplish the same by utilizing the precision driving of a very flexible cable. The catheter apparatus in addition to being capable of imaging is also capable of being steered by the flexible guidewire secured to the tip.

It is apparent from the foregoing that there has been provided a catheter apparatus, system, and method which is particularly useful for intravascular two-dimensional ultrasonography and which can be utilized with many different types of operations, as for example, in performing atherectomies.

What is claimed is:

1. A catheter for imaging within a human body, the catheter comprising:

an elongate tubular member adapted to be introduced into the human body, the tubular member including a proximal portion and a distal portion;

a braided shield disposed on the exterior of the tubular member, the braided shield formed of a magnetic material;

**13**

- an imaging device disposed within the distal portion of the tubular member, the imaging device adapted to emit energy waves for imaging within the human body; and an elongate flexible cable disposed within the tubular member and electrically coupled to the imaging device. <sup>5</sup>
2. The catheter of claim 1 further comprising a cover covering the braided shield.
3. The catheter of claim 2 wherein the cover is a heat shrinkable plastic.
4. The catheter of claim 2 wherein the braided shield is adopted to act as an electric shield. <sup>10</sup>

**14**

5. The catheter of claim 1 further comprising a lumen defined within the tubular member.
6. The catheter of claim 5 wherein the lumen is coupled to an infusion port for introducing a drug into the lumen.
7. The catheter of claim 1 further comprising an inflatable balloon disposed on the tubular member.
8. The catheter of claim 1 further comprising a cutting device.

\* \* \* \* \*

专利名称(译)	用于血管内二维超声检查的方法和设备		
公开(公告)号	<a href="#">US6764450</a>	公开(公告)日	2004-07-20
申请号	US10/438111	申请日	2003-05-13
[标]申请(专利权)人(译)	大笑PAUL 慕		
申请(专利权)人(译)	大笑PAUL G.		
当前申请(专利权)人(译)	SCIMED LIFE SYSTEMS INC.		
[标]发明人	YOCK PAUL G		
发明人	YOCK, PAUL G.		
IPC分类号	A61B8/12 A61B8/14 A61B6/00 A61M25/00 A61B8/00 A61B17/22 A61B19/00		
CPC分类号	A61B5/02007 A61B8/12 A61B8/4461 A61B17/22012 A61B17/320783 A61B8/445 A61B2017/00924 A61B2017/22038 A61B2017/22045 A61B2017/22052 A61B2017/22074 A61B2017/22078 A61B2019/5238 A61B2019/528 A61B2090/376 A61B2090/3784		
优先权	09/290533 1998-12-23 US		
其他公开文献	US20030199761A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

提供导管用于插入患者的血管中，用于对血管壁进行超声成像。导管包括管状元件和内部容纳的驱动电缆，用于围绕超声波发生装置的导管进行有效的周向扫描。管状元件和驱动电缆都具有足够的尺寸和柔韧性，以允许它们引入容器并随后通过容器前进到需要成像的容器壁的位置。

