



US 20090171209A1

(19) **United States**(12) **Patent Application Publication**
KIM et al.(10) **Pub. No.: US 2009/0171209 A1**(43) **Pub. Date: Jul. 2, 2009**(54) **ULTRASOUND DIAGNOSTIC DEVICE AND
METHOD OF DISPLAYING ULTRASOUND
IMAGES**(76) Inventors: **Sung Yun KIM**, Seoul (KR); **Yun
Jin Kim**, Seoul (KR)Correspondence Address:
JONES DAY
222 EAST 41ST ST
NEW YORK, NY 10017 (US)(21) Appl. No.: **12/343,352**(22) Filed: **Dec. 23, 2008**(30) **Foreign Application Priority Data**

Dec. 27, 2007 (KR) 10-2007-0138414

Publication Classification(51) **Int. Cl.**
A61B 8/00 (2006.01)(52) **U.S. Cl.** **600/443**(57) **ABSTRACT**

The present invention relates to an ultrasound diagnostic device. The ultrasound diagnostic device comprises: a storage unit configured to store a plurality of consecutive image frames based on ultrasound echoes reflected from a target object; an image processing unit configured to form preview images of the image frames, wherein the preview images are stored in the storage unit in association with the corresponding image frames; and a user input unit allowing a user to input a selection instruction for selecting one of the preview images, wherein the image processing unit is further configured to read out an image frame corresponding to the selected preview image from the storage unit in response to the selection instruction.




FIG. 1




FIG. 2





FIG. 3



ULTRASOUND DIAGNOSTIC DEVICE AND METHOD OF DISPLAYING ULTRASOUND IMAGES

[0001] The present application claims priority from Korean Patent Application No. 10-2007-0138414 filed on Dec. 27, 2007, the entire subject matter of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] 1. Technical Field

[0003] The present invention generally relates to ultrasound diagnostic devices, and more particularly to an ultrasound diagnostic device and a method of displaying ultrasound images.

[0004] 2. Background Art

[0005] An ultrasound diagnostic device has become an important and popular diagnostic tool due to its non-invasive and non-destructive nature. Modern high-performance ultrasound imaging diagnostic devices and techniques are commonly used to produce two- or three-dimensional images of internal features of patients. The ultrasound diagnostic device may provide the ultrasound images in various image display modes. The image display modes may include a real-time display mode, a freeze mode and a cine replay mode.

[0006] When in the real-time display mode, the ultrasound diagnostic device may transmit and receive ultrasound signals to obtain ultrasound image data. The ultrasound diagnostic device may display an ultrasound image of a target object in real time based on the ultrasound image data. In such a case, while displaying the ultrasound image, the ultrasound image data, which include a plurality of image frames, may be also stored in a storage unit such as a cine memory. When the image frames are stored, indices may be assigned thereto. The indices may be assigned according to the acquisition time of the image frames.

[0007] If the freeze mode is set, then the conventional ultrasound diagnostic device may stop transmitting the ultrasound signals to the target object and provide the indices of the image frames stored in the storage unit. If a user selects one of the indices by using an input device such as a mouse, a keyboard or a track ball, then an image frame corresponding to the selected index may be read out from the storage unit and then displayed on a display unit. In such a case, since the user has to select the indices one by one to display a desirable image frame, the user may feel inconvenient when searching for the desirable image frame.

[0008] If the cine replay mode is set in the conventional ultrasound diagnostic device, then the image frames stored in the storage unit may be read out in the order (or in the inverse order) of the acquisition times. A cine image may be replayed based on the read-out image frames. Also, the ultrasound diagnostic device may provide indices on a screen of the display unit in the cine replay mode. The user may select an index corresponding to a start image frame of the cine image to be replayed and an index corresponding to an end image frame of the cine image to be replayed. The conventional ultrasound diagnostic device merely sets a replay period by selecting indices corresponding to the start image frame and

the end image frame of the cine image. Thus, the cine image for only one replay period may be displayed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1 is a block diagram showing an embodiment of an ultrasound diagnostic device.

[0010] FIG. 2 is an exemplary diagram showing an example of displaying a plurality of preview images and a selected image frame.

[0011] FIG. 3 is an exemplary diagram showing an example of displaying a plurality of preview images with bookmarks set and a selected cine image.

DETAILED DESCRIPTION OF THE INVENTION

[0012] FIG. 1 is a block diagram showing an embodiment of an ultrasound diagnostic device. Referring to FIG. 1, the ultrasound diagnostic device 100 may include a probe 110 for transmitting and receiving ultrasound signals. The probe 110 may include at least one transducer element configured to generate ultrasound signals in response to transmit pulse signals produced from transmit pulsers (not shown). The ultrasound signals may be transmitted to a target object. The probe 110 may convert ultrasound echoes reflected from the target object into electrical receive signals.

[0013] The probe 110 may be coupled to a beam forming unit 120, which may apply delays to the transmit pulse signals to form a transmit pattern such that the ultrasound signals generated from the elements are focused on scan lines. Also, the beam forming unit 120 may be configured to apply delays to the receive signals in consideration of distances between the elements and focal points and sum the delayed receive signals, thereby forming a receive-focused beam.

[0014] The ultrasound diagnostic device 100 may further include a signal processing unit 130 configured to perform signal processing upon the receive-focused beam to thereby form cine data. The cine data may be constructed with a plurality of frames. The ultrasound diagnostic device 100 may further include a storage unit 140. The cine data may be stored in the storage unit 140.

[0015] The ultrasound diagnostic device 100 may include a user input unit 150 allowing the user to input selection instructions for selecting one of image display modes of the ultrasound diagnostic device 100. The user input unit 150 may be an arbitrary input device such as a mouse, a keyboard, a trackball and the like. The image display modes may include a real-time display mode, a freeze mode, a cine replay mode and the like. Also, the user input unit 150 may further allow the user to input a bookmark setting instruction for setting bookmarks to numerous frames of the cine data stored in the storage unit 140.

[0016] The ultrasound diagnostic device 100 may further include an image processing unit 160 configured to perform image processing upon the cine data to thereby form ultrasound image signals. The image processing unit 160 may scan convert the cine data and render the scan-converted data to thereby form the ultrasound image signals. The image processing unit 160 may further form preview images corresponding to the respective frames of the cine data. The preview images may be formed in smaller sizes than the frames. Further, the preview images may be linked to the corresponding frames and stored in the storage unit 140.

[0017] In one embodiment, the image processing unit 160 may be configured to set a mark to a frame whose data value

steeply varies among the frames. For example, the image processing unit 160 may compute mean deviation of each frame and set the mark to a frame whose mean deviation varies over a threshold value. Also, the image processing unit 160 may be configured to set a mark to a frame obtained when a view mode is changed. In such a case, the image processing unit 160 may form preview images only for the frames with the marks set. The frames may be stored in the storage unit 140 in association with the preview images.

[0018] In one embodiment, the image processing unit 160 may set bookmarks in response to the bookmark setting instruction inputted through the user input unit 150. The bookmarks may be set to first and last frames of a cine image to be replayed. A plurality of replay periods may be set through a plurality of bookmarks. Bookmark information may include information of frames to be replayed. The bookmark information may be indicated at the preview images displayed on the display unit 170. If the bookmark setting instruction is not inputted from the user input unit 150, then the bookmarks may be set at a constant interval. The display unit 170 may receive the ultrasound image signals from the image processing unit 160 to thereby display an ultrasound image of the target object.

[0019] Hereinafter, an operation of the ultrasound diagnostic device 100 will be described below for the real-time display mode, the freeze mode and the cine replay mode. If the real-time display mode is set, then the image processing unit 160 may directly receive cine data from the signal processing unit 130 and perform image processing thereupon to thereby form the ultrasound image signals. The display unit 170 may display the ultrasound image of the target object in real time based on the ultrasound image signals.

[0020] If the freeze mode is set from the real-time display mode, then the image processing unit 160 may stop receiving the cine data from the signal processing unit 130 and read out preview images from the storage unit 140. The read-out preview images may be transmitted to the display unit 170 so that the preview images 210 may be displayed at a predetermined position on a screen of the display unit 170, as shown in FIG. 2. Also, the image processing unit may read out preview images, on which the marks are set based on the instructions inputted from the user input unit 150 for display on the display unit 170.

[0021] If a selection instruction for selecting one of the preview images displayed on the display unit 170 is inputted from the user input unit 150, then the image processing unit 160 may read out frame data corresponding to the selected preview image and perform image processing upon the read-out frame data to thereby form a frame image signal. The display unit 170 may display a frame image 220 based on the frame image signal, as shown in FIG. 2. In such a case, the frame image 220 may be displayed together with the preview images 210. Since the user can easily select a desirable frame image through the preview images 210, an operation time of the ultrasound diagnostic device may be reduced.

[0022] Further, if the cine replay mode is set in response to the instruction inputted from the user input unit 150, then the image processing unit 160 may read out preview images 310, on which the bookmarks are set, among the preview images stored in the storage unit 140. The read-out preview images may be displayed on the display unit 170, as shown in FIG. 3. If the user selects one of the preview images displayed on the screen of the display unit 170, then the image processing unit 160 may read out frame data based on frame information

included in the bookmark information. The image processing unit 160 may be configured to perform image processing upon the frame data to thereby form a cine image. The cine image 320 may be displayed on the display unit 170, as shown in FIG. 3.

[0023] It is described that the preview images may be formed for the frames obtained in the real-time display mode and stored together with the cine data in the storage unit 140 in one embodiment. However, it should be noted herein that the preview images may be formed based on frames constructing the cine data, which are stored in the storage unit 140, when the freeze mode or the cine replay mode is set.

[0024] As mentioned above, since the preview images for the frames stored in the cine memory are provided, the user may easily select a desirable frame. Thus, an operation time of the ultrasound diagnostic device may be reduced. Also, since the plurality of bookmarks may be set to the frames, a plurality of cine images may be replayed.

[0025] In accordance with one aspect of the present invention, there is provided an ultrasound diagnostic device, comprising: a storage unit configured to store a plurality of consecutive image frames based on ultrasound echoes reflected from a target object; an image processing unit configured to form preview images of the image frames, wherein the preview images are stored in the storage unit in association with the corresponding image frames; and a user input unit allowing a user to input a selection instruction for selecting one of the preview images, wherein the image processing unit is further configured to read out an image frame corresponding to the selected preview image from the storage unit in response to the selection instruction.

[0026] In accordance with another aspect of the present invention, there is provided a method of displaying an ultrasound image, comprising: a) storing a plurality of consecutive image frames based on ultrasound echoes reflected from a target object; b) forming preview images of the image frames; c) receiving a selection instruction for selecting one of the preview images; and d) reading out an image frame corresponding to the selected preview image in response to the selection instruction.

[0027] Any reference in this specification to “one embodiment,” “an embodiment,” “example embodiment,” etc. means that a particular feature, structure or characteristic described in connection with the embodiment is included in at least one embodiment of the present invention. The appearances of such phrases in various places in the specification are not necessarily all referring to the same embodiment. Further, when a particular feature, structure or characteristic is described in connection with any embodiment, it is submitted that it is within the purview of one skilled in the art to effect such feature, structure or characteristic in connection with other ones of the embodiments.

[0028] Although embodiments have been described with reference to a number of illustrative embodiments thereof, it should be understood that numerous other modifications and embodiments can be devised by those skilled in the art that will fall within the spirit and scope of the principles of this disclosure. More particularly, numerous variations and modifications are possible in the component parts and/or arrangements of the subject combination arrangement within the scope of the disclosure, the drawings and the appended claims. In addition to variations and modifications in the component parts and/or arrangements, alternative uses will also be apparent to those skilled in the art.

What is claimed is:

1. An ultrasound diagnostic device, comprising:
a storage unit for storing a plurality of consecutive image frames based on ultrasound echoes reflected from a target object;
an image processing unit for forming preview images of the image frames, wherein the preview images are stored in the storage unit in association with the corresponding image frames; and
a user input unit allowing a user to input a selection instruction for selecting one of the preview images,
wherein the image processing unit is further configured to read out an image frame corresponding to the selected preview image from the storage unit in response to the selection instruction.
2. The ultrasound diagnostic device of claim 1, wherein the image processing unit is configured to set marks to image frames whose specific value is over a threshold value among the consecutive image frames, the image processing unit being further configured to form preview images only for the image frames with the marks set.
3. The ultrasound diagnostic device of claim 2, wherein the specific value is a mean deviation of each image frame.
4. The ultrasound diagnostic device of claim 1, wherein the user input unit further allows the user to input a bookmark setting instruction for setting a bookmark indicating image frame information of image frames to be replayed at one or more image frames, and wherein the storage unit stores bookmark information containing the image frame information.
5. The ultrasound diagnostic device of claim 4, wherein the image processing unit is configured to set bookmarks at a constant interval to the consecutive image frames.
6. The ultrasound diagnostic device of claim 5, wherein the image processing unit is configured to form preview images with the image frame information indicated based on the image frames with the bookmarks set and the bookmark information.

7. The ultrasound diagnostic device of claim 5, wherein the image processing unit is configured to set a plurality of bookmarks to replay by a plurality of periods.

8. A method of displaying an ultrasound image, comprising:

- a) storing a plurality of consecutive image frames based on ultrasound echoes reflected from a target object;
- b) forming preview images of the image frames;
- c) receiving a selection instruction for selecting one of the preview images; and
- d) reading out an image frame corresponding to the selected preview image in response to the selection instruction.

9. The method of claim 8, wherein the step a) includes setting marks to frames whose specific value is over a threshold value among the consecutive image frames, and wherein the step b) includes forming preview images for only the image frames with the marks set.

10. The method of claim 9, wherein the specific value is a mean deviation of each image frame.

11. The method of claim 8, wherein the step a) further includes receiving a bookmark setting instruction for setting a bookmark indicating image frame information upon image frames to be replayed at one or more frames, and storing bookmark information containing the image frame information.

12. The method of claim 11, wherein the step b) includes forming preview images with the frame information indicated based on the image frames with the bookmarks set and the bookmark information.

13. The method of claim 12, further comprising a selection instruction for selecting one of preview images indicating bookmark information and displaying image frames based on image frame information included in the bookmark information of the selected preview image.

* * * * *

专利名称(译)	超声诊断装置和显示超声图像的方法		
公开(公告)号	US20090171209A1	公开(公告)日	2009-07-02
申请号	US12/343352	申请日	2008-12-23
[标]申请(专利权)人(译)	KIM崇运 金运金		
申请(专利权)人(译)	KIM崇运 金运金		
当前申请(专利权)人(译)	KIM崇运 金运金		
[标]发明人	KIM SUNG YUN KIM YUN JIN		
发明人	KIM, SUNG YUN KIM, YUN JIN		
IPC分类号	A61B8/00		
CPC分类号	G06F19/3406 G06F19/321 G16H30/20 G16H40/63 A61B8/00		
优先权	1020070138414 2007-12-27 KR		
其他公开文献	US9223931		
外部链接	Espacenet USPTO		

摘要(译)

超声波诊断装置技术领域超声诊断设备包括：存储单元，被配置为基于从目标对象反射的超声回波来存储多个连续图像帧；图像处理单元，被配置为形成图像帧的预览图像，其中预览图像与对应的图像帧相关联地存储在存储单元中；用户输入单元，允许用户输入用于选择预览图像之一的选择指令，其中，图像处理单元还用于响应于选择，从存储单元中读出与所选择的预览图像对应的图像帧。指令。

