



US 20140228679A1


(19) **United States**(12) **Patent Application Publication**
Bonutti(10) **Pub. No.: US 2014/0228679 A1**(43) **Pub. Date: Aug. 14, 2014**(54) **METHODS FOR POSITIONING AN
ULTRASONIC CATHETER****Publication Classification**(51) **Int. Cl.***A61B 8/00* (2006.01)
A61B 8/12 (2006.01)
A61M 25/01 (2006.01)
A61B 8/08 (2006.01)(52) **U.S. Cl.**CPC *A61B 8/4263* (2013.01); *A61B 8/0841*
(2013.01); *A61B 8/12* (2013.01); *A61M*
25/0108 (2013.01); *A61M 25/0102* (2013.01);
A61B 8/445 (2013.01)
USPC 600/424(71) Applicant: **P Tech, LLC**, Effingham, IL (US)(72) Inventor: **Peter M. Bonutti**, Effingham, IL (US)(73) Assignee: **P Tech, LLC**, Effingham, IL (US)(21) Appl. No.: **14/256,629**(22) Filed: **Apr. 18, 2014****Related U.S. Application Data**


(63) Continuation of application No. 13/048,163, filed on Mar. 15, 2011, which is a continuation of application No. 12/431,835, filed on Apr. 29, 2009, now abandoned, which is a continuation of application No. 10/990,870, filed on Nov. 17, 2004, now abandoned.

(57)

ABSTRACT

An emitter may be disposed in a patient. Output from the emitter may be detected by a detector connected with the guide rod and by a detector connected with the tracheal tube. Alternatively, a detector may detect the output from an emitter connected with the guide rod and by an emitter connected with the tracheal tube. Emitter units may be ultrasonic transducers and emit ultrasonic energy. The detector may respond to ultrasonic energy.








Fig.2




Fig.3




Fig.4













Fig.8






























METHODS FOR POSITIONING AN ULTRASONIC CATHETER

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application is a continuation of U.S. patent application Ser. No. 12/431,835, filed Apr. 29, 2009, which in turn is a continuation of U.S. patent application Ser. No. 10/990,870, filed Nov. 17, 2004, which in turn is a continuation of U.S. patent application Ser. No. 09/728,553, filed on Dec. 2, 2000, now U.S. Pat. No. 6,820,614, the entire contents of which are incorporated by reference.

FIELD OF THE INVENTION

[0002] The present invention relates to a new and improved method and apparatus for use in tracheal intubation or other medical procedures

BACKGROUND OF THE INVENTION

[0003] Tracheal intubation has previously been utilized to provide an unobstructed air passage to a patient's lungs. Tracheal intubation is frequently done under emergency circumstances which are not optimal. It has previously been recognized that it is necessary to have a tracheal tube bend around the patient's epiglottis and move from the patient's pharynx into the larynx at the upper end of the patient's trachea rather than into the patient's esophagus. However, it is difficult for a person inserting the tracheal tube to know where the leading end portion of the tracheal tube is located relative to the patient's larynx.

[0004] Various methods and devices for assisting in tracheal intubation are disclosed in U.S. Pat. Nos. 4,832,020; 4,865,586; 4,913,139; 5,353,787; 5,235,970; 5,560,351; and 5,694,929.

SUMMARY OF THE INVENTION

[0005] An improved method and apparatus for use in tracheal intubation or other medical procedure may include a positioning apparatus. When the positioning apparatus is used for tracheal intubation, the positioning apparatus is located relative to a patient's trachea by engaging a portion of the patient's body, such as the Adam's apple. A flexible guide rod may be moved relative to the positioning apparatus until a leading end portion of the guide rod has moved into the patient's trachea. A tracheal tube is slid along the guide rod into the patient's trachea.

[0006] During movement of the guide rod relative to the positioning apparatus, the guide rod may be moved through either a tubular guide member or a tracheal tube which extends through the patient's mouth into the patient's pharynx. Before beginning to move the guide rod, the distance which the guide rod is to be moved may advantageously be determined. This may be done as a function of spacing between locations on the positioning apparatus. If desired, indicia may be provided on the positioning apparatus and cooperating indicia may be provided on the guide rod.

[0007] A magnet may be utilized to attract a leading end portion of the guide rod. The magnet is disposed outside of the patient's body and may be positioned adjacent to an anterior side of the trachea. Magnetic attraction between the magnet and the leading end portion of the guide rod deflects the guide rod. This steers the leading end portion of the guide rod into the entrance to the patient's trachea. A magnet may be used to

steer a member relative to a patient's body tissue during performance of operations other than tracheal intubation.

[0008] In order to locate the guide rod and/or tracheal tube relative to the patient's trachea, an image of body tissue adjacent to the leading end portion of the guide rod and/or tracheal tube may be transmitted to a location outside of the patient's body. Movement of the guide rod and/or tracheal tube into the patient's trachea is interrupted when the image transmitted from the leading end portion of the guide rod or tracheal tube indicates that the leading end portion of the guide rod or tracheal tube has been moved to a desired position relative to the patient's trachea.

[0009] It is believed that transmission of an image of body tissue adjacent to the leading end portion of the tracheal tube may advantageously be performed when the tracheal tube is utilized without benefit of the positioning apparatus. However, the transmission of an image of body tissue adjacent to the leading end portion of the tracheal tube may be performed when the positioning apparatus is used in association with the tracheal tube. Positioning of the guide rod relative to the patient's trachea may also be facilitated by the transmitting of images of body tissue adjacent to a leading end portion of the guide rod.

[0010] Detectors and emitters may be utilized to detect the position of the leading end portion of the guide rod and/or the tracheal tube relative to the patient's trachea. When this is done, an emitter, such as a magnet or a light source, may be connected with a leading end portion of the guide rod and/or the tracheal tube. One or more detectors may be provided on the outside of the patient's neck to detect the output from the emitter when the guide rod and/or the tracheal tube are in a desired position relative to the patient's trachea. Alternatively, a detector may be connected with the leading end portion of a guide rod and/or tracheal tube and one or more emitters positioned relative to the outside of the patient's neck. The detector would provide an output indicating when the guide rod and/or tracheal tube is moved to a desired position relative to the patient's trachea.

[0011] During movement of the guide rod and/or tracheal tube along the patient's respiratory system and into the patient's trachea, force may be applied against the leading end portion of the guide rod and/or tracheal tube to steer the leading end portion of the guide rod and/or tracheal tube. The application of force against the leading end portion of the guide rod and/or tracheal tube may be accomplished by expanding an expandable element connected with the guide rod and/or the tracheal tube.

[0012] It should be understood that any one of the features of the present invention may be used separately or in combination with other features of the invention. It's believed that various combinations of the features, other than those disclosed herein, may advantageously be utilized and will be apparent to those skilled in the art from the description contained herein. In addition, it should be understood that features of the present invention may be used for purposes other than tracheal intubation.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] The foregoing and other features of the present invention will become more apparent upon a consideration of the following description taken in connection with the accompanying drawings wherein:

[0014] FIG. 1 is a fragmentary schematic illustration depicting the use of a positioning apparatus to position a guide rod relative to the mouth and trachea of a patient;

[0015] FIG. 2 is a fragmentary schematic illustration depicting the manner in which a tracheal tube is moved along the guide rod of FIG. 1 into the trachea of the patient;

[0016] FIG. 3 is a fragmentary schematic illustration, similar to FIG. 1, illustrating the manner in which a laryngoscope may be combined with the positioning apparatus;

[0017] FIG. 4 is a fragmentary schematic illustration depicting the use of another embodiment of the positioning apparatus to position a guide rod relative to the mouth and trachea of a patient;

[0018] FIG. 5 is an enlarged schematic fragmentary sectional view of a portion of the apparatus of FIG. 4 and illustrating the relationship between a guide rod and a guide tube;

[0019] FIG. 6 is an enlarged schematic fragmentary sectional view of a portion of the apparatus of FIG. 4 and illustrating the relationship between the guide tube, guide rod, and a guide member in the positioning apparatus;

[0020] FIG. 7 is a schematic fragmentary sectional view illustrating a manner in which the positioning apparatus engages a patient's Adam's apple and the manner in which a magnet is moved along the outside of the neck of the patient;

[0021] FIG. 8 (on sheet 3 of the drawings) is an enlarged fragmentary schematic illustration of indicia on a portion of the guide rod of FIG. 4;

[0022] FIG. 9 is a fragmentary schematic illustration of the guide rod with the positioning apparatus and guide tube of FIG. 4 removed after positioning of the guide rod relative to the patient's trachea;

[0023] FIG. 10 is a fragmentary schematic illustration, generally similar to FIG. 9, illustrating the manner in which a tracheal tube is moved along the guide rod into the patient's trachea;

[0024] FIG. 11 is a fragmentary schematic illustration, generally similar to FIG. 4, illustrating an embodiment of the apparatus in which the tracheal tube is used to guide movement of the guide rod;

[0025] FIG. 12 is a fragmentary schematic illustration, similar to FIG. 1, illustrating an embodiment of the positioning apparatus which transmits an image of body tissue adjacent to a leading end portion of the guide rod;

[0026] FIG. 13 is a fragmentary schematic illustration, generally similar to FIGS. 1 and 12, of an embodiment of the invention in which a detector on a leading end portion of a guide rod detects emitters disposed on the neck of the patient;

[0027] FIG. 14 is a fragmentary schematic illustration, depicting the manner in which a plurality of emitters are arranged in an array around the Adam's apple of the patient of FIG. 13;

[0028] FIG. 15 is a fragmentary schematic illustration, generally similar to FIG. 13, of an embodiment of the invention in which detectors on the neck of the patient detect an emitter on a leading end portion of the guide rod;

[0029] FIG. 16 is a fragmentary schematic illustration, generally similar to FIG. 14, illustrating a manner in which a plurality of detectors are positioned in an array around the Adam's apple on the neck of the patient of FIG. 15;

[0030] FIG. 17 is an enlarged schematic fragmentary sectional view of the leading end portion of a guide rod on which a detector and a plurality of expandable steering elements are disposed;

[0031] FIG. 18 is a plan view, taken generally along the line 18-18 of FIG. 17, further illustrating the relationship of the expandable steering elements to the leading end portion of the guide rod;

[0032] FIG. 19 is a schematic fragmentary sectional view of a leading end portion of a guide rod on which an emitter and a plurality of expandable steering elements are disposed;

[0033] FIG. 20 is an enlarged schematic fragmentary sectional view of a leading end portion of a tracheal tube and illustrating the manner in which a light source and light conductor are disposed on the tracheal tube to facilitate visualization of tissue disposed adjacent to the leading end portion of the tracheal tube;

[0034] FIG. 21 is an enlarged schematic fragmentary sectional view of a leading end portion of a tracheal tube and illustrating a plurality of detectors which are disposed on the leading end portion of tracheal tube;

[0035] FIG. 22 is an enlarged schematic fragmentary sectional view of a leading end portion of a tracheal tube illustrating the manner in which a plurality of emitters and expandable steering elements are mounted on the leading end portion of the tracheal tube;

[0036] FIG. 23 is a schematic illustration depicting the positioning apparatus of FIGS. 1 and 2;

[0037] FIG. 24 is a schematic illustration, generally similar to FIG. 23, illustrating another embodiment of the apparatus of FIGS. 1 and 2;

[0038] FIG. 25 is a fragmentary schematic illustration of a portion of a positioning apparatus having another embodiment of the positioning section;

[0039] FIG. 26 is a fragmentary schematic illustration depicting the relationship between the positioning section of FIG. 25 and a patient's Adam's apple during use of the positioning apparatus;

[0040] FIG. 27 is a fragmentary schematic illustration of a portion of a positioning apparatus having another embodiment of the positioning section; and

[0041] FIG. 28 is a fragmentary schematic illustration depicting the relationship between the positioning section of FIG. 27 and a patient's Adam's apple during use of the positioning apparatus.

DETAILED DESCRIPTION OF THE INVENTION

General Description

[0042] The present invention relates to a new and improved method and apparatus for use in tracheal intubation or other medical procedures. A portion of a patient's head 10 and respiratory system 11 has been illustrated schematically in FIG. 1. The schematicized illustration of the patient's head 10 and respiratory system 11 includes a mouth 12 which is connected with a throat 14 in a neck 16 of the patient.

[0043] A pharynx extends downward from a nasal cavity in the head 10 of the patient. The pharynx is connected with an esophagus 26 and a trachea 28 in the neck 16 of the patient. The esophagus 26 extends from the pharynx to the stomach of the patient. The trachea 28 extends from the pharynx to the bronchial tubes and lungs of the patient.

[0044] The trachea 28 (FIG. 1) has an upper end portion 30 which is referred to as the larynx. Vocal cords or folds 32 have been indicated schematically in FIG. 1 and are disposed in the larynx 30. The vocal cords 32 are adjacent to the Adam's apple 34 of the patient. The Adam's apple 34 is a laryngeal prominence formed by lamina of cartilage in the larynx.

[0045] Opening of a passage for air from the patient's mouth to the patient's lungs may require insertion of a flexible tracheal tube 38 (FIG. 2). Movement of the flexible tracheal tube 38 from the patient's mouth 12 into the pharynx of the patient is relatively easily accomplished. However, directing the tracheal tube 38 into the patient's trachea 28 may present difficulties. This is because the tracheal tube must extend past the epiglottis into the larynx 30 at the upper end of the trachea 28. The tracheal tube 38 must not enter the esophagus 26 rather than the trachea 28. During movement of the leading end of the tracheal tube 38 through the larynx 30, it is desirable to have the tracheal tube near the central portion of the laryngeal cavity in order to minimize irritation of the vocal folds or cords 32 by the tracheal tube.

[0046] In accordance with one of the features of the present invention, a flexible guide wire or rod 50 (FIG. 1) is utilized to guide movement of the flexible tracheal tube 38 (FIG. 2) into the trachea 28. The flexible guide rod 50 has a soft generally spherical leading end portion 52. The leading end portion 52 of the guide rod 50 is formed of a resiliently compressible material which is readily deflected by engagement with the vocal cords or folds 32 and by engagement with the surface of the trachea 28. If desired, the leading end portion 52 of the guide rod 50 may be coated with a suitable lubricant to facilitate movement of the leading end portion between the vocal cords with minimum of irritation.

[0047] In accordance with another of the features of the invention, the guide wire 50 is initially positioned relative to the patient's trachea 28 with a positioning apparatus 56 (FIG. 1). The positioning apparatus 56 engages the patient's Adam's apple 34 to locate the positioning apparatus relative to the trachea 28 of the patient. In addition, the positioning apparatus 56 provides a measurement which is a function of the distance between the Adam's apple 34 and the mouth 12 of the patient. This measurement is utilized to determine the distance through which the guide rod 50 is to be moved relative to the positioning apparatus 56 as the guide rod is inserted into the trachea 28.

Positioning Apparatus

[0048] The positioning apparatus 56 has been and will be described herein in association with tracheal intubation. However, it is contemplated that the positioning apparatus 56 will be used in association with many other medical procedures where accurate positioning of an object relative to body tissue is desired. The positioning apparatus may be used in association with endoscopic, arthroscopic or fiber optic surgical procedures. It is believed that the positioning apparatus 56 will be used in conjunction with medical procedures where it is necessary to position an object at a location in a patient's body where there is only limited access.

[0049] The positioning apparatus 56 positions the guide rod 50 relative to the patient's trachea 28 during insertion of the guide rod into the patient's trachea. In addition, the positioning apparatus 56 provides an indication of the distance which the guide rod is to be moved into the patient's trachea. By using the positioning apparatus 56, a person moving the guide rod 50 into the patient's trachea 28 can know where the leading end portion 52 of the guide rod is located relative to the trachea.

[0050] The flexible guide rod 50 may be formed of either polymeric material or metal. The illustrated polymeric guide rod 50 has a relatively small diameter and is readily deflected. The guide rod 50 has a circular cross sectional configuration.

[0051] The guide rod 50 is axially movable relative to the positioning apparatus 56 under the influence of force manually applied to the portion of the guide rod disposed to the left (as viewed in FIG. 1) of the positioning apparatus 56. This force results in axial movement of the guide rod 50 relative to the positioning apparatus 56. In addition, the leading end 52 of the guide rod 50 may deflect body tissue to clear a passage for the guide rod 50.

[0052] As the guide rod 50 is moved axially relative to the positioning apparatus 56, the guide rod may be resiliently deflected by engagement with the body tissue of the patient. As the guide rod 50 is manually pushed toward the right (as viewed in FIG. 1), the leading end 52 of the guide rod moves toward the larynx 30.

[0053] The positioning apparatus 56 is used to locate the leading end portion 52 of the guide rod 50 as the guide rod moves toward the larynx 30. The positioning apparatus 56 includes a base section 78 and an arcuate upper section 80 (FIG. 1). The base section 78 engages the patient's Adam's apple 34 to locate the positioning apparatus 56 relative to the patient's trachea 28. The upper section 80 of the positioning apparatus 56 guides movement of the guide rod 50 during insertion of the guide rod into the patient's trachea 28.

[0054] The base section 78 and upper section 80 of the positioning apparatus 56 cooperate to provide a measurement of the distance between the patient's mouth 12 and the patient's Adam's apple 34. This distance will vary from patient to patient depending upon the size of the patient, the specific configuration of the head 10 of the patient, and other factors. The distance which the guide rod 50 must be moved axially into the patient's larynx 30 will vary as a function of variations in the distance between the patient's mouth 12 and the patient's Adam's apple 34. This is because the patient's Adam's apple 34 is located adjacent to the entrance to the trachea 28.

[0055] The positioning apparatus 56 can be used to position many different objects at desired locations in a patient's body. For example, the guide rod 50 or a similar member could be inserted into a patient's stomach or colon. The base section 78 of the positioning apparatus would be positioned in engagement with an exterior surface on the patient's body at a location where the leading end portion 52 of the guide rod 50 is to be moved. The upper section 80 of the positioning apparatus 56 would cooperate with the base section 78 and guide rod 50 to provide a clear indication of the location of the leading end portion 52 of the guide rod 50 relative to the patient's body tissue, for example, the patient's stomach or colon.

[0056] The base section 78 (FIG. 1) of the positioning apparatus 56 includes a tubular cylindrical body section 86. The base section 78 also includes a positioning section 96 which engages the patient's Adam's apple 34 and is supported by the body section 86. The positioning section 96 engages the patient's Adam's apple 34. Although the illustrated positioning section 96 (FIG. 1) engages only a single location on the patient's neck 16, the positioning section could be constructed so as to engage a plurality of locations on the patient's neck. For example, it may be preferred to use a positioning section 96 having two positioning fingers disposed on laterally opposite sides of the Adam's apple 34.

[0057] It is contemplated that the positioning section 96 could have many different constructions. It is believed that it may be particularly advantageous to utilize a positioning section 96 having the construction illustrated in FIGS. 25 and

26 herein. Alternatively, the positioning section 96 may have the construction illustrated in FIGS. 27 and 28 or FIGS. 4 and 7 herein if desired.

[0058] Force may be manually applied against the positioning section 96 to straighten the trachea 28 of the patient. Thus, the patient's trachea 28 may have a slight anterior bend when the patient's head 10 is in the position illustrated in FIG. 1. This slight bend can be eliminated by the manual application of minimal force to the positioning section 96. This force presses the positioning section 96 against the patient's neck.

[0059] Although it is preferred to use the patient's Adam's apple 34 to locate the positioning apparatus 56 relative to the patient's trachea 28, a different portion of the patient's body could be used to locate the positioning apparatus relative to the patient's trachea. For example, the patient's shoulders could be used. Alternatively, bones in the patient's neck 16 could be used to locate the positioning apparatus 56 relative to the patient's trachea 28. However, it is believed that it will be preferred to use the patient's Adam's apple 34 to locate the positioning apparatus 56 due to the close proximity of the patient's Adam's apple to the upper end of the patient's trachea 28.

[0060] The arcuate upper section 80 of the positioning apparatus 56 includes an arcuate member 108 which is slidably connected with the body section 86 at a connection 110. The connection 110 is movable axially along the cylindrical body section 86. The body section 86 is movable transversely to the arcuate member 108, in the manner indicated by the arrows 112 in FIG. 1. Suitable indicia, indicated by lines in FIG. 1, may be provided on the arcuate member 108 to indicate the position of the connection 110 relative to the arcuate member.

[0061] The connection 110 may include a plurality of set screws (not shown) having manually engagable flanges or arms. One of the set screws may be tightened to prevent movement between the body section 86 and the connection 110. Another set screw may be tightened to prevent movement between the arcuate member 108 and the connection 110.

[0062] When the connection 110 has been moved to a desired location along the body section 86, a set screw in the connection is tightened to hold the arcuate member 108 against axial movement along to the cylindrical body section 86. The arcuate member 108 is then moved transversely to the body section 86, that is, in the direction of the arrows 112, to position a guide section 114 in alignment with the patient's mouth 12 and trachea 28. When the tubular guide section 114 has been aligned with the patient's trachea 28, another set screw in the connection 110 is tightened to hold the arcuate member 108 against transverse movement relative to the body section 86.

[0063] The guide rod 50 extends through a cylindrical passage in the guide section 114. Therefore, transverse movement of the arcuate member 108 relative to the body section 86, that is, in the direction indicated by the arrows 112 positions the guide rod 50 in alignment with the patient's mouth 12. The guide rod 50 is axially movable relative to the guide section 114 into the patient's mouth 12 and trachea 28.

[0064] In the illustrated embodiment of the invention, the distance between the patient's Adam's apple 34 and the arcuate member 108 is indicated by indicia 124 (FIG. 1). The indicia 124 is disposed on the cylindrical body section 86 of the positioning apparatus 56. The position of the connection 110 relative to the indicia 124 indicates the distance which the

arcuate member is spaced from the positioning section 96. The distance which the connection 110 is spaced from the positioning section 96 is a function of the distance between the patient's Adam's apple 34 and the entrance to the patient's mouth 12.

[0065] In the illustrated embodiment of the invention, the indicia 124 is formed by a plurality of colored bands 130. Each of the bands 130 has a different color from the other bands. Each of the bands 130 has the same axial extent. However, the bands could have different axial extents if desired. Rather than using the colored bands 130 as the indicia 124, numerical indicia could be provided. However, it is believed that it may be easier to read the different colored bands 130 than to read numerical indicia.

[0066] Colored bands 142 are provided on the guide rod 50. The colored bands 142 have different colors which correspond to the colors of the bands 130 on the cylindrical body section 86 of the positioning apparatus 56. The colored bands 142 on the guide rod 50 are spaced from the end portion 52 of the guide rod by the same distance which correspondingly colored bands 130 on the body section 86 are spaced from the center of the Adam's apple 34.

[0067] The bands 142 on the guide rod 50 cooperate with an end portion 156 (FIG. 1) of the guide section 114 to indicate when the leading end portion 52 of the guide rod is in a desired position relative to the patient's trachea 28. Thus, assuming that a red colored band 130 on the cylindrical body section 86 of the positioning apparatus 56 is aligned with the connection 110, the red band on the guide rod 50 will be moved to a position in which it is adjacent to the guide section 114. When the guide rod 50 has been moved to a position in which the red band is adjacent to the guide section 114, the leading end portion 52 of the guide rod will have moved through a desired distance into the patient's trachea 28 and will be aligned with the patient's Adam's apple 34.

[0068] When the positioning apparatus 56 is to be associated with a different portion of a patient's body, the indicia 124 would be revised to correspond to the distance which the guide rod 50 is to be moved relative to the arcuate member 108 to bring the leading end portion 52 of the guide rod into alignment with the positioning section 96 or to a position spaced a desired distance from the positioning section. It is contemplated that the positioning apparatus 56 maybe used during endoscopic, arthroscopic, or fiber optic surgery at many locations in a patient's body, for example during surgery on joints in the patient's body.

[0069] The positioning apparatus 56 may be used in association with the delivery of medicants to relatively inaccessible locations in a patient's body. For example, a medicant could be connected with the leading end portion 52 of the guide rod 50 and released when the indicia 124 indicated that the medicant has been moved to a desired position relative to the positioning section 96. The medicant may be released by activating a holder, disposed at the leading end portion 52 of the guide rod. A Bowden cable or other actuator may extend through the guide rod to the medicant holder to operate the medicant holder from a closed condition to an open condition to release the medicant.

Tracheal Intubation

[0070] Once the guide rod 50 has been moved through a desired distance into the patient's trachea 28, the positioning apparatus 56 is separated from the guide rod 50 while the guide rod remains stationary relative to the patient's trachea.

Thus, once the indicia **142** on the guide rod **50** indicates that the leading end portion **52** of the guide rod has been moved through a desired distance into the patient's trachea **28**, axial movement of the guide rod **50** is interrupted. At this time, one of the colored bands **142** on the guide rod **50** corresponding to the one of the colored bands **130** aligned with the connection **110**, is aligned with the end surface **156** on the guide section **114**.

[0071] The guide section **114** is then slid axially outward, that is toward the left as viewed in FIG. 1, along the guide rod **50**. During this sliding movement of the guide section **114** along the guide rod **50**, the guide rod is manually held against movement relative to the patient's mouth **12** and trachea **28**. The upper section **80** and base section **78** are separated from the patient during movement of the guide section **114** along the guide rod **50**. As this occurs, the guide rod **50** is stationary relative to the patient.

[0072] Once the upper section **80** has been separated from the guide rod **50**, the tracheal tube **38** (FIG. 2) is slid along the guide rod **50** into the patient's trachea **28**. Thus, the end of the guide rod **50** remote from the patient's mouth **12** and trachea **28** is inserted into the tracheal tube **38**. As this is done, the guide rod **50** is manually held against movement relative to the patient's mouth **12** and trachea **28**. The tracheal tube **38** is then moved axially along the guide rod **50** while the leading end portion **52** of the guide rod remains stationary in the patient's trachea.

[0073] As the tracheal tube **38** is moved axially along the guide rod **50**, the guide rod directs the leading end portion of the tracheal tube into the patient's larynx **30** and past the vocal cords **32**. The leading end of the tracheal tube **38** is centered in the space between the vocal cords and the entrance to the patient's trachea by the guide rod **50**. This minimizes irritation of the patient's vocal cords **32**. The tracheal tube **38** is moved along the guide rod **50** at least until the leading end of the tracheal tube engages the leading end portion **52** of the guide rod **50**.

[0074] It is contemplated that it may be desired to move the tracheal tube **38** further into the patient's trachea **28** than the distance which the guide rod **50** is moved into the patient's trachea. If this is the case, the tracheal tube **38** is pushed axially along the guide rod **50** past the leading end portion **52** of the guide rod. As this occurs, the leading end portion **52** of the guide rod **50** is compressed slightly and enters the tracheal tube **38**.

[0075] Once the tracheal tube **38** has been moved to a desired depth into the patient's trachea **28**, the guide rod **50** is removed from the tracheal tube (FIG. 7). The tracheal tube **38** then provides a passage for the conduction air, other gases, and/or medication to the patient's lungs.

Laryngoscope

[0076] This contemplated that a laryngoscope **170** (FIG. 3) maybe connected with the connection **110** which interconnects the body section **86** and arcuate upper section **80** of the positioning apparatus **56**. The laryngoscope **170** and body section **86** are moveable relative to each other to enable the laryngoscope to be positioned in the patient's mouth **12**. As the laryngoscope **170** is inserted into the patient's mouth **12**, the laryngoscope engages the patient's tongue. The laryngoscope then holds the patients tongue in a desired position in the mouth **12** of the patient.

[0077] The laryngoscope **170** is then inserted further into the patient's mouth **12** to expose progressively deeper struc-

tures within the oropharynx. The laryngoscope **170** could be advanced to facilitate visualization of the glottic opening in a known manner. Although the laryngoscope may be provided as part of the positioning apparatus **56**, in the manner illustrated in FIG. 3, it is contemplated that the laryngoscope **170** could be separate from the positioning apparatus if desired. Regardless of whether the laryngoscope **170** is formed as part of the positioning apparatus **56** or separate from the positioning apparatus, the laryngoscope is utilized in a known manner in management of the patient's tongue and airway.

Second Embodiment

[0078] A second embodiment of the invention is illustrated in FIGS. 4 through 10. Since the embodiment of the invention illustrated in FIGS. 4-10 is generally similar to embodiment of the invention illustrated in FIGS. 1-3, similar terminology will be utilized to refer to similar components.

[0079] A portion of a patient's head **210** has been illustrated schematically in FIG. 4. The patient's head includes a mouth **212** which is connected with a throat **214** and a neck **216** of the patient. Although the patient's head **210** has been schematically illustrated in an upright orientation in FIG. 4, it should be understood that the patient's head could be in a different orientation if desired. For example, the patient's head **210** could be in the orientation illustrated in FIGS. 1 and 2 for the patient's head **10**.

[0080] A pharynx **220** extends downward from a nasal cavity **222** in the head **210** of the patient. The pharynx **220** is connected with an esophagus **226** and a trachea **228** in the neck **216** of the patient. The esophagus **226** extends from the pharynx **220** to the stomach of the patient. The trachea **228** extends from the pharynx to the bronchial tubes and lungs of the patient.

[0081] The trachea **228** (FIG. 4) has an upper end portion **230** which is referred to as the larynx. Vocal cords or folds **232** have been indicated schematically in FIG. 3 and are disposed in the larynx **230**. The vocal cords **232** are adjacent to the Adam's apple **234** of the patient. The Adam's apple **234** is a laryngeal prominence formed by lamina of cartilage in the larynx.

[0082] Opening of a passage for air from the patient's mouth to the patient's lungs may require insertion of a flexible tracheal tube **238** (FIG. 10). Movement of the flexible tracheal tube **238** from the patient's mouth **212** into the pharynx **220** of the patient is relatively easily accomplished. However, directing the tracheal tube **238** into the patient's trachea **228** may present difficulties. This is because an anterior bend **240** must be formed in the tracheal tube **238**. The anterior bend **240** extends around the epiglottis **242** into the larynx **230** at the upper end of the trachea **228**. The anterior bend **240** can be minimized by placing the patient in the orientation illustrated in FIGS. 1 and 2.

[0083] During movement of the leading end of the tracheal tube **238** through the larynx **230**, it is desirable to have the tracheal tube near the central portion of the laryngeal cavity in order to minimize irritation of the vocal folds or cords **232** by the tracheal tube. In accordance with a feature of the present invention, a flexible guide wire or rod **250** (FIGS. 4 and 9) is utilized to guide movement of the flexible tracheal tube **238** (FIGS. 9 and 10) into the trachea **228**. The flexible guide rod **250** (FIG. 9) has a soft generally spherical leading end portion **252**. The leading end portion **252** of the guide rod **250** is formed of a resiliently compressible material which is readily deflected by engagement with the vocal cords or folds **232**

and by engagement with the surface of the trachea 228. If desired, the leading end portion 252 of the guide rod 250 may be coated with a suitable lubricant to facilitate movement of the leading end portion between the vocal cords with minimum of irritation.

[0084] In accordance with another feature of the invention, the guide wire 250 is initially positioned relative to the patient's trachea 228 with a positioning apparatus 256 (FIG. 4). The positioning apparatus 256 engages the patient's Adam's apple 234 to locate the positioning apparatus relative to the trachea 228 of the patient. In addition, the positioning apparatus 256 provides a measurement which is a function of the distance between the Adam's apple 234 and the mouth 212 of the patient. This measurement is utilized to determine the distance through which the guide rod 250 is to be moved relative to the positioning apparatus 256 as the guide rod is inserted into the trachea 228.

[0085] In accordance with still another feature of the present invention, a magnet 260 (FIG. 4) is utilized to attract the leading end portion 252 of the guide rod 250 and to steer the leading end portion of the guide rod into the patient's trachea 228. The magnet 260 is a permanent magnet formed of a strongly magnetizable material such as cobalt and neodymium. Of course, other known magnetizable materials having high saturation magnetization values, such as cerium, praseodymium, and/or samarium with cobalt and/or other materials, could be used. Alternatively, the magnet 260 may be an electromagnet.

[0086] To enable the leading end portion 252 of the guide rod 250 to be attracted by a magnetic field emanating from the magnet 260, the leading end portion 252 of the guide rod contains ferrite particles. The ferrite particles may or may not be magnetized. Of course, other known magnetizable or magnetic particles could be utilized. When a magnet is positioned on the leading end portion 252 of the guide rod 250, the polarity of the leading end of the magnet on the guide rod is opposite from the polarity of the magnet 260.

[0087] As the guide rod 250 is moved downward (as viewed in FIG. 4) along the patient's pharynx toward the larynx 230, the leading end portion 252 of the guide rod enters the field of the magnet 260. The field of the magnet 260 has sufficient strength to cause the guide rod 250 to deflect slightly toward the right (as viewed in FIG. 4). As this occurs, the leading end portion 252 of the guide rod moves into the larynx 230 at a location adjacent to the center of the larynx. This enables the leading end portion 252 of the guide rod 250 to move between the vocal cords or folds 232 with a minimum of irritation to the vocal cords. Although the magnet 260 is described herein as steering the leading end portion 252 of the guide rod 250 into the trachea, it is contemplated that the magnet could be utilized to steer members at many different locations in a patient's body.

[0088] The magnet 260 may be an electromagnet. If the magnet 260 is an electromagnet, the magnet may be turned on and off, that is, energized and de-energized during steering of the leading end portion 252 of the guide 250. If desired, the leading end portion 252 of the guide rod 250 could also be formed by an electromagnet. If this was done, conductors for connecting the leading end portion 252 of the guide 250 would extend along the inside of the guide rod. By reversing the direction of current flow to either the electromagnet forming the magnet 260 or the electromagnet forming the leading end portion 252 of the guide rod 250, the two electromagnets could be made to sequentially attract and repel each other.

[0089] Steering of the leading end portion 252 of the guide rod 250 with the magnet 360 is facilitated by moving the magnet along the patient's neck 216, in the manner indicated schematically in FIG. 7. The magnet 360 may be moved up and down along the patient's neck. The magnet 360 may also be moved sideways relative to the patient's neck. By moving the magnet 360 relative to the patient's neck, a magnetic field emanating from the magnet is effective to pull the leading end portion 252 of the guide rod 250 in the desired direction.

[0090] Although the use of the magnet 260 has been disclosed herein in association with the embodiment of the invention illustrated in FIGS. 4-10, it is contemplated that the magnet 260 could be used in association with other embodiments of the invention. For example, the magnet 260 could be used with the embodiment of the invention illustrated in FIGS. 1 and 2.

[0091] The magnet 260 may be used to steer devices other than the guide rod 250. When the positioning apparatus 56 (FIG. 1) is to be associated with a portion of a patient's body other than the trachea, the magnet 260 (FIG. 4) could be used to steer any one of many different devices to a desired location in the patient's body. A positioning apparatus, similar to the positioning apparatus 56 of FIG. 1 or the positioning apparatus 256 of FIG. 4, and a magnet, similar to the magnet 260 may be used during endoscopic, arthroscopic, or fiber optic surgery at many different locations in a patient's body. Thus, the magnet 260 may be used to steer a guide rod being positioned relative to a joint by a positioning apparatus, similar to the positioning apparatus 56 of FIG. 1 and the positioning apparatus 256 of FIG. 4, during surgery at the joint. The magnet 260 may also be used to position medicants at desired locations in the patient's body. Although it is believed that the magnet 260 will be advantageously used in association with a positioning apparatus similar to the positioning apparatus 56 of FIG. 1 or the other positioning apparatus 256 of FIG. 4, the magnet may be used in situations where the positioning apparatus is not required.

Positioning Apparatus of FIGS. 4-10

[0092] The positioning apparatus 256 (FIG. 4) positions the guide rod 250 relative to the patient's trachea 228 during insertion of the guide rod into the patient's trachea. In addition, the positioning apparatus 256 provides an indication of the distance which the guide rod is to be moved into the patient's trachea. By using the positioning apparatus 256, a person moving the guide rod 250 into the patient's trachea 228 can know where the leading end portion 252 of the guide rod is located relative to the trachea.

[0093] During movement of the guide rod 250 into the patient's trachea, the guide rod is moved axially through a flexible, generally cylindrical, guide tube 264 (FIG. 5). The guide tube 264 is formed of a resilient polymeric material. The guide tube 264 has a main section 266 and a leading end section 268. The leading end section 268 has a side wall 270 which is thinner than a side wall 272 of the main section 266. The side wall 270 is integrally molded as one piece with the thicker side wall 272. A generally cylindrical passage 274 (FIG. 5) extends axially through the guide tube 264.

[0094] The thin walled leading end section 268 of the guide tube 264 is molded so as to naturally assume the arcuate configuration illustrated in FIGS. 4 and 5. This enables the end section 268 of the guide tube 264 to be positioned in the patient's pharynx 220 (FIG. 4) with the end section forming a bend which extends around the upper end portion of the

patient's epiglottis **242**. Since the leading end section **268** has a relatively thin side wall (FIG. 5), the end section can be easily deflected as it is moved into position in the patient's pharynx **220**. The thicker side wall **272** of the main section **266** of the guide tube **264** is effective to support the leading end section **268** in the patient's pharynx **220** and to depress a tongue **76** in the mouth **212** of the patient (FIG. 1).

[0095] The guide rod **250** may be formed of either polymeric material or metal. The illustrated polymeric guide rod **250** has a relatively small diameter and is readily deflected. The guide rod **250** has a circular cross sectional configuration.

[0096] The guide rod **250** extends axially through the guide tube **264** (FIG. 4). The guide rod **250** is axially movable relative to the guide tube **264** under the influence of force manually applied to the portion of the guide rod disposed to the right (as viewed in FIG. 4) of the positioning apparatus **256**. This force results in axial movement of the guide rod **250** along the guide tube **264**.

[0097] As the guide rod **250** is axially moved along the guide tube **264**, the arcuate leading end section **268** of the guide tube **264** resiliently deflects the guide rod **250** to form the arcuate bend illustrated in FIG. 4. As the guide rod **250** is manually pushed toward the left (as viewed in FIG. 4), the leading end **52** of the guide rod moves downward (as viewed in FIG. 4) toward the larynx **230**. As the leading end **252** of the guide rod **250** moves downward (as viewed in FIG. 4), tissues which may tend to block movement of the guide rod are pushed aside by the leading end of the guide rod. This clears a passage for the guide rod **250**.

[0098] The positioning apparatus **256** is used to locate the leading end portion **252** of the guide rod **250** as the guide rod moves along the guide tube **264**. The positioning apparatus **256** includes a base section **278** and an upper section **280** (FIG. 4). The base section **278** engages the patient's Adam's apple **234** to locate the positioning apparatus **256** relative to the patient's trachea **228**. The upper section **280** of the positioning apparatus **256** holds the guide tube **264** which guides movement of the guide rod **250** during insertion of the guide rod into the patient's trachea **228**.

[0099] The base section **278** and upper section **280** of the positioning apparatus **256** cooperate to provide a measurement of the distance between the patient's mouth **212** and the patient's Adam's apple **234**. This distance will vary from patient to patient depending upon the size of the patient, the specific configuration of the head **210** of the patient, and other factors. The distance which the guide rod **250** must be moved axially relative to the guide tube **264** to move the leading end portion **252** of the guide rod into the patient's larynx **230** will vary as a function of variations in the distance between the patient's mouth **212** and the patient's Adam's apple **234**. This is because the patient's Adam's apple **234** is located adjacent to the entrance to the trachea **228**.

[0100] The base section **278** of the positioning apparatus **256** includes an upright tubular cylindrical body section **286**. The body section **286** has a cylindrical chamber **288**. The cylindrical upper section **280** of the positioning apparatus **256** is telescopically received in the chamber **288**.

[0101] In addition, the base section **278** includes an end section **290**. The end section **290** extends perpendicular to the body section **286**. The end section **290** has a cylindrical central passage **292** which extends perpendicular to and intersects the central axis of the chamber **288**. The body section **286** and the end section **290** are integrally molded as one piece of polymeric material.

[0102] The base section **278** also includes a positioning section **296** which engages the patient's Adam's apple **234** and is supported by the end section **290**. The positioning section **296** includes a cylindrical support rod **298** which extends through the passage **292** and is connected with a locating portion **302** which engages the patient's Adam's apple **234**. The locating portion **302** includes a generally hemispherical dome **304** and a resilient annular collar **306** which is connected to the rim of the dome **304**. The collar **306** extends around the Adam's apple **234** and engages upper and lower sides and left and right sides of the Adam's apple to center the dome **304** on the Adam's apple.

[0103] If desired, the locating portion **302** could be constructed to engage only two sides of the Adam's apple **234**. For example, the left and right sides of the Adam's apple **234**. It is believed that it may be desired to form the locating portion **302** with the construction illustrated in FIGS. 25 and 26 herein. Alternatively, the locating portion **302** could be constructed so as to engage only the central portion of the Adam's apple **234**.

[0104] However, it is believed that it may be desired to form the locating portion **302** so that it extends around the Adam's apple **234** so as to locate the positioning section **296** relative to the Adam's apple. Force may be manually applied against the positioning section **296** to minimize the anterior bend **240** (FIG. 10) which must be formed in the tracheal tube **238**. The end section **290** is axially slidable along the support rod **298** so that the body section **286** is disposed adjacent to the chin **310** of the patient.

[0105] Although it is preferred to use the patient's Adam's apple **234** to locate the positioning apparatus **256** relative to the patient's trachea **228**, a different portion of the patient's body could be used to locate the positioning apparatus relative to the patient's trachea. For example, the patient's shoulders could be used. Alternatively, bones in the patient's neck **216** could be used to locate the positioning apparatus **256** relative to the patient's trachea **228**. However, it is believed that it will be preferred to use the patient's Adam's apple **234** to locate the positioning apparatus **256** due to the close proximity of the patient's Adam's apple to the upper end of the patient's trachea **228**.

[0106] The upper section **280** of the positioning apparatus **256** includes a cylindrical rod portion **314** which is telescopically received in the body section **286** of the positioning apparatus. An upper end section **316** has a cylindrical passage **318** through which the guide tube **264** extends. The passage **318** has a longitudinal central axis which extends parallel to the longitudinal central axis of the passage **292** and to the longitudinal central axis of the support rod **298**. The guide tube **264** is slidable in the passage **318**.

[0107] The guide tube **264** extends from the passage **318** into the patient's mouth **212**. Thus, the passage **318** in the upper section **280** of the positioning apparatus **256** is axially aligned with the patient's mouth **212**. Similarly, the passage **292** (FIG. 4) in the end section **290** of the base section **278** of the positioning apparatus **256** is axially aligned with the patient's Adam's apple **234**. Therefore, the positioning apparatus **256** can be utilized to measure the distance between the Adam's apple **234** and the patient's mouth **212**.

[0108] The entrance through which the guide rod **250** must pass into the patient's trachea **228** is adjacent to the Adam's apple **234**. Therefore, the distance through which the leading end portion **252** of the guide rod **250** must be moved relative to the guide tube **264** (FIG. 4) to enter the patient's trachea

228, is a function of the distance between the patient's Adam's apple 234 and the patient's mouth 212. The positioning apparatus 256 measures the distance between the patient's Adam's apple 234 and the patient's mouth by determining the position of the base section 278 and upper section 280 of the positioning apparatus relative to each other.

[0109] In the illustrated embodiment of the invention, the distance between the patient's Adam's apple 234 and the patient's mouth 212 is indicated by indicia 324 (FIG. 6). The indicia 324 is disposed on the cylindrical rod portion 314 of the upper section 280 of the positioning apparatus 256. The rod portion 314 is telescopically received in the cylindrical chamber 288 in the body section 286 of the positioning apparatus 256.

[0110] The position of an annular upper end surface 328 on (FIG. 6) the body section 286 relative to the indicia 324 indicates the distance which the rod portion 314 is extended from the body section 286. The distance which the rod portion 314 is extended from the body section 286 is a function of the distance between the patient's Adam's apple 234 and the entrance to the patient's mouth 212.

[0111] In the illustrated embodiment of the invention, the indicia 324 is formed by a plurality of colored bands 330, 332, 334, 336, 338 and 340 (FIG. 6). Each of the bands 330-340 has a different color from the other bands. It should be understood that a lesser or greater number of colored bands 330-340 could be provided if desired. It should also be understood that although the bands 330-340 have the same axial extent, the bands could have different axial extents if desired. Rather than using the colored bands 330-340 as the indicia 324, numerical indicia could be provided. However, it is believed that it may be easier to read the different colored bands 330-340 than to read numerical indicia.

[0112] Bands 342, 344, 346, 348, and 350 (FIG. 8) are provided on the guide rod 250. The colored bands 342-350 have different colors which correspond to the colors of the bands 132-140 on the rod portion 314 (FIG. 6) of the positioning apparatus 256. It should be understood that although only the bands 342-350 having colors corresponding to the colors of the bands 132-140 are illustrated, an additional band having a color corresponding to the color of the band 330 in FIG. 6 is provided on the guide rod 250.

[0113] The bands 342-350 (FIG. 8) on the guide rod 250 cooperate with an annular end surface 356 (FIG. 4) on the guide tube 264 to indicate when the leading end portion 252 of the guide rod is in a desired position relative to the patient's trachea 228. Thus, assuming that the colored band 334 on the rod portion 314 of the positioning apparatus 256 is aligned with the end surface 328 on the body section 286 (as illustrated in FIG. 6), the band 344 (FIG. 8) on the guide rod 250 will be moved to a position in which it is partially covered by the guide tube 264 and projects outward from the end surface 356 (FIG. 4) for a distance corresponding to the distance which the band 334 projects outward from the end surface 328 on the body section 286 (FIG. 5). The band 344 has a color which is the same as the color of the band 334. When the guide rod 250 has been moved to a position in which the band 344 is partially enclosed by the guide tube 264, the leading end portion 252 of the guide rod will have moved through a desired distance into the patient's trachea 228, for example, a distance of approximately ten centimeters.

[0114] The bands 342-350 (FIG. 8) on the guide rod 250 are spaced a predetermined distance from the end surface 356 (FIG. 4) on the guide tube 264 when the leading end portion

252 of the guide rod is disposed in abutting engagement with the leading end section 268 of the guide tube 264. During movement of the indicia on the guide rod 250 from a position spaced from the end surface 356 of the guide tube 264 to a position in which the leading band on the guide rod 150 is adjacent to the end surface 356, the leading end portion 252 of the guide rod 250 will have moved from the pharynx 220 of the patient and into the larynx 230 past the vocal cords 232.

[0115] As the guide rod 250 continues to be manually pushed into the guide tube 264, the leading end portion 252 of the guide rod advances downward (as viewed in FIG. 4) in the trachea 228 of the patient. Movement of the guide rod 250 into the trachea 228 of the patient is interrupted when the band 344 having a color corresponding to the color of the band 334 (FIG. 6) has been partially covered by the guide tube 264.

[0116] The magnet 260 is utilized to steer the guide rod 250 during movement of the leading end portion 252 of the guide rod from the patient's mouth 212 into the patient's trachea 228. As the leading end portion 252 of the guide rod 250 is moved downward along the inside of the patient's neck, the magnet 360 is moved downward along the outside of the patient's neck. The magnetic field provided by the magnet 360 is effective to pull the leading end portion 252 downward as the magnet moves downward. Eventually, the leading end portion 252 of the guide rod 250 and magnet 260 will move downward from the entrance to the trachea 228 through a desired distance, for example a distance of approximately ten centimeters. Of course, the leading end portion 252 of the guide rod 250 could be moved through a different distance into the trachea 228 if desired.

[0117] It is contemplated that the distance between the patient's Adam's apple 234 and the entrance to the patient's mouth 212 will vary from patient to patient. However, the distance which the leading end portion 252 of the guide rod 250 is moved into the patient's trachea 228 will remain constant at a desired distance, for example, ten centimeters. This is because as the distance measured by the positioning apparatus 256 increases, the distance which the guide rod 250 is moved relative to the guide tube 264 increases. Conversely, as the distance which is measured by the positioning apparatus 256 decreases, the distance which the guide rod 250 is moved relative to the guide tube 264 decreases. The distance which is measured by the positioning apparatus 256 varies as a function of the distance between the mouth 212 and larynx 230 of the patient.

Tracheal Intubation

[0118] Once the guide rod 250 has been moved through a desired distance into the patient's trachea 228, the guide tube 264 and positioning apparatus 256 are separated from the guide rod 250 while the guide rod remains stationary relative to the patient's trachea. Thus, once the indicia on the guide rod 250 indicates that the leading end portion 252 of the guide rod has been moved through a desired distance into the patient's trachea 228, axial movement of the guide rod 250 is interrupted. At this time, one of the colored bands 342-350 on the guide rod 250 corresponding to the one of the colored bands 330-340 aligned with the end surface 328 (FIG. 4) on the body section 286 of the positioning apparatus is aligned with the end surface 356 (FIG. 4) on the guide tube 264.

[0119] The guide tube 264 is then slid axially outward, that is toward the right as viewed in FIG. 4, along the guide rod 250. During this sliding movement of the guide tube 264 along the guide rod 250, the guide rod is manually held

against movement relative to the patient's mouth 212 and trachea 228. The positioning apparatus 256 is moved away from the patient along with the guide tube 264.

[0120] Once the guide tube 264 has been separated from the guide rod 250 (FIG. 9), the tracheal tube 238 is slid along the guide rod 250 into the patient's trachea 228. Thus, the end of the guide rod 250 remote from the patient's mouth 212 and trachea 228 is inserted into the tracheal tube 238. As this is done, the guide rod 250 is manually held against movement relative to the patient's mouth 212 and trachea 228. The tracheal tube 238 is then moved axially along the guide rod 250 while the leading end portion 252 of the guide rod remains stationary in the patient's trachea. If desired, the magnet 260 may be utilized to attract the leading end portion 252 of the guide rod 250, in the manner illustrated in FIG. 9, to facilitate maintaining of the leading end portion of the guide rod stationary in the patient's trachea 228.

[0121] As the tracheal tube 238 is moved axially along the guide rod 250, the guide rod directs the leading end portion of the tracheal tube along a bend 360 (FIG. 9) formed in the guide rod. After the leading end portion of the tracheal tube 238 has moved around the bend 360, the leading end portion of the tracheal tube enters the patient's larynx and moves past the vocal cords 232. The leading end of the tracheal tube 238 is centered in the space between the vocal cords and the entrance to the patient's trachea by the guide rod 250. This minimizes irritation of the patient's vocal cords 232. The tracheal tube 238 is moved along the guide rod 250 at least until the leading end of the tracheal tube engages the leading end portion 252 of the guide rod 250.

[0122] It is contemplated that it may be desired to move the tracheal tube 238 further into the patient's trachea than the distance which the guide rod 250 is moved into the patient's trachea. If this is the case, the tracheal tube 238 is pushed axially along the guide rod 250 past the leading end portion 252 of the guide rod. As this occurs, the leading end portion 252 of the guide rod 250 is compressed slightly and enters the tracheal tube 238.

[0123] Once the tracheal tube 238 has been moved to a desired depth into the patient's trachea 228, the guide rod 250 is removed from the tracheal tube (FIG. 10). The tracheal tube 238 then provides a passage for the conduction air, other gases, and/or medication to the patient's lungs.

Method of Utilization

[0124] When the tracheal tube 238 is to be inserted into a patient's trachea 228, the guide rod 250 is first positioned relative to the guide tube 264 at a location spaced from the patient. At this time, the leading end portion 252 of the guide rod 250 is disposed in abutting engagement with the leading end portion 268 of the guide tube 264. The upper section 280 of the positioning apparatus 256 is loosely positioned on the guide tube 264. The lower or base section 278 of the positioning apparatus 256 is separate and spaced from the upper section 280 of the positioning apparatus. A suitable lubricant may be applied to the leading end portion 252 of the guide rod 250 and to the leading end portion 268 of the guide tube 264.

[0125] The guide tube 264 is then inserted into the patient's mouth 212. As the guide tube 264 is inserted into the patient's mouth, the leading end portion 268 of the guide tube 264 and the leading end portion 252 of the guide rod 250 move from the patient's mouth into the pharynx 220 of the patient. As the leading end portion 268 of the guide tube 264 moves into the pharynx 220 of the patient, the natural resilience of the mate-

rial of the guide tube causes the guide tube to spring back to its initial or free configuration illustrated in FIGS. 3 and 4.

[0126] As the guide tube 264 and guide rod 250 are manually moved together into the patient's mouth 212, the guide tube bends itself around the upper (as viewed in FIG. 3) portion of the patient's epiglottis 242. This results in the leading end portion 252 of the guide rod 250 being pointed downward (as viewed in FIG. 3) toward the lower end portion of the patient's pharynx 220. A person initially inserting the guide tube 264 and guide rod 250 into the patient's mouth 212 can visually ascertain when the guide tube and guide rod have moved to the position illustrated in FIG. 3.

[0127] When the guide tube 264 and guide rod 250 have been positioned in this manner relative to the patient's mouth 212 and pharynx 220, the positioning apparatus 256 is assembled. To assemble the positioning apparatus, the rod portion 314 of the upper section 280 is telescopically inserted into the chamber 288 in the body section 286 of the positioning apparatus. Contemporaneously therewith, the locating portion 302 of the positioning apparatus 296 is moved into engagement with the patient's Adam's apple 234. The base section 278 and upper section 280 of the positioning apparatus 256 are moved axially along the guide tube 264 and support rod 298 until the base section and upper section of the positioning apparatus 256 are adjacent to the patient's chin 310 (FIG. 4). At this time, the coincident central axes of the rod portion 314 and body section 286 of the positioning apparatus 256 will extend perpendicular to the central axes of the guide tube 264 and support rod 298.

[0128] The magnet 260 is then positioned immediately beneath the patient's Adam's apple 234. This enables the magnetic field from the magnet 260 to extend leftward and upward (as viewed in FIG. 4) to the entrance to the patient's larynx 230. This results in the magnet 260 and positioning apparatus 256 being disposed in the orientation illustrated in FIG. 3 relative to the patient.

[0129] Once the positioning apparatus 256, guide tube 264 and guide rod 250 have been moved to the positions shown in FIG. 3 relative to the patient's head 210, the person using the positioning apparatus 256 visually determines the distance between the patient's Adam's apple 234 and the patient's mouth 212. This is accomplished by viewing the indicia 324 (FIG. 6) on the rod portion 314 of the positioning apparatus 256. By determining which of the bands 330-340 is aligned with the end surface 328 on the body section 286 of the positioning apparatus 256, the operator determines the distance between the patient's Adam's apple and the patient's mouth. The distance which the guide rod 250 must be moved into the patient's trachea 228 is a direct function of the distance between the patient's Adam's apple 234 and the patient's mouth 212.

[0130] The operator then begins to manually apply force against the rightward (as viewed in FIG. 4) portion of the guide rod 250 while holding the guide tube 264 against movement. This results in the leading end portion 252 of the guide rod moving downward toward the entrance to the patient's larynx 230. As the guide rod 250 begins to move downward, the bent leading end portion 268 of the guide tube 60 directs the leading end portion 252 of the guide rod 80 downward around the patient's epiglottis 242 in a direction toward the entrance to the larynx 230.

[0131] It is contemplated that the resiliently deflectable guide rod 250 will initially be formed with a bend which is a continuation of the bend in the leading end portion of the

guide tube 264. Therefore, the natural resilience of the guide rod 250 will tend to cause the guide rod to bend rightward toward the patient's Adam's apple as the leading end portion 252 of the guide rod begins to move downward toward the larynx 230.

[0132] As the leading end portion 252 of the guide rod 250 approaches the entrance to the larynx 230, the field emanating from the magnet 260 attracts the leading end portion 252 of the guide rod 250. The magnetic attraction forces applied to the leading end portion 252 of the guide rod 250 also promote rightward (as viewed in FIG. 4) bending of the guide rod 250 toward the patient's Adam's apple 234. Thus, the combined effect of the magnet 260 and the natural resilience of the preformed guide rod 250 urge the leading end portions 52 of the guide rod 250 toward the entrance to the larynx 230 and away from the adjacent entrance to the esophagus 226. This ensures that the leading end portion 252 of the guide rod 250 enters the trachea 228 rather than the esophagus 226. If desired, the magnet 260 could be positioned above or on the patient's Adam's apple 234 and then moved downward as the guide rod 250 advances.

[0133] If desired, the flexible guide rod 250 could initially be formed with a straight configuration and only the magnet 260 would steer the leading end portion 252 of the guide rod into the entrance to the trachea 228. Alternatively, the use of the magnet 260 could be eliminated and only the preformed configuration of the guide rod 250 would be used to direct the leading end portion 252 of the guide rod into the entrance to the trachea 228. However, it is believed that it will be preferred to use both the preformed configuration of the guide rod 250 and the magnet 260 to direct the leading end portion 252 of the guide rod into the patient's trachea 228.

[0134] The colored bands 342-350 (FIG. 8) on the guide rod 250 cooperate with the end surface 356 (FIG. 4) of the guide tube 264 to provide an indication of the location of the leading end portion 252 of the guide rod relative to the patient's Adam's apple 234. As the leading end portion 252 of the guide rod 250 moves downward from the position shown in FIG. 3 toward the entrance to the larynx 230, the indicia bands 342-350 will move toward the end surface 356 of the guide rod 250. As the leading end portion 252 of the guide rod 250 moves through the entrance to the larynx 230, the indicia on the guide rod 250 will be approaching the end surface 356 of the guide tube 264.

[0135] Continued axial movement of the guide rod 250 relative to the stationary guide tube 264 moves the leading end portion 252 of the guide rod to a position immediately above the patient's vocal cords 232. As this occurs, the leading end portion 252 of the guide rod 250 is strongly attracted by the magnetic field emanating from the magnet 260. Due to the approach of the indicia on the guide rod 250 toward the end surface 356 of the guide tube 264, the operator realizes that the leading end portion 252 of the guide rod 250 is adjacent to the magnet 260 and moves the magnet downward (as viewed in FIG. 4) along the neck 216 of the patient as the guide rod 250 continues to be moved leftward through the stationary guide tube 264. As the magnet 260 is manually moved downward (as viewed in FIG. 4) with the leading end portion 252 of the guide rod 250, the magnet continues to attract the leading end portion of the guide rod.

[0136] One of the bands 330-340, having a particular color, for instance, red, on the rod portion 314 (FIG. 6) will be adjacent to the end surface 328 on the body section of the positioning apparatus 256. When a correspondingly colored

band, that is, when the red band 344 on the guide rod 250 (FIG. 8), is partially covered by the guide tube 264 and extends axially outward from the end surface 356, the operator will know that the leading end portion 252 of the guide rod 250 will have moved past the vocal 232 to the desired position relative to the patient's trachea. Insertion of the guide rod 250 into the guide tube 264 is then interrupted.

[0137] After the guide rod 250 has been inserted for the desired distance into the patient's trachea 228, the guide tube 264 and positioning apparatus 256 are separated from the guide rod 250. During separation of the guide tube 264 and positioning apparatus 256 from the guide rod 250, the guide rod is maintained stationary relative to a patient's trachea 228. In the illustrated embodiment of the invention, the guide tube 264 is merely moved rightward (as viewed in FIG. 4) along the stationary guide rod 250 to disengage the guide tube and the positioning apparatus from the guide rod.

[0138] If desired, a slot could be provided in the guide tube 264 to facilitate disengagement of the guide tube from the guide rod. A corresponding slot could be formed in the end section 316 of the positioning apparatus 256. The slots in the guide tube 264 and end section 316 could be partially or fully blocked during insertion of the guide rod 250 into the guide tube 264. When the guide tube 264 is to be separated from the guide rod 250, that is after the guide rod has been inserted for the desired distance into the patient's trachea 228, latch or closure members for the slots could be moved to open positions and the guide tube 264 and apparatus 256 moved out of engagement with the stationary guide rod 250.

[0139] Once the guide tube 264 and positioning apparatus 256 have been disengaged from the guide rod 250, the guide rod is utilized to guide movement of the tracheal tube 238 into the patient's trachea 228. The tracheal tube 238 has a substantially larger diameter than the guide tube 264 to provide for a relatively large central opening through which air or other gas may pass into the patient's trachea 228.

[0140] When the tracheal tube 238 is to be moved into the patient's trachea 228, the guide rod 250 is telescopically inserted into the leading end of the tracheal tube. At this time, the right end (as viewed in FIG. 4) of the guide rod 250 will extend beyond the far right end of the tracheal tube 238. Therefore, the guide rod 250 can be manually grasped and the tracheal tube 238 moved axially along the guide rod while the guide rod remains stationary relative to the patient's trachea 228.

[0141] The tracheal tube 238 is moved leftward, in the manner indicated by the arrow in FIG. 9, along the stationary guide rod 250 into the patient's mouth 212. The tracheal tube 238 is then moved around the bend 360 in the stationary guide rod 250 and into the patient's trachea 228. Since the guide rod 250 extends from the patient's pharynx 220 into the trachea 228, the guide rod 250 blocks movement of the leading end portion of the tracheal tube 238 into the patient's esophagus 226. The guide rod 250 acts as a track along which the tracheal tube 238 moves into the patient's larynx 230 and not into the adjacent esophagus 226.

[0142] As the leading end portion of the tracheal tube 238 approaches and moves past the vocal cords 232, the guide rod 250 guides movement of the leading end portion of the tracheal tube in such a manner as to minimize irritation of the vocal cords. Thus, the guide rod 250 centers the leading end portion of the tracheal tube 238 in the space between the vocal cords. By lubricating the leading end portion of the tracheal tube 238 and centering the leading end portion of the tracheal

tube in the space between the vocal cords **232**, the tracheal tube can be moved into the patient's trachea **228** with a minimal amount of irritation to the vocal cords.

[0143] As the tracheal tube **238** is moved through the patient's larynx **230**, the magnet **260** is disposed adjacent to the leading end portion **252** of the guide rod **250**. Therefore, the leading end portion **252** of the guide rod **250** is attracted by the magnet **260** and tends to remain stationary in the patient's trachea **228**. As the tracheal tube **238** is inserted into the patient's trachea **228**, the leading end portion of the tracheal tube **238** moves past the leading end portion **252** of the guide rod **250**. As this occurs, the leading end portion **252** of the guide rod **250** is slightly compressed and moves into the tracheal tube **238**. Once the tracheal tube **238** has moved to a desired position relative to the trachea **228**, the guide rod **250** is withdrawn from the tracheal tube **238** while the tracheal tube is maintained stationary relative to the patient's trachea.

[0144] In the embodiment of the invention illustrated in FIGS. 4-10, the magnet **260** (FIG. 4) is utilized to attract the leading end portion **252** of the guide rod **250**. However, it is contemplated that the magnet **260** could be used for other purposes if desired. For example, the magnet **260** could be used to position a suture anchor relative to body tissue.

[0145] When the magnet **260** is to be utilized to position a suture anchor relative to body tissue, a leading end portion of the suture anchor is formed of a magnetizable material, such as ferrite. Alternatively, the leading end portion of the suture anchor could be formed of a magnetic material such as cobalt, neodymium, cerium, praseodymium, and/or samarium. If this was done, the magnet **260** would be oriented relative to the magnet on the suture anchor to have a pole of the magnet **260** of opposite polarity to the leading end of the suture anchor toward the suture anchor.

[0146] The trailing end portion of the suture anchor may be formed of a nonmagnetic material, such as a biodegradable polymer. The suture would extend through an opening in the nonmagnetic material of the trailing end portion of the suture anchor. Once the suture anchor had been moved to a desired position relative to body tissue by attraction of the magnet **260** for the leading end portion of the suture anchor, the leading end portion of the suture anchor may be separated from the trailing end portion of the suture anchor. The leading end portion of the suture anchor could then be removed from the patient's body to eliminate the possibility of an undesired interaction in the future with a magnetic field device, such as a magnetic resonance imaging device (MRI). The suture would be held in place by the nonmagnetic trailing end portion of the suture anchor.

Embodiment of FIG. 11

[0147] In the embodiment of the invention illustrated in FIGS. 4-10, a guide tube **264** is utilized to guide movement of the guide rod **250** as the guide rod is moved from the patient's pharynx **220** into the patient's trachea **228**. The guide tube **264** is then removed and a tracheal tube **238** is slid along the guide rod **250** into the patient's trachea. In the embodiment of the invention illustrated in FIG. 11, the tracheal tube is used to guide movement of the guide rod into the patient's trachea. This eliminates the need for a separate guide tube. Since the embodiment of the invention illustrated in FIG. 11 is generally similar to the embodiment of the invention illustrated in FIGS. 4-9, similar numerals will be utilized to designate

similar components, the suffix letter "a" being associated with being associated with the numerals of FIG. 11 to avoid confusion.

[0148] A patient's head **210a** (FIG. 11) includes a mouth **212a** which is connected with a throat **214a** in a neck **216a** of the patient. A pharynx **220a** is connected with an esophagus **226a** and a trachea **228a**. A larynx **230a** forms an upper end portion of the trachea **228a** and contains vocal cords **232a**. An Adam's apple **234a** is formed by laminae of cartilage in the patient's larynx **230a**.

[0149] A positioning apparatus **256a** is utilized to position a tracheal tube **238a** and a guide rod or wire **250a** during insertion of the guide rod and during insertion of the tracheal tube into the patient's trachea **228a**. The tracheal tube **238a** (FIG. 11) is flexible and is formed of a resilient polymeric material. The tracheal tube **238a** is initially formed with a bend **380** in a leading end portion of the tracheal tube. When the tracheal tube **238a** is released or unrestrained, the natural resilience of the tracheal tube causes the bend **380** to form in the manner illustrated in FIG. 10. However, the tracheal tube **238a** is flexible so that the bend **380** is easily removed from the tracheal tube by the application of a relatively small force or pressure against the leading end portion of the tracheal tube.

[0150] In the embodiment of the invention illustrated in FIG. 10, the bend **380** in the tracheal tube **238a** has a greater extent than a corresponding bend in a leading end section **268** of the guide tube **264** (FIG. 4). If desired, the bend in the tracheal tube **238a** (FIG. 11) could be shortened so that the leading end portion of the tracheal tube **238a** has a configuration which corresponds to the configuration of the guide tube **264** of FIG. 4.

[0151] The positioning apparatus **256a** (FIG. 11) includes a base section **278a** and an upper section **280a**. A rod portion **314a** of the upper section **280a** is telescopically received in a chamber **288a** in the base section **278a**. Indicia **324a** on the rod portion **314a** cooperates with a body section **286a** of the base section **278a** to provide a visual indication of the distance between the patient's Adam's apple **234a** and the patient's mouth **212a** in the manner previously described in conjunction with the positioning apparatus of FIG. 4.

[0152] The base section **278a** of the positioning apparatus **256a** includes a positioning section **96a** which engages the patient's Adam's apple **234a**. The positioning section **96a** includes a locating portion **302a** which engages the patient's Adam's apple **234a**. The locating portion **302a** includes a dome **304a** and a soft annular collar **306a**. Rather than using the collar **306a**, it may be preferred to utilize a pair of positioning fingers which engage the neck **216a** of the patient at laterally opposite sides of the Adam's apple **234a**.

[0153] Indicia (not shown) is provided on the guide rod **250a** to indicate the position of the guide rod relative to a proximal end of the tracheal tube **238a**, that is, the right end as viewed in FIG. 11. It should be understood that the tracheal tube **238a** and the guide rod **250a** extend toward the right from the fragmentary end portions illustrated in FIG. 11. The indicia on the guide rod **250a** is formed by bands corresponding to the bands **342-350** of FIG. 8. Rather than cooperating with the end **156** (FIG. 4) of a guide tube **264**, the bands on the guide rod **250a** (FIG. 11) cooperate with an end (not shown) of the tracheal tube **238a** to indicate the position of the guide rod **250a** relative to the tracheal tube **238a**.

[0154] When the guide rod **250a** is to be moved from the patient's pharynx **220a** into the patient's trachea **228a**, the

guide rod is moved axially relative to the stationary tracheal tube **238a**. As this occurs, a leading end portion **252a** of the guide rod **250a** moves downward (as viewed in FIG. 11) past the patient's vocal cords or folds **32a** and into the patient's trachea. As the leading end portion **252a** of the guide rod **250a** moves from the patient's pharynx **220a** into the patient's trachea **228a**, the leading end portion of the guide rod gently deflects body tissue. For example, the leading end portion **252a** of the guide rod **250a** may gently engage and slightly deflect the patient's vocal cords or folds **32a**.

[0155] A magnet **260a** is initially positioned adjacent to the patient's Adam's apple **234a**, in the manner indicated in dashed lines in FIG. 11. Ferrite particles in the soft, resiliently compressible leading end portion **252a** of the guide wire **250a** are attracted by the magnet **260a**. This attraction causes the leading end portion **252a** of the guide wire **250a** to move into the open upper end portion of the trachea **228** rather than into the adjacent open upper end portion of the esophagus **226a**. In addition, movement of the leading end portion **252a** of the guide wire **250a** into the open upper end portion of the trachea **228** is promoted by the bend **380** in the tracheal tube **238a**. If desired, the magnet **260a** could initially be positioned on or above the patient's Adam's apple **234a** and moved downward from there.

[0156] As the guide wire continues to be inserted into the tracheal tube **238a**, the guide wire moves downward in the patient's trachea **228a**. At the same time, the magnet **260a** is moved downward along the outer side of the patient's neck **216a**. The indicia (not shown) on the guide rod **250a** provides an indication to an operator of the position of the leading end portion **252a** of the guide rod. This enables the operator to follow the leading end portion **252a** of the guide rod **250a** with the magnet **260a** as the guide rod continues to be moved through the tracheal tube **238a** into the patient's trachea **228a**.

[0157] Once the guide rod **250a** has been moved for a desired distance into the trachea **228a**, the guide rod **250a** is held stationary relative to the patient's trachea. The tracheal tube **238a** is then moved axially toward the left (as viewed in FIG. 11) and downward into the patient's trachea **228a**. During this downward movement of the tracheal tube **238a**, the guide rod **250a** blocks sidewise movement of the leading end of the tracheal tube so that the tracheal tube enters the larynx **230a** rather than the adjacent open upper end of the esophagus **226a**. As the tracheal tube **238a** continues to be inserted into the trachea **228a**, the leading end of the tracheal tube **238a** moves into engagement with the leading end portion **252a** of the guide rod **250a**. The leading end portion **252a** of the guide rod **250a** is then compressed somewhat by the leading end portion of the tracheal tube **238a** and moves into the passage in the tracheal tube. The tracheal tube **238a** is then moved further into the trachea **228a**.

[0158] After the tracheal tube **238a** has been positioned relative to the patient's trachea, the guide rod **250a** is withdrawn from the tracheal tube while the tracheal tube remains stationary relative to the patient's trachea **228a**. The positioning apparatus **256a** is then separated from the tracheal tube **238a**.

Embodiment of FIG. 12

[0159] In the embodiment of the invention illustrated in FIG. 1, a leading end portion **52** of the guide wire or rod **50** is inserted between the vocal cords or folds in the respiratory system **11** of the patient. It's contemplated that movement of the leading end portion **52** of the guide rod **50** between the

vocal cords **32** to a desired depth in the patient's trachea **28** may be facilitated by transmitting images of body tissue adjacent to the leading end portion of the guide rod to a viewing location outside of the patient's body. Since the embodiment of the invention illustrated in FIG. 12 is generally similar in the embodiment invention illustrated in FIGS. 1 and 2, similar numerals will be utilized to designate similar components, the suffix letter "b" being added to the numerals of FIG. 12 in order to avoid confusion.

[0160] A positioning apparatus **56b** is utilized to position a flexible guide rod **50b** relative to the patient's respiratory system **11b**. The positioning apparatus **56b** includes a base section **78b** which is connected with a positioning section **96b**. The positioning section **96b** engages the patient's Adam's apple **34b**. An arcuate member **108b** is connected with the base section **78b**. The guide rod **50b** is moveable relative to a guide section **114b** connected with arcuate member **108b**. The construction and the manner of using the positioning apparatus **56b** and guide rod **50b** is the same as was previously described in conjunction with the embodiment invention illustrated in FIGS. 1 and 2.

[0161] In accordance with a feature the embodiment invention illustrated in FIG. 12, light from a light source **400** is conducted through a fiber optic tube **402** to a leading end portion **52b** of the flexible guide rod **50b**. The light transmitted from the light source **400** through the fiber optic tube **402** to the leading end portion **52b** of the guide rod **50b** is directed from the leading end portion of the guide rod on to adjacent body tissue, in the manner indicated schematically at **404** in FIG. 12. If desired, a plurality of fiber optic tubes **402** could be provided to conduct light from the light source **400** to the leading end portion **52b** of the guide rod. These fiber optic tubes could be bundled together or could be spaced part at the leading end portion **52b** of the guide rod **50b**.

[0162] The light **404** which illuminates the body tissue immediately ahead of the leading end portion **52b** of the guide rod **50b** is reflected from the body tissue and is transmitted through a fiber optic tube **408** to the eye **410** of a viewer. This results in the transmission of an image of the body tissue adjacent to the leading end portion **52b** of the guide rod **50b** to the viewer to facilitate visualization, by the viewer, of the body tissue. If desired, a plurality of fiber optic tubes **408** could be provided to conduct light from the leading end portion **52b** of the guide rod to the eye **410** of the viewer. These fiber optic tubes could be bundled together or could be spaced apart at the leading end portion **52b** of the guide rod **50b**.

[0163] By visualizing the body tissue immediately ahead of the leading end portion **52b** of the guide rod **50b**, the viewer can determine the location of the leading end portion of the guide rod relative to the larynx **30b** and vocal chords **32b** of a patient as the leading end portion of the guide rod moves into the larynx and between the vocal chords. Since the light **404** illuminates body tissue immediately ahead of the leading end portion **52b** of the guide rod **50b**, the light enables the viewer to continuously visualize where the leading end portion **52b** of the guide rod **50b** is located along the insertion path in the respiratory system **11b** of the patient.

[0164] In the embodiment invention illustrated in FIG. 12, the fiber optic tubes **402** and **408** extend through the guide rod **50b** to enable an image of body tissue immediately ahead of the leading end portion **52b** of the guide rod to be transmitted to a viewer. It is contemplated that movement of a tracheal tube, corresponding to tracheal tube **38** of FIG. 2, along the

guide rod **50b** into the patient's respiratory system **11b** will be facilitated by illuminating body tissue immediately ahead of the leading end portion of the tracheal tube. Therefore, the side wall of the tracheal tube may be provided with fiber optic tubes which transmit light from a light source, such as a light source **400**, to a location immediately ahead of the leading end portion of the tracheal tube and transmit an image of illuminated body tissue immediately ahead of the leading end portion of tracheal tube to a viewer.

[0165] As the tracheal tube is moved along the guide rod **50b** into the patient's respiratory system, in the manner previously explained in conjunction with the embodiment invention illustrated in FIG. 2, body tissue immediately ahead of the leading end portion **52b** of the stationary guide rod **50b** is illuminated and body tissue immediately ahead of the tracheal tube is illuminated. Therefore, as the leading end portion of the tracheal tube approaches the vocal chords **32b**, a surgeon or other viewer can easily determine the location of the leading end portion of the tracheal tube relative to the vocal chords. As the leading end portion of the tracheal tube approaches the leading end portion **52b** of the guide rod, the image transmitted to the viewer will be of body tissue illuminated by both light transmitted from the leading end portion **52b** of the guide rod and light transmitted from the leading end portion of the tracheal tube.

[0166] The leading end portion of the tracheal tube may be inserted into trachea **28b** of a patient for greater distance than the distance which the guide rod **50b** is inserted into the trachea. As the leading end portion of the tracheal tube moves past the leading end portion **52b** of the guide rod **50b**, illumination from the leading end portion of the guide rod **50b** will be at least partially blocked from transmission back to the viewer through fiber optics in the tracheal tube. Therefore, the viewer will easily be able to determine when the leading end portion of the tracheal tube has moved past the leading end portion of the guide rod **50b**.

[0167] Although the eye **410** of a viewer has been schematically illustrated in FIG. 12, it is contemplated that the image transmitted through the fiber optic tube **408** may be displayed on a viewing screen. If this was done, the image transmitted through the fiber optic tube **408** would be transmitted to a computer and a viewing screen associated with the computer would display an image of the body tissue immediately ahead of the leading end portion **52b** of the guide rod **50b**. As the tracheal tube is moved along the guide rod into the patient's respiratory system **11b**, an image of body tissue immediately ahead of the leading end portion of the tracheal tube may also be transmitted to the computer.

[0168] A second computer screen may be utilized to display an image of the body tissue immediately ahead of the leading end portion of the tracheal tube. If this is done, the surgeon or other viewer would be able to see an image of body tissue immediately ahead the leading end portion **52b** of the guide rod **50b** and an image of body tissue immediately ahead of the leading end portion of the tracheal tube. When simultaneously viewing the two images on two separate screens or on separate portions of a single screen, the surgeon or other viewer would be able to determine the positions of the leading end portions of both the guide rod **50b** and the tracheal tube relative to each other and to the respiratory system **11b** of a patient.

[0169] Although it's preferred to utilize the tracheal tube and it's associated illumination system in conjunction with the guide rod **50b**, the tracheal tube may be utilized by itself.

Thus, fiber optic tubes which extend through the side wall of the tracheal tube and correspond to the fiber optic tubes **402** and **408** of FIG. 12, would provide an image of the body tissue immediately ahead of the leading end portion of the tracheal tube as the tracheal tube is moved into the patient's respiratory system **11b** along an insertion path. The image transmitted from the leading end portion of the tracheal tube to the eye of the viewer or to a display screen would enable a surgeon or other viewer to determine the location of the leading end portion of the tracheal tube relative to the patient's respiratory system **11b**.

[0170] When the tracheal tube and it's associated illumination and image transmitting systems are utilized without guide rod **50b**, the positioning apparatus **56b** may be modified to guide movement of the tracheal tube in much the same manner as in which the positioning apparatus **56b** is utilized to guide movement of the guide rod **50b**. If this is done, colored bands or other indicia could be provided on the tracheal tube to indicate the position of the tracheal tube in the same manner as previously discussed in connection with the guide rods **50** and **250**.

[0171] It is contemplated that the positioning apparatus **56b** may be used for purposes other than tracheal intubation. Thus, the positioning apparatus **56b** may be used to position devices other than the guide rod **50b** during endoscopic, arthroscopic, or fiber optic surgery at any one of many locations in a patient's body. A magnet, similar to the magnet **260** of FIGS. 4 and 7 may be used to steer a leading end portion of the device being positioned in the patient's body. The leading end portion of the device being positioned in the patient's body may be located at a position adjacent to or spaced a desired distance from a positioning section, corresponding to the positioning section **96b**, by the use of suitable indicia, which may be similar to the indicia used in conjunction with the guide rods **50** and **250**.

[0172] When the positioning apparatus **50b** is to be used to position a medicant or a device of any desired type at a selected location in a patient's body, the positioning section **96b** is positioned in engagement with a selected portion of the patient's body. The selected portion of the patient's body may be a portion of the patient's body other than the Adam's apple **34b**. Although it is believed that it will probably be preferred to engage an exterior surface on the patient's body with the positioning section **96b**, the positioning section could be placed in engagement with a surface disposed within the patient's body if desired.

[0173] While the positioning section **96b** is engaging the selected portion of the patient's body, the guide rod **50b** or a similar elongated member is moved relative to the guide section **114b** connected with the arcuate member **108b**. The leading end portion **52b** of the guide rod **50b** or similar elongated member is then moved into the patient's body. The leading end portion **52b** may be moved into the patient's body through a naturally occurring opening or through an incision formed in the patient's body.

[0174] The image transmitted through the guide rod or similar elongated member **50b** to the viewer will indicate when the leading end portion **52b** has moved to a desired position in the patient's body. Once the leading end portion **52b** of the guide rod or similar elongated member **50b** has moved to the desired position relative to the patient's body, any desired procedure may be performed in the patient's body. For example, a surgical procedure could be conducted with one or more devices connected with the leading end

portion **52b** of the guide rod or similar elongated member. The positioning apparatus **56b** may be used to position a therapeutic agent or device at the desired position in the patient's body.

Embodiment of FIGS. 13 and 14

[0175] In the embodiment invention illustrated in FIG. 12, the light source **400** and fiber optic tube **402** function as an emitter which emits illumination **404** onto body tissue immediately ahead of the leading end portion **52b** of the guide rod **50b** to facilitate visualization of the body tissue. In the embodiment invention illustrated in FIGS. 13 and 14, a plurality of emitters are positioned adjacent to an outer side surface of the patient's neck. A detector on a leading end portion of a guide rod is moved into the patient's respiratory system. Since the embodiment invention illustrated in FIGS. 13 and 14 is generally similar to the embodiment invention illustrated in FIGS. 1, 2 and 12, similar numerals will be utilized to identify similar components, the suffix letter "c" being associated with the numerals of FIGS. 13 and 14 to avoid confusion.

[0176] A positioning apparatus **56c** (FIG. 13) is utilized to position a flexible guide wire or rod **50c** relative to a respiratory system **11c** of a patient. The respiratory system **11c** of the patient extends from the mouth **12c** through a larynx **30c** to a trachea **28c** of the patient. The positioning apparatus **56c** engages an Adam's apple **34c** of a patient to locate the guide rod **50c** relative to the patient's respiratory system **11c**.

[0177] The positioning apparatus **56c** has the same general construction and mode operation as the positioning apparatus **56** of FIGS. 1 and 2. The positioning apparatus **56c** includes a base section **78c** having a body section **86c** which is pivotally connected with a positioning section **96c**. The positioning section **96c** engages an outer surface of the neck of the patient adjacent to the Adam's apple **34c** to locate the positioning apparatus **56c** relative to the patient's respiratory system **11c**. If desired, the positioning apparatus **96c** could include a collar which would extend around the patient's Adam's apple **34c** in the manner previously described in conjunction with the embodiment invention illustrated in FIG. 7. Alternatively, the positioning apparatus **96c** could include a pair of fingers which engage opposite lateral sides of the patient's Adam's apple.

[0178] An arcuate member **108c** is connected with and is moveable relative to the body section **86c** of the positioning apparatus **56c** at a connection **110c**. A flexible guide rod **50c** is axially slidable relative to a guide section **114c** which is connected with the arcuate member **108c**. The construction of the positioning apparatus **56c** is the same as was previously described in conjunction with the embodiment invention illustrated in FIGS. 1 and 2.

[0179] In accordance with a feature of the embodiment invention illustrated in FIG. 13, a sensor assembly **420** is provided to inform a surgeon or other user of the positioning apparatus **56c**, of the position of the guide rod **50c** relative to the patient's respiratory system **11c**. The sensor assembly **420** includes an emitter portion **424** (FIG. 14) which provides an output and a detector portion **426** (FIG. 13) which responds to the output from the emitter portion **424**. In the embodiment of invention illustrated in FIGS. 13 and 14, the emitter portion **424** is positioned on an outer side surface of the neck of the patient adjacent to the Adam's apple **34c**. The detector portion **426** is connected with a leading end portion **52c** of a guide rod **50c**. However, it should be understood that the

emitter portion **424** could be connected with the guide rod **50c** and the detector portion **426** positioned adjacent to the Adam's apple **34c** of the patient.

[0180] In the illustrated embodiment invention, the emitter portion **424** of the sensor assembly **420** includes a plurality of emitters units **430** which are positioned an array which extends around the Adam's apple **34c** (FIG. 14) of the patient. The emitter units **430** are secured to the neck of the patient by a suitable adhesive. The emitter units **430** may be positioned in any desired spatial relationship with the patient's Adam's apple **34c**.

[0181] Alternatively, the emitter units **430** may be connected with the positioning section **96c**. Thus, the positioning section **96c** of the positioning apparatus **56c** is provided with three fingers which engage the neck of the patient adjacent to the Adam's apple **34c**. Each of the emitter units **430** may be connected with one of the fingers of the positioning section **96c**. The positioning section **96c** would accurately locate the emitter units **430** relative to the patient's Adam's apple **34c**.

[0182] In the embodiment of the invention illustrated in FIG. 13, the positioning section **96c** engages the Adam's apple **34c** and the emitter units are disposed in a generally circular array which extends around the Adam's apple **34c**. However, it should be understood that the emitter units **430** could be connected with a collar, similar to the collar **306** of FIG. 7. The collar may be connected with the positioning section **96c** (FIG. 13). Alternatively, the collar could be separate from the positioning apparatus.

[0183] Although it is preferred to utilize the positioning apparatus **56c** in conjunction with the guide rod **50c**, in the manner previously described in conjunction with the embodiment of the invention illustrated in FIG. 1, it is contemplated that the positioning apparatus **56c** may be omitted and the guide rod **50c** moved along an insertion path into the patient's respiratory system without benefit of the assistance provided by the positioning apparatus. If this is done, the emitter units **430** (FIG. 14) could be connected with a support structure which holds the emitter units **430** in a fixed relationship relative to each other and facilitates positioning of the emitter units relative to the patient's Adam's apple **34c**. For example, a positioning section having a plurality of fingers, could be manually centered on the patient's Adam's apple **34c** to locate the emitter units **430** relative to the Adam's apple. Similarly, a collar, corresponding to the collar **306** of FIG. 7, could be provided on a circular or oval support which would extend around the patient's Adam's apple **34c** to locate the emitter units **430** relative to the patient's Adam's apple. Regardless of the specific structure which is utilized to position the emitter units **430** relative to each other, this apparatus could be manually positioned relative to the patient's Adam's apple **34c** without being connected with a positioning apparatus having a construction similar to the construction of the positioning apparatus **56c**.

[0184] When the positioning apparatus **56c** is to be utilized to assist in the positioning of the guide rod **50c** relative to the patient's respiratory system **11c**, the positioning section **96c** is positioned in engagement with the patient's Adam's apple **34c**. The emitter units **430** may be suitably mounted on the positioning section **96c**. This would locate the emitter units **430** relative to the patient's Adam's apple **34c** (FIG. 14). It should be understood that the emitter units **430** could be mounted on a support other than the positioning section **96c** if desired. Of course, the emitter units **430** may be secured directly to the neck of the patient by a suitable adhesive, as

illustrated in FIG. 14. When this is done, a support structure interconnecting the emitter units 430 may be used to facilitate positioning of the emitter units relative to the patient's Adam's apple 34c.

[0185] The arcuate member 108c is then positioned axially along the body section 86c. When the arcuate member 108c has been moved to a desired position relative to the body section 86c, the connection 110c is secured to hold the arcuate member against axial movement along the body section. The arcuate member 108c is then moved relative to the body section 86c to position the guide section 114c and the leading end portion 52c of the guide rod 50c in alignment with the entrance to the patient's mouth 11c. The guide rod 50c is then moved into the patient's respiratory system 11c along an insertion path.

[0186] As the guide rod 50c is moved along the insertion path into the patient's respiratory system 11c, the detector portion 426 of the sensor assembly 420 approaches the emitter units 430. As this occurs, the detector portion provides an output over leads 434 and 436 to a computer or micro processor 438. The computer or micro processor has an output, indicated schematically at 440, which can be viewed by a surgeon or other individual moving the guide rod 50c along the insertion path into the patient's respiratory system 11c.

[0187] The computer output may include a display having a schematic illustration of a typical patient's respiratory system. The positions of the emitter units 430 relative to the typical respiratory system and the position of the detector portion 426 relative to the emitter units 430 would be indicated on the display. Thus, a display screen connected with the computer 438 has an illustration representative of the patient's respiratory system 11c. A plurality of indicators are provided on the display screen to indicate the positions of the emitter units 430 relative to the schematic illustration of the patient's trachea. An indicator is provided to indicate the position of the leading end of the guide rod 50c relative to the schematic illustration of the patient's respiratory system. The display screen has one illustration of the patient's respiratory system 11c as viewed in a medial plane and another illustration of the patient's respiratory system as viewed in a frontal plane. Indicators corresponding to the emitter units 430 and detector 426 are provided in both illustrations.

[0188] As the leading end portion 52c of the guide rod 50c moves along the insertion path into the patient's respiratory system 12c, the detector portion 426 of the sensor assembly 420 approaches the emitter portion 424 of the sensor assembly. As this occurs, the strength of the output from the detector portion 426 through the leads 434 and 436 increases. As the strength of the output from the detector portion 426 increases, the computer and the associated display indicates to an operator of the apparatus 56c that the leading end portion 52c of the guide rod 50c is approaching a junction between the patient's esophagus 26c and the pharynx.

[0189] If the guide rod continues movement along its intended course of insertion, that is, into the patient's larynx 30c and not into the patient's esophagus 26c, the strength of the output signal provided by the detector portion 426 will increase. However, if the leading end portion 52c of the guide rod 50c enters the patient's esophagus 26c, the strength of the output signal from the detector portion 426 will decrease. The decreasing strength of the signal from the detector portion 426 provides a clear indication to the operator of the apparatus 56c that the leading end portion 52c of the guide rod 50c has deviated from its intended course.

[0190] As the detector portion 426 of the sensor assembly 420 moves between the patient's vocal chords 32c into alignment with the emitter portion 424 of the sensor assembly 420, the strength of the signal transmitted to the computer 438 will be maximized. As the guide rod 50c continues to be moved into the patient's trachea 28c along the insertion path, the strength of the signal transmitted through the leads 434 and 436 to the computer 438 will decrease to indicate to the operator of the apparatus 56c that the leading end portion 52c of the guide rod has moved past the patient's Adam's apple 34c.

[0191] Although it is believed that it will be preferred to display the output of the computer 438 in association with one or more illustrations of the patient's respiratory system 11c in the manner previously mentioned, the computer output information could be transmitted in a different manner if desired. For example, the computer 438 could have a light display system which indicates how close the detector 426 is to the emitter units 430. Similarly, the computer 438 could have an audio output which indicates how close the detector 426 is to the emitter units. Of course, the computer could have an output which is a combination of a display screen, lights and/or audio signals.

[0192] Once the guide rod 50c has been moved to the desired position along the patient's respiratory system 11c, the positioning apparatus 56c may be disconnected from the guide rod 50c. A tracheal tube, corresponding to tracheal tube 38 of FIG. 2, is then moved along the guide rod 50c into the patient's trachea 28c. The manner in which the tracheal tube is moved along the guide rod 50c into the patient's trachea 28c is the same as was previously discussed in conjunction with the embodiment of the invention illustrated in FIGS. 1 and 2. A magnet, corresponding to the magnet 260 of FIGS. 4 and 7, may be utilized to steer the leading end portion of the guide rod 50c. If desired, an electromagnet which can be turned on and off may be utilized.

[0193] The tracheal tube which is utilized in association with the guide rod 50c of FIG. 13 may have the same construction as the tracheal tube 38 utilized with the guide rod 50 of FIG. 2. Alternatively, the tracheal tube utilized with the guide rod 50c may have a second detector portion, having the same construction as the detector portion 426 of the guide rod 50c. If the tracheal tube is provided with a second detector portion, the emitter portion 424 of the sensor assembly 420 is maintained in position relative to the patient's Adam's apple 34c.

[0194] By providing the tracheal tube with a second detector portion, and by maintaining the emitter portion 424 in position relative to the patient's Adam's apple 34c, the output from the second detector portion may be utilized to locate the leading end portion of the tracheal tube as the tracheal tube is moved along the guide rod 50c into the patient's respiratory system 11c. If this is done, leads, corresponding to the leads 434 and 436 would extend along the side wall of the tracheal tube from the second detector portion to the computer 438. The output from the computer 438 would indicate the position of the leading end portion of the tracheal tube relative to the emitter 424. The output from the second detector portion on the leading end portion of tracheal tube would indicate the position of the leading end portion of the tracheal tube relative to the position of the leading end portion of the guide rod 50c.

[0195] The output from the computer may be a display having the construction previously described in conjunction with the guide rod 50c. Thus, a display screen connected with

the computer 438 has an illustration representative of the patient's respiratory system 11c. A plurality of indicators are provided on the display screen to indicate the positions of the emitter units 430 relative to the patient's trachea. An indicator is provided to indicate the position of the leading end of the tracheal tube relative to the patient's respiratory system. The display screen has one illustration of the patient's respiratory system 11c as viewed in a medial plane and another illustration of the patient's respiratory system as viewed in a frontal plane. Indicators corresponding to the emitter units 430 and detector on the tracheal tube are provided in both illustrations.

[0196] In the embodiment of the invention illustrated in FIGS. 13 and 14, the emitter units 430 are magnets which emit a magnetic field. The detector portion 426 is a magnetometer which responds to variations in the strength of a magnetic field. Thus, the output from the detector portion 426 increases as the detector portion moves closer to the patient's Adam's apple 34c and the magnets forming the emitter units 430. The detector portion 436 may be Hall effect device, magnetoresistor, or a galvanometer device. Regardless of what specific type of magnetic field responsive device is utilized to form the detector portion 426 of the sensor assembly, the output from the detector portion will vary as the distance between the leading end portion 52c of the guide rod 50c and the magnets in the emitter units 430 varies.

[0197] In the embodiment of the invention illustrated in FIGS. 13 and 14, the sensor assembly 420 is the type which responds to a magnetic field. However, it is contemplated that the sensor assembly 420 could be constructed so as to respond to other types of emissions. For example, light sources could be utilized as the emitter units 430 and the detector portion 436 may be a photo cell which responds to variations in the amount of light received. Alternatively, the emitter units 430 could be sources of radio frequency radiation and the detector portion 426 could be constructed so as to have an output which varies as the distance between the detector portion and the sources of radio frequency radiation varies. If desired, the emitter units 430 could be ultrasonic transducers and the detector 426 could respond to ultrasonic energy.

[0198] The sensor assembly 420 has been illustrated in FIGS. 13 and 14 in association with the positioning apparatus 56c. However, it should be understood that the sensor assembly 420 could be utilized in association with the positioning apparatus 256 of FIGS. 4-10 or the positioning apparatus 256a of FIG. 11. If this was done, the use of the magnet 260 or 260a (FIGS. 4, 7 and 11) may be eliminated to avoid interference with magnetic fields from the emitter units 430. Of course, if the emitter units provided outputs which were not affected by the magnetic field from the magnets 260 and 260a, the magnets 260 and 260a could still be utilized.

[0199] The positioning apparatus 56c and sensor assembly 420 have been illustrated in association with a tracheal intubation procedure. It is contemplated that the positioning apparatus 56c and/or sensor assembly 420 may be used in association with other medical procedures if desired. For example, the positioning apparatus 56c and/or sensor assembly 420 may be used in the performance of endoscopic, arthroscopic or fiber optic surgical procedures. The positioning apparatus 56c and/or sensor assembly 420 may be used in association with surgery on joints or other portions of a patient's body. The positioning apparatus 56c and/or sensor assembly 420 may be used to deliver medicants to a desired location in a patient's body

Embodiments of FIGS. 15 and 16

[0200] In the embodiment of the invention illustrated in FIGS. 13 and 14, the emitter portion 424 of the sensor assembly 420 is disposed adjacent to the outer surface of the neck of the patient while the detector portion 426 of the sensor assembly is connected with the guide rod 50c. In the embodiment of the invention illustrated in FIGS. 15 and 16, the detector portion of the sensor assembly is disposed adjacent to the outer surface of the patient's neck and the emitter portion of the sensor assembly is connected with the leading end portion of the guide rod. Since the embodiment of the invention illustrated in FIGS. 15 and 16 is generally similar to the embodiment of the invention illustrated in FIGS. 1, 2, 13 and 14, similar numerals will be utilized to identify similar components, the suffix letter "d" being associated with the numerals of FIGS. 15 and 16 to avoid confusion.

[0201] The positioning apparatus 56d is utilized to position a flexible guide rod 50d relative to a patient's respiratory system 11d. The positioning apparatus 56d includes a base section 78d having a body section 86d and a positioning section 96d. An arcuate member 108d is connected with the body section 86d at a connection 110d. When the arcuate member 108d has been moved to a desired position along the base section 86d, the connection 110d is actuated to hold the member 108d against axial movement along the body section 86d. When the guide section 114d has been moved into alignment with the patient's mouth 12d, the connection 110d is again actuated to hold the arcuate member 108d against movement relative to the base section 86d.

[0202] The guide section 114d cooperates with the flexible guide rod 50d to position the guide rod during movement of the guide rod into the patient's respiratory system 11d along an insertion path. The general construction and mode of operation of the positioning apparatus 56d is the same as was previously described in conjunction with the positioning apparatus 56 of FIGS. 1 and 2.

[0203] In accordance with a feature of this embodiment of the invention, a sensor assembly 420d is provided to sense when the guide rod 50d has moved to a desired position relative to the patient's respiratory system 11d. The sensor assembly 420d includes a detector portion 426d (FIG. 16) and an emitter portion 424d (FIG. 15).

[0204] The sensor portion 426d of the sensor assembly 420d is positioned on the outer surface of a neck of a patient (FIG. 16) adjacent to the patient's Adam's apple 34d. The emitter portion 424d is connected with a leading end portion 52d of the guide rod 50d (FIG. 15). The sensor portion 426d (FIG. 16) is mounted directly on the patient's neck by a suitable adhesive. However, if desired, the sensor portion 426d could be connected with the positioning section 96d of the positioning apparatus 56d. If this is done, when the positioning section 96d of the positioning apparatus 56d is positioned in engagement with the patient's Adam's apple 34d, the sensor portion 426 of the sensor assembly 420d would also be positioned relative to the patient's Adam's apple. However, if desired, the sensor portion 426d could be mounted on a support and positioned relative to the patient's Adam's apple 34d independently of the positioning section 96d of the positioning apparatus 56d.

[0205] The sensor portion 426d of the sensor assembly 420d includes a plurality of sensor units 440 which are disposed in an array around the patient's Adam's apple 34d (FIG. 16). The sensor units 440 have leads 442 which are connected with a computer or micro processor 444. The com-

puter or micro processor 444 has an output, indicated schematically in 446 in FIG. 16, which is indicative of the position of the emitter portion 424d of the sensor assembly 420d relative to the position of the sensor portion 426d of the sensor assembly. The emitter portion 424d of the sensor assembly 420d is connected with the leading end portion 52d of the guide rod 50d.

[0206] During use of the positioning apparatus 56d, the leading end portion 52d of the flexible guide rod 50d is aligned with the mouth 12d of the patient. The guide rod 50d is then moved into the patient's respiratory system 11d along an insertion path. As the guide rod 50d is moved into the patient's respiratory system 11d, the emitter portion 424d of the sensor assembly 420d approaches the sensor portion 426d of the sensor assembly 420d. As this occurs, the strength of the output from the sensor units 440 increases.

[0207] The increasing strength of the output from the sensor units 440 results in a change in the output 446 from the computer 444. The output 446 from the computer 444 may take the form of a display which schematically indicates the position of the emitter portion 424d of the sensor assembly 420d relative to the sensor portion 426d of the sensor assembly. Thus, a display screen for the computer 444 may have a schematic illustration representative of a typical patient's respiratory system. The display screen would indicate the position of the sensor portion 426d of the sensor assembly 420d relative to the patient's respiratory system and the position of the emitter portion 424d of the sensor assembly 420d relative to the patient's respiratory system. Since the emitter portion 424d is connected with the leading end portion 52d of the guide rod 50d, the display for the computer 444 would indicate the position of the leading end portion 52d of the guide rod relative to the patient's Adam's apple 34d.

[0208] Although it is believed that the use of a display screen may be preferred, the output 446 from the computer 444 could take a different form if desired. For example, the computer could have an audio output. Alternatively, a display graph formed of a series of lights could provide a visual output. As the emitter portion 424d approaches the sensor units 440, the number of illuminated lights in the series of lights would increase. When the emitter portion 424d is aligned with the center of the array of sensor units 440 and the patient's Adam's apple 34d, the entire series of lights would be illuminated. Of course, the output 446 from the computer 444 could include both audio and visual outputs.

[0209] In the embodiment of the invention illustrated in FIGS. 15 and 16, the emitter portion 424d of the sensor assembly 420d is a magnet which emits a magnetic field. The sensor portion 426d of the sensor assembly 420d has an output which varies as a function of the strength of the magnetic field at the sensor units. Therefore, as the leading end portion 52d of the guide rod 50d approaches the patient's Adam's apple 34d, the strength of the magnetic field to the sensor units 440 increases and the output transmitted to the computer 444 increases.

[0210] In the specific embodiment of the invention illustrated in FIG. 16, the sensor units 440 are Hall effect devices. However, it is contemplated that other known devices which respond to variations in a magnetic field may be utilized in place of the Hall effect devices which form the sensor units 440. For example, magnetoresistors could be utilized as the sensor units 440 in place of the Hall effect devices.

[0211] Once the guide rod 50d has been positioned relative to the patient's respiratory system 11d, the positioning appa-

ratus 56d is disconnected from the guide rod 50d while the guide rod is maintained stationary relative to the patient's respiratory system 11d. A flexible tracheal tube, corresponding to the tracheal tube 38 of FIG. 2, is then moved along the guide rod 50d into the patient's respiratory system 11d. The manner of insertion of the tracheal tube into the patient's respiratory system 11d, by sliding the tracheal tube along the guide rod 50d, is the same as was previously described in conjunction with the embodiment of the invention illustrated in FIG. 2.

[0212] It is contemplated that the sensor portion 426d of the sensor assembly 420d can be utilized in association with the tracheal tube. Thus, the tracheal tube can be provided with a second emitter portion having the same construction as the emitter portion 424d. In the embodiment of the invention illustrated in FIGS. 15 and 16, a magnet, which emits a magnetic field, would be mounted on a leading end portion of the tracheal tube.

[0213] As the tracheal tube having an emitter, is moved along the guide rod 50d, the magnet on the leading end portion of the tracheal tube would have an effect on the sensor units 440. The effect on the magnet on the sensor units 440 increases as the leading end portion of the tracheal tube approaches the patient's Adam's apple 34d. It is contemplated that the tracheal tube may be inserted into the patient's trachea 28d further than the guide rod 50d. If this is done, the output from the sensor units 440d diminishes in magnitude as the leading end portion of the tracheal tube is moved down the patient's trachea past the sensor units.

[0214] Although it is preferred to utilize the sensor assembly 420d in association with the positioning apparatus 56d, the sensor assembly could be utilized separately from the positioning apparatus. For example, the sensor units 440 may be mounted in an array on a separate support structure. The support structure would be positioned in an engagement with the exterior of the patient's neck with the array of sensor units 440 centered about the patient's Adam's apple, in the manner illustrated schematically in FIG. 16.

[0215] The guide rod 50d would then be moved along the patient's respiratory system 11d without benefit of the positioning apparatus 56d. As the guide rod 50d moves along the patient's respiratory system 11d, the strength of the magnetic field from the emitter portion 424d of the sensor assembly 420d detected by the sensor units 440 would increase. This would result in an increase in the output from the sensor units 440 to the computer 444. The output 446 from the computer 444 would indicate to the operator moving the guide rod 50d, the position of the guide rod along an insertion path into the patient's respiratory system 11d.

[0216] Once the guide rod 50d has been positioned in the foregoing manner relative to the patient's respiratory system 11d, without benefit of the positioning apparatus 56d, the tracheal tube would be moved along the guide rod into the patient's respiratory system 11d. The tracheal tube could have the same construction and move in the same manner as the tracheal tube 38 of FIG. 2.

[0217] Alternatively, the tracheal tube could be provided with a second emitter portion, corresponding to the emitter portion 424d of the sensor assembly 420. Thus, a magnet could be provided on the leading end portion of the tracheal tube. As the leading end portion of the tracheal tube moves along the insertion path into the patient's respiratory system 11d, the magnetic field detected by the sensor units 440 would increase due to the magnet connected with the leading end

portion of the tracheal tube approaching the magnet on the leading end portion **52d** of the guide rod **50d**.

[0218] It is also contemplated that the tracheal tube could be positioned relative to the patient's respiratory system **11d** without benefit of the guide rod **50d**. The tracheal tube would be provided with an emitter corresponding to the emitter **424d**. As tracheal tube is moved into the patient's respiratory system **11d** without benefit of the guide rod **50d**, the output from the emitter connected to the leading end portion of the tracheal tube would be detected by the sensor units **440**. The output from the sensor units **440** would indicate the position of the leading end portion of the tracheal tube relative to the patient's respiratory system **11d**.

[0219] In the embodiment of the invention illustrated in FIGS. **13-16**, magnets have been utilized as emitter units. The magnets which form the emitter portion **424** of the sensor assembly **420** are permanent magnets formed of a strongly magnetizable material such as cobalt or neodymium. Of course, other known magnetizable materials having saturation magnetization values, such as cerium, praseodymium and/or samarium with cobalt and/or other materials could be used. Alternatively, the magnets in the emitter portion **424** (FIG. **14**) and **424d** (FIG. **15**) could be electromagnets.

[0220] The detector portion **426** (FIG. **13**) and **426d** (FIG. **16**) of the sensor assemblies **420** and **420d** may be any known device which respond to changes in the strength and/or direction of a magnet field. For example, the detector portions **426** include one or more Hall effect devices and/or one or more magnetoresistors.

[0221] Although the emitter portions **424** and **424d** of the sensor assemblies **420** and **420d** have been described herein as emitting magnetic fields, it is contemplated that the emitter portions **424** and **424d** could have outputs other than a magnetic field. For example, the emitter portions **424** and/or **424d** (FIGS. **14** and **15**) could be miniaturized radio frequency devices. Thus, the emitter portions of the sensor assemblies could be formed by radio signal transmitters having miniaturized radio circuitry which provide a radio frequency output signal. If a radio frequency transmitter is utilized in the emitter portion **424** or **424d** of the sensor assemblies, the sensor portion **426** or **426d** would be a radio frequency receiver. The radio frequency receiver could include a receiving antenna which receives radio frequency signals. The field of the antenna may be controlled by appropriate placement, orientation, and/or configuration of the antenna.

[0222] Alternatively, the emitter portions **424** and **424d** could emit ultrasonic energy. The sensor portion **426** or **426d** would respond to ultrasonic energy.

Embodiment of FIGS. **17** and **18**

[0223] In the embodiment of the invention illustrated in FIGS. **13** and **14**, the sensor assembly **420** includes a detector portion **426** which is disposed on the leading end portion **52c** of the guide rod **50c** and responds to a magnetic field. The operator of the positioning apparatus **56c** is informed, by a display system connected with the computer **438**, of the position of the leading end portion **52c** of the guide rod **50c** relative to the patient's respiratory system **11c**. In the embodiment of the invention illustrated in FIG. **17** and **18**, the leading end portion of the guide rod is steerable to enable the operator to alter the course of movement of the leading end portion of the guide rod to maintain the leading end portion of the guide rod on a desired insertion path into the patient's respiratory system. Since the embodiment of the invention

illustrated in FIGS. **17** and **18** is generally similar in the embodiment of the invention illustrated in FIGS. **13-16**, similar numerals will be utilized to designate similar components, the suffix letter "e" being associated with the numerals of FIGS. **17** and **18** to avoid confusion.

[0224] The embodiment of the invention illustrated in FIGS. **17** and **18** is utilized with a positioning apparatus having the same construction as the positioning apparatus of FIGS. **1**, **2**, and **13-16**. However, the embodiment of the invention illustrated in FIGS. **17** and **18** could be used with the positioning apparatus **256** and/or **256a** of FIGS. **4-11** if desired. The guide rod **50e** of FIGS. **17** and **18** is provided with a steering apparatus **460**. The steering apparatus **460** is operable to change the course of movement of the leading end portion **52e** of the flexible guide rod **50e** as the guide rod moves along the insertion path into the patient's respiratory system.

[0225] The steering apparatus **460** applies force against body tissue in the patient's respiratory system to deflect the leading end portion **52e** of the flexible guide rod **50e** away from an undesired course of movement. For example, when the leading end portion of the guide rod **50e** is approaching a junction between the patient's esophagus **26** (FIG. **1**) and trachea **28**, the steering apparatus **460** (FIGS. **17** and **18**) may be activated to deflect the leading end portion **52e** of the guide rod **50e** away from the entrance to the patient's esophagus. Similarly, when the leading end portion **52e** of the guide rod **50e** is approaching the larynx **30**, the steering apparatus **460** may be activated to align the leading end portion **52e** of the guide rod with an opening between vocal chords in the patient's larynx.

[0226] In the illustrated embodiment of the invention, the steering apparatus **460** includes a plurality of expandable elements **464**, **466** and **468** (FIG. **18**). Although three expandable elements **464-468** have been illustrated as being disposed in a circular array about the leading end portion **52e** of the guide rod **50e**, a greater or lesser number of expandable elements could be provided in association with the leading end portion of the guide rod if desired.

[0227] The expandable elements **464**, **466** and **468** are individually activatable so that one, two or all three of the expandable elements can be expanded. For example, just the expandable element **464** (FIG. **18**) may be expanded to apply force against the leading end portion **52e** of the guide rod **50e** to move the guide rod downward (as viewed in FIG. **18**) relative to a path of movement of the guide rod through the patient's respiratory system. Alternatively, the expandable elements **466** and **468** may be expanded at the same time to deflect the leading end portion **52e** of the guide rod **50e** upward (as viewed in FIG. **18**). It is believed that it may be desired to center the leading end portion **52e** of the guide rod **50e** in a passage in the patient's respiratory system. When this is to be done, all three expandable elements **464**, **466**, and **468** would be expanded.

[0228] In the illustrated embodiment of the invention, the expandable elements **464**, **466** and **468** are balloons or bladders which are expanded under the influence of fluid pressure, that is, under the influence of either a gas or a liquid. To enable the expandable elements **464**, **466** and **468** to be individually expanded, conduits **472**, **474** and **476** are each connected in fluid communication with one of the expandable elements **464**, **466** or **468**. For example, when the expandable element **464** is to be expanded, fluid under pressure is connected through the conduit **472** to the expandable element **464**. Similarly,

when the expandable element **466** is to be expanded, fluid under pressure is connected through the conduit **474** to the expandable element **466**. Finally, when the expandable element **468** is to be expanded, fluid under pressure is connected through the conduit **476** to the expandable element **468**.

[0229] After one or more of the expandable elements **464**, **466** and/or **468** have been expanded to steer the leading end portion **52e** of the guide rod **50e**, the expandable elements **464**, **466** and/or **468** are contracted. This may be accomplished by connecting the conduits **472**, **474** and/or **476** with a source of suction or low pressure. The expandable elements **464**, **466** and **468** are contracted under the influence of their own natural resilience. If desired, springs could be provided in association with the expandable elements to contract the expandable elements **464**-**468**.

[0230] The contracted expandable elements **464**, **466** and **468** are disposed in engagement with an outer side surface of the leading end portion **52e** of the guide rod **50e**. If desired, recesses could be provided in the leading end portion of the guide rod **50e** to receive each of the expandable elements **464**, **466** and **468** when the expandable elements are in their contracted condition.

[0231] It is believed that it will be preferred to form the expandable elements **464**, **466** and **468** of a resiliently stretchable polymeric material so that the expandable elements can be expanded, under the influence of fluid pressure, by stretching the material of the expandable elements. When the expandable elements are to be deflated, the resiliently stretched elastomeric material of the expandable elements **464**-**468** will tend to force fluid out of the expandable elements and cause them to return to their contracted conditions. When the retracted, the expandable elements **464**, **466** and **468** are disposed in either separate recesses or a single annular recess which extends around the leading end portion of the guide rod **50e**. The contracted expandable elements do not project outward from the outer side surface of the guide rod **50e**. Alternatively, the contracted expandable elements **464**-**468** could be contracted, under the influence of their own natural resilience, into tight abutting engagement with the outer side surface of the guide rod **50e**.

[0232] It is contemplated that the conduits **472**, **474** and **476** and expandable elements **464**, **466** and **468** may be formed in a manner similar to that disposed in U.S. patent application Ser. No. 08/470,142 filed Jun. 6, 1995 by Peter M. Bonutti et al. and entitled Method Of Using Expandable Cannula. The disclosure of the aforementioned application Ser. No. 08/470,142 is hereby incorporated herein in its entirety by this reference thereto. Alternatively, the expandable elements **464**, **466** and **468** could be formed in manners similar to that disclosed in U.S. Pat. No. 3,833,003 and/or 5,197,971.

[0233] Although the illustrated expandable elements **464**-**468** are expanded under the influence of fluid pressure, they could be expanded in a different manner if desired. For example, mechanical actuators could be provided. The mechanical actuators may be utilized to move members which are not balloons.

[0234] In order to enable an operator of the positioning apparatus to determine the location of the leading end portion **52e** of the guide rod **50e** relative to the patient's respiratory system, a sensor assembly, similar to the sensor assembly **420** of FIGS. **13** and **14**, is utilized in association with the steering apparatus **460**. In the embodiment of the invention illustrated in FIG. **17**, the detector portion **426e** of the sensor assembly includes a detector **480** which responds to an output from an

emitter portion of the sensor assembly. The detector **480** is enclosed by a soft dome or cap **482** which forms part of the leading end portion **52e** of the guide rod **50e**. The dome or cap **482** cushions engagement of the leading end portion **52e** of the guide rod **50e** with body tissue along the patient's respiratory system. In addition, the dome **482** protects the detector portion **426e**.

[0235] The detector **480** may be a Hall effect device which cooperates with emitters, which are magnets, in the manner described in conjunction with FIGS. **13** and **14**. Alternatively, the detector **480** may respond to radio frequency radiation. If desired, the detector **480** could be constructed so as to respond to ultrasonic energy. Rather than providing a detector **480** on the leading end portion **52e** of the guide rod **50e**, an emitter could be provided in the manner described in conjunction with FIGS. **15** and **16**.

[0236] The detector portion **426e** (FIG. **17**) is connected with a computer, similar to the computer **438** of FIG. **13**, by a lead **486** (FIG. **17**). The output from the computer indicates to an operator the position of the leading end portion **52e** of the guide rod **50e** relative to the patient's respiratory system. The output of the computer will also indicate to the operator when the leading end portion **52e** of the guide rod **50e** may deviate from the intended course of insertion of the guide rod into the patient's respiratory system.

[0237] When the output from the computer indicates that the leading end portion of the guide rod may not move along the intended insertion path, the operator may initiate expansion of one or more of the expandable elements **464**-**468**. The expandable elements will apply force against the patient's body tissue and against the leading end portion **52e** of the guide rod **50e** to deflect the guide rod in such a manner as to maintain the guide rod on its intended insertion path into the patient's respiratory system.

[0238] As was previously described in conjunction with the embodiments of the invention illustrated in FIGS. **13**-**16**, a visual display system, illustrative of the patient's respiratory system, may be connected with the computer which receives the output from a sensor assembly **420** or **420d**. By viewing an illustration depicting the location and path of movement of the leading end portion **52e** of the flexible guide rod **50e**, an operator will know when to expand one or more of the expandable elements **464**, **466** and **468**.

[0239] It is contemplated that the steering apparatus **460** and position sensing assembly may be used with devices for purposes other than tracheal intubation. For example, the steering apparatus **460** and position sensing assembly used with the guide rod **50e** of FIG. **17** could be used in association with a device which is used to position medicant at a selected location in a patient's body. It is also contemplated that the steering apparatus **460** and position sensing assembly could be used in conjunction with endoscopic, arthroscopic, or fiber optic surgery.

Embodiment of FIG. **19**.

[0240] In the embodiment of the invention illustrated in FIGS. **17** and **18**, the steering apparatus **460** is disclosed in conjunction with the guide rod **50e** which is used with a sensor assembly, corresponding with the sensor assembly **420** of FIG. **13**, in which the detector portion is disposed on the leading end portion **52e** of the guide rod. In the embodiment of the invention illustrated in FIG. **19**, the steering apparatus is disposed in association with a guide rod having an emitter portion of a sensor assembly disposed on the lead-

ing end portion of the guide rod in the manner illustrated in FIGS. 15 and 16. Since the embodiment of the invention illustrated in FIG. 19 is generally similar to the embodiments of the invention illustrated in FIG. 13-18, similar numerals will be utilized to designate similar components, the suffix letter "f" being associated with the numerals of FIG. 19 in order to avoid confusion.

[0241] A guide rod 50f has a leading end portion 52f. The guide rod 50f is used with a positioning apparatus similar to the positioning apparatus 56d of FIG. 15. The flexible guide rod 50f (FIG. 19) is associated with a sensor assembly corresponding to the sensor assembly 420d of FIG. 15. Thus, the guide rod 50f has an emitter portion 424f (FIG. 19) which is connected with the leading end portion 52f of the guide rod. The output from the emitter portion 424f is detected by suitable detectors disposed adjacent to the exterior surface of the patient's neck and to the patient's Adam's apple, in the manner illustrated schematically in FIG. 16.

[0242] In the embodiment of the invention illustrated in FIG. 19, the emitter portion 424f includes a light source 490. The light source 490 is connected with source of electrical energy by a lead 492. The light source 490 has been illustrated schematically in FIG. 19 as being an incandescent light source. However, it may be preferred to provide a solid state device as a light source 490. For example, one or more light emitting diodes could be disposed on the leading end portion 52f of the guide rod 50f to function as a light source.

[0243] It is contemplated that the electrical energy conducted over the lead 492 to the light source 490 may be varied as the light source moves along the insertion path into the patient's respiratory system. For example, if the light source is pulsed from a maximum light emission level to a minimum light emission level, detection of the location of the leading end portion 52f of the guide rod 50f may be facilitated.

[0244] The light source 490 may be detected by suitable photo optic devices, such as photo cells or may be visually detected by the operator of the apparatus associated with the guide rod 50f. When the light source 490 is to be detected by the operator of the positioning apparatus, that is, when the operator is to function as the detector portion of the sensor assembly, it is believed that pulsing the light source will facilitate visual detection of the light source by the operator. It should be understood that both photo electric detection apparatus and visual detection by the operator could be utilized to locate the position of the leading end portion 52f of the guide rod 50f as the guide rod is moved into the patient's respiratory system.

[0245] A steering apparatus 460f (FIG. 19) is connected with the leading end portion 52f of the guide rod 50f. The steering apparatus 460f includes a plurality of expandable elements 464f and 466f. Although only two expandable elements 464f and 466f have been illustrated schematically in FIG. 19, it should be understood that a third expandable element, corresponding to the expandable element 468 of FIG. 18, is connected with the leading end portion 52f of the guide rod 50f. The expandable elements are connected with a source of inflation fluid by conduits 472f, 474f and 476f.

[0246] When one or more of the expandable elements connected with the leading end portion 52f (FIG. 19) of the guide rod 50f are to be expanded, fluid under pressure is conducted to the expandable elements. For example, when the expandable element 464f is to be operated from a contracted condition to an expanded condition, fluid under pressure, which may be either a gas or liquid, is conducted through the conduit

472f to the expandable element 464f. As the expandable element 464f is operated from a contracted condition to an expanded condition of the influence of fluid pressure, the expandable element applies force against the adjacent body tissues in the patient's respiratory system and applies force against the leading end portion 52f of the guide rod 50f. The force applied against the leading end portion 52f of the guide rod 50f deflects the leading end portion 52f of the guide rod 50f downward (as used in FIG. 19) to maintain the guide rod on the intended path of insertion into the patient's respiratory system. The output from the emitter portion 424f of the sensor assembly enables the operator to determine when it is necessary to expand one or more of the expandable elements and to determine which of the expandable elements to be expanded.

[0247] In the embodiment of the invention illustrated in FIG. 19, the emitter on the leading end portion of the guide rod 50f is a light source 490. However, a different type of emitter could be provided if desired. For example, the emitter could be a magnet which cooperates with detectors in the manner previously described in conjunction with FIGS. 15 and 16. Alternatively, the emitter could be a miniaturized radio frequency transmitter.

Embodiment of FIG. 20

[0248] In the embodiment of the invention illustrated in FIGS. 13 through 19, sensor assemblies have been illustrated as being associated with a guide rod of a positioning apparatus. In the embodiment of the invention illustrated in FIG. 12, fiber optics are utilized in association with a light source to enable an operator to view images of body tissue immediately ahead of the leading end portion of a guide rod 50b. In the embodiment of the invention illustrated in FIG. 20, a light source and fiber optics are associated with a tracheal tube to enable an operator to view images of body tissue immediately ahead of a leading end portion of the tracheal tube during of insertion of the tracheal tube into a patient's respiratory system. Since the embodiment of the invention illustrated in FIG. 20 is generally similar to the embodiments of the invention illustrated in FIGS. 1, 2 and 12, similar numerals will be utilized to designate similar components, the suffix letter "g" being associated with the numerals of FIG. 20 to avoid confusion.

[0249] A flexible tracheal tube 38g (FIG. 20) has a leading end portion 500. A light source 400g is disposed on the leading end portion 500 of the tracheal tube 38g. The light source 400g is connected with a source of electrical energy by leads 504 and 506. When the tracheal tube 38g is moving along an insertion path into a patient's respiratory system, the light source 400g illuminates body tissue immediately ahead of the leading end portion 500 of the tracheal tube 38g.

[0250] In the embodiment of the invention illustrated in FIG. 20, the light source 400g is mounted on the leading end portion of the tracheal tube 38g. However, it is contemplated that the light source could be disposed at a location remote from the leading end portion 500 of the tracheal tube 38g and illumination transmitted from the light source to the leading end portion of the tracheal tube through a fiber optic tube, corresponding to the fiber optic tube 402 of FIG. 12. Of course, a plurality of fiber optic tubes could be utilized if desired.

[0251] The light source 400g has been illustrated schematically in FIG. 20 as being an incandescent light source. However, it is contemplated that one or more solid state devices, such as light emitting diodes, could form the light source

400g if desired. A plurality of light sources 400g could be disposed in a circular array on the leading end portion 500 of the tracheal tube 38g.

[0252] A prismatic lens 510 is also mounted on the leading end portion 500 of the tracheal tube 38g. The lens 510 is enclosed by a transparent dome 512 which is connected with the leading end portion 500 of the tracheal tube 38g. Light is transmitted from the lens 510 through a fiber optic tube 408g to the eye of a viewer or to a display unit associated with a computer. The lens 510 is oriented so that images of body tissue immediately ahead of the leading end portion 500 of the tracheal tube 38g are transmitted through the fiber optic tube 408g. Although only a single light source 400g and single lens 510 have been illustrated schematically in FIG. 20, it should be understood that a plurality of light sources and/or a plurality of lenses may be mounted on the leading end portion 500 of the tracheal tube 38g.

[0253] The flexible tracheal tube 38g may be utilized in association with the positioning apparatus 56 of FIGS. 1 and 2 or with the positioning apparatus 256 of FIG. 4. Alternatively, the tracheal tube 38g may be utilized by itself, that is without a positioning apparatus. If the tracheal tube 38g is utilized with a positioning apparatus similar to the positioning apparatus 56 or 256, the tracheal tube may be moved along a guide rod similar to the guide rod 50 or the guide rod 250 as the tracheal tube is moved into a patient's respiratory system. However, the tracheal tube may be moved along a guide rod into a patient's respiratory system without utilizing a positioning apparatus, similar to the positioning apparatus 56 or 256 of FIGS. 1 and 4.

[0254] The tracheal tube 38g may be moved along an insertion path into a patient's respiratory system without benefit of a guide rod. If desired, a steering apparatus, corresponding to the steering apparatus 460 and 460f of FIG. 17-19, may be associated with the leading end portion of the tracheal tube 38g. Thus, expandable elements, corresponding to the expandable elements 464, 466 and 468 of FIG. 18 may be connected with the leading end portion 500 of the tracheal tube 38g. The expandable elements connected with the leading end portion 500 of the tracheal tube 38g may be connected in fluid communication with a source of fluid under pressure through conduits disposed in the side wall of the tracheal tube. Since images of body tissue immediately ahead of the leading end portion of the tracheal tube are transmitted through the fiber optic tube 408g, an operator who is positioning the tracheal tube relative to a patient's respiratory system will be able to view images of the body tissue and, from these images, be able to determine when to activate one or more expandable elements of a steering apparatus connected with the leading end portion 500 of the tracheal tube 38g.

Embodiment of FIG. 21

[0255] In the embodiment of the invention illustrated in FIG. 20, images of patient's body tissue are transmitted from the leading end portion of the tracheal tube for viewing by an operator who is inserting the tracheal tube into the respiratory system of a patient. In the embodiment of the invention illustrated in FIG. 21, the tracheal tube is associated with a sensor assembly having the same construction as the sensor assembly 420 of FIGS. 13 and 14. Since the embodiment of the invention illustrated in FIG. 21 is generally similar to the embodiment of the invention illustrated in FIGS. 13, 14 and 20, similar numerals will be utilized to designate similar

components, the suffix letter "h" being associated with the numerals of FIG. 21 to avoid confusion.

[0256] A tracheal tube 38h (FIG. 21) has a leading end portion 500h. A detector portion 426h is provided on the leading end portion 500h of the tracheal tube 38h. The detector portion 426h cooperates with an emitter portion of a sensor assembly having the same construction as the emitter portion 424 (FIG. 14) of the sensor assembly 420.

[0257] The tracheal tube 38h includes a plurality of magnetic flux sensor units 440h which respond to variations in a magnetic flux field in which the sensor units are exposed. In the illustrated embodiment of the invention, the sensor units 440h are Hall effect devices. However, the sensor units 440h could be other known types of devices which respond to a magnetic flux field.

[0258] The sensors 440h are connected with a computer, similar to the computer 438 of FIG. 13, by a plurality of leads 442h. The computer to which the leads 442h are connected has a display unit which displays an image of a typical respiratory system. The display indicates the position of the leading end portion 500h of the tracheal tube 38h relative to the patient's respiratory system.

[0259] In addition, the computer display may also indicate the position of a guide rod, corresponding to the guide rod 50c of FIG. 13, relative to the patient's respiratory system. Therefore, the computer display shows the position of the leading end portion 500h of the tracheal tube 38h relative to the leading end portion 52c (FIG. 13) of the guide rod 50c. Although the tracheal tube 38h may advantageously be utilized in association with a guide rod, similar to the guide rod 50c, it is contemplated that the tracheal tube 50h could be utilized by itself without an associated guide rod. Of course, if the tracheal tube 38h was utilized by itself without a guide rod similar to the guide rod 50c of FIG. 13, the output from the computer would indicate the position of the leading end portion 50h of the tracheal tube 38h relative to the patient's respiratory system and would not indicate the location of the guide rod.

[0260] It is contemplated that a steering apparatus similar to the steering apparatus 460 of FIG. 17 may be utilized with the tracheal tube 38h (FIG. 21). A plurality of expandable elements, corresponding to the expandable elements 464, 466 and 468 of FIG. 18, would be connected with the leading end portion 50h of the tracheal tube 38h. The cooperation between the Hall effect devices forming the sensor units 440h and the magnets of an associated detector portion of a sensor assembly would enable an operator inserting the tracheal tube 38h into a patient's respiratory system to determine when one or more of the expandable elements should be expanded to steer the leading end portion 500h of the tracheal tube 38h.

Embodiment of FIG. 22

[0261] In the embodiment of the invention illustrated in FIG. 19, a light source 490 and steering apparatus 460f is associated with the leading end portion 52f of a guide rod 50f. In the embodiment of the invention illustrated in FIG. 22, a plurality of light sources and a steering apparatus are associated with the leading end portion of a tracheal tube. Since the embodiment of the invention illustrated in FIG. 22 is generally similar to the embodiments of the invention illustrated in FIGS. 19-21, similar numerals will be utilized to designate similar components, the suffix letter "j" being associated with the numerals of FIG. 22 to avoid confusion.

[0262] A tracheal tube 38j has a leading end portion 500j. A plurality of light sources 490j are mounted on the leading end portion 500j of the tracheal tube 38j. The light sources 490j are energized by electrical energy connected over leads 492j. Although the light sources 490j have been indicated schematically in FIG. 22 as being incandescent light sources, it is contemplated that solid state devices, such as light emitting diodes, could be utilized as the light sources if desired.

[0263] The steering apparatus 460j is mounted on the leading end portion 500j of the tracheal tube 38j. The steering apparatus 460j includes a plurality of expandable elements 464j and 466j. Although only two expandable elements 464j and 466j have been illustrated schematically in FIG. 22, it should be understood that there are three expandable elements connected with the leading end portion 500j of the tracheal tube 38j. The expandable elements are disposed in an array around the end of the tracheal tube in much the same manner as illustrated schematically in FIG. 18 in association with the guide rod 50e.

[0264] The expandable elements 464j and 466j are connected with conduits 472j and 474j. The conduits 472j and 474j are formed in the side wall of the tracheal tube 38j in the manner indicated schematically in FIG. 22. Of course, a third conduit is provided to conduct fluid to and from a third expandable element on the end portion 500j of the tracheal tube 38j. It should be understood that the conduits 472j and 474j could be formed separately from the tracheal tube 38j if desired.

[0265] When the steering apparatus 460j is to be utilized to change the course of movement of the leading end portion 500j of the tracheal tube 38j relative to a patient's respiratory system, one or more of the expandable elements in the steering apparatus 460j is inflated under the influence of fluid pressure conducted through an associated conduit. For example, if the expandable element 464j is to be operated from a contracted condition to the expanded condition illustrated schematically in FIG. 22, fluid pressure is connected through the conduit 472j. As the expandable element 464j expands, forces are applied against tissue in the patient's respiratory system by the expandable element 464j. At the same time, the expandable element 464j is effective to apply force against the leading end portion 500j of the tracheal tube 38j to deflect the tracheal tube downward (as viewed in FIG. 22).

[0266] It is contemplated that the tracheal tube 38j may be utilized in association with a guide rod, such as the guide rod 50f of FIG. 19 or the guide rod 50 of FIG. 1. However, if desired, the tracheal tube 38j could be inserted into a patient's respiratory system without the benefit of a guide rod.

[0267] When the tracheal tube 38j is to be inserted into a patient's respiratory system, either with or without a guide rod, the light sources 490j are energized. Energization of the light sources 490j results in the emission of light which can be detected by photo cells or similar devices positioned adjacent to the outside of the patient's neck. If desired, the photo cells could be eliminated and an operator could visually locate the leading end portion 50j of the tracheal tube 38j by viewing the illumination conducted through the patient's body tissues to the surface of the patient's neck. It is contemplated that an operator will, in all probability, locate the leading end portion 500j of the tracheal tube 38j by a combination of the output from photo detectors and visually viewing the patient's neck. If desired, the light sources 490 can be pulsed to provide a

variation in the illumination from the light sources to facilitate visual locating of the leading end portion of the tracheal tube 38j by an operator.

[0268] When the inflatable elements 464j and/or 466j are to be operated from the expanded condition illustrated in FIG. 22 to a contracted condition, the conduits 472j and 474j may be exhausted to atmosphere. It is believed that it may be preferred to connect the conduits 472j and 474j with a source of low pressure or suction so that fluid is drawn out of the expandable elements.

[0269] As the fluid pressure in the expandable elements 460j and 466j is reduced, the natural resilience of the expandable elements causes them to contract tightly against the leading end portion 500j of the tracheal tube 38j. If desired, a plurality of recesses may be provided in the leading end portion 500j of the tracheal tube 38j to receive the expandable elements 464j and 466j. Of course, if additional expandable elements are associated with the leading end portion 500j of the tracheal tube 38j, additional recesses would be provided to receive these expandable elements when they are contracted.

[0270] Various types of emitters and detectors have been illustrated in FIGS. 20, 21 and 22 in association with the tracheal tube 38j. It should be understood that any of the emitters or detector systems previously described in association with a guide rod may be utilized in association with a tracheal tube. For example, a radio frequency transmitter and a receiver may be utilized as the emitter portion and the sensor portion of a sensor assembly which is utilized to detect the location of the leading end portion of a tracheal tube relative to a patient's respiratory system.

[0271] Although it is believed that it will probably be preferred to utilize a steering apparatus, similar to the steering apparatus 460j in association with the tracheal tube, the steering apparatus could be omitted if desired.

Positioning Apparatus—General—Mode of Operation

[0272] The general mode operation of the positioning apparatus 56 of FIG. 1 is illustrated schematically in FIG. 23. As was previously explained, the positioning apparatus 56 includes an arcuate member 108. The arcuate member 108 has a center of curvature indicated at 600 in FIG. 23.

[0273] The body section 86 of the positioning apparatus 56 has a central axis which extends through the center 600. The positioning section 96 is connected with an end of the body section 86 which is disposed closest to the center 600 of curvature of the arcuate member 108. The indicia 124 (FIG. 1) on the body section 86 is effective to indicate the length of the body section 86.

[0274] The guide rod 50 also has a central axis which extends through the center 600 of curvature of the arcuate section 108. The indicia 142 (FIG. 1) on the guide rod 50 indicates the distance from the leading end portion 52 of the guide rod 50 from the arcuate member 108. The guide rod 50 and body section 86 of the positioning apparatus 56 are both radiused from the center 600 of curvature of the arcuate member. When the indicia 142 (FIG. 1) indicates that the guide rod 50 (FIG. 23) extends from the arcuate member 108 for the same distance as the body section 86, the leading end portion 52 of the guide rod 50 is aligned with the positioning apparatus 96. Since the positioning apparatus 96 is accurately located relative to the patient's respiratory system 11 (FIG. 1) by engagement with the patient's Adam's apple 34, the position of the leading end portion 52 of the guide rod relative to

the patient's larynx **30** is known when the leading end portion **52** of the guide rod **50** is aligned with positioning apparatus **96**.

[0275] An alternative embodiment of the positioning apparatus **56** is illustrated in FIG. **24**. Since the embodiment of the positioning apparatus illustrated in FIG. **24** is generally similar to the embodiment of the positioning apparatus **56** illustrated in FIGS. **1** and **23**, similar numerals will be utilized to indicate similar components, the suffix letter "k" being associated with the components of FIG. **24** to avoid confusion.

[0276] A positioning apparatus **56k** includes a body section **86k**. A positioning section **96k** is connected with an end portion of the body section **86k**. The positioning section **96k** engages the patient's Adam's apple, in the manner previously described in conjunction with the apparatus **56** of FIG. **1**.

[0277] In the embodiment of the invention illustrated in FIG. **24**, a member **108k** is fixedly connected with the body section **86k** and extends at a known angle, indicated at **604** in FIG. **24**. A guide section **114k** is disposed at an end of the member **108k** opposite from the connection **606** with the body section **86k**. The guide rod section **114k** guides movement of a guide rod **50k** along a path which extends through a center **600k**.

[0278] The center **600k** is disposed at the intersection of a longitudinal central axis of the body section **86k** and a longitudinal central axis of the guide rod **50k**. An angle, indicated at **610** in FIG. **24**, formed between the longitudinal central axis of the body section **86k** and the guide rod **50k** is known. The distance from the positioning section **96k** to the connection **606** between the body section **86k** and member **108k** is known. The angles **604** and **610** are known. The length of the member **108** is also known. Therefore the distance which the guide rod **50k** must extend from the guide section **114k** to have the leading end portion **52k** of the guide rod aligned with the positioning section **96k** can readily be determined by trigonometric functions.

[0279] It should be understood that features of any one embodiment of the invention may be used with features of other embodiments of the invention. For example, the positioning apparatus **256** of FIGS. **4-10** could have the same construction as the positioning apparatus **56** of FIGS. **1-3**. Similarly, the magnet **260** of FIG. **4** could be used with the embodiment of the invention illustrated in FIGS. **1-3**. The sensor assemblies **420** could be used with either the positioning apparatus **56** of FIG. **1** or the positioning apparatus **256** of FIGS. **4-10**. Other combinations of features of the invention will undoubtedly be utilized.

Embodiment of FIGS. **25** and **26**

[0280] In the embodiments of the invention illustrated in FIGS. **1-24**, the positioning apparatus **56** has a positioning section **96** which engages the patient's Adam's apple **34**. In the embodiment of the invention illustrated in FIGS. **25** and **26**, the positioning apparatus engages a plurality of locations on the patient's neck. Since the embodiment of the invention illustrated in FIGS. **25** and **26** is generally similar to the embodiments of the invention illustrated in FIGS. **1-24**, similar numerals will be utilized to designate similar components, the suffix letter "m" being associated with the numerals of FIGS. **25** and **26** to avoid confusion.

[0281] A positioning apparatus **56m** is utilized to position a guide rod **50m** corresponding to the guide rod **50** of FIG. **1**, relative to a patient's trachea **28m** during insertion of the guide rod into the patient's trachea. In addition, the position-

ing apparatus **56m** provides an indication of the distance which the guide rod **50m** is to be moved into the patient's trachea **28m**. The positioning apparatus **56m** includes a base section **78m** which is connected with an arcuate upper section, corresponding to the arcuate upper section **80** of FIG. **1**. The base section **78m** includes a tubular cylindrical body section **86b**. The base section **78m** also includes a positioning section **96m**. The positioning section **96m** locates the positioning apparatus **56m** relative to the patient's Adam's apple **34m**.

[0282] In accordance with a feature of the embodiment of the invention illustrated in FIGS. **25** and **26**, the positioning section **96** includes a pair of positioning fingers **622** and **624** which engage the neck **16m** of the patient at locations disposed on laterally opposite sides of the Adam's apple **34m**. Thus, the positioning finger **622** is provided with a relatively soft resilient spherical end portion **628** which is pressed against the patient's neck **16m** at a location adjacent to the left (as viewed in FIG. **26**) side of the patient's Adam's apple. Similarly, the positioning finger **624** has a soft resilient spherical end portion **630** which is pressed against the patient's neck **16m** at a location adjacent to the right (as viewed in FIG. **26**) side of the patient's Adam's apple **34m**. The positioning fingers **622** and **624** cooperate with the patient's Adam's apple **34m** to locate the positioning section **96m** laterally relative to the patient's Adam's apple **34m**.

[0283] In the embodiment of the positioning section **96m** illustrated in FIGS. **25** and **26**, the positioning section is provided with a straight center positioning finger **634** which is formed as a continuation of the tubular cylindrical body section **86m** of the positioning apparatus **56m**. Thus, the body section **86m** and center positioning finger **634** are integrally formed as one piece. The center positioning finger **634** has a soft resilient spherical end portion **636** which is pressed against the patient's Adam's apple **34m** at the center of the patient's Adam's apple.

[0284] Force may be applied against the body section **86m** of the positioning apparatus **56m** and transmitted to the patient's neck **16m** to straighten the trachea of the patient. Thus, a slight bend in the trachea can be minimized by the manual application of a relatively small force to the positioning apparatus **56m**. This force is transmitted through the end portions **628** and **630** of the positioning fingers **622** and **624** to the patient's neck to straighten the patient's neck. In addition, a portion of the force will be transmitted through the center positioning finger **634** directly to the patient's Adam's apple **34m**.

[0285] The position of the end portions **628** and **630** of the positioning fingers **622** and **624** relative to the body section **86m** of the base section **78m** of the positioning apparatus **56m** (FIG. **25**) can be varied. Thus, the positioning fingers **622** and **624** are fixedly connected to a slide block **640** which is axially movable along the body section **86m**. The body section **86m** extends through a cylindrical central opening in the slide block **640**. A set screw **642** (FIG. **25**) having manually engageable wings or flanges can be tightened to hold the positioning fingers **622** and **624** in a desired position relative to the body section **86m** of the positioning apparatus **56m**. This enables the length of the center positioning finger **634** to be adjusted. By adjusting the length of the center finger **634**, a relatively small amount of force can be transmitted through the center finger **634** directly to the patient's Adam's apple **34m** and substantially larger forces can be transmitted

through the positioning fingers **622** and **624** to the patient's neck **16m** to locations disposed on opposite sides of the patient's Adam's apple **34m**.

[0286] It should be understood that the positioning section **96m** of FIGS. **25** and **26** can be utilized in any of the positioning apparatus disclosed in FIGS. **1** through **24** herein. When the positioning section **96m** is to be associated with the positioning apparatus **56c** of FIG. **13**, the emitter units **430** (FIG. **14**) could be mounted on or adjacent to the end portions **628**, **630** and **636** (FIGS. **25** and **26**) of the positioning fingers **622**, **624** and **634**. Similarly, when the positioning section **96m** is utilized in association with the positioning apparatus **56d** of FIGS. **15** and **16**, the sensor units **440** may be disposed adjacent to and connected with the end portions **628**, **630** and **636** (FIG. **25**) of the positioning fingers **622**, **624** and **634**.

[0287] It should be understood that the positioning apparatus **56m** (FIGS. **25** and **26**) may be associated with guide rods having the construction of the guide rod **50** of FIG. **1**, the guide rod **250** of FIGS. **4** and **8**, the guide rod **50e** of FIGS. **17** and **18**, or the guide rod **50f** of FIG. **19**. It should also be understood that the positioning apparatus **56m** may be associated with a tracheal tube having the construction of any one of the tracheal tubes **38** (FIG. **2**), **238** (FIGS. **9** and **10**), **38g** (FIG. **20**), **38h** (FIG. **21**), or **38j** (FIG. **22**).

Embodiment of FIGS. **27** and **28**

[0288] In the embodiment of the invention illustrated in FIGS. **25** and **26**, the positioning fingers **622** and **624** are fixedly connected with the body section **86m** of the positioning apparatus **56m** by the slide block **640** while the positioning fingers **634** is integrally formed as one piece with the body section **36m**. In the embodiment of the invention illustrated in FIGS. **27** and **28**, the positioning fingers are movable relative to the body section of the positioning apparatus. Since the embodiment of the invention illustrated in FIGS. **27** and **28** is generally similar to the embodiments of the invention illustrated in FIGS. **1-26**, similar numerals will be utilized to designate similar components, the suffix letter "r" being associated with the numerals of FIGS. **27** and **28** to avoid confusion.

[0289] A positioning apparatus **56r** positions a guide rod, corresponding to the guide rod **50** of FIG. **1**, relative to a patient's trachea during insertion of the guide rod into the patient's trachea. In addition, the positioning apparatus **56r** provides an indication of the distance which the guide rod is to be moved into the patient's trachea. Although only a portion of the positioning apparatus **56r** is illustrated in FIGS. **27** and **28**, it should be understood that the positioning apparatus may have the same general construction as the positioning apparatus of any one of the embodiments illustrated in FIGS. **1-19**.

[0290] The positioning apparatus **56r** includes a base section **78r** which is connected with an arcuate upper section corresponding to the arcuate upper section **80** of FIG. **1**. The upper section of the positioning apparatus **56r** guides movement of a guide rod, corresponding to the guide rod **50** of FIG. **1**, during insertion of the guide rod into the patient's trachea.

[0291] In accordance with a feature of the present invention, a positioning section **96r** is connected with the base section **78r**. The positioning section **96r** locates the positioning apparatus **56r** relative to the patient's Adam's apple **34r** (FIG. **28**). The positioning section **96r** is connected with an end of a body section **86r** of the positioning apparatus **56r** by a universal pivot connection **652**. The pivot connection **652**

allows the orientation of the base section **78r** of the positioning apparatus **56r** to be changed in any direction relative to the positioning section **96r**. Thus, the body section **86r** of the positioning apparatus **56r** can be raised or lowered (as viewed in FIG. **27**) or pivoted to the left or right (as viewed in FIG. **28** [0292] The positioning section **96r** includes a plurality of positioning fingers **622r**, **624r** and **634r**. The positioning fingers **622r**, **624r** and **634r** are provided with soft resilient spherical end portions **628r**, **630r**, and **636r**. Although the positioning section **96r** may be located in any one of many different orientations relative to the patient's Adam's apple **34r**, the position section **96r** is illustrated in FIG. **28** with the end portions **628r** and **630r** disposed on laterally opposite sides of the patient's Adam's apple **34r**. The end portion **636r** is disposed adjacent to the lower end portion of the patient's Adam's apple **34r**. If desired, the orientation of the positioning section **96r** could be rotated by 180 degrees from the orientation illustrated in FIG. **28**. If this was done, the end portion **636r** on the positioning finger **634r** would be disposed adjacent to the upper portion of the patient's Adam's apple **34r**. It is believed that it will probably be preferred to align the pivot connection **652** with the center of the patient's Adam's apple **34r**. However, if desired, the pivot connection **652** could be offset from the center of the patient's Adam's apple **34**.

[0293] In the embodiments of the invention illustrated in FIGS. **25-28**, the positioning sections **96m** and **96r** have been illustrated as having three positioning fingers. However, it is contemplated that the positioning sections could have either a greater number of positioning fingers or a lesser number of positioning fingers if desired. For example, the center positioning finger **634** of the embodiment of the invention illustrated in FIGS. **25** and **26** could be omitted. If this was done, the positioning finger **622** would be positioned on one side of the patient's Adam's apple **34m** and the positioning finger **624** would be positioned on the laterally opposite side of the patient's Adam's apple, in the manner illustrated in FIG. **26**, without engaging the central portion of the patient's Adam's apple. Alternatively, the positioning section **96m** or **96r** could be provided with four positioning fingers. If this was done, two of the positioning fingers would be positioned in engagement with the neck of the patient adjacent to one side of the patient's Adam's apple and the other two positioning fingers would be positioned in engagement with the patient's neck on a laterally opposite side of the patient's Adam's apple.

CONCLUSION

[0294] An improved method and apparatus for use in tracheal intubation or other medical procedures may include a positioning apparatus **56**, **256**. When the positioning apparatus **56**, **256** is used for tracheal intubation, the positioning apparatus is located relative to a patient's trachea **28**, **228** by engaging a portion of the patient's body, such as the Adam's apple **34**, **234**. A flexible guide rod **50**, **250** may be moved relative to the positioning apparatus until a leading end portion **52**, **252** of the guide rod has moved into the patient's trachea. A tracheal tube **38**, **238** is slid along the guide rod into the patient's trachea.

[0295] During movement of the guide rod **50**, **250** relative to the positioning apparatus **56**, **256**, the guide rod may be moved through either a tubular guide member **264** or a tracheal tube **38**, **238** which extends through the patient's mouth into the patient's pharynx. Before beginning to move the guide rod **50**, **250**, the distance which the guide rod is to be

moved may advantageously determined. This may be done as a function of spacing between locations on the positioning apparatus **56, 256**. If desired, indicia **124, 324** may be provided on the positioning apparatus **56, 256** and cooperating indicia **142, 342-350** may be provided on the guide rod **50, 250**.

[0296] A magnet **260** may be utilized to attract a leading end portion **252** of the guide rod **250**. The magnet **260** is disposed outside of the patient's body and may be positioned adjacent to an anterior side of the trachea. Magnetic attraction between the magnet **260** and the leading end portion **252** of the guide rod deflects the guide rod. This steers the leading end portion of the guide rod **250** into the entrance to the patient's trachea. A magnet may be used to steer a member relative to a patient's body tissue during performance of operations other than tracheal intubation

[0297] In order to locate the guide rod **50, 250** and/or tracheal tube **38, 238** relative to the patient's trachea, an image of body tissue adjacent to the leading end portion of the guide rod and/or tracheal tube may be transmitted to a location outside of the patient's body (FIGS. **12** and **20**). Movement of the guide rod **50, 250** and/or tracheal tube **38, 238** into the patient's trachea is interrupted when the image transmitted from the leading end portion of the guide rod or tracheal tube indicates that the leading end portion of the guide rod or tracheal tube has been moved to a desired position relative to the patient's trachea.

[0298] It is believed that transmission of an image of body tissue adjacent to the leading end portion of the tracheal tube **38, 238** may advantageously be performed when the tracheal tube is utilized without benefit of the positioning apparatus **56, 256**. However, the transmission of an image of body tissue adjacent to the leading end portion of the tracheal tube **38, 238** may be performed when the positioning apparatus is used in association with the tracheal tube. Positioning of the guide rod **50, 250** relative to the patient's trachea may also be facilitated by the transmitting of images of body tissue adjacent to a leading end portion of the guide rod.

[0299] Detectors and emitters **424, 426** may be utilized to detect the position of the leading end portion of the guide rod **50, 250** and/or the tracheal tube **38, 238** relative to the patient's trachea. When this is done, an emitter **424**, such as a magnet or a light source, may be connected with a leading end portion **52, 252** of the guide rod **50, 250** and/or the tracheal tube **38, 238**. One or more detectors **426** may be provided on the outside of the patient's neck to detect the output from the emitter **424** when the guide rod **50, 250** and/or the tracheal tube **38, 238** are in a desired position relative to the patient's trachea. Alternatively, a detector **426** may be connected with the leading end portion of a guide rod **50, 250** and/or tracheal tube **38, 238** and one or more emitters **424** positioned relative to the outside of the patient's neck. The detector **426** would provide an output indicating when the guide rod **50, 250** and/or tracheal tube **38, 238** is moved to a desired position relative to the patient's trachea.

[0300] During movement of the guide rod **50, 250** and/or tracheal tube **38, 238** along the patient's respiratory system and into the patient's trachea, force may be applied against the leading end portion **52, 252** of the guide rod and/or tracheal tube to steer the leading end portion of the guide rod and/or tracheal tube. The application of force against the leading end portion **52, 252** of the guide rod **50, 250** and/or tracheal tube **38, 238** may be accomplished by expanding an

expandable element **464-468** connected with the guide rod **50, 250** and/or the tracheal tube **38, 238**.

[0301] It should be understood that any one of the features of the present invention may be used separately or in combination with other features of the invention. It's believed that various combinations of the features, other than those disclosed herein, may advantageously be utilized and will be apparent to those skilled in the art from the description contained herein. In addition, it should be understood that features of the present invention may be used for purposes other than tracheal intubation. From the above description of the invention, those skilled in the art will perceive improvements, changes and modifications. Such improvements, changes and modifications within the skill of the art are intended to be covered by the appended claims.

1-20. (canceled)

21. A method for positioning a medical device in a respiratory system of a patient, the method comprising:

providing a medical device system including a flexible guide rod having a distal end, a visible light source operatively connected to the flexible guide rod such that visible light from the visible light source is emitted outward from adjacent the distal end of the flexible guide rod, and a medical device for treating the patient slidably receivable on the flexible guide rod;

inserting the flexible guide rod into a treatment portion of a respiratory system of the patient's body;

emitting visible light from the visible light source outward from adjacent the distal end of the flexible guide rod and into said treatment portion of the respiratory system such that the emitted visible light within said treatment portion of the respiratory system transmits through the patient's body;

visually observing, outside the patient's body, the emitted visible light transmitted through the patient's body to determine the location of the distal end of the flexible guide rod within said treatment portion of the respiratory system of the patient's body;

slidably moving, after said visually observing the emitted visible light transmitted through the patient's body, the medical device distally along the flexible guide rod toward the distal end of the flexible guide rod to a selected position relative to the distal end of the flexible guide rod and within said treatment portion of the respiratory system of the patient's body.

22. The method for positioning a medical device in a respiratory system of a patient as set forth in claim 21, wherein said emitting visible light from the visible light source and said visually observing said visible light outside the patient's body are performed simultaneously with said inserting the flexible guide rod.

23. The method for positioning a medical device in a respiratory system of a patient as set forth in claim 22, further comprising positioning, simultaneously with said emitting visible light from the visible light source and said visually observing said visible light outside the patient's body and before said slidably moving the medical device, the distal end of the flexible guide rod in a selected position within the treatment portion of the respiratory system of the patient's body.

24. The method for positioning a medical device in a respiratory system of a patient as set forth in claim 23, wherein the medical device system further includes a guide tube in

which the flexible guide rod is slidably received, the guide tube having an open distal end,

the method further comprising:

inserting, before said inserting the flexible guide rod, the guide tube into the respiratory system of the patient's body; and

positioning, before said inserting the flexible guide rod, the open distal end of the guide tube adjacent the treatment portion of the respiratory system of the patient's body.

25. The method for positioning a medical device in a respiratory system of a patient as set forth in claim **24**, wherein said inserting the flexible guide rod comprises slidably moving the flexible guide rod relative to the guide tube in a distal direction such that the distal end of the flexible guide rod moves distally away from the open distal end of the guide tube.

26. The method for positioning a medical device in a respiratory system of a patient as set forth in claim **25**, wherein a distal end section of the guide tube encompassing the open distal end of the guide tube has an arcuate shape to facilitate said positioning the open distal end of the flexible guide tube.

27. The method for positioning a medical device in a respiratory system of a patient as set forth in claim **21**, wherein the medical device system further includes a guide tube in which the flexible guide rod is slidably received, the guide tube having an open distal end,

the method further comprising:

inserting, before said inserting the flexible guide rod, the guide tube into the respiratory system of the patient's body; and

positioning, before said inserting the flexible guide rod, the open distal end of the guide tube adjacent the treatment portion of the respiratory system of the patient's body.

28. The method for positioning a medical device in a respiratory system of a patient as set forth in claim **27**, wherein said inserting the flexible guide rod comprises slidably moving the flexible rod relative to the guide tube in a distal direction such that the distal end of the flexible guide rod moves distally away from the open distal end of the guide tube.

29. The method for positioning a medical device in a respiratory system of a patient as set forth in claim **27**, wherein a distal end section of the guide tube encompassing the open distal end of the guide tube has an arcuate shape to facilitate said positioning the open distal end of the guide tube adjacent the treatment portion of the respiratory system of the patient's body.

30. The method for positioning a medical device in a respiratory system of a patient as set forth in claim **29**, wherein said slidably moving the flexible guide rod relative to the guide tube includes bending a distal end section of the flexible guide rod into an arcuate shape corresponding to the arcuate shape of the distal end section of the guide tube as the distal end of the flexible guide rod moves distally away from the open distal end of the guide tube.

31. The method for positioning a medical device in a respiratory system of a patient as set forth in claim **21**, wherein the flexible guide rod comprises an optical fiber having a distal end adjacent the distal end of the flexible guide rod, and a proximal end configured to remain outside the patient's body during said method for positioning a medical device, wherein the visible light source is adjacent the proximal end

of the optical fiber, wherein said emitting visible light from the visible light source comprises transmitting visible light from the visible light source located outside the body through the optical fiber of the flexible guide rod.

32. The method for positioning a medical device in a respiratory system of a patient as set forth in claim **21**, wherein the flexible guide rod includes a plurality of markers spaced predetermined distances from the distal end of the flexible guide rod,

the method further comprising:

visibly observing, after said inserting the flexible guide rod, one or more of the markers outside the patient to determine a position of the distal end of the flexible guide rod in the treatment portion of the respiratory system of the patient's body.

33. The method for positioning a medical device in a respiratory system of a patient as set forth in claim **21**, further comprising:

endoscopically observing the flexible guide rod in the respiratory system of the patient's body during said inserting the flexible guide rod.

34. The method for positioning a medical device in a respiratory system of a patient as set forth in claim **21**, wherein said treatment portion of the respiratory system is the nasal cavity, whereby said inserting the flexible guide rod comprises inserting the flexible guide rod into the nasal cavity of the respiratory system of the patient's body.

35. A method for positioning a medical device in a respiratory system of a patient, the method comprising:

providing a medical device system including a guide tube having an open distal end, a flexible guide rod having a distal end, a visible light source operatively connected to the flexible guide rod such that visible light from the visible light source is emitted outward from adjacent the distal end of the flexible guide rod, wherein the flexible guide rod is slidably receivable in the guide tube;

inserting the guide tube into the respiratory system of the patient's body;

positioning the open distal end of the guide tube adjacent a treatment portion of the respiratory system of the patient's body;

slidably moving the flexible guide rod relative to the guide tube in a distal direction such that the distal end of the flexible guide rod moves distally away from the open distal end of the guide tube and into the treatment portion of a respiratory system of the patient's body;

emitting visible light from the visible light source outward from adjacent the distal end of the flexible guide rod and into said treatment portion of the respiratory system such that the emitted visible light within said treatment portion of the respiratory system transmits through the patient's body;

visually observing, outside the patient's body, the emitted visible light transmitted through the patient's body to determine the location of the distal end of the flexible guide rod within said treatment portion of the respiratory system of the patient's body.

36. The method for positioning a medical device in a respiratory system of a patient as set forth in claim **35**, wherein the medical device system further includes an inflatable balloon slidably movable relative to the guide tube,

the method further comprising:

slidably moving, after said positioning the open distal end of the guide tube, the inflatable balloon relative to

the guide tube such that the inflatable balloon enters the treatment portion of the respiratory system of the patient's body; and
inflating the inflatable balloon, after said slidably moving the inflatable balloon, to apply a force against body tissue in the respiratory system of the patient's body.

* * * * *

专利名称(译)	定位超声导管的方法		
公开(公告)号	US20140228679A1	公开(公告)日	2014-08-14
申请号	US14/256629	申请日	2014-04-18
申请(专利权)人(译)	P科技有限责任公司		
当前申请(专利权)人(译)	P科技有限责任公司		
[标]发明人	BONUTTI PETER M		
发明人	BONUTTI, PETER M.		
IPC分类号	A61B8/00 A61B8/12 A61M25/01 A61B8/08 A61M16/04		
CPC分类号	A61B8/4263 A61B8/0841 A61B8/445 A61M25/0108 A61M25/0102 A61B8/12		
其他公开文献	US10065009		
外部链接	Espacenet USPTO		

摘要(译)

发射器可以设置在患者体内。来自发射器的输出可以由与导杆连接的检测器和与气管导管连接的检测器检测。或者，检测器可以检测来自与导杆连接的发射器和与气管导管连接的发射器的输出。发射器单元可以是超声换能器并发射超声能量。检测器可响应超声能量。

