



US006394956B1

(12) **United States Patent**
Chandrasekaran et al.

(10) **Patent No.:** **US 6,394,956 B1**
(45) **Date of Patent:** **May 28, 2002**

(54) **RF ABLATION AND ULTRASOUND CATHETER FOR CROSSING CHRONIC TOTAL OCCLUSIONS**

(75) Inventors: **Chandru V. Chandrasekaran**, Mercer Island; **Zihong Guo**, Bellevue, both of WA (US); **Anthony J. Pantages**, Los Altos; **Donald Masters**, Sunnyvale, both of CA (US); **Ryan Kaveckis**, Seattle, WA (US)

(73) Assignee: **Scimed Life Systems, Inc.**, Maple Grove, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/514,970**

(22) Filed: **Feb. 29, 2000**

(51) **Int. Cl.**⁷ **A61B 8/00**

(52) **U.S. Cl.** **600/439; 600/466; 607/122**

(58) **Field of Search** 600/439, 437, 600/459, 462, 463, 466, 467, 469, 470, 471; 607/122; 128/898

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,000,185 A	3/1991	Yock
5,024,234 A	6/1991	Leary et al.
5,054,492 A	10/1991	Scribner et al.
5,314,438 A	5/1994	Shturman
5,454,809 A	10/1995	Janssen
5,588,432 A	12/1996	Crowley
5,599,346 A	2/1997	Edwards et al.
5,626,576 A	5/1997	Janssen
5,680,860 A	10/1997	Imran
5,683,366 A	11/1997	Eggers et al.

5,740,808 A	4/1998	Panescu et al.	
5,749,914 A	5/1998	Janssen	
5,817,092 A	10/1998	Behl	
5,848,969 A	* 12/1998	Panescu et al.	600/462
5,967,984 A	* 10/1999	Chu et al.	600/439
6,032,673 A	* 3/2000	Savage et al.	128/989
6,165,127 A	* 12/2000	Crowley	600/463

FOREIGN PATENT DOCUMENTS

WO	WO 90/07303	7/1990
WO	WO 97/45157	12/1997

* cited by examiner

Primary Examiner—Marvin M. Lateef


Assistant Examiner—Ali M. Imam

(74) *Attorney, Agent, or Firm*—Christensen O'Connor Johnson Kindness PLLC

(57) **ABSTRACT**

A combination catheter includes an ultrasound transducer and RF ablation electrode. The ultrasound transducer transmits ultrasound signals into and receives echo signals from a vessel. The echo signals are processed and used to produce an image of the tissue surrounding the catheter. A driveshaft rotates the ultrasound transducer to obtain a 360° view of the vessel wall. At the distal end of the driveshaft is an electrode. An RF generator is electrically coupled to the driveshaft to deliver RF energy to the electrode at the distal end of the driveshaft to ablate occluding material in the vessel. The electrode may have a variety of tip shapes including concave, roughened, or expandable configurations, depending on the size of the vessel and composition of the occluding material to be ablated. Alternatively, the RF ablation energy may be delivered to a guidewire that is used to route the ultrasound catheter through a patient's vasculature. Finally, a steerable catheter can be used to further position the ultrasound catheter and ablation electrode in the vessel.

7 Claims, 5 Drawing Sheets






Fig. 1.




Fig. 2.




Fig. 3A.




Fig. 3B.






Fig. 3C.






Fig. 6.




Fig. 7.

1

RF ABLATION AND ULTRASOUND CATHETER FOR CROSSING CHRONIC TOTAL OCCLUSIONS

FIELD OF THE INVENTION

The present invention relates to medical devices in general, and in particular to catheter ablation systems for revascularizing occluded vessels.

BACKGROUND OF THE INVENTION

One common form of vascular disease is characterized by deposits that form in a patient's arteries or veins. Once such blockages form in cardiac arteries, they are a significant factor in the occurrence of heart attacks.

In addition to cardiac bypass surgery, new less-invasive techniques such as balloon angioplasty or rotational ablation are being used to treat occluded vessels. In the case of rotational atherectomy, a high speed abrasive burr is routed through the patient's vasculature to the point of the occlusion and used to bore a new lumen through the occlusion in order to restore blood flow. The success of balloon angioplasty and rotational ablation often depends on the nature of the material blocking the vessel. These techniques generally work best when the material is not highly calcified or does not completely occlude the vessel. Total chronic occlusions are typically characterized by a hard calcified material that completely seals off blood flow in a vessel. Some success has been achieved in treating these blockages by advancing a flexible guidewire to the point of the occlusion and "pecking" at the occlusion to create a pathway through it. The problem with the guidewire technique is that it is time-consuming and presents a risk of vessel perforation if the guidewire becomes misaligned.

Given the fact that total chronic occlusions account for between 20–25% of all occlusions treated, there is a need for a system that employs a more aggressive ablation mechanism to reduce the treatment time but reduces the likelihood that the ablation mechanism will become misaligned in the patient's vessel in order to provide an effective method of treating this type of vessel blockage.

SUMMARY OF THE INVENTION

To treat total chronic occlusions, the present invention is a combination ultrasound and ablation catheter that provides a physician with an image of the position of the catheter in the vessel and an image of the occluding material. An ultrasound transducer is located at the distal end of a catheter which generates ultrasound signals and receives corresponding echo signals from the tissue. The echo signals are transmitted to an ultrasound processor which produces an image of the vessel. The catheter is rotated by a driveshaft in order to provide a 360° view of the vessel. In one embodiment of the invention, the ultrasound transducer in the catheter is set at an angle such that echo signals are received from a position slightly ahead of the distal end of the catheter.

To create a new lumen in the vessel, radio frequency (RF) ablation energy is transmitted to an electrode that is located at a distal tip of the combination catheter. The RF energy ablates a portion of the occluding material to create a new lumen in the vessel. In one embodiment of the invention, the ultrasound transducer is rotated by a conductive driveshaft. The electrode is electrically coupled to the driveshaft and the RF energy is applied to the driveshaft to be transmitted to the occlusion. The conductive driveshaft is surrounded by a

2

non-conductive sheath. The electrode extends out the distal end of the non-conductive sheath such that RF ablation energy is directed from the exposed electrode and into the occluding material.

According to another aspect of the present invention, the electrode at the distal end of the ultrasound catheter may have a variety of shapes including a concave shape, a convex, hemispherical shape with a roughened outer surface or an expandable tip made of a series of braided wires.

In another embodiment of the invention, the catheter system includes an ultrasound catheter having an ultrasound transducer that is rotated by a driveshaft to obtain images of the vessel and occluding material. The ultrasound catheter is routed in one lumen of a multi-lumen catheter. In another lumen of the multi-lumen catheter is a conductive guidewire. RF ablation energy is applied to the conductive guidewire to ablate the occluding material in the vessel.

In accordance with yet another aspect of the invention, the combination ultrasound and RF ablation catheter is routed through a steerable sheath in order to further aid in the placement of the catheter within the vessel. Alternatively, the electrode that delivers the RF ablation energy is incorporated into the steerable sheath, wherein the ultrasound catheter extends through a hole in the electrode at the distal end of the sheath to obtain images of the vessel and occluding material.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing aspects and many of the attendant advantages of this invention will become more readily appreciated as the same become better understood by reference to the following detailed description, when taken in conjunction with the accompanying drawings, wherein:

FIG. 1 illustrates a combination RF ablation and ultrasound catheter system for crossing total chronic occlusions according to one embodiment of the present invention;

FIG. 2 illustrates a spring biased contact that applies RF ablation energy to a driveshaft that rotates an ultrasound transducer;

FIGS. 3A–3C illustrate a variety of RF electrode tip shapes according to other aspects of the present invention;

FIG. 4 illustrates an embodiment of the invention in which RF ablation energy is applied to occluding material in a vessel via a conductive guidewire;

FIG. 5 illustrates the use of a steerable sheath through which an RF ablation and ultrasound catheter are routed;

FIG. 6 illustrates an alternative embodiment of the present invention wherein a steerable sheath includes an electrode that delivers RF energy to an occlusion; and

FIG. 7 illustrates yet another embodiment of the invention wherein a catheter includes a separate ultrasound catheter and RF ablation catheter.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

FIG. 1 illustrates a combination ultrasound and RF ablation catheter system according to one embodiment of the present invention. The combination ultrasound and RF ablation system 10 includes a catheter 12 that is routed through a patient's vasculature to the point of a partial or total chronic occlusion that is restricting blood flow through a blood vessel (not shown). The catheter 12 is moved through the vasculature by an advancer 14 at the proximal end of the catheter 12. At the distal tip of the catheter 12 is an

ultrasound transducer **34** that transmits ultrasound signals into the vessel tissue and receives corresponding echo signals. The echo signals are transmitted from the ultrasound transducer **34** to an ultrasound processor **20** that produces an image of the tissue surrounding the imaging head **16** on a video monitor **22**.

To provide a 360° view of the vessel, the ultrasound transducer **34** is rotated by an electrically conductive driveshaft **30** that is rotated by the advancer **14** or motor drive at a rate of approximately 1,500–2,000 rpm. Surrounding the driveshaft **30** is a sheath **32** that prevents the driveshaft **30** from engaging the vessel walls. The details of the rotation ultrasound catheter **12** and advancer **14** are set forth in U.S. Pat. No. 5,000,185 which is assigned to Cardiovascular Imaging Systems, Inc. of Sunnyvale, Calif. and is herein incorporated by reference.

The ultrasound transducer **34** is integrated with a conductive electrode **38** that is secured to the distal end of the conductive driveshaft **30**. According to one aspect of the present invention, the ultrasound transducer **34** is positioned in a window **36** on the side of the electrode such that ultrasound signals are transmitted to and echo signals are received from an area in the vessel that is adjacent the electrode **38** as well as a region that is just ahead or distal to the electrode **38**.

In the presently preferred embodiment of the invention, an infusion control **25** at the proximal end of the catheter **12** pumps fluid such as saline, through the catheter **12** and around the ultrasound transducer **34** to clear blood cells away from the transducer. The saline acts as an acoustic coupling media between the transducer and the surrounding blood field.

In order to remove the occluding material from the vessel, the present invention also includes a radio frequency (RF) generator **50** that delivers RF energy to the electrode **38** at the distal end of the catheter **12**. The RF energy is preferably transmitted through the conductive driveshaft **30** that rotates the ultrasound transducer **34** and the electrode **38**. The sheath **32** that surrounds the driveshaft **30** is preferably non-conductive such that the RF energy enters the patient at the point of the electrode **38** exits the sheath **32**. The RF energy vaporizes a portion of the occluding material in the vessel in order to revascularize the vessel. The RF energy is preferably returned to the RF generator **50** via an external patient pad (not shown) that serves as the return electrode. By utilizing the driveshaft **30** as the conductor for delivering the RF energy to the electrode **38**, no additional wires are needed within the catheter **12**. In the presently preferred embodiment of the invention, the driveshaft **30** is made of stainless steel. However, other conductive materials such as graphite or other metals could be used.

In the example shown in FIG. 1, the position of the electrode **38** with respect to the distal end of the surrounding sheath **32** is fixed by a sleeve **52**, which is bonded to the distal end of the sheath **32**. A cylindrical bearing **54** is secured around the driveshaft **30** proximal to the electrode **38**. The sleeve **52** includes a tapered region **56** that lies between the cylindrical bearing **54** and the electrode **38**. The ultrasound catheter cannot move forward because the cylindrical bearing **54** engages the tapered region **56** when the driveshaft **30** moved distally. Similarly, the electrode **38** cannot be withdrawn into the sheath **32** because the electrode **38** has a diameter that is larger than the diameter of the tapered region **56**. The sleeve **52** is preferably made of a rubberized, sonically transparent material such as a heat shrink tubing. The tapered region is made by heating the tubing with a wrap of a current carrying wire.

FIG. 2 illustrates a currently preferred method of coupling the RF ablation energy produced by the RF generator **50** to the conductive driveshaft that rotates the ultrasound transducer **34**. At the proximal end of the catheter **12**, is a slip ring coupler **60** that delivers ultrasound driving signals to and receives corresponding echo signals from the ultrasound transducer **34** that is positioned at the distal end of the catheter **12**, as described in U.S. Pat. No. 5,000,185.

To deliver the RF ablation energy to the driveshaft **30**, a spring contact **62** is coupled to the driveshaft **30** such that the spring contact **62** maintains an electrical connection as the driveshaft **30** is rotated. Upon activation of the RF generator **50** by the physician, RF ablation energy travels along the conductive driveshaft **30** to the electrode **38** at the distal tip of the catheter where the energy ablates occluding material in the vessel. By viewing an ultrasound image of the tissue on the monitor **22**, the physician is able to keep the catheter **12** at the proper position in the vessel and minimize the risk of applying the RF ablation energy in the vicinity of the vessel wall.

In order to control the delivery of RF ablation energy from the electrode **38** into the occluding material, a variety of electrode tip shapes may be used. In addition to the conventional hemispherical distal electrode tip, an electrode may include a distal tip having a concave surface **70** as shown in FIG. 3A. Alternatively, the electrode may include a distal tip having a hemispherical, convex distal tip **72** that is roughened as shown in FIG. 3B. The roughened surface creates an increased RF potential at the peaks of the roughened surface, which may uniformly distribute the area in which the RF ablation energy enters the occluding material in the patient's vessel.

In yet another embodiment of the invention, the electrode includes an expandable distal tip **74** that is made of a pattern of intermeshed conductive wires as shown in FIG. 3C. When the electrode is extended out of a surrounding sheath, the wires revert to a pre-bent shape, thereby expanding the diameter of the electrode. The expanded electrode may be useful to create larger lumens in the occluding material.

FIG. 4 shows yet another embodiment of the present invention. Here, separate lumens of multi-lumen catheter **80** are used to route an ultrasound catheter **82** and a guidewire **84** between the proximal end of the catheter and the treatment site. In practice, the guidewire **84** is first advanced into the patient and the multi-lumen catheter **80** is routed over the guidewire **84** followed by the ultrasound catheter **82** in a different lumen of the multi-lumen catheter **80**.

In this embodiment of the invention, the ultrasound catheter **82** is only used to obtain images of the patient's vessel. The RF generator **50** is connected to the guidewire **84**, which is conductive, in order to deliver RF ablation energy to the occluding material at a point where the guidewire exits the multi-lumen catheter **80**. In order to control the delivery of RF energy within the vessel, it is desirable that the length of the guidewire **84** that extends beyond the distal end of the multi-lumen catheter **80** be controlled. Therefore, the multi-lumen catheter **80** may include a marker band or other radio-opaque material near its distal end to allow the relative position of the distal end of the guidewire **84** and the distal end of the multi-lumen catheter **80** to be monitored.

In practice, the ultrasound catheter **82** is advanced in the vessel and an image of the tissue surrounding the ultrasound catheter **82** is obtained. After an image has been obtained, the ultrasound catheter **82** is retracted into the multi-lumen catheter **80** and the guidewire **84** is advanced out the distal end of the multi-lumen catheter **80** and RF ablation energy

5

is applied to the guidewire, thereby ablating a portion of the occluding material in the vessel. The ultrasound catheter **82** is then extended into the newly created lumen and the process repeats until the vessel has been revascularized.

In order to further control the position of the ultrasound/ RF ablation catheter in the vessel, a combination ultrasound/ RF ablation catheter **98** may be routed in a steerable sheath **100** as shown in FIG. **5**. The steerable sheath **100** preferably includes a steering wire **102** positioned along one wall of the sheath. A control mechanism **104** at the proximal end of the steerable sheath **100** is manipulated by the physician to retract or extend the steering wire **102**, thereby causing deflection of the distal tip of the steerable sheath **100**. The deflection of the distal tip is preferably adjusted such that the RF ablation/ultrasound catheter **98** is positioned in the center of the vessel in order to avoid applying the RF ablation energy too close to the vessel walls.

FIG. **6** shows yet another alternative embodiment of the present invention. Here, an ultrasound catheter **110** is routed through a steerable sheath **112** in order to position the ultrasound catheter **110** at a desired location in a patient's vessel. The ultrasound catheter **110** extends through a hole **114** at the distal end of the steerable sheath **112**. In contrast to the embodiment shown in FIG. **5** that utilizes a combination ultrasound and RF ablation catheter, the catheter **110** is only used for obtaining ultrasound images of the vessel walls. To deliver the RF ablation energy, the steerable sheath **112** includes a conductive distal tip **116** having a hole **114** in it through which the ultrasound catheter **110** can be extended. RF energy is supplied to the conductive tip **116** to ablate occluding material in the vessel. The conductive tip **116** may be roughened as with the electrode tip shown in FIG. **3B** to control the area in which ablation energy enters the occluding material.

In operation, the ultrasound catheter **110** can be advanced through the hole **114** in the distal tip **116** of the steerable sheath **112**. Once an image of the tissue has been obtained, the ultrasound catheter **110** can be retracted into the steerable sheath **112** and RF ablation energy applied to the distal tip **116**. The ultrasound catheter **110** is then inserted into the newly ablated area and the process continues.

FIG. **7** shows yet another alternative embodiment of the present invention. A multi-lumen catheter **120** includes a lumen through which an ultrasound catheter **122** can be routed. In addition, an aspiration/ablation catheter **130** can be used for ablating occluding material in the vessel and aspirating the ablated material. An aspiration/ablation catheter **130** is terminated with a cylindrical electrode **132** having a central lumen **134** in it that is connected to a vacuum source (not shown). RF energy is applied to the cylindrical electrode **132** to cut a core in the occluding material. Aspiration is applied to the aspiration catheter to remove ablated material.

As can be seen, the present invention is a simple catheter system that obtains images of a vessel and ablates occluding

6

material such that a greater number of total chronic occlusions may be able to be treated without resorting to cardiac bypass surgery. Although the present embodiment of the invention utilizes a mechanically rotated ultrasound transducer, it will be appreciated that the ultrasound transducer could be rotated by hand to obtain a desired or 360° view of a vessel wall. This is a so-called "A" mode of operation. Alternatively, it is possible to use multiple transducers oriented in different directions so that a desired or 360° view of the vessel wall can be created with minimum rotation the ultrasound catheter.

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

1. A system for treating occluded vessels, comprising:
 - an ultrasound catheter including:
 - at least one ultrasound transducer that directs ultrasonic energy into and receives corresponding echo signals from a vessel wall;
 - a conductive driveshaft that rotates the at least one ultrasound transducer to obtain a 360° image of the vessel wall;
 - an electrode coupled to the distal end of the conductive driveshaft; and
 - an RF energy source that selectively applies RF ablation energy to the conductive driveshaft to deliver the RF ablation energy to the electrode.
2. The system of claim **1**, wherein the at least one ultrasound transducer is fitted within the electrode and is positioned to direct ultrasound signals into and receive echo signals from a position in the vessel distal to the electrode.
3. The system of claim **1**, wherein the electrode has a distal tip that is concave.
4. The system of claim **1**, wherein the electrode has a distal tip that is hemispherical and roughened.
5. The system of claim **1**, wherein the electrode has a distal tip that is expandable.
6. The system of claim **1**, wherein the ultrasound catheter is routed through a steerable sheath.
7. A method of ablating an occlusion in a vessel, comprising:
 - advancing a catheter into the vessel near the area of the occlusion;
 - advancing a conductive driveshaft within the catheter, wherein the driveshaft rotates an imaging device for obtaining images of the occlusion and/or the vessel in the area near the occlusion, said drive shaft also having an electrode for delivery of ablation energy;
 - rotating said drive shaft to obtain 360-degree images of said occlusion and/or said vessel; and
 - applying ablation energy to said conductive drive shaft to be delivered to the occlusion by said electrode.

* * * * *

专利名称(译)	射频消融和超声导管穿越慢性完全闭塞		
公开(公告)号	US6394956	公开(公告)日	2002-05-28
申请号	US09/514970	申请日	2000-02-29
申请(专利权)人(译)	SCIMED LIFE SYSTEMS INC.		
当前申请(专利权)人(译)	BOSTON SCIENTIFIC SCIMED , INC.		
[标]发明人	CHANDRASEKARAN CHANDRU V GUO ZIHONG PANTAGES ANTHONY J MASTERS DONALD KAVECKIS RYAN		
发明人	CHANDRASEKARAN, CHANDRU V. GUO, ZIHONG PANTAGES, ANTHONY J. MASTERS, DONALD KAVECKIS, RYAN		
IPC分类号	A61B18/14 A61B18/00 A61B8/12 A61B8/00		
CPC分类号	A61B8/12 A61B8/445 A61B8/4461 A61B18/1492 A61B2017/003 A61B2018/00208 A61F9/0079 A61B2018/0041 A61B2018/00541 A61B2018/144 A61B2018/1861 A61B2019/5278 A61B2018/00351 A61B2090/3782		
外部链接	Espacenet USPTO		

摘要(译)

组合导管包括超声换能器和RF消融电极。超声换能器将超声信号发射到血管中并从血管接收回波信号。处理回波信号并用于产生导管周围组织的图像。驱动轴旋转超声换能器以获得血管壁的360°视图。在驱动轴的远端是电极。RF发生器电耦合到驱动轴，以将RF能量传递到驱动轴远端处的电极，以消融容器中的阻塞材料。电极可具有各种尖端形状，包括凹形，粗糙形或可膨胀构型，这取决于容器的尺寸和待烧蚀的闭塞材料的组成。或者，RF消融能量可以被传递到导丝，该导丝用于将超声导管引导通过患者的脉管系统。最后，可操纵的导管可用于进一步将超声导管和消融电极定位在血管中。

