



US007472597B2

(12) **United States Patent**
Zhang et al.

(10) **Patent No.:** **US 7,472,597 B2**
(45) **Date of Patent:** **Jan. 6, 2009**

(54) **ULTRASONIC IMAGING DEVICE AND THE INFORMATION PROCESSING METHOD THEREOF**

(75) Inventors: **Liguo Zhang**, Nanshan (CN); **Zhiyong Guan**, Nanshan (CN); **Xujin He**, Nanshan (CN)

(73) Assignee: **Shenzhen Mindray Bio-Medical Electronics Co., Ltd.**, Shenzhen (CN)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 395 days.

(21) Appl. No.: **11/323,087**

(22) Filed: **Dec. 30, 2005**

(65) **Prior Publication Data**

US 2006/0288785 A1 Dec. 28, 2006

(30) **Foreign Application Priority Data**

Jun. 26, 2005 (CN) 2005 1 0035602

(51) **Int. Cl.**
G01S 15/00 (2006.01)
A61B 8/14 (2006.01)

(52) **U.S. Cl.** **73/606**; 73/618; 73/626; 600/437; 600/443

(58) **Field of Classification Search** 73/606, 73/596, 597, 618, 626; 600/437, 443, 447, 600/453, 455, 457, 448
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,231,510 B1 * 5/2001 Negrin et al. 600/443

6,468,217 B1 10/2002 Faziolo
6,475,146 B1 * 11/2002 Frelburger et al. 600/437
6,638,227 B2 * 10/2003 Bae 600/443
6,771,822 B1 * 8/2004 Brackett 382/232
6,885,113 B2 * 4/2005 Lim 290/40 R
2004/0028376 A1 * 2/2004 Maita 386/68
2005/0096539 A1 * 5/2005 Leibig et al. 600/437
2007/0161898 A1 * 7/2007 Hao et al. 600/443
2007/0167780 A1 * 7/2007 Imamura et al. 600/443

FOREIGN PATENT DOCUMENTS

CN 1296705 A 5/2001
CN 1528243 A 9/2004
JP 200527745 A 2/2005

* cited by examiner

Primary Examiner—Hezron Williams


Assistant Examiner—J M Saint Surin


(74) *Attorney, Agent, or Firm*—Kory D. Christensen; Stoel Rives LLP

(57) **ABSTRACT**

An ultrasonic imaging device, comprising: a receiver, for receiving ultrasonic signals which carry information about human body; a processor, for analyzing and processing the received ultrasonic signals in order to get image and/or sound signals; a controller, for issuing at least one instruction; and a recorder, for recording the image and/or sound signals on recording medium in digital form in accordance with the instruction.

11 Claims, 3 Drawing Sheets



**Fig.1**

(Prior Art)





Fig.2

**Fig.3**

ULTRASONIC IMAGING DEVICE AND THE INFORMATION PROCESSING METHOD THEREOF

FIELD OF THE INVENTION

The invention relates to ultrasonic imaging device, in particular, relates to an ultrasonic imaging device which comprises integrated recording device, and the information processing method used in the ultrasonic imaging device.

DESCRIPTION OF THE RELATED ART

In medical ultrasonic systems, the ultrasonic signals which carry the information relating to human body should be recorded. FIG. 1 shows the ultrasonic system used on human body, comprising probe **101**, ultrasonic transmitting unit **102**, ultrasonic receiving unit **103**, central control unit **104**, control panel **105**, beamformer **106**, black and white image signal processing unit **107**, color bloodstream signal processing unit **108**, Doppler signal processing unit **109**, scan-transforming unit **110**, speaker **111** and display **112**.

The probe **101** is a transducer of ultrasound, for transducing the electric power to sound power and vice versa. The ultrasonic transmitting unit **102** could generate a set of high voltage pulses in a specific timing. The high voltage pulses are transduced into ultrasonic waves entering into human body's tissue by probe **101**. The ultrasonic waves reflected by the tissue are transduced into electric signals by probe **101**. The ultrasonic receiving unit **103** processes the received electric signals for achieving high voltage isolation amplification and A/D conversion, and then sends the processed signals into beamformer **106** for synthesizing the beam. The synthesized back wave signals are sent into black and white image signal processing unit **107**, color bloodstream processing unit **108** and Doppler signal processing unit **109** respectively, for analyzing and processing. The black and white image signal processing unit **107** renders the signals by brightness modulation, and outputs B mode image, M mode image, the color bloodstream signal processing unit **108** outputs color bloodstream image, the Doppler signal processing unit **109** renders the signals by using of Doppler frequency-shifting effects and outputs positive and negative direction sound signals of bloodstream besides the sound spectrum. The image signals output by above-mentioned three units are sent to scan-transforming unit **110**, for producing image signals suit for displaying on display **112**. The scan-transformed image signals are then sent into display **112** for displaying. The positive and negative direction sound signals of bloodstream produced by Doppler signal processing are sent into speaker **111**, which converts the sound signals into audible sound signals for output. The central control unit **104** controls the operations of all the above-mentioned units. The control panel **105**, display **112** and speaker **111** are the human-machine interface of the ultrasonic system. The control panel **105** is the input device of the ultrasonic system. The user could input control instructions and information etc. to central control unit by control panel **105**. The display **112** is the output device of image, and the speaker **111** is the output device of sound. In order to record the processed image and/or sound signal, the ultrasonic system connects a VCR (not shown), which located outside the ultrasonic system, and sends the respective signals output by the three signal processing units into the external VCR for recording.

In the conventional ultrasonic systems, the VCR (Video Cassette Recorder) system is used for recording the image and sound signals captured by ultrasonic system, wherein, the

VCR system is located outside the ultrasonic system. There are many disadvantages for recording image and sound signal of the ultrasonic system by external VCR. First, the analog recording used by VCR is subject to the influence of environment such that the reliability of the recording is low and does not suit for long time preservation. Second, the tapes serve as recording medium are expensive and the capacity thereof is small. Third, the external VCR takes up a lot of space, and could not operate conveniently.

SUMMARY OF THE INVENTION

In order to solve above-mentioned problems, the object of present invention is to provide an ultrasonic imaging device, which comprising the function of recording image and/or sound signal.

One aspect of present invention is to provide an ultrasonic imaging device, comprising: a receiver, for receiving ultrasonic signals which carry information about human body; a processor, for analyzing and processing the received ultrasonic signals in order to get image and/or sound signals; a controller, for issuing at least one instruction; a recorder, for recording the image and/or sound signals on recording medium in digital form in accordance with the instruction.

The other aspect of present invention is to provide an information processing method used for ultrasonic imaging device, including steps: (a) receiving the ultrasonic signals which carry information about human body; (b) analyzing and processing the received signals in order to get image and/or sound signals; (c) issuing at least one instruction; (d) recording the image and/or sound signals onto a recording medium in digital form in accordance with the instruction.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be described in detail with accompanied figures and the embodiments, wherein:

FIG. 1 shows the block gram of the ultrasonic system;

FIG. 2 shows the block gram of the ultrasonic imaging device of present invention; and

FIG. 3 is the flowchart of the information processing procedure of present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

The embodiments of present invention will be described in detail with accompanied figures.

FIG. 2 shows the structure of the ultrasonic imaging device of present invention, comprising: probe **101**, ultrasonic transmitting unit **102**, ultrasonic receiving unit **103**, central control unit **104**, control panel **105**, beamformer **106**, black and white image signal processing unit **107**, color bloodstream signal processing unit **108**, Doppler signal processing unit **109**, scan-transforming unit **110**, speaker **111**, display **112**, image and sound encoding compressor **213**, DVD recording sub-control system **214**, DVD recording unit **215**, image and sound decoding decompressor **216** and microphone **217**. The same units as those in FIG. 1 are assigned with the same reference numbers and the descriptions thereof are omitted.

In comparing with conventional ultrasonic systems, the ultrasonic imaging device of present invention further comprises a recording module for recording the image and/or sound signals onto a recording medium. The recording module encodes and compresses the image and/or sound signals produced by the ultrasonic device as well as the sound signals inputted from the microphone **217** in real-time by use of

image and sound encoding compressor **213**. Then the recording module sends the encoded and compressed image and/or sound signals as well as encoded and compressed sound signals which are input from the microphone into DVD recording unit **215** in accordance with the control of DVD recording sub-control unit **214**. The encoded and compressed signals are then recorded onto recording medium.

Moreover, under the control of DVD recording sub-control unit **214**, the DVD recording unit **215** could read the encoded and compressed image and/or sound signals from the recording medium, and send the signals to image and sound decoding decompressor **216** for decoding and decompressing. The decoded and decompressed image signals are then sent to scan-transforming unit **210** for the transformation from interleave scan to progressive scan. The scan-transformed image signals are combined with the display items of the ultrasonic system (such as menu, etc.), and are further displayed on the display **112** in a progressive way. The decoded and decompressed sound signals are played back by the speaker **111**.

In the whole ultrasonic system, the control panel **205** and the microphone **217** are input devices. The users could input various instructions (such as record, playback, open, close, etc.) into central control unit **204** via the control panel **205**. The control of operations of the ultrasonic system and the recording module are handled by central control unit **204**. The central control unit **204** controls ultrasound transmitting and receiving, beamforming, signal processing and scan-transforming, etc. directly, and controls the recording module by sending instructions to DVD recording sub-control system **214**. The user could input sound signals to the ultrasonic system via microphone **217** for recording.

The central control unit sends control instructions to DVD recording sub-control system **214**, then the DVD recording sub-control system **214** parses the received instructions and generates corresponding commands to image and sound encoding compressor, image and sound decoding decompressor, DVD recording unit, respectively. Those components then operate according to the commands generated by DVD recording sub-control system **214**.

The central control unit **204** communicates with DVD recording sub-control system **214** via serial communication protocol, which is suit for saving bit-width of the hardware. The length of control serial code could be determined depends on the number of the control instructions (such record, playback, open, close, etc.). The length of the control code (i.e. the number of the instructions) could be easily expanded and is not constrained by hardware, which is suit for the integration of the recording module.

It should be noted that, by using of other components, the present embodiment could be implemented in many other similar ways. The input device of the ultrasonic system could be the menu on the display, which could be operated to input various instructions. The central control unit could communicate with DVD recording sub-control system via other communication protocols, such as parallel communication protocol, etc. The signal processing unit could include separate M mode/B mode ultrasonic signal processing unit. The Doppler signal processing unit could include pulse wave and/or continuous wave Doppler ultrasonic signal processing unit. Moreover, the recording unit in present invention is not limit to DVD recording unit, any other recorder that could record data on recording medium, such as CD-ROM recorder, could be used as the recording unit.

Another embodiment of present invention will be described in reference to accompanied figures.

FIG. 3 shows the flowchart of the information processing method of the invention.

In step S1, the ultrasonic receiving unit receives the ultrasonic signals which carry the information about human body. In step S2, the signal processing unit (such as black and white signal processing unit, etc.) analyzes and processes the received signals. In step S3, the control unit sends out the instruction for indicating the recording after encoding compression procedure or indicating the playback after decoding decompression procedure. If the instruction indicates encoding compression and recording (S3: R), the encoding compressor encodes and compresses the signals, then records the encoded signals in a digital form in step S4. If the instruction indicates decoding decompression and playback (S3: P), the decoding decompressor decodes and decompresses the signals, then scan-transforms the decoded signals in step S5, such that the signals which carry the information of human body could be displayed.

In the above-mentioned information processing method, the received and processed signals could be (but not limits to) M mode ultrasonic signals, B mode ultrasonic signals, C mode ultrasonic signals, CM mode ultrasonic signals and Doppler ultrasonic signals, etc.

By using of above-mentioned information processing method, the ultrasonic imaging device could achieve the recording of image and/or sound signals.

Although the invention is described by way of embodiments, it is understood by those skilled in the art that many modifications and changes could be made without departing from the essence of the spirit and scope of the appended claims.

ADVANTAGES OF THE INVENTION

The present invention further integrates recording function of image and/or sound signals in ultrasonic system without influences the performance of the ultrasonic system. The ultrasonic imaging device of the invention is highly integrated and easy to control. Moreover, the ultrasonic imaging device of the invention could records the image and sound signals on the medium which are good at preservation. The recording procedure could operate in real-time, such that the ultrasonic imaging device could be used widely in ultrasonic systems.

What is claimed is:

1. An ultrasonic imaging device, comprising:

a receiver, for receiving ultrasonic signals which carry information about a human body;

a processor, for analyzing and processing the received ultrasonic signals in order to obtain image and/or sound signals;

a controller, for issuing at least one instruction;

a recorder, for recording the image and/or sound signals on a recording medium in digital form in accordance with the instruction, wherein the recorder is integrated within the ultrasonic imaging device; and

an encoding compressor, for encoding and compressing the image and/or sound signals in accordance with the instruction,

wherein the recorder records the encoded and compressed signals onto the recording medium in accordance with the instruction.

2. The ultrasonic imaging device according to claim 1, further comprising:

a decoding decompressor, for decoding and decompressing the digital signals in the recording medium in accordance with the instruction;

an imaging device, for transforming the scan format of the decoded and decompressed signals in order to display

5

the ultrasonic signals which carry information about human body on a display device.

3. The ultrasonic imaging device according to claim 2, wherein the processor comprises:

a Doppler signal processing unit, for rendering the signals by use of Doppler frequency-shifting effects.

4. The ultrasonic imaging device according to claim 3, wherein the Doppler signal processing unit comprises:

a pulse wave and/or continuous wave Doppler signal processing unit.

5. The ultrasonic imaging device according to claim 2, further comprising:

a sound output device, for outputting the decoded and decompressed signals as audible sound signals.

6. The ultrasonic imaging device according to claim 1, wherein the processor comprises:

M mode and/or B mode ultrasonic signals processing unit, for rendering the signals in a brightness modulation way.

7. The ultrasonic imaging device according to claim 1, further comprising:

a sound input device, for transferring the received sound signals to the encoding compressor.

8. The ultrasonic imaging device according to claim 1, wherein, the controller issuing the instruction via serial communication protocol.

9. An information processing method for ultrasonic imaging device, comprising:

6

(a) receiving the ultrasonic signals which carry information about human body;

(b) analyzing and processing the received signals in order to obtain image and/or sound signals;

(c) issuing at least one instruction;

(d) recording the image and/or sound signals onto a recording medium in digital form in accordance with the instruction; and

(e) encoding and compressing the image and/or sound signals in accordance with the instruction; wherein the encoded and compressed signal are recorded on the recording medium in accordance with the instruction.

10. The information processing method according to claim 9, further comprising:

decoding and decompressing the digital signals in the recording medium in accordance with the instruction; and transforming the scan format of the decoded and decompressed signals in order to display the signals which carry information about human body.

11. The information processing method according to claim 10, wherein, in step (b), the received signals are at least one of M mode ultrasonic signal, B mode ultrasonic signal, C mode ultrasonic signal, CM mode ultrasonic signal and Doppler ultrasonic signal.

* * * * *

专利名称(译)	超声波成像装置及其信息处理方法		
公开(公告)号	US7472597	公开(公告)日	2009-01-06
申请号	US11/323087	申请日	2005-12-30
[标]申请(专利权)人(译)	深圳迈瑞生物医疗电子股份有限公司		
申请(专利权)人(译)	深圳迈瑞生物医疗电子股份有限公司.		
当前申请(专利权)人(译)	深圳迈瑞生物医疗电子股份有限公司.		
[标]发明人	ZHANG LIGUO GUAN ZHIYONG HE XUJIN		
发明人	ZHANG, LIGUO GUAN, ZHIYONG HE, XUJIN		
IPC分类号	G01S15/00 A61B8/14		
CPC分类号	A61B8/00 A61B8/488 A61B8/468		
优先权	200510035602.1 2005-06-26 CN		
其他公开文献	US20060288785A1		
外部链接	Espacenet USPTO		

摘要(译)

一种超声波成像装置，包括：接收器，用于接收携带有关人体信息的超声波信号；处理器，用于分析和处理所接收的超声信号，以获得图像和/或声音信号；控制器，用于发出至少一条指令；记录器，用于根据指令以数字形式在记录介质上记录图像和/或声音信号。

