

(12) **Patent Application Publication**
Kim

(43) **Pub. Date:** **Jun. 16, 2011**

Publication Classification

(52) **U.S. Cl.** 600/437

(57) **ABSTRACT**

An ultrasound diagnostic system is disclosed. The ultrasound diagnostic system allows an examiner and an examinee to view a diagnosis result on different screens through a single display unit by adjusting viewing angles depending on positions of the examiner and the examinee, thereby providing a screen for the current diagnosis status to the examinee without a separate monitor for the examinee and providing an optimized screen for diagnosis to the examiner.

Dec. 11, 2009 (KR) 10-2009-0122852




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5





Fig. 6



ULTRASOUND DIAGNOSTIC SYSTEM

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of Korean Patent Application No. 10-2009-0122852, filed Dec. 11, 2009, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates to an ultrasound diagnostic system and, more particularly, to an ultrasound diagnostic system that allows an examiner and an examinee to view a diagnosis result on different screens through a single display unit by adjusting viewing angles depending on positions of the examiner and the examinee.

[0004] 2. Description of the Related Art

[0005] Generally, an ultrasound diagnostic system refers to a non-invasive apparatus that irradiates an ultrasound signal from a surface of a patient body towards a target internal organ beneath the body surface and obtains an image of a monolayer or blood flow in soft tissue from information in the reflected ultrasound signal (ultrasound echo-signal). The ultrasound diagnostic system has been widely used for diagnosis of the heart, the abdomen, the urinary organs, and in obstetrics and gynecology due to various merits such as small size, low price, real-time image display, and high stability through elimination of radiation exposure, as compared with other image diagnostic systems, such as X-ray diagnostic systems, computerized tomography scanners (CT scanners), magnetic resonance imagers (MRIs), nuclear medicine diagnostic apparatuses, and the like.

[0006] The ultrasound diagnostic system transmits an ultrasound signal to a diagnosis target, receives the ultrasound echo-signal reflected therefrom, and displays an ultrasound image, particularly, a two-dimensional grey-scale ultrasound image, on a monitor, which corresponds to a display mode, for example, B-mode, M-mode, Doppler mode, etc., based on the received echo-signal. It should be noted that the above description is provided for understanding the background of the invention and is not a description of a conventional technique.

[0007] In diagnosis with the ultrasound diagnostic system, two monitors are used to provide a diagnosis result to both an examiner and an examinee such that the monitors for the examiner and the examinee display the same image or such that the monitor for the examiner displays all necessary information for diagnosis and the monitor for the examinee displays only an image of the diagnosis result.

[0008] As such, separate monitors are needed to provide the diagnosis result to both the examiner and the examinee.

SUMMARY OF THE INVENTION

[0009] The present invention is conceived to solve the problem of the related art as described above, and an aspect of the invention is to provide an ultrasound diagnostic system that allows an examiner and an examinee to view a diagnosis result on different screens through a single display unit by adjusting viewing angles depending on positions of the examiner and the examinee.

[0010] In accordance with one aspect of the invention, an ultrasound diagnostic system includes: an ultrasound diagnostic unit configured to transmit an ultrasound signal to an

examinee and to receive the ultrasound signal reflected from the examinee to generate an ultrasound image of the examinee; a display unit comprising a plurality of barrier layers; a viewing angle selection unit configured to select viewing angles depending on positions of an examiner and the examinee; a switching unit configured to selectively activate the plurality of barrier layers in response to a selection of the selection unit; an image processor configured to mix and output a plurality of images to the display unit depending on the viewing angles selected by the viewing angle selection unit to independently provide diagnosis information and the ultrasound images generated by the ultrasound diagnostic unit to the examiner and the examinee; and a controller configured to control the ultrasound diagnostic unit and the image processor in response to a selection of the examiner.

[0011] The barrier layers may be barrier layers of a parallax barrier type.

[0012] The barrier layers may include at least a longitudinal lattice-shaped barrier layer, a transverse lattice-shaped barrier layer, and a diagonal lattice-shaped barrier layer.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] The above and other aspects, features and advantages of the invention will become apparent from the following description of embodiments given in conjunction with the accompanying drawings, in which:

[0014] FIG. 1 is a block diagram of an ultrasound diagnostic system according to one embodiment of the present invention;

[0015] FIG. 2 illustrates barrier layers of the ultrasound diagnostic system according to the embodiment of the present invention;

[0016] FIG. 3 illustrates two screens viewed at right and left sides in the ultrasound diagnostic system according to the embodiment of the present invention;

[0017] FIG. 4 illustrates two screens viewed at upper and lower sides in the ultrasound diagnostic system according to the embodiment of the present invention; and

[0018] FIGS. 5 and 6 illustrate two screens diagonally viewed in the ultrasound diagnostic system according to the embodiment of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENT

[0019] Exemplary embodiments of the invention will now be described in detail with reference to the accompanying drawings. It should be noted that the drawings are not to precise scale and may be exaggerated in thickness of lines or size of components for descriptive convenience and clarity only. Furthermore, terms used herein are defined by taking functions of the invention into account and can be changed according to the custom or intention of users or operators. Therefore, definition of the terms should be made according to overall disclosures set forth herein.

[0020] FIG. 1 is a block diagram of an ultrasound diagnostic system according to one embodiment, FIG. 2 illustrates barrier layers of the ultrasound diagnostic system according to the embodiment, FIG. 3 illustrates two screens viewed at right and left sides in the ultrasound diagnostic system according to the embodiment, FIG. 4 illustrates two screens viewed at upper and lower sides in the ultrasound diagnostic system according to the embodiment, and FIGS. 5 and 6

illustrate two screens diagonally viewed in the ultrasound diagnostic system according to the embodiment.

[0021] Referring to FIG. 1, an ultrasound diagnostic system 100 of this embodiment includes an ultrasound diagnostic unit 10, a display unit 40, a viewing angle selection unit 60, a switching unit 70, an image processor 30, and a controller 20.

[0022] The ultrasound diagnostic unit 10 transmits an ultrasound signal to an examinee and receives the ultrasound signal reflected from the examinee to generate an ultrasound image of the examinee.

[0023] As shown in FIG. 2, the display unit 40 includes a plurality of barrier layers of a parallax barrier type formed by overlapping a longitudinal lattice-shaped barrier layer 51, a transverse lattice-shaped barrier layer 52 and diagonal lattice-shaped barrier layers 53, 54 on top of one another.

[0024] The viewing angle selection unit 60 selects viewing angles depending on positions of an examiner and the examinee. In other words, the viewing angle selection unit 60 selects viewing angles at which the examiner and the examinee view the single display unit 40.

[0025] The switching unit 70 selectively activates the plurality of barrier layers in response to a selection of the selection unit 60. For example, when an examiner is located at a right or left side of an examinee lying on a table in the diagnostic system, the switching unit 70 activates the diagonal lattice-shaped barrier layer 54 as well as the longitudinal lattice-shaped barrier layer 51.

[0026] The image processor 30 mixes and outputs a plurality of images to the display unit 40 depending on the viewing angles selected by the viewing angle selection unit 60 to independently provide diagnosis information and the ultrasound images generated by the ultrasound diagnostic unit 10 to the examiner and the examinee.

[0027] The controller 20 controls the ultrasound diagnostic unit 10 and the image processor 30 in response to a selection of the examiner.

[0028] As such, when an examiner wishes to provide the diagnostic status to an examinee during diagnosis with the ultrasound diagnostic unit, viewing angles of the examiner and the examinee are selected through the viewing angle selection unit 60, and the image processor 30 mixes and outputs images for the examiner and the examinee to the display unit 40 such that the images are independently provided to the examiner and the examinee through the barrier layers 50.

[0029] In FIG. 3, when an examiner and an examinee are located at left and right sides in the diagnostic system, the longitudinal lattice-shaped barrier layer 51 is activated through the viewing angle selection unit 60 to allow the display unit 40 to display a screen, which is viewed from the left side by the examiner as Screen A providing information for both diagnosis and a diagnosis result and is viewed from the right side by the examinee as Screen B providing only the diagnosis result, so that the examiner and the examinee can see the independent screens through the single display unit 40.

[0030] In FIG. 4, when an examiner and an examinee are located at upper and lower sides in the diagnostic system, the transverse lattice-shaped barrier layer 52 is activated through the viewing angle selection unit 60 to allow the display unit 40 to display a screen, which is viewed from the upper side by the examiner as Screen A providing information for both diagnosis and a diagnosis result and is viewed from the lower side by the examinee as Screen B providing only the diagnosis

result, so that the examiner and the examinee can see the independent screens through the single display unit 40.

[0031] Further, in FIGS. 5 and 6, when an examiner and an examinee are diagonally located in the diagnostic system, the diagonal lattice-shaped barrier layers 53, 54 are activated through the viewing angle selection unit 60 to allow the display unit 40 to display a screen, which is viewed from a lateral upper side by the examiner as Screen A providing information for both diagnosis and a diagnosis result and is viewed from a lateral lower side by the examinee as Screen B providing only the diagnosis result, so that the examiner and the examinee can see the independent monitors through the single display unit 40.

[0032] As such, the ultrasound diagnostic system of the embodiment can realize dual screens to be independently provided to both an examiner and an examinee through the single display unit 40 wherever the examiner and the examinee are positioned in the ultrasound diagnostic system.

[0033] According to the embodiment, the ultrasound diagnostic system allows an examiner and an examinee to view a diagnosis result on different screens through a single display unit by adjusting viewing angles depending on positions of the examiner and the examinee, thereby providing a screen for the current diagnosis status to the examinee without a separate monitor for the examinee and providing an optimized screen for diagnosis to the examiner.

[0034] Although some embodiments have been provided to illustrate the invention in conjunction with the drawings, it will be apparent to those skilled in the art that the embodiments are given by way of illustration only, and that various modifications and equivalent embodiments can be made without departing from the spirit and scope of the invention. The scope of the invention should be limited only by the accompanying claims.

What is claimed is:

1. An ultrasound diagnostic system comprising:

an ultrasound diagnostic unit configured to transmit an ultrasound signal to an examinee and to receive the ultrasound signal reflected from the examinee to generate an ultrasound image of the examinee;

a display unit comprising a plurality of barrier layers;

a viewing angle selection unit configured to select viewing angles depending on positions of an examiner and the examinee;

a switching unit configured to selectively activate the plurality of barrier layers in response to a selection of the selection unit;

an image processor configured to mix and output a plurality of images to the display unit depending on the viewing angles selected by the viewing angle selection unit to independently provide diagnosis information and the ultrasound images generated by the ultrasound diagnostic unit to the examiner and the examinee; and

a controller configured to control the ultrasound diagnostic unit and the image processor in response to a selection of the examiner.

2. The ultrasound diagnostic system according to claim 1, wherein the barrier layers are barrier layers of a parallax barrier type.

3. The ultrasound diagnostic system according to claim 1, wherein the barrier layers comprise at least a longitudinal lattice-shaped barrier layer, a transverse lattice-shaped barrier layer, and a diagonal lattice-shaped barrier layer.

* * * * *

专利名称(译)	超声诊断系统		
公开(公告)号	US20110144488A1	公开(公告)日	2011-06-16
申请号	US12/959215	申请日	2010-12-02
[标]申请(专利权)人(译)	金大中YOUNG		
申请(专利权)人(译)	金大中YOUNG		
当前申请(专利权)人(译)	金大中YOUNG		
[标]发明人	KIM DAE YOUNG		
发明人	KIM, DAE YOUNG		
IPC分类号	A61B8/00		
CPC分类号	A61B8/463 G01S7/52053 G02B27/2214 G02B2027/0129 G02B27/022 G02B30/27		
优先权	1020090122852 2009-12-11 KR		
其他公开文献	US8961419		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种超声诊断系统。超声诊断系统允许检查者和受检者通过单个显示单元通过根据检查者和被检者的位置调整视角来在不同屏幕上查看诊断结果，从而向受检者提供当前诊断状态的屏幕而无需为考生提供单独的监视器，并为考官提供优化的诊断屏幕。

