



US006447451B1

(12) **United States Patent**
Wing et al.

(10) **Patent No.:** **US 6,447,451 B1**
(45) **Date of Patent:** **Sep. 10, 2002**

(54) **MOBILE ULTRASOUND DIAGNOSTIC
INSTRUMENT AND DOCKING STAND**

(75) Inventors: **Gregory Wing**, Carnation; **Steven
Bunce**, Sedro Wooly; **Andrew T.
Dunn**, Redmond; **Brian Epps**, Seattle;
Paul Stevens, Kirkland, all of WA (US)

(73) Assignee: **SonoSite, Inc.**, Bothell, WA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/564,600**

(22) Filed: **May 3, 2000**

Related U.S. Application Data

(60) Provisional application No. 60/132,515, filed on May 4,
1999.

(51) **Int. Cl.**⁷ **A61B 8/01**

(52) **U.S. Cl.** **600/437**

(58) **Field of Search** 248/289.11; 600/137,
600/104, 102, 106, 437, 459, 228-229;
439/374; 73/618; 128/903, 904

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,640,960 A	6/1997	Jones et al.	128/661.07
5,655,741 A *	8/1997	Watkins	248/289.11
5,687,717 A	11/1997	Halpern et al.	128/630
5,840,012 A *	11/1998	Krauter et al.	600/102
5,888,087 A *	3/1999	Hanson et al.	439/374

* cited by examiner

Primary Examiner—Marvin M. Lateef


Assistant Examiner—Ruby Jain


(74) *Attorney, Agent, or Firm*—Townsend and Townsend
and Crew LLP; Henry K. Woodward

(57) **ABSTRACT**

A mobile ultrasound diagnostic instrument including a self-powered ultrasound console having electronics for driving a transducer array and processing reflected ultrasound waves, and a visual display for processed ultrasound waves. A docking stand is provided for the console and includes a sleeve for slidably receiving the console of the instrument, the sleeve being configured to expose the visual display and manual controls of the console. A vertical support positions the sleeve in a raised position above the base, which preferably includes wheels for moving the docking stand and diagnostic instrument during use. The sleeve preferably includes a signal connector for mating with a connector of the console and receiving video signals for auxiliary display. A power connector can be provided for mating with a power connector of the console for operating the console and for charging batteries in the console. The sleeve is attached to the vertical support by universal motion joint whereby the sleeve can be rotated and tilted during use, and the vertical support is extendible to vary height of the sleeve. Preferably the vertical support includes a coupler for joining the first portion of the vertical support attached to the sleeve and a second portion of the vertical support attached to the base, the first portion being removable from the second portion and attachable to a second vertical support such as an immobile stand for desk use.

14 Claims, 6 Drawing Sheets



*FIG. 1*




FIG. 2




FIG. 2A






FIG. 3

*FIG. 4*

*FIG. 5*




FIG. 6

MOBILE ULTRASOUND DIAGNOSTIC INSTRUMENT AND DOCKING STAND

This application claims the benefit of provisional application 60/132,515 filed May 4, 1999.

BACKGROUND OF THE INVENTION

This invention relates generally to medical ultrasonic diagnostic systems, and more particularly the invention relates to a mobile ultrasound diagnostic instrument and docking stand.

Modern ultrasonic diagnostic systems are large, complex instruments. Today's premium ultrasound systems, while mounted in carts for portability, continue to weigh several hundred pounds. In the past, ultrasound systems such as the ADR 4000 ultrasound system produced by Advanced Technology Laboratories, Inc. were smaller desk top units about the size of a personal computer. However, such instruments lack many of the advanced features of today's premium ultrasound systems such as color Doppler imaging and three dimensional display capabilities. As ultrasound systems become more sophisticated they also become bulkier.

Disclosed in U.S. Pat. No. 5,722,412 is a diagnostic ultrasound instrument which exhibits many of the features of a premium ultrasound system in a hand-held unit. The instrument can be produced as a single unit or in a preferred embodiment the instrument is a two-part unit one including a transducer, beamformer, and image processor and the other including a display and power source for both units. In such a configuration the transducer/processor unit can be manipulated with one hand with a cable between the two units enables the video to be shown on the display unit while the lateral unit is held or positioned for optimal viewing of the ultrasound image. The cable also provides energy for the transducer/processor unit from the display unit.

The present invention is directed to a mobile ultrasound diagnostic instrument such as disclosed in the '412 patent and a docking stand which facilitates independent use of the instrument for diagnostic purposes or use of the instrument with larger, more complex systems.

SUMMARY OF THE INVENTION

In accordance with a preferred embodiment of the invention, a mobile ultrasound diagnostic instrument includes a docking stand for a self-powered ultrasound console. The console includes electronics for driving a transducer array and processing reflected ultrasound waves, and a visual display for processed ultrasound waves. The docking stand includes a sleeve for slidably receiving the console of the instrument, the sleeve being configured to expose the visual display and manual controls of the console. A vertical support positions the sleeve in a raised position above a base for the vertical support. In alternative embodiments, controls can be provided in the stand, and the console can comprise a personal computer, for example.

In accordance with features of the invention, the sleeve can include a signal connector for mating with a connector of the console and receiving video signals for auxiliary display. The sleeve can further include a power connector for mating with a power connector of the console for operating the console and for charging batteries in the console. The connector can provide input/output signals.

In accordance with the preferred embodiment, the sleeve is attached to the vertical support by a universal motion joint whereby the sleeve can be rotated and tilted during use or

limited incline or rotation only can be provided. The vertical support is extendible to vary the height of the sleeve, and the vertical support can include a coupler for joining a first portion of the vertical support attached to the sleeve and a second portion of the vertical support attached to the base, the first portion being removable from the second portion and attachable to a second vertical support for desk use, for example. The base for the vertical support preferably includes wheels for moving the docking stand, the second vertical support for desk use preferably including an immobile base.

In accordance with other features of the docking stand, an arm can be attached to the vertical support and configured to receive a plurality of ultrasound transducers and cables for use in connecting the scanners and the console. A shelf can be attached to the vertical support for supporting a recorder, for example, and the sleeve can include a recess for receiving gel for use in coupling the transducer array and a human patient.

The invention and objects and features thereof will be more readily apparent from the following detailed description and appended claims when taken with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of an ultrasound diagnostic instrument and docking stand in accordance with one embodiment of the invention.

FIG. 2 is an exploded perspective view of a console of the diagnostic instrument and a receptive sleeve of the docking stand, and FIG. 2A is a side view in section illustrating the console in the sleeve.

FIG. 3 is a perspective view illustrating universal motion connection of the sleeve and a vertical support of the docking stand.

FIG. 4 is an exploded perspective view illustrating a first portion of the vertical support mating with a second portion of a second vertical support for desk use, for example.

FIG. 5 is a perspective view illustrating a support arm for scanheads and a platform for a recorder in accordance with embodiments of the invention.

FIG. 6 is a perspective view of another embodiment of the invention.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

FIG. 1 is a perspective view of a mobile ultrasound diagnostic instrument and docking stand in accordance with an embodiment of the invention. The diagnostic instrument includes a console 10 and a transducer scanhead 12 which is connected to console 10 through cable 14. The instrument can be of the type disclosed in U.S. Pat. No. 5,722,412.

Console 10 is received within a sleeve receptacle 16 which is supported in a raised position by means of a vertical support 18 that mounts to a base 20 having a plurality of wheels 22 for movement. FIG. 2 is an exploded perspective view of console 10 and sleeve 16 which is configured to expose a visual display 24 and manual controls shown generally at 26 and a track ball controller 28 on the console. Cable 14 which connects the scanhead 12 to console 10 includes an adapter 30 which plugs into console 10. Connector 30 allows any one of a plurality of scanheads designed for specific applications to be interfaced with the console, as desired.

When console 10 is inserted in sleeve 16 as illustrated in the side view of FIG. 2A, a power connector 32 on the base of the console 10 mates with a power connector 34 in the

3

base of the sleeve which connects console **10** to a power supply through power cable **36** for operating the console and for charging batteries in the console. Similarly, a connector **38** in the base of console **10** mates with a connector **40** in the base of sleeve **16** whereby processed signals such as video signals can be connected through cable **42** to an auxiliary display for viewing. The connector can provide input/output signals including serial data and Ethernet/USB, for example. Sleeve **16** includes a receptacle **44** for auxiliary supplies such as a gel for application to a patient prior to ultrasound scanning.

Referring to FIG. 3, in a preferred embodiment vertical support **18** includes a first portion **48** which mates with a second portion **50** through a coupler shown generally at **52**. A coupler **54** attaches sleeve **16** to the first portion **48** whereby sleeve **16** can be tilted at various angles by means of handle **55**. Coupler **52** permits rotation of sleeve **16** and the upper portion **48** of the vertical support in a horizontal plane whereby coupler **52** and coupler **54** permit a universal motion joint in positioning the console **10** during use. Upper vertical support **48** includes a depending portion **56** of reduced diameter which is received within the lower vertical support **50** whereby the upper portion **48** is adjustable in height by means of a thumb screw **58**. Thus sleeve **16** and console **10** can be varied in height by adjusting depending member **56** with thumb screw **58**.

Referring to FIG. 4, console **10**, sleeve **16**, and upper portion **48** of the vertical support can be removed from the moveable docking stand of FIG. 1 and placed on a second immobile base **62**. Base **62** supports a lower vertical support **60** with a coupler **52'** and thumb screw **58'** receiving projection **56** from the upper vertical support **48**. This embodiment of the invention is suitable for use on a desk **64**, for example.

In practice, it is often desirable to have specific scanheads which are designed and programmed for specific applications such as gynecology, urology, and prostrate examinations for example. As shown in FIG. 5, an arm **60** is attached to the vertical support **18** for receiving a plurality of scanheads **12'**, cables **14'**, and connectors **30'**. Further, each scanhead and connector can include special purpose software associated therewith for specific applications so that module **10** need not be programmed for all specific applications. A platform **62** can be attached to vertical support **18** for supporting a recorder **64** or communication unit, for example, to which the video signals from console **10** are connected through cable **42**. Additionally, a flat panel display **66** can be supported by attachment **68** to vertical support **18** so that an operator can have a larger picture of the ultrasound image.

FIG. 6 is an assembly drawing of another embodiment of the mobile stand illustrating its major features. Portable scanning unit **101** is supported by receiver assembly **102**, which includes a positive locking mechanism to secure the device during use. A security lock may be added to prevent theft of the scanning unit. Note that the controls of the scanning unit are exposed, as is the transducer connector on the rear of the unit, thus allowing full functionality of the scanner while supported by the receiver assembly.

Transducer holder features **103** are provided on both sides of receiver assembly **102** to allow convenient storage of transducers on the stand. An additional support feature **106** is provided on one side to support long transducers such as an intervaginal transducer. The transducer holder features **103** incorporate a grip made of a soft material (e.g. rubber) to secure the transducer.

4

The receiver assembly **102** is mounted on a tilt and swivel head **10** that allows rotation and inclination of the assembly and the scanner unit. The receiver assembly **102** incorporates a handle **104** which allows convenient repositioning of the assembly and movement of the entire stand. The handle **104** is also designed so that a standard 8-oz. bottle of acoustic coupling gel which is used in ultrasound examinations can lay on its side in the handle opening.

The entire receiver assembly **102** and tilt/swivel mechanism **107** is mounted on support tube **108**, which may be raised or lowered by applying pressure to pedal **118** which allows tube **108** to move up and down in a controlled manner. A gas piston assembly mounted in base wing **109** enables smooth, controlled motion. Base wing **109** also incorporates depression **111** suitable for storing a standard 8-oz. bottle of acoustic coupling gel, and depressions **110** suitable for holding the connector associated with an ultrasound transducer. Base wing **109** also incorporates mounting tracks to support accessory shelf **114**. In this drawing, accessory shelf **114** is shown supporting a video printer **112** and top cover **113**. Shelves may be used to support a variety of equipment including video recorders, image archive devices, and miscellaneous accessories.

The entire assembly is mounted on mobile base **115** which incorporates at least three wheels **116**. At least two of these wheels may be locked to prevent motion of the stand, in this case via locking levers **117**.

There has been described a mobile ultrasound diagnostic instrument and docking stand which is flexible in facilitating use of the instrument in a clinical environment either as a mobile unit for movement on the floor or as an immobile unit for positioning on a desk. While the invention has been described with reference to specific embodiments, the description is illustrative of the invention and is not to be construed as limiting the invention. For example, the vertical support for the docking stand can be provided with vertical flexibility and use by extending the vertical upper portion either inside the lower portion as described or by supporting the upper portion with clamps attached to the outside of the lower portion. Thus various modifications and applications may occur to those skilled in the art without departing from the true spirit and scope of the invention as defined by the appended claims.

What is claimed is:

1. A mobile ultrasound diagnostic instrument comprising:

a) an ultrasound console including electronics for driving a transducer array and processing reflected ultrasound waves, a signal connector for input and output of signals or reception of video signals for an auxiliary display, and a visual display for processed ultrasound waves, and

b) a docking stand including

- 1) a sleeve for slidably receiving the console of the instrument, the sleeve configured to expose the visual display and manual control on the console, and having a signal connector for mating with said connector of the console,
- 2) a vertical support for positioning the sleeve in a raised position, and
- 3) a base for the vertical support.

2. The mobile ultrasound diagnostic instrument as defined by claim 1 wherein the console comprises a personal computer.

3. The mobile ultrasound diagnostic instrument as defined by claim 1 wherein said sleeve includes a power connector for mating with a power connector of the console for operating the console and for charging batteries in the console.

5

4. The mobile ultrasound diagnostic instrument as defined by claim 1 wherein said sleeve includes a power connector for mating with a power connector of the console for operating the console and for charging batteries in the console.

5. The mobile ultrasound diagnostic instrument as defined by claim 1 wherein said sleeve is attached to the vertical support by a motion joint whereby the sleeve can be rotated and/or tilted during use.

6. The mobile ultrasound diagnostic instrument as defined by claim 5 wherein the vertical supported is extendible to vary the height of the sleeve.

7. The mobile ultrasound diagnostic instrument as defined by claim 5 wherein the vertical support includes a coupler for joining a first portion of the vertical support attached to the sleeve and a second portion of the vertical support attached to the base, the first portion being removable from the second portion and attachable to a second vertical support.

8. The mobile ultrasound diagnostic instrument as defined by claim 7 wherein the base for the vertical support includes wheels for moving the docking stand.

6

9. The mobile ultrasound diagnostic instrument as defined by claim 8 wherein the second vertical support includes an immobile base.

10. The mobile ultrasound diagnostic instrument as defined by claim 5 and further including an arm attached to the vertical support and configured to receive a plurality of ultrasound transducer scanners and cables for use in inter-connecting scanners and console.

11. The mobile ultrasound diagnostic instrument as defined by claim 10 and further including a shelf attached to the vertical support for supporting a device such as a recorder or communication unit.

12. The mobile diagnostic instrument as defined by claim 1 and further including a transducer scanhead and a cable connecting the scanhead to the console.

13. The mobile diagnostic instrument as defined by claim 1 and further including a display mounted to the stand.

14. The mobile diagnostic instrument as defined by claim 1 wherein the stand further includes controls for the transducer array.

* * * * *

专利名称(译)	移动式超声诊断仪和对接支架		
公开(公告)号	US6447451	公开(公告)日	2002-09-10
申请号	US09/564600	申请日	2000-05-03
[标]申请(专利权)人(译)	索诺塞特公司		
申请(专利权)人(译)	SONOSITE INC.		
当前申请(专利权)人(译)	SONOSITE INC.		
[标]发明人	WING GREGORY BUNCE STEVEN DUNN ANDREW T EPPS BRIAN STEVENS PAUL		
发明人	WING, GREGORY BUNCE, STEVEN DUNN, ANDREW T. EPPS, BRIAN STEVENS, PAUL		
IPC分类号	F16M11/00 F16M11/12 F16M11/42 F16M11/02 G01S15/89 G01S15/00 G01S7/52 G06F1/16 A61B8/00		
CPC分类号	F16M11/041 F16M11/10 F16M11/12 F16M11/2014 F16M11/42 G01S7/52017 G01S7/5208 G01S15/899 G06F1/1632 A61B8/4405 A61B8/4411 A61B8/4427 A61B8/4433		
助理审查员(译)	JAIN , RUBY		
外部链接	Espacenet USPTO		

摘要(译)

一种移动超声诊断仪器，包括自供电超声控制台，其具有用于驱动换能器阵列和处理反射的超声波的电子器件，以及用于处理的超声波的视觉显示器。为控制台提供对接支架，并且包括用于可滑动地接收仪器的控制台的套管，该套管被配置为暴露控制台的视觉显示和手动控制。垂直支撑件将套筒定位在基座上方的升高位置，该升高位置优选地包括用于在使用期间移动对接支架和诊断仪器的轮子。套筒优选地包括信号连接器，用于与控制台的连接器配合并接收用于辅助显示器的视频信号。可以提供电源连接器，用于与控制台的电源连接器配合，用于操作控制台和为控制台中的电池充电。套筒通过万向运动接头连接到垂直支撑件，由此套筒可在使用期间旋转和倾斜，并且垂直支撑件可延伸以改变套筒的高度。优选地，垂直支撑件包括用于连接附接到套管的垂直支撑件的第一部分的连接器和连接到基座的垂直支撑件的第二部分，第一部分可从第二部分移除并且可连接到第二垂直支撑件。作为桌面使用的固定支架。

