



US009271698B2

(12) **United States Patent**
Wei(10) **Patent No.:** **US 9,271,698 B2**
(45) **Date of Patent:** **Mar. 1, 2016**(54) **CART FOR ULTRASONIC IMAGING
APPARATUS AND ULTRASONIC IMAGING
SYSTEM**(75) Inventor: **Bo Wei**, Wuxi (CN)(73) Assignee: **GE Medical Systems Global
Technology Company, LLC**, Waukesha,
WI (US)(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 1457 days.(21) Appl. No.: **12/957,145**(22) Filed: **Nov. 30, 2010**(65) **Prior Publication Data**

US 2011/0128815 A1 Jun. 2, 2011

(30) **Foreign Application Priority Data**

Nov. 30, 2009 (CN) 2009 1 0225857

(51) **Int. Cl.****H05K 7/14** (2006.01)**A61B 8/00** (2006.01)**B62B 5/00** (2006.01)(52) **U.S. Cl.**CPC **A61B 8/4405** (2013.01); **B62B 5/00**
(2013.01); **Y10T 29/49826** (2015.01); **Y10T**
29/49959 (2015.01)(58) **Field of Classification Search**USPC 600/437, 459, 104, 106, 102, 229;
710/303, 304; 307/149

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,577,932 A 11/1996 Palmer
6,629,927 B1 10/2003 Mesaros et al.6,648,825 B1 11/2003 Mesaros et al.
7,591,786 B2 * 9/2009 Holmberg A61B 8/00
600/437
2003/0217600 A1 11/2003 Collins et al.
2005/0247480 A1 11/2005 Schulz
2006/0046561 A1 3/2006 Lam et al.
2008/0161688 A1 7/2008 Poland
2008/0221454 A1 9/2008 Davidsen
2008/0225534 A1 9/2008 Rus et al.
2009/0005686 A1 1/2009 Yanagihara et al.
2009/0270727 A1 10/2009 Zhao et al.
2010/0056913 A1 3/2010 Hirakui et al.

FOREIGN PATENT DOCUMENTS


CN 1471898 A 2/2004
CN 1473548 A 2/2004

(Continued)

OTHER PUBLICATIONS

Unofficial translation of SIPO Official Action and Search Report for
CN Application No. 200910225857.2, dated Feb. 8, 2014.*Primary Examiner* — Rexford Barnie*Assistant Examiner* — Xuan Ly(74) *Attorney, Agent, or Firm* — Armstrong Teasdale LLP(57) **ABSTRACT**

A cart for use with an ultrasonic imaging apparatus, comprising: a supporting part, a cart body and a bottom part; said cart body is connected to the supporting part and the bottom part; said supporting part is provided with an interface thereon for supporting and connecting the ultrasonic imaging apparatus; said cart body is an elevator structure provided with a power cable therein for supplying power to the ultrasonic imaging apparatus; the lower portion of the supporting part and the upper portion of the bottom part are both provided with a power socket; said power cable is a coiled cord structure, and its two ends are connected to the two power sockets; a stretchable elastic component having elastic recovery is provided inside the coiled cord structure of the power cable.

17 Claims, 4 Drawing Sheets

(56)

References Cited

FOREIGN PATENT DOCUMENTS

CN	1655720 A	8/2005
CN	1758878 A	4/2006
CN	2906843 Y *	5/2007

CN	101163986 A	4/2008
CN	101238390 A	8/2008
CN	101411626 A	4/2009
CN	101541246 A	9/2009
CN	101569537 A	11/2009
EP	1271033 A2	1/2003

* cited by examiner




FIG. 1
PRIOR ART




FIG. 2




FIG. 3




FIG. 4




FIG. 5

1

CART FOR ULTRASONIC IMAGING APPARATUS AND ULTRASONIC IMAGING SYSTEM

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of Chinese Patent Application No. 200910225857.2 filed Nov. 30, 2009, which is hereby incorporated by reference in its entirety.

BACKGROUND OF THE INVENTION

The present invention relates to the field of ultrasonic imaging apparatus, in particular to a cart in an ultrasonic imaging apparatus.

A cart-type ultrasonic system comprises a cart for supporting an ultrasonic imaging apparatus, the height of the cart is up-down adjustable. The cart is provided with a power cable therein in order to supply power to the ultrasonic imaging apparatus, as shown in FIG. 1, the power cable 10 connects an inlet and outlet of a DC current, the power cable 10 is a coiled cord which is retractile when the cart moves up and down. However, since the main material of the cable is resin, the ductility of the resin makes the power cable 10 could not return its original length but become longer after a period of use. When the cart lowers, the elongated power cable 10 may be in tangle, which can cause serious damage to the power cable 10 and cause safety problems.

BRIEF DESCRIPTION OF THE INVENTION

Embodiments described herein provide a cart used for an ultrasonic imaging apparatus to solve the above mentioned problem. The cart replaces the creep deformation of the power cable with an elastic deformation to realize better power cable management and to improve the reliability and safety of the power cable.

Moreover, embodiments described herein provide an ultrasonic imaging system that can resolve the above issue, which replaces the creep deformation of the power cable with an elastic deformation to realize better power cable management and to improve the reliability and safety of the power cable.

The cart used for an ultrasonic imaging apparatus provided in the present invention comprises: a supporting part, a cart body and a bottom part, said cart body is connected to the supporting part and the bottom part; said supporting part is provided with an interface thereon for supporting and connecting the ultrasonic imaging apparatus; said cart body is an elevator structure provided with a power cable therein for supplying power to the ultrasonic imaging apparatus; the lower portion of the supporting part and the upper portion of the bottom part are both provided with a power socket; said power cable is a coiled cord structure, and its two ends are connected to the two power sockets; a stretchable elastic component having elastic recovery is provided inside the coiled cord structure of the power cable.

In some embodiments, the stretchable elastic component is a spring.

In some embodiments, both ends of the spring are fastened at the two ends of the power cable respectively.

In some embodiments, both ends of the spring have a suspension ring, both ends of the power cable is fixed with a cable clip with a hole; a bolt or screw passes through the suspension ring of the spring and the hole on the cable clip fixed on the power cable to fasten the spring to the power cable.

2

In some embodiments, when the spring is in a natural state, its length is equal to a length of the coiled cord structure of the power cable in its natural state.

In some embodiments, the cart body comprises a fixed end in the lower section of the cart body and a moving end which is movable up and down in the upper section of the cart body; said fixed end is connected and fixed to the bottom part, said moving end is connected to the supporting part; one end of the power cable fastened with a spring is fixed to the fixed end of the cart body, and the other end thereof is fixed to the moving end of the cart body.

In some embodiments, the bottom part comprises a plurality of supporting legs having wheels.

The ultrasonic imaging system provided by the present invention comprises an ultrasonic imaging apparatus and a cart for supporting the ultrasonic imaging apparatus; said cart comprises: a supporting part, a cart body and a bottom part, said cart body is connected to the supporting part and the bottom part; said supporting part is provided with an interface thereon for supporting and connecting the ultrasonic imaging apparatus; said cart body is an elevator structure provided with a power cable therein for supplying power to the ultrasonic imaging apparatus; the lower portion of the supporting part and the upper portion of the bottom part are both provided with a power socket; said power cable is a coiled cord structure, and its two ends are connected to the two power sockets; a stretchable elastic component having elastic recovery is provided inside the coiled cord structure of the power cable.

In some embodiments, the stretchable elastic component is a spring, the both ends thereof are fastened at the two ends of the power cable respectively.

In some embodiments, both ends of the spring have a suspension ring, both ends of the power cable is fixed with a cable clip with a hole; a bolt or screw passes through the suspension ring and the hole on the cable clip fixed on the power cable to fasten the spring to the power cable.

In some embodiments, when the spring is in a natural state, its length is equal to a length of the coiled cord structure of the power cable in its natural state.

In some embodiments, the cart body comprises a fixed end in the lower section of the cart body and a moving end which is movable up and down in the upper section of the cart body; said fixed end is fixed to the bottom part, said moving end is connected to the supporting part; one end of the power cable fastened with a spring is fixed to the fixed end of the cart body, and the other end thereof is fixed to the moving end of the cart body.

In some embodiments, the bottom part comprises a plurality of supporting legs having wheels.

In this invention, a stretchable elastic component having elastic recovery is provided inside the coiled cord structure of the power cable, which can reduce or eliminate creep deformation of the coiled cord structure of the power cable to ensure the power cable can be restored and returns to its original normal length after a long period of use. In addition, the spring in the present invention also works as a guider for the movement of the power cable by making the power cable move straightly, whereby the power cable's scratching and crashing with other components can be prevented when moving randomly. The present invention enhances the safety of the cart and prolongs the service life of the power cable. The present invention also has the advantages of having a simple structure and low cost.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a structural schematic diagram of a cart in the prior art.

3

FIG. 2 is a structural schematic diagram of a cart of the present invention.

FIG. 3 is a structural schematic diagram of the power cable and spring mated together in the present invention.

FIG. 4 shows exploded structural schematic diagram of the power cable and spring mated together.

FIG. 5 is a structural schematic diagram of the cart in another state in the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, embodiments of the invention will be explained in details with reference to the attached drawings. The present invention is not limited to the embodiments.

As shown in FIG. 2, a cart used for an ultrasonic imaging apparatus provided by the present invention comprises: a supporting part 100, a cart body 101 and a bottom part 102, said cart body 101 is connected to the supporting part 100 and the bottom part 102; said supporting part 100 is provided with an interface thereon for supporting and connecting the ultrasonic imaging apparatus (not shown in the figure); said cart body 101 is an elevator structure provided with a power cable 1011 therein for supplying power to the ultrasonic imaging apparatus; the lower portion of the supporting part 100 and the upper portion of the bottom part 102 are both provided with a power socket (not shown in the figure); said power cable 1011 is a coiled cord structure, and its two ends are connected to the two power sockets.

Now referring to FIG. 3 in the meanwhile, a spring 1012 is designed and assembled inside the power cable 1011, when the spring 1012 is in a natural state, its length is equivalent to a length of the coiled cord structural part of the power cable 1011 in its natural state. Of course, they may be not equal as well. The two ends of the spring 1012 are fastened to the two ends of the power cable 1011. As shown in the embodiment of FIG. 4, fastening of the spring 1012 and the power cable 1011 is implemented through the following structure: the two ends of the spring 1012 are provided with a suspension ring 1013, a pair of cable clips 1014 with a hole thereon are fastened to the two ends of the power cable 1011, the spring 1012 and the power cable 1011 are fastened together by passing a screw or a bolt through the suspension ring 1013 of the spring 1012 and the hole on the cable clips 1014 fastened onto the power cable 1011. In order to optimize the effect of the spring 1012 on the power cable 1011, one end of the power cable 1011 having the spring 1012 is fixed to the fixed end of the cart body 101, and the other end is fixed to the moving end of the cart body 101. When the moving end of the cart body 101 moves up and down, the spring 1012, together with the power cable 1011, compresses or expands up and down. As shown in FIG. 2, when the cart body 101 is lifted, the power cable 1011 and the spring 1012 therein is in a stretching state; FIG. 5 shows that when the cart body 101 is lowered, the power cable 1011 and the spring 1012 therein is in a compression state. Since the spring 1012 has the characteristic of elastic deformation, the defect of creep deformation of the power cable 1011 is alleviated, and the power cable 1011 can still be restored and returns to its original normal length after a long period of use.

The spring 1012 in the present invention also has a function of guiding the power cable 1011 in movement and making the power cable 1011 move straightly so that the power cable's scratching and crashing with other components can be prevented during random movement.

Said spring 1012 is a tension spring. Of course, other stretchable components having elastic recovery can also be used to replace the spring 1012.

4

Said bottom part 102 comprises a plurality of supporting legs 1021, 1022, 1023, 1024 with wheels. In the embodiment, there are four supporting legs to enable the cart to move conveniently.

What is claimed is:

1. A cart for use with an ultrasonic imaging apparatus, said cart comprising:

a supporting part comprising:

an interface configured to support and couple to the ultrasonic imaging apparatus; and

a lower portion comprising a first power socket;

a bottom part comprising an upper portion comprising a second power socket; and

a cart body coupled to said supporting part and said bottom part, said cart body comprising an elevator structure comprising an internal power cable configured to supply power to the ultrasonic imaging apparatus, said power cable comprising:

a coiled cord structure comprising a first end coupled to said first power socket and a second end coupled to said second power socket; and

a spring having elastic recovery, wherein a first point of said coiled cord structure is anchored to a first point of said spring using a first fastening mechanism and a second point of said coiled cord structure is anchored to a second point of said spring using a second fastening mechanism such that said first point and said second point of said coiled cord structure cannot extend beyond said respective first and second points of said spring, and wherein said first and second fastening mechanisms further anchor said coiled cord structure and said spring to said cart body.

2. A cart according to claim 1, wherein said first and second points of said spring each comprises a respective first and second suspension ring, said first and second points of said coiled cord structure are coupled to said cart body with respective first and second cable clips each having a hole extending therethrough, each of said first and second suspension rings and cable clip holes sized to receive said first and second fastening mechanisms therein to fasten said spring to said coiled cord structure.

3. A cart according to claim 2, wherein, when said spring is in a first state, a length thereof is equal to a length of said coiled cord structural part in a respective first state.

4. A cart according to claim 2, wherein said cart body further comprises a lower section and an upper section configured to move vertically, said lower section is coupled to said bottom part, said upper section is coupled to said supporting said second end of said power cable coupled to said lower section, said first end of said power cable coupled to said upper section.

5. A cart used for an ultrasonic imaging apparatus according to claim 1, wherein said bottom part further comprises a plurality of supporting legs with wheels.

6. An ultrasonic imaging system, comprising:

an ultrasonic imaging apparatus; and

a cart configured to support said ultrasonic imaging apparatus, said cart comprising:

a supporting part comprising an interface configured to support and couple to the ultrasonic imaging apparatus and a lower portion comprising a first power socket;

a bottom part comprising an upper portion comprising a second power socket; and

a cart body coupled to said supporting part and said bottom part, said cart body comprising an elevator structure comprising an internal power cable config-

5

ured to supply power to the ultrasonic imaging apparatus, said power cable comprising a coiled cord structure comprising a first end coupled to said first power socket and a second end coupled to said second power socket, and a spring having elastic recovery, wherein a first point of said coiled cord structure is anchored to a first point of said spring using a first fastening mechanism and a second point of said coiled cord structure is anchored to a second point of said spring using a second fastening mechanism such that said first point and said second point of said coiled cord structure cannot extend beyond said respective first and second points of said spring, and wherein said first and second fastening mechanisms further anchor said coiled cord structure and said spring to said cart body.

7. An ultrasonic imaging system according to claim 6, wherein said first and second points of said spring each comprises a respective first and second suspension ring, said first and second points of coiled cord structure are coupled to said cart body with respective first and second cable clips each having a hole extending therethrough, each of said first and second suspension rings and cable clip holes sized to receive said first and second fastening mechanisms therein to fasten said spring to said coiled cord structure.

8. An ultrasonic imaging system according to claim 7, wherein, when said spring is in a first state, a length thereof is equal to a length of said coiled cord structural part in a respective first state.

9. An ultrasonic imaging system according to claim 8, wherein said cart body further comprises a lower section and an upper section configured to move vertically, said lower section is coupled to said bottom part, said upper section is coupled to said supporting said second end of said power cable coupled to said lower section, said first end of said power cable coupled to said upper section.

10. An ultrasonic imaging system according to claim 6, wherein said bottom part further comprises a plurality of supporting legs with wheels.

11. A method of assembling an ultrasonic imaging system having an ultrasonic imaging apparatus and a cart, the cart including a supporting part, a bottom part, and a cart body, said method comprising:

coupling the supporting part to the ultrasonic imaging apparatus, the supporting part including a lower portion having a first power socket;
providing a second power socket within the bottom part; and
coupling the cart body to the supporting part and the bottom part, the cart body having an elevator structure including an internal power cable configured to supply power to the ultrasonic imaging apparatus, the power

6

cable including a coiled cord structure with a first end coupled to the first power socket and a second end coupled to the second power socket, the power cable further including a spring having elastic recovery, wherein a first point of the coiled cord structure is anchored to a first point of the spring using a first fastening mechanism and a second point of the coiled cord structure is anchored to a second point of the spring using a second fastening mechanism such that the first point and the second point of the coiled cord structure cannot extend beyond the respective first point and second points of the spring, and wherein the first and second fastening mechanisms further anchor the coiled cord structure and the spring to the cart body.

12. A method according to claim 11, said method further comprising coupling the spring to the power cable.

13. A method according to claim 12, wherein coupling the spring to the power cable further comprises:

coupling a first suspension ring at the first point of the spring to the first point of the coiled cord structure; and
coupling a second suspension ring at the second point of the spring to the second point of the coiled cord structure coupling the first point of the coiled cord structure to the cart body with a first cable clip; and coupling the second point of the coiled cord structure to the cart body with a second cable clip.

14. A method according to claim 13, wherein coupling the spring to the power cable further comprises:

inserting the first fastening mechanism through a first hole within the first cable clip and through the first suspension ring; and

inserting the second fastening mechanism through a second hole within the second cable clip and through the second suspension ring.

15. A method according to claim 11, wherein coupling the cart body to the supporting part and the bottom part comprises:

coupling a lower section of the cart body to the bottom part and to the second end of the power cable; and

coupling an upper section to the supporting part and to the first end of the power cable, the upper section configured to move vertically.

16. A method according to claim 11, further comprising coupling a plurality of supporting legs with wheels to the bottom part.

17. A cart according to claim 1, wherein said spring is stretchable between a first position and a second position, wherein in the first position said spring has a first length, and wherein in the second position, said spring has a second length that is at least twice the first length.

* * * * *

专利名称(译)	用于超声成像设备和超声成像系统的推车		
公开(公告)号	US9271698	公开(公告)日	2016-03-01
申请号	US12/957145	申请日	2010-11-30
申请(专利权)人(译)	魏博		
当前申请(专利权)人(译)	通用电气医疗系统全球性技术公司，有限责任公司		
[标]发明人	WEI BO		
发明人	WEI, BO		
IPC分类号	H05K7/14 A61B8/00 B62B5/00		
CPC分类号	A61B8/4405 B62B5/00 Y10T29/49826 Y10T29/49959		
优先权	200910225857.2 2009-11-30 CN		
其他公开文献	US20110128815A1		
外部链接	Espacenet USPTO		

摘要(译)

一种与超声波成像装置一起使用的推车，包括：支撑部分，推车主体和底部部分；所述车体连接到支撑部分和底部；所述支撑部分上设有接口，用于支撑和连接超声波成像装置；所述车体是电梯结构，其中设有电源线，用于向超声成像设备供电；支撑部分的下部和底部的上部均设有电源插座；所述电力电缆为螺旋线结构，其两端连接两个电源插座；在电力电缆的盘绕的绳索结构内部提供具有弹性恢复的可拉伸弹性部件。

