



(43) **Pub. Date:** **Nov. 12, 2009**

(22) Filed: **May 8, 2009**




FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7




FIG.8




FIG.9




FIG.10




FIG.11




FIG.12




FIG.13




FIG.14




FIG.15






FIG.16**FIG.17**

HOOD FOR ULTRASOUND PROBE DEVICE AND ULTRASOUND PROBE DEVICE

CROSS REFERENCE TO RELATED APPLICATION

[0001] This application claims the benefit of Japanese Application No. 2008-122533 filed in Japan on May 8, 2008, the contents of which are incorporated herein by this reference.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates to an ultrasound probe device including an insertion section having an ultrasound probe, and a hood for the ultrasound probe device fitted for the ultrasound probe device.

[0004] 2. Description of the Related Art

[0005] As a device for obtaining an ultrasound tomographic image of an inside of a living body, an ultrasound probe device formed by including an ultrasound probe transmitting and receiving ultrasound at an insertion section to be inserted into a body is used.

[0006] As one example of such an ultrasound probe device, there is known an ultrasound endoscope which is formed by being provided with an ultrasound probe at a distal end portion of an insertion section, and obtains an ultrasound tomographic image of a target region by causing the ultrasound probe to abut on the target region in the body as disclosed in, for example, Japanese Patent Publication No. 3504396.

SUMMARY OF THE INVENTION

[0007] A hood for an ultrasound probe device of the present invention is capable of being fitted to an insertion section of an ultrasound probe device having an ultrasound probe, and has a cylindrical shape, wherein a reflectivity of ultrasound in at least a region to which the ultrasound transmitted from the ultrasound probe is irradiated in a state fitted to the insertion section is 25% or less.

[0008] Further, a hood for an ultrasound probe device of the present invention has a cylindrical shape having opening portions at both ends, and is capable of being fitted to an insertion section of an ultrasound probe device having an ultrasound probe in the opening portion at a proximal end side of the cylindrical shape, wherein in a state fitted to the insertion section, at least a region to which ultrasound transmitted from the ultrasound probe is irradiated of an inner surface inclines to be closer to the ultrasound probe toward the opening portion at the proximal end side.

[0009] Further, a hood for an ultrasound probe device of the present invention has a cylindrical shape having opening portions at both ends, and is capable of being fitted to an insertion section of an ultrasound probe device having an ultrasound probe in the opening portion at a proximal end side of the cylindrical shape, wherein the opening portion at the distal end side of the cylindrical shape is formed to include a region to which ultrasound transmitted from the ultrasound probe is irradiated, in a state fitted to the insertion section.

[0010] Further, an ultrasound probe device of the present invention includes an insertion section having an ultrasound probe, and a hood section which has a cylindrical shape having an opening portion at a distal end side, and is disposed

at the insertion section to surround the ultrasound probe, wherein a space surrounded by the hood section is capable of being decompressed.

[0011] The above and other objects, features and advantages of the invention will become more clearly understood from the following description referring to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] FIG. 1 is a view explaining an entire configuration of an ultrasound probe device;

[0013] FIG. 2 is a view explaining a configuration of a distal end portion of an insertion section of the ultrasound probe device;

[0014] FIG. 3 is a view explaining a shape of a hood section of a first embodiment;

[0015] FIG. 4 is a view showing a state in which the hood section is caused to abut on a target region;

[0016] FIG. 5 is a view showing a state in which the target region is sucked into the hood section;

[0017] FIG. 6 is a view showing a shape of a hood section of a second embodiment;

[0018] FIG. 7 is a view showing a shape of a hood section of a modified example of the second embodiment;

[0019] FIG. 8 is a view showing a shape of a hood section of a third embodiment;

[0020] FIG. 9 is a view of a state in which a target region is sucked by the hood section of the third embodiment;

[0021] FIG. 10 is a view showing a shape of a hood section of a fourth embodiment;

[0022] FIG. 11 is a view showing a state in which the hood section of the fourth embodiment is contracted;

[0023] FIG. 12 is a view showing the hood section of a modified example of the fourth embodiment;

[0024] FIG. 13 is a view showing a state in which the hood section of the modified example of the fourth embodiment is housed;

[0025] FIG. 14 is an explanatory view showing a schematic configuration of an ultrasound probe device of a fifth embodiment;

[0026] FIG. 15 is a perspective view showing a configuration of a distal end portion of an insertion section of the ultrasound probe device of the fifth embodiment;

[0027] FIG. 16 is a flowchart explaining a sixth embodiment; and

[0028] FIG. 17 is a flowchart explaining the sixth embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0029] Preferred embodiments of a hood for an ultrasound probe device and the ultrasound probe device of the present invention will be described with reference to the drawings. In each of the drawings used for the following description, the scale is made to differ for each of the components so that each of the components has such a size to be recognizable on the drawings, and the present invention is not limited only to the numbers and quantities of the components, shapes of the components, the ratios of the sizes of the components, and

relative positional relationship of the respective components, which are illustrated in these drawings.

First Embodiment

[0030] Hereinafter, a first embodiment of the present invention will be described. FIG. 1 is a view explaining an entire configuration of an ultrasound probe device. FIG. 2 is a view explaining a configuration of a distal end portion of an insertion section of the ultrasound probe device. FIG. 3 is a view explaining a shape of a hood section of the first embodiment. FIG. 4 is a view showing a state in which the hood section is caused to abut on a target region. FIG. 5 is a view showing a state in which the target region is sucked into the hood section.

[0031] An ultrasound probe device 1 of the present embodiment transmits and receives ultrasound by an ultrasound probe 22 in a state in which an insertion section 20 is inserted into a body of a subject in order to obtain an ultrasound tomographic image of a predetermined region of the subject.

[0032] The ultrasound probe device 1 includes the insertion section 20 to be inserted into a body, and a grasping section 2 which is provided to connect to the insertion section 20 and is grasped by an operator, as shown in FIG. 1. Further, the ultrasound probe 22 transmitting and receiving ultrasound is placed at a distal end portion 21 at a side opposite from a side provided with the grasping section 2 of the insertion section 20.

[0033] Hereinafter, in the ultrasound probe device 1, an axis which extends to a side of the distal end portion 21 of the insertion section 20 from a side of the grasping section 2, and is along the insertion section 20, will be called an insertion axis, and a side toward the distal end portion 21 from the grasping section 2 along the insertion axis will be called a distal end side, whereas a side opposite from the distal end side will be called a proximal end side.

[0034] In the present embodiment, the ultrasound probe 22 is of a mode which is generally called a convex type, and has a scanning range 22a of ultrasound in a substantially sector shape from a distal end direction of the insertion axis to a side in a plane including the insertion axis as shown in FIG. 3.

[0035] The mode of the ultrasound probe 22 is not limited to that of the present embodiment, but may be of the mode of a linear type with, for example, a plurality of ultrasound transducers being arranged in a line on a plane. By the linear type ultrasound probe, for example, the scanning range of ultrasound in a substantially sector shape as in the present embodiment also can be obtained by performing, so-called sector scanning. Further, it goes without saying that the shape and the direction of the scanning range of the ultrasound probe 22 are not limited to those of the present embodiment.

[0036] A cylindrical hood section 10 which has an opening portion 10a at a distal end side and surrounds the ultrasound probe 22 is placed at the distal end portion 21 of the insertion section 20 as shown in FIG. 2. The hood section 10 has a cylindrical shape in which the opening portion 10a and an opening portion 10b are formed respectively at the distal end side and a proximal end side as shown in FIG. 1, and the opening portion 10b at the proximal end side has a shape which can be fitted onto an outer peripheral surface portion of the distal end portion 21 of the insertion section 20, in the present embodiment.

[0037] Namely, in the present embodiment, the hood section 10 is made attachable to and detachable from the insertion section 20 as a separate member from the insertion sec-

tion 20 as the hood for an ultrasound probe device. As a result of the hood section 10 being configured to be attachable to and detachable from the insertion section 20 like this, washing and disinfection of the ultrasound probe device 1 can be easily carried out. The hood section 10 may be formed integrally with a member configuring the distal end portion 21 of the insertion section 20.

[0038] The hood section 10 is preferably configured such that in at least a region to which ultrasound transmitted from the ultrasound probe 22 is irradiated, that is, a region which is laid on the scanning range 22a, a reflectivity of the ultrasound becomes 25% or less.

[0039] Owing to the reflectivity of ultrasound of the hood section 10 being 25% or less, occurrence of artifact which is an image other than the ultrasound tomographic image of a subject, which occurs as a result of the ultrasound reflected by the hood section 10 being received by the ultrasound probe 22, can be suppressed.

[0040] The material configuring the hood section 10 is not especially limited, but if the hood section 10 is configured by one or a plurality of kinds of materials of, for example, polyethylene, polymethyl pentene, silicon rubber, nylon and the like, the reflectivity of ultrasound can be made 25% or less.

[0041] Further, the shape of the hood section 10 is not especially limited, but if the thickness of the hood section 10 is made an integral multiple of one quarter of the wavelength of the ultrasound transmitted by the ultrasound probe 22 so that the ultrasound reflected in an inner surface of the hood section 10, for example, and the ultrasound reflected in an outer surface of the hood section 10 have opposite phases to each other and cancel out each other, the reflectivity of the hood section 10 can be reduced, which is preferable.

[0042] Further, a treatment instrument insertion channel 24 and a suction channel 23 are formed in the distal end portion 21 of the insertion section 20, as the channels which communicate with a space surrounded by the hood section 10.

[0043] The treatment instrument insertion channel 24 communicates with a treatment instrument insertion port 4 provided in the grasping section 2 in the proximal end side of the ultrasound probe device 1. By inserting a treatment instrument such as a puncture needle into the treatment instrument insertion port 4, a treatment instrument can be led out into the space surrounded by the hood section 10 through the treatment instrument insertion channel 24. The treatment instrument insertion channel 24 is preferably disposed so that the treatment instrument which is led out into the hood section 10 through the treatment instrument insertion channel 24 can be guided into the scanning range 22a of ultrasound.

[0044] Further, the suction channel 23 communicates with a suction connector 3 provided in the grasping section 2 in the proximal end side of the ultrasound probe device 1. A suction device not illustrated is connected to the suction connector 3, and an operator can perform a suction operation for decompressing the inside of the space surrounded by the hood section 10 through the suction channel 23 by operating the suction device.

[0045] Further, at least one of the suction channel 23 and the treatment instrument insertion channel 24 is connected to an air-supply and water-supply device not illustrated, and in the present embodiment, at least one of gas and liquid can be supplied into the space surrounded by the hood section 10 through the suction channel 23 or the treatment instrument insertion channel 24 in accordance with the operation or the operator.

[0046] The treatment instrument insertion channel 24 and the suction channel 23 may be in the mode of making one channel which communicates with the space surrounded by the hood section 10 to serve a double purpose, or may be in the mode in which a plurality of channels are formed for each of the channels 24 and 23.

[0047] According to the ultrasound probe device 1 configured as above, in the state in which the opening portion 10a at the distal end side of the hood section 10 is caused to abut on a target region 90 in which a lesion portion 91, for example, is present in an organ, a digestive tract wall and the like in a subject as shown in FIG. 4, gas inside the space surrounded by the hood section 10 is exhausted through the suction channel 23 and the space is decompressed, whereby the target region 90 can be drawn into the space surrounded by the hood section 10 as shown in FIG. 5.

[0048] In this case, the ultrasound probe 22 is placed in the space surrounded by the hood section 10. Therefore, according to the present embodiment, the target region 90 can be caused to abut on the ultrasound probe 22, and observation of the target region 90 by ultrasound tomographic image can be stably performed.

[0049] Though not illustrated, in the state in which the opening portion 10a at the distal end side of the hood section 10 is caused to abut on the target region 90 as shown in FIG. 4, an ultrasound medium such as physiological saline is fed into the space surrounded by the hood section 10 through the suction channel 23, after which, the gas inside the space surrounded by the hood section 10 is exhausted and the space can be decompressed.

[0050] In this case, even when the target region 90 is a region which is difficult to deform or a region which is hardened due to lesion, and it is difficult to cause the target region 90 to abut on the ultrasound probe 22 because the target region 90 cannot be drawn into the hood section 10 only by decompression, ultrasound can be transmitted to and received from the target region 90 via the ultrasound medium filled in the hood section 10, and therefore, it is more preferable.

[0051] Other than the case in which the ultrasound probe 22 is caused to abut on the target region 90, when treatment is performed for the lesion portion 91 of the target region 90 with use of a treatment instrument such as a puncture needle, for example, a relative position of the treatment instrument with respect to the target region 90 changes by the action of the force to press the treatment instrument against the target region.

[0052] However, according to the present embodiment, as shown in FIG. 5, after it is checked by the ultrasound tomographic image that the target region 90 including the lesion portion 91 is drawn into the hood section 10, a puncture needle 30 as an example of the treatment instrument is led out into the space surrounded by the hood section 10 through the treatment instrument insertion channel 24, whereby treatment can be stably performed without changing the position of the target region 90 and the treatment instrument.

Second Embodiment

[0053] Hereinafter, a second embodiment of the present invention will be described. The second embodiment shows an example of another mode of the shape of the hood section. FIG. 6 is a view showing the shape of the hood section of the second embodiment. FIG. 7 is a view showing a shape of a hood section of a modified example of the second embodiment.

[0054] The second embodiment differs from the above described first embodiment in the shape of the hood section. Therefore, only the difference will be described hereinafter. The same components as those in the first embodiment are assigned with the same reference numerals and characters, and description thereof will be properly omitted.

[0055] As shown in FIG. 6, in a hood section 11 of the present embodiment, an inner surface 11a of at least a region to which ultrasound transmitted from the ultrasound probe 22 is irradiated inclines with respect to the insertion axis so as to be closer to the ultrasound probe 22 toward a proximal end side. Further, the hood section 11 is formed so that a thickness of at least the region to which ultrasound transmitted from the ultrasound probe 22 is irradiated becomes larger toward the proximal end side.

[0056] An angle of the inclination of the inner surface 11a of the hood section 11 is preferably such an angle that the ultrasound transmitted from the ultrasound probe 22 does not return to the ultrasound probe 22 when the ultrasound specularly reflects at the inner surface 11a.

[0057] The inner surface 11a of the hood section 11 is given the inclination to be closer to the ultrasound probe 22 toward the proximal end side like this, and thereby, occurrence of artifact which is an image other than the ultrasound tomographic image of a subject, and generates as a result of the ultrasound reflected by the inner surface 11a being received by the ultrasound probe 22 can be suppressed.

[0058] Further, the inclination of the inner surface 11a of the hood section 11 is formed by making the thickness of the corresponding spot of the hood section 11 larger in an inner direction toward the proximal end side, and therefore, an outside diameter of the hood section 11 does not become large due to the inclination of the inner surface 11a being provided.

[0059] The configuration in which the inner surface of the region to which the ultrasound transmitted from the ultrasound probe 22 is irradiated, of the hood section is inclined to be closer to the ultrasound probe 22 toward the proximal end side is not limited to the above described configuration, and may be the mode shown as a modified example in FIG. 7, for example.

[0060] In the modified example shown in FIG. 7, a hood section 12 has a so-called tapered inner shape which extensively opens toward a distal end side. In such a mode, the inner surface of the hood section 12 can be given an inclination closer to the ultrasound probe 22 toward the proximal end side, and occurrence of artifact which is an image other than the ultrasound tomographic image of a subject, which occurs as a result of the ultrasound reflected by the inner surface being received by the ultrasound probe 22 can be suppressed.

[0061] Further, according to the modified example shown in FIG. 7, the inner surface of the hood section 12 has the same tapered shape in the entire circumference around the insertion axis. Therefore, when the hood section 12 is fitted onto the distal end portion 21 of the insertion section 20, positioning in the rotational direction around the insertion axis of the hood section 12 is not required, and an operation becomes easy.

Third Embodiment

[0062] Hereinafter, a third embodiment of the present invention will be described. The third embodiment shows an example of another mode of a shape of a hood section. FIG. 8 is a view showing the shape of the hood section of the third

embodiment. FIG. 9 is a view showing the state in which a target region is sucked by the hood section of the third embodiment.

[0063] The third embodiment differs from the above described first embodiment in the shape of the hood section. Therefore, only the difference will be described hereinafter. The same components as those in the first embodiment are assigned with the same reference numerals and characters, and description thereof will be properly omitted.

[0064] As shown in FIG. 8, in a hood section 13 of the present embodiment, an opening portion 13a at a distal end side has a shape cut by a plane 13b having a predetermined angle with respect to an insertion axis. As a result, the opening portion 13a of the hood section 13 is formed to include a region to which ultrasound transmitted from the ultrasound probe 22 is irradiated. In other words, in the hood section 13 of the present embodiment, the opening portion at the distal end side is formed to be in a shape cut by the plane forming the predetermined angle with respect to the side surface in the above described cylindrical shape.

[0065] Namely, the present embodiment is configured so that the hood section 13 is not laid on the scanning range 22a of ultrasound of the ultrasound probe 22. Further, the hood section 13 includes the opening portion 13a at the distal end side, and therefore, the target region can be sucked into the space surrounded by the hood section 13 as in the above described first embodiment.

[0066] The present embodiment has such a configuration, and has nothing to block the scanning range 22a of ultrasound of the ultrasound probe 22. Therefore, a clearer ultrasound tomographic image can be obtained in addition to the same effect as that of the above described first embodiment.

[0067] Further, in the present embodiment, the opening portion 13a at the distal end side of the hood section 13 forms a predetermined angle with respect to the insertion axis, and therefore, even when the angle formed by the insertion axis of the insertion section 20 and a wall surface of the target region 90 is an obtuse angle as shown in FIG. 9, the target region 90 can be easily sucked into the space surrounded by the hood section 13. This is especially effective when the target region is an inner wall surface of a digestive tract which has a relatively small diameter, such as an esophagus or enteric canal, a trachea, a blood vessel or the like, in which the degree of freedom of the position and posture of the ultrasound probe device 1 is low.

Fourth Embodiment

[0068] Hereinafter, a fourth embodiment of the present invention will be described. The fourth embodiment shows an example of another mode of the shape of the hood section. FIG. 10 is a view showing the shape of the hood section of the fourth embodiment. FIG. 11 is a view showing the state in which the hood section of the fourth embodiment is contracted. FIG. 12 is a view showing a hood section of a modified example of the fourth embodiment. FIG. 13 is a view showing a state in which the hood section of the modified example of the fourth embodiment is housed.

[0069] The fourth embodiment differs from the above described first embodiment in the shape of the hood section. Therefore, only the difference will be described hereinafter. The same components as those in the first embodiment are assigned with the same reference numerals and characters, and description thereof will be properly omitted.

[0070] As shown in FIGS. 10 and 11, a hood section 14 of the present embodiment has a cylindrical shape having an opening portion 14a at a distal end side, and has a configuration contractible in the direction along the insertion axis.

[0071] The configuration of making the hood section 14 contractible is not especially limited, but in the present embodiment, as an example, the hood section 14 is configured by an elastically deformable resin material, and a side surface portion 14b is formed into a bellows shape, whereby the hood section 14 is elastically contracted in the insertion axis direction. The hood section may be of a mode contracting in a diameter direction instead of the insertion axis direction.

[0072] The present embodiment has such a configuration. Therefore, gas inside the space surrounded by the hood section 14 is exhausted through the suction channel 23 and the space is decompressed in the state in which an opening portion 14a at a distal end side of the hood section 14 is caused to abut on the target region 90, whereby the target region is drawn into the hood section 14, and the hood section 14 is contracted in the insertion axis direction as shown in FIG. 11.

[0073] Thereby, even when the target region 90 is a region which is difficult to deform or a region which is hardened by lesion, the target region 90 can be caused to abut on the ultrasound probe 22.

[0074] Further, a contraction amount in the insertion axis direction of the hood section 14 changes in accordance with the decompression state inside the space surrounded by the hood section 14, and therefore, the contraction amount can be properly changed. Therefore, a distance between the target region 90 and the ultrasound probe 22, or a distance between the target region 90 and the distal end portion 21 can be made to be an optimal value for observation or treatment, and operability is enhanced.

[0075] For example, after observation of the target region 90 is performed by the ultrasound probe 22, and the detailed positioning of the lesion portion 91 is identified, the distance between the target region 90 and the distal end portion 21 can be increased until the optimal space for treatment by the treatment instrument is obtained without change in the position of the lesion portion 91 and the treatment instrument insertion channel 24 with respect to the direction orthogonal to the insertion axis. Thus, the treatment instrument can be positioned to the lesion portion 91 of the target region 90 accurately and easily.

[0076] Besides the configuration which contracts the hood section in the axial direction, even when a hood section 15 is configured to be capable of advancing and retreating movement in the axial direction as in the modified example of the present embodiment shown in FIGS. 12 and 13, the same effect can be obtained.

[0077] In the modified example of the present embodiment shown in FIGS. 12 and 13, a cylinder section 15b in a cylindrical shape is placed at an outer circumference of the distal end portion 21 of the insertion section 20, and the hood section 15 is inserted with a proximal end side as a piston portion slidable in the insertion axis direction inside the cylinder section 15b.

[0078] A working fluid 15c is filled in a space closed by the proximal end side of the hood section 15 and the cylinder section 15b. If a compressible fluid is adopted as the working fluid 15c, the working fluid 15c works as a spring, and therefore, the same effect as the configuration which contracts the hood section in the axial direction is obtained.

[0079] Further, as compared with the configuration which contracts the hood section as in the above described embodiment, the modified example of the present embodiment is preferable because due to favorable rectilinearity of advancing and retreating movement of the hood section 15, positioning can be reliably performed, and operability is enhanced.

[0080] In the modified example of the present embodiment shown in FIGS. 12 and 13, such a configuration may be

adopted that a compressible or non-compressible fluid is used as the working fluid **15c**, the space housing the working fluid **15c** of the cylinder section **15b** is caused to communicate with the grasping section **2** side by piping not illustrated placed in the insertion section, and the pressure inside the cylinder section **15b** is made controllable.

[0081] According to such a configuration, the advancing amount of the hood section **15** in the insertion axis direction can be changed in accordance with the pressure inside the cylinder section **15b**, and positioning of the target region **90** and the distal end portion **21** of the insertion section **20** can be performed more precisely.

[0082] Further, when the ultrasound probe device **1** is inserted into a subject, the pressure inside the cylinder section **15b** is reduced, whereby the hood section **15** is housed and the length in the insertion axis direction of the distal end portion **20** can be shortened. Therefore, operability at the time of insertion is enhanced.

[0083] In the above described first to fourth embodiments, the hood sections differing in shape respectively are described, but it goes without saying that the hood sections are attachable to and detachable from the insertion sections of the ultrasound probe devices, and therefore, the hood sections are properly replaceable in accordance with the regions and treatment contents for which the ultrasound probe devices are used.

Fifth Embodiment

[0084] A fifth embodiment of the present invention will be described hereinafter. The fifth embodiment is another example of an ultrasound probe device to which the hood sections of the above described embodiments are applicable.

[0085] FIG. **14** is an explanatory view showing a schematic configuration of an ultrasound probe device of the fifth embodiment. FIG. **15** is a perspective view showing a configuration of a distal end portion of the insertion section of the ultrasound probe device of the fifth embodiment.

[0086] The fifth embodiment differs from the ultrasound probe devices of the above described first to fourth embodiments in the constitution having an optical observation system at the insertion section. Therefore, only the difference will be described hereinafter. The same components as those in the first embodiment are assigned with the same reference numerals and characters, and description thereof will be properly omitted.

[0087] An ultrasound probe device **101** of the present embodiment is mainly configured by an insertion section **102** which is inserted into a body of a subject, an operation section **103** located at a proximal end of the insertion section **102**, and a universal cord **104** extended from a side portion of the operation section **103**.

[0088] An endoscope connector **104a** connected to a light source device not illustrated is provided at a proximal end portion of the above described universal cord **104**. From the endoscope connector **104a**, an electric cable **105** which is attachably and detachably connected to a camera control unit not illustrated through an electric connector **105a**, and an ultrasound cable **106** which is attachably and detachably connected to an ultrasound observation device not illustrated via an ultrasound connector **106a** are extended.

[0089] The above described insertion section **102** is configured by connecting in sequence from a distal end side, a distal end portion **120**, a bending section **108** which is located at a proximal end side of the distal end portion **120** and bendable, and a flexible tube section **109** which is located at a rear end of the bending section **108** to extend to a distal end portion of the above described operation section **103**, is small in diam-

eter and elongated, and has flexibility. Further, the ultrasound probe **22** for transmitting and receiving ultrasound is provided at the distal end side of the above described distal end portion **120**.

[0090] The above described operation section **103** is provided with an angle knob **111** which controls the above described bending section **108** to bend in a desired direction, an air supply and water supply button **112** for performing air supply and water supply operation, a suction button **113** for performing a suction operation, a treatment instrument insertion port **114** which is an inlet port of a treatment instrument to be led into a body, and the like.

[0091] As shown in FIG. **15**, an observation optical system **125** constituted of an illumination lens configuring an illumination optical section for irradiating illumination light to an observation region, and an objective lens configuring an observation optical section capturing an optical image of the observation region is placed at the distal end portion **120** of the insertion section **102**.

[0092] Further, as in the first embodiment, the ultrasound probe **22** is placed at the distal end portion, and a hood section **129** having a cylindrical shape surrounding the ultrasound probe **22** is provided. The hood section **129** is configured by a light transmitting material which transmits a light with a wavelength in a visible light region at a predetermined transmissivity.

[0093] Further, the treatment instrument insertion channel **24** and the suction channel **23** which communicate with the space surrounded by the hood section **129** are formed in the distal end portion **120**. The suction channel **23** may be also used as the channel for inserting a treatment instrument through.

[0094] As above, in the present embodiment, the hood section **129** is configured by a light transmitting material, and thereby, in the ultrasound probe device **101** including the observation optical system **125** for performing observation of the inside of a body by visible light, the same operation and effect as in the above described embodiments can be obtained. Further, when the observation optical system **125** is included in the ultrasound probe device **101**, the observation optical system **125** and the treatment instrument insertion path are preferably disposed so that the treatment instrument which passes through the treatment instrument insertion path is within the field of view of the observation optical system **125**.

Sixth Embodiment

[0095] With use of the hood for an ultrasound probe device or the ultrasound probe device described in any of the above described first to fifth embodiments, the manipulation described as follows can be performed.

[0096] FIG. **16** shows a flow relating to the manipulation in the case of approaching from outside a body with use of the ultrasound probe device as an example. As shown in FIG. **16**, the present embodiment includes at least a step (S1) of boring a hole into a body cavity from a body surface, a step (S2) of inserting the ultrasound probe device with a hood into the body cavity, a step (S3) of searching an object region, a step (S4) of bringing a hood opening portion into contact with the object region, a step (S5) of decompressing an inside of the hood, a step (S6) of performing ultrasound observation of the object region, a step (S7) of extracting the ultrasound probe device from the body cavity, and a step (S8) of closing the hole. Hereinafter, the details of the respective steps will be described.

[0097] (S1)

[0098] S1 is the step of boring a hole into a body cavity from a body surface. The method for boring a hole is not especially limited, the conventionally known method can be used, and, for example, a surgical knife, or an electric knife can be used. Further, a hole may be bored by insertion of a trocar in accordance with the purpose.

[0099] In step S1, after the hole is bored, inert gas may be introduced into the body cavity. When the intended observation region is a lung, a hole is preferably bored between the ribs.

[0100] (S2)

[0101] S2 is the step of inserting the ultrasound probe device with the hood into a body cavity. The hood mentioned here means the hood for the ultrasound probe device described in any of the above described first to fifth embodiments, and may be attachable and detachable with respect to the ultrasound probe device, or may be formed integrally with the ultrasound probe device.

[0102] Further, in step S2, the observation system other than the ultrasound probe device may be inserted into a body cavity. For example, an endoscope capable of visible light observation, fluorescent observation, or infrared observation may be inserted. In this case, dissection for an endoscope may be performed separately from that for the ultrasound probe device in step S1.

[0103] (S3)

[0104] S3 is the step of searching an object region. Search for the object region may be performed by using the ultrasound probe device, or may be performed by using an observation system other than the ultrasound probe device when the observation system other than the ultrasound probe device is used, or may be performed with use of both of the ultrasound probe device and the observation system.

[0105] (S4)

[0106] S4 is the step of bringing the hood opening portion into contact with the object region. Since the inside of the hood is decompressed in S5 which is the next step, the entire circumference of the hood opening portion is preferably in contact with a living body.

[0107] (S5)

[0108] S5 is the step of decompressing the inside of the hood. A living tissue including the object region is drawn into the hood by decompression of the inside of the hood, and the object region can be brought into contact with the ultrasound probe of the ultrasound probe device. The method for decompressing the inside of the hood is not especially limited, but when a gas supply and water supply conduit line is provided in the ultrasound probe device, it can be used.

[0109] (S6)

[0110] S6 is the step of performing ultrasound observation of the object region. In S5 which is the previous step, the living tissue is drawn into the hood by decompression, and therefore, ultrasound observation can be stably performed. Further, in step S6, an ultrasound medium may be introduced into the hood. The ultrasound medium is not especially limited, and, for example, physiological saline, water or the like can be used.

[0111] Further, treatment may be performed while observation is performed. Puncture and extraction of the tissue may be performed with use of a puncture needle while observation is performed, for example, or injection of a medicine may be performed with use of a puncture needle, or extraction of the tissue may be performed with use of grasping forceps, or the tissue may be cut off with use of a radio frequency snare.

[0112] (S7)

[0113] S7 is the step of extracting the ultrasound probe device from the body cavity.

[0114] (S8)

[0115] S8 is the step of closing the hole. The method for closing the incised spot is not especially limited, and the conventionally known method can be used.

[0116] FIG. 17 shows a flow relating to the procedure of the manipulation in the case of approaching from the inside of a lumen with use of the ultrasound probe device. As shown in FIG. 17, the present embodiment includes at least a step (SI) of inserting an ultrasound probe device with a hood into a body, a step (SII) of searching an object region, a step (SIII) of bringing a hood opening portion into contact with the object region, a step (SIV) of decompressing the inside of the hood, a step (SV) of performing ultrasound observation of the object region, and a step (SVI) of extracting the ultrasound probe from the inside of the body. Hereinafter, the details of the respective steps will be described.

[0117] (SI)

[0118] SI is the step of inserting the ultrasound probe device with the hood into a body cavity. The hood mentioned here means the hood for the ultrasound probe device described in any of the above described first to fifth embodiments, and may be attachable and detachable with respect to the ultrasound probe device, or may be formed integrally with the ultrasound probe device. An insertion route of the ultrasound probe device is not especially limited, and can be selected from oral and transanal route, for example, in accordance with the object observation region.

[0119] (SII)

[0120] SII is the step of searching an object region.

[0121] (SIII)

[0122] SIII is the step of bringing the hood opening portion into contact with the object region. Since the inside of the hood is decompressed in SIV which is the next step, the entire circumference of the hood opening portion is preferably in contact with a living body.

[0123] (SIV)

[0124] SIV is the step of decompressing the inside of the hood. A living tissue including the object region is drawn into the hood by decompression of the inside of the hood, and the object region can be brought into contact with the ultrasound probe of the ultrasound probe device. The method for decompressing the inside of the hood is not especially limited, but when a gas supply and water supply conduit line is provided in the ultrasound probe device, it can be used.

[0125] (SV)

[0126] SV is the step of performing ultrasound observation of the object region. In SIV which is the previous step, the living tissue is drawn into the hood by decompression, and therefore, ultrasound observation can be stably performed. Further, in step SV, an ultrasound medium may be introduced into the hood. The ultrasound medium is not especially limited, and, for example, physiological saline, water or the like can be used.

[0127] Further, treatment may be performed while observation is performed. Puncture and extraction of the tissue may be performed with use of a puncture needle while observation is performed, for example, or injection of a medicine may be performed with use of a puncture needle, or extraction of the tissue may be performed with use of grasping forceps, or the tissue may be cut off with use of a radio frequency snare.

[0128] (SVI)

[0129] SVI is the step of extracting the ultrasound probe device from the body cavity.

[0130] The present invention is not limited to the above described embodiments, but can be properly modified within

the range without departing from the spirit or idea of the invention read from claims and the entire description, and the hoods for ultrasound probe devices and the ultrasound probe devices with such modifications are also included in the technical range of the present invention.

[0131] Having described the preferred embodiments of the invention referring to the accompanying drawings, it should be understood that the present invention is not limited to those precise embodiments and various changes and modifications thereof could be made by one skilled in the art without departing from the spirit or scope of the invention as defined in the appended claims.

What is claimed is:

1. A hood for an ultrasound probe device, which is capable of being fitted to an insertion section of an ultrasound probe device having an ultrasound probe, and has a cylindrical shape, wherein a reflectivity of ultrasound in at least a region to which the ultrasound transmitted from the ultrasound probe is irradiated in a state fitted to the insertion section is 25% or less.
2. A hood for an ultrasound probe device, which has a cylindrical shape having opening portions at both ends, and is capable of being fitted to an insertion section of an ultrasound probe device having an ultrasound probe in the opening portion at a proximal end side of the cylindrical shape, wherein in a state fitted to the insertion section, at least a region to which ultrasound transmitted from the ultrasound probe is irradiated, of an inner surface inclines to be closer to the ultrasound probe toward the opening portion at the proximal end side.
3. The hood for an ultrasound probe device according to claim 2, wherein in the state fitted to the insertion section, the inner surface of the cylindrical shape has a tapered shape which extensively opens toward the opening portion at a distal end side from the opening portion at the proximal end side.
4. The hood for an ultrasound probe device according to claim 2, wherein in at least the region to which ultrasound transmitted from the ultrasound probe is irradiated, a thickness of the cylindrical shape increases toward the opening portion at the proximal end side.
5. A hood for an ultrasound probe device, which has a cylindrical shape having opening portions at both ends, and is capable of being fitted to an insertion section of an ultrasound probe device having an ultrasound probe in the opening portion at a proximal end side of the cylindrical shape, wherein the hood section is in a shape in which the opening portion at a distal end side is cut by a plane forming a predetermined angle with respect to a side surface of the cylindrical shape.
6. An ultrasound probe device, comprising: an insertion section having an ultrasound probe; and a hood section which has a cylindrical shape having an opening portion at a distal end side, and is disposed at the insertion section to surround the ultrasound probe,

wherein a space surrounded by the hood section is capable of being decompressed.

7. The ultrasound probe device according to claim 6, wherein the hood section is attachable to and detachable from the insertion section.
8. The ultrasound probe device according to claim 6, wherein in the hood section, a reflectivity of ultrasound in at least a region to which the ultrasound transmitted from the ultrasound probe is irradiated is 25% or less.
9. The ultrasound probe device according to claim 6, wherein in the hood section, at least a region to which ultrasound transmitted from the ultrasound probe is irradiated, of an inner surface inclines to be closer to the ultrasound probe toward a proximal end side from the opening portion at the distal end side.
10. The ultrasound probe device according to claim 9, wherein in the hood section, the inner surface has a tapered shape which extensively opens toward a direction of the opening portion at the distal end side.
11. The ultrasound probe device according to claim 9, wherein in the hood section, in at least the region to which ultrasound transmitted from the ultrasound probe is irradiated, a thickness of the cylindrical shape increases from the opening portion at the distal end side toward the proximal end side.
12. The ultrasound probe device according to claim 6, wherein the hood section is formed so that the opening portion at the distal end side includes a region to which ultrasound transmitted from the ultrasound probe is irradiated.
13. The ultrasound probe device according to claim 6, wherein the hood section is in a shape in which the opening portion at the distal end side is cut by a plane forming a predetermined angle with respect to an insertion axis of the insertion section.
14. The ultrasound probe device according to claim 6, wherein the hood section is contractible.
15. The ultrasound probe device according to claim 6, wherein the insertion section is capable of housing the hood section.
16. The ultrasound probe device according to claim 6, wherein the ultrasound probe is of a convex type or a linear type.
17. The ultrasound probe device according to claim 6, wherein the insertion section comprises at least one channel communicating with a space surrounded by the hood section.
18. The ultrasound probe device according to claim 17, wherein at least two of the channels are included, at least one of the channels is a channel for inserting a treatment instrument, and at least one of the channels is a channel for suction.
19. The ultrasound probe device according to claim 6, wherein the insertion section comprises an optical observation system.
20. The ultrasound probe device according to claim 19, wherein the hood section is formed of a material transmitting visible light.

* * * * *

专利名称(译)	用于超声探头装置和超声探头装置的罩		
公开(公告)号	US20090281429A1	公开(公告)日	2009-11-12
申请号	US12/437986	申请日	2009-05-08
[标]申请(专利权)人(译)	奥林巴斯医疗株式会社		
申请(专利权)人(译)	奥林巴斯医疗系统股份有限公司.		
当前申请(专利权)人(译)	奥林巴斯医疗系统股份有限公司.		
[标]发明人	NISHINA KENICHI NAKAZATO TAKEHARU		
发明人	NISHINA, KENICHI NAKAZATO, TAKEHARU		
IPC分类号	A61B8/14		
CPC分类号	A61B1/00089 A61B1/00101 A61B8/445 A61B8/12 A61B5/6886		
优先权	2008122533 2008-05-08 JP		
外部链接	Espacenet USPTO		

摘要(译)

本发明的超声波探头装置包括具有超声波探头的插入部和具有圆筒形状的罩部，该罩部在远端侧具有开口部，并且设置在插入部以包围超声波探头，并且能够减压罩部分包围的空间。

