



US010349964B2

(12) **United States Patent**
Nita et al.

(10) **Patent No.:** US 10,349,964 B2
(45) **Date of Patent:** *Jul. 16, 2019

(54) **CONNECTOR FOR SECURING
ULTRASOUND CATHETER TO
TRANSDUCER**

(71) Applicant: **Flowcardia, Inc.**, Tempe, AZ (US)

(72) Inventors: **Henry Nita**, Redwood Shores, CA (US); **Martinos Tran**, Tracy, CA (US)

(73) Assignee: **Flowcardia, Inc.**, Franklin Lakes, NJ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 384 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/256,233**

(22) Filed: **Sep. 2, 2016**

(65) **Prior Publication Data**

US 2016/0367284 A1 Dec. 22, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/169,009, filed on Jan. 30, 2014, now Pat. No. 9,433,433, which is a (Continued)

(51) **Int. Cl.**

A61B 8/00 (2006.01)

A61B 17/32 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A61B 17/320068** (2013.01); **A61B 8/12** (2013.01); **A61B 8/445** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC .. A61B 17/320068; A61B 2017/00867; A61B 8/12; A61B 8/445

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,296,620 A 1/1967 Rodda
3,433,226 A 3/1969 Boyd

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2007240154 A1 1/2008
DE 2256127 A1 5/1974

(Continued)

OTHER PUBLICATIONS

Japanese Office Action for Japanese Application No. 2010-134566, dated Mar. 2, 2012.


(Continued)

Primary Examiner — Jonathan Cwern

(57) **ABSTRACT**

An ultrasound system has an ultrasound transducer having a transducer housing and a horn provided at the distal end of the transducer housing, an ultrasound transmission member, a sonic connector that is connected to the horn and the proximal end of the ultrasound transmission member, and a catheter knob having a proximal end that is coupled to the distal end of the transducer housing. The catheter knob has a proximal bore that houses the sonic connector. The system also includes a nesting piece that is retained inside the proximal bore of the catheter knob. The nesting piece can be moved from a first position where the sonic connector is received inside the nesting piece to a second position where the sonic connector is separated from the nesting piece when ultrasound energy is being propagated through the ultrasound transmission member.

11 Claims, 7 Drawing Sheets



Related U.S. Application Data

continuation of application No. 12/831,883, filed on Jul. 7, 2010, now Pat. No. 8,641,630, which is a continuation of application No. 11/192,749, filed on Jul. 29, 2005, now Pat. No. 7,758,510, which is a continuation of application No. 10/666,459, filed on Sep. 19, 2003, now Pat. No. 6,942,620.

(51) Int. Cl.

A61B 8/12 (2006.01)
A61B 90/50 (2016.01)
A61B 17/00 (2006.01)

(52) U.S. Cl.

CPC *A61B 90/50* (2016.02); *A61B 2017/00867* (2013.01); *C08L 2201/12* (2013.01)

(56) References Cited

U.S. PATENT DOCUMENTS

3,443,226 A	5/1969	Knight	5,046,503 A	9/1991	Schneiderman
3,565,062 A	2/1971	Kurls	5,053,008 A	10/1991	Bajaj
3,585,082 A	6/1971	Siller	5,058,570 A	10/1991	Idemoto et al.
3,612,038 A	10/1971	Halligan	5,076,276 A	12/1991	Sakurai et al.
3,631,848 A	1/1972	Muller	5,091,205 A	2/1992	Fan
3,679,378 A	7/1972	Van Impe et al.	5,100,423 A	3/1992	Fearnott
3,719,737 A	3/1973	Vaillancourt et al.	5,109,859 A	5/1992	Jenkins
3,739,460 A	6/1973	Addis et al.	5,114,414 A	5/1992	Buchbinder
3,754,746 A	8/1973	Thiele	5,116,350 A	5/1992	Stevens
3,823,717 A	7/1974	Pohlman et al.	5,127,917 A	7/1992	Niederhauser et al.
3,835,690 A	9/1974	Leonhardt et al.	5,131,393 A	7/1992	Ishiguro et al.
3,839,841 A	10/1974	Amplatz	5,156,143 A	10/1992	Bocquet et al.
3,896,811 A	7/1975	Storz	5,163,421 A	11/1992	Bernstein et al.
4,016,882 A	4/1977	Broadwin et al.	5,171,216 A	12/1992	Dasse et al.
4,033,331 A	7/1977	Guss et al.	5,180,363 A	1/1993	Idemoto et al.
4,136,700 A	1/1979	Broadwin et al.	5,183,470 A	2/1993	Wettermann
4,337,090 A	6/1982	Harrison	5,195,955 A	3/1993	Don Michael
4,368,410 A	1/1983	Hance et al.	5,215,614 A	6/1993	Wijkamp et al.
4,417,578 A	11/1983	Banko	5,217,565 A	6/1993	Kou et al.
4,425,115 A	1/1984	Wuchinich	5,221,255 A	6/1993	Mahurkar et al.
4,453,935 A	6/1984	Newton	5,226,421 A	7/1993	Frisbie et al.
4,486,680 A	12/1984	Bonnet et al.	5,234,416 A	8/1993	Macaulay et al.
4,495,232 A	1/1985	Bauser et al.	5,236,414 A	8/1993	Takasu
4,505,767 A	3/1985	Quin	5,242,385 A	9/1993	Sahatjian et al.
4,535,759 A	8/1985	Polk et al.	5,243,997 A	9/1993	Uflacker et al.
4,545,767 A	10/1985	Suzuki et al.	5,248,296 A	9/1993	Alliger
4,565,589 A	1/1986	Harrison	5,255,669 A	10/1993	Kubota et al.
4,565,787 A	1/1986	Bossle et al.	5,267,954 A	12/1993	Nita
4,572,184 A	2/1986	Stohl et al.	5,269,291 A	12/1993	Carter
4,664,112 A	5/1987	Kensey et al.	5,269,297 A	12/1993	Weng et al.
4,665,906 A	5/1987	Jervis	5,269,793 A	12/1993	Simpson
4,679,558 A	7/1987	Kensey et al.	5,279,546 A	1/1994	Mische et al.
4,700,705 A	10/1987	Kensey et al.	5,287,858 A	2/1994	Hammerslag et al.
4,721,117 A	1/1988	Mar et al.	5,290,229 A	3/1994	Paskar
4,750,902 A	6/1988	Wuchinich et al.	5,304,115 A	4/1994	Pflueger et al.
4,781,186 A	11/1988	Simpson et al.	5,304,131 A	4/1994	Paskar
4,808,153 A	2/1989	Parisi	5,312,328 A	5/1994	Nita et al.
4,811,743 A	3/1989	Stevens	5,318,014 A	6/1994	Carter
4,827,911 A	5/1989	Broadwin et al.	5,318,570 A	6/1994	Hood et al.
4,838,853 A	6/1989	Parisi	5,324,255 A	6/1994	Passafaro et al.
4,854,325 A	8/1989	Stevens	5,324,260 A	6/1994	O'Neill et al.
4,870,953 A	10/1989	DonMicheal et al.	5,325,860 A	7/1994	Seward et al.
4,886,060 A	12/1989	Wiksell	5,326,342 A	7/1994	Pflueger et al.
4,920,954 A	5/1990	Alliger et al.	5,328,004 A	7/1994	Fannin et al.
4,923,462 A	5/1990	Stevens	5,329,927 A	7/1994	Gardineer et al.
4,924,863 A	5/1990	Sterzer	5,341,818 A	8/1994	Abrams et al.
4,931,047 A	6/1990	Broadwin et al.	5,342,292 A	8/1994	Nita et al.
4,936,281 A	6/1990	Stasz	5,344,395 A	9/1994	Whalen et al.
4,936,845 A	6/1990	Stevens	5,346,502 A	9/1994	Estabrook et al.
4,979,952 A	12/1990	Kubota et al.	5,362,309 A	11/1994	Carter
5,000,185 A	3/1991	Yock	5,368,557 A	11/1994	Nita
5,015,227 A	5/1991	Broadwin et al.	5,368,558 A	11/1994	Nita et al.
5,026,384 A	6/1991	Farr et al.	5,376,084 A	12/1994	Bacich et al.
5,030,201 A	7/1991	Palestrant	5,378,234 A	1/1995	Hammerslag et al.
5,030,357 A	7/1991	Lowe	5,380,274 A	1/1995	Nita
			5,380,316 A	1/1995	Aita et al.
			5,382,228 A	1/1995	Nita et al.
			5,383,460 A	1/1995	Jang
			5,389,096 A	2/1995	Aita et al.
			5,391,144 A	2/1995	Sakurai et al.
			5,397,293 A	3/1995	Alliger et al.
			5,397,301 A	3/1995	Pflueger et al.
			5,403,324 A	4/1995	Ciervo et al.
			5,405,318 A	4/1995	Nita
			5,409,483 A	4/1995	Campbell et al.
			5,417,672 A	5/1995	Nita et al.
			5,417,703 A	5/1995	Brown et al.
			5,421,923 A	6/1995	Clarke et al.
			5,427,118 A	6/1995	Nita et al.
			5,431,168 A	7/1995	Webster, Jr.
			5,431,663 A	7/1995	Carter
			5,443,078 A	8/1995	Uflacker
			5,447,509 A	9/1995	Mills et al.
			5,449,369 A	9/1995	Imran
			5,449,370 A	9/1995	Vaitekunas
			5,451,209 A	9/1995	Ainsworth et al.
			5,462,529 A	10/1995	Simpson et al.
			5,465,733 A	11/1995	Hinohara et al.

(56)	References Cited				
U.S. PATENT DOCUMENTS					
5,474,530 A	12/1995	Passafaro et al.	6,159,187 A	12/2000	Park et al.
5,474,531 A	12/1995	Carter	6,165,127 A	12/2000	Crowley
5,480,379 A	1/1996	La Rosa	6,165,188 A	12/2000	Saadat et al.
5,484,398 A	1/1996	Stoddard	6,179,809 B1	1/2001	Khairkhahan et al.
5,487,757 A	1/1996	Truckai et al.	6,180,059 B1	1/2001	Divino, Jr. et al.
5,498,236 A	3/1996	Dubrul et al.	6,190,353 B1	2/2001	Makower et al.
5,507,738 A	4/1996	Ciervo	6,206,842 B1	3/2001	Tu et al.
5,516,043 A	5/1996	Manna et al.	6,210,356 B1	4/2001	Anderson et al.
5,527,273 A	6/1996	Manna et al.	6,217,543 B1	4/2001	Anis et al.
5,538,512 A	7/1996	Zenzon et al.	6,217,565 B1	4/2001	Cohen
5,540,656 A	7/1996	Pflueger et al.	6,217,588 B1	4/2001	Jerger et al.
5,542,917 A	8/1996	Nita et al.	6,221,015 B1	4/2001	Yock
5,597,497 A	1/1997	Dean et al.	6,231,546 B1	5/2001	Milo et al.
5,597,882 A	1/1997	Schiller et al.	6,231,587 B1	5/2001	Makower
5,607,421 A	3/1997	Jeevanandam et al.	6,235,007 B1	5/2001	Divino, Jr. et al.
5,611,807 A	3/1997	O'Boyle	6,241,692 B1	6/2001	Tu et al.
5,618,266 A	4/1997	Liprie	6,241,703 B1	6/2001	Levin et al.
5,626,593 A	5/1997	Imran	6,241,744 B1	6/2001	Imran et al.
5,627,365 A	5/1997	Chiba et al.	6,248,087 B1	6/2001	Spears et al.
5,649,935 A	7/1997	Kremer et al.	6,277,084 B1	8/2001	Abele et al.
5,658,282 A	8/1997	Daw et al.	6,283,983 B1	9/2001	Makower et al.
5,665,062 A	9/1997	Houser	6,287,271 B1	9/2001	Dubrul et al.
5,685,841 A	11/1997	Mackool	6,287,285 B1	9/2001	Michal et al.
5,695,460 A	12/1997	Siegel et al.	6,287,317 B1	9/2001	Makower et al.
5,695,507 A	12/1997	Auth et al.	6,296,620 B1	10/2001	Gesswein et al.
5,715,825 A	2/1998	Crowley	6,298,620 B1	10/2001	Hatzinikolas
5,720,724 A	2/1998	Ressemann et al.	6,302,875 B1	10/2001	Makower et al.
5,725,494 A	3/1998	Brisken	6,309,358 B1	10/2001	Okubo
5,728,062 A	3/1998	Brisken	6,315,741 B1	11/2001	Martin et al.
5,738,100 A	4/1998	Yagami et al.	6,315,754 B1	11/2001	Daoud et al.
5,797,876 A	8/1998	Spears et al.	6,331,171 B1	12/2001	Cohen
5,816,923 A	10/1998	Milo et al.	6,346,192 B2	2/2002	Buhr et al.
5,827,203 A	10/1998	Nita	6,379,378 B1	4/2002	Werneth et al.
5,827,971 A	10/1998	Hale et al.	6,387,109 B1	5/2002	Davison et al.
5,830,127 A	11/1998	DeCastro	6,387,324 B1	5/2002	Patterson et al.
5,830,222 A	11/1998	Makower	6,394,956 B1	5/2002	Chandrasekaran et al.
5,846,218 A	12/1998	Brisken et al.	6,398,736 B1	6/2002	Seward
5,873,835 A	2/1999	Hastings et al.	6,409,673 B2	6/2002	Yock
5,876,385 A	3/1999	Ikari et al.	6,416,533 B1	7/2002	Gobin et al.
5,893,838 A	4/1999	Daoud et al.	6,423,026 B1	7/2002	Gesswein et al.
5,895,397 A	4/1999	Jang et al.	6,427,118 B1	7/2002	Suzuki
5,902,287 A	5/1999	Martin	6,433,464 B2	8/2002	Jones
5,904,667 A	5/1999	Falwell	6,434,418 B1	8/2002	Neal et al.
5,916,192 A	6/1999	Nita et al.	6,450,975 B1	9/2002	Brennan et al.
5,916,912 A	6/1999	Ames et al.	6,454,737 B1	9/2002	Nita et al.
5,935,142 A	8/1999	Hood	6,454,757 B1	9/2002	Nita et al.
5,935,144 A	8/1999	Estabrook	6,454,997 B1	9/2002	Divino, Jr. et al.
5,937,301 A	8/1999	Gardner et al.	6,484,052 B1	11/2002	Visuri et al.
5,944,737 A	8/1999	Tsonton et al.	6,491,707 B2	12/2002	Makower et al.
5,957,882 A	9/1999	Nita et al.	6,494,891 B1	12/2002	Cornish et al.
5,957,899 A	9/1999	Spears et al.	6,494,894 B2	12/2002	Mirarchi
5,964,223 A	10/1999	Baran	6,500,141 B1	12/2002	Irion et al.
5,967,984 A	10/1999	Chu et al.	6,508,781 B1	1/2003	Brennan et al.
5,971,949 A	10/1999	Levin et al.	6,508,784 B1	1/2003	Shu
5,976,119 A	11/1999	Spears et al.	6,511,458 B2	1/2003	Milo et al.
5,989,208 A	11/1999	Nita	6,514,249 B1	2/2003	Maguire et al.
5,989,275 A	11/1999	Estabrook et al.	6,524,251 B2	2/2003	Rabiner et al.
5,997,497 A	12/1999	Nita et al.	6,533,766 B1	3/2003	Patterson et al.
6,004,280 A	12/1999	Buck et al.	6,544,215 B1	4/2003	Bencini et al.
6,004,335 A	12/1999	Vaitekunas et al.	6,547,754 B1	4/2003	Evans et al.
6,007,499 A	12/1999	Martin et al.	6,547,788 B1	4/2003	Maguire et al.
6,007,514 A	12/1999	Nita	6,551,337 B1	4/2003	Rabiner et al.
6,022,309 A	2/2000	Celliers et al.	6,554,846 B2	4/2003	Hamilton et al.
6,024,764 A	2/2000	Schroepel	6,555,059 B1	4/2003	Myrick et al.
6,029,671 A	2/2000	Stevens et al.	6,558,502 B2	5/2003	Divino, Jr. et al.
6,030,357 A	2/2000	Daoud	6,562,031 B2	5/2003	Chandrasekaran et al.
6,036,689 A	3/2000	Tu et al.	6,573,470 B1	6/2003	Brown et al.
6,051,010 A	4/2000	DiMatteo et al.	6,576,807 B1	6/2003	Brunelot et al.
6,066,135 A	5/2000	Honda	6,582,387 B2	6/2003	Derek et al.
6,113,558 A	9/2000	Rosenschein et al.	6,589,253 B1	7/2003	Cornish et al.
6,120,515 A	9/2000	Rogers et al.	6,595,989 B1	7/2003	Schaer
6,123,698 A	9/2000	Spears et al.	6,596,235 B2	7/2003	Divino, Jr. et al.
6,142,971 A	11/2000	Daoud et al.	6,602,467 B1	8/2003	Divino, Jr. et al.
6,149,596 A	11/2000	Bancroft	6,602,468 B2	8/2003	Patterson et al.
6,159,176 A	12/2000	Broadwin et al.	6,605,217 B2	8/2003	Buhr et al.
			6,607,698 B1	8/2003	Spears et al.
			6,610,077 B1	8/2003	Hancock et al.
			6,613,280 B2	9/2003	Myrick et al.
			6,615,062 B2	9/2003	Ryan et al.

(56)	References Cited							
U.S. PATENT DOCUMENTS								
6,616,617 B1	9/2003	Ferrera et al.	8,152,753 B2	4/2012	Nita et al.			
6,622,542 B2	9/2003	Derek et al.	8,172,758 B2	5/2012	Harhen			
6,623,448 B2	9/2003	Slater	8,221,343 B2	7/2012	Nita et al.			
6,635,017 B1	10/2003	Moehring et al.	8,226,566 B2	7/2012	Nita			
6,650,923 B1	11/2003	Lesh et al.	8,246,643 B2	8/2012	Nita			
6,652,547 B2	11/2003	Rabiner et al.	8,257,378 B1	9/2012	O'connor			
6,660,013 B2	12/2003	Rabiner et al.	8,308,677 B2	11/2012	Nita et al.			
6,676,900 B1	1/2004	Divino, Jr. et al.	8,343,134 B2	1/2013	Kost et al.			
6,682,502 B2	1/2004	Bond et al.	8,414,543 B2	4/2013	Mcguckin, Jr. et al.			
6,685,657 B2	2/2004	Jones	8,496,669 B2	7/2013	Nita et al.			
6,689,086 B1	2/2004	Nita et al.	8,506,519 B2	8/2013	Nita			
6,695,781 B2	2/2004	Rabiner et al.	8,613,700 B2	12/2013	Ueno et al.			
6,695,782 B2	2/2004	Ranucci et al.	8,613,751 B2	12/2013	Nita et al.			
6,695,810 B2	2/2004	Peacock, III et al.	8,617,096 B2	12/2013	Nita et al.			
6,702,748 B1	3/2004	Nita et al.	8,632,560 B2	1/2014	Pal et al.			
6,702,750 B2	3/2004	Yock	8,641,630 B2 *	2/2014	Nita	A61B 8/12		
6,719,715 B2	4/2004	Newman et al.				600/459		
6,719,725 B2	4/2004	Milo et al.	8,647,293 B2	2/2014	Nita			
6,729,334 B1	5/2004	Baran	8,647,296 B2	2/2014	Moberg et al.			
6,733,451 B2	5/2004	Rabiner et al.	8,663,259 B2	3/2014	Levine et al.			
6,758,846 B2	7/2004	Goble et al.	8,668,709 B2	3/2014	Nita et al.			
6,761,698 B2	7/2004	Shibata et al.	8,690,818 B2	4/2014	Bennett et al.			
6,814,727 B2	11/2004	Mansouri-Ruiz	8,690,819 B2	4/2014	Nita et al.			
6,855,123 B2	2/2005	Nita	8,702,595 B2	4/2014	Ueki			
6,866,670 B2	3/2005	Rabiner et al.	8,708,892 B2	4/2014	Sugiyama et al.			
6,936,025 B1	8/2005	Evans et al.	8,708,994 B2	4/2014	Pettis et al.			
6,936,056 B2	8/2005	Nash et al.	8,725,228 B2	5/2014	Koblish et al.			
6,942,620 B2 *	9/2005	Nita	8,725,228 B2	5/2014	Koblish et al.			
		A61B 17/22004	8,764,700 B2	7/2014	Zhang et al.			
		600/459	8,768,433 B2	7/2014	Jenkins et al.			
			8,790,291 B2	7/2014	Nita et al.			
			8,974,446 B2	3/2015	Nguyen et al.			
			8,978,478 B2	3/2015	Ishioka			
			9,101,387 B2	8/2015	Plowe et al.			
6,942,677 B2	9/2005	Nita et al.	9,107,590 B2	8/2015	Hansmann et al.			
6,955,680 B2	10/2005	Satou et al.	9,237,837 B2	1/2016	Omoto et al.			
7,004,173 B2	2/2006	Sparks et al.	9,265,520 B2	2/2016	Nita			
7,004,176 B2	2/2006	Lau	9,282,984 B2	3/2016	Nita			
7,056,294 B2	6/2006	Khairkhahan et al.	9,314,258 B2	4/2016	Nita et al.			
7,131,983 B2	11/2006	Murakami	9,381,027 B2	7/2016	Nita et al.			
7,137,963 B2	11/2006	Nita et al.	9,421,024 B2	8/2016	Nita et al.			
7,149,587 B2	12/2006	Wardle et al.	9,433,433 B2 *	9/2016	Nita	A61B 8/12		
7,150,853 B2	12/2006	Lee et al.	9,603,615 B2	3/2017	Sarge			
7,166,098 B1	1/2007	Steward et al.	9,770,250 B2	9/2017	Nita et al.			
7,220,233 B2	5/2007	Nita et al.	9,955,994 B2	5/2018	Nita			
7,267,650 B2	9/2007	Chow et al.	10,004,520 B2	6/2018	Nita et al.			
7,297,131 B2	11/2007	Nita	2002/0022858 A1	2/2002	Demond et al.			
7,335,180 B2	2/2008	Nita et al.	2002/0049409 A1	4/2002	Noda et al.			
7,341,569 B2	3/2008	Soltani et al.	2002/0077550 A1	6/2002	Rabiner et al.			
7,384,407 B2	6/2008	Rodriguez et al.	2002/0188276 A1	12/2002	Evans et al.			
7,393,338 B2	7/2008	Nita	2002/0189357 A1	12/2002	Lai et al.			
7,421,900 B2	9/2008	Karasawa et al.	2003/009153 A1	1/2003	Brisken et al.			
7,425,198 B2	9/2008	Moehring et al.	2003/0036705 A1	2/2003	Hare et al.			
7,494,468 B2	2/2009	Rabiner et al.	2003/0040762 A1	2/2003	Dorros et al.			
7,503,895 B2	3/2009	Rabiner et al.	2003/0199817 A1	10/2003	Thompson et al.			
7,540,852 B2	6/2009	Nita et al.	2003/0216732 A1	11/2003	Truckai et al.			
7,604,608 B2	10/2009	Nita et al.	2003/0225332 A1	12/2003	Okada et al.			
7,621,902 B2	11/2009	Nita et al.	2004/0019349 A1	1/2004	Fuimaono et al.			
7,621,929 B2	11/2009	Nita et al.	2004/0024393 A1	2/2004	Nita et al.			
7,628,763 B2	12/2009	Noriega et al.	2004/0054367 A1	3/2004	Teodoro, Jr. et al.			
7,648,478 B2	1/2010	Soltani et al.	2004/0164030 A1	8/2004	Lowe et al.			
7,758,510 B2 *	7/2010	Nita	2004/0167511 A1	8/2004	Buehlmann et al.			
		A61B 8/12	2004/0193033 A1	9/2004	Badehi et al.			
		600/300	2005/0033311 A1	2/2005	Guldfeldt et al.			
7,771,358 B2	8/2010	Moehring et al.	2005/0149110 A1	7/2005	Wholey et al.			
7,771,452 B2	8/2010	Pal et al.	2005/0165388 A1	7/2005	Bhola			
7,775,994 B2	8/2010	Lockhart	2005/0171527 A1	8/2005	Bhola			
7,776,025 B2	8/2010	Bobo, Jr.	2005/0228286 A1	10/2005	Messerly et al.			
7,819,013 B2	10/2010	Chan et al.	2006/0074441 A1	4/2006	Mcguckin, Jr. et al.			
7,850,623 B2	12/2010	Griffin et al.	2006/0149169 A1	7/2006	Nunomura et al.			
7,918,819 B2	4/2011	Karmarkar et al.	2006/0206039 A1	9/2006	Wilson et al.			
7,935,108 B2	5/2011	Baxter et al.	2006/0264809 A1	11/2006	Hansmann et al.			
7,938,819 B2	5/2011	Kugler et al.	2007/0032749 A1	2/2007	Overall et al.			
7,942,809 B2	5/2011	Leban	2007/0161945 A1	7/2007	Nita et al.			
7,955,293 B2	6/2011	Nita et al.	2007/0178768 A1	8/2007	Harshnan et al.			
7,993,308 B2	8/2011	Rule et al.	2008/0033284 A1	2/2008	Hauck			
8,038,693 B2	10/2011	Allen	2008/0071343 A1	3/2008	Mayberry et al.			
8,043,251 B2	10/2011	Nita et al.	2008/0208084 A1	8/2008	Horzewski et al.			
8,052,607 B2	11/2011	Byrd	2008/0221506 A1	9/2008	Rodriguez et al.			
8,083,727 B2	12/2011	Kugler et al.	2008/0294037 A1	11/2008	Richter			
8,133,236 B2	3/2012	Nita						

(56)	References Cited	DE	4042435	C2	2/1994
	U.S. PATENT DOCUMENTS	DE	10146011	A1	4/2003
		EP	0005719	A1	12/1979
		EP	0316789	A2	5/1989
	2009/0017293 A1 1/2009 Arai et al.	EP	0316796	A2	5/1989
	2009/0143795 A1 6/2009 Robertson	EP	0376562	A2	7/1990
	2010/0004558 A1 1/2010 Frankhouser et al.	EP	0379156	A2	7/1990
	2010/0023037 A1 1/2010 Nita et al.	EP	0394583	A2	10/1990
	2010/0069854 A1 3/2010 Okoh et al.	EP	0443256	A1	8/1991
	2010/0076454 A1 3/2010 Bos	EP	0472368	A2	2/1992
	2010/0121144 A1 5/2010 Farhadi	EP	0541249	A2	5/1993
	2010/0217306 A1 8/2010 Raabe et al.	EP	0820728	A2	1/1998
	2010/0268206 A1 10/2010 Manwaring et al.	EP	1323481	A2	7/2003
	2011/0046522 A1 2/2011 Chan et al.	GB	1106957		3/1968
	2011/0105960 A1 5/2011 Wallace	JP	H2-7150	U	10/1988
	2011/0130834 A1 6/2011 Wilson et al.	JP	01-099547		4/1989
	2011/0196399 A1 8/2011 Robertson et al.	JP	6086822	A	3/1994
	2011/0196403 A1 8/2011 Robertson et al.	JP	H07500752	A	1/1995
	2011/0237982 A1 9/2011 Wallace	JP	7116260	A	5/1995
	2011/0313328 A1 12/2011 Nita	JP	9-503137		3/1997
	2012/0010506 A1 1/2012 Ullrich	JP	10-216140		8/1998
	2012/0109021 A1 5/2012 Hastings et al.	JP	2000-291543		10/2000
	2012/0130475 A1 5/2012 Shaw	JP	2001-104356		4/2001
	2012/0217306 A1 8/2012 Morrill Webb et al.	JP	2001-321388		11/2001
	2012/0238916 A1 9/2012 Nita et al.	JP	2002-186627		7/2002
	2012/0238946 A1 9/2012 Nita et al.	JP	2005-253874		9/2005
	2012/0311844 A1 12/2012 Nita et al.	JP	2006-522644	A	10/2006
	2012/0330196 A1 12/2012 Nita	JP	2007512087	A	5/2007
	2013/0046297 A1 2/2013 Lingeman et al.	JP	2007520255	A	7/2007
	2013/0060169 A1 3/2013 Yamada	WO	8705739	A1	9/1987
	2013/0331652 A1 12/2013 Okamoto	WO	8705793	A1	10/1987
	2013/0338580 A1 12/2013 Yamatani et al.	WO	8906515	A1	7/1989
	2014/0005706 A1 1/2014 Gelfand et al.	WO	9001300	A1	2/1990
	2014/0012087 A1 1/2014 Omoto	WO	9004362	A1	5/1990
	2014/0039491 A1 2/2014 Bakos et al.	WO	9107917	A2	6/1991
	2014/0171804 A1 6/2014 Van Hoven	WO	9211815	A2	7/1992
	2014/0224375 A1 8/2014 Willis	WO	9308750	A2	5/1993
	2014/0236118 A1 8/2014 Unser et al.	WO	9316646	A1	9/1993
	2014/0243712 A1 8/2014 Humayun et al.	WO	9412140	A1	6/1994
	2014/0350401 A1 11/2014 Sinelnikov	WO	9414382	A1	7/1994
	2014/0358028 A1 12/2014 Vetter et al.	WO	9508954	A1	4/1995
	2014/0358029 A1 12/2014 Vetter et al.	WO	9509571	A1	4/1995
	2015/0025544 A1 1/2015 Nita et al.	WO	9515192	A1	6/1995
	2015/0073357 A1 3/2015 Bagwell et al.	WO	9635469	A1	11/1996
	2015/0105621 A1 4/2015 Farhadi	WO	9705739	A1	2/1997
	2015/0105715 A1 4/2015 Pikus et al.	WO	9721462	A1	6/1997
	2015/0133918 A1 5/2015 Sachar	WO	9745078	A1	12/1997
	2015/0148795 A1 5/2015 Amos et al.	WO	9827874	A1	7/1998
	2015/0157443 A1 6/2015 Hauser et al.	WO	9835721	A2	8/1998
	2015/0190660 A1 7/2015 Sarge et al.	WO	9851224	A2	11/1998
	2015/0297258 A1 10/2015 Escudero et al.	WO	9852637	A1	11/1998
	2015/0359651 A1 12/2015 Wübbeling	WO	9925412	A2	5/1999
	2016/0128717 A1 5/2016 Nita	WO	0053341	A1	9/2000
	2016/0128767 A1 5/2016 Azamian et al.	WO	0067830	A1	11/2000
	2016/0135835 A1 5/2016 Onuma	WO	02094103	A1	11/2002
	2016/0183956 A1 6/2016 Nita	WO	03039381	A1	5/2003
	2016/0271362 A1 9/2016 Van Liere	WO	2004012609	A1	2/2004
	2016/0328998 A1 11/2016 Nita et al.	WO	2004093736	A2	11/2004
	2016/0338722 A1 11/2016 Nita et al.	WO	2004112888	A2	12/2004
	2016/0367284 A1 12/2016 Nita et al.	WO	2005053769	A2	6/2005
	2017/0065288 A1 3/2017 Imai et al.	WO	2005112770	A1	12/2005
	2017/0128090 A1 5/2017 Sarge	WO	2006049593	A1	5/2006
	2017/0265879 A1 9/2017 Washburn, II et al.	WO	2013109269	A1	7/2012
	2017/0265886 A1 9/2017 Nita et al.	WO	2014022716	A2	2/2014
	2017/0354428 A1 12/2017 Nita et al.	WO	2014105754	A1	7/2014
	2018/0042636 A1 2/2018 Nita	WO	2014106847	A1	7/2014
	2018/0140321 A1 5/2018 Deepa	WO	2018097856	A1	5/2018
	2018/0168668 A1 6/2018 Zheng	WO	20180187159	A1	10/2018
	2018/0177515 A1 6/2018 Boyle et al.				
	2018/0197856 A1 7/2018 Chou et al.				
	2018/0221040 A1 8/2018 Roll Hoye				
	2018/0280005 A1 10/2018 Parmentier				
	2018/0280044 A1 10/2018 Nita et al.				

OTHER PUBLICATIONS

Sehgal, et al., Ultrasound-Assisted Thrombolysis, Investigative Radiology, 1993, vol. 28, Issue 10, pp. 939-943.


Siegel, et al., "In Vivo Ultrasound Arterial Recanalization of Atherosclerotic Total Occlusions", Journal of the American College of Cardiology, Feb. 1990, vol. 15, No. 2, pp. 345-351.


FOREIGN PATENT DOCUMENTS



DE	2438648	A1	2/1976
DE	8910040	U1	12/1989
DE	3821836	A1	1/1990


(56)	References Cited	
	OTHER PUBLICATIONS	
	"What is Electron Beam Curing?" downloaded from web on Nov. 14, 2002, 4 pages total. (http://www.ms.ornl.gov/researchgroups/composites/new%20orccmt%20pages/pages/ebwha).	Office Action dated Aug. 3, 2010 from Japanese Application No. 2006-517355 filed on Jun. 16, 2004.
	EP Extended Search Report dated Aug. 13, 2009; Application 04710537.5-1269, 5 pages.	Office Action dated Jan. 26, 2010 from Japanese Application No. 2006-517355 filed on Jun. 16, 2004.
	Noone, D.: Experimental and Numerical Investigation of Wire Waveguides for Therapeutic Ultrasound Angioplasty. M.Eng. Dublin City University. 2008.	International Preliminary Report and Written Opinion dated Aug. 1, 2017 for PCT Application No. PCT/US2017/030675.
	Definition of the term "connected", retrieved on Sep. 21, 2013. < www.thefreedictionary.com/connected > 1 page total.	International Preliminary Report and Written Opinion dated Feb. 6, 2018 for PCT Application No. PCT/US2018/017022.
	Supplemental European Search Report dated Nov. 5, 2009 for European Application No. EP03766931.	Extended European Search Report dated Mar. 5, 2012 for European Application No. 12153606.4-1269.
	International Search Report dated Oct. 28, 2003 for PCT Application No. PCT/US2003/023468.	Margaret Fyfe et al., Mast cell degranulation and increased vascular permeability induced by therapeutic' ultrasound in the rat ankle joint, <i>Br. J. exp. Path.</i> , 1984, vol. 65, pp. 671-676.
	Extended European Search Report dated Mar. 22, 2012 for European Application No. EP11188799.	"Irradiation, Biological, and Other Technologies: E-beam, Biological, and Sharps Treatment Systems", Non-Incineration Medical Waste Treatment Technologies, Aug. 2001, Chapter 9, pp. 69-74, Health Care Without Harm, Washington, DC.
	International Search Report dated Dec. 23, 2005 for PCT Application No. PCT/US2004/019378.	Paul Yock et al., Catheter-Based Ultrasound Thrombolysis Shake, Rattle, and Repertuse, https://doi.org/10.1161/01.CIR.95.6.1360 Circulation. 1997;95:1360-1362 Originally published Mar. 18, 1997.
	Extended European Search Report for Patent Application No. 06718204.8, dated May 30, 2012.	Calhoun et al., "Electron-Beam Systems for Medical Device Sterilization", downloaded from web on Oct. 8, 2002 < www.devicelink.com/mpb/archive/97/07/002.html > 7 pages total.
	International Search Report dated Aug. 1, 2013 for PCT Application No. PCT/US2013/053306.	Definition of the term "coupled", retrieved on May 18, 2013. < www.merriam-webster.com/dictionary/couple > 1 page total.
	International Preliminary Report dated Aug. 1, 2013 for PCT Application No. PCT/US2013/053306.	"E-Beam Theory" RDI-IBA Technology Group, downloaded from web on Oct. 8, 2002 < www.e-beamrdi/EbeamTheory.htm > 2 pages total.
	Written Opinion dated Aug. 1, 2013 for PCT Application No. PCT/US2013/053306.	Office Action dated May 20, 2010 from Japanese Application No. 2006-541200 filed on Oct. 25, 2004.
	Supplemental European Search Report dated Apr. 29, 2009 for European Application No. EP 04711207.3.	Office Action dated Oct. 11, 2012 from Japanese Application No. 2010-181956.

* cited by examiner












FIG. 7






FIG. 8





**CONNECTOR FOR SECURING
ULTRASOUND CATHETER TO
TRANSDUCER**

**CROSS-REFERENCE TO RELATED
APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 14/169,009, filed Jan. 30, 2014, now U.S. Pat. No. 9,433,433, which is a continuation of Ser. No. 12/831, 883, now U.S. Pat. No. 8,641,630, which is a continuation of Ser. No. 11/192,749, filed Jul. 29, 2005, entitled "Connector for Securing Ultrasound Catheter to Transducer" (now U.S. Pat. No. 7,758,510), which is a continuation of Ser. No. 10/666,459, filed Sep. 19, 2003, entitled "Connector for Securing Ultrasound Catheter to Transducer" (now U.S. Pat. No. 6,942,620), each of which is incorporated by reference as though set forth fully herein.

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention pertains to medical equipment, and more particularly, to a device and method for attaching an ultrasound catheter to an ultrasound transducer which prevents frequency shifts and minimizes the mechanical impact of the handling connection area during a medical procedure.

Description of the Related Art

A number of ultrasound systems and devices have heretofore been proposed for use in ablating or removing obstructive material from blood vessels. Ultrasound catheters have been utilized to ablate various types of obstructions from blood vessels of humans and animals. Successful applications of ultrasound energy to smaller blood vessels, such as the coronary arteries, require the use of relatively small diameter ultrasound catheters which are sufficiently small and flexible to undergo transluminal advancement through the tortuous vasculature of the aortic arch and coronary tree. These ultrasound catheters incorporate a very small diameter ultrasound transmission member which extends through such catheters. The proximal end of the ultrasound transmission member is typically connected to an ultrasound transducer via a sonic connector.

The attachment of the ultrasound transmission member to an ultrasound transducer plays a very important role in ultrasound energy propagation. The attachment region needs to be accurately aligned and free of mechanical stress and other interfaces. For example, undesirable stress at the attachment region can be caused by pressing upon, pushing, pulling, torquing, bending or bumping the attachment region during use of the ultrasound catheter. In addition, it is preferable for the sonic connector to be free from any interface (i.e., contact) with any other component during energy transmission. Otherwise, such stresses and interfaces can negatively impact the propagation of ultrasound energy through the ultrasound transmission member. Contact of the sonic connector with any other part of the catheter housing during the delivery of ultrasound energy might also cause a shift in frequency and impact performance.

Thus, there still exists a need for an improved connection of the proximal end of the ultrasound transmission member to an ultrasound transducer.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an improved connection between the ultrasound catheter and the ultrasound transducer.

It is yet another object of the present invention to improve the propagation of ultrasound energy by limiting and minimizing the impact of undesirable external forces.

In order to accomplish the objects of the present invention, there is provided an ultrasound system and method of using the ultrasound system during a medical procedure. The ultrasound system has an ultrasound transducer having a transducer housing and a horn provided at the distal end of the transducer housing, an ultrasound transmission member, a sonic connector that is connected to the horn and the proximal end of the ultrasound transmission member, and a catheter knob having a proximal end that is coupled to the distal end of the transducer housing. The catheter knob has a proximal bore that houses the sonic connector. The system also includes a nesting piece that is retained inside the proximal bore of the catheter knob. The nesting piece can be moved from a first position where the sonic connector is received inside the nesting piece to a second position where the sonic connector is separated from the nesting piece when ultrasound energy is being propagated through the ultrasound transmission member.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of an ultrasound system according to one embodiment of the present invention.

FIG. 2 is a cross-sectional view of the Y-connector and catheter knob of the system of FIG. 1.

FIG. 3 is a cross-sectional view of the Y-connector, the catheter knob, the slide collar assembly and the transducer housing of the system of FIG. 1 with the slide collar assembly in the non-supporting position.

FIG. 4 is a cross-sectional view of the Y-connector, the catheter knob, the slide collar assembly and the transducer housing of the system of FIG. 1 with the slide collar assembly in the supporting position.

FIG. 5 is an exploded perspective view of some of the elements of the slide collar assembly of the system of FIG. 1.

FIG. 6 is an assembled perspective view of the elements of FIG. 5.

FIG. 7 is an exploded perspective view of the catheter knob of the system of FIG. 1.

FIG. 8 is an assembled perspective view of the catheter knob of FIG. 7.

FIG. 9 is a perspective view of the system of FIG. 1 with the slide collar assembly in the non-supporting position.

FIG. 10 is a perspective view of the system of FIG. 1 with the slide collar assembly in the supporting position.

FIG. 11 is a perspective view of the catheter knob of the system of FIG. 1 with the slide collar assembly in the non-supporting position.

FIG. 12 is a perspective view of the catheter knob of the system of FIG. 1 with the slide collar assembly in the supporting position.

**DETAILED DESCRIPTION OF THE
PREFERRED EMBODIMENT**

The following detailed description is of the best presently contemplated modes of carrying out the invention. This description is not to be taken in a limiting sense, but is made merely for the purpose of illustrating general principles of embodiments of the invention. The scope of the invention is best defined by the appended claims. In certain instances, detailed descriptions of well-known devices, compositions,

components, mechanisms and methods are omitted so as to not obscure the description of the present invention with unnecessary detail.

FIG. 1 illustrates an ultrasound system according to the present invention for use in ablating and removing occlusive material inside the vessel of an animal or human being. The ultrasound system includes an ultrasonic catheter device 10 which has an elongate catheter body 12 having a proximal end 14, a distal end 16, and defining at least one lumen extending longitudinally therethrough. The ultrasound catheter device 10 is operatively coupled at its proximal end 14, by way of a Y-connector 18, a catheter knob 20, and a slide collar assembly 22, to an ultrasound transducer housing 24. As shown in FIGS. 3-4, an ultrasound transducer 34 is housed inside the transducer housing 24. The ultrasound transducer 34 is connected to a signal generator 26, which can be provided with a foot actuated on-off switch 28. The signal generator 26 can be supported by an IV pole 27. When the on-off switch 28 is depressed, the signal generator 26 sends an electrical signal to the ultrasound transducer 34, which converts the electrical signal to ultrasound energy. Such ultrasound energy subsequently passes through the catheter device 10 and is delivered to the distal end 16.

Referring also to FIGS. 2-4, an ultrasound transmission member 32 extends through the lumen of the catheter 10 from the distal end 16 to the proximal end 14. The ultrasound transducer 34 is coupled via a sonic connector 36 (described in greater detail below) to the ultrasound transmission member 32, so that the ultrasound energy can be passed through the sonic connector 36 and the ultrasound transmission member 32 to be delivered to the distal end 16 of the catheter 10. A guidewire 30, which can be any conventional monorail or over-the-wire guidewire, may be utilized in conjunction with the catheter 10 in a manner that is well-known in the catheter art.

The frontal portion of the Y-connector 18 is connected to the proximal end 12 of the catheter 10 using techniques that are well-known in the catheter art. An injection pump (not shown) or IV bag (not shown) can be connected, by way of an infusion tube (not shown), to an infusion port or sidearm 40 of the Y-connector 18. The injection pump can be used to infuse coolant fluid (e.g., 0.9% NaCl solution) into and/or through the lumen of the catheter 10. Such flow of coolant fluid may be utilized to prevent overheating of the ultrasound transmission member 32 extending longitudinally through the lumen of the catheter 10. Such flow of the coolant fluid through the lumen of the catheter 10 serves to bathe the outer surface of the ultrasound transmission member 32, thereby providing for an equilibration of temperature between the coolant fluid and the ultrasound transmission member 32. Thus, the temperature and/or flow rate of coolant fluid may be adjusted to provide adequate cooling and/or other temperature control of the ultrasound transmission member 32. In addition to the foregoing, the injection pump may be utilized to infuse a radiographic contrast medium into the catheter 10 for purposes of imaging.

Examples of iodinated radiographic contrast media which may be selectively infused into the catheter 10 via the injection pump are commercially available as Angiovist 370 from Berlex Labs, Wayne, N.J. and Hexabrix from Malinckrodt, St. Louis, Mo.

The proximal end of the ultrasound transmission member 32 is attached to the sonic connector 36 which is configured to effect operative and removable attachment of the proximal end of the ultrasound transmission member 32 to the distal horn 42 of the ultrasound transducer 34. The sonic connector 36 is preferably configured and constructed to

permit passage of ultrasound energy through the ultrasound transmission member 32 with minimal lateral side-to-side movement of the ultrasound transmission member 32 while, at the same time, permitting unrestricted longitudinal forward/backward vibration or movement of the ultrasound transmission member 32.

The ultrasound transmission member 32 may be formed of any material capable of effectively transmitting the ultrasonic energy from the ultrasound transducer 34 to the distal end 16 of the catheter 10, including but not necessarily limited to metal, plastic, hard rubber, ceramic, fiber optics, crystal, polymers, and/or composites thereof. In accordance with one aspect of the invention, all or a portion of the ultrasound transmission member 32 may be formed of one or more materials which exhibit super-elasticity. Such materials should preferably exhibit super-elasticity consistently within the range of temperatures normally encountered by the ultrasound transmission member 32 during operation of the catheter 10. Specifically, all or part of the ultrasound transmission member 32 may be formed of one or more metal alloys known as "shape memory alloys". Such super-elastic metal alloys are well-known in the art and will not be described in any further detail herein.

The proximal end of the Y-connector 18 is attached to the distal end of the catheter knob 20 by threadably engaging the proximal end of the Y-connector 18 inside a threaded distal bore 44 at the distal end of the catheter knob 20. O-rings 46 are provided in the threaded distal bore 44 to minimize transverse vibrations. The proximal end of the catheter knob 20 receives the extension 70 of the transducer housing 24 and is supported by the slide collar assembly 22. The slide collar assembly 22 is positioned over the distal end of the transducer housing 24, and has a non-supporting position where the slide collar assembly 22 is retracted towards the transducer housing 24; and has a supporting position where the slide collar assembly 22 is extended to cover at least a portion of the catheter knob 20. Thus, the slide collar assembly 22 functions as a support member that is disposed on the transducer housing 24 to support at least a portion of the catheter knob 20.

Referring also to FIGS. 5 and 6, the slide collar assembly 22 has an inner ring 50 (also referred to as collar 50) and an outer ring 52 (also referred to as collar 52). The inner ring 50 has a bore 54 and a longitudinal slit 58 that extends through the length of the inner ring 50. The distal portion of the bore 54 can be stepped as shown at 55 (see FIG. 3) to function as a pushing surface that pushes a nesting piece 94 (described below) in a distal direction as the inner ring 50 is moved from the non-supporting position to the supporting position. The outer ring 52 also has a bore 56, and has a narrowed proximal end 57. The inner ring 50 is retained inside the bore 56 of the outer ring 52 and abuts the narrowed proximal end 57 which acts as a stop to limit the proximal movement of the inner ring 50. Each of the inner ring 50 and the outer ring 52 has an opening 60 and 62, respectively, that are aligned with each other and that are adapted to receive a locking pin 64. A tubular inner sleeve 66 extends through the inside of the bore 54 of the inner ring 50 to ensleeve the first extension 70 of the transducer housing 24, as explained below. The sleeve 66 has a proximal section 80 and an enlarged distal section 82. The inner ring 50 is normally fitted around the proximal section 80 when the slide collar assembly 22 is in the non-supporting position, but the inner ring 50 is fitted around the distal section 82 when the slide collar assembly 22 is in the supporting position. Thus, providing the distal section 82 in an enlarged configuration allows for the inner ring 50 to

achieve a friction-fit with the distal section 82, while the inner ring 50 experiences a loose fit over the proximal section 80.

The transducer housing 24 has a cylindrical wall 68 having a distal extension that comprises two stepped cylindrical extensions 70 and 72 extending from the distal end of the cylindrical wall 68. The first extension 70 is attached to the distal end of the cylindrical wall 68, and has a greater outer diameter than the second extension 72 that is attached to the distal end of the first extension 70. A throughbore 76 extends from the hollow interior 78 of the cylindrical wall 68 and through the extensions 70 and 72. The throughbore 76 can have the same diameter throughout its length. The second extension 72 is adapted to be received inside the proximal bore 90 of the catheter knob 20, while the first extension 70 is received inside the sleeve 66. In addition, an opening 84 is provided in the proximal section 80 of the sleeve 66 and is aligned with a corresponding opening 86 on the first extension 70, with the openings 84, 86 adapted to receive a locking pin 88 that secures the sleeve 66 to the first extension 70 at a fixed position.

A longitudinal slot 92 is provided on the sleeve 66. When the slide collar assembly 22 is in the non-supporting position (i.e., inner ring 50 positioned over the proximal section 80), the slot 92 is opened. However, when the slide collar assembly 22 is moved to the supporting position, the inner ring 50 is positioned over the distal section 82 and compresses the enlarged distal section 82 to close the slot 92. With the slot 92 closed, the sleeve 66 provides a frictional grip of the proximal end 91 of the catheter knob 20.

Referring now to FIGS. 2-4 and 7-8, the catheter knob 20 has a proximal bore 90 that can be sleeved over the second extension 72 in a manner such that the outer surface of the catheter knob 20 can be substantially flush with the outer surface of the first extension 70 (as best shown in FIGS. 3 and 4). The proximal bore 90 houses the sonic connector 36 and a nesting piece 94. An elastic element 96, such as a spring, is seated in the distal part of the proximal bore 90, and has one end carried on a projection 98 provided at the distal end of the nesting piece 94. The nesting piece 94 has a generally cylindrical configuration and has a receptacle 100 which functions to selectively retain the sonic connector 36, as will be explained in greater detail below. In addition, a control ring 110 is positioned around the outer surface 112 of the catheter knob 20. The control ring 110 cooperates with the nesting piece 94 to move the nesting piece 94 in a reciprocal manner inside the proximal bore 90 of the catheter knob 20, as explained below.

The nesting piece 94 has two opposite and aligned openings 102; only the top opening 102 is shown in FIG. 7, but the bottom opening is the same and is aligned on a straight line with the top opening 102. Similarly, the catheter knob 20 has two opposite and aligned channels 104; only the top channel 104 is shown in FIG. 7, but the bottom channel is the same and is aligned on a straight line with the top channel 104. In addition, the control ring 110 has two opposite and aligned openings 114. The channels 104 and the openings 102, 114 are aligned, as best shown in FIGS. 3 and 4. Two opposing pins 106 are provided, with each pin 106 adapted to be fitted inside a corresponding set of channel 104 and openings 102, 114, so as to couple the control ring 110 and the nesting piece 94 as a unitary moving piece. The width of the channels 104 define the distal and proximal limits of movement for the control ring 110 and the nesting piece 94. The catheter knob 20 also has an annular flange 116 provided about its outer surface 112 that also defines the distal limit of the movement of the control ring 110.

In use, the sonic connector 36 is shown in FIGS. 3-4 as connecting the transducer horn 42 (e.g., with a threaded connection) with the ultrasound transmission member 32. The sonic connector 36 is always located at a fixed position inside the proximal bore 90 of the catheter knob 20. When the slide collar assembly 22 is in the non-supporting position shown in FIGS. 3, 9 and 11, the elastic element 96 normally biases the nesting piece 94 in the proximal direction so that the sonic connector 36 is received inside the receptacle 100 of the nesting piece 94 to be supported by the nesting piece 94. The proximal movement of the nesting piece 94 will cause the pins 106 to move in the proximal direction inside the channels 104, thereby causing the control ring 110 to move proximally away from the flange 116. The outer ring 52 and the inner ring 50 are positioned completely over the proximal section 80 of the sleeve 66, with the narrowed proximal end 57 positioned adjacent the cylindrical wall 68 of the transducer housing 24.

When the slide collar assembly 22 is now moved from the non-supporting position to the supporting position shown in FIGS. 4, 10 and 12, the user pushes the outer ring 52 in the distal direction. The step 55 on the distal end of the inner ring 50 engages the proximal end of the control ring 110 and pushes the control ring 110 in the distal direction. Movement of the control ring 110 in the distal direction will cause the pins 106 to move in the distal direction inside the channels 104, thereby causing the nesting piece 94 to counter the bias of the elastic element 96 and move in the distal direction. As the nesting piece 94 moves in the distal direction, the sonic connector 36 becomes free from the receptacle 100 of the nesting bore 94. In addition, the distal movement of the inner ring 50 will cause the inner surface of the inner ring 50 to engage the enlarged distal section 82 of the sleeve 66, which functions to close the slot 92 so as to frictionally grip the proximal portion 91 of the knob 20 when the slide collar assembly 22 is in the supporting position. The flange 116 and the width of the channels 104 function as stops to limit the distal movement of the control ring 110.

In the supporting position, the sonic connector 36 is not supported by the nesting piece 94 so that the sonic connector 36 can be free from any component or material interfaces, thereby promoting improved ultrasound energy propagation. The medical procedure can then be carried out while the slide collar assembly 22 is in the supporting position. Upon completion of the medical procedure, the above-described steps are reversed. In particular, the combined inner and outer rings 50, 52 (slide collar assembly 22) are retracted in the proximal direction so that they are now positioned over the proximal section 80 of the sleeve 66. The bias of the elastic element 96 will push the nesting piece 94 in the proximal direction so that the sonic connector 36 is received inside the receptacle 100 of the nesting piece 94. In addition, the proximal movement of the nesting piece 94 will cause the pins 106 to move in the proximal direction inside the channels 104, thereby causing the control ring 110 to move proximally away from the flange 116. Now, the catheter 10 can be disconnected from the transducer 34.

While the description above refers to particular embodiments of the present invention, it will be understood that many modifications may be made without departing from the spirit thereof. The accompanying claims are intended to cover such modifications as would fall within the true scope and spirit of the present invention.

What is claimed is:

1. A system comprising:
an ultrasound transducer housing containing a transducer horn that is connected to a signal generator;

a transducer mechanism comprising a slide collar assembly that comprises an outer ring that is disposed around an inner ring having a longitudinal slit through a wall of the inner ring;
and
a catheter having:
a flexible body;
a proximal end;
a distal end;
at least one longitudinal lumen;
an ultrasound transmission member having a proximal end and disposed in the lumen;
a connector joining the proximal end of the ultrasound transmission member and the transducer horn;
a knob having a proximal end that is coupled to the distal end of the transducer housing, the knob having a proximal bore that houses the connector;
and
a nesting piece that is retained inside the proximal bore of the knob, the nesting piece movable from a first position where the connector is received inside the nesting piece to a second position where the connector is separated from the nesting piece.

2. The system of claim 1, wherein the transducer mechanism is configured to move from a first position to a second position, and wherein the transducer mechanism is configured such that movement of the transducer mechanism from the first position to the second position engages a control ring on the catheter.

3. The system of claim 2, wherein the catheter mechanism has a longitudinal interface.

4. The system of claim 2, wherein the catheter mechanism has a transverse interface.

5. The system of claim 2, wherein the connector and the transducer horn have a threaded connection.

6. The system of claim 2, wherein the connector and the transducer horn have a frictional connection.

7. The system of claim 2, wherein the catheter mechanism freely overlaps at least a portion of the connector.

8. The system of claim 2, wherein the catheter mechanism comprises removable components.

9. The system of claim 2, wherein the catheter mechanism comprises fixed and removable components.

10. The system of claim 2, wherein the catheter mechanism is configured to be movable in a direction parallel to the ultrasound transmission member.

11. A method comprising:
providing a catheter comprising:
an elongated flexible body,

a proximal end,
a distal end,
a knob having a proximal end, and a distal end, wherein the elongated flexible body extends from the distal end of the knob,
a control ring disposed around the proximal end of the knob,
a nesting piece that is retained inside a proximal bore of the knob, the nesting piece movable from a first position where a connector is received inside the nesting piece to a second position where the connector is separated from the nesting piece,
at least one longitudinal lumen,
an ultrasound transmission member having a proximal end and extending through the lumen,
a connector that is secured to the proximal end of the ultrasound transmission member and disposed within the nesting piece, and
a catheter mechanism comprising the control ring and the nesting piece, the catheter mechanism being movable from a first position where the nesting piece is engaged around the connector so as to restrain the connector and a second position where the nesting piece is disengaged from the connector;
providing a transducer housing comprising:
a transducer horn that is connectable to a signal generator, and
a transducer mechanism comprising a slide collar assembly separate from and disposed around a longitudinally slit inner ring, wherein the transducer mechanism is movable from a first position to a second position, operatively coupling the transducer housing to the proximal end of the ultrasound transmission member;
moving the transducer mechanism from the first position to the second position to engage the control ring on the catheter and move the nesting piece from the first position to the second position, when the transducer is connected and transmitting ultrasound energy to the catheter, the catheter mechanism in the first position substantially prevents the transmission of ultrasound energy to the ultrasound transmission member and the catheter mechanism in the second position permits the transmission of ultrasound energy to the ultrasound transmission member;
and
transmitting ultrasound energy to the proximal end of the catheter.

* * * * *

专利名称(译)	用于将超声导管固定到换能器的连接		
公开(公告)号	US10349964	公开(公告)日	2019-07-16
申请号	US15/256233	申请日	2016-09-02
[标]申请(专利权)人(译)	FLOWCARDIA		
申请(专利权)人(译)	FLOWCARDIA INC.		
当前申请(专利权)人(译)	FLOWCARDIA INC.		
[标]发明人	NITA HENRY TRAN MARTINOS		
发明人	NITA, HENRY TRAN, MARTINOS		
IPC分类号	A61B8/00 A61B17/32 A61B8/12 A61B90/50 A61B17/00 A61B6/00 A61B8/14		
CPC分类号	A61B17/320068 A61B8/12 A61B90/50 A61B8/445 C08L2201/12 A61B2017/00867		
其他公开文献	US20160367284A1		
外部链接	Espacenet		

摘要(译)

超声系统具有超声换能器，其具有换能器壳体和设置在换能器壳体的远端处的喇叭，超声传输构件，连接到喇叭和超声传输构件的近端的声波连接器，以及导管旋钮具有近端，该近端连接到换能器壳体的远端。导管旋钮具有容纳声波连接器的近端孔。该系统还包括嵌套件，该嵌套件保持在导管旋钮的近端孔内。嵌套件可以从第一位置移动到第二位置，在第一位置，声波连接器被接收在嵌套件内，在第二位置，当超声能量传播通过超声传输构件时，声波连接器与嵌套件分离。

