




US 20150182200A1

(19) **United States**(12) **Patent Application Publication**
Birglehner et al.(10) **Pub. No.: US 2015/0182200 A1**(43) **Pub. Date: Jul. 2, 2015**(54) **DAMPER FOR MEDICAL ULTRASONIC
PROBE****Publication Classification**(71) Applicant: **General Electric Company,**
Schenectady, NY (US)(72) Inventors: **Erich Birglehner, Zipf (AT); Thomas**
Rittenschober, Zipf (AT)(73) Assignee: **General Electric Company,**
Schenectady, NY (US)(21) Appl. No.: **14/143,235**(22) Filed: **Dec. 30, 2013**(51) **Int. Cl.**
A61B 8/00 (2006.01)(52) **U.S. Cl.**
CPC **A61B 8/546** (2013.01); **A61B 8/4444**
(2013.01); **A61B 8/4483** (2013.01)(57) **ABSTRACT**

A medical ultrasonic probe includes an ultrasonic probe having a probe head and a connector. The connector includes a fluid cooling system comprising a pump configured to pump a cooling fluid between the connector and the probe head. A damper including a housing has a first portion defining a cavity receiving the cooling fluid and a second portion including a gas that is separated from the first portion by a membrane.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

DAMPER FOR MEDICAL ULTRASONIC PROBE

BACKGROUND

[0001] Medical ultrasonic probes may host a plurality of electronics in the probe handle. Thermal management may become a challenge in the presence of electronics with considerable power consumption in the probe handle. In some cases, the heat generated by this power consumption is not sufficiently removed by means of natural convection via the probe surface. In such cases an additional cooling system such as the liquid cooling systems taught in U.S. Pat. No. 8,475,375, incorporated herein by reference in its entirety, may be employed.

SUMMARY

[0002] In one embodiment a medical ultrasonic probe includes an ultrasonic probe having a probe head and a connector. The connector includes a fluid cooling system comprising a pump configured to pump a cooling fluid between the connector and the probe head. A damper including a housing has a first portion defining a cavity receiving the cooling fluid and a second portion including a gas that is separated from the first portion by a membrane.

[0003] In another embodiment a vibration damper for an ultrasonic probe includes a damper located within a connector of a portable medical ultrasonic probe. The damper forms an interior chamber. An elastomeric membrane is mounted in the chamber separating the chamber into a first compartment having a sealed air compartment and a second compartment having a fluid inlet port and a fluid outlet port for respectively receiving and releasing a cooling fluid.

[0004] In another embodiment a process for providing fluid cooling to medical ultrasonic probe includes providing a medical ultrasonic probe having a probe head with a first heat exchanger. The process further includes providing a connector containing a cooling system connected to the medical ultrasonic probe by fluid lines and comprising second heat exchanger; a pump; and a damper which absorbs vibrations induced in a cooling fluid within by the operation of the pump. The process also includes operating the pump to drive the cooling fluid through the damper, the first heat exchanger and the second heat exchanger through the fluid lines.

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] FIG. 1 is a schematic representation of an ultrasound probe and connector.

[0006] FIG. 2 is representative view of fluid flow within a damper.

[0007] FIG. 3 is a cross-sectional view of the damper.

[0008] FIG. 4 is an exploded view of the damper.

[0009] FIG. 5 is a view of an ultrasound probe including a probe head, cable and connector.

[0010] FIG. 6 is a schematic representation of an ultrasound probe and connector with an alternative fluid flow circuit.

DETAILED DESCRIPTION

[0011] Referring to FIG. 1 and FIG. 5, an ultrasound probe 10 includes a probe head 12, a connector 14 and a cable 16 connecting the probe head 12 to the connector 14. Probe head 12 includes a transducer and receiver to send and receive ultrasound energy. Cable 16 provides for electric and fluid communication between the probe head 12 and connector 14.

Connector 14 includes an interface 18 to an ultrasound station that may include a monitor and processor for processing the images received from the probe head and sending instructions for operation of the probe head.

[0012] Referring to FIG. 1, a cooling system allow for heat created from the ultrasound probe electronics to be removed from the probe. The cooling system includes a first heat exchanger 20 located within probe head 12, a second heat exchanger 22 located within the housing 24. The first heat exchanger 20 is in fluid communication with the second heat exchanger 22 with a conduit portion 26 that extends through cable 16. A cooling fluid is pumped through the conduit portion 26 to transfer heat from the first heat exchanger 20 to the second heat exchanger 24. In one embodiment the cooling fluid is a liquid. A fan (not shown) located within the housing of connector 14 circulates air over the second heat exchanger 22 to remove heat that is transferred from the first heat exchanger 20 to the second heat exchanger 22. In one embodiment second heat exchanger 22 has a number of external ridges or fins to increase the outer surface area of the second heat exchanger 22 to assist in removing heat from the second heat exchanger 22.

[0013] In one embodiment, connector 14 includes a reservoir 28 in which a pump 30 is located. Pump 30 is the device that circulates the cooling fluid between the first heat exchanger 20 and the second heat exchanger 24. Second heat exchanger 22 is in fluid communication with reservoir 28 and pump 30 through a conduit portion 32. Pump 30 may cause pressure variations and resultant vibrations in the cooling fluid, as the cooling fluid is circulated between the first heat exchanger 20 and the second heat exchanger 22. In one embodiment, pump 30 also causes the cooling fluid to flow to the first heat exchanger 20 after passing through a damper 34. The cooling fluid is pumped from pump 30 to damper 34 through a conduit 36. The cooling fluid after leaving damper 34 is directed to the first heat exchanger 20 via a conduit 38. Conduit 26, 32, 36 and 38 may be tubes having a hollow portion through which the cooling fluid may circulate. Additionally, other fluid circuits are contemplated. Referring to FIG. 6 the cooling fluid may be directed from the first heat exchanger 20 to the reservoir 28 and/or pump 30 via return conduit 26 and then from the reservoir/pump to the second heat exchanger 22 via a conduit 76 after which the cooling fluid may be circulated to damper 34 via a conduit 78 prior to being returned to the first heat exchanger 20.

[0014] In one embodiment, heat exchanger 22, reservoir 28, pump 30 and damper 34 are all located within a housing 40 of connector 14. Damper 34 dampens, suppresses and/or ameliorates the transient and harmonic vibrations that are caused by the cooling fluid induced by pump 30 within the probe head 12. In one embodiment damper 40 is to be understood as a separate element rather than a portion of the conduit or fluid tubes such as a compliant section of a fluid tube on the high-pressure side of the pump. Damper 40 is also to be understood as a deliberate added structure as opposed to the fluid air boundary in a partially filled reservoir. Damper 40 may be secured to or adjacent to an outer surface of reservoir 28 or maybe constructed as part of housing 40.

[0015] Referring to FIG. 2, damper 40 includes an inlet port 42 and an outlet port 44. Inlet port 42 is operatively connected to conduit 36 to allow the cooling fluid from the pump to enter into damper 40. Outlet port 44 is operatively connected to conduit 38 that in turn is connected to first heat exchanger 20. In one embodiment damper 40 is located between the pump

and/or reservoir and the probe head 12. This placement reduces and/or eliminates the vibrations within the cooling fluid prior to entering the probe head. It is possible for damper 40 to be placed elsewhere in the cooling fluid flow circuit, such as between the pump and reservoir and or between the second heat exchanger and the pump or between the first heat exchanger and the second heat exchanger.

[0016] Referring to FIG. 2, the cooling fluid entering inlet port 42 has a laminar flow. As the cooling fluid circulates within the damper 40 the flow of the cooling fluid is turbulent as represented by the non laminar flow lines 48. The cooling fluid exits damper 40 through second inlet 44 with a laminar flow as the cooling fluid enters conduit 38 and is circulated to first heat exchanger 20.

[0017] Referring to FIG. 3 and FIG. 4, damper 40 has a membrane 50, a lower portion 52 and an upper portion 54. The lower portion 52 is provided with inlet port 42 and outlet port 44 that are used for the inlet and outlet of the cooling fluid. The lower portion 52 and the upper portion 54 have mating threads 56 and 58 respectively that engage each other to securely assemble damper 40. The lower member 52 is provided with a ledge 60 that supports the outer circumferential periphery of the membrane 50. When the threads 56 and 58 are fully engaged the peripheral edge of membrane 50 is captured between the ledge 60 and a bottom edge 62 of the upper portion 54 in such a way that a fluid tight hermetic seal is obtained. Cooling fluid introduced into the damper 40 via input port 42 is kept in a cavity 64 formed by the lower portion 52 and the membrane 50.

[0018] Membrane 50 may be formed of an elastomeric material such that when it is stretched by pressure variations in the cooling fluid it absorbs energy. The energy of displacing the membrane 50 upward vibrations within the cooling fluid is at least partially dissipated in internal friction inherent in its displacement. In one embodiment the membrane is a fluoropolymer rubber. In one embodiment the membrane is an elastomer with a Shore A hardness of about 75. In one embodiment the membrane has a thickness of about 1 mm. Of course other Shore A hardness values and membrane thicknesses are contemplated.

[0019] In one embodiment the upper portion 54 includes male threads that are threaded into the female threads 60 of lower portion 52. Membrane 50 being captured the upper portion 54 and lower portion 52 until significant resistance is met to create a fluid tight seal. In this manner the cooling fluid within cavity 64 does not migrate into the gas cavity 66 between the membrane 50 and upper portion 54.

[0020] In one embodiment the lower portion 52 may be formed of a metal such as aluminum. Of course other types of materials are contemplated. Lower portion includes openings through which fluid inlet port 42 and fluid outlet port 44 extend. In one embodiment ledge 60 of lower portion 52 has a width of about 2.5 cm. Cavity 64 is configured such that the cooling fluid has a laminar flow entering inlet port 42 and is converted to turbulent flow as the cooling fluid circulates within the cavity 64 and then is converted back to laminar flow as the cooling fluid exits outlet port 44 through conduit 38. In one embodiment cavity 64 has a cylindrical shape about 20 mm in diameter and about 2.7 mm in height. Of course other diameter and height dimensions are contemplated.

[0021] Inlet port 42 and outlet port 44 each have a longitudinal axis that extends through a center portion of inlet port 42 and outlet port 44 respectively. In one embodiment, the longitudinal axis of inlet port 42 is not collinear with the longi-

tudinal axis of outlet port 44. In one embodiment the longitudinal axis of inlet port intersects the longitudinal axis of the outlet port within cavity 64. The arrangement of inlet port 42, outlet port 44 and the geometry of damper 40 contribute to the turbulent flow of the cooling fluid within cavity 64. In one embodiment inlet port 42 and outlet port 44 are closely adjacent and extend from the arcuate outer circumference of the lower portion 52. In one embodiment the longitudinal axis of the inlet port and the longitudinal axis of the outlet port form an angle of about 20 degrees.

[0022] The gas within cavity 66 may be air or may be another gas to assist in the removal and minimization of vibrations within the cooling fluid as the cooling fluid is circulated to the probe head 12. Membrane 50 maybe substantially planar in a neutral position or may have an arcuate shape as illustrated in FIG. 3. The shape of membrane 50 may vary depending on the pressure within the cooling fluid circuit and/or the vibrations within the cooling fluid as the cooling fluid enters damper 40.

[0023] Lower portion 52 includes an outer arcuate side wall through which the inlet port 42 and outlet port 44 extend and a base floor. Ledge 60 is generally parallel to the plane defined by the base floor. Cavity 64 is defined by the inner surface of the side wall 68 and the inner surface of the base floor 70 as well as the lower or first surface of membrane 50. Similarly, cavity 66 is formed by the inner side wall 72 and the inner side of a cover portion 74 of upper portion 54 and the upper surface or second surface of membrane 50. In one embodiment cavity 66 simply contains the ambient air present when the lower portion 52 and the upper portion 54 are threaded together. In one embodiment cavity 66 is about 3.2 mm high and has a diameter of about 20 mm over most of its height. In one embodiment the upper portion 54 is constructed of a metal such as aluminum. However, other materials are also contemplated.

[0024] In one embodiment the longitudinal axis of inlet port 42 and outlet port 44 both lie in a common plane that is parallel to a plane defined by the ledge 60 and or base 70.

[0025] In one embodiment the damper is used in conjunction with a Doppler scan used to sense the movement of elements of a human body, such as flowing blood. The damper reduces the probability of artifacts caused by vibrations of the sensing head of probe head 12. In the case of sensing blood flow this reduces or eliminates the possibility of the scan incorrectly indicating reverse blood flow. In one embodiment damper 34 is used with pumps that have a vibrational frequency of around 50 Hz and dominant higher harmonics up to 200 Hz and scans sensing frequencies of greater than 50 Hz.

[0026] Although the present disclosure has been described with reference to example embodiments, workers skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the claimed subject matter. For example, although different example embodiments may have been described as including one or more features providing one or more benefits, it is contemplated that the described features may be interchanged with one another or alternatively be combined with one another in the described example embodiments or in other alternative embodiments. Because the technology of the present disclosure is relatively complex, not all changes in the technology are foreseeable. The present disclosure described with reference to the example embodiments and set forth in the following claims is manifestly intended to be as broad as possible. For example, unless specifically otherwise noted,

the claims reciting a single particular element also encompass a plurality of such particular elements.

What is claimed is:

1. A medical ultrasonic probe:
an ultrasonic probe having a probe head;
a connector including:
a fluid cooling system comprising:
a pump configured to pump a cooling fluid between the connector and the probe head;
a damper including a housing having a first portion defining a cavity receiving the cooling fluid and a second portion including a gas separated from the first portion by a membrane.
2. The medical ultrasonic probe of claim 1 wherein the membrane is an elastomeric material.
3. The medical ultrasonic probe of claim 2 wherein the elastomeric membrane is comprised of a fluoropolymer rubber.
4. The medical ultrasonic probe of claim 2 wherein the first portion of the housing includes an inlet for receiving the cooling fluid and a separate outlet for the cooling fluid to exit the housing, the inlet and outlet being non-colinear.
5. The ultrasonic probe of claim 4 wherein damper has a cylindrical shape with a circular side wall and two planer end walls, the membrane being mounted intermediate and generally parallel to the end walls in a first position.
6. The ultrasonic probe of claim 5 wherein the damper includes a first half shell threadably secured to a second half shell, a periphery of the membrane being captured between the juncture of the two half shells, hermetically sealing the first portion from the second portion.
7. The ultrasonic probe of claim 5 wherein the cooling fluid inlet and a cooling fluid outlet are adjacent one another in the circular sidewall of the first portion.
8. The ultrasonic probe of claim 7 wherein the inlet and outlet are closely adjacent to each other, each of the inlet and outlet having a longitudinal axis that intersect within the first portion of the damper.
9. The ultrasonic probe of claim 8 wherein the inlet and outlet both lie in a common plane which is parallel to the end walls of the chamber.
10. The ultrasonic probe of claim 4 wherein the pump pumps the cooling fluid having a laminar flow into the inlet, the first portion causing the flow of the cooling fluid to become turbulent within the first portion, the cooling fluid having a laminar flow as it exits the outlet.
11. The ultrasonic probe of claim 1, further including a cable connecting the probe head with the connector; the probe head including a first heat exchanger, the connector including a second heat exchanger, the first heat exchanger and second heat exchanger being in fluid communication with a first conduit extending through the cable, the pump being operatively connected to a reservoir and pumping the cooling fluid into the damper through the inlet into the first portion of the housing and out the outlet to the heat exchanger through a second conduit.
12. A vibration damper for an ultrasonic probe comprising:
a damper located within a connector of a portable medical ultrasonic probe, the damper forming an interior chamber;
an elastomeric membrane mounted in the chamber separating the chamber into a first compartment having a sealed air compartment and a second compartment having a fluid inlet port and a fluid outlet port for respectively receiving and releasing a cooling fluid.
13. The vibration damper of claim 12 wherein the chamber has a cylinder like shape with a circular side wall and two planer end walls, the membrane being mounted generally parallel to the end walls.
14. The vibration damper of claim 12 wherein the fluid flow within the first compartment between the fluid inlet port and the fluid outlet port is turbulent.
15. The vibration damper of claim 13 wherein the fluid ports comprise an inlet and an outlet that are closely adjacent to each other and lie in a common plane which is parallel to the end walls of the chamber, a longitudinal axis of the fluid inlet port and a longitudinal axis of the fluid outlet port are not collinear.
16. The vibration damper of claim 12 wherein the cooling elastomeric membrane is comprised of a fluoropolymer rubber.
17. The vibration damper of claim 12 wherein the first compartment of the chamber is designed to accept laminar flow cooling fluid at its inlet, cause the flow to become turbulent in the interior of the chamber and then to become laminar again at its outlet, the membrane and second compartment absorbs vibrations within the cooling fluid as it passes through the first compartment.
18. A process for providing fluid cooling to a medical ultrasonic probe comprising:
providing a medical ultrasonic probe having a probe head with a first heat exchanger;
providing a connector containing a cooling system connected to the medical ultrasonic probe by fluid lines and comprising:
a second heat exchanger;
a pump;
a damper which absorbs vibrations induced in a cooling fluid within by the operation of the pump; and
operating the pump to drive the cooling fluid through the damper, the first heat exchanger and the second heat exchanger through the fluid lines.
19. The process of claim 18 wherein the vibration damper comprises an elastomeric membrane, separating the damper into a first chamber receiving the cooling fluid therein and a second sealed chamber containing gas.
20. The process of claim 18 further including pumping the cooling fluid with a laminar flow from the pump into the first chamber through a fluid inlet, circulating the cooling fluid within the first chamber in a turbulent flow, absorbing the vibrations in the cooling fluid by the membrane and discharging the cooling fluid in a laminar flow from the first chamber to the first heat exchanger.

* * * * *

专利名称(译)	用于医用超声探头的阻尼器		
公开(公告)号	US20150182200A1	公开(公告)日	2015-07-02
申请号	US14/143235	申请日	2013-12-30
[标]申请(专利权)人(译)	通用电气公司		
申请(专利权)人(译)	通用电气公司		
当前申请(专利权)人(译)	通用电气公司		
[标]发明人	BIRGLEHNER ERICH RITTENSCHÖBER THOMAS		
发明人	BIRGLEHNER, ERICH RITTENSCHÖBER, THOMAS		
IPC分类号	A61B8/00		
CPC分类号	A61B8/546 A61B8/4483 A61B8/4444 G01S7/52079 G10K11/004		
其他公开文献	US10292686		
外部链接	Espacenet USPTO		

摘要(译)

医用超声波探头包括具有探头和连接器的超声波探头。该连接器包括流体冷却系统，该流体冷却系统包括泵，该泵构造在连接器和探头之间泵送冷却流体。包括壳体的阻尼器具有限定容纳冷却流体的腔的第一部分和包括通过膜与第一部分分离的气体的第二部分。

