



US009055910B2

(12) **United States Patent**
Nakajima

(10) **Patent No.:** **US 9,055,910 B2**
(45) **Date of Patent:** **Jun. 16, 2015**

(54) **ULTRASONIC DIAGNOSIS DEVICE**

(56) **References Cited**

(75) Inventor: **Shinji Nakajima**, Mitaka (JP)

U.S. PATENT DOCUMENTS

(73) Assignee: **HITACHI ALOKA MEDICAL, LTD.**,
Tokyo (JP)

4,625,731 A	12/1986	Quedens et al.
4,870,954 A	10/1989	Satoh
5,129,397 A	7/1992	Jingu et al.
5,867,148 A	2/1999	Kamimaki et al.
6,682,157 B2	1/2004	Ito
6,709,391 B2	3/2004	Mesaros et al.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 232 days.

(Continued)

(21) Appl. No.: **13/639,371**

FOREIGN PATENT DOCUMENTS

(22) PCT Filed: **May 25, 2011**

(86) PCT No.: **PCT/JP2011/062016**

CN	1655722 A	8/2005
CN	2814617 Y	9/2006

§ 371 (c)(1),

(2), (4) Date: **Oct. 4, 2012**

(Continued)

(87) PCT Pub. No.: **WO2011/148988**

PCT Pub. Date: **Dec. 1, 2011**

U.S. Non-Final Office Action dated Apr. 23, 2014, issued in related U.S. Appl. No. 13/639,355 (37 pages).

(Continued)

(65) **Prior Publication Data**

US 2013/0021732 A1 Jan. 24, 2013

(30) **Foreign Application Priority Data**

May 27, 2010 (JP) 2010-121433

Primary Examiner — Lisa Lea Edmonds

Assistant Examiner — Keith Depew

(74) Attorney, Agent, or Firm — Westerman, Hattori, Daniels & Adrian, LLP

(51) **Int. Cl.**

H05K 7/00 (2006.01)

A61B 8/00 (2006.01)

(52) **U.S. Cl.**

CPC **A61B 8/4405** (2013.01); **A61B 8/462**
(2013.01); **A61B 8/463** (2013.01); **A61B 8/54**
(2013.01)

(58) **Field of Classification Search**

CPC **A61B 8/462**


USPC 248/131, 133, 415, 424, 425, 188.2,
248/188.3, 592, 593, 595; D24/160, 186,
D24/234; 361/679.01

See application file for complete search history.

(57) **ABSTRACT**

The disclosed ultrasonic diagnosis device is provided with an attitude correction mechanism, between a tilt section and a display unit, for eliminating inclination of the display unit caused by drooping down of the end portion of an arm mechanism. The attitude correction mechanism has a shaft member and a bearing, and rotates the display unit about the normal of a display surface thereof. A prong enters a slit, thereby preventing the display unit from rotating more than necessary.

13 Claims, 25 Drawing Sheets



(56)

References Cited**U.S. PATENT DOCUMENTS**

6,746,402	B2	6/2004	Ustuner	
7,424,994	B2 *	9/2008	Jeong	248/278.1
7,594,728	B2	9/2009	Seal et al.	
7,775,485	B2 *	8/2010	Asai et al.	248/125.7
D626,236	S *	10/2010	Ninomiya et al.	D24/185
7,999,987	B2	8/2011	Namose	
8,201,791	B2 *	6/2012	Zhang et al.	248/278.1
8,310,468	B2 *	11/2012	Martin	345/204
8,348,845	B2 *	1/2013	Ninomiya et al.	600/437
8,474,835	B1 *	7/2013	Rossi	280/47.35
2002/0190609	A1	12/2002	Takeuchi et al.	
2003/0025054	A1	2/2003	Toennesland et al.	
2003/0220564	A1	11/2003	Wilkins et al.	
2003/0220565	A1	11/2003	Mesaros et al.	
2003/0220571	A1	11/2003	Mesaros et al.	
2004/0068185	A1 *	4/2004	Marshall et al.	600/437
2006/0238966	A1 *	10/2006	Sung	361/681
2006/0241435	A1 *	10/2006	Koga et al.	600/437
2007/0051861	A1	3/2007	Teramachi et al.	
2007/0067792	A1	3/2007	Kitagawa et al.	
2008/0115607	A1	5/2008	Chang et al.	
2008/0132786	A1	6/2008	Asai et al.	
2008/0228071	A1 *	9/2008	Mesaros	600/437
2008/0234577	A1 *	9/2008	Murkowski et al.	600/437
2009/0212133	A1	8/2009	Collins, Jr.	
2009/0223033	A1	9/2009	Houser	
2010/0094130	A1	4/2010	Ninomiya et al.	
2010/0152588	A1	6/2010	Ninomiya et al.	

FOREIGN PATENT DOCUMENTS

CN	1846629	A	10/2006
CN	1917815	A	2/2007
CN	101047038	A	10/2007
CN	101202123	A	6/2008
CN	100506165	C	7/2009
CN	100518661	C	7/2009
CN	101541246	A	9/2009
CN	201404228	Y	2/2010
EP	2092892	A1	8/2009
JP	63-009429	A	1/1988
JP	1-176407	U	12/1989
JP	03-109620	A	5/1991
JP	05-015529	A	1/1993
JP	06-090951	A	4/1994
JP	08-140970	A	6/1996
JP	2003-144433	A	5/2003
JP	2004-000624	A	1/2004
JP	2005-526566	A	9/2005
JP	2007-021088	A	2/2007
JP	2007-097775	A	4/2007
JP	2007097775	A *	4/2007
JP	2007-520304	A	7/2007
JP	2007-520305	A	7/2007
JP	2008-126015	A	6/2008
JP	2008-142331	A	6/2008
JP	2009-125371	A	6/2009
JP	2009-136692	A	6/2009
JP	2009-254725	A	11/2009

OTHER PUBLICATIONS

Notification of Transmittal of Translation of the International Preliminary Report on Patentability (Form PCT/IB/338) of International Patent Application No. PCT/JP2011/062016, dated Dec. 20, 2012, with Form PCT/IPEA/409.

Second and Supplementary Notice Informing the Applicant of the Communication of the International Application (Form PCT/IB/308) of International Patent Application No. PCT/JP2011/062016, dated Sep. 27, 2012.

Chinese Office Action dated May 6, 2014, issued in Chinese Patent Application No. 201180026317.7 with English translation (11 pages) (corresponding to U.S. Appl. No. 13/639,355).

Chinese Office Action dated Apr. 29, 2014, issued in Chinese Patent Application No. 201180026286.5 with English translation (11 pages) (corresponding to U.S. Appl. No. 13/639,307).

U.S. Non-Final Office Action dated Jun. 20, 2014, issued in related U.S. Appl. No. 13/639,307 (38 pages).

Extended Search Report dated Oct. 18, 2013, issued in European Patent Application No. 11786685.5 (5 pages).

International Search Report of PCT/JP2011/062016, mailing date of Jul. 12, 2011.

Notification Concerning Transmittal of International Preliminary Report on Patentability (Form PCT/IB/326) of related International Patent Application No. PCT/JP2011/062017 dated Dec. 6, 2012, with Forms PCT/IB/373 and PCT/ISA/237.

Notification of Transmittal of Translation of the International Preliminary Report on Patentability (Form PCT/IB/338) of related International Patent Application No. PCT/JP2011/062017 dated December 13, 2012, with Forms PCT/IB/373 and PCT/ISA/237.

Second and Supplementary Notice Informing the Applicant of the Communication of the International Application (Form PCT/IB/308) of related International Patent Application No. PCT/JP2011/062017, dated Sep. 27, 2012.

International Search Report dated Jul. 12, 2011, issued in related application No. PCT/JP2011/062015.

Notification of Transmittal of Translation of the International Preliminary Report on Patentability (Form PCT/IB/338) of related International Patent Application No. PCT/JP2011/062015, dated Dec. 13, 2012, with Forms PCT/IB/373 and PCT/ISA/237.

Notification Concerning Transmittal of International Preliminary Report on Patentability Form PCT/IB/326 of related International Patent Application No. PCT/JP2011/062015 dated Dec. 6, 2012, with Forms PCT/IB/373 and PCT/ISA/237.

Second and Supplementary Notice Informing the Applicant of the Communication of the International Application (Form PCT/IB/308) of related International Patent Application No. PCT/JP2011/062015 dated Sep. 27, 2012.

International Search Report dated Jul. 12, 2011, issued in related application No. PCT/JP2011/062014.

Notification of Transmittal of Translation of the International Preliminary Report on Patentability (Form PCT/IB/338) of related International Patent Application No. PCT/JP2011/062014, dated Dec. 13, 2012, with Forms PCT/IB/373 and PCT/ISA/237.

Notification Concerning Transmittal of International Preliminary Report on Patentability Form PCT/IB/326 of related International Patent Application No. PCT/JP2011/062014 dated Dec. 6, 2012, with Forms PCT/IB/373 and PCT/ISA/237.

Second and Supplementary Notice Informing the Applicant of the Communication of the International Application (Form PCT/IB/308) of related International Patent Application No. PCT/JP2011/062014, dated Sep. 27, 2012.

International Search Report of related PCT/JP2011/062017, mailing date of Jul. 12, 2011.

Extended European Search Report dated Mar. 6, 2013, issued in corresponding European Patent Application No. 11786688.9.

Chinese Office Action dated Jun. 4, 2014, issued corresponding in Chinese Patent Application No. 201180026310.5 with English translation (17 pages).

Chinese Office Action dated May 23, 2014, issued in Chinese Patent Application No. 201180026312.4 with English translation (16 pages) (this document is corresponding to U.S. Appl. No. 13/639,305).

* cited by examiner




FIG. 1





FIG. 2



3
G
F




FIG. 4

FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16





FIG. 17



8
1
G
E




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27

1

ULTRASONIC DIAGNOSIS DEVICE

TECHNICAL FIELD

The present invention relates to an ultrasonic diagnosis device, and more particularly to an arm mechanism (a support mechanism) that changes position and attitude of a display unit.

BACKGROUND ART

Ultrasonic diagnosis devices used in the field of medicine generally include a main unit (a cart), and an operation panel supported on the main unit. The main unit houses a plurality of electronic circuit boards and power source sections. The operation panel includes a switch, a pointing device, a rotary knob, a sub display, or the like. A display unit is mounted on the operation panel via an arm mechanism. In such a structure, the operation panel, the arm mechanism, and the display unit constitute a movable section. The display unit may be mounted directly on the main unit, rather than via the operation panel.

As disclosed in Patent Literature 1, an arm mechanism generally includes a plurality of pivot mechanisms and a plurality of arms. The arm mechanism further includes a tilt mechanism. A member having sufficient rigidity is used as each of the members forming the arm mechanism. Further, the arm mechanism is configured such that backlash is minimized in coupling portions between the members.

PRIOR ART DOCUMENTS

Patent Literatures

Patent Literature 1: JP 2007-21088 A

SUMMARY OF THE INVENTION

Problems to be Solved by the Invention

However, when the display unit is drawn far from the main unit, particularly in the left-right direction, accumulation of fine slip or displacement may, under certain circumstances, actually cause the lower edge and the upper edge of the display unit not to be horizontal and to be inclined, although the arm mechanism supports the display unit so as to put it in a vertical attitude. This is not because the display unit is rotated or inclined with respect to the end portion (the display unit attaching end portion) of the arm mechanism, but because, as a result of drooping of the end portion itself, the end portion can no longer take a horizontal attitude. Specifically, the display unit appears to be rotated about the normal line of the display surface. The above problems become noticeable when a large size display unit is used or when the arm mechanism is capable of forming a large extension distance. Even if the inclination of the display unit is approximately several degrees, this may make the user feel uncomfortable, uneasy, and unpleasant.

Here, there exist some types of PC display stands that enable the display unit to rotate by 90 degrees about a normal line that is vertical to the display surface; i.e. that can select a vertical attitude or a horizontal attitude. However, these devices are not aimed at maintaining intermediate angles or maintaining a slightly rotated state, nor do they enable the display unit to rotate in both directions. As the ultrasonic diagnosis devices are dedicated devices (i.e. as there is no need for displaying sentences on the display unit taking a

2

vertical attitude as in a word processing operation, for example), such a rotation function is not necessary in the first place and a rotation mechanism has not therefore been mounted on conventional display units.

An advantage of the present invention is to enable the display unit that is inclined due to the arm mechanism to return to an apparently correct attitude.

Solution to Problems

Preferably, an ultrasonic diagnosis device includes a display unit that displays an ultrasonic image, and an arm mechanism that is disposed on a base and supports the display unit, wherein the arm mechanism includes an arm mechanism main unit that is composed of at least one arm member and at least one pivot mechanism, and an attitude correction mechanism that is provided between the arm mechanism main unit and the display unit and, when an apparent rotation caused by drooping of an end portion of the arm mechanism main unit on the display side is generated in the display unit, rotates the display unit in the opposite direction so that the apparent rotation of the display unit can be eliminated.

With the above structure, when the end portion in the arm mechanism (arm mechanism main unit) on the display unit side droops down to a position below an originally expected position to generate an apparent rotation of the display unit (inclination of the display unit), it is possible to cause the display unit to rotate in a direction opposite the apparent rotation by the attitude correction mechanism to make the lower edge and the upper edge of the display unit (or a display surface) horizontal (or to make the right edge and left edge of the display surface vertical to a floor plane). It is therefore possible to eliminate uncomfortable or uneasy feeling. In considering it in a converse manner, if the arm mechanism originally has sufficient mechanical strength or rigidity, the problems resulting from drooping of the end portion can be solved or reduced. There is therefore no need for excessive strength or rigidity in the arm mechanism.

Preferably, the attitude correction mechanism includes a rotation shaft that is provided on one of the end portion on the display unit side and the display unit, a bearing portion that is provided on the other of the end portion on the display unit side and the display unit and is coupled with the rotation shaft, and a limitation portion that limits a rotation angle range of the display unit about the rotation shaft. This structure is aimed at supporting the display unit by an engagement relationship between the rotation shaft and the bearing, and rotating the display unit.

Preferably, the limitation portion includes a movable member that is provided on one of the end portion on the display unit side and the display unit, and a member that is provided on the other of the end portion on the display unit side and the display unit and limits a movable range of the movable member. As the attitude correction is intended for eliminating an inclination of approximately several degrees, for example, resulting from drooping of the end portion, a large rotation correction range is not required. By limiting the range, it is possible to perform fine adjustment easily and also to avoid adverse effects on other structures (a cable, for example) caused by rotating the display unit to a significant degree.

Preferably, a center line of the rotation shaft is provided in parallel with a normal line of a display surface of the display unit, and the center line of the rotation shaft passes a center line of a tilt shaft provided in the arm mechanism main unit such that the center line of the rotation shaft is orthogonal to the center line of the tilt shaft. With this structure, a tilt

movement and an attitude correction movement can be performed simultaneously in a simple manner.

Advantageous Effects of the Invention

According to the present invention, when the display unit is resultantly inclined due to the arm mechanism, it is possible to return the display unit to an apparently correct attitude.

BRIEF DESCRIPTION OF THE DRAWINGS

[FIG. 1]

First perspective view illustrating an ultrasonic diagnosis device according to an embodiment of the present invention.

[FIG. 2]

Second perspective view illustrating the ultrasonic diagnosis device according to the embodiment.

[FIG. 3]

Side view schematically illustrating a movable mechanism that changes the position and attitude of a movable section.

[FIG. 4]

Side view schematically illustrating a state in which the operation panel moves upward and forward.

[FIG. 5]

First exploded perspective view illustrating the movable mechanism as viewed obliquely from above.

[FIG. 6]

Second exploded perspective view illustrating the movable mechanism as viewed obliquely from below.

[FIG. 7]

Perspective view illustrating a left-right slide mechanism which is inverted.

[FIG. 8]

Perspective view illustrating a forward-backward slide mechanism.

[FIG. 9]

Perspective view illustrating a mechanism which locks the forward-backward sliding motion.

[FIG. 10]

Perspective view illustrating a brake mechanism which provides sliding resistance during a rotating motion.

[FIG. 11]

View for explaining a change in the range of a rotatable angle in accordance with a forward and backward sliding position.

[FIG. 12]

View illustrating operation examples of a rotation limit mechanism.

[FIG. 13]

Perspective view illustrating another embodiment of the rotation limit mechanism.

[FIG. 14]

Top view illustrating a first example state of an operation panel and a display unit.

[FIG. 15]

Top view illustrating a second example state of an operation panel and a display unit.

[FIG. 16]

Top view illustrating a third example state of an operation panel and a display unit.

[FIG. 17]

Cross sectional view illustrating a home position lock mechanism.

[FIG. 18]

Cross sectional view illustrating a shutter mechanism.

[FIG. 19]

Cross sectional view illustrating a lower part structure of the shutter mechanism.

[FIG. 20]

Cross sectional view illustrating an intermediate part structure of the shutter mechanism.

[FIG. 21]

Cross sectional view illustrating an upper part structure of the shutter mechanism.

[FIG. 22]

View for explaining the operation of the shutter mechanism.

[FIG. 23]

Cross sectional view illustrating a state of a display unit restraint mechanism before being actuated.

[FIG. 24]

Cross sectional view illustrating an actuated state of the display unit restraint mechanism.

[FIG. 25]

Partial cross sectional view illustrating an attitude correction mechanism.

[FIG. 26]

View for explaining an operation of the attitude correction mechanism.

[FIG. 27]

View for explaining inclination of the display unit due to drooping down of a motion end of an arm array.

MODE FOR CARRYING OUT THE INVENTION

Preferred embodiments of the present invention will now be described with reference to the drawings.

(1) Basic Structure of an Ultrasonic Diagnosis Device (FIGS. 1 to 4)

FIG. 1 illustrates a preferred embodiment of an ultrasonic diagnosis device according to the present invention. This ultrasonic diagnosis device, which is used in the field of medicine, performs transmission/reception of ultrasound with respect to a living organism (particularly, a human body) captures a received signal, and forms an ultrasonic image based on the received signal.

The ultrasonic diagnosis device 10 includes a main unit 12, a movable section 14, and a movable mechanism 16. The main unit 12 has a box shape and houses therein a plurality of electronic circuit boards and power source sections. The lower part of the main unit 12 protrudes slightly forward to form a main unit base 12A. Four casters 26 are provided under the main unit base 12A. The projection portion of the main unit base 12A functions as a footrest on which a foot is placed. The main unit 12 includes a front face 12B, a side face 12C, and a top face 12D. A rounded convex corner surface is formed from the front face 12B over to the top face 12D. A connector unit 28 formed of a plurality of main unit side connectors is provided on the front face 12B.

A probe is to be removably mounted to each main unit side connector. More specifically, a probe is composed of a probe connector (a connector box), a probe cable, and a probe head. The probe connector is mounted to one of the main unit side connectors. A support column, which will be described below, is provided on the main unit base 12A, and is covered with a column cover 30. The support column is provided on the front face side of the unit 12, in the center in the left-right direction. A handle 12E is provided on the backward end of the main unit 12.

As will be described below, the movable mechanism 16 includes a lifting mechanism, a left-right slide mechanism, a forward-backward slide mechanism, and a rotation mecha-

nism. The left-right slide mechanism, the forward-backward slide mechanism, and the rotation mechanism are provided in a layered structure and together form a horizontal movement mechanism. In FIG. 1, reference numeral 34 indicates a knob that constitutes a part of a home position lock mechanism.

In the present embodiment, the movable section 14 is composed of an operation panel 18, a base 20, an arm mechanism 22, and a display unit 24. The operation panel 18 is composed of a first operation section 36 and a second operation section 38 provided to rise from the back side of the first operation section 36. The first operation section 36 has a first operation surface, and the second operation section 38 has a second operation surface. A plurality of switches or the like are arranged on the first operation surface, and a sub display or the like is provided on the second operation surface. The angle of inclination of the second operation surface is larger than that of the first operation surface. A handle 18A is provided on the front side of the first operation section 36. This handle 18A also serves as a palm rest on which a wrist or a portion near the wrist is placed.

On the back side of the operation panel 18, the base 20 extending in the depth direction is provided, and the arm mechanism 22 is mounted on the base 20. The arm mechanism 22 is a mechanism for varying the position and attitude (orientation) of the display unit 24. The display unit 24 is formed as a flat panel display, and reference numeral 40 indicates a display unit main body. A handle 42 having an arc shape is provided on the lower portion on the front surface of the display unit main body 40. A user can hold the handle 42 to position the display unit 24 or direct the display unit 24 at a desired attitude. Further, by holding the handle 18A to move the handle 18A in the horizontal direction, the position of the movable section 14 in the left-right direction and the forward-backward direction can be determined and also the movable section 14 can be rotated about a predetermined rotation axis. Also, on the upper surface of an attachment end of the base 20, on the back side of the second operation section 38, a display unit restraint mechanism is provided.

FIG. 2 illustrates the ultrasonic diagnosis device illustrated in FIG. 1 as viewed obliquely from the back. As described above, the ultrasonic diagnosis device 10 includes the movable section which includes the operation panel 18, the base 20, the arm mechanism 22, and the display unit 24. The movable section is supported by the main unit 12. More specifically, the movable section is supported by the main unit 12 via the movable mechanism, which will be described below.

The arm mechanism 22 will be described in detail. On the backward end 20A of the base 20, a first pivot portion 44 is provided. One end of a first arm 46 is mounted on the first pivot portion 44, and a second pivot portion 48 is mounted on the other end of the first arm 46. An intermediate arm 50 which stands upright and has a short length is mounted on the second pivot portion 48, and an upper end of the intermediate arm 50 is coupled to one end of a second arm 52. The second arm 52 is an arm having parallel links capable of an inclined movement, and a third pivot portion 54 is provided on the other end of the second arm 52. Further, a tilt portion 56 is provided between the third pivot portion 54 and the display unit 24, and an attitude correction mechanism 58 which will be described below is provided between the tilt portion 56 and the display unit 24.

The first arm 46 is a horizontal arm, and the other end portion of the first arm 46 is warped slightly upward. In the arm mechanism 22, the elements from the first pivot portion 44 to the tilt portion 56 form an arm mechanism main unit, and the attitude correction mechanism 58 is provided further

to the arm mechanism main unit. As will be described below, the attitude correction mechanism 58 is a mechanism that cancels, when the end portion of the arm mechanism 22 on the display unit side droops down to make the display unit 24 appear to be inclined or rotated, such an inclination or rotation of the display unit 24.

FIG. 3 illustrates the principle of the movable mechanism 16. FIG. 3 illustrates a schematic structure, and the details of each mechanism will be illustrated in FIG. 5 and subsequent drawings. As described above, the main unit 12 includes the front face 12B and the top face 12D, and the rounded convex corner face 12F is formed from the front face 12B over to the top face 12D. The movable mechanism 16 has a lifting mechanism 60 and a horizontal movement mechanism 68. The horizontal movement mechanism 68 includes a left-right slide mechanism 62, a forward-backward slide mechanism 64, and a rotation mechanism 66. These mechanisms are stacked to form a layered structure, as described above.

The lifting mechanism 60 includes a support column formed of a fixed column 70 and a movable column 72. The movable column 72 is held by the fixed column 70 in a manner that the movable column 72 can move in the upward-downward direction. Reference numeral 73 indicates a holding member for this purpose. A movable base 74 that performs an up-down movement is coupled to an upper end portion 72A of the movable column 72. The movable base 74 is a horizontal plate that expands toward the forward direction from the upper end portion 72A.

The left-right slide mechanism 62 is mounted on the movable base 74. The left-right slide mechanism 62 includes a pair of rails 78 arranged in the front-back direction, and a pair of rail slots 76 that receive the rails 78 for allowing slide movement thereof in the left-right direction. Here, reference numeral 86 indicates the home position lock mechanism that includes a knob 34. The details of the home position lock mechanism 86 will be described below.

The forward-backward slide mechanism 64 includes a center case 79 having a bottom surface which is a left-right slide base. On the left-right slide base, a pair of rails 80 are arranged side by side in the left-right direction. A slider 82 is mounted on the pair of rails 80. The slider 82 constitutes a forward-backward slide base, on which the rotation mechanism 66 is mounted. Here, a rotation limitation mechanism which will be described below is provided between the left-right slide base and the operation panel 18. Further, a shutter mechanism 84 is provided for opening/closing an opening portion formed on the upper surface side of the center case 79, as will also be described in detail below. The rotation mechanism 66 is a mechanism that allows the operation panel 18; i.e. the movable section 14, to rotate about a rotation center axis 67. The rotation center axis 67 is specifically positioned at a sliding position in the left-right and forward-backward directions (a two-dimensional position), which is defined by the left-right slide mechanism 62 and the forward-backward slide mechanism 64.

As described above, the operation panel 18 includes the first operation section 36 and the second operation section 38, and also includes the handle 18A provided on the front surface side. On the bottom wall of the operation panel 18, a rotation member (rotor) of the rotation mechanism 66 is coupled. The base 20 includes an attachment portion 20B and a rear end portion 20A. The attachment portion 20B is coupled to the operation panel 18 at an intermediate location on the back surface side thereof, and the base 20 extends therefrom toward the depth side, with the end portion of the base 20 being the rear end portion 20A. A display unit restraint mechanism, which will be described below, is placed

on an upper surface 20D of the attachment portion 20B. The lower surface 20C of the base 20 is curved to have a concave shape as viewed from the side surface direction.

In FIG. 3, the movable section 14 is in a home position. More specifically, the movable section 14 is located at the lowermost end, the backward end, and the center position in the left-right direction, with the rotation angle being 0 degrees. In such a case, with respect to the rounded convex corner face 12F formed from the front face 12B over to the top face 12D of the main unit 12, the lower surface 20C, which is a similarly rounded concave curved surface, is in a close position. With such a positional relationship between these members, it is possible to avoid collision of the movable section 14 with the main unit 12 and also to position the operation panel 18 on the front face side of the main unit 12 at a lowest possible location.

In FIG. 3, the length from the rotation center axis 67 to the front end of the operation panel 18 is indicated as L1, and the length from the rotation center axis 67 to the rear end of the base 20 is indicated as L2. As illustrated, L2 is greater than L1. Accordingly, the operation panel 18 can be turned in a small radius even when the movable section is rotated, whereas with the rotation of the base 20 in a large radius, the region within which the display unit can move can be expanded. Here, the distance from the top face 12D to the lowermost position of the operation panel 18 is indicated as h1, and the distance from the top face 12D to the lower surface position of the movable base 74 is indicated as h2. In the present embodiment, because the lowermost position of the operation panel 18 can be lowered and also the thickness of the horizontal movement mechanism 68 is made small, as indicated by h1 and h2, it is possible to form a large space under the horizontal movement mechanism 68 at all occasions. As the support column and the movable base 74 form an inverted L shape as viewed from the side face, in combination with such a configuration, it is possible to form a sufficient space under the horizontal movement mechanism 68. The user's foot and the like can be placed in such a space.

As described above, the horizontal movement mechanism 68 has a layered structure. From this point of view, the movable base 74 forms the lowermost layer, the left-right slide base forms a lower layer, the forward-backward slide base forms an intermediate layer, and the rotation base forms an upper layer. Then, the bottom wall of the operation panel 18 forms the uppermost layer. In this embodiment, with such a layered structure being assumed as a precondition, rotation limitation or the like can be attained with a simple mechanism. This will be described below.

FIG. 4 illustrates the movable section 14 which is located at the lifted position and is also at the forward end. Here, the rotation angle of the movable section 14 is 0 degrees. The center case 79 houses therein the forward-backward slide mechanism 64 and the main portions of the rotation mechanism 66. A side case 88 is provided on each of the right and left sides of the center case 79. These side cases 88 cover right and left end portions of the left-right slide mechanism 62, and each side case 88 is specifically formed of an upper cover 88A and a lower cover 88B. The side cases 88 are fixed to the center case 79 and move in the left and right directions with the left-right movement of the center case 79. Here, it is possible to form the side cases 88 integrally with the center case 79.

The upper surface of the center case 79 is opened, and the center portion thereof serves as a passage for the rotation member in the rotation mechanism 66. When the movable section 14 is positioned at the forward end, a large opening portion 79A is to be exposed on the rear side of the operation

panel 18. However, such an exposure of the opening portion 79A would deteriorate the appearance and would also cause problems such as poor safety or entry of foreign matter. Accordingly, in the present embodiment, a shutter mechanism, which will be described below, is provided. By closing the opening portion 79A, which is exposed, with such a shutter mechanism 84, foreign matter externally entering as indicated by reference numeral 92 can be blocked. As the left-right slide mechanism 62 is covered with the side cases 88 as described above, this mechanism is also protected from an external force or the like, as indicated by reference numeral 90.

As described above, in the present embodiment, the various mechanisms are covered with the center case 79 and the side cases 88, which results in an increase in safety or the like. Further, the opening portion which is necessarily formed with the forward movement of the operation panel 18 can be specially closed by the shutter mechanism 84.

(2) Movable Mechanism (FIGS. 5 to 13)

Next, the movable mechanism will be described in detail with reference to FIGS. 5 and 6. First, FIG. 5 will be referenced.

As described above, the lifting mechanism 60 includes the support column 94 and the movable base 74. The support column 94 is composed of the fixed column 70 and the movable column 72. The left-right slide mechanism 62 includes the center case 79, and a pair of upper portions 88a forming a portion of the side cases are provided on the right and left sides of the center case 79. Lower portions of the side case are omitted in the drawing. The center case and the side cases together form a mechanism case. The bottom wall of the center case 79 is the left-right slide base 96.

The forward-backward slide mechanism 64 includes a pair of forward-backward slide rails 98 that are members extending in the forward-backward direction. A forward-backward slide base 100 is mounted on the pair of forward-backward slide rails 98. Specifically, the forward-backward slide base 100 is provided on a pair of forward-backward sliders 102 such that the forward-backward slide base 100 can move in the forward-backward direction. More specifically, on the left-right slide base 96, the pair of forward-backward slide rails 98 is fixed, and also a block 104 and a guide shaft 110 are fixed. The block 104 includes projecting portions 106 and 108, as will be described below. The projecting portions 106 and 108 are rollers that constitute a portion of the rotation limitation mechanism.

The rotation mechanism 66 includes a non-rotational base (stator) 112, a rotor (a rotational base serving as a rotor) 114, and a non-rotational gear 116. The rotor 114 performs a rotational movement about the rotation center axis and is coupled to a bottom wall 119 of the operation panel 18. The non-rotational base 112 and the non-rotational gear 116 are coupled integrally. The upper surface of the center case 79 is opened and serves as a space for movement of the assembly including the rotor 114. The shutter mechanism 84 is provided so as to close such an opening portion as required. While the shutter mechanism 84 is in a closed state in FIG. 5, the shutter mechanism 84 is placed in an opened state when the forward-backward slide base 100 is located at the backward end. When the forward-backward slide base 100 is located at the forward end, the shutter mechanism 84 is in a closed state as illustrated in FIG. 5.

The operation panel 18 includes a panel frame 118 having the bottom wall 119. The panel frame 118 includes a handle portion 118A on the front side thereof and also has a hollow interior. An opening portion 119A is formed in the bottom wall 119 slightly toward the backward side with respect to the

center thereof. The rotor **114** is attached to the opening portion **119A**, and the non-rotational gear **116** protrudes into the panel frame **118** via the opening portion **119A**.

The base **20** includes a rear end portion **20A** in which an opening portion **20E** for mounting the pivot mechanism and for passing a cable therethrough is formed. A passage **20F** serving as a slot is formed continuously to the opening portion **20E**, so as to allow a cable to be externally inserted into the rear end portion after the movable section is set onto the main unit.

In the hollow portion of the handle portion **118A**, a release lever **124** is disposed, and also cables **126** and **128** are also disposed as required. The release lever **124** is operated for releasing a lock state when the operation of the left-right slide mechanism **62** and the forward-backward slide mechanism **64** is in a stop state; i.e. in a lock state, in the present embodiment. The lock state is attained by holding the shaft member with a fixed force, and at this time, the lock state is attained by increasing the frictional resistance. A brake mechanism **120** is placed on the bottom wall **119** of the panel frame **118**, and engages the non-rotational gear **116** to exert a constant braking force with the rotation movement of the operation panel **18**. As the frictional resistance of the brake mechanism **120** is relatively large, the operation panel **18** is prevented from performing rotation movement by itself, even if an external force acts on the display unit to move the arm mechanism. The cable **122** performs a locking operation when the brake mechanism **120** functions as a lock mechanism.

FIG. **6** illustrates an exploded perspective view of the movable mechanism as viewed obliquely from below. As has been already described, from bottom to top, the left-right slide mechanism, the forward-backward slide mechanism, the rotation mechanism, and the operation panel are stacked. The left-right slide mechanism **62** will be described. The left-right slide base **96** is a horizontal plate, and a pair of left-right slide rails **130**, which are members extending in the left-right direction, are provided on the lower surface side thereof. A guide shaft **132** is attached to the left-right slide base **96**. Reference numeral **134** indicates a left-right slide lock mechanism, which holds the guide shaft **132** to thereby lock the slide movement in the left-right direction. Further, reference numeral **136** indicates a home position lock mechanism, which will be described below. Reference numeral **128** indicates a rail stand which is fixed to the movable base **74**. The left-right slide base **96** moves freely in the left-right direction on the rail stand **128**. On the left-right slide base **96**, the rotation mechanism moves freely in a sliding manner in the forward-backward direction by means of the forward-backward slide mechanism **64**.

On the bottom wall **119** of the operation panel, a frame body **140** projecting downward from the lower surface side thereof is formed. Specifically, the frame body **140** is formed on the bottom surface **119B**. The frame body **140** defines a movement region **142** for receiving a projecting portion pair **138** serving as a moving element and allowing the projecting portion pair **138** to move therein. The frame body **140** and the moving elements **138** serving as the projecting portion pair constitute a rotation limitation mechanism. The rotation limitation mechanism is a mechanism that variably sets the rotatable angle range in accordance with the sliding position of the operation panel in the forward-backward direction. In the present embodiment, the rotatable angle range is set to zero when the operation panel is located at the backward end, and the rotatable angle range gradually increases towards the forward end. In order to define such a change, the frame body **140** has a left-right width that gradually widens from the front side toward the rear side thereof. Here, FIG. **6** also illustrates

the shutter mechanism **84** in its closed position. When the forward-backward slide base is located at the backward end on the forward-backward slide mechanism **64**, the shutter mechanism **84** is in an opened state as described above. The bottom wall **119** includes the opening portion **119A** formed therein, into which a portion of the rotor **114** is inserted.

Next, with reference to FIGS. **7** to **11**, each of the mechanisms described above will be individually described.

FIG. **7** illustrates the left-right slide mechanism **62**, although the left-right slide base **96** is illustrated as being inverted. On the lower surface side of the left-right slide base **96**, the pair of left-right slide rails **130** is provided as described above. The pair of left-right slide rails **130** are provided at a fixed interval in the front-rear direction. The pair of slide rails **130** engage the rail stand **128** such that the left-right slide base **96** is movable with respect to the rail stand **128** in the left-right direction. The left-right slide lock mechanism **134** is mounted on the rail stand **128**. The left-right slide lock mechanism **134** is a mechanism that locks the slide movement in the left-right direction by holding the guide shaft **132**. The operation force of the left-right slide lock mechanism **134** is applied by a cable **136**, a spring, or the like. Actually, a release force is applied by the cable **136**. The left-right slide lock mechanism **134** includes a slide block **138** for holding the guide shaft **132**, and the slide block **138** includes, on the front surface side thereof, an engagement surface **139**. The engagement surface **139** has an engagement hole that receives a horizontal pin provided in the home position lock mechanism. The surfaces on the right and left sides of the engagement hole are slanted.

FIG. **8** illustrates the forward-backward slide mechanism **64**. The forward-backward slide mechanism **64** includes a pair of forward-backward slide rails **98** which are provided in the left-right direction at a fixed distance. The forward-backward slide mechanism **64** further includes a guide shaft **110**. A block **104**, which is provided on the front end side of the guide shaft **110**, is fixed to the left-right slide base. On the forward-backward slide rails **98**, the forward-backward slide base **100**, which is movable in the forward-backward direction, is mounted via a pair of sliders **142**. The non-rotational base **112** is mounted on the forward-backward base **100**. The non-rotational base **112** includes a hollow portion formed in the center portion, in which the forward-backward slide lock mechanism **144** is disposed. As illustrated in FIG. **9**, the forward-backward slide lock mechanism **144** is a mechanism that locks a slide movement in the forward-backward direction by holding the guide shaft **110**. The cable **146** or a spring mechanism is provided for applying such an operation force. More specifically, the cable **146** transmits a release force.

Referring back to FIG. **8**, on the forward-backward slide base **100**, a pair of slide pins **220** are formed at a fixed distance in the left-right direction so as to project therefrom. Each slide pin **220**, which is a member projecting upward, constitutes an important element of the shutter mechanism. Specifically, when the forward-backward slide base **100** moves in the forward-backward direction, the pair of slide pins **220** also move in the forward-backward direction accordingly, such that the pair of slide pins **220** operate in accordance with the sliding position in the forward-backward direction to thereby determine the degree of opening of the shutter plate, as will be described below.

FIG. **10** illustrates an example of the brake mechanism **120**. The rotor **114** is coupled to the bottom wall in a fixed manner. As such, the operation panel can rotate freely with the rotor **114**. A pair of racks; i.e. a first rack **148** and a second rack **150**, engage with the non-rotational gear **116**. The second rack **150** is held by the block **151** such that the second rack **150** can

move in the axial direction. A guide shaft **154** is coupled to the second rack **150** via a pair of arm members **152**, and a pair of sliders **156** are provided on the guide shaft **154**. The first rack **148** is fixed to these sliders **156**. A grip portion **158** is provided at the center portion of the guide shaft **154** and is fixed to the first rack **148**.

When the operation panel rotates, the first rack **148** and the second rack **150** that are engaged with the non-rotational gear **116** move in a sliding manner in opposite directions. In this case, the guide shaft **154** also moves in a sliding manner with respect to the grip portion **158**. By exerting a predetermined brake force on the grip portion **158**, the sliding movement of the guide shaft **154** is restricted; specifically, the brake force acts on the rotation movement of the operation panel. Although the cable **122** is used to control the operation of the grip portion **158**, this cable **122** is not necessary if the brake force is continuously exerted on the grip portion **158**. Further, a single rack may be provided, rather than two racks.

FIG. 11 illustrates the release lever **124**. The release lever **124** is a member which is operated by a user to release (an unlock operation) the plurality of lock mechanisms collectively. Specifically, wires **160** and **162** are wound around the rotational shaft of the release lever **124** via a guide **164**, and a wire **166** is similarly wound around the rotational shaft of the release lever **124** via a guide **168**. Accordingly, by holding the release lever **124**, it is possible to place the three lock mechanisms into a released state simultaneously. In the present embodiment, however, as a brake force continuously acts on the rotation mechanism, the release mechanism actually functions only on the left-right slide mechanism and the forward-backward slide mechanism. More specifically, only two wires are actually wound around the rotational shaft of the release lever **124**. As a matter of course, the release lever **124** can be operated to perform a lock operation. In any case, such a structure, in which it is possible to achieve a plurality of lock (unlock) operations by a single action, is simple and can provide good operability.

FIG. 12 illustrates an operation of the rotation limitation mechanism. FIG. 12(A) illustrates a state in which the operation panel is at the backward end; FIG. 12(B) illustrates a state in which the operation panel is at the center position in the forward-backward direction; and FIG. 12(C) illustrates a state in which the operation panel is at the forward end. In FIG. 12, the left side corresponds to the front side of the operation panel and the right side corresponds to the rear side of the operation panel. Reference numeral **67** indicates a rotation center axis.

In FIG. 12(A), the frame body **140** defines a movement region **142** of a moving element **138**. More specifically, the frame body **140** is formed by a regulation wall **170**. In the movement region **142**, the width d in the left-right direction gradually increases from the front side toward the rear side. Reference numeral **142A** indicates a front side position, reference numeral **142B** indicates an intermediate position, and a reference numeral **142C** indicates a rear side position. In FIG. 12(A), the moving element **138** is positioned at the forward end of the movement region **142**, and is not in a state in which the movement element can move in the left-right direction. At such a home position, the rotational movement of the operation panel is inhibited. In other words, the rotatable angle range is zero. As such, because the rotational movement of the operation panel is restricted when the operation panel is at the backward end, it is possible to avoid the problem that the movable section collides with the main unit.

In FIG. 12(B), the moving element **138** is at the intermediate position; i.e., the operation panel is drawn toward the front side to the intermediate position. In such a state, the

moving element **138** can move over a predetermined range in the left-right direction; more specifically, can move along an arc. In FIG. 12(C), the operation panel is drawn to the forward end, and in this state, the moving element **138** can move maximally in the left-right direction; more specifically, in the arc direction, and a large rotatable angle range is set.

As described above, with the rotation limitation mechanism, it is possible to adaptively set the rotatable angle range in accordance with the sliding position of the operation panel in the forward-backward direction. Accordingly, there can be obtained the advantage that the angle range which is appropriate for the sliding position can be set while avoiding collision between the movable section and the main unit. In particular, as a very large rotation is permitted when the operation panel is located at the forward end or near the forward end, the advantage of significantly improved usability can be achieved.

FIG. 13 illustrates another embodiment of the rotation limitation mechanism. On a left-right slide base **172**, a single forward-backward slide rail **176** is provided, and two guide shafts **178** are provided via a predetermined member. On the forward-backward slide rail **176**, a forward-backward slide base **174** is mounted. Further, a frame body **186** which defines a movement region of a contact element **182** is mounted on the left-right slide base **172**. The width of the frame body **186** in the left-right direction is increased from the rear side toward the front side. Specifically, the change of size in the frame body **186** is opposite that of the frame body illustrated in FIG. 12.

The contact element **182** described above is mounted on a rotator; i.e., a rotation base **180**, via a coupling shaft **184**. FIG. 13 illustrates a state in which the operation panel is located at the backward end, in which state the contact element **182** is located at the rearmost position, and the movement of the contact element **182** in the left-right direction is completely restricted by the frame body **186**. In other words, at such a home position, the rotation movement of the operation panel is inhibited. With the sliding movement of the operation panel in the forward direction, movement of the contact element **182** in the left-right direction is permitted. Specifically, the rotation of the operation panel is allowed in accordance with the left-right width of the frame body **186**.

(3) Setting Examples (FIGS. 14 to 16)

Next, various setting examples will be described with reference to FIGS. 14 to 16. Referring to FIG. 14, the handle **18A** is provided on the front side of the operation panel **18**. The user can move the movable section **14** while holding the handle **18A**, thereby setting the position and attitude of the operation panel **18** as desired. Further, the handle **42** is provided on the display unit **24**, and the display unit **24** can be set to a desired position and attitude by moving the display unit **24** while holding the handle **42**. As described above, the movable mechanism which supports the movable section **14** is normally in a locked state or in a state in which a friction is exerted, and the arm mechanism is also in such a locked state. However, because, in the present embodiment, the brake force in the movable mechanism is set to be always greater than the brake force in the arm mechanism, it is possible to prevent the movable section **14** from moving by itself when the display unit **24** is moved.

In FIG. 14, the operation panel **18** is located at the center position in the left-right direction and at the backward end in the forward-backward direction. The pivot angle of the operation panel in this state is set to 0 degrees. In other words, the operation panel **18** is located at the home position. Meanwhile, due to the action of the arm mechanism **22**, the display unit **24** is drawn to the position above the operation panel **18**.

FIG. 15 illustrates a state in which the movable section is slid to the left direction from the state illustrated in FIG. 14. Further, FIG. 16 illustrates a state in which the operation panel 18 is further drawn in the forward direction and to the right direction from the state of the operation panel 18 as illustrated in FIG. 14 and is then further pivoted counterclockwise. In another example, by positioning the operation panel at the right end and forward end and then pivoting the operation panel 18 clockwise, even when a user, who is located a certain distance from the main unit, takes a slanted posture with respect to the main unit, it is possible to position the operation panel right in front of the user and further direct the operation panel toward the user. Also, in the present embodiment, it is possible to move the display unit in back of the main unit and further direct the display unit toward the rear side. It is also possible to locate the display unit to the right side of the main unit and then lower and position the display unit near the head of the user lying in a bed. As such, in the present embodiment, as the base extends in the depth direction and the arms in the arm mechanism have a certain degree of length, the movable region of the display unit 24 is significantly large.

(4) Home Position Lock Mechanism (FIG. 17)

With reference to FIG. 17, the home position lock mechanism 136 will be described. The home position lock mechanism 136 is a mechanism which inhibits the slide movement in both the left-right direction and the forward-backward direction when the operation panel; i.e., the movable section, is at a home position. In this state, the operation panel is prohibited from moving by merely gripping the release lever 124.

The knob 34 is connected to a shaft 188, and with the rotation of the knob 34, the shaft 188 rotates, which further causes a cam member 190 to rotate. Here, the cam member 190 and the peripheral structure thereof are illustrated in a simplified manner. With the action of the cam member 190, a horizontal pin 192 is driven forward. The horizontal pin 192 is urged forward by a spring 196. Stated conversely, the horizontal pin 192 is capable of retreating movement over a predetermined distance.

On the movable base, the slide block 138 is provided. The slide block 138 has, as a front surface, an engagement surface 139 having an engagement hole 194. The right and left sides of the engagement hole 194 are formed as slope surfaces. Accordingly, if, in a state in which the horizontal pin 192 projects, the left-right slide base 96 moves horizontally to reach the center position, the leading end portion of the horizontal pin 192 ascends the slope surface formed on the engagement surface 139 and finally comes into the engagement hole 194. In this state, the movement of the left-right slide base 96 in the left-right direction is prohibited; i.e., the left-right slide base 96 is placed into a locked state in the left-right direction.

On the other hand, with the rotation movement of the shaft 188, a member 198 extending in the vertical direction is thrust upward to thereby thrust a first vertical pin 202 and a second vertical pin 206 upward. However, a spring 204 is interposed between the first vertical pin 202 and the second vertical pin 206, and the second vertical pin 206 is urged upward with respect to the first vertical pin 202. As such, a structure which extends through a block 104 in the up-down direction is formed in the block 104, and the thrust-up force of the first vertical pin 202 is applied to the second vertical pin 206 via the spring 204. The upper portion of the second vertical pin 206 is formed as a thrust portion 108, which is a roller. As described above, the frame body 140 defines a movement space of the thrust portion 108 and includes a recess portion

142a formed at a position corresponding to the home position. The recess portion 142a is a hollow and therefore has a shape which is retracted upward with respect to the bottom surface 119B. Accordingly, when the knob 34 is operated, an upward urging force is continuously applied to the thrust portion 108, so that the thrust portion 108 moves horizontally while remaining in contact with the bottom surface 119B. Then, when the thrust portion 108 is fitted into the recess portion 142a, the horizontal movement of the thrust portion 108 is inhibited; specifically, the bottom wall 119 is fixed with respect to the left-right slide base 96. In this state, the slide movement in the forward-backward direction and the rotation movement are inhibited. As such, it is possible to lock the left-right movement, the forward-backward movement, and also the rotation movement by simply operating the knob 34. In addition, the operation of the knob 34 can be performed at positions other than the center position or the forward end position, and when the center position is achieved in the slide movement, a lock state is automatically formed, and also when the rotation angle becomes 0 degrees at the backward end position, a lock state in the forward-backward direction and the rotation direction can be automatically formed. In the present embodiment, by using the layered relationship to exert an acting force through a plurality of layers as described above, the integral lock mechanism can be achieved.

(5) Shutter Mechanism (FIGS. 18 to 22)

Next, with reference to FIGS. 18 to 22 the shutter mechanism will be described in detail. Referring to FIG. 18, the pair of forward-backward slide rails 98 are provided on the left-right slide base 96, and the forward-backward slide base 100 is mounted on these forward-backward slide rails 98. In FIG. 18, the forward-backward slide base 100 is at the forward end. On the forward-backward slide base 100, the rotor 114 is rotatably mounted, and the non-rotational gear 116 is further provided. The rotor 114 is fitted into an annular base 119B formed in the bottom wall 119, and is integrated with the bottom wall 119 in such a fitted state. The non-rotational gear 116 enters the panel frame via the opening portion 119A. Only a slight gap is present between the forward-backward slide base 100 and the bottom wall 119, and in the present embodiment, the shutter mechanism 84 is disposed in such a gap. The shutter mechanism 84 may be coupled with the left-right slide base 96 or placed within the center case. The shutter mechanism 84 includes a pair of lower plates 208, a pair of first shutter plates 210, a pair of second shutter plates 212, and a pair of upper plates 214. Each of the plates 208, 210, 212, and 214 is a thin sheet-like member which is formed of a resin having a black color, for example. Each plate is desirably formed of an opaque member.

On the pair of lower plates 208, a pair of rotational shafts 218 are spaced at an interval in the left-right direction. Each rotational shaft 218 functions as a rotational shaft for the respective first shutter plate 210 and second shutter plate 212. The pair of rotational shafts 218 and the pair of upper plates 214 may be coupled in a fixed manner. Each of the pair of lower plates 208, the pair of first shutter plates 210, and the pair of second shutter plates 212 has a single pin slot formed therein as will be described below, and a slide pin 220 is inserted in each pin slot. A pair of slide pins 220 are provided at a distance in the left-right direction on the forward-backward slide base 100, and perform a slide movement with the forward-backward slide movement of the forward-backward slide base 100. Meanwhile, the pair of rotational shafts 218 do not slide in the forward-backward direction, although the pair of rotational shafts 218 slide in the left-right direction with the movement of the slide base 96. As indicated by reference numeral 216, the opening in the upper portion of the main

15

case serves as a movement space for the rotor **114**; specifically, an exposed opening portion is uncovered on the rear side of the operation panel, and this leads to a problem that the internal mechanisms are exposed through such an opening portion as indicated by reference numeral **216**. The shutter mechanism is a mechanism which conceals such an opening portion with the slide movement of the operation panel in the forward-backward direction.

FIG. **19** illustrates the pair of lower plates **208**. In FIG. **19**, the upper side corresponds to the front direction of the operation panel and the lower side corresponds to the rear side of the operation panel. In FIG. **19**, the forward-backward slide base **100** is at the forward end. Each lower plate **208** includes a linear pin slot **222**. The pair of slide pins **220** spaced in the left-right direction are provided on the forward-backward slide base **100**. In addition, a pair of rotational shafts **218** are provided as fixed shafts.

FIG. **20** illustrates a pair of the first shutter plates **210**. Each first shutter plate **210** performs rotational movement about the rotational shaft **218**. A pin slot **224** is formed in each of the first shutter plates **210**. Each pin slot **224** has a bent shape including a linear portion and a portion directed inwardly therefrom as illustrated in FIG. **20**. In FIG. **20**, the pair of the first shutter plates **210** are in a closed state. The pair of first shutter plates **210** in an opened state are indicated by reference numeral **210A**. The pair of first shutter plates **210** serve to conceal especially the back area in the exposed space portion.

FIG. **21** illustrates a pair of second shutter plates **212**. Each second shutter plate **212** performs a rotational movement about the rotational shaft **218**. In the state illustrated in FIG. **21**, a pin slot **226** is formed of an inwardly directed portion and a straight portion. In other words, the pin slot **226** has a bent shape. In FIG. **22**, the pair of second shutter plates **212** are in a closed state. The pair of first shutter plates **212** in an opened state are indicated by reference numeral **212A**. The pair of second shutter plates **212** serve to conceal the portion of the exposed opening portion from the intermediate area to the rear area.

Next, with reference to FIG. **22**, the operation of the shutter mechanism will be described. FIG. **22(A)** illustrates a state in which the forward-backward slide base **100** is at the backward end; FIG. **22(B)** illustrates a state in which the forward-backward slide base **100** is at the intermediate position; and FIG. **22(C)** illustrates a state in which the forward-backward slide base **100** is at the forward end. First, in the state illustrated in (A), all the shutter plates are in the opened state. Specifically, because the operation panel is located at the backward end and the opening portion is covered by the operation panel located above, the problem of exposure of the opening portion does not arise. Here, a passage of the rotational shaft member is formed between the two layered members provided on the left and right sides, and this passage forms the exposed opening portion at the rear portion of the moving rotational shaft member.

In FIG. **22(B)**, the operation panel is at the intermediate position, and in such a state, only the pair of first shutter plates **210** is placed in the closed state and the exposed opening portion formed on the rear side of the rotational shaft member is partially covered. In the state illustrated in FIG. **22(C)**, the operation panel is at the forward end, and a large exposed opening portion is formed on the back of the rotational shaft member. By placing the pair of second shutter plates **212** into the closed state, such an exposed opening portion is substantially covered. More specifically, when the operation panel moves from the backward end to the forward end, the pair of first shutter plates first start the closing movement, and sub-

16

sequently the pair of second shutter plates start the closing movement. As such, by shifting the operation times for the two shutter plate pairs located at the upper and lower levels and also by allocating separate areas to be covered to these shutter plate pairs, even when a relatively large exposed opening portion is generated, such an opening portion can be concealed effectively and rapidly.

In the shutter mechanism described above, the pin slot is formed in each shutter plate, and the slide pin moves within the pin slot. The contact relationship between the pin slot and the slide pin changes depending on the lateral displacement of the pin slot; i.e., the shape of the pin slot, resulting in generation of a rotational force of the shutter plates. In the present embodiment, by employing the double shutter plates which are vertically layered and allowing these shutter plates to operate stepwise, and also by separating the areas covered by these shutter plates in the forward-backward direction, it is possible to conceal the exposed opening at an appropriate timing with the movement of the rotational shaft member and also to exert the concealing effect over the whole opening portion even if the opening portion to be concealed is large.

The pair of cover plates described above may be provided as required. Providing such a pair of cover plates can provide an advantage of enabling smooth movement of the shutter plates and also allowing physical protection of the shutter plates. In the present embodiment, because the two shutter plates are sandwiched by pairs of plates located above and below these shutter plates, it is possible to enable the two shutter plates to move smoothly in the horizontal direction. As the shutter mechanism of the present embodiment is configured to have the layered plate structure as described above, it is possible to reduce the overall thickness of the shutter mechanism to be significantly thin, which results in the advantage that the thickness of the horizontal movement mechanism can be reduced.

(6) Display Unit Restraint Mechanism (FIGS. **23** and **24**)

Next, with reference to FIGS. **23** and **24**, the display unit restraint mechanism will be described. Referring to FIG. **23**, the operation panel **18** includes the second operation section **38**, the upper end portion **38A** of which is illustrated in an enlarged view in FIG. **23**. Meanwhile, the base **20** is coupled to the back surface side of the operation panel **18**, and FIG. **23** illustrates the attachment end of the base **20**. A display unit restraint mechanism **228** is provided in a gap having a triangular cross section which is sandwiched by the top face front end **20D** of the base **20** and the back surface **38B** of the upper end portion **38A**.

The display unit restraint mechanism **228** is a mechanism which holds the handle **42** provided to the display unit to restrain the display unit itself during transportation of the device or the like. The display unit restraint mechanism **228** includes a fixed portion **230** and a rotation portion **232**. The fixed portion **230** includes a catch member **236** forming a receiving groove **234**. The catch member **236** has an opening which is opened toward the upward direction, which functions as a receiving port of the handle **42**.

The rotation portion **232** is capable of rotational movement about a predetermined rotation center axis. The rotation portion **232** includes a cover portion **240** serving as a forward end on the rotation side. The surface of the cover portion **240** on the outer side is curved outward and bent, where a catching surface **240A** is formed. By catching the catching surface **240A** by finger tips to cause the cover portion **240** to move, it is possible to rotate the entire rotation portion **232**.

The rotation portion **232** includes a hook member **242** which performs a rotation movement about a fixed axis **244**. A spring **248** applies an urging force to the hook member **242**

in a direction in which the hook member 242 rises up. The outer surface of the hook member 242 is a saw-toothed uneven surface 242A having projections and depressions, and a fixing pin 246 is in contact with the uneven surface 242A in the state illustrated in FIG. 23. As the urging force toward the outside acts on the hook member 242 by the spring 248, the fixing pin 246 fits into the depression of the uneven surface 242A, and, when the rotational section 232 is rotated, a consecutive click feeling can be obtained. Meanwhile, the upper end portion 38A includes a cut-out portion in which a hook slot 250 is formed. Further, the rotation portion 232 is held so as to prevent the rotation portion 232 from popping out of the position illustrated in FIG. 23 easily.

FIG. 23 illustrates an unactuated state of the display unit restraint mechanism 228. Meanwhile, FIG. 24 illustrates an actuated state of the display unit restraint mechanism 228. In FIG. 24, a handle main unit 42A fits into the receiving groove 234. The handle main unit 42A is a rod-like member extending in the horizontal direction. The cover portion 240 of the rotation portion 232 covers over the handle main unit 42A, so that the upward movement of the handle main unit 42A is restricted by the cover portion 240. Specifically, by cooperation of the fixed portion and the rotation portion 232, the handle main unit 42A is held firmly.

In a state in which the rotation portion 232 is rotated clockwise as illustrated in FIG. 24, the rising movement of the hook member 242 is permitted to thereby allow the leading end 236A thereof to be fitted into the hook slot 250. Specifically, in the housed state in which the rotation portion 232 is rotated counterclockwise, rise of the hook member 242 is inhibited by the pin or other structures, whereas by rotating the rotation portion 232 clockwise, a free movement of the hook member 242 is permitted so that the hook member 242 can rise by the action of the spring 248. In this case, the hook member 242 functions as a strut between the main unit of the rotation portion 232 and the operation panel to inhibit counterclockwise rotation of the rotation portion 232. Then, by pushing the outer surface of the hook member 242 to place the hook member 242 in a fallen state, it is possible to rotate the rotational member 232 counterclockwise to thereby restore the display restraint mechanism 228 in the unactuated state. In this state, it is possible to pull the handle main unit 32A upward out of the receiving groove 234. Here, while in the state in which the display unit is restrained, the display unit is in a substantially vertical state, the display unit may be slightly inclined forward.

In the present embodiment, as the display unit restraint mechanism 228 is disposed in a triangular gap space at the back side of the operation panel, there can be achieved advantages that the dead space can be effectively used and that the display unit restraint mechanism 228 can be placed out of sight of the user who is sitting so as to make the appearance of the device preferable. As a matter of course, when the user is standing, it is possible for the user to visually recognize the display unit restraint mechanism 228, and it is also easy to insert the user's hand into the triangular gap space.

(7) Attitude Correction Mechanism (FIGS. 25 to 27)

Next, the attitude correction mechanism will be described with reference to FIGS. 25 to 27. FIG. 25 illustrates a portion of the arm mechanism 22; more specifically, schematically illustrates the second arm 52 and the third pivot portion 54. Reference numeral 252 indicates a pivot center axis in the third pivot portion 54. The tilt portion 56 is coupled to the third pivot portion 54. The tilt portion 56 is disposed within the cover 254 and includes a tilt axis 254 as a horizontal axis. A fitting 256 is coupled to the tilt axis 254. A slot 256A is formed on the lower side of the fitting 256, and a side prong

258 coupled to the third pivot portion 54 is placed within the slot 256A. As such, due to the contact relationship between the slot 256A and the side prong 258, a limitation is imposed on the maximum tilt rotational angle in the tilt portion 56.

The attitude correction mechanism 58 is illustrated between the tilt portion 56 and the display unit 24. The attitude correction mechanism 58 includes a shaft member 262 provided on the front plate of the fitting 256. The shaft member 262 is coupled to a frame 264 provided within the case 263 of the display unit 24. Reference numeral 268 indicates a correction movement center axis. Due to the engaging relationship between the shaft member 262 and a bearing 266, the display unit 24 can perform rotational movement in both directions about the correction movement center axis 268 with the maximum angle being ± 5 degrees, for example. Such a correction rotation range can be determined arbitrarily. In the present embodiment, as will be described in detail below, because the attitude correction mechanism 58 is provided in order to eliminate an apparent rotation of the display unit 24 resulting from drooping of the end portion of the arm mechanism, the maximum correction angle is desirably selected to be within a range of ± 2 to ± 20 degrees, and more desirably within a range of ± 2 to ± 10 degrees. As it becomes difficult to protect the interior members if too large a rotational movement is permitted, such a degree of the correction angle range as described above is desirable. However, a ± 90 degrees rotational mechanism may be provided. The frame 264 includes an arc-shape slit 264A extending in the left-right direction formed therein, and a forward prong 260 which is a portion of the fitting 256 is inserted in the slit 264A. Specifically, with the relative rotational movement of the display unit 24, the forward prong 260 moves in the left-right direction within the slit 264A, and further rotation of the display unit 24 is inhibited when the forward prong 260 reaches the left and right ends of the slit 264A.

In the structure illustrated in FIG. 25, as the correction movement center axis 268 passes through the horizontal tilt center axis of the tilt axis 254, the correction movement center axis 268 and the tilt axis 254 are in an orthogonal relationship. With such a structure, it is easy to hold the display unit 24 with both hands to allow the display unit 24 to perform the tilt movement and the rotation movement simultaneously. In the present embodiment, the attitude correction mechanism 58 is provided as a portion of the arm mechanism 22. More specifically, the attitude correction mechanism 58 is provided in order to solve the problem of an apparent rotation of the display unit caused by the arm mechanism main unit in the arm mechanism 22.

FIG. 26 illustrates an action of the attitude correction mechanism. Reference numeral 262 indicates the shaft member, and FIG. 26 further illustrates a fitting relationship between the slit 264A having an arc shape and the forward prong 260. Reference numeral 24 indicates the display unit, and in the present embodiment, it is possible to cause the display unit 24 to rotate in both the clockwise and counterclockwise directions about the shaft member 262. These states are illustrated by reference numerals 24A and 24B.

FIG. 27 illustrates a specific action of the attitude correction mechanism. A base 276 is provided on a main unit 274, and an arm mechanism 270 is mounted on the base 276. The arm mechanism 270 includes a plurality of pivot mechanisms and a plurality of arm mechanisms, and reference numerals 278, 282, and 286 indicate pivot axes. Further, as the plurality of arms, a first arm 280 and a second arm 284 are illustrated. In FIG. 27, warp or drooping of the end portion caused by these arms 280 and 284 or the pivot mechanisms is illustrated in an exaggerated manner. Specifically, with respect to the

vertical pivot axis **278**, the pivot axis **282** is slightly inclined, and the pivot axis **286** is largely inclined at an inclination angle of θ .

Consequently, the end portions of the plurality of arms droop down, which makes the display unit **272**, which is mounted at a correct angle with respect to the end portion, appear to be rotated or drooping down. Such a problem is likely to occur when the plurality of arms are extended to a great degree toward the right or left side of the main unit. When such drooping occurs, the upper edge and the lower edge of the display unit **272** are inclined with respect to the horizontal level by the angle θ . Such a state is not desirable to the user, who may feel uncomfortable or uneasy. Accordingly, in the present embodiment, it is possible to cause the display unit **272** to slightly rotate about a correction movement center axis **288**; more specifically, the attitude of the display unit can be corrected to the attitude which is parallel to the vertical line, as indicated by reference numeral **272A**. As a result, even if drooping occurs in the arm mechanism, the display unit itself is parallel to the horizontal line, whereby the uncomfortable or uneasy feeling felt by the user can be eliminated.

By providing the attitude correction mechanism as described above, even if a predetermined amount of drooping of the end portion is allowed, this does not cause any adverse effects on the user. Thus, an advantage that benefits will accrue in the design or the like of the arm mechanism **270** can be obtained. As a matter of course, it is not necessary to actually operate the attitude correction mechanism if no such drooping problems occur. Further, if the user feels no discomfort, the display unit **272** which appears to rotate may be used in such a condition.

REFERENCE SYMBOLS

10 ultrasonic diagnosis device, **12** main unit, **14** movable section, **16** movable mechanism, **18** operation panel, **20** base, **22** arm mechanism, **24** display unit, **42** handle, **58** attitude correction mechanism, **60** lifting mechanism, **62** left-right slide mechanism, **64** forward-backward slide mechanism, **65** rotation limitation mechanism, **66** rotation mechanism, **68** horizontal movement mechanism, **84** shutter mechanism, **136** home position lock mechanism, **228** display unit restraint mechanism.

The invention claimed is:

1. An ultrasonic diagnosis device, comprising:
a display unit that displays an ultrasonic image; and
an arm mechanism that is disposed on a base and supports the display unit,

wherein

the arm mechanism includes:

an arm mechanism main unit that is composed of at least one arm member and at least one pivot mechanism; and
an attitude correction mechanism that is provided between the arm mechanism main unit and the display unit and, when an apparent rotation caused by drooping of an end portion of the arm mechanism main unit on the display side is generated in the display unit, rotates the display unit in the opposite direction so that the apparent rotation of the display unit can be eliminated, and

the apparent rotation of the display unit is a phenomenon in which a lower edge and an upper edge of a display surface of the display unit are not horizontal and are inclined,

the attitude correction mechanism is a mechanism that returns the lower edge and the upper edge of the display surface of the display unit to be horizontal,

the attitude correction mechanism is a mechanism that is capable of rotating the display unit in both positive and negative directions, and

wherein said attitude correction mechanism is configured to enable user selection of a desired correction angle that is less than about ± 20 degrees, wherein movement in both positive and negative directions about the rotation center axis is restricted to a maximum angle of less than about ± 20 degrees.

2. The ultrasonic diagnosis device according to claim **1**, wherein

the attitude correction mechanism includes:

a rotation shaft that is a shaft provided on one of the end portion on the display unit side and the display unit, the rotation shaft being substantially orthogonal to the display surface;

a bearing portion that is provided on the other of the end portion on the display unit side and the display unit and is coupled with the rotation shaft; and

a limitation portion that limits a rotation angle range of the display unit about the rotation shaft to said maximum angle of less than about ± 20 degrees.

3. The ultrasonic diagnosis device according to claim **2**, wherein the limitation portion includes:

a movable member that is provided on one of the end portion on the display unit side and the display unit; and
a member that is provided on the other of the end portion on the display unit side and the display unit and limits a movable range of the movable member.

4. The ultrasonic diagnosis device according to claim **3**, wherein

a center line of the rotation shaft is provided in parallel with a normal line of a display surface of the display unit, and the center line of the rotation shaft passes a center line of a tilt shaft provided in the arm mechanism main unit such that the center line of the rotation shaft is orthogonal to the center line of the tilt shaft.

5. The ultrasonic diagnosis device according to claim **1**, wherein said attitude correction mechanism is configured to enable user selection of any desired correction angle necessary, within said angle of less than about ± 20 degrees, to rotate the display unit such as to eliminate the apparent rotation of the display unit such that the lower edge and the upper edge of the display surface of the display unit are returned to horizontal.

6. A method of using the ultrasonic diagnosis device according to claim **1**, including:

when an apparent rotation caused by drooping of an end portion of the arm mechanism main unit on the display side is generated in the display unit such that the lower edge and the upper edge of the display surface of the display unit are not horizontal, using the attitude correction mechanism to rotate the display unit such as to eliminate the apparent rotation of the display unit such that the lower edge and the upper edge of the display surface of the display unit are returned to horizontal.

7. The method according to claim **6**, further including having said attitude correction mechanism configured to enable user selection of a desired correction angle that is less than about ± 20 degrees.

8. The method according to claim **6**, further including having said attitude correction mechanism configured to enable user selection of any desired correction angle necessary to rotate the display unit such as to eliminate the apparent rotation of the display unit such that the lower edge and the upper edge of the display surface of the display unit are returned to horizontal.

21

9. The ultrasonic diagnosis device according to claim 1, wherein movement in both positive and negative directions is restricted to a maximum angle of less than about ± 10 degrees.

10. The ultrasonic diagnosis device according to claim 1, wherein movement in both positive and negative directions about the rotation center axis is restricted to a maximum angle of less than about ± 5 degrees. 5

11. The ultrasonic diagnosis device according to claim 1, wherein movement in both positive and negative directions about the rotation center axis is restricted to a maximum angle of less than about ± 20 degrees by providing a first abutting member fixed to the display unit that abuts a second abutting member adjacent said display unit such as to limit movement between said first and second abutting members. 10

12. The ultrasonic diagnosis device according to claim 11, wherein said first and second abutting members include a frame member having a slit and a pin that extends within said slit, whereby movement is limited between said first and second abutting members by said pin engaging ends of said slit. 15 20

13. The ultrasonic diagnosis device according to claim 12, wherein said frame member is fixedly attached to said display unit.

22

* * * * *

专利名称(译)	超声波诊断装置		
公开(公告)号	US9055910	公开(公告)日	2015-06-16
申请号	US13/639371	申请日	2011-05-25
申请(专利权)人(译)	中岛真司		
当前申请(专利权)人(译)	日立ALOKA MEDICAL. , LTD.		
[标]发明人	NAKAJIMA SHINJI		
发明人	NAKAJIMA, SHINJI		
IPC分类号	H05K7/00 A61B8/00		
CPC分类号	A61B8/4405 A61B8/462 A61B8/463 A61B8/54		
优先权	2010121433 2010-05-27 JP		
其他公开文献	US20130021732A1		
外部链接	Espacenet USPTO		

摘要(译)

所公开的超声波诊断装置在倾斜部分和显示单元之间设置有姿态校正机构，用于消除由于臂机构的端部下垂而引起的显示单元的倾斜。姿态校正机构具有轴构件和轴承，并使显示单元围绕其显示表面的法线旋转。插脚进入狭缝，从而防止显示单元旋转超过必要的程度。

