



(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
04.03.2015 Bulletin 2015/10

(51) Int Cl.:
A61B 17/29 (2006.01)

(21) Application number: **13781829.0**

(86) International application number:
PCT/ES2013/070159

(22) Date of filing: **12.03.2013**

(87) International publication number:
WO 2013/160503 (31.10.2013 Gazette 2013/44)

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**
Designated Extension States:
BA ME

(71) Applicant: **Servocad Microtronics S.L.**
08241 Barcelona (ES)

(72) Inventor: **HERNANDEZ JUANPERA, Jesús**
E-08241 Barcelona (ES)

(74) Representative: **Isern-Jara, Nuria**
Avda. Diagonal 463 Bis 2°
08036 Barcelona (ES)


(30) Priority: **23.04.2012 ES 201230596**

(54) **LAPAROSCOPIC SURGICAL INSTRUMENT**

(57) Completely mechanically-operated laparoscopic surgical instrument, which can be disposed of after a single use or which can be sterilised and reused more than once, essentially comprising two gripping elements (2, 3) which are hinged to one another by means of a pivot shaft (4), a working tool (30) provided with two jaws

hinged to one another by a pivot shaft, and an actuation mechanism that can transmit movement from the gripping zone to the working tool (30), wherein said tool can adopt multiple positions and/or orientations when being used with the aid of substantially annular bodies coupled to connecting rods associated to the gripping elements.

FIG.1



Description

OBJECT OF THE INVENTION

[0001] The purpose of the invention patent application herein is to register a laparoscopic surgical instrument that incorporates significant innovations and advantages.

[0002] More specifically, the invention proposes the development of a completely mechanically-operated laparoscopic surgical instrument, which can be disposed of after a single use or which can be sterilised and reused more than once, which can be very useful for laparoscopy and endoscopic procedures due to the fact that the working tool can adopt multiple positions and/or orientations when being used.

BACKGROUND OF THE INVENTION

[0003] At present laparoscopic surgical devices intended for surgical operations that require suturing and ligating of body tissues by means of incisions made in the walls of the body are well known. However, in a large majority of these devices, the surgical tool (two jaws hinged together) acts in a single plane, hence offering a very limited degree of freedom that makes it difficult for the surgeon to use, although the shaft or tube connecting the gripping zone with the jaw members can be rotated on some of them.

[0004] To resolve the aforementioned problem, a laparoscopic instrument that is described in European patent EP-A-1 250891 is known. This instrument is known for comprising a pair of coupling mechanisms that can link, on the one hand, a gripping element to a jaw member while the second gripping element is linked to the second jaw member. Additionally, the two gripping elements can rotate relative to the second plane due to the structural configuration of the two attachment mechanisms.

[0005] However, this instrument is relatively complex and its freedom of movement remains limited as a 360° rotation of the axis that connects the jaw members with the gripping elements is not possible, and handling this instrument during surgery still involves some difficulty.

DESCRIPTION OF THE INVENTION

[0006] The invention herein has been developed with the aim of providing a laparoscopic surgical instrument that is considered a novelty within the field of application and resolves the aforementioned drawbacks, further providing other additional advantages that will be apparent from the description detailed hereinafter.

[0007] It is therefore an object of this invention to provide a laparoscopic surgical instrument which primarily includes a gripping zone provided with two gripping elements hinged to one another by means of a pivot shaft; a working tool provided with two gripping elements

hinged to one another by means of a pivot shaft; and an actuation mechanism that can transmit movement from the gripping zone to the working tool.

[0008] In particular, the invention is characterised in that said actuation mechanism comprises two push rods, wherein the distal end of each of the push rods is connected to a respective jaw and the proximal end is pivotally connected to a respective substantially annular body, the two substantially annular bodies being able to move longitudinally, such that the push rods can fully rotate relative to the central axis of the substantially annular body. The two substantially annular bodies are arranged slidably in a swinging movement on an elongated tubular portion through which the two push rods run along, in which each gripping element is coupled to two substantially annular bodies by two connecting rods, each one of said connecting rods being pivotally joined to a substantially annular body.

[0009] The central axis of the pivot shaft on which both gripping elements are hinged, the central shafts corresponding to the attachment points of the ends of the connecting rods that are attached to such gripping elements are aligned with each other in all operating conditions, therefore the two gripping elements can act together and/or independently of each other for joint and/or separate actions on one or both jaws.

[0010] Thanks to these characteristics, a completely mechanically-operated instrument is obtained, namely, free from electronic components, which provides a degree of freedom of movement for the jaw members compared to currently known laparoscopy instruments since it not only allows independent movement of each of the two jaws in different inclined positions relative to the longitudinal axis of the instrument but also allows a 360 degree rotation in a simple and intuitive way for the surgeon.

[0011] With no electronic components required for operation, the manufacturing costs are reduced and therefore it can be disposable. In addition, another advantageous aspect is the fact that the use of components that are sensitive to moisture or electromagnetic radiation that require, for example, additional sealing elements is prevented.

[0012] It will be apparent to one skilled in the art that the jaw members that form, for example, a clip can be substituted by cutters, pincers or scalpels which can also be disposed of after use.

[0013] According to another aspect of the invention, each push rod has an end extending perpendicularly relative to the rest of the body of the push rod that is rotably coupled in a groove which runs in a guided manner along the inner wall of the substantially annular body. Advantageously, the connecting rods have a central portion serving as a rod that can be adjusted in length.

[0014] Preferably, guiding means are provided for the linear displacement of the ends of the connecting rods attached to the substantially annular bodies. In a preferred embodiment, the guide means comprise a plate provided with two windows through which extensions of

the substantially annular bodies protrude in which screws are set which fix the connecting rod to the substantially annular body, such that the extensions move linearly through such windows.

[0015] Each gripping element includes a number of retaining means at the upper part thereof. Said retaining means have a fixed part on the upper part of the gripping element which includes an extension in the form of a toothed sector and a fixed protrusion located on said extension in the form of a toothed sector such that it meshes with the toothed sector. Furthermore, the retaining means may include a fastener that locks the extension in the form of a toothed sector in position.

[0016] The fastener comprises a linearly displaceable rod section that has a protrusion at its lower part that can be fitted into a groove that is part of a plurality of grooves below the toothed area.

[0017] Preferably, the instrument comprises return means for returning one or both gripping elements to a predetermined position after an angular displacement of at least one of the gripping elements.

[0018] Additionally, it also has blocking means for blocking the movement of one of the gripping elements relative to the other gripping element. Said blocking means have a manually operable trigger located in one of the gripping elements that acts on a ratchet fixed to the other gripping element.

[0019] Advantageously, it is provided with at least one connection socket for connecting to a source of electrical power supply, such that it transmits an electrical voltage to the working tool. Additionally, two connection sockets may be provided.

[0020] Also advantageously, one of the gripping elements includes an extension having a curved trajectory, in particular the gripping element located the closest to the working tool during a condition of use, such that it makes it easier for the surgeon to grip the instrument when handling the latter.

[0021] Preferably, provision has been made for the arrangement of a protective housing that at least partially surrounds the actuation mechanism, such that it is protected from dirt and any knocks.

[0022] According to another object of the invention, a third push rod is provided that runs parallel with respect to the two push rods mentioned above which is fixed at one end to a hinge connected to the working tool, such that the working tool can move to the right and/or left relative to the position of said push rod.

[0023] According to another characteristic, one part of the push rods are housed in a number of grooves present in a guide support, such that they are protected from the outside by preventing them from becoming bent or damaged, said push rods being guided properly and reliably.

[0024] Other characteristics and advantages of the laparoscopic surgical instrument object of the invention herein will become apparent from the description of a preferred, although not exclusive embodiment, which is illustrated by way of non-limiting example in the drawings

appended, in which:

BRIEF DESCRIPTION OF THE DRAWINGS

5 **[0025]**

Figure 1.- Perspective view of a laparoscopic surgical instrument according to the invention herein with the working tool in a closed position;

10 Figure 2.- Schematic side elevated view of the laparoscopic surgical instrument with the jaw members in a closed position and in which the main parts of the actuation mechanism are shown;

15 Figure 3.- Side elevation view of the laparoscopic surgical instrument in which the jaw members are closed to each other and in a downwardly inclined position;

20 Figure 4.- Side elevation view of the laparoscopic surgical instrument in which the jaw members are closed to each other and in an upwardly inclined position;

25 Figure 5.- Side elevation view of the laparoscopic surgical instrument in which the jaw members are open;

Figure 6.- Side elevation view of the laparoscopic surgical instrument in which the jaw members are closed;

30 Figure 7.- Detailed view of the transmission mechanism when the working tool is open, as shown in Figure 5;

Figure 8.- Detailed view of the actuation mechanism when the working tool is in the position shown in Figure 4;

35 Figure 9.- Detailed perspective view of the area where the jaw members are hinged;

Figure 10.- Detailed top-down plan view of the area where the jaw members are;

40 Figure 11.- Schematic plan view in which the arrangement of the push rods is shown relative to the substantially annular bodies;

Figure 12.- Detailed perspective view of a substantially annular body; and

45 Figure 13.- Detailed cross-sectional view of the ring shown in the previous figure.

DESCRIPTION OF A PREFERRED EMBODIMENT

50 **[0026]** In view of the mentioned figures and according to the adopted numbering, an example of a preferred embodiment of the invention can be seen therein, which comprises the parts and elements indicated and described in detail below.

55 **[0027]** Thus, as shown in the accompanying figures, a laparoscopic surgical instrument, indicated generally by the reference (1), comprises a gripping zone provided with two gripping elements (2,3) hinged together by a pivot shaft (4), a working tool (30) provided with two jaws (31, 32) hinged together by a pivot shaft (33) and an

actuation mechanism that can transmit movement from the gripping zone to the working tool (30), said actuation mechanism being described in greater detail below.

[0028] The two gripping elements (2, 3) have an elongated shape with a thimble, which are very similar in form to conventional scissors thimbles. The gripping element (2) has an extension having a curved trajectory (201) on a lower part thereof, as shown in Figures 1 and 2.

[0029] Now, with particular reference to the aforementioned actuation mechanism, it comprises two elongated push rods (5, 6) with a square cross-section and made of a metal or electrically-conductive material that run parallel to each other, wherein the distal end of each of the push rods (5, 6) is hingedly connected to a respective jaw (31, 32) and the proximal end is pivotally connected to a respective substantially annular body (7, 8).

[0030] The connection between the push rods (5, 6) and the corresponding jaws (31, 32) is made by means of intermediate joints (50, 60), respectively, as seen more clearly in Figures 10 and 11.

[0031] The two substantially annular bodies (7, 8) can further move longitudinally, allowing the tubular portion (14) to rotate on its own axis, such that the push rods (5, 6) can be rotated completely relative to the central axis of the substantially annular body, namely, up to 360°, thereby changing the position or orientation of the working tool, without ceasing to actuate or move due to the action of one or both gripping elements (2, 3). In order to activate the rotation action, a rotating wheel (29) is used that can rotate manually in both directions, such that it allows the working tools to rotate on their axis regardless of the position of the gripping element (2, 3).

[0032] An insulating cover (9) is provided around one part of the two push rods (5, 6) which is outside a protective housing (10) that protects the actuation mechanism.

[0033] This protective housing (10) is formed by two halves that can be joined together, for example, from plastic material, provided with multiple holes through which the parts necessary for proper operation of the surgical instrument (1) protrude. For clarity, this protective housing (10) is only shown in Figure 1.

[0034] These two substantially annular bodies (7, 8) are arranged slidably in a swinging movement on an elongated tubular portion (14) through which the two push rods (5, 6) run along, in which each gripping element (2, 3) is coupled to the two substantially annular bodies (7, 8) by means of a set of two connecting rods (11, 12). Said elongated tubular portion (14) is connected to the rotating wheel (29) such that it enables the rotation of the push rods (5, 6).

[0035] The rotating wheel (29) is coupled to a pinion (40) that is in contact with an elastic plate (41) secured through a protuberance that acts as retaining means in order to prevent the idle rotation of the rotating wheel (29).

[0036] As seen in Figure 8, each of said connecting rods (11, 12) is pivotally attached to a substantially annular body by means of bolting elements (26) located at

each end of the connecting rods. Each set of connecting rods (11, 12) is located on each side of the surgical instrument (1) relative to its longitudinal central axis.

[0037] Such bolting elements (26) are fixed in through-holes located on two protrusions (70) that protrude outwardly and which are diametrically opposite, as seen in detail in Figures 12 and 13.

[0038] It is worth noting that the central shafts corresponding to the attachment points of the ends of the connecting rods (11, 12) that are attached to such gripping elements are aligned with each other in all operating conditions, therefore the two gripping elements can act together and/or independently of each other for joint and/or separate actions on one or both jaws.

[0039] Each push rod (5, 6) has a end (50, 60) extending perpendicularly relative to the rest of the body of the push rod (5, 6) that is rotably coupled in a groove which runs in a guided manner along the inner wall of the substantially annular body (7, 8).

[0040] To ensure the linear displacement of the ends of the connecting rods attached to the substantially annular bodies, a plate (24) provided with two windows (25) is provided through which extensions of the substantially annular bodies protrude in which screws are set (26) which fix the connecting rod to the substantially annular body, such that the extensions move linearly through such windows (25). It is understood that the instrument herein (1) is provided with two identical plates, a plate (24) for each set of two connecting rods (11, 12).

[0041] Finally, a third push rod (35) is provided that runs parallel relative to the two push rods which is secured at one end to a hinge attached to the working tool (30) to rotate said working tool (30) to the right and/or left with respect to the longitudinal axis of said third push rod (35). This movement is performed by moving the part of the instrument that protrudes from the housing forwards or backwards by means of a zip system (34) which is connected to said third push rod (35) and a lever (36) that protrudes vertically, said zip system (34) being located inside the protective housing (10). To prevent the inadvertent movement of the third push rod (35), blocking means that act on the zip system (34) have been included to prevent its displacement.

[0042] This actuation mechanism described above advantageously allows the working tool to adopt multiple positions, namely, the two jaws can be oriented either in an open or closed position, upwards, downwards, to the right or to the left, as shown in some examples of positioning of the working tool in Figures 3, 6 and 9. Such positions are conducted by the movement, simultaneously or individually, towards and away from a gripping element (2, 3) relative to another gripping element (3, 2), the joint swivel movement of both gripping elements (2, 3) relative to the longitudinal axis defined by the push rods and the rotation of the rotating wheel (29).

[0043] Each gripping element (2, 3) includes retaining means at the upper part thereof having a fixed part (17) on the top of the gripping element that includes an ex-

tension (170) in the form of a toothed sector and a protrusion (180) formed in a centred manner on a laminar plate (18) which is fixed and located on said extension (170) in the form of a toothed sector such that it meshes with the toothed sector. Furthermore, the retaining means include a fastener (19) that locks the extension (170) in the form of a toothed sector in position. It should be mentioned that two fasteners (19) are provided; one associated with each fixed part (17).

[0044] The surgical instrument (1) also has blocking means for blocking the movement of one of the gripping elements relative to the other gripping element. When a part of the gripping element (2) is removed, these blocking means, which can be seen in detail in Figure 2, have a trigger (20) with a substantially C shape which is operable manually using elastic return means (27) arranged downwardly, the trigger (20) being located in the gripping element (2) which acts by means of a protrusion (28) on a ratchet (21) attached to the other gripping element (3). The actuation of the ratchet (21) can be cancelled voluntarily by means of a switch (22) which is easily accessible and located on the gripping element (2).

[0045] A connection socket (23) is provided at the rear of the surgical instrument (1), for example, the bipolar type for connecting to a source of electrical power supply; therefore a voltage can be transmitted to the working tool, if necessary. It will be apparent that more than one connection socket can be included in the surgical instrument (1) described herein.

[0046] Finally, a pair of inlet sockets (16) are provided at the top in order to connect a conduit for supplying a fluid that can be used for medical purposes, if it were required.

[0047] The details, shapes and dimensions and other accessory elements as well as the materials used in the manufacture of the laparoscopic surgical instrument of the invention may be conveniently replaced by others which are technically equivalent and do not depart from the essential nature of the invention or from the scope defined by the claims provided hereinafter.

Claims

1. Laparoscopic surgical instrument (1) comprising:

a gripping zone provided with two gripping elements (2,3) hinged to one another by means of a pivot shaft (4);

a working tool (30) provided with two jaws hinged to one another by means of a pivot shaft; an actuation mechanism that can transmit movement from the gripping zone to the working tool (30),

characterised by the fact that said actuation mechanism comprises:

two push rods (5, 6), wherein the distal end

of each of the push rods (5, 6) is hingedly connected to a respective jaw and the proximal end is pivotally connected to a respective substantially annular body, the two substantially annular bodies (7, 8) being able to move longitudinally, such that the push rods (5, 6) can fully rotate about the central axis of the substantially annular body by means of linked rotating means;

the two substantially annular bodies being arranged slidably in a swinging movement on an elongated tubular portion through which the two push rods (5, 6) run along, said tubular portion being associated with the rotation means,

in which each gripping element (2, 3) is coupled to the two substantially annular bodies (7, 8) by means of two connecting rods, each one of said connecting rods pivotally joined to a substantially annular body, and in which the central axis of the pivot shaft on which both gripping elements are articulated, the central shafts corresponding to the attachment points of the ends of the connecting rods that are attached to such gripping elements are aligned with each other in all operating conditions, therefore the two gripping elements (2, 3) can act together and/or independently of each other for joint and/or separate actions on one or both jaws.

2. Laparoscopic surgical instrument (1) according to claim 1, **characterised by** the fact that each push rod (5, 6) has an ending that extends perpendicularly relative to the body of the push rod (5, 6) that is rotably coupled in a groove that runs in a guided manner along the inner wall of the substantially annular body (7, 8).


3. Laparoscopic surgical instrument (1) according to claim 1, **characterised by** the fact that the connecting rods have a central portion serving as a rod that can be adjusted in length.

4. Laparoscopic surgical instrument (1) according to claim 1, **characterised by** the fact that guide means are provided for the linear displacement of the ends of the connecting rods attached to the substantially annular bodies (7, 8).

5. Laparoscopic surgical instrument (1) according to claim 4, **characterised by** the fact that the guide means comprise a plate provided with two windows through which extensions of substantially annular bodies protrude in which screws are set which fix the connecting rod to the substantially annular body (7, 8), such that the extensions move linearly through such windows.

6. Laparoscopic surgical instrument (1) according to claim 1, **characterised by** the fact that each gripping element (2,3) includes a number of retaining means at the upper part thereof.
7. Laparoscopic surgical instrument (1) according to claim 6, **characterised by** the fact that said retaining means have a part (17) fixed on the upper part of the gripping element which includes an extension in the form of a toothed sector (170) and a fixed protrusion (180) located on said extension in the form of a toothed sector (170) such that it meshes with the toothed sector.
8. Laparoscopic surgical instrument (1) according to claims 6 and 7, **characterised by** the fact that the retaining means includes a fastener that locks the extension in the form of a toothed sector in position.
9. Laparoscopic surgical instrument (1) according to claim 8, **characterised by** the fact that the fastener (19) comprises a linearly displaceable rod section that has a protrusion at its lower part that can be fitted into a groove that is part of a plurality of grooves below the toothed area.
10. Laparoscopic surgical instrument (1) according to claim 1, **characterised by** the fact that it comprises return means for returning one or both gripping elements to a predetermined position after an angular displacement of at least one of the gripping elements.
11. Laparoscopic surgical instrument (1) according to claim 1, **characterised by** the fact that it has blocking means for blocking the movement of one of the gripping elements relative to the other gripping element.
12. Laparoscopic surgical instrument (1) according to claim 11, **characterised by** the fact that said blocking means have a manually operable trigger (20) located in one of the gripping elements (2) which actuates on a ratchet (21) fixed in the other gripping element.
13. Laparoscopic surgical instrument (1) according to claim 1, **characterised by** the fact that it has at least one connection socket (23) for connecting to a source of electrical power supply such that it transmits a voltage to the working tool.
14. Laparoscopic surgical instrument (1) according to claim 1, **characterised by** the fact that one of the gripping elements includes an extension (201) having a curved trajectory on the lower part thereof, in particular arranged on the gripping element located closer to the working tool (30) during a condition of use.
15. Laparoscopic surgical instrument (1) according to claim 1, **characterised by** the fact that it includes a protective housing (10) that at least partially surrounds the actuation mechanism.
16. Laparoscopic surgical instrument (1) according to claim 1, **characterised by** the fact that the push rods (5, 6) have a square or rectangular cross-section.
17. Laparoscopic surgical instrument (1) according to claim 1, **characterised by** the fact that the substantially annular body includes two protrusions that protrude outwardly and which are diametrically opposite provided with through-holes.
18. Laparoscopic surgical instrument (1) according to claim 1, **characterised by** the fact that rotation means comprise a rotary wheel (29) that is linked to an elongated tubular portion.
19. Laparoscopic surgical instrument (1) according to claim 1, **characterised by** the fact that a third push rod is provided which runs parallel relative to the two push rods which is secured at one end to a hinge attached to the working tool (30) to rotate the working tool (30) to the right and/or left with respect to the longitudinal axis of said push rod (35), said third push rod (35) being connected to a zip system (34) provided with blocking means to activate/prevent actuation of said zip system (34).
20. Laparoscopic surgical instrument (1) according to claim 19, **characterised by** the fact that it includes actuation means for moving the zip system (34) which have a lever (36) projecting outwardly from the inside of the protective housing.
21. Laparoscopic surgical instrument (1) according to claim 1, **characterised by** the fact that one part of the push rods are housed in a number of grooves that are present in a guide support.

FIG. 1






FIG. 2




FIG. 4




FIG. 6




FIG. 3




FIG. 5

FIG. 7




FIG. 8




FIG. 9






FIG. 10









FIG. 13



INTERNATIONAL SEARCH REPORT

International application No.
PCT/ES2013/070159

A. CLASSIFICATION OF SUBJECT MATTER

A61B17/29 (2006.01)

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC, INVENES, WPI, PAJ.

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	ES 2337984 T3 (HUNT ROBERT B.) 03/05/2010, page 6, lines 19-56; page 7, lines 21-37; figures 5-11.	1-21
A	ES 2369530 T3 (AESCULAP WERKE AG) 01/12/2011, page 9, line 18-page 12, line 3; figures 3-13.	1-21
A	US 5827323 A (KLIEMAN CHARLES H. et al.) 27/10/1998, column 5, line 55-column 13, line 25; figures.	1-21
A	US 2005075664 A1 (OLYMPUS CORPORATION) 07/04/2005, paragraphs [1]; [9]; [48-194]; figures.	1-21
A	ES 2333509 A1 (UNIVERSIDAD DE CANTABRIA et al.) 22/02/2010, page 6, line 10-page 8, line 55; figures.	1-21

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance.

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure use, exhibition, or other means.

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search
12/07/2013

Date of mailing of the international search report
(17/07/2013)

Name and mailing address of the ISA/

OFICINA ESPAÑOLA DE PATENTES Y MARCAS
Paseo de la Castellana, 75 - 28071 Madrid (España)
Facsimile No.: 91 349 53 04

Authorized officer
J. Cuadrado Prados

Telephone No. 91 3495522

Form PCT/ISA/210 (second sheet) (July 2009)

INTERNATIONAL SEARCH REPORT

International application No.
PCT/ES2013/070159

C (continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of documents, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	ES 2114962 T3 (UNITED STATES SURGICAL CORP) 16/06/1998, column 5, line 19-column 10, line 58; figures.	1-21

Form PCT/ISA/210 (continuation of second sheet) (July 2009)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/ES2013/070159

Information on patent family members

Patent document cited in the search report	Publication date	Patent family member(s)	Publication date
ES2337984T T3	03.05.2010	US2002072766 A1 US6506208 B2 WO0166025 A1 JP2003525687 A JP3803294B B2 EP1261286 A1 EP1261286 A4 AU2971601 A AT445369T T US6358268 B1	13.06.2002 14.01.2003 13.09.2001 02.09.2003 02.08.2006 04.12.2002 18.07.2007 17.09.2001 15.10.2009 19.03.2002
ES2369530T T3	01.12.2011	WO03030708 A2 WO03030708 A3 EP1450698 A2 EP1450698 A4 AU2002322309 A1 AT519436T T US2002072766 A1 US6506208 B2	17.04.2003 17.06.2004 01.09.2004 03.03.2010 22.04.2003 15.08.2011 13.06.2002 14.01.2003
US5827323 A	27.10.1998	JPH10174689 A JP3163274B B2 WO9814124 A1 AU4504097 A US5817119 A WO9610957 A1 JPH10510169 A JP3163107B B2 EP0785754 A1 EP0785754 A4 CA2202376 A1 BR9509298 A AU3970895 A AU692951B B2 US5792165 A US5582617 A WO9503001 A1 JPH09501333 A EP0710089 A1 EP0710089 A4 DE69429350T T2 CA2167367 A1 AU7366994 A AT209875T T	30.06.1998 08.05.2001 09.04.1998 24.04.1998 06.10.1998 18.04.1996 06.10.1998 08.05.2001 30.07.1997 07.06.2000 18.04.1996 03.11.1998 02.05.1996 18.06.1998 11.08.1998 10.12.1996 02.02.1995 10.02.1997 08.05.1996 07.05.1997 22.08.2002 02.02.1995 20.02.1995 15.12.2001
US2005075664 A1	07.04.2005	NONE	
ES2333509 A1	22.02.2010	WO2011042584 A1	14.04.2011
ES2114962T T3	16.06.1998	US2007162072 A1 US2006259071 A1	12.07.2007 16.11.2006

Form PCT/ISA/210 (patent family annex) (July 2009)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/ES2013/070159

Information on patent family members

Patent document cited in the search report	Publication date	Patent family member(s)	Publication date
		US2002177874 A1	28.11.2002
		US7087071 B2	08.08.2006
		US5766205 A	16.06.1998
		US5782859 A	21.07.1998
		US5514157 A	07.05.1996
		US5607450 A	04.03.1997
		US5571115 A	05.11.1996
		US5490819 A	13.02.1996
		US5431662 A	11.07.1995
		US5391180 A	21.02.1995
		EP0557806 A2	01.09.1993
		EP0557806 A3	27.04.1994
		DE69318324T T2	05.11.1998
		CA2088884 A1	13.08.1993
		CA2088884 C	15.10.2002
		US5383888 A	24.01.1995

Form PCT/ISA/210 (patent family annex) (July 2009)

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- EP 1250891 A [0004]

专利名称(译)	腹腔镜手术器械		
公开(公告)号	EP2842503A1	公开(公告)日	2015-03-04
申请号	EP2013781829	申请日	2013-03-12
[标]申请(专利权)人(译)	SERVOCAD微电子学		
申请(专利权)人(译)	SERVOCAD微电子学S.L.		
当前申请(专利权)人(译)	SERVOCAD微电子学，S.L.		
[标]发明人	HERNANDEZ JUANPERA JESUS		
发明人	HERNANDEZ JUANPERA, JESÚS		
IPC分类号	A61B17/29		
CPC分类号	A61B17/29 A61B17/2909 A61B18/1445 A61B2017/291 A61B2017/2927 A61B2017/2929 A61B2017/2938 A61B2217/007		
优先权	2012030596 2012-04-23 ES		
其他公开文献	EP2842503A4 EP2842503B1		
外部链接	Espacenet		

摘要(译)

完全机械操作的腹腔镜手术器械，可在一次使用后丢弃或可多次消毒和重复使用，主要包括两个夹紧元件（2,3），它们通过枢轴相互铰接（4），工作工具（30）设置有两个通过枢轴彼此铰接的夹爪，以及可以将夹持区域的运动传递到工作工具（30）的致动机构，其中所述工具可以采用多个位置当借助于与连接到与夹紧元件相关联的连杆的基本上环形的主体一起使用时，和/或取向。

