



(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
27.09.2017 Bulletin 2017/39

(51) Int Cl.:
A61B 17/03 ^(2006.01) **A61B 17/04** ^(2006.01)
A61B 17/34 ^(2006.01)

(21) Application number: **15858114.0**

(86) International application number:
PCT/KR2015/009109

(22) Date of filing: **31.08.2015**

(87) International publication number:
WO 2016/080639 (26.05.2016 Gazette 2016/21)

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**
Designated Extension States:
BA ME
Designated Validation States:
MA

(71) Applicant: **Kim, Ki Seong**
Goyang-si, Gyeonggi-do 10322 (KR)

(72) Inventor: **Kim, Ki Seong**
Goyang-si, Gyeonggi-do 10322 (KR)

(74) Representative: **McCartney, Jonathan William**
Haseltine Lake LLP
Redcliff Quay
120 Redcliff Street
Bristol BS1 6HU (GB)


(30) Priority: **21.11.2014 KR 20140163452**

(54) **LAPAROSCOPIC PORT SITE CLOSING APPARATUS**

(57) Disclosed is a laparoscopic port site closure device. The device is configured such that a cartridge receiving a surgical suture therein is provided at a fore-end of a needle guide for port site closure; the surgical suture is caught in a needle tip that is pierced through a body tissue by being guided by the needle guide; and when

the needle is withdrawn, the surgical suture is pulled out along a path through which the needle was pierced into the tissue, and the surgical suture is tied outside a patient's body, thereby being capable of closing a laparoscopic port site.

【FIG. 5】



Description**Technical Field**

5 [0001] The present invention relates generally to a laparoscopic port site closure device. More particularly, the present invention relates to a laparoscopic port site closure device configured such that a cartridge receiving a surgical suture therein is provided at a fore-end of a needle guide for port site closure; the surgical suture is caught in a needle tip that is pierced through a body tissue by being guided by the needle guide; and when the needle is withdrawn, the surgical suture is pulled out along a path through which the needle is pierced into the tissue, and the surgical suture is tied outside a patient's body, thereby being capable of closing a laparoscopic port site.

Background Art

15 [0002] In general, laparoscopic surgery, unlike conventional open surgical procedures, refers to a surgical technique where four to six incisions about 0.5~1.2cm in size are made on the patient's abdomen, and trocars, which have a diameter of 0.5~1.2cm and are 15~16cm long, are placed through these incisions. A light source, a camera, and surgical instruments are then introduced into the abdomen through the trocars. The surgeon performs the procedure, watching a television monitor on which the camera transmits an image of the organs inside the abdomen.

20 [0003] Laparoscopic surgery is used for cholecystectomy, bile duct stone removal, hepatic duct stone removal, appendectomy, and removal of tumors in a variety of organs. Patients with laparoscopic surgery have much less pain, fewer complications such as enteroplegia, shorter hospital stays, rapid recovery, and less post-operative scarring compared to patients with open surgical procedures.

25 [0004] For laparoscopic surgery, after a plurality of trocars is placed into a patient's abdomen, carbon dioxide gas is used to inflate the abdomen through one of the trocars in order to give the surgeon room to work. The endoscope and surgical instruments are then introduced through other trocars. The surgeon performs a surgery for the affected area, monitoring the surgical site.

30 [0005] After the procedure, in order to close the incisions, a trocar site closure tool is used. The trocar site closure tool is configured such that the incisions are closed by stitching while the needle is held by the forceps that are placed into the abdominal cavity through the trocar. After closing the incisions, in order to prevent the stitches from being untied, opposite ends of the surgical suture are pulled out of the patient's body through the trocar, and the knots are tied outside the patient's body. After tying the knots, the knots are formed into the abdominal cavity by pushing the knots using a compressor.

35 [0006] However, the conventional trocar site closure tool for laparoscopic surgery described above is problematic in that when the surgical suture, which is pulled out through the incision along with the needle, is pulled using the forceps, the surgical suture may be easily cut by the pressure of the forceps.

[0007] Further, after stitching the incisions, to prevent the stitches from being untied, the knots are tied. When opposite ends of the surgical suture are pulled out of the patient's body in order to tie the knots, an additional instrument, such as forceps or pincette, is required.

[0008] As another related art, a fascial closure device is shown in FIG. 1.

40 [0009] The fascial closure device, which is in a tube shape for being introduced into a port site, includes: a tubular body 1 formed with needle guides 2 that face each other and guide insertion of a needle 3; and a pair of wings 5 being mounted to a lower portion of the tubular body 1, and being opened and closed using cam method, wherein each of the wings 5 is provided with a silicon pad 6 at a location where the needle 3 penetrates through, and the wings 5 are configured to be opened by rotating an operating stick 4 and configured to be closed by reversely rotating the operating stick 4.

45 [0010] The conventional fascial closure device solves a few of the above problems occurring in the related art. However, the fascial closure device is still problematic in the closure process. Reference will be made to the closure process using the conventional fascial closure device.

50 [0011] As shown in FIGS. 2 and 3, the needle 3 penetrates through a tissue along the guide path 2 by threading the surgical suture 7. Here, the needle 3 is placed on the silicon pad 6 of the wing 5. When the needle 3 is further pushed into the silicon pad 6, a needle tip penetrates therethrough. After that, when the needle 3 is pulled out, the surgical suture 7 remains compressed in the silicon pad 6.

55 [0012] After the surgical suture 7 is compressed in the silicon pad 6 of the wings 5, the needle 3 is removed. The operating stick 4 is then rotated so as to close the wings 5, whereby the compressed surgical suture 7 is concentrated around the axis of the tubular body 1. When the tubular body 1 is withdrawn, the surgical suture 7 is pulled out and tied, whereby the closure is completed.

[0013] However, the conventional fascial closure device is problematic in that the suture area is easily infected by the surgical suture that is placed thereon during the recovery because the surgical suture, which penetrates through a tissue

around the port site, is pulled out of a patient's body through the port.

[0014] Further, the conventional fascial closure device requires cutting the surgical suture into a predetermined length and threading the needle with the surgical suture. Thus, the procedure is inconvenient. The conventional fascial closure device is further problematic in that when the binding force of the silicon pad to the surgical suture becomes weak, it is difficult to pull out the surgical suture, thereby requiring additional work.

[0015] Further, in the process of threading the surgical suture in the needle, a surgeon or a nurse may be stuck or infected by the needle. In the process of closing a plurality of ports, the above mentioned problems occur repeatedly, whereby the operation time may be long.

Disclosure

Technical Problem

[0016] Accordingly, the present invention has been made keeping in mind the above problems occurring in the related art, and the present invention is intended to propose a laparoscopic port site closure device.

[0017] The present invention is configured such that a tubular body of the laparoscopic port site closure device is provided with a detachable cartridge at an end thereof so as to be capable of being repeatedly used by replacing only the cartridge. Thus, the laparoscopic port site closure device according to the present invention is convenient and kept free from spreading infection.

[0018] The present invention is configured such that the cartridge includes wings capable of being open enough to fit a location where a needle is inserted; and surgical suture being received therein, the surgical suture temporarily locked to the wings. Thus, the laparoscopic port site closure device according to the present invention does not require tying the surgical suture, whereby it is possible to realize speedy closure.

[0019] The present invention is configured such that the surgical suture, which is placed in the abdominal cavity, is simply pulled out of a patient's body in order to close an opening in the tissue. Thus, the laparoscopic port site closure device according to the present invention prevents an incision area, namely an opening port site, from intervention of the surgical suture therein.

[0020] The present invention includes a needle for catching and withdrawing the surgical suture that is placed in the abdominal cavity. Thus, the laparoscopic port site closure device according to the present invention prevents the surgical suture from slipping off from the needle.

[0021] The present invention is configured such that the surgical suture that is received in the laparoscopic port site closure device is provided with an additional structure at opposite ends thereof so as to be caught and pulled out using the needle. Thus, the laparoscopic port site closure device according to the present invention realizes easy closure.

[0022] The present invention is configured such that the cartridge, in which the surgical suture is received, is replaceable. Thus, the laparoscopic port site closure device according to the present invention is capable of being used repeatedly, thereby economical.

Technical Solution

[0023] In order to achieve the above object, according to one aspect of the present invention, there is provided a laparoscopic port site closure device.

[0024] The laparoscopic port site closure device, which is in a tube shape for being introduced into a port site, includes: a tubular body provided with needle guides that face each other and guide insertion of a needle; wings mounted to a lower portion of the tubular body such that the wings are opened and closed through a cam method; and an operating stick penetrating through the tubular body to operate the wings by being rotated to push and open the wings and to pull and close the wings by being rotated reversely. The laparoscopic port site closure device further includes: a replaceable cartridge provided on a lower end of the tubular body to be detachably combined with the operating stick, wherein the cartridge is provided with the wings capable of being opened by operating the operating stick, and provided with a compartment for receiving surgical suture therein, wherein the laparoscopic port site closure device is configured such that opposites ends of the surgical suture in the compartment are threaded through the wings such that the ends of the surgical suture are pulled out of a patient's body by being caught by a suture slot of a needle that is pierced into the patient's body from outside.

[0025] The needle may include a suture slot for catching and pulling out a surgical suture by being concavely formed on a needle tip in an opposite direction of pulling the surgical suture.

[0026] The surgical suture may be received at a lower end of the cartridge, wherein each end of the surgical suture may be provided with a spiral coil, with a stopper provided at each end of the coil, such that the surgical suture is easily caught in the suture slot. Herein, the surgical suture is folded and received in a case to be easily unfolded toward outside when being pulled out of the case.

[0027] Attachment and detachment of the cartridge and operation of the wings that are provided in the cartridge may be dependent on a location of the operating stick. To achieve this, the device may be provided with protrusions and grooves.

Advantageous Effects

[0028] According to the present invention having the above-described characteristics, the advantageous effects of the present invention are as follows. The present invention is configured such that a tubular body of the laparoscopic port site closure device is provided with a detachable cartridge at an end thereof so as to be capable of being repeatedly used by replacing only the cartridge. Thus, the present invention is convenient and kept free from transmitting infection. The present invention is further configured such that the cartridge includes wings capable of being open enough to fit a location where a needle is inserted; and surgical suture being received therein, the surgical suture temporarily locked to the wings. Thus, the laparoscopic port site closure device according to the present invention does not require tying the surgical suture, whereby it is possible to realize speedy closure of an incision site. The present invention is further configured such that the surgical suture, which is placed in the abdominal cavity, is simply pulled out of a patient's body in order to close an opening in the tissue. Thus, the laparoscopic port site closure device according to the present invention prevents an incision area, namely an opening port site, from intervention of the surgical suture therein, thereby realizing speedy recovery. The present invention includes a needle for catching and withdrawing the surgical suture that is placed in the abdominal cavity. Thus, the laparoscopic port site closure device according to the present invention prevents the surgical suture from slipping off the needle, thereby realizing a speedy and safe procedure.

[0029] The present invention is configured such that the surgical suture that is received in the laparoscopic port site closure device is provided with an additional structure at opposite ends thereof so as to be caught and pulled out using the needle. Thus, the laparoscopic port site closure device according to the present invention realizes easy closure of an incision site. The present invention is configured such that the cartridge, in which the surgical suture is received, is replaceable. Thus, the laparoscopic port site closure device according to the present invention is capable of being used repeatedly and is thereby economical.

Description of Drawings

[0030]

FIG. 1 is a view illustrating a conventional laparoscopic port site closure device;
 FIGS. 2a and 2b are sectional views of essential portions illustrating a closure process using the device of FIG. 1;
 FIG. 3 is a schematic view illustrating a final tie structure of surgical suture in the closure process of FIG. 1;
 FIG. 4a is a perspective view illustrating an appearance of the present invention;
 FIG. 4b is a partial exploded perspective view of FIG. 4a;
 FIG. 5 is a perspective view of the present invention illustrating a state where a needle is inserted into a wing by opening the wing;
 FIG. 6 is a view illustrating a cartridge according to the present invention;
 FIG. 7 is an exploded perspective view illustrating the cartridge according to the present invention;
 FIG. 8 is a view illustrating a configuration of an operating stick that operates the cartridge according to the present invention;
 FIGS. 9 to 12 are views illustrating operation of the cartridge in response to manipulation of the operating stick according to the present invention;
 FIG. 13 is a view of an essential portion illustrating a configuration of the needle according to the present invention;
 FIG. 14 is a view illustrating a structure of surgical suture according to the present invention;
 FIG. 15 is a schematic view illustrating a closure process using a laparoscopic port site closure device according to the present invention;
 FIG. 16 is a schematic view illustrating a state where the surgical suture is caught in the needle according to the present invention; and
 FIG. 17 is a schematic view illustrating a state of a port site being finally sutured by the surgical suture according to the present invention.

Best Mode

[0031] Reference will now be made in greater detail to an exemplary embodiment of the present invention, an example of which is illustrated in the accompanying drawings.

[0032] As shown in FIGS. 4 to 7, a laparoscopic port site closure device according to the present invention, which is

in a tube shape for being introduced into a port site, includes: a tubular body provided with needle guides that face each other and guide insertion of a needle; wings mounted to a lower portion of the tubular body such that the wings are opened and closed through a cam method; and an operating stick penetrating through the tubular body to operate the wings by being rotated to push and open the wings and to pull and close the wings by being rotated reversely. The laparoscopic port site closure device further includes: a replaceable cartridge 30 provided on a lower end of the tubular body 10 to be detachably combined with the operating stick 20, wherein the cartridge 30 is provided with the wings 33 capable of being opened by operating the operating stick, and provided with a compartment 32 for receiving surgical suture 40 therein, wherein the laparoscopic port site closure device is configured such that opposites ends of the surgical suture 40 in the compartment are threaded through the wings 33 such that the ends of the surgical suture are pulled out of a patient's body by being caught by a suture slot of a needle 50 that is pierced into the patient's body from outside.

[0033] The tubular body 10 may be divided into two parts, and may include a cone-shaped handle 11 and a tube that extends from the handle, wherein inner protrusions 12 are provided inside of the tube at a lower portion thereof at positions facing each other; needle guide holes 13 are provided on the handle 11 for guiding introduction and withdrawal of the needle, the needle guide holes ranging from an upper portion of the handle 11 to a side wall of the tube at opposite positions; and a crank-shaped guide groove 14 is provided inside the handle 11 and guides a rotation and forward-backward movement of the operating stick 20 and fixes a location of the operating stick.

[0034] The guide groove 14 is provided in each half of the tubular body, wherein the guide groove 14 includes an inward groove and an outward groove 14a and 14b so as to form the crank shaped guide groove 14.

[0035] The operating stick 20 may include a handle 21 and a rod that extends from the handle, wherein outer protrusions 22 that are disposed opposite to each other are provided at an end of the rod, and guide protrusions 23 that are disposed opposite to each other are provided below the handle 21 by protruding and serve to mount and demount the cartridge 30 such that the cartridge is combined with the tubular body 10.

[0036] The cartridge 30 may include: a first support 300 including a mounting slot 301 provided in the center thereof, and locking channels 302 disposed opposite to each other provided on an outer circumferential surface thereof; a second support 310 provided beneath the first support, the second support being in a planar shape so as to support a surface of each of the wings 33, and including wing protrusions 311 disposed opposite to each other as a pivot of the wings; a third support 320 being in a planar shape rotated at an angle of 90 degrees relative to the second support, having a width to come into close contact with the wings 33 when the wings are closed, and including the compartment 32 that is in a cone shape and is provided at a lowermost end thereof and a cover 322 for covering the compartment; and the wings 33 each including: a wing hole 331 for being engaged with the wing protrusions 311 of the second support 310; an arch-shaped link hole 333 that is provided outside the wing hole 331, the link hole 333 having an opening at an edge thereof with a ridge 334 provided by protruding in the opening; a mounting hole 335 for mounting an end of the surgical suture 40; and a communication slot 336 provided on an outer surface of the wing to communicate with the mounting hole 335, wherein the wings comprise a pair of wings that are disposed opposite to each other.

[0037] When the cartridge 30 including the wings 33 is assembled with the tubular body, the cartridge may share the same center point as the tubular body and may have no protruding surfaces.

[0038] The compartment 32 may include a notch 337 provided at a portion of an outer surface thereof so as to serve as a suture outlet for the surgical suture that is received therein.

[0039] The surgical suture 40 may be received at a lower end of the cartridge 30, wherein each end of the surgical suture 40 may be provided with a spiral coil 42, with a stopper 43 provided at each end of the coil, such that the surgical suture is easily caught in the suture slot. Herein, the surgical suture is folded and received in a case 45 to be easily unfolded toward outside when being pulled out of the case.

[0040] Further, the spiral coil 42 that is combined with the surgical suture may include a silicon tube 46 fitted over a junction between the spiral coil and the surgical suture.

[0041] An end of the coil, which is made of metal, may be melted to form a ball-shaped stopper 43.

[0042] The spiral coil 42 may be made of a metal wire having a diameter of 0.1~0.15mm by coiling the wire such that the coil is extended when pulled by an external force.

[0043] The needle 50 may be long enough to reach from the needle guide holes 13 to the wings 33 that are opened, and the needle 50 may be provided with a suture slot 52 at a tip thereof by being concavely formed thereon.

[0044] In other words, the suture slot 52 of the needle 50 may be concavely formed on the needle tip in an opposite direction of pulling the surgical suture so as to catch and pull out the surgical suture.

[0045] Reference numeral 11a denotes a handle cover of the tubular body for allowing easily recognizing a lock or an unlock state of the operating stick 20, and reference numeral 10a denotes a locking clip for assembling the tubular body that is divided into two parts.

[0046] Reference will now be made in greater detail to operation of the laparoscopic port site closure device, hereinbelow.

[0047] The laparoscopic port site closure device according to the present invention may be configured such that the surgical suture 40, which is in the case 45, is received in the compartment 32, and the coil 42 provided at each end of

the surgical suture is inserted into the mounting hole 335 of the wings 33, wherein the surgical suture is pulled out through the notch 337 of the compartment 32.

[0048] Here, the silicon tube 46 of the surgical suture may be made of a soft material so as to be deformed to help the surgical suture to be caught in the communication slot 336 for temporal fixation. Further, the silicon tube 46 covers and protects the junction between the surgical suture and the spiral coil, wherein the surgical suture is combined with the end of the coil 42.

[0049] When the cartridge 30 that receives the surgical suture is inserted into the tubular body 10, the inner protrusions 12 at the lower portion of the tubular body are combined with the cartridge 30 by passing the ridge 334 of the wings 33. Here, the outer protrusions 22 of the operating stick 20 are guided to and mounted to the mounting slot 301 of the first support 300.

[0050] When the laparoscopic port site closure device according to the present invention is used to close the port site, as a manner similar to a conventional operation, after a cone-shaped fore-end of the cartridge 30 is inserted into the patient's body by holding the cone-shaped handle 11 according to the present invention, the link hole 333 is engaged with the inner protrusions 12 around the wing protrusions 311 by pulling the handle 21 of the operating stick 20, wherein the wings 33 are combined with the wing protrusions 311 of the second support 310. Here, when the operating stick 20 is rotated at an angle of 45 degrees clockwise, the wings 33 are opened along an edge of the arch-shaped link hole 333.

[0051] The opened wings 33 may be perpendicular to the tubular body 10, and an angle of rotation is dependent on the link hole 333.

[0052] The guide protrusions 23 of the operating stick 20 are engaged with the inward groove 14a of the guide groove 14 such that a location of the operating stick 20 is fixed, whereby the opened wings 33 remain open (see FIG. 10).

[0053] The guide groove 14 is crank shaped and includes grooves 14a and 14b for guiding a rotation and forward-backward movement of the operating stick 20 and fixing a location of the operating stick.

[0054] After the wings 33 is opened and fixed, as shown in FIG. 5, when the needle 50 is inserted through the guide holes 13, the needle tip is pierced through a tissue around a port. The needle is then withdrawn after the coil 42 is passed through the wings 33. Here, the stopper 43 of the coil is caught in the suture slot 52 of the needle, wherein the coil is extended along the needle that is pulled, whereby a tied portion of the surgical suture is safely pulled out of the patient's body (see FIGS. 15 and 16).

[0055] As shown in FIG. 9, after opposite ends of the surgical suture 40 are pulled out of the patient's body, when the operating stick 20 is rotated at an angle of 45 degrees counterclockwise, the guide protrusions 23 engaged with the inward groove 14a of the guide groove 14 are disengaged. When the operating stick 20 is then pushed, the opened wings 33 are closed. When the cone-shaped handle 11 is pulled out, the entire tubular body 10 of the laparoscopic port site closure device comes out of the patient's body. Here, the surgical suture is tied using the conventional suturing method, and the coil is removed (see FIG. 17).

[0056] When the cartridge 30 is replaced after using the laparoscopic port site closure device and the surgical suture therein, as shown in FIG. 11, the operating stick 20 is further rotated at an angle of 45 degrees counterclockwise. Here, the guide protrusions 23 of the operating stick are locked to the outward groove 14b of the crank shaped guide groove 14, and the outer protrusions 22 engaged with the locking channels 302 of the cartridge 30 are moved to an unlock location. Thereby, the cartridge 30 is detached from the operating stick 20 (see FIGS. 11 and 12).

[0057] The cartridge 30 detached from the operating stick 20 is still combined with the tubular body 10 because the inner protrusions 12 provided inside the tubular body 10 at the lower portion thereof are engaged with the link hole 333 and the ridge 334 of the wings 33. This engagement is configured such that the tubular body 10 is detached from the cartridge 30 by a user's physical force.

[0058] A new cartridge 30 is combined with the tubular body 10 in a reverse process so as to reuse the laparoscopic port site closure device.

[0059] The needle 50 is configured to catch and pull out the coil 42. Thus, the suture slot 52 for catching the surgical suture is longitudinally formed on the needle tip so as to pull out the surgical suture.

[0060] Further, each end of the surgical suture 40 may be provided with the coil so as to easily pull out the surgical suture using the needle, wherein the coil is made of a harmless metal material and is coiled into a spiral shape so as to be easily threaded through the needle. The coil maintains an original shape thereof using elasticity thereof, and the coil is extended by being caught in the needle. Here, a coil having enough elasticity and rigidity to be extended long may be used for the coil. Each end of the coil may be melted to form the ball-shaped stopper 43, whereby it is possible to manufacture a stopper having a simple structure through easy processing.

[0061] The stopper 43 of the coil prevents the coil from deviating from the suture slot 52 of the needle, and also prevents the surgical suture from being separated from the coil.

[0062] The surgical suture 40 is folded and received in the tubular case, and opposite ends of the surgical suture 40 are threaded through the wings 33 in order to use. The surgical suture may be provided in a state where the surgical suture is received in the cartridge.

[0063] The spiral coil 42 is capable of being threaded through the needle tip using a gap between spirals even when

the tip of the needle 50 is inserted not perfectly in the middle of the coil. Further, the spiral coil 42 is capable of being threaded through the needle tip using the gap between the spirals regardless of a direction where an opening of the suture slot 52 faces when inserted. Once the coil is caught in the suture slot 52 of the inserted needle tip, the stopper 43 of the coil is caught in the suture slot 52 by being pulled by the needle, thereby extending and being pulled outside.

Thus, it is possible to prevent failure in removing the surgical suture.

[0064] The present invention is capable of clearly removing the surgical suture when closing a port site, thereby helping the recovery of a patient by lowering the possibility of infection during the recovery. Further, the present invention is capable of realizing an easy procedure by having a handle manipulation structure that allows easy closure of the insertion site, thereby helping medical staff. Furthermore, the present invention is simple and economical because the cartridge receiving the surgical suture therein is replaceable.

[Description of reference characters of important parts]

10:	tubular body	11:	cone-shaped handle
21:	handle	12:	inner protrusions
22:	outer protrusions	23:	guide protrusions
311:	wing protrusions	13:	needle guide holes
14:	guide groove	20:	operating stick
30:	cartridge	32:	compartment
33:	wings	40:	surgical suture
42:	coil	43:	stopper
45:	case	46:	silicon tube
50:	needle	52:	suture slot
300:	first support	301:	mounting slot
302:	locking channels	310:	second support
320:	third support	322:	cover
331:	wing hole	333:	link hole
334:	ridge	335:	mounting hole
336:	communication slot		

Claims

1. A laparoscopic port site closure device, which is in a tube shape for being introduced into a port site, comprising: a tubular body provided with needle guides that face each other and guide insertion of a needle; wings mounted to a lower portion of the tubular body such that the wings are opened and closed through a cam method; and an operating stick penetrating through the tubular body to operate the wings by being rotated to push and open the wings and to pull and close the wings by being rotated reversely, the laparoscopic port site closure device further comprising:

a replaceable cartridge (30) provided on a lower end of the tubular body (10) to be detachably combined with the operating stick (20), wherein the cartridge (30) is provided with the wings (33) capable of being opened by operating the operating stick, and provided with a compartment (32) for receiving surgical suture (40) therein, wherein

the laparoscopic port site closure device is configured such that opposites ends of the surgical suture (40) in the compartment are threaded through the wings (33) such that the ends of the surgical suture are pulled out of a patient's body by being caught by a suture slot of a needle (50) that is pierced into the patient's body from outside.

2. The device of claim 1, wherein the tubular body (10) is divided into two parts, and includes a cone-shaped handle (11) and a tube that extends from the handle, wherein inner protrusions (12) are provided inside of the tube at a lower portion thereof at positions facing each other; needle guide holes (13) are provided on the handle (11) for guiding introduction and withdrawal of the needle, the needle guide holes ranging from an upper portion of the handle (11) to a side wall of the tube at opposite positions; and a crank-shaped guide groove (14) is provided inside the handle (11) and guides a rotation and forward-backward movement of the operating stick (20) and fixes a location of the operating stick.

3. The device of claim 1, wherein the operating stick (20) includes a handle (21) and a rod that extends from the handle,

with outer protrusions (22) provided at an end of the rod at opposite positions, and guide protrusions (23) provided below the handle (21) by protruding at opposite positions, the guide protrusions serving to mount and demount the cartridge (30) such that the cartridge is combined with the tubular body (10).

5 **4.** The device of claim 1, wherein the cartridge (30) includes:

10 a first support (300) including a mounting slot (301) provided in a center thereof, and locking channels (302) provided on opposite positions of an outer circumferential surface thereof;

15 a second support (310) provided beneath the first support, the second support being in a planar shape so as to support a surface of each of the wings (33), and including wing protrusions (311) disposed opposite to each other as a pivot of the wings;

20 a third support (320) being in a planar shape rotated at an angle of 90 degrees relative to the second support, having a width to come into close contact with the wings (33) when the wings are closed, and including the compartment (32) that is in a cone shape and is provided at a lowermost end thereof, and a cover (322) for covering the compartment; and

25 the wings (33) each including: a wing hole (331) for being engaged with the wing protrusions (311) of the second support (310); an arch-shaped link hole (333) that is provided outside the wing hole (331), the link hole (333) having an opening at an edge thereof with a ridge (334) provided by protruding in the opening; a mounting hole (335) for mounting an end of the surgical suture (40); and a communication slot (336) provided on an outer surface of the wing to communicate with the mounting hole (335), wherein the wings comprise a pair of wings that are disposed opposite to each other.


30 **5.** The device of claim 3, wherein when the cartridge (30) including the wings (33) is assembled with the tubular body, the cartridge shares a same center point as the tubular body and has no protruding surfaces.

35 **6.** The device of claim 3, wherein the compartment (32) includes a notch (337) provided at a portion of an outer surface thereof so as to serve as a suture outlet for the surgical suture that is received therein.


40 **7.** A laparoscopic port site closure device, which is in a tube shape for being introduced into a port site, the device comprising: a tubular body provided with needle guides that face each other and guide insertion of a needle; wings mounted to a lower portion of the tubular body such that the wings are opened and closed through a cam method; and an operating stick penetrating through the tubular body to operate the wings by being rotated to push and open the wings and to pull and close the wings by being rotated reversely, the laparoscopic port site closure device further comprising:

45 a needle (50) including a suture slot (52) for catching and pulling out surgical suture by being concavely formed on a needle tip in an opposite direction of pulling the surgical suture.


【FIG. 1】




【FIG. 2a】




【FIG. 2b】




【FIG. 3】




【FIG. 4a】




【FIG. 4b】




【FIG. 5】




【FIG. 6】




【FIG. 7】




【FIG. 8】




【FIG. 9】




【FIG. 10】




【FIG. 11】




【FIG. 12】




【FIG. 13】




【FIG. 14】




【FIG. 15】



【FIG. 16】



【FIG. 17】



INTERNATIONAL SEARCH REPORT

International application No.

PCT/KR2015/009109

A. CLASSIFICATION OF SUBJECT MATTER <i>A61B 17/03(2006.01)i, A61B 17/04(2006.01)i, A61B 17/34(2006.01)i</i> According to International Patent Classification (IPC) or to both national classification and IPC																		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) A61B 17/03; A61B 17/11; A61B 17/06; A61B 17/00; A61B 17/068; A61B 17/04; A61B 17/34																		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Korean Utility models and applications for Utility models: IPC as above Japanese Utility models and applications for Utility models: IPC as above																		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) eKOMPASS (KIPO internal) & Keywords: shutdown, guide, guide, blade, cartridge, suture, needle, change, detachment																		
C. DOCUMENTS CONSIDERED TO BE RELEVANT																		
<table border="1"> <thead> <tr> <th>Category*</th> <th>Citation of document, with indication, where appropriate, of the relevant passages</th> <th>Relevant to claim No.</th> </tr> </thead> <tbody> <tr> <td>Y</td> <td>JP 2012-515020 A (AXIOM TECHNOLOGY PARTNERS, LLC.) 05 July 2012 See abstract; claim 1; paragraphs [0033]-[0038], [0045]-[0049], [0055], [0057], [0070], [0079], [0080]; and figures 1, 9, 12, 29, 31.</td> <td>1-7</td> </tr> <tr> <td>Y</td> <td>KR 10-1132070 B1 (NATIONAL CANCER CENTER) 02 April 2012 See abstract; claims 3, 6; and figure 3.</td> <td>1-7</td> </tr> <tr> <td>A</td> <td>JP 2009-279464 A (SHO, Shoshi et al.) 03 December 2009 See abstract; claim 1; and figures 3-6.</td> <td>1-7</td> </tr> <tr> <td>A</td> <td>JP 2014-511205 A (APICA CARDIOVASCULAR LIMITED) 15 May 2014 See abstract; claim 1; and figure 1.</td> <td>1-7</td> </tr> <tr> <td>A</td> <td>US 5964773 A (GREENSTEIN, Robert J.) 12 October 1999 See abstract; claim 1; and figure 1.</td> <td>1-7</td> </tr> </tbody> </table>	Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.	Y	JP 2012-515020 A (AXIOM TECHNOLOGY PARTNERS, LLC.) 05 July 2012 See abstract; claim 1; paragraphs [0033]-[0038], [0045]-[0049], [0055], [0057], [0070], [0079], [0080]; and figures 1, 9, 12, 29, 31.	1-7	Y	KR 10-1132070 B1 (NATIONAL CANCER CENTER) 02 April 2012 See abstract; claims 3, 6; and figure 3.	1-7	A	JP 2009-279464 A (SHO, Shoshi et al.) 03 December 2009 See abstract; claim 1; and figures 3-6.	1-7	A	JP 2014-511205 A (APICA CARDIOVASCULAR LIMITED) 15 May 2014 See abstract; claim 1; and figure 1.	1-7	A	US 5964773 A (GREENSTEIN, Robert J.) 12 October 1999 See abstract; claim 1; and figure 1.	1-7
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.																
Y	JP 2012-515020 A (AXIOM TECHNOLOGY PARTNERS, LLC.) 05 July 2012 See abstract; claim 1; paragraphs [0033]-[0038], [0045]-[0049], [0055], [0057], [0070], [0079], [0080]; and figures 1, 9, 12, 29, 31.	1-7																
Y	KR 10-1132070 B1 (NATIONAL CANCER CENTER) 02 April 2012 See abstract; claims 3, 6; and figure 3.	1-7																
A	JP 2009-279464 A (SHO, Shoshi et al.) 03 December 2009 See abstract; claim 1; and figures 3-6.	1-7																
A	JP 2014-511205 A (APICA CARDIOVASCULAR LIMITED) 15 May 2014 See abstract; claim 1; and figure 1.	1-7																
A	US 5964773 A (GREENSTEIN, Robert J.) 12 October 1999 See abstract; claim 1; and figure 1.	1-7																
☐ Further documents are listed in the continuation of Box C. ☒ See patent family annex.																		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family																		
Date of the actual completion of the international search 07 DECEMBER 2015 (07.12.2015)	Date of mailing of the international search report 07 DECEMBER 2015 (07.12.2015)																	
Name and mailing address of the ISA/KR  Korean Intellectual Property Office Government Complex-Daejeon, 189 Seonsa-ro, Daejeon 302-701, Republic of Korea Facsimile No. 82-42-472-7140	Authorized officer Telephone No.																	

Form PCT/ISA/210 (second sheet) (January 2015)

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/KR2015/009109

Patent document cited in search report	Publication date	Patent family member	Publication date
JP 2012-515020 A	05/07/2012	CN 102318193 A	11/01/2012
		CN 102318193 B	06/08/2014
		EP 2385798 A2	16/11/2011
		EP 2386143 A1	16/11/2011
		EP 2386143 B1	29/05/2013
		JP 2015-110049 A	18/06/2015
		JP 5720031 B2	20/05/2015
		US 2012-0035623 A1	09/02/2012
		US 2012-0112947 A1	10/05/2012
		US 2015-119906 A1	30/04/2015
		US 8410969 B2	02/04/2013
		US 8926639 B2	06/01/2015
		WO 2010-081096 A2	15/07/2010
		WO 2010-081096 A3	16/12/2010
		WO 2010-081136 A1	15/07/2010
KR 10-1132070 B1	02/04/2012	KR 10-2011-0091054 A	11/08/2011
JP 2009-279464 A	03/12/2009	JP 2003-225241 A	12/08/2003
		JP 2005-161050 A	23/06/2005
		JP 2010-188153 A	02/09/2010
		JP 4405158 B2	27/01/2010
		JP 4624085 B2	02/02/2011
		JP 5048099 B2	17/10/2012
		US 2003-0181924 A1	25/09/2003
		US 2004-0147941 A1	29/07/2004
		US 2005-0149067 A1	07/07/2005
		US 2008-0114379 A1	15/05/2008
		US 2008-0114380 A1	15/05/2008
		US 7344545 B2	18/03/2008
		US 7530985 B2	12/05/2009
		US 7618425 B2	17/11/2009
		US 8016840 B2	13/09/2011
		US 8021376 B2	20/09/2011
JP 2014-511205 A	15/05/2014	AU 2012-211082 A2	29/08/2013
		CA 2824936 A1	02/08/2012
		EP 2667792 A2	04/12/2013
		US 2013-338706 A1	19/12/2013
		WO 2012-103546 A2	02/08/2012
		WO 2012-103546 A3	01/11/2012
US 5964773 A	12/10/1999	US 5964773 A	12/10/1999

专利名称(译)	腹腔镜端口部位闭合装置		
公开(公告)号	EP3222219A1	公开(公告)日	2017-09-27
申请号	EP2015858114	申请日	2015-08-31
[标]申请(专利权)人(译)	金基成		
申请(专利权)人(译)	KIM , KI SEONG		
当前申请(专利权)人(译)	KIM , KI SEONG		
[标]发明人	KIM KI SEONG		
发明人	KIM, KI SEONG		
IPC分类号	A61B17/03 A61B17/04 A61B17/34		
CPC分类号	A61B17/0482 A61B17/0483 A61B17/0485 A61B17/3403 A61B2017/06042 A61B2017/3405 A61B17/0057 A61B17/06109 A61B17/06119 A61B2017/00473 A61B2017/00637 A61B2017/00663 A61B17/34 A61B17/04 A61B2017/0461 A61B17/06004 A61B17/06114 A61B2017/0023		
优先权	1020140163452 2014-11-21 KR		
其他公开文献	EP3222219A4		
外部链接	Espacenet		

摘要(译)

公开了一种腹腔镜端口部位闭合装置。该装置被配置成使得在其中接收外科缝合线的药筒设置在针引导件的前端处，用于端口部位闭合；手术缝合线被针尖夹住，针尖被针导向器刺穿过身体组织；当针被抽出时，手术缝合线沿着穿过针刺入组织的路径被拉出，并且手术缝合线被绑在患者体外，从而能够关闭腹腔镜端口部位。

【FIG. 5】

