

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 November 2001 (29.11.2001)

PCT

(10) International Publication Number
WO 01/89397 A1

(51) International Patent Classification⁷: **A61B 17/34**

[GB/GB]; 31 Spring Valley Drive, Bramley, Leeds LS13 4RN (GB). **ALMOND, Thomas, Edward** [GB/GB]; 12 West end Rise, Horsforth, Leeds LS18 5JL (GB).

(21) International Application Number: PCT/GB01/02281

(22) International Filing Date: 24 May 2001 (24.05.2001)

(74) Agent: **BROWNE, Robin, Forsythe**; Urquhart-Dykes & Lord, Tower House, Merrion Way, Leeds LS2 8PA (GB).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0012461.0 24 May 2000 (24.05.2000) GB


(71) Applicant (for all designated States except US): **SURGICAL INNOVATIONS LTD** [GB/GB]; Clayton Park, Clayton Wood Rise, Leeds LS16 6RF (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

[Continued on next page]

(54) Title: SURGICAL SEAL



(57) Abstract: A seal for laparoscopic port comprising: a base adapted to engage a cannula, the base including an axial aperture for a surgical instrument; a multiplicity of jaws mounted on the base, the jaws being moveable radially with respect to the aperture between an open position wherein the shaft of the surgical instrument may pass freely and the closed position wherein the jaws engage said shaft and provide a restraining force restraining radial movement of the shaft; and an actuator rotatable to urge the jaws to move between said open position and said closed position.

WO 01/89397 A1



IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

SURGICAL SEAL

This invention relates to a seal for use with a surgical instrument to provide a gas tight seal through which the instrument may pass. The invention relates particularly but not exclusively to a seal for a laparoscopic port.

Laparoscopic procedures are performed through a small incision, usually through narrow endoscopic tubes or cannulae inserted through a small entrance incision in the skin. An instrument inserted into the body must be sealed to ensure that gases do not enter or exit through the incision, for example in procedures in which the surgical region is insufflated. The introduction of a tube into an anatomical cavity such as the abdominal cavity is usually achieved using a trocar and cannula assembly. The cannula assembly may comprise a cannula attached to a cannula housing which generally includes a valve assembly adapted to maintain a seal across the opening of the valve assembly both with and without an instrument inserted through it. Various valve systems for cannula assemblies have been proposed, for example in US 5209737, US 5308336, US 5385553 and US 5545142. US 5603702 discloses a complex structure with several hinged guard members disposed in an overlapping petal-like arrangement. US 5407433 and US 5411483 disclose universal seals for laparoscopic ports. However these suffer from the disadvantage that the entire seal can move in an orbital manner. This can cause failure of the seal between the gasket and instrument during surgery.

Furthermore the friction between the annular gasket of US 5411483 and the shaft of the instrument depends on the diameter of the shaft. High frictional forces are undesirable because they impede free movement of the instrument during surgery.

According to the present invention a seal for a laparoscopic port comprises:
a base adapted to engage a cannula, the base including an axial aperture for a surgical instrument;

a multiplicity of jaws mounted on the base, the jaws being moveable radially with respect to the aperture between an open position wherein a shaft of the surgical instrument may pass freely and a closed position wherein the jaws engage said shaft and provide a restraining force restraining radial movement of the shaft; and

-2-

actuator rotatable to urge the jaws to move between said open position and said closed position.

In preferred embodiments the jaws may engage or restrain shafts having different diameters. In this way a single seal may be used with several instruments. In particularly preferred embodiments the jaws may be adjusted to engage a shaft having any diameter between preselected upper and lower limits.

The jaws are preferably moveable along guides provided on the carrier plate. The guides may constitute channels between raised formations, tracks or runners. Each jaw preferably comprises a follower member adapted to be received in a respective guideway in the actuator arranged so that rotation of the actuator causes radial movement of the jaw.

In a particularly preferred embodiment of the invention each guideway comprises an arcuate channel formed in the actuator, a projection or other follower being received in the channel.

The channels may have the configuration of parabolic curves.

The seal of this invention may include a diaphragm adapted to contact the shaft of a surgical instrument extending through the aperture. The diaphragm preferably includes a lip, each jaw including a radially outwardly facing portion adapted to engage the lip so that the aperture of the diaphragm is forced to open as the jaws move to the open position.

The aperture of the jaws is preferably continuously adjustable between maximum and minimum positions. This allows the seal to accommodate various sizes of instrument shafts. A further advantage is that the jaws may be opened to facilitate removal of tissue samples during a surgical procedure.

Seals in accordance with this invention may be used with a variety of laparoscopic instruments. Most instruments have a smooth coaxial point at the distal end to facilitate insertion through the cannula and seal. However spiked instruments, for example clip applicators or pyramidal trocars may damage the diaphragm as the instrument is inserted through the seal.

In preferred embodiments of this invention a multiplicity of shield members are disposed on the proximal side of the diaphragm to prevent accidental damage to the diaphragm. The shield members are preferably moveable radially between open and closed positions in the same direction and at the same time, that is synchronously with the jaws. Preferably each shield member is attached to a respective jaw.

-3-

The shield members may be interleaved to form a continuous barrier covering the diaphragm, for example arranged like the petals of an iris shaped configuration. Alternatively the shield members may be in alternating forward and backward axial disposition to form a continuous interleaved barrier.

In a particularly preferred embodiment each jaw member has two laterally extending wing-like shield flanges arranged to extend generally circumferentially of the surgical instrument receiving aperture, one or more shield members being axially forward of the other to engage a complimentary shield member on an adjacent jaw.

The actuator may be arranged so that the jaws may be fully opened or closed by a rotation through an angle of 30 to 180°. This makes it easy for a surgeon to open or close the jaws using his fingers but without rotation of the wrist.

A top cover may be placed over the actuator to prevent occlusion of the moving parts and ingress of dirt during use.

Any convenient number of jaws may be provided, preferably at least 5 or more, more preferably 6 to 8, most preferably 7.

The invention is further described by means of example but not in any limitative sense with reference to the accompanying drawings of which:

Figure 1 is an exploded view of a seal in accordance with the invention.

Figure 2 represents three plan views of the seal.

Figure 3 represents three plan views of the seal illustrating closing of the jaws.

Figure 4 is a perspective view of a jaw of a seal in accordance with a preferred embodiment of the invention.

Figure 5 shows plan and elevational views on reduced scale of the jaw shown in Figure 4.

Figure 6 shows an assembly of seven jaws in a circular array.

Figure 7 shows the array of jaws of Figures 6 contained in the carrier plate.

Figures 8 to 10 are plan views illustrating the opening of the jaws.

The seal illustrated in the Figures comprises a base 1 having a locking device 2 adapted to facilitate attachment to a cannula. In an alternative embodiment of the invention the base 1 may be integral with a cannula.

A diaphragm or gasket 3 composed of elastomeric material lies within the base 1. The diaphragm includes an inner surface 4 adapted to receive the base of a carrier plate 18.

-4-

An annular lip 5 is adapted to receive and form a gas tight seal with the shaft of an instrument (not shown). The inwardly facing surface 16 of a flange 17 extends axially from the diaphragm adjacent the rim 5. Outward movement of the flange 17 opens the aperture defined by the rim 5.

The carrier plate 18 includes a multiplicity of guideways 9 formed by axially extending runners 9. A moveable jaw member 6 can move radially within each guide way 9 in use. In the illustrated embodiment there are six jaws. Each jaw contains a radially inwardly facing tooth 16 and radially outwardly facing hook portion 7. The hook portion 7 engages the surface 16 of the diaphragm flange 17. The tooth portion 16 of each jaw serves to engage the shaft of a surgical instrument passing through the seal. A lug 8 extending axially from the upper surface of the jaw as shown is received in a channel 14 of the upper surface 13 of the actuator 12. The actuator has a generally cylindrical outer surface which may be rotated manually by a surgeon in use. The channels 14 each have a parabolic curved configuration and are spaced equidistantly around the upper surface 13 of the actuator. The configuration of the channels 14 may have the general form of an iris. Rotation of the actuator 12 causes the lugs and consequently the jaws to move radially inwardly or outwardly relative to the carrier 18. Accordingly the teeth 16 of the jaws 6 may move into and out of engagement with a shaft (not shown) extending through the aperture 15 of the seal. During opening of the jaws, the hooked portion 7 dilate the lip 5 of the gasket so that a generally even frictional force is encountered irrespective of the diameter of the shaft.

Figures 2a, b and c show the seal with the jaws in different positions. The same reference numerals are used to denote like components in Figures 1, 2 and 3.

In Figure 2a the jaws are open with the teeth 16 retracted. When the seal is engaged to a cannula, rotation of the actuator 12 in a clockwise direction causes the lugs 8 and consequently the jaws to move radially inwardly as shown in Figure 2b.

Figure 2c is a partially cut away view illustrating the jaws in the closed position.

The relative positions of the lugs 8 in the channels 14 are shown in Figures 3a, b and c. In Figure 3c the lugs are at the inner-most ends of the channels 14 so that the jaws are closed to the maximum extent. Rotation of the actuator 12 shown in Figure 3c in an anti-clockwise direction causes the jaws to move radially outwardly. Full opening of the jaws is achieved by rotation of the actuator through about 60°.

-5-

The curvature of the channels 14 is selected so that outward pressure on a jaw by lateral movement of the shaft of the surgical instrument is sufficient to overcome frictional forces within the seal. Accordingly lateral movement of the shaft cannot open the jaws. The shaft is securely held and cannot move in an orbital motion to break the seal with the gasket lip 5. Similarly a larger diameter shaft which engages the jaws in Figure 3b is also securely held. However the jaws may be easily opened by a surgeon to facilitate removal of the instrument, for example with a tissue sample of a larger diameter than the shaft.

The seal of this invention may incorporate a top cover, for example formed from transparent waterproof material to prevent ingress of dirt or physiological material between the moving surfaces of the seal.

Figures 4 to 8 illustrate a preferred seal for a laparoscopic port in accordance with this invention. The arrangement is generally similar to that shown in Figures 1 to 3.

The moveable jaw member 20 shown in Figures 4 and 5 include a radially inwardly facing tooth 21 and a radially outwardly facing hook portion 22. The hook portion is arranged to engage the surface of the diaphragm, not shown. The jaw member 20 has flange shaped shield members 23, 24 extending laterally from the jaw member so that the shield members extend generally circumferentially of the axially extending instrument receiving aperture.

The jaws are arranged to form a circular array, for example comprising 7 jaws as shown in Figure 6. This shield member 23 is disposed axially distally of the shield member 24 so that it underlies a radially inwardly extending ring 24 of an adjacent jaw as shown in Figure 6. In this way a continuous annular shield is formed protecting the less flexible body of the diaphragm 26 from damage by a trocars or other pointed instrument.

Figure 7 shows the jaws located in the carrier plate 25. The jaws are each able to slide radially within guideways in the carrier plate.

Figures 8 to 10 show successive stages in opening of the jaws within the carrier plate 25. The hooked portions 22 (not visible in Figures 8 to 10) engage a complementary ring in the diaphragm 26 (opening the central aperture as the jaws are withdrawn). In Figure 8 the central aperture has a small diameter D1 and the shield members 24 almost completely cover the underlying diaphragm. In Figure 9 a larger diameter aperture D2 results from opening of the jaws exposing the underlying, radially outward shield members 23. The shield members 23, 24 define a seven sided polygonal configuration.

-6-

In Figure 10 a maximum diameter aperture D3 results from full opening of the jaws exposing the shield members 23, 24 to a maximum extent.

CLAIMS

1. A seal for laparoscopic port comprising:
a base adapted to engage a cannula, the base including an axial aperture for a surgical instrument;
a multiplicity of jaws mounted on the base, the jaws being moveable radially with respect to the aperture between an open position wherein the shaft of the surgical instrument may pass freely and the closed position wherein the jaws engage said shaft and provide a restraining force restraining radial movement of the shaft; and
an actuator rotatable to urge the jaws to move between said open position and said closed position.
2. A seal as claimed in claim 1, wherein the jaws may be adjusted to engage a shaft having any diameter between preselected upper and lower limits.
3. A seal as claimed in any preceding claim, wherein the jaws are moveable along guides on the carrier plate.
4. A seal as claimed in claim 3 wherein the guides comprise channels between raised formations, tracks or runners.
5. A seal as claimed in claim 4, wherein each jaw comprises a follower member adapted to be received in a respective guideway in an actuator arranged so that rotation of the actuator causes radial movement of the jaw.
6. A seal as claimed in claim 5, wherein each guideway comprises an arcuate channel formed in the actuator, a projection or other follower being received in the channel.
7. A seal as claimed in claim 6, wherein the channels have the configuration of parabolic curves.

-8-

8. A seal as claimed in any preceding claim, including a diaphragm adapted to contact the shaft of a surgical instrument extending through the aperture.

9. A seal as claimed in claim 8, wherein the diaphragm includes a lip, each jaw including a radially outwardly facing portion adapted to engage the lip so that the aperture of the diaphragm is forced to open as the jaws move to an open position.

10. A seal as claimed in any preceding claim, wherein the aperture of the jaws is continuously adjustable between maximum and minimum positions.

11. An actuator as claimed in any preceding claim, wherein the jaws may be fully opened or closed by a rotation through an angle of 30 to 180°.

12. A seal as claimed in any preceding claim, including a multiplicity of shield members disposed on the proximal side of the diaphragm to prevent accidental damage to the diaphragm in use.

13. A seal as claimed in claim 12, wherein the shield members are moveable radially between open and closed positions synchronously with the jaws.

14. A seal as claimed in claim 13, wherein each shield member is attached to a respective jaw.

15. A seal as claimed in claim 14, wherein the shield members are interleaved to form a continuous barrier covering the diaphragm.

16. A seal as claimed in any preceding claim, wherein each jaw member has two laterally extending shield members.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

-9/9-




FIG. 10

INTERNATIONAL SEARCH REPORT

Intern: Application No
PCT/GB 01/02281

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61B17/34

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 820 600 A (ORTH MIKE ET AL) 13 October 1998 (1998-10-13) column 9, line 61 - column 10, line 19; figures 5A,B,4 ---	1-8, 10-16
X	EP 0 630 660 A (U.S.S.C.) 28 December 1994 (1994-12-28) column 12, line 14 - line 55; figures 8-10 ---	1,2,8-10
X	DE 39 15 597 C (WOLF) 10 May 1990 (1990-05-10) column 1, line 42 - line 62; figures 1-3 ---	1-4
A	US 5 603 702 A (SMITH ROBERT C ET AL) 18 February 1997 (1997-02-18) cited in the application abstract; figures 5,6 --- -/--	12-16

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

6 September 2001

Date of mailing of the international search report

13/09/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Moers, R

INTERNATIONAL SEARCH REPORT

Intern: Application No
PCT/GB 01/02281

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3 920 215 A (KNAUF DIETER W) 18 November 1975 (1975-11-18) column 2, line 15 -column 3, line 19; figures 1-3 ----	3-7
A	EP 0 426 407 A (APPLIED VASCULAR DEVICES INC) 8 May 1991 (1991-05-08) abstract; figures 1-7 -----	3-7

INTERNATIONAL SEARCH REPORT

Information on patent family members

Intern Application No

PCT/GB 01/02281

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5820600 A	13-10-1998	EP 0904120 A JP 2000510731 T WO 9742991 A	31-03-1999 22-08-2000 20-11-1997
EP 630660 A	28-12-1994	US 5492304 A CA 2123956 A DE 69414471 D DE 69414471 T ES 2123684 T US 5657963 A	20-02-1996 17-12-1994 17-12-1998 20-05-1999 16-01-1999 19-08-1997
DE 3915597 C	10-05-1990	DE 59004853 D EP 0396882 A US 4985033 A	14-04-1994 14-11-1990 15-01-1991
US 5603702 A	18-02-1997	AU 692275 B AU 2840895 A CA 2154125 A DE 69505750 D DE 69505750 T EP 0696459 A ES 2123192 T JP 8057056 A US 5895377 A	04-06-1998 22-02-1996 09-02-1996 10-12-1998 06-05-1999 14-02-1996 01-01-1999 05-03-1996 20-04-1999
US 3920215 A	18-11-1975	NONE	
EP 0426407 A	08-05-1991	US 5127626 A CA 2028896 A DE 69020686 D DE 69020686 T DE 426407 T JP 3184566 A	07-07-1992 01-05-1991 10-08-1995 02-11-1995 23-07-1992 12-08-1991

专利名称(译)	手术密封		
公开(公告)号	EP1284664A1	公开(公告)日	2003-02-26
申请号	EP2001936612	申请日	2001-05-24
申请(专利权)人(译)	手术INNOVATIONS LIMITED		
当前申请(专利权)人(译)	应用医疗资源INC.		
[标]发明人	MORAN PETER ALMOND THOMAS EDWARD		
发明人	MORAN, PETER ALMOND, THOMAS EDWARD		
IPC分类号	A61B1/00 A61B17/34		
CPC分类号	A61B17/3462 A61B2017/3464 A61B2017/347		
优先权	2000012461 2000-05-24 GB		
其他公开文献	EP1284664B1		
外部链接	Espacenet		

摘要(译)

一种用于腹腔镜端口的密封件，包括：适于接合套管的基座，所述基座包括用于手术器械的轴向孔；多个钳口安装在基座上，钳口可相对于孔径向移动，在打开位置和手术器械的轴可以自由通过的位置和闭合位置，其中钳口接合所述轴并提供限制径向的约束力轴的运动；和致动器，其可旋转以促使钳口在所述打开位置和所述关闭位置之间移动。