



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
11.02.2015 Bulletin 2015/07

(51) Int Cl.:
A61F 2/00 (2006.01) **A61B 17/42 (2006.01)**

(21) Application number: **14179669.8**

(22) Date of filing: **04.08.2014**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME

(71) Applicant: **Coloplast A/S**
3050 Humlebaek (DK)

(72) Inventor: **Shariati, Amir**
Parkland, FL Florida 33076 (US)

(30) Priority: **05.08.2013 US 201361862386 P**
01.08.2014 US 201414449459

(54) **Hysteropexy mesh apparatuses**

(57) The invention describes a hysteropexy mesh 10 comprising an anterior vaginal portion 12, a right broad ligament portion 14, a left broad ligament portion 16, a sacral portion 18, and a posterior vaginal portion 20. In the illustrated embodiment, anterior vaginal portion 12 is substantially rectangular in shape with a major dimension 121 of about 10 cm and a minor dimension 122 of about 4.0 cm.

Right broad ligament portion 14 extends from the long edge of anterior vaginal portion 12, left broad ligament portion 16 extends from the other long edge of anterior vaginal portion 12.

Right and left broad ligament portions 14 and 16 are substantially L-shaped. Each of the broad ligament portions has a thickness dimension 142 of about 1.2 cm and a major dimension 141 of about 3.5 cm.

Left broad ligament portion 16 is between anterior vaginal portion 12 and posterior vaginal portion 20. Posterior vaginal portion 20 is substantially rectangular in shape and has a major dimension 201 of about 15 cm and a minor dimension 202 of about 4.0 cm.

Sacral portion 18 is substantially rectangular in shape and has a major dimension 181 of about 8 cm and a minor dimension 202 of about 4.0 cm.




FIG. 1

Description

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of Provisional Application Serial No. 61/862,386, filed August 5, 2013, the contents of which are incorporated herein in their entirety for all purposes.

FIELD OF THE INVENTION

[0002] The invention relates generally to apparatuses and methods for performing hysteropexy.

BACKGROUND OF THE INVENTION

[0003] Uterine prolapse occurs when pelvic floor muscles and ligaments stretch and weaken, providing inadequate support for the uterus. The uterus then descends into or protrudes from the vagina. Uterine prolapse can happen to women of any age, but it often affects postmenopausal women who've had one or more vaginal deliveries. Damage to supportive tissues during pregnancy and childbirth, effects of gravity, loss of estrogen, and repeated straining over the years all can weaken the pelvic floor and lead to uterine prolapse.

[0004] At the present time, sacral colpopexy is the gold standard procedure for post-hysterectomy patients who have vaginal vault prolapse. Patients who still have their uterus and are undergoing sacral colpopexy are having a total hysterectomy or a supracervical hysterectomy at the same time. This can lead to mesh erosion. The only reason that most hysterectomies are performed is because the appropriate mesh that can provide anterior, posterior, and apical uterine support is not available. Hysteropexy is the surgical fixation of a displaced uterus. The hysteropexies that are performed at the present time are either supporting the uterus by placing the mesh anteriorly or posteriorly.

BRIEF SUMMARY OF THE INVENTION

[0005] The present invention provides embodiments of apparatuses and methods configured for use in hysteropexy and methods of using the same.

[0006] In one embodiment, a hysteropexy is presented comprising a hysteropexy mesh comprising: an anterior vaginal portion, substantially rectangular in shape, having a major dimension of about 10 cm and a minor dimension of about 4.0 cm; a right broad ligament portion, substantially L-shaped, extending from one long edge of the anterior vaginal portion and having a thickness dimension about 1.2 cm and a major dimension of about 3.5 cm; a left broad ligament portion, substantially L-shaped, extending from the other long edge of the anterior vaginal portion and having a thickness dimension about 1.2 cm and a major dimension of about 3.5 cm; a sacral portion, substantially rectangular in shape, having

a major dimension of about 8.0 cm and a minor dimension of about 4.0 cm; and a posterior vaginal portion, substantially rectangular in shape, having a major dimension of about 15 cm and a minor dimension of about 4.0 cm; where the left broad ligament portion extends between and connects the anterior vaginal portion and the posterior vaginal portion.

[0007] In another embodiment the hysteropexy mesh comprises one of polypropylene, polyester, polyethylene, silicone, a urethane, a polyurethane, copolymers, or block copolymers thereof.

[0008] In another embodiment a method of treating hysteropexy is provided comprising: create a peritoneal incision just above the rectum; separate rectum from the posterior aspect of the vagina by dissection until the perineal body is reached and the levator muscles are exposed; penetrate peritoneum overlying the sacral promontory and inferiorly dissected to meet posterior dissection from cul de sac; identify and clear off anterior longitudinal ligament and presacral vessels on the sacral promontory; manipulate uterus to create vesicouterine fascia incision and bladder flap; dissect vesicovaginal space to separate the bladder from the anterior aspect of the vagina until the level of the trigone is reached; create broad ligament incisions on each side near the cervix; insert hysteropexy mesh and attach by suture the posterior vaginal portion of the mesh to the posterior aspect of the vagina; pass folded anterior vaginal portion and right and left broad ligament arms through incision in the broad ligament on the left; unfold anterior vaginal portion and attach by suture to the anterior aspect of the vagina; pass right broad ligament portion through incision in the broad ligament on the right; manipulate uterus and attach right broad ligament portion of mesh to posterior vaginal portion of mesh and the posterior aspect of the cervix; attach sacral portion of mesh to the anterior longitudinal ligament at the level of the S1 vertebrae by suture in a tension free fashion; close peritoneal incision made on the sacrum by suture and cover with the bladder peritoneum using another suture; and close any remaining incisions to complete procedure.

[0009] In another embodiment the hysteropexy procedure is performed robotically, laparoscopically, or in open surgery through a laparotomy incision.

[0010] In yet another embodiment a medical device kit is provided comprising the hysteropexy mesh of the current disclosure and instructions for implantation.

[0011] Although the present invention has been described with reference to preferred embodiments, persons skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention. All references cited throughout the specification, including those in the background, are incorporated herein in their entirety. Those skilled in the art will recognize, or be able to ascertain, using no more than routine experimentation, many equivalents to specific embodiments of the invention described specifically herein. Such equivalents are intended to be

encompassed in the scope of the following claims.

[0012] While multiple embodiments are disclosed, still other embodiments of the present invention will become apparent to those skilled in the art from the following detailed description. As will be apparent, the invention is capable of modifications in various obvious aspects, all without departing from the spirit and scope of the present invention. Accordingly, the detailed descriptions are to be regarded as illustrative in nature and not restrictive.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013]

FIG. 1 is a plan view of an embodiment of a hysteropexy mesh comprising an anterior vaginal portion, a right broad ligament portion, a left broad ligament portion, a sacral portion, and a posterior vaginal portion.

FIG. 2 is a plan view of an embodiment of a hysteropexy mesh with anterior vaginal portion folded along its longitudinal midline.

FIG. 3 is an anterior view of an embodiment of a hysteropexy mesh implanted in the pelvic region showing the uterus, the pubic bone, and the anterior vagina.

FIG. 4 is a posterior view of an embodiment of a hysteropexy mesh implanted in the pelvic region showing the uterus, the broad ligament, and a portion of the sacrum.

FIG. 5 is a lateral view of an embodiment of a hysteropexy mesh implanted in the pelvic region showing the pubic bone, the bladder, the uterus, the rectum, and the sacrum.

DETAILED DESCRIPTION

[0014] Embodiments and methods for using a hysteropexy mesh configured to be implanted in the pelvic region of a patient are discussed below.

[0015] A plan view of an embodiment of a hysteropexy mesh 10 is shown in FIG. 1. Mesh 10 comprises an anterior vaginal portion 12, a right broad ligament portion 14, a left broad ligament portion 16, a sacral portion 18, and a posterior vaginal portion 20.

[0016] In the illustrated embodiment, mesh 10 is an integral mesh, and each of the above-identified portions 12-20 are regions of the whole. In such embodiments, mesh 10 may be cut, stamped, or otherwise machined from a single sheet of mesh.

[0017] In other embodiments, the portions may be separate or separable. For example, in certain embodiments, anterior vaginal portion 12, right broad ligament portion 14, and left broad ligament portion 16 may comprise one

integral mesh, sacral portion 18 may comprise a second integral mesh, and posterior vaginal portion 20 may comprise a third integral mesh, and these may be coupled to each other, such as with a suture or an ultrasonic weld.

[0018] In the illustrated embodiment, anterior vaginal portion 12 is substantially rectangular in shape with a major dimension 121 of about 10 cm and a minor dimension 122 of about 4.0 cm.

[0019] Right broad ligament portion 14 extends from the long edge of anterior vaginal portion 12, such that an edge of right broad ligament portion 14 is in common (i.e., substantially aligned) with a short edge of anterior vaginal portion 12.

[0020] Left broad ligament portion 16 extends from the other long edge of anterior vaginal portion 12, such that an edge of left broad ligament portion 16 is in common (i.e., substantially aligned) with the same short edge of anterior vaginal portion 12 and the edge of right broad ligament portion 14.

[0021] Right and left broad ligament portions 14 and 16 are substantially L-shaped, and may be rounded as shown in FIG. 1. Each of the broad ligament portions has a thickness dimension 142 of about 1.2 cm and a major dimension 141 of about 3.5 cm.

[0022] Left broad ligament portion 16 is between anterior vaginal portion 12 and posterior vaginal portion 20. Posterior vaginal portion 20 is substantially rectangular in shape and has a major dimension 201 of about 15 cm and a minor dimension 202 of about 4.0 cm. The edge of left broad ligament portion 16 that is in common with the edge of anterior vaginal portion 12 and the edge of right broad ligament portion 14 is also in common with a short edge of posterior vaginal portion 20.

[0023] Sacral portion 18 is substantially rectangular in shape and has a major dimension 181 of about 8 cm and a minor dimension 202 of about 4.0 cm.

[0024] As shown in FIG. 2, mesh 10 is configured to be folded substantially along the longitudinal midline of anterior vaginal portion 12 and is further configured to be folded between sacral portion 18 and posterior vaginal portion 20. In certain embodiments, mesh 10 is packaged as depicted in FIG. 2, such that mesh 10 is folded substantially along the longitudinal midline of anterior vaginal portion 12 and between sacral portion 18 and posterior vaginal portion 20. In such embodiments, mesh 10 may be removed from the packaging, passed through the left side broad ligament incision, then unfolded to be attached to the anterior vaginal wall.

[0025] FIGS. 3-5 are anterior, posterior, and lateral illustrations, respectively, of mesh 10 implanted into the pelvic region of a patient. FIG. 3 is an anterior view of mesh 10 implanted in the pelvic region showing the uterus 300, the pubic bone 303, and the anterior vagina 307. FIG. 4 is a posterior view of mesh 10 implanted in the pelvic region showing uterus 300, the broad ligament 304, and a portion of the sacrum 305. FIG. 5 is a lateral view of mesh 10 implanted in the pelvic region showing pubic bone 303, bladder 306, uterus 300, rectum 308,

and sacrum 305. These figures may be reference to better understand the steps of embodiments of the method discussed below.

[0026] In one embodiment, the mesh 10 is a knitted monofilament polypropylene mesh having a mass per area between approximately 15-35 g/m² with a pore size between approximately 500-1500 μm and a thickness of approximately 260 μm. This mesh is thin and light weight (i.e., the basis weight is less than approximately 35 g/m²) to provide a thin and comfortable mesh that is less likely to erode tissue that contacts the mesh and less likely to be sensed through the tissue layers by the patient. Other suitable materials for the support include fabrics formed from polyester, polyethylene, silicone, urethanes, polyurethanes, copolymers, or block copolymers of these or suitably similar polymeric materials. Suitable such knitted monofilament polypropylene mesh is available from Coloplast Corp., Minneapolis, MN. Other suitable woven polypropylene mesh material is available from, for example, HemiaMesh, Chivasso, Italy.

[0027] Embodiments of the disclosed method may be performed robotically, laparoscopically, or in open surgery through a laparotomy incision.

[0028] In embodiments where the method is performed robotically, a uterine manipulator may be placed vaginally to allow for manipulation of uterus 300 for the anterior and posterior dissection of the vaginal walls and attachment of the mesh. Then a robotic tenaculum may be used to grab the fundus of the uterus to manipulate the uterus for the anterior and posterior dissection of the vaginal walls and attachment of the mesh. A tenaculum can then be used through an accessory port to be placed on the fundus of the uterus to manipulate the uterus for the anterior and posterior dissection of the vaginal walls and attachment of the mesh.

[0029] In embodiments where the procedure is being performed laparoscopically, the tenaculum may be used to be placed on the fundus of uterus 300 to manipulate uterus 300 for the anterior and posterior dissection of the vaginal walls and attachment of the mesh or a uterine manipulator may be placed vaginally to allow for manipulation of uterus 300 for the anterior and posterior dissection of the vaginal walls and attachment of the mesh.

[0030] In embodiments where the procedure is being performed open through a laparotomy incision a uterine manipulator may be placed vaginally to allow for manipulation of uterus 300 for the anterior and posterior dissection of the vaginal walls and attachment of the mesh.

[0031] In the disclosed embodiments, the other steps of the method may be performed as follows.

[0032] Uterus 300 is elevated so the posterior vagina is visualized. An incision is made in the peritoneum just above the rectum 308. Dissection is then performed bluntly and sharply in the rectovaginal space to separate rectum 308 from the posterior aspect of the vagina until the perineal body is reached and the levator muscles are exposed.

[0033] After that, the peritoneum overlying the sacral

promontory is tented up and entered sharply with scissors. The peritoneal dissection is then carried inferiorly to meet the dissection posteriorly in the cul de sac below. The anterior longitudinal ligament as well as the presacral vessels on the sacral promontory are identified and cleared off.

[0034] Uterus 300 is then pulled dorsally and apically so that the anterior aspect of uterus 300 and the vagina are visualized. An incision is made in the vesicouterine fascia and the bladder flap is created sharply. The dissection is performed bluntly and sharply in the vesicovaginal space to separate the bladder from the anterior aspect of the vagina. This is done until the level of the trigone is reached.

[0035] Two one-centimeter incisions 301, 302 are made with the use of scissors and/or cautery in the broad ligament on each side near the cervix.

[0036] Then, posterior vaginal portion 20 of mesh 10 is attached to the posterior aspect of the vagina, such as with interrupted sutures.

[0037] The folded anterior vaginal portion 12 and the right and left broad ligament arms 14, 16 are then passed through incision 301 in the broad ligament on the left.

[0038] Anterior vaginal portion 12 is then unfolded and attached to the anterior aspect of the vagina using interrupted sutures.

[0039] Right broad ligament portion 14 is then passed through incision 302 in the broad ligament on the right. Uterus 300 is then lifted again, such as with a tenaculum or a manipulator and right broad ligament portion 14 of mesh 10 is attached to posterior vaginal portion 20 of mesh 10 and the posterior aspect of the cervix. Sacral portion 18 of mesh 10 is then attached to the anterior longitudinal ligament at the level of the S1 vertebrae, such as with two interrupted sutures in tension free fashion.

[0040] To minimize exposure of the mesh to intraperitoneal organs, posterior vaginal portion 20 of mesh 10 and the peritoneal incision made on the sacrum are then closed using absorbable suture. Anterior vaginal portion 12 of mesh 10 is then covered with the bladder peritoneum using another absorbable suture. Any remaining incisions are closed and the surgery is complete.

[0041] In the specification and in the claims, the terms "including" and "comprising" are open-ended terms and should be interpreted to mean "including, but not limited to...." These terms encompass the more restrictive terms "consisting essentially of" and "consisting of."

[0042] It must be noted that as used herein and in the appended claims, the singular forms "a", "an", and "the" include plural reference unless the context clearly dictates otherwise. As well, the terms "a" (or "an"), "one or more" and "at least one" can be used interchangeably herein. It is also to be noted that the terms "comprising", "including", "characterized by" and "having" can be used interchangeably.

[0043] Unless defined otherwise, all technical and scientific terms used herein have the same meanings as commonly understood by one of ordinary skill in the art

to which this invention belongs. All publications and patents specifically mentioned herein are incorporated by reference in their entirety for all purposes including describing and disclosing the chemicals, instruments, statistical analyses and methodologies which are reported in the publications which might be used in connection with the invention. All references cited in this specification are to be taken as indicative of the level of skill in the art. Nothing herein is to be construed as an admission that the invention is not entitled to antedate such disclosure by virtue of prior invention.

[0044] The following paragraphs enumerated consecutively from 1 to 6 provide for various aspects of the present invention.

[0045] In one embodiment, in a first paragraph (1), the present invention provides a hysteropexy mesh comprising: an anterior vaginal portion, substantially rectangular in shape, having a major dimension of about 10 cm and a minor dimension of about 4.0 cm; a right broad ligament portion, substantially L-shaped, extending from one long edge of the anterior vaginal portion and having a thickness dimension about 1.2 cm and a major dimension of about 3.5 cm; a left broad ligament portion, substantially L-shaped, extending from the other long edge of the anterior vaginal portion and having a thickness dimension about 1.2 cm and a major dimension of about 3.5 cm; a sacral portion, substantially rectangular in shape, having a major dimension of about 8.0 cm and a minor dimension of about 4.0 cm; and a posterior vaginal portion, substantially rectangular in shape, having a major dimension of about 15 cm and a minor dimension of about 4.0 cm; where the left broad ligament portion extends between and connects the anterior vaginal portion and the posterior vaginal portion.

(2) The hysteropexy mesh of claim 1, wherein the mesh comprises one of polypropylene, polyester, polyethylene, silicone, a urethane, a polyurethane, copolymers, or block copolymers thereof.

(3) A method of treating hysteropexy comprising: create a peritoneal incision just above the rectum; separate rectum from the posterior aspect of the vagina by dissection until the perineal body is reached and the levator muscles are exposed; penetrate peritoneum overlying the sacral promontory and inferiorly dissected to meet posterior dissection from cul de sac; identify and clear off anterior longitudinal ligament and presacral vessels on the sacral promontory; manipulate uterus to create vesicouterine fascia incision and bladder flap; dissect vesicovaginal space to separate the bladder from the anterior aspect of the vagina until the level of the trigone is reached; create broad ligament incisions on each side near the cervix; insert hysteropexy mesh and attach by suture the posterior vaginal portion of the mesh to the posterior aspect of the vagina; pass folded anterior vaginal portion and right and left broad

ligament arms through incision in the broad ligament on the left; unfold anterior vaginal portion and attach by suture to the anterior aspect of the vagina; pass right broad ligament portion through incision in the broad ligament on the right; manipulator uterus and attach right broad ligament portion of mesh to posterior vaginal portion of mesh and the posterior aspect of the cervix;

attach sacral portion of mesh to the anterior longitudinal ligament at the level of the S1 vertebrae by suture in a tension free fashion; close peritoneal incision made on the sacrum by suture and cover with the bladder peritoneum using another suture; and close any remaining incisions to complete procedure.

(4) The method of paragraph (3), wherein the procedure is performed robotically, laparoscopically, or in open surgery through a laparotomy incision.

(5) A medical device kit comprising: the hysteropexy mesh of paragraph (1); and instructions for the implantation of the medical device.

(6) The medical device kit of paragraph (5), wherein the instructions comprise: create a peritoneal incision just above the rectum; separate rectum from the posterior aspect of the vagina by dissection until the perineal body is reached and the levator muscles are exposed; penetrate peritoneum overlying the sacral promontory and inferiorly dissected to meet posterior dissection from cul de sac; identify and clear off anterior longitudinal ligament and presacral vessels on the sacral promontory; manipulate uterus to create vesicouterine fascia incision and bladder flap; dissect vesicovaginal space to separate the bladder from the anterior aspect of the vagina until the level of the trigone is reached; create broad ligament incisions on each side near the cervix; insert hysteropexy mesh and attach by suture the posterior vaginal portion of the mesh to the posterior aspect of the vagina; pass folded anterior vaginal portion and right and left broad ligament arms through incision in the broad ligament on the left; unfold anterior vaginal portion and attach by suture to the anterior aspect of the vagina; pass right broad ligament portion through incision in the broad ligament on the right; manipulator uterus and attach right broad ligament portion of mesh to posterior vaginal portion of mesh and the posterior aspect of the cervix; attach sacral portion of mesh to the anterior longitudinal ligament at the level of the S1 vertebrae by suture in a tension free fashion; close peritoneal incision made on the sacrum by suture and cover with the bladder peritoneum using another suture; and close any remaining incisions to complete procedure.

[0046] Although the present invention has been de-

scribed with reference to preferred embodiments, persons skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention. All references cited throughout the specification, including those in the background, are incorporated herein in their entirety. Those skilled in the art will recognize, or be able to ascertain, using no more than routine experimentation, many equivalents to specific embodiments of the invention described specifically herein. Such equivalents are intended to be encompassed in the scope of the following claims.

Claims

1. A hysteropexy mesh comprising:

an anterior vaginal portion, substantially rectangular in shape, having major dimension of about 10 cm and a minor dimension of about 4.0 cm; a right broad ligament portion, substantially L-shaped, extending from one long edge of the anterior vaginal portion and having a thickness dimension about 1.2 cm and a major dimension of about 3.5 cm;

a left broad ligament portion, substantially L-shaped, extending from the other long edge of the anterior vaginal portion and having a thickness dimension about 1.2 cm and a major dimension of about 3.5 cm;

a sacral portion, substantially rectangular in shape, having a major dimension of about 8.0 cm and a minor dimension of about 4.0 cm; and a posterior vaginal portion, substantially rectangular in shape, having a major dimension of about 15 cm and a minor dimension of about 4.0 cm;

where the left broad ligament portion extends between and connects the anterior vaginal portion and the posterior vaginal portion.

2. The hysteropexy mesh of claim 1, wherein the mesh comprises one of polypropylene, polyester, polyethylene, silicone, a urethane, a polyurethane, copolymers, or block copolymers thereof.

3. A method of treating hysteropexy comprising:

creating a peritoneal incision just above the rectum;

separating the rectum from the posterior aspect of the vagina by dissection until perineal body is reached and levator muscles are exposed; penetrating peritoneum overlying sacral promontory and inferiorly dissect to meet posterior dissection from cul de sac;

identifying and clear anterior longitudinal ligament and presacral vessels on sacral promon-

tory;

manipulating uterus to create vesicouterine fascia incision and bladder flap;

dissecting vesicovaginal space to separate the bladder from anterior aspect of the vagina until the level of the trigone is reached;

creating broad ligament incisions on each side near the cervix;

inserting hysteropexy mesh of claim 1 and attach by suture the posterior vaginal portion of the mesh to the posterior aspect of the vagina; passing folded anterior vaginal portion and right and left broad ligament arms through incision in the broad ligament on the left;

unfolding anterior vaginal portion and attach by suture to the anterior aspect of the vagina; passing right broad ligament portion through incision in the broad ligament on the right;

manipulating uterus and attach right broad ligament portion of mesh to posterior vaginal portion of mesh and the posterior aspect of the cervix; attaching sacral portion of mesh to the anterior longitudinal ligament at the level of the S1 vertebrae by suture in a tension free fashion;

closing peritoneal incision made on the sacrum by suture and cover with the bladder peritoneum using another suture; and

closing any remaining incisions to complete procedure.

4. The method of claim 3, wherein the procedure is performed robotically, laparoscopically, or in open surgery through a laparotomy incision.

5. A medical device kit comprising:

the hysteropexy mesh of claim 1; and instructions for the implantation of the medical device.

6. The medical device kit of claim 5, wherein the instructions comprise:

create a peritoneal incision just above the rectum;

separate rectum from the posterior aspect of the vagina by dissection until the perineal body is reached and the levator muscles are exposed;

penetrate peritoneum overlying the sacral promontory and inferiorly dissect to meet posterior dissection from cul de sac;

identify and clear off anterior longitudinal ligament and presacral vessels on the sacral promontory;

manipulate uterus to create vesicouterine fascia incision and bladder flap;

dissect vesicovaginal space to separate the bladder from the anterior aspect of the vagina

until the level of the trigone is reached;
create broad ligament incisions on each side
near the cervix;
insert hysteropexy mesh and attach by suture
the posterior vaginal portion of the mesh to the 5
posterior aspect of the vagina;
pass folded anterior vaginal portion and right
and left broad ligament arms through incision in
the broad ligament on the left;
unfold anterior vaginal portion and attach by su- 10
ture to the anterior aspect of the vagina;
pass right broad ligament portion through inci-
sion in the broad ligament on the right;
manipulator uterus and attach right broad liga- 15
ment portion of mesh to posterior vaginal portion
of mesh and the posterior aspect of the cervix;
attach sacral portion of mesh to the anterior lon-
gitudinal ligament at the level of the S1 vertebrae
by suture in a tension free fashion;
close peritoneal incision made on the sacrum 20
by suture and cover with the bladder peritoneum
using another suture; and
close any remaining incisions to complete pro-
cedure.

25

30

35

40

45

50

55




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5



EUROPEAN SEARCH REPORT

Application Number
EP 14 17 9669

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A, P	EP 2 754 412 A1 (BRAUN SURGICAL S A B [ES]) 16 July 2014 (2014-07-16) * figures 1-7 * * paragraph [0002] - paragraph [0004] * * the whole document *	1-6	INV. A61F2/00 ADD. A61B17/42
A	WO 2011/037837 A2 (GEN HOSPITAL CORP [US]; PULLIAM SAMANTHA J [US]; WEINSTEIN MILENA M [U]) 31 March 2011 (2011-03-31) * figures 3-5, 15-16 * * paragraph [0044] - paragraph [0048] * * paragraph [0060] - paragraph [0066] *	1-6	
A	US 2013/066145 A1 (FAIRNENY TY [US] ET AL) 14 March 2013 (2013-03-14) * paragraph [0062] - paragraph [0064]; figure 1 *	1-6	
A	US 2010/305394 A1 (ROSENBLATT PETER L [US]) 2 December 2010 (2010-12-02) * claims 1-14; figures 3-5 *	1-6	
A	FR 2 976 788 A1 (CT HOSPITALIER UNIVERSITAIRE NIMES [FR]) 28 December 2012 (2012-12-28) * abstract; figures 2-6 *	1-6	TECHNICAL FIELDS SEARCHED (IPC) A61F A61B
A	WO 2010/087923 A1 (BARD INC C R [US]; YOUNG ROBERT [US]; FREITAG WALTER [US]; EVANS DOUG) 5 August 2010 (2010-08-05) * paragraph [0007] - paragraph [0010]; claims 1-20; figures 1-12 *	1-6	
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 19 December 2014	Examiner Portoni, Luisa
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

2

EPO FORM 1503 03 82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 14 17 9669

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

19-12-2014

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 2754412 A1	16-07-2014	EP 2754412 A1	16-07-2014
		WO 2014108493 A1	17-07-2014

WO 2011037837 A2	31-03-2011	US 2012184805 A1	19-07-2012
		WO 2011037837 A2	31-03-2011

US 2013066145 A1	14-03-2013	NONE	

US 2010305394 A1	02-12-2010	US 2010305394 A1	02-12-2010
		WO 2010138894 A2	02-12-2010

FR 2976788 A1	28-12-2012	NONE	

WO 2010087923 A1	05-08-2010	CA 2751416 A1	05-08-2010
		CN 102341061 A	01-02-2012
		EP 2391304 A1	07-12-2011
		KR 20110126118 A	22-11-2011
		US 2012108894 A1	03-05-2012
		WO 2010087923 A1	05-08-2010

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 61862386 B [0001]

专利名称(译)	子宫固定网装置		
公开(公告)号	EP2835111A1	公开(公告)日	2015-02-11
申请号	EP2014179669	申请日	2014-08-04
[标]申请(专利权)人(译)	科洛普拉斯特公司		
申请(专利权)人(译)	COLOPLAST A / S		
当前申请(专利权)人(译)	COLOPLAST A / S		
[标]发明人	SHARIATI AMIR		
发明人	SHARIATI, AMIR		
IPC分类号	A61F2/00 A61B17/42		
CPC分类号	A61F2/0045 A61B17/4241 A61F2/0063 A61F2/0095 A61F2002/0072 A61F2230/0019 A61F2230/0043		
优先权	61/862386 2013-08-05 US 14/449459 2014-08-01 US		
其他公开文献	EP2835111B1		
外部链接	Espacenet		

摘要(译)

本发明描述了一种子宫外固定网10，其包括阴道前部12，右阔韧带部分14，左阔韧带部分16，骶部18和阴道后部20。在所示实施例中，阴道前部12是形状基本为矩形，主要尺寸121约为10厘米，次要尺寸122约为4.0厘米。右阔韧带部分14从前阴道部分12的长边延伸，左阔韧带部分16从前阴道部分12的另一长边延伸。左右阔韧带部分14和16基本上为L形。每个阔韧带部分的厚度尺寸142约为1.2厘米，主要尺寸141约为3.5厘米。左阔韧带部分16位于阴道前部12和后阴道部分20之间。阴道后部20的形状基本为矩形，主要尺寸201约为15cm，次要尺寸202约为4.0cm。骶骨部分18的形状基本上为矩形，并且具有约8cm的主要尺寸181和约4.0cm的次要尺寸202。




FIG. 1