

(19)



(11)

EP 3 205 298 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
13.05.2020 Bulletin 2020/20

(51) Int Cl.:
A61B 17/42 ^(2006.01) **A61B 18/14** ^(2006.01)
A61B 34/20 ^(2016.01) **A61B 18/00** ^(2006.01)

(21) Application number: **17155486.8**

(22) Date of filing: **09.02.2017**

(54) **COLPOTOMY SYSTEM FOR TOTAL LAPAROSCOPIC HYSTERECTOMY**

KOLPOTOMIESYSTEM FÜR EINE LAPAROSKOPISCHE HYSTEREKTOMIE

SYSTÈME DE CAPSULOTOMIE POUR HYSTÉRECTOMIE TOTALE LAPAROSCOPIQUE

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(30) Priority: **10.02.2016 US 201662293444 P**
31.01.2017 US 201715420625

(43) Date of publication of application:
16.08.2017 Bulletin 2017/33

(73) Proprietor: **Covidien LP**
Mansfield, MA 02048 (US)

(72) Inventors:
• **MARCZYK, Stanislaw**
Stratford, CT 06614 (US)

• **CALDERONI, Anthony**
Bristol, CT 06010 (US)

(74) Representative: **Maschio, Antonio**
Maschio & Soames IP Limited
30 Carlton Crescent
Southampton SO15 2EW (GB)

(56) References cited:
WO-A1-2015/138708 US-A1- 2006 205 996
US-A1- 2010 087 798 US-A1- 2012 143 209
US-A1- 2012 323 079 US-A1- 2015 351 621
US-B1- 6 210 330

EP 3 205 298 B1

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

TECHNICAL FIELD

[0001] The present disclosure relates to medical instrumentation. More particularly, the present disclosure relates to a colpotomy system including a navigation system for determining a distance between two surgical instruments.

BACKGROUND OF RELATED ART

[0002] A uterine manipulator is used by practitioners for many laparoscopic procedures involving the female pelvic organs (e.g., uterus, tubes, ovaries, etc.) as surgery without a uterine manipulator may be more time consuming. For example, laparoscopies in which a uterine manipulator has substantial utility include tubal ligations, diagnostic laparoscopies for evaluating pelvic pain and infertility, treatment of endometriosis, removal of pelvic scars (adhesions) involving the uterus, fallopian tubes and ovaries, etc.

[0003] Most state of the art manipulators are semi-rigid instruments having a manipulating handle that is grasped outside the vagina and a working end which operatively engages tissue in the uterus. Exposure of the vital regions of the pelvis is difficult and surgery with open or laparoscopic instruments is often difficult and, in some cases, suboptimal. For example, the uterus typically can only be safely elevated about 45 degrees from the vaginal axis, or lowered 10-15 degrees from the same and movement to the right or left is minimal, at most, due to the pelvic bones. Once the uterine organ is repositioned into a desired location, the surgeon can perform one of the above mentioned surgical procedures.

[0004] One potential complication of any surgical procedure involving the uterus, e.g., partial or complete hysterectomy, is the risk of persistent and excessive bleeding due to the large blood supply in the pelvic region and blood-laden organs. For example, the open technique carries increased risk of hemorrhage due to the need to move the intestinal organs and bladder in order to reach the reproductive organs and to search for collateral damage from endometriosis or cancer. However, an open hysterectomy provides the most effective way to ensure complete removal of the reproductive system, as well as providing a wide opening for visual inspection of the abdominal cavity.

[0005] Some hysterectomies are done through the manipulation of the cervix and/or uterus utilizing a uterine manipulator and resection of the cervix (total hysterectomy) or uterus (supracervical) utilizing one or more laparoscopic instruments inserted through the navel (or other body access made with a trocar). Even though these techniques tend to reduce the recovery time in most instances, the risk of bleeding still remains US 2015/351621 A1 discloses a colpotomy system comprising a surgical instrument having a cutting element at a

distal end and a uterine instrument having a handle operably coupled to a shaft, the shaft extending through a retaining member to access a surgical site, the retaining member including a plurality of LED's to indicate the position.

SUMMARY

[0006] The present invention is defined in independent claim 1 and certain optional features thereof are defined in the dependent claims. In so far as the terms "invention", "example", "aspect", and "embodiment" are used herein, this will be interpreted in such a way that the only protection sought is for the invention as claimed. The present disclosure relates to a uterine instrument including a first handle portion, a second handle portion, a first shaft operably coupled to the first handle portion, the first shaft having a first balloon positioned at a distal end thereof, and a second shaft operably coupled to the second handle portion, the second shaft having a second balloon positioned at a distal end thereof. The uterine instrument further includes a retaining member configured to engage the second balloon of the second shaft, the first shaft configured to extend through the second shaft and the retaining member to access a surgical site. The retaining member includes a plurality of transmitters for transmitting at least one signal.

[0007] In disclosed embodiments, the first handle portion is a movable handle and the second handle portion is a stationary handle.

[0008] In disclosed embodiments, in operation, the first balloon is inflated to retain the first shaft in a uterus and the second balloon is inflated to seal an abdominal cavity.

[0009] In disclosed embodiments, the retaining member is a colpotomy cup.

[0010] In disclosed embodiments, the retaining member has a proximal ring and a distal ring, the proximal ring having a plurality of posts for supporting the distal ring. A transmitter of the plurality of transmitters is incorporated within the distal ring.

[0011] In disclosed embodiments, the at least one signal is a single frequency sound wave or radio wave or electromagnetic wave.

[0012] In disclosed embodiments, the uterine instrument is operated in tandem with a surgical instrument having at least one receiver for receiving the at least one signal emitted from the plurality of transmitters. The receiver is positioned at a distal end of the surgical instrument, the distal end further including a cutting element.

[0013] In disclosed embodiments, a distance between the cutting element of the surgical instrument and a distal ring of the retaining member is calculated by a processor.

[0014] In disclosed embodiments, if the distance exceeds a predetermined threshold, a notification is relayed to a user of the uterine instrument. Alternatively, if the distance exceeds a predetermined threshold, the cutting element is automatically deactivated.

[0015] The present disclosure relates to a colpotomy

system including a surgical instrument having a cutting element and a receiver at a distal end thereof and a uterine instrument. The uterine instrument has a handle operably coupled to a shaft having a balloon at a distal end thereof, the shaft extending through a retaining member to access a surgical site, the retaining member including a plurality of transmitters for transmitting at least one signal. A distance between the cutting element of the surgical instrument and one end of the retaining member of the uterine instrument is calculated to determine whether the cutting element is within a predetermined operating zone.

[0016] The present disclosure further relates to an exemplary method of accessing a surgical site. The method includes introducing at the surgical site a surgical instrument having a cutting element and a receiver at a distal end thereof and introducing at the surgical site a uterine instrument having a handle operably coupled to a shaft having a balloon at a distal end thereof, the shaft extending through a retaining member to access a surgical site, the retaining member including a plurality of transmitters for transmitting at least one signal. The method further includes calculating a distance between the cutting element of the surgical instrument and one end of the retaining member of the uterine instrument and determining whether the cutting element is within a predetermined operating zone.

DESCRIPTION OF THE DRAWINGS

[0017] The above and other aspects, features, and advantages of the present disclosure will become more apparent in light of the following detailed description when taken in conjunction with the accompanying drawings in which:

FIG. 1 is a schematic representation of a uterine manipulator, in accordance with the embodiments of the present disclosure;

FIG. 2 illustrates the uterine manipulator of FIG. 1 entering and being retained within the uterus, in accordance with the embodiments of the present disclosure;

FIG. 3 illustrates an enlarged view of the distal end of the uterine manipulator of FIG. 1, in accordance with the embodiments of the present disclosure;

FIG. 4 illustrates the retaining member of the uterine manipulator of FIG. 1, in accordance with the embodiments of the present disclosure;

FIG. 5 illustrates the area of detail of FIG. 4 showing a transmitter embedded within the retaining member of the uterine manipulator of FIG. 1, in accordance with the embodiments of the present disclosure;

FIG. 6 illustrates the transmitter of FIG. 5, in accordance with the embodiments of the present disclosure;

FIG. 7 illustrates a surgical instrument including an electro-cautery cutting element, in accordance with

the embodiments of the present disclosure;

FIG. 8 illustrates an enlarged view of the distal end of the surgical instrument including the electro-cautery cutting element of FIG. 7, in accordance with the embodiments of the present disclosure;

FIG. 9 illustrates an enlarged view of the actuation elements of the surgical instrument including the electro-cautery cutting element of FIG. 7, in accordance with the embodiments of the present disclosure;

FIG. 10 illustrates the area of detail of FIG. 8 showing an enlarged view of a receiver embedded within the surgical instrument including the electro-cautery cutting element of FIG. 7, in accordance with the embodiments of the present disclosure;

FIG. 11 illustrates the receiver, in accordance with the embodiments of the present disclosure;

FIG. 12 illustrates a predetermined operating zone of operation of the surgical instrument in cylindrical coordinate system form, in accordance with the embodiments of the present disclosure;

FIG. 13 illustrates, in cylindrical coordinate system form, the electro-cautery cutting element of FIG. 7 being outside the predetermined operating zone of operation, in accordance with the embodiments of the present disclosure;

FIG. 14 illustrates a retaining member incorporating a single inductive coil loop, as well as a tip of a surgical cutting device approaching a distal ring of the retaining member, in accordance with another embodiment of the present disclosure;

FIG. 15 illustrates the single inductive coil loop used in the retaining member of FIG. 14, in accordance with embodiments of the present disclosure;

FIG. 16 illustrates a cross-sectional view of the distal ring of the retaining member taken along line X-X of FIG. 14, in accordance with embodiments of the present disclosure;

FIG. 17 illustrates a retaining member incorporating a series of inductive coil loops, as well as a tip of a surgical cutting device approaching a distal ring of the retaining member, in accordance with another embodiment of the present disclosure;

FIG. 18 illustrates the series of inductive coil loops used in the retaining member of FIG. 17, in accordance with embodiments of the present disclosure; and

FIG. 19 illustrates an inductive sensor that serves as the inductive coil loops used in FIGS. 14 and 17, in accordance with embodiments of the present disclosure.

DETAILED DESCRIPTION

[0018] Particular embodiments of the present disclosure are described hereinbelow with reference to the accompanying drawings. However, it is to be understood that the disclosed embodiments are merely exemplary

of the disclosure and may be embodied in various forms. Well-known functions or constructions are not described in detail to avoid obscuring the present disclosure in unnecessary detail. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a basis for the claims and as a representative basis for teaching one skilled in the art to variously employ the present disclosure in virtually any appropriately detailed structure. Like reference numerals refer to similar or identical elements throughout the description of the figures.

[0019] As used herein, the term "distal" refers to that portion of the instrument, or component thereof which is farther from the user while the term "proximal" refers to that portion of the instrument or component thereof which is closer to the user.

[0020] Reference will now be made in detail to embodiments of the present disclosure. While certain exemplary embodiments of the present disclosure will be described, it will be understood that it is not intended to limit the embodiments of the present disclosure to those described embodiments. To the contrary, reference to embodiments of the present disclosure is intended to cover alternatives, modifications, and equivalents as may be included within the scope of the embodiments of the present disclosure as defined by the appended claims.

[0021] FIG. 1 is a schematic representation of a uterine manipulator 100, in accordance with the embodiments of the present disclosure.

[0022] The uterine manipulator 100 includes a first handle portion 10 and a second handle portion 20. The first handle portion 10 is a movable handle and the second handle portion 20 is a stationary handle. Thus, the first handle portion 10 is movable relative to the second handle portion 20. A first shaft 45 is operably coupled to the first handle portion 10. The first shaft 45 has a first balloon 40 positioned at a distal end thereof. A second shaft 30 is operably coupled to the second handle portion 20. The second shaft 30 has a second balloon 50 positioned at a distal end thereof. The first shaft 45 and the second shaft 30 may also be rotatable. A tube 25 with a coupling provides a fluid pathway to inflate either or both of first and second balloons 40, 50. The first and second balloons 40, 50 may also be independently inflatable and each balloon 40, 50 would have a separate tube attachable to a source of inflation fluid. A pressure source "PS" may be coupled to the tube 25 and provide inflation fluid under pressure to one or both balloons 40, 50. The inflation fluid may be a liquid (e.g., sterile saline) or a gas (e.g., CO₂).

[0023] A retaining member 60 is configured to engage the second balloon 50 of the second shaft 30. The retaining member 60 may be a colpotomy cup. The retaining member 60 may be connected to a control box or generator (not shown) via the cable 70. The first shaft 45 is configured to extend through the second shaft 30 and through the retaining member 60 to access a surgical site, as described below with reference to FIG. 2. The

retaining member 60 may be a single use component of the uterine manipulator 100.

[0024] FIG. 2 illustrates the uterine manipulator 100 of FIG. 1 entering and being retained within a uterus 200, in accordance with the embodiments of the present disclosure.

[0025] In operation, a distal end of the uterine manipulator 100 enters the opening 220 of the uterus 200. The first balloon 40 is inflated within the cervical cavity 240 and the second balloon 50 is inflated within the vaginal cavity 230. Thus, the first balloon 40 is inflated to retain the first shaft 45 in the uterus 200 and the second balloon 50 is inflated to seal an abdominal cavity and provide a substantially fluid-tight barrier.

[0026] FIG. 3 illustrates an enlarged view 300 of the distal end of the uterine manipulator 100 of FIG. 1, in accordance with the embodiments of the present disclosure.

[0027] The enlarged view 300 illustrates the first shaft 45 extending through a central opening 450 (see FIG. 4) of the retaining member 60. First and second balloons 40, 50 are shown in a deflated state.

[0028] FIG. 4 illustrates the retaining member 60 of the uterine manipulator 100 of FIG. 1, in accordance with the embodiments of the present disclosure.

[0029] The retaining member 60 includes a proximal ring 410 and a distal ring 440. The proximal ring 410 has a plurality of posts 420 for supporting the distal ring 440. In one exemplary embodiment, there are three posts 420. The retaining member 60 further includes a central opening 450 for receiving the first shaft 45, as discussed above with reference to FIG. 3. Alternatively, the proximal ring 410 may be a solid ring with no posts.

[0030] The distal ring 440 includes a plurality of transmitters 430. In the exemplary embodiments there are 3 transmitters 430 embedded or incorporated within the distal ring 440. Each transmitter 430 may be aligned with a post 420. Each transmitter 430 may emit a single frequency sound wave through a respective opening 435. Of course, one skilled in the art may contemplate the transmitters 430 transmitting other types of signals, such as electromagnetic signals or radio signals. The transmitters 430 may emit the same frequency or each transmitter 430 may emit a unique frequency.

[0031] FIG. 5 is an enlarged view 500 illustrating the area of detail of FIG. 4 showing a transmitter 430 embedded or incorporated within the retaining member 60 of the uterine manipulator 100 of FIG. 1, in accordance with the embodiments of the present disclosure, whereas FIG. 6 illustrates the transmitter 430 of FIG. 5, in accordance with the embodiments of the present disclosure.

[0032] The transmitter 430 has a body portion 610 with a pair of electrical contacts 630, as well as a speaker 620. The pair of electrical contacts 630 are used to supply power to generate, for example, the sound wave that is emitted through speaker 620. Of course, one skilled in the art may contemplate the transmitters 430 transmitting other types of signals, such as electromagnetic signals

or radio signals. The transmitter 430 is aligned with the opening 435 of the distal ring 440. The transmitter 430 is also aligned with the posts 420 of the retaining member 60. Even though the exemplary embodiments refer to three transmitters 430, one skilled in the art may contemplate any number of transmitters 430 embedded or incorporated within the distal ring 440 or any other portion or portions of the retaining member 60.

[0033] FIG. 7 illustrates a surgical instrument 700 including an electro-cautery cutting and sealing element 742, in accordance with the embodiments of the present disclosure, whereas FIG. 8 illustrates an enlarged view of the distal tip 740 of the surgical instrument 700 including the electro-cautery cutting element of FIG. 7, in accordance with the embodiments of the present disclosure.

[0034] The surgical instrument 700 may be an electro-cautery knife including a housing 710. One end of the housing 710 is connected to a cable 720, which is connected to a generator 725. The other end of the housing 710 is connected to a shaft 730 having a tip 740. The tip 740 includes an opening 732 within which is housed the receiver 750. The tip further includes a cutting and sealing element 742, such as a knife, secured to the shaft 730 by an insulator 744. The receiver 750 is positioned at a distal end of the surgical instrument 700, the distal end further including the cutting and sealing element 742. In operation, the surgical instrument 700 is used to both dissect tissue and to cauterize blood vessels. Thus, the surgical instrument 700 relies on high-voltage, high-frequency electrical signals of various waveforms to selectively sever, clamp or coagulate living tissue during surgical procedures.

[0035] FIG. 9 illustrates an enlarged view of the actuation elements of the surgical instrument 700 including the electro-cautery cutting element of FIG. 7, in accordance with the embodiments of the present disclosure.

[0036] The housing 710 includes several actuation elements or mechanisms. Actuation mechanism 770 is a rocker type actuator for allowing a user to select between, for example, coagulation and cutting modes. Actuation mechanism 780 activates the "navigation mode," as described below with reference to FIGS. 12 and 13. Indicators 760 may be LED lights indicating whether the tip 740 of the surgical instrument 700 is within a predetermined operating zone 1200, as defined below with reference to FIGS. 12-13. When the tip 740 of the surgical instrument 700 is within the predetermined operating zone 1200, the indicators 760 may turn green, whereas when the tip 740 of the surgical instrument 700 is outside the predetermined operating zone 1200, the indicators 760 may turn red. Of course, it is possible to have further colors, such as yellow and orange, for example, as the tip 740 of the surgical instrument 700 approaches the boundary of the operating zone 1200. Additionally, at least one transmitter of the plurality of transmitters 430 may be triggered when the tip 740 of the surgical instrument 700 approaches or enters the predetermined operating zone 1200.

[0037] FIG. 10 illustrates the area of detail of FIG. 8 showing an enlarged view 1000 of a receiver 750 embedded within the surgical instrument 700 including the electro-cautery cutting element of FIG. 7, in accordance with the embodiments of the present disclosure, whereas FIG. 11 illustrates the receiver 750, in accordance with the embodiments of the present disclosure.

[0038] The enlarged view 1000 depicts the receiver 750 resting within the shaft 730 of the surgical instrument 700, such that the receiver 750 is aligned with the opening 732 of the shaft 730. The receiver 750 is configured to communicate with the transmitter 430 of the retaining member 60, as described below with reference to FIGS. 12 and 13.

[0039] FIG. 12 illustrates a predetermined operating zone 1200 for the surgical instrument 700 including the electro-cautery cutting and sealing element 742 of FIG. 7, in cylindrical coordinate system form, in accordance with the embodiments of the present disclosure, whereas FIG. 13 illustrates, in cylindrical coordinate system form, the electro-cautery cutting and sealing element 742 of FIG. 7 being in a region 1300 outside the predetermined operating zone 1200, in accordance with the embodiments of the present disclosure. The predetermined operating zone may also be referred to as a safe zone.

[0040] Total Laparoscopic Hysterectomy (TLH) is a minimally invasive procedure usually performed for benign indications. The key part of the procedure is the circular transection around the fundus of the cervix, called colpotomy. It separates the uterus from the cervix. It is performed with the surgical instrument 700 including the cutting and sealing element 742, which is inserted to the surgical site through a surgical port. To present the cervical fundus for transection, the surgeon commonly uses the uterine manipulator 100 to reposition/manipulate the uterus.

[0041] In operation, and with reference to FIGS. 1 and 2, the uterine manipulator 100 is inserted through the vagina and has a steerable and rotatable first shaft 45 with a first balloon 40 which anchors or secures to the uterus and allows moving it upward, as well as rotating it in a coronal plane. Proximal to the first balloon 40 is the retaining member 60, or colpotomy cup, which rests against the cervical fundus and pushes it up during the surgical procedure. The retaining member 60 serves as a guide during colpotomy. The cervical fundus is located in proximity to several vital organs, including the bladder, color, arteries, urethra, and ureter.

[0042] To improve the accuracy of instrument placement during colpotomy, a navigation system is provided. The navigation system determines a distance between the retaining member 60 of the uterine manipulator 100 and the tip 740 of the cutting and sealing element 742 of the surgical instrument 700. Thus, the uterine instrument 100 is operated in tandem with the surgical instrument 700 having the receiver 750 for receiving the at least one signal emitted from the plurality of transmitters 430 of the retaining member 60.

[0043] A distance between the cutting and sealing element 742 of the surgical instrument 700 and the distal ring 440 of the retaining member 60 is calculated by a processor (not shown). If the distance exceeds a predetermined threshold, a notification may be relayed to a user of the uterine instrument 100. Alternatively, if the distance exceeds a predetermined threshold, the cutting and sealing element 742 may be automatically deactivated by the processor. In other words, a distance between the cutting and sealing element 742 of the surgical instrument 700 and one end of the retaining member 60 of the uterine instrument 100 is calculated to determine whether the cutting and sealing element 742 is within the predetermined operating zone 1200.

[0044] Therefore, the transmitters 430 located on or within the distal ring 440 of the retaining member 60 communicate with the receiver 750 located at the distal end of the surgical instrument 700. Sonic signals may be emitted by the transmitters 430 that are received by the receiver 750. Of course, one skilled in the art may contemplate other types of signals, such as electro-magnetic signals or radio signals. A processor associated with the receiver 750 calculates the distance between each transmitter 430 and the tip 740 having the cutting and sealing element 742 of surgical instrument 700. After calculating such distance, the processor calculates whether the tip 740 having the cutting and sealing element 742 is within the predetermined operating zone 1200 (FIG. 12). This information is then passed on, in real-time, during the surgery, to the surgeon to disable the cutting and sealing element 742 if it is outside the predetermined operating zone 1200.

[0045] The predetermined operating zone 1200 is depicted in cylindrical coordinate form in FIG. 12. The predetermined operating zone 1200 may have the shape of a circle or ellipse or toroid or donut or cylinder concentric with the distal ring 440 of the retaining member 60, as shown in FIG. 4. The donut-shaped or cylinder-shaped predetermined operating zone 1200 may have a radius R. If the tip 740 having the knife 742 is in the predetermined operating zone 1200, then the following conditions are satisfied:

$$R_1 \leq R_K \leq R_2$$

$$z_1 \leq z_K \leq z_2$$

$$\text{for: } 0^\circ \leq t \leq 360^\circ$$

where R_K , z_K , t are the coordinates of the cutting tip K of the electro-cautery instrument in the cylindrical coordinate system, and

where R_1 , R_2 , z_1 , z_2 are the limits of the allowable donut shape zone around the colpotomy cup ring ($r=R$, $z=0$) where a safe transaction can be per-

formed.

[0046] In other words, the knife 742 is within the confines or boundaries or within the radius R of the donut-shaped or cylinder-shaped predetermined operating zone 1200. Of course, one skilled in the art may contemplate any width or height for the predetermined operating zone 1200.

[0047] Regarding FIG. 13, it is assumed that the transmitters 430 are located at points A, B, and C of the distal ring 440 represented in cylindrical coordinate system form and defined by the vectors R_A , R_B , and R_C . Each transmitter 430 transmits a signal in sequence which travels with specific speed through tissue and reaches the receiver 750. The receiver 750 receives those signals transmitted by the transmitters 430 and based on measured travel time calculates the distances a, b, and c from the respective transmitters 430 to the receiver 750. Now the processor solves a set of equations to find the Cartesian coordinates of vectors a, b, and c, and then the coordinates of vector K (x_K , y_K , z_K), where vector K extends from O to K (FIG. 13) and K represents the tip 740 of the cutting element 742. Since $R_K = \text{SQRT}(x_K^2 + y_K^2)$, the processor can now check whether the tip 740 having the cutting element 742 is within the predetermined operating zone 1200 for performing the colpotomy.

[0048] Thus, the navigation system provided herein allows the activation of the surgical instrument 700 only when the tip 740 having the cutting element 742 is within the predetermined operating zone 1200 or in close proximity to the outer boundary or outer perimeter or edge of the retaining member 60. Therefore, the surgeon can perform colpotomy safely while avoiding contact with adjacent tissue. In other words, the cutting element 742 must operate within the confines or boundary or outer perimeter of the distal ring 440 of the retaining member 60. If the cutting element 742 falls outside the boundary of the distal ring 440 of the retaining element 60, then the cutting element 742 is deactivated either automatically or by the surgeon.

[0049] FIG. 14 illustrates a retaining member 1400 incorporating a single inductive coil loop 1460, as well as a tip 1530 of a surgical cutting device 1500 approaching a distal ring 1440 of the retaining member 1400, in accordance with another embodiment of the present disclosure.

[0050] The retaining member 1400 includes a proximal ring 1410 and a distal ring 1440. The proximal ring 1410 has a plurality of posts 1420 for supporting the distal ring 1440. In one exemplary embodiment, there are three posts 1420. Alternatively, the proximal ring 1410 may be a solid ring with no posts.

[0051] The retaining member 1400 further includes a central opening 1450 for receiving a shaft 1510 of the surgical cutting device 1500. The surgical cutting device 1500 further includes a tapered portion 1520 and a tip 1530 extending from the tapered portion 1520. The tapered portion 1520 may be constructed from a ferromag-

netic material. The ferromagnetic material may preferably be a metal. The tip 1530 may be an electrocautery isolated tip.

[0052] The distal ring 1440 includes a plurality of transmitters 1430. In the exemplary embodiments there are, for example, 3 transmitters 1430 embedded or incorporated within the distal ring 1440. Each transmitter 1430 may be aligned with a post 1420. Each transmitter 1430 may emit a single frequency sound wave through a respective opening 1435. Of course, one skilled in the art may contemplate the transmitters 1430 transmitting other types of signals, such as electromagnetic signals or radio signals. The transmitters 1430 may emit the same frequency or each transmitter 1430 may emit a unique frequency. One skilled in the art may contemplate any number of transmitters embedded within different portions of the distal ring 1440.

[0053] A single inductive coil loop 1460 is incorporated or embedded within the distal ring 1440 of the retaining member 1400. A cutout section 1401 depicts a portion of the single inductive coil loop 1460 circumferentially embedded or incorporated within the retaining member 1400.

[0054] FIG. 15 illustrates the single inductive coil loop 1460 used in the retaining member 1400 of FIG. 14, in accordance with embodiments of the present disclosure.

[0055] The single inductive coil loop 1460 includes a core 1462 and a wire 1464 wound around the entire length of the core 1462.

[0056] FIG. 16 illustrates a cross-sectional view 1470 of the distal ring 1440 of the retaining member 1400 taken along line X-X of FIG. 14, in accordance with embodiments of the present disclosure.

[0057] The distal ring 1440 defines an opening 1472 for accommodating the single inductive coil loop 1460 therein. A cover 1474 encloses the single inductive coil loop 1460 within the distal ring 1440. The cover 1474 may serve as an isolator. The opening 1472 may be a substantially semi-circular opening.

[0058] Referring to FIGS. 14-16, the single inductive coil loop 1460 allows for a method of sensing a radial position of the tip 1530 of the surgical cutting device 1500, as the tip 1530 approaches the distal ring 1440 of the retaining member 1400. The single inductive coil loop 1460 serves as an inductive sensor (FIG. 19). The tip 1530 of the surgical cutting device 1500 includes a tapered portion 1520 composed or formed or constructed from a ferromagnetic material. The ferromagnetic material may preferably be a metal. Once the tip 1530 is in close proximity to the retaining member 1400, the tapered portion 1520 changes the inductance of the single inductive coil loop 1460. This data or information is transmitted by the transmitters 1430 to, for example, a display device. A user can evaluate or analyze the data or information collected and, based on that data or information, safely conduct transection of the uterus without risk of damaging adjacent organs. Such data or information is valuable when visibility of the operating site is impaired.

[0059] FIG. 17 illustrates a retaining member 1700 incorporating a series of inductive coil loops 1764, as well as a tip 1530 of a surgical cutting device 1500 approaching a distal ring 1440 of the retaining member 1700, in accordance with another embodiment of the present disclosure.

[0060] The retaining member 1700 includes a proximal ring 1410 and a distal ring 1440. The proximal ring 1410 has a plurality of posts 1420 for supporting the distal ring 1440. In one exemplary embodiment, there are three posts 1420. Alternatively, the proximal ring 1410 may be a solid ring with no posts.

[0061] The retaining member 1700 further includes a central opening 1450 for receiving a shaft 1510 of the surgical cutting device 1500. The surgical cutting device 1500 further includes a tapered portion 1520 and a tip 1530 extending from the tapered portion 1520. The tapered portion 1520 may be constructed from a ferromagnetic material. The ferromagnetic material may preferably be a metal. The tip 1530 may be an electrocautery isolated tip.

[0062] The distal ring 1440 includes a plurality of transmitters 1430. In the exemplary embodiments there are 3 transmitters 1430 embedded or incorporated within the distal ring 1440. Each transmitter 1430 may be aligned with a post 1420. Each transmitter 1430 may emit a single frequency sound wave through a respective opening 1435. Of course, one skilled in the art may contemplate the transmitters 1430 transmitting other types of signals, such as electromagnetic signals or radio signals. The transmitters 1430 may emit the same frequency or each transmitter 1430 may emit a unique frequency. One skilled in the art may contemplate any number of transmitters embedded within different portions of the distal ring 1440.

[0063] A series of inductive coil loops 1764 are incorporated or embedded within the distal ring 1440 of the retaining member 1700 via a core 1760. A cutout section 1401 depicts a portion of the series of inductive coil loops 1764 circumferentially embedded or incorporated within the retaining member 1700. The series of inductive coil loops 1764 are positioned around a core 1760. The series of inductive coil loops 1764 may be equally spaced apart from each other around the core 1760.

[0064] FIG. 18 illustrates the series of inductive coil loops 1764 used in the retaining member 1700 of FIG. 17, in accordance with embodiments of the present disclosure.

[0065] The series of inductive coil loops 1764 are wires that are placed or positioned around the core 1760. One skilled in the art may contemplate any number of inductive coil loops 1764 wound around the core 1762.

[0066] Referring to FIGS. 17-18, the series of inductive coil loops 1764 allow for a method of sensing a radial position, as well as an angular position of the tip 1530 of the surgical cutting device 1500, as the tip 1530 approaches the distal ring 1440 of the retaining member 1700. Each of the inductive coil loops 1764 serves as an

inductive sensor (FIG. 19). The tip 1530 of the surgical cutting device 1500 includes a tapered portion 1520 composed or formed or constructed from a ferromagnetic material. The ferromagnetic material may preferably be a metal. Once the tip 1530 is in close proximity to the retaining member 1700, the tapered portion 1520 changes the inductance of the series of inductive coil loops 1764. This data or information is transmitted by the transmitters 1430 to, for example, a display device. A user can evaluate or analyze the data or information collected and, based on that data or information, safely conduct transection of the uterus without risk of damaging adjacent organs. Such data or information is valuable when visibility of the operating site is impaired.

[0067] FIG. 19 illustrates an inductive sensor 1900 that serves as the inductive coil loops used in FIGS. 14 and 17, in accordance with embodiments of the present disclosure. In FIG. 14, one single coil served as an inductive sensor to identify a radial location of a tip of an instrument, whereas in FIG. 17, a series of coils constituted a series of inductive sensors allowing identification of both radial and angular location of the tip of the surgical instrument. The inductive sensor is an electronic proximity sensor, which detects metallic objects without touching them. The sensor consists of an induction loop, as illustrated in FIGS. 15 and 18.

[0068] It is to be understood that the various embodiments shown and described herein are to be taken as exemplary. Elements and materials, and arrangements of those elements and materials, may be substituted for those illustrated and described herein, parts may be reversed, and certain features of the present disclosure may be utilized independently, all as would be apparent to one skilled in the art after having the benefit of the description herein. Changes may be made in the elements described herein without departing from the scope of the present disclosure and following claims. It is to be understood that the particular examples and embodiments set forth herein are non-limiting, and modifications to structure, dimensions, materials, and methodologies may be made without departing from the scope of the present disclosure.

[0069] While various embodiments of the present disclosure have been shown and described herein, it will be obvious to those skilled in the art that these embodiments are provided by way of example only. Numerous variations, changes, and substitutions will now occur to those skilled in the art without departing from the present disclosure. Accordingly, it is intended that the invention be limited only by the scope of the appended claims.

Claims

1. A colpotomy system comprising:

a surgical instrument (700) having a cutting element (742) at a distal end thereof; and

a uterine instrument (100) having a handle (10) operably coupled to a shaft (45) having a balloon (40) at a distal end thereof, the shaft extending through a retaining member (60) to access a surgical site, the retaining member including a plurality of transmitters (430) disposed about a distal ring (440) of the retaining member (60) for transmitting at least one signal to define a predetermined operating zone;
said surgical instrument further having a receiver (750) at a distal end thereof for receiving said at least one signal emitted from said plurality of transmitters (430);
a processor configured to calculate a distance between the cutting element of the surgical instrument and one end of the retaining member of the uterine instrument to determine whether the cutting element is within the predetermined operating zone.

2. The colpotomy system according to claim 1, wherein the retaining member has a proximal ring (410), the proximal ring (410) having a plurality of posts (420) for supporting the distal ring (440).
3. The colpotomy system according to claim 2, wherein a transmitter of the plurality of transmitters is incorporated within the distal ring.
4. The colpotomy system of claim 2 or 3, wherein the predetermined operating zone is defined by the circumference of the distal ring.
5. The colpotomy system according to any one of claims 1 to 4, wherein the at least one signal is a single frequency sound wave or radio wave or electromagnetic wave.
6. The colpotomy system of any one of claims 1 to 5, wherein if the distance exceeds a predetermined threshold, a notification is relayed to a user of the uterine instrument.
7. The colpotomy system of any of claims 1 to 6, wherein if the distance exceeds a predetermined threshold, the cutting element is automatically deactivated.
8. The colpotomy system of any preceding claim, wherein the uterine instrument comprises:

the handle being a first handle portion (10);
a second handle portion (20);
the shaft being a first shaft (45) operably coupled to the first handle portion;
the balloon being a first balloon (40) positioned at a distal end thereof;
a second shaft (30) operably coupled to the second handle portion, the second shaft having a

- second balloon (50) positioned at a distal end thereof; and
the retaining member configured to engage the second balloon of the second shaft, the first shaft configured to extend through the second shaft and the retaining member to access a surgical site.
9. The colpotomy system of claim 8, wherein the first handle portion is a movable handle and the second handle portion is a stationary handle.
10. The colpotomy system of claim 8 or 9, wherein, in operation, the first balloon is inflated to retain the first shaft in a uterus and the second balloon is inflated to seal an abdominal cavity.
11. The colpotomy system of any preceding claim, wherein the retaining member is a colpotomy cup.

Patentansprüche

1. Ein Kolpotomiesystem, umfassend:

ein chirurgisches Instrument (700) mit einem Schneidelement (742) an einem distalen Ende davon; und
ein Uterus-Instrument (100) mit einem Griff (10), der mit einer Welle (45) mit einem Ballon (40) an einem distalen Ende desselben funktionell gekoppelt ist, wobei sich die Welle durch ein Halteelement (60) erstreckt, um Zugang zu einer Operationsstelle zu erhalten, wobei das Halteelement eine Vielzahl von Sendern (430) umfasst, die um einen distalen Ring (440) des Halteelements (60) herum angeordnet sind, um mindestens ein Signal zu übertragen, um eine vorbestimmte Operationszone zu definieren; wobei das chirurgische Instrument ferner einen Empfänger (750) an seinem distalen Ende zum Empfangen des mindestens einen, von den mehreren Sendern (430) ausgesendeten Signals aufweist;
einen Prozessor, der so konfiguriert ist, dass er einen Abstand zwischen dem Schneidelement des chirurgischen Instruments und einem Ende des Halteelements des Uterus-Instruments berechnet, um zu bestimmen, ob sich das Schneidelement innerhalb der vorbestimmten Operationszone befindet.

2. Kolpotomiesystem nach Anspruch 1, wobei das Halteelement einen proximalen Ring (410) aufweist, wobei der proximale Ring (410) eine Vielzahl von Stäben (420) zum Abstützen des distalen Rings (440) aufweist.

3. Kolpotomiesystem nach Anspruch 2, bei dem ein Sender der Vielzahl von Sendern in den distalen Ring eingebaut ist.
4. Kolpotomiesystem nach Anspruch 2 oder 3, wobei die vorbestimmte Operationszone durch den Umfang des distalen Rings definiert ist.
5. Kolpotomiesystem nach einem der Ansprüche 1 bis 4, wobei das mindestens eine Signal eine Schallwelle mit einer einzigen Frequenz oder eine Radiowelle oder eine elektromagnetische Welle ist.
6. Das Kolpotomiesystem nach einem der Ansprüche 1 bis 5, bei dem, wenn der Abstand einen vorbestimmten Schwellenwert überschreitet, eine Benachrichtigung an einen Benutzer des Uterus-Instruments übermittelt wird.
7. Kolpotomiesystem nach einem der Ansprüche 1 bis 6, wobei das Schneidelement automatisch deaktiviert wird, wenn der Abstand einen vorbestimmten Schwellenwert überschreitet.
8. Kolpotomiesystem nach einem der vorhergehenden Ansprüche, wobei das Uterus-Instrument umfasst:
dass der Griff ein erster Griffabschnitt ist (10);
einen zweiten Griffabschnitt (20);
dass die Welle eine erste Welle (45) ist, die mit dem ersten Griffteil funktionell verbunden ist;
dass der Ballon ein erster Ballon (40) ist, der an einem distalen Ende davon positioniert ist;
eine zweite Welle (30), die funktionell mit dem zweiten Griffabschnitt gekoppelt ist, wobei die zweite Welle einen zweiten Ballon (50) aufweist, der an einem distalen Ende davon positioniert ist; und
dass das Halteelement so konfiguriert ist, dass es in den zweiten Ballon der zweiten Welle eingreift, dass die erste Welle so konfiguriert ist, dass sie sich durch die zweite Welle und das Halteelement erstreckt, um den Zugang zu einer Operationsstelle zu ermöglichen.
9. Kolpotomiesystem nach Anspruch 8, wobei der erste Griffabschnitt ein beweglicher Griff und der zweite Griffabschnitt ein stationärer Griff ist.
10. Kolpotomiesystem nach Anspruch 8 oder 9, bei dem in der Operation der erste Ballon aufgeblasen wird, um die erste Welle in einem Uterus zu halten, und der zweite Ballon aufgeblasen wird, um eine Bauchhöhle abzudichten.
11. Kolpotomiesystem nach einem der vorhergehenden Ansprüche, bei dem das Halteelement ein Kolpotomiebecher ist.

Revendications

1. Système de colpotomie comprenant :

un instrument chirurgical (700) ayant un élément de découpe (742) à une extrémité distale de celui-ci ; et
un instrument utérin (100) ayant une poignée (10) accouplée fonctionnellement à un arbre (45) ayant un ballonnet (40) à une extrémité distale de celui-ci, l'arbre s'étendant à travers un élément de retenue (60) pour accéder à un site chirurgical, l'élément de retenue comprenant une pluralité d'émetteurs (430) disposés autour d'un anneau distal (440) de l'élément de retenue (60) pour émettre au moins un signal pour définir une zone de fonctionnement prédéterminée ;
ledit instrument chirurgical ayant en outre un récepteur (750) à une extrémité distale de celui-ci pour recevoir ledit au moins un signal émis à partir de ladite pluralité d'émetteurs (430) ;
un processeur configuré pour calculer une distance entre l'élément de découpe de l'instrument chirurgical et une extrémité de l'élément de retenue de l'instrument utérin pour déterminer si l'élément de découpe se trouve à l'intérieur de la zone de fonctionnement prédéterminée.

2. Système de colpotomie selon la revendication 1, dans lequel l'élément de retenue a un anneau proximal (410), l'anneau proximal (410) ayant une pluralité de montants (420) pour supporter l'anneau distal (440).

3. Système de colpotomie selon la revendication 2, dans lequel un émetteur de la pluralité d'émetteurs est incorporé à l'intérieur de l'anneau distal.

4. Système de colpotomie selon la revendication 2 ou 3, dans lequel la zone de fonctionnement prédéterminée est définie par la circonférence de l'anneau distal.

5. Système de colpotomie selon l'une quelconque des revendications 1 à 4, dans lequel l'au moins un signal est une onde sonore monofréquence ou une onde radio ou une onde électromagnétique.

6. Système de colpotomie selon l'une quelconque des revendications 1 à 5, dans lequel si la distance dépasse un seuil prédéterminé, une notification est relayée à un utilisateur de l'instrument utérin.

7. Système de colpotomie selon l'une quelconque des revendications 1 à 6, dans lequel si la distance dépasse un seuil prédéterminé, l'élément de découpe est automatiquement désactivé.

8. Système de colpotomie selon l'une quelconque des revendications précédentes, dans lequel l'instrument utérin comprend :

la poignée étant une première partie de poignée (10) ;
une seconde partie de poignée (20) ;
l'arbre étant un premier arbre (45) accouplé fonctionnellement à la première partie de poignée ;
le ballonnet étant un premier ballonnet (40) positionné à une extrémité distale de celui-ci ;
un second arbre (30) accouplé fonctionnellement à la seconde partie de poignée, le second arbre ayant un second ballonnet (50) positionné à une extrémité distale de celui-ci ; et
l'élément de retenue conçu pour mettre en prise le second ballonnet du second arbre, le premier arbre étant conçu pour s'étendre à travers le second arbre et l'élément de retenue pour accéder à un site chirurgical.

9. Système de colpotomie selon la revendication 8, dans lequel la première partie de poignée est une poignée mobile et la seconde partie de poignée est une poignée fixe.

10. Système de colpotomie selon la revendication 8 ou 9, dans lequel, en fonctionnement, le premier ballonnet est gonflé pour retenir le premier arbre dans un utérus et le second ballonnet est gonflé pour sceller une cavité abdominale.

11. Système de colpotomie selon l'une quelconque des revendications précédentes, dans lequel l'élément de retenue est une coupelle de colpotomie.




FIG. 1






FIG. 2






FIG. 5





FIG. 6






FIG. 9




FIG. 10






FIG. 11






FIG. 14





FIG. 15



X-X
FIG. 16




FIG. 17




FIG. 18




FIG. 19

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 2015351621 A1 [0005]

专利名称(译)	结肠镜系统用于腹腔镜子宫切除术		
公开(公告)号	EP3205298B1	公开(公告)日	2020-05-13
申请号	EP2017155486	申请日	2017-02-09
[标]申请(专利权)人(译)	柯惠有限合伙公司		
申请(专利权)人(译)	COVIDIEN LP		
当前申请(专利权)人(译)	COVIDIEN LP		
[标]发明人	MARCZYK STANISLAW CALDERONI ANTHONY		
发明人	MARCZYK, STANISLAW CALDERONI, ANTHONY		
IPC分类号	A61B17/42 A61B18/14 A61B34/20 A61B18/00		
CPC分类号	A61B17/42 A61B17/4241 A61B18/12 A61B2017/4216 A61B2017/4225 A61B2018/00559 A61B2018/00589 A61B2018/00601 A61B18/14 A61B34/20 A61B2017/00123 A61B2017/00221 A61B2017/320052 A61B2018/00607 A61B2018/0063 A61B2018/1412 A61B2034/2051 A61B2090/061 A61B17/320016 A61B34/70 A61B2017/00743		
代理机构(译)	MASCHIO , ANTONIO		
优先权	62/293444 2016-02-10 US 15/420625 2017-01-31 US		
其他公开文献	EP3205298A1		
外部链接	Espacenet		

摘要(译)

结肠切开术系统包括具有切割元件和在其远端处的接收器的外科器械和子宫器械。子宫器械具有手柄（10），手柄（10）可操作地联接至在其远端具有球囊（40）的轴（45），该轴延伸穿过保持构件（60）以进入手术部位，该保持构件包括用于发射至少一个信号的多个发射器（430）。计算手术器械的切割元件与子宫器械的保持构件的一端之间的距离，以确定切割元件是否在预定的操作区域内。

