

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
14 March 2002 (14.03.2002)


(10) International Publication Number
WO 02/19923 A1

PCT

- | | | |
|---|--|--|
| (51) International Patent Classification⁷: | A61B 17/08,
17/10 | [US/US]; 30 Cut Spring Road, Stratford, CT 06614 (US).
MILLER, Arnold [US/US]; 27 Intervale Road, Chestnut Hill, MA 02467 (US). |
| (21) International Application Number: | PCT/US00/24094 | |
| (22) International Filing Date: | 1 September 2000 (01.09.2000) | (74) Agents: WINTER, Gene, S. et al.; St. Onge, Steward, Johnston & Reens LLC, 986 Bedford Street, Stamford, CT 06905-5619 (US). |
| (25) Filing Language: | English | (81) Designated States (<i>national</i>): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW. |
| (26) Publication Language: | English | (84) Designated States (<i>regional</i>): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, |
| (71) Applicant (<i>for all designated States except US</i>): | ADVANCED VASCULAR TECHNOLOGIES, LLC
[US/US]; Units F9 and F10, Four Oxford Road, Milford, Ct 06460 (US). | |
| (72) Inventors; and | | |
| (75) Inventors/Applicants (<i>for US only</i>): | ALLEN, William, J. | |

[Continued on next page]

- (54) Title:** SURGICAL FASTENER AND DELIVERY SYSTEM



(57) Abstract: A surgical fastener (10) preferably made from a shape memory alloy is provided which can access internal tissue (18) or other synthetic material through a small surgical access port or incision. After the fastener (10) is deployed through layers (14, 16) of tissue, it assumes a shape that automatically applies to the layers of tissue an appropriate hemostatic compression which is relatively independent of tissue thickness. The fastener is a suitable replacement for conventional non bio-absorbable sutures and staples in certain clinical applications. Its shape, method of deployment and low force requirements make it suitable for standard surgical procedures and especially suitable for laparoscopic and other less invasive surgery where access to the wound site is limited, including endovascular surgery. A delivery instrument (50) for deploying the fastener is also provided.



IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

SURGICAL FASTENER AND DELIVERY SYSTEM

Field of Invention

The invention relates to a fastener and a deployment instrument for joining multiple layers of thin, flexible material. More specifically, the invention
5 relates to a surgical fastener and a deployment instrument for joining living tissue and/or synthetic materials which may be used as a substitute for tissue.

Background of the Invention

Historically, living tissue has been most commonly surgically repaired by thread, such as a suture, introduced by a pointed metal needle and tied
10 with just enough tension to establish hemostasis or control of bleeding by compressing the tissue. Correct tension is established by the surgeon based on observation and judgment derived from extensive training. Excess tension can cause necrosis (the localized death of living tissue) and eventual failure of the repair.

15 An alternate method of joining tissue using metal staples has evolved over the last 90 years to a point where specialized staples for both skin and internal tissue closure are in common use today. The staples, which have sharp points for penetrating tissue, are formed in place by delivery instruments which bend them to a permanent shape suitable for tissue
20 retention. The delivery instruments include mechanisms, such as an anvil,

which control to some extent the relationship between tissue and staple, including the compression necessary to control bleeding. To the extent that they do so, surgeon skill is less of a factor in successful wound closure.

For conventional surgery, the clinical results for suturing and stapling are essentially the same, but both have their disadvantages. Sutures are suitable for all types of wound closure, but require that the surgeon have adequate access to the wound site and possess the skill to choose and apply the suture correctly. Conventional staples can also be appropriate for internal use, but require that a strong, rigid anvil be placed behind the tissues to be joined. Furthermore, the application of staples requires that there be enough space for an instrument, which can produce the necessary force to form the staple against the anvil. Stapling, however, is generally faster and, as previously noted, requires a lower level of skill.

The recent development of a beneficial, less invasive technique for gall bladder removal has suggested the feasibility of other abdominal procedures, such as bowel and hernia repair, that require the remote application of an internal fastener. As a result, less invasive instruments have been developed for both suturing and stapling remotely from the wound site by the surgeon. At the same time, patient benefit considerations are driving the development of less invasive techniques for a full range of abdominal and thoracic procedures including coronary artery bypass and valve replacement.

To date, stapling has proven to be more suitable for less invasive surgery than suturing. Instruments developed for that purpose approximately replicate the functions of stapler developed for open surgery and are

approximately as easy to use. Instruments developed for less invasive suturing, on the other hand, are slow and cumbersome and do not solve the essential problem of tensioning the suture and tying the knot remotely. Sutures will find limited use in less invasive surgery but it is most likely that
5 related wound closure problems beyond the capability of conventional staples will be solved by innovative mechanical fasteners which can more easily be remotely applied.

For instance, a new fastener has been designed for a less invasive hernia repair in which a synthetic mesh is used to reinforce the repair by
10 anchoring it to surrounding tissue. Suturing is feasible but difficult. Conventional stapling is not feasible because an anvil cannot access the distal side of the tissue. The new fastener has the shape of a coil spring with the wire sharpened at one end and has been used successfully to attach the mesh by screwing the coil through it into the tissue. This new fastener can
15 access the wound site through a small port in the abdominal wall. This fastener, however, does not produce compression upon the synthetic and natural tissue layers and thus does not produce hemostasis because the fastener is screwed into the wound site in its natural shape. Because this fastener does not create hemostasis, it may not be suitable for a wide range
20 of surgical applications.

Other surgical fasteners have been fabricated from shape memory alloy. U.S. Patent No. 4,485,816 to Krumme discloses a shape-memory surgical staple that uses an electric current to heat the staple to make it close.

U.S. Patent No. 5,002,562 to Pyka et al. discloses a fastener made from shape memory alloy that has the shape of a suturing loop in its undeformed shape. As noted above, however, sutures and staples are not always desirable for all surgical application.

5 It is believed that other applications exist or will be identified for fastening layers of tissue where anvil access is not practical and where compression must be applied to the tissue to achieve hemostasis. For example, these criteria apply to the attachment of a graft more or less at right angles to another, larger, blood vessel ("end to side" anastomosis) such as
10 the aorta for vascular bypass purposes. The availability of a less invasive vascular bypass procedure implies a significant patient benefit. Another example is the use of the fastener in endovascular procedures to attach a graft within large vessels such as the aorta, iliac or femoral arteries to repair aneurysms and occlusions. Stents, which are currently used for this purpose,
15 are often insufficiently compliant to prevent leakage and consequent failure of the repair. Direct fixation of the graft to the inner wall of the vessel by the fasteners described herein may overcome this inherent problem of current techniques for endovascular repair.

 What is desired, therefore, is a mechanical fastener and deployment
20 instrument that can access internal tissue through a small surgical access port or incision and that can be applied conveniently and remotely.

Summary of the Invention

Accordingly, an object of the present invention is to provide a surgical fastener that can access internal tissue through a small surgical access port or incision.

5 It is a further object of the present invention to provide a surgical fastener that can be applied remotely.

It is yet another object of the present invention to provide a surgical fastener that uses the superelastic properties of a shape memory alloy without having to apply heat to the fastener.

10 It is still another object of the present invention to provide a deployment instrument that can be used to deploy the surgical fasteners of above.

These objects of the invention are achieved by a surgical fastener preferably made from a shape memory alloy that accesses internal tissue or other synthetic material through a small surgical access port or incision. After
15 the fastener is deployed through layers of tissue, it assumes a shape that automatically applies to the layers of tissue an appropriate hemostatic compression which is relatively independent of tissue thickness. The fastener is a suitable replacement for conventional non bio-absorbable sutures and staples in certain clinical applications. Its shape, method of deployment and
20 low force requirements make it it suitable for standard surgical procedures and especially suitable for laparoscopic and other less invasive surgery where

access to the wound site is limited, including endovascular surgery. The invention is expected to be especially useful for attaching synthetic grafts to an aorta.

Brief Description of the Drawings

5 FIGS. 1A, 1B and 1C are an isometric view and two side views, respectively, of the first embodiment of the surgical fastener in accordance with the invention.

FIG. 2 is an isometric view of the second embodiment of the surgical fastener in accordance with the invention.

10 FIG. 3 is a side cutaway view of the second embodiment of the surgical fastener of FIG. 2 in accordance with the invention.

FIG. 4 a side cutaway view of the third embodiment of the surgical fastener in accordance with the invention.

FIGS. 5A-5F are front cutaway views of a deployment instrument
15 showing the insertion of the surgical fastener of FIG. 1.

FIGS. 6A-6F are front isometric views of another embodiment of a deployment instrument showing the insertion of a surgical fastener.

FIG. 7 is a front isometric view of the deployment instrument of FIGS

5A-5F as it is shipped.

FIG. 8 is a front cutaway view of the deployment instruments of FIGS. 5A-5F and 6A-6F.

FIGS. 9A-9D are side cutaway views showing the use of a deployment
5 instrument with the surgical fastener of FIG. 2.

Detailed Description of the Invention

Surgical fasteners, each in accordance with the invention, are shown in FIGS. 1A-4. The surgical fastener is a one piece metal element appropriately configured during manufacture to hold layers of tissue in compression. To
10 apply the fastener, as shown in FIGS. 5A-5F, 6A-6F, and 9A-9D, a straight tube or needle included in a delivery mechanism is preferably used to hold and deflect the fastener from its final shape into a straight configuration. In application, the tube is either inserted through the tissue or held against the tissue to be joined and the fastener is pushed from the tube until the fastener
15 penetrates the tissue and gradually assumes its original shape, trapping and compressing the layers of tissue 18 between its various elements.

In order to straighten the various surgical wire fasteners described herein without permanent deformation, a superelastic alloy of nickel and titanium is preferably used to make the fasteners. The fastener is preferably
20 made from a commercial material Nitinol, which is referred to as a "shape memory alloy." Superelasticity can be conveniently likened to memory.

Although forced into a straight line after forming, the superelastic fastener is able to "remember" its former shape and to return to it when no longer constrained within a straight tube. Nitinol in superelastic form has an extremely high elastic limit, which allows large amounts of bending without permanent deformation. In general, Nitinol is capable of strain ratios of up to 8% without experiencing permanent deformation. For round wire, the fastener is designed to function within the limits of $d/2R$ equal to or less than 0.08, where d is the diameter of the wire and R is the radius to which the wire is formed. It should be noted that the fastener described herein can be made from any material so long as it is adequately elastic. Preferably, the material has superelastic characteristics.

The preferred embodiment of the fastener 10, shown in FIG. 1A-1C, is essentially that of the body of an extension spring having coils 12. At rest, the coils of this fastener 10 are spring biased towards each other so that a force F_A is required to effect separation of said coils. The force at which the coils just begin to separate is the preload value for the fastener. Additional force causes separation of the coils 12 as a function of the gradient of the fastener. Shown in FIG. 1C, layers of tissue 18 that are trapped between adjacent coils 12 of the fastener will be clamped with a force F_1 being substantially normal to the surface of the tissue 18 and having a value somewhat higher than the preload value of the fastener. This force, which is a function of fastener material, dimensions and winding technique, is chosen to insure hemostasis when vascular tissue is to be clamped. It should be noted that a compression spring could be used in place of an extension spring so long as the tissue is

thick enough that it is compressed between the coils of the fastener once it is in place. The theory and practice of winding preloaded coils of metallic wire is routinely practiced in the manufacture of extension springs and is well known to those skilled in the art.

5 When the fastener of FIG. 1A-1C is made of a superelastic material and the strain ratio limitation described above is observed, the fastener can be straightened to penetrate tissue 18 and then released to allow its coils to reform on both the proximate 14 and distal 16 sides of the tissue thereby clamping the tissue between two coils. The number of coils 12 is not
10 especially critical. At least two full coils 12 are required and more, such as four coils, are preferable to make placement in the tissue less critical. The coils 12 preferably have a diameter of 3/16 to 1/4 of an inch. Preferably, the end of the fastener inside of the body rests flush next to the adjacent coil so that the body will not be injured from the fastener end.

15 FIGS. 2 and 3 show another embodiment of the fastener 20 before and after installation in two layers 14, 16 of tissue 18. The presence of the tissue layers prevents the fastener from returning completely to its original state. The force required to spread the spring biased fastener apart by this amount therefore also represents the substantially normal compressive force F_2
20 applied to the layers of tissue 18. That force, which is a function of wire diameter and fastener geometry, is chosen by design to achieve homeostasis. Those parameters also determine the gradient or stiffness of the fastener as measured in terms of force F_2 versus deflection of the fastener. Since

different tissue thicknesses produce different deflections, and therefore different compressive forces, the gradient must be sufficiently low to maintain reasonable hemostasis over the normal range of tissue thickness without inducing necrosis.

5 FIG. 2 is an isometric view of the fastener 20 shown schematically in FIG. 3. The lower coil 24 penetrates the tissue and curves in a half circle to re-enter the tissue layers. The upper coils 22 bear on the tissue and tend to trap it inside of the larger lower coil. The number of upper coils 22 can vary without altering the essential behavior of the fastener 20. Preferably, two or
10 more coils 22 are used to help distribute clamping forces more uniformly about the lower coil thereby preventing misorientation of the fastener 20 in the tissue 18.

The fastener 40 in FIG. 4 has symmetrical coils to distribute stress uniformly on both sides of the tissues to be joined.

15 The fasteners in FIGS. 2-3 and 4 are similar to the fastener in FIG. 1A-1C in that they are spring biased and use coils to apply pressure. The coils in FIGS. 2-3 and 4 each have an axis that is oriented substantially transverse to the direction that the fastener takes when it is in a straightened form, whereas the coils in FIGS. 1A-1C each have an axis that is substantially
20 transverse to its straightened form.

The fasteners in FIGS. 1C, 3 and 4 all show a fastener clamping two

layers of living tissue 18 which include a proximal layer 14 and a distal layer 16 of tissue. The fasteners described herein, however, can fasten any type of materials together, such as a graft or synthetic fibers which may be used as a substitute for tissue, or a combination thereof. The synthetic fibers, for
5 example, may be a material such as Gore-Tex, Dacron or Teflon. Autogenous and nonautogenous human tissue, as well as animal tissue, may also be used.

For all fasteners described above, the leading end 21 of the fastener, shown in FIG. 2, can be sharpened for ease of penetration either by cutting
10 the wire on a bias or by tapering the end to a sharp point during manufacture of the fastener. The bias cut is commonly used to make sharp points on conventional staples and taper pointing is used to make a certain class of suture needles. Both techniques are well known to those skilled in the art. Other sharpening techniques such as trocar points may also be effectively
15 applied to the fastener. Alternatively or additionally, the tube 154 of the delivery instrument 150 that houses the fastener, as shown in FIGS. 5A-5F and 6A-6F, can have a sharpened tip which is used to penetrate the tissue 18 prior to pushing the fastener from said tube.

A wide variety of fasteners can be designed within the scope of this
20 invention for an equally wide variety of fastening purposes. Some of these shapes are shown in FIGS. 1A-4 and it should be apparent that other variations are both possible and likely as the invention becomes more widely applied.

The surgical fasteners described herein can also be used in applications that require the insertion of a fastener from the interior. For example, the fasteners can be used in endovascular procedures to attach a graft within large vessels such as the aorta or iliac arteries to repair

5 aneurysms or occlusions.

FIGS. 5A-5F show a first embodiment of a deployment instrument 50 and the method for inserting the fastener. The deployment instrument 50 consists of a plunger 52 having a head portion 60, a needle 54 having a head portion 55, and a sleeve 51 having a head portion 57 and a stop 56. The

10 plunger fits slidably inside a lumen of the needle 54, which fits slidably inside of the sleeve 51. FIGS. 5A-5F show the fastener 10 being used to attach a graft 16 to a blood vessel having a first layer of tissue 14 and an opposite wall 17. The fasteners described herein, however, can be used for any layers of material or tissue. Furthermore, the delivery instrument 50 can

15 deliver any of the fasteners described herein.

Depending on the situation, support for the lower membrane will be required in order to insert the fastener. This will normally be the rigidity of the body tissue itself or a mechanical support which is provided separately, often as an integral part of the instrument that deploys the graft.

20 For the deployment instrument shown in FIGS. 5A-5D, the head portion 60 of the plunger 52 has two stops attached to it. One stop 62 pivotally

engages the head portion 55 of the needle 54 and also pivotally engages the head portion 56 of the sleeve 51. The other stop 64 can engage the head portion 55 of the needle 54. These stops 63, 64 are used to control the amount of depth that the needle and/or fastener may be inserted into the tissue 18.

In FIG. 5A, the deployment instrument is shown ready to insert a fastener 10 into layers of tissue 18 with the tip of the instrument 50 placed against the tissue. First, the stop 62 is engaged against the head portion 55 of the needle such that the needle 54 and plunger 52 can be inserted into the tissue 18 in unison. The needle 54 and plunger 52 are inserted until the head portion 55 of the needle 54 rests upon the head portion 57 of the sleeve 51 as shown in FIG. 5B. It should be apparent that if the needle is inserted into a blood vessel, as shown in FIGS. 5A-5D, care should be taken not to insert the needle past the opposite wall 17 of the vessel.

In FIG. 5C, the stop 62 is swung to engage the stop 62 on the sleeve. This will enable the needle 54 to be raised while the plunger remains still with respect to the plunger 60. While the needle 54 is withdrawn, the restraining force of the needle upon the fastener is removed and the fastener begins to form in its unstressed and undeformed shape.

In FIG. 5D, the needle is raised until its head portion 55 engages stop 64. When the needle 54 engages stop 64, a doctor can be certain that the needle has exited the layers of tissue 18. The lower portion of fastener 10 will

now have formed itself in the shape of a coil.

In FIG. 5E, the stop is swung away from the head portion 55 such that the needle 54 of can be withdrawn fully. As shown, the fastener begins to form in its unstressed shape as the needle 54 is removed.

5 FIG. 5F shows the full withdrawal of the deployment instrument 50. The fastener 10 can now fully assume its unstressed shape. It should be noted that the unstressed coils of the fastener 10 shown in FIGS. 5D through 5F are shown having an exaggerated shape for the sake of clarity. The fastener 10 more accurately would appear as shown in FIG. 1C with the coils
10 exerting a compressive pressure upon the layers of tissue 18.

FIGS. 6A through 6F show a second embodiment of the delivery instrument 100 which can deliver any of the fasteners described herein. The plunger 102 has a head portion 110 having both a short stop 114 and a long stop 112 attached to it. The head portion 55 of the needle 104 has two slots
15 116 and 118 to accept the long 112 and short 114 stops, respectively, at different times of the process. The needle is slidingly accepted by sleeve 101 having a head portion 107. The tip of the delivery instrument 100, fastener 10 and needle 104 for FIGS. 6A-6F appear the same as in FIGS. 5A-5F, respectively, and are not shown for the sake of clarity.

20 First, as shown in FIG. 6A, the long stop 112 is brought in contact to the head portion 105 of the needle. The plunger 105 and needle 104 are then

inserted into the tissue in unison by pushing down in the direction of arrow 120 until the needle's head portion 105 comes into contact with the sleeve's head portion 107 as shown in FIG. 6B. The needle 104 and fastener have penetrated the layers of tissue.

5 The head portion of the plunger is then rotated as shown in FIG. 6C in the direction of arrow 122 until the long stop 112 can be inserted into slot 116. The needle's head portion 105 is then raised in the direction of arrow 124 until the needle's head portion 105 comes into contact with the short stop 114 as shown in FIG. 6D. In FIG. 6D, the needle 104 will be fully withdrawn from the
10 layers of tissue.

In FIG. 6E, the plunger's head portion 110 is rotated in the direction of arrow 126 until the short stop 114 can be inserted into slot 118. The needle's head portion is then fully raised in the direction of arrow 128 until the head portion 105 comes into contact with the plunger's head portion 110. The
15 needle 104 is now fully retracted from the fastener which should be fastened in the tissue and formed in its unstressed state.

It should be apparent that many types of stops could be used to position the needle 54 and plunger 53 of the deployment instrument 50. For example, the needle could function with only a single stop attached to the
20 shaft of the plunger. Alternatively, visual indicators could also be used, but would be inherently less reliable. It should be apparent that the delivery instrument as shown in FIGS. 5A-5F and 6A-6F could function properly

without the short stops 64, 114, but not as reliably. Also, the delivery instrument as shown in FIGS. 5A-5F and 6A-6F could function without the sleeve 51 or 101, respectively. It should be apparent that a plurality of any of these deployment instruments described herein could be integrated in a single deployment instrument for sequential or simultaneous deployment of the fastener.

FIG. 7 shows a deployment instrument 50 as it might be shipped from a manufacturer. The surgical fastener 10 preferably is already inserted and straightened inside of the needle 54 for ease of use. The deployment instrument 50 can be shipped with or without the sleeve 51, which can be added later when the fastener is ready to be inserted.

FIG. 8 shows an enlarged view of the needle of either FIGS. 5A-5F or 6A-6F with a fastener inside of it. A typical aspect ratio of the length to diameter for this device can be in the order of 40 or 50 for less invasive use. The diameter of the fastener is preferably between .012 to .014 of an inch, more preferably its diameter is .013 of an inch, the inside diameter of the lumen 53 of the needle 54 is preferably .017 of an inch and the outside diameter of the needle is preferably .025 of an inch.

FIGS. 9A-9D show a third embodiment of the deployment instrument 150 and the method for inserting the fastener. The third embodiment of the deployment instrument 150 is different from the first two embodiments in that the retraining tube 154 is not sharpened to penetrate tissue. Thus, the

surgical fastener used with the deployment instrument 150 should have a sharpened end to penetrate tissue. The deployment instrument 150, consisting of slender tubes and rods, is inherently small in diameter compared to its length. Thus, FIGS. 9A-9D are illustrated with a much less favorable aspect ratio for the sake of clarity. A typical aspect ratio of the length to diameter for this device can be in the order of 40 or 50 for less invasive use. It should be apparent that other ergonomically sophisticated designs for the deployment instrument 150 can be envisioned and realized. It should also be apparent that several of these deployment instruments could be integrated in a single deployment instrument 150 for sequential or simultaneous deployment of the fastener.

FIG. 9A shows a deployment instrument 150 resting on layers of tissue 18 to be joined. The deployment instrument 150 restrains a fastener by placing stress upon it. The fastener 20, which in this example is the fastener of FIG. 1, resides in a substantially straightened form entirely within the restraining tube 154. It should be apparent that any of the fasteners described herein if given a pointed end 21 can be used with the deployment instrument of FIGS. 9A-9D. The pointed end 21 of the fastener 20 is facing toward the tissue. A plunger 152 rests on the fastener 20 and is configured to push the fastener partially out of the restraining tube until it stops against shield as in FIG. 9B.

FIG. 9B shows the fastener partially installed by the plunger. As the fastener emerges from its restraining tube it penetrates the proximal 14 and

distal 16 layers of tissue and gradually assumes the remembered shape of its lower coil, piercing the distal tissue layer 16 again as it turns upward.

The lower coil 24 of the fastener 20, however, preferably remains substantially on the distal side of the tissue. At this point, pusher 152 bears on the shield
5 and can progress no further. Depending on the clinical application, it may be necessary to support the tissue distally during penetration.

FIG. 9C shows restraining tube 154 moving upward, gradually freeing the fastener 20 to assume its remembered shape. It will obviously not be able to do so until the restraining tube 154 is completely clear which happens when
10 the restraining tube stops against pusher 152. The restraining tube 154 tends to pull the fastener 20 out of the tissue due to friction producing forces exerted by the fastener on the restraining tube as the former tries to assume its remembered shape. This tendency is offset by the pusher 152 bearing on the upper end of the fastener 20 as the restraining tube 154 moves upward.

15 FIG. 9D shows restraining tube 154 in its fully upward position as determined by the plunger 152. The restraining tube 154 has cleared the fastener 20 and allowed it to assume its remembered, coiled shape 22, bearing against the tissue 18. The fastener 20 forms within the guide tube 151 suggesting that the guide tube 151, properly shaped, may serve to guide
20 the fastener 20 as it forms above the tissue 18. This may be a useful feature, especially for more complex fasteners which may re-form incorrectly when released from constraint.

The guide tube 151 can serve a dual function as described above, providing a reference stop for plunger 152 and a forming guide for the fastener 20. In some cases the guide tube 151 will not be required.

It should be understood that the foregoing is illustrative and not limiting
5 and that obvious modifications may be made by those skilled in the art without departing from the spirit of the invention. Accordingly, reference should be made primarily to the accompanying claims, rather than the foregoing specification, to determine the scope of the invention.

What is claimed is:

1. A surgical fastener for securing together a plurality of layers of material, comprising:
an element having first and second ends and made from a material which enables the element to be transformed from a first shape to a second
5 shape upon the occurrence of a predetermined condition, the first shape of the element enabling its first end to penetrate the plurality of layers of material, and with the second shape of the element being in the form of a spring with a plurality of spring biased coils.
2. The surgical fastener according to Claim 1, wherein the second shape of the first end of the element has the shape of an end coil with the first end being circumferentially aligned with an adjacent coil of the element when it is in its second shape.
3. The surgical fastener according to Claim 1, wherein the second shape of the element forms an extension spring with coils, which are spring biased towards each other.
4. The surgical fastener according to Claim 1, wherein the first shape of the element is substantially straight.
5. The surgical fastener according to Claim 4, and further including:
a hypodermic needle having a lumen sized to slidably receive the
element in its first shape and an externally manipulatable plunger sized to
slidably move through said lumen to advance the element stored therein to a
5 distal end of the needle.
6. The surgical fastener according to Claim 5, wherein the element is stored under stress within the lumen of the needle and said predetermined condition is a removal of said stress upon emergence of said element from the lumen in response to an actuation of said plunger.

7. The surgical fastener according to Claim 1, wherein the element is made from a shape memory alloy.
8. The surgical fastener according to Claim 7, wherein the shape memory alloy is Nitinol.
9. The surgical fastener according to Claim 1, wherein one of the layers is tissue and wherein said coils are spring biased so as to produce between at least one adjacent pair of coils a compressive hemostasis gripping force when said tissue and said other layer of material are between said pair of adjacent
5 coils.
10. A surgical fastener for securing together a plurality of layers of material, at least one of which layer is a living tissue, comprising:
an element having first and second ends said element transforming from a first substantially straight wire shape to a second shape upon an
5 occurrence of a predetermined condition, the first shape of the element enabling a penetration of its first end through the plurality of layers of material, and wherein the second shape of the element includes at least one coil at the second end of the element, said coil being spring biased towards the first end of the element, whereby the plurality of layers of material can be pressed
10 together between the coil and said first end.
11. The surgical fastener according to Claim 10, wherein the second shape of the first end has a shape of an extension spring.
12. The surgical fastener according to Claim 11, wherein the element in its first shape defines an axis, and wherein the second shape's coil is wound about a second axis that is substantially parallel with the first axis.
13. The surgical fastener according to Claim 11, wherein the element in its first shape defines an axis, and wherein the second shape's coil is wound about a second axis that is substantially transverse with the first axis.

14. The surgical fastener according to Claim 10, wherein the element is made from a shape memory alloy.

15. The surgical fastener according to Claim 14, wherein the element is made of Nitinol.

16. The surgical fastener according to Claim 10, wherein the element is made of plastic.

17. The surgical fastener according to Claim 10, and further including:
a hypodermic needle having a lumen sized to slidingly receive the
element in its first shape, and an externally manipulatable plunger sized to
slidingly move through said lumen to advance the element stored therein to a
5 distal end of the needle.

18. The surgical fastener according to Claim 17, wherein the element is stored under stress within the lumen of the needle and said predetermined condition is a removal of said stress upon emergence of said element from the lumen in response to an actuation of said plunger.

19. A surgical fastener delivery system for securing together a plurality of layers of material, comprising:

an element having first and second ends and made from a material
which enables the element to be transformed from a first substantially straight
5 pre-stressed wire shape to a second shape upon a removal of the stress upon
the element, the first shape of the element enabling its first end to penetrate
the layers of material, and with the second shape of the element including at
least one spring biased coil;

a restraining tube having a lumen sized to slidingly receive the element
10 in its first shape and store the element under said stress; and

an externally manipulatable plunger sized to slidingly move through said lumen to advance the element stored therein to a distal end of the restraining tube; and

- 15 a first stop located on the plunger and oriented so as to engage the tube when the element has penetrated the layers of material, whereby emergence of said element from the lumen in response to an actuation of said plunger removes said stress upon the element so that it can assume its second shape and grip the layers of material.

20. The surgical fastener delivery system of Claim 19, wherein the restraining tube is a hypodermic needle, and further comprising:

 a sleeve to slidingly receive the hypodermic needle and limit its advance there through; and

- 5 a second stop attached to the plunger for engaging the sleeve.

21. The surgical fastener delivery system of Claim 20, wherein said plunger is rotatably movable within said hypodermic needle, said hypodermic needle is rotatably movable within said sleeve and said first stop can also engage the sleeve.

22. The surgical fastener delivery system of Claim 20, wherein the restraining tube is a hypodermic needle and the first and second stops are pivotally attached to the plunger.

23. A surgical fastener delivery system for securing together a plurality of layers of material, comprising:

- an element having first and second ends and made from a shape memory alloy that enables the element to be transformed from a first
5 substantially straight pre-stressed shape to a second shape upon a removal of the stress upon the element, the first shape of the element enabling its first end to penetrate the layers of material, and with the second end of the second shape of the element including a plurality of coils being spring biased;

a hypodermic needle having a lumen sized to slidably receive the
10 element in its first shape and store the element under said stress; and
an externally manipulatable plunger sized to slidably move through
said lumen to advance the element stored therein to a distal end of the
restraining tube.

24. The surgical fastener according to Claim 1, wherein the first end of the
second shape of the element forms an extension spring with coils that are
spring biased.

25. A method for inserting a surgical fastener into a plurality of layers of
material, the steps comprising:
providing an element having first and second ends and made from a
material which enables the element to be transformed from a first substantially
5 straight shape to a second shape upon a removal of stress on the element,
the first shape of the element enabling its first end to penetrate the plurality of
layers of material, wherein the second shape of the element includes at least
one coil at the second end of the element being spring biased towards the first
end of the element,
10 placing the element under stress in a restraining device;
removing the first end from the restraining device such that it
penetrates the plurality of layers of material;
removing the element from the restraining device such that the stress
from the restraining device is removed and the element transforms from the
15 first shape to the second shape; and
pressing together between the coil and said first end the plurality of
layers of material.

26. The method for inserting a surgical fastener of Claim 25, wherein the
restraining device is a hypodermic needle, and further comprising the step of
penetrating the needle through the layers of material such that the element
penetrates the plurality of layers of material.

27. The method for inserting a surgical fastener of Claim 26, further comprising the steps of:

guiding the hypodermic needle through a sleeve; and
limiting an advance of the hypodermic needle through the sleeve.

28. The method for inserting a surgical fastener of Claim 25, further comprising the steps of:

guiding the restraining device through a sleeve; and
limiting an advance of the restraining device through the sleeve.

29. The method for inserting a surgical fastener of Claim 25, further comprising the steps of:

guiding the restraining device through a sleeve; and
limiting an advance of the restraining device through the sleeve.




FIG. 1A




FIG. 2




FIG. 1B




FIG. 3




FIG. 1C






FIG. 4

2/6



3/6



4/6




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E






FIG. 6F

5/6



6/6




FIG. 9D

FIG. 9C

FIG. 9B

FIG. 9A

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US00/24094

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : A61B 17/08; A61B 17/10

US CL : 606/151-158, 215-221

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 606/151-158, 215-221

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

BRS: spring, coil, helix, fastener, memory or nitinol or (ni adj ti), bind, pinch, clamp, clasp, (closure or closing)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,258,000 A (Gianturco) 02 November 1993, whole document	1-29
Y	US 5,830,221 A (Stein et al.) 03 November 1998, whole document.	1-29
Y	US 5,810,882 A (Bolduc et al.) 22 September 1998, whole document.	1-29
A	US 5,259,394 A (Bens) 09 November 1993, whole document.	1-29

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

02 NOVEMBER 2000

Date of mailing of the international search report

28 DEC 2000

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

JONATHAN GOLDBERG

Telephone No. (703) 308-0161

专利名称(译)	手术紧固件和输送系统		
公开(公告)号	EP1237484A1	公开(公告)日	2002-09-11
申请号	EP2000961483	申请日	2000-09-01
[标]申请(专利权)人(译)	高级VASULAR TECH		
申请(专利权)人(译)	血管先进技术有限责任公司		
当前申请(专利权)人(译)	血管先进技术有限责任公司		
[标]发明人	ALLEN WILLIAM J MILLER ARNOLD		
发明人	ALLEN, WILLIAM, J. MILLER, ARNOLD		
IPC分类号	A61B17/08 A61B17/00 A61B17/04 A61B17/06 A61B17/064 A61B17/068 A61B17/10		
CPC分类号	A61B17/064 A61B17/0469 A61B17/068 A61B17/083 A61B2017/00867 A61B2017/06076 A61B2017/06171 A61B2017/0649		
优先权	09/321077 1999-05-27 US 60/087007 1998-05-28 US		
外部链接	Espacenet		

摘要(译)

优选地，由形状记忆合金制成的外科紧固件（10）可以通过小的外科进入端口或切口进入内部组织（18）或其他合成材料。在紧固件（10）穿过组织的层（14,16）展开之后，它呈现自动施加到组织层的形状，其具有相对独立于组织厚度的适当的止血压缩。在某些临床应用中，紧固件是传统的非生物可吸收缝线和U形钉的合适替代品。其形状，部署方法和低力要求使其适用于标准外科手术，尤其适用于腹腔镜和其他微创手术，其中伤口部位的进入受限，包括血管内手术。还提供了一种用于展开紧固件的输送器械（50）。