



US010307146B2

**(12) United States Patent
Kim****(10) Patent No.: US 10,307,146 B2
(45) Date of Patent: Jun. 4, 2019****(54) LAPAROSCOPIC PORT SITE CLOSURE
DEVICE**(2013.01); *A61B 2017/00473* (2013.01); *A61B*
2017/00637 (2013.01); *A61B 2017/00663*
(2013.01); *A61B 2017/06042* (2013.01)(71) Applicant: **Ki Seong Kim**, Gyeonggi-do (KR)**(58) Field of Classification Search**(72) Inventor: **Ki Seong Kim**, Gyeonggi-do (KR)CPC *A61B 17/0057*; *A61B 17/06004*; *A61B*
17/06114; *A61B 17/0482*; *A61B*
17/06109(73) Assignee: **Ki Seong Kim**, Gyeonggi-do (KR)

See application file for complete search history.

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 66 days.**(56) References Cited**

U.S. PATENT DOCUMENTS

(21) Appl. No.: **15/104,189**5,964,773 A * 10/1999 Greenstein *A61B 17/0469*
606/144(22) PCT Filed: **Aug. 31, 2015**2012/0035623 A1 * 2/2012 Bagaoisan *A61B 17/0057*
606/144(86) PCT No.: **PCT/KR2015/009109**

FOREIGN PATENT DOCUMENTS

§ 371 (c)(1),

(2) Date: **Jun. 13, 2016**JP 2009-279464 12/2009
JP 2012-515020 7/2012
JP 2014-511205 5/2014
KR 101132070 4/2012
WO WO 2010/081096 7/2010(87) PCT Pub. No.: **WO2016/080639**PCT Pub. Date: **May 26, 2016**

* cited by examiner

(65) Prior Publication Data

US 2017/0245846 A1 Aug. 31, 2017

Primary Examiner — Richard G Louis**(30) Foreign Application Priority Data**(74) *Attorney, Agent, or Firm* — IP & T Group LLP

Nov. 21, 2014 (KR) 10-2014-0163452

(57) ABSTRACT**(51) Int. Cl.***A61B 17/00* (2006.01)*A61B 17/34* (2006.01)*A61B 17/04* (2006.01)*A61B 17/06* (2006.01)**(52) U.S. Cl.**CPC *A61B 17/0057* (2013.01); *A61B 17/0482*
(2013.01); *A61B 17/06004* (2013.01); *A61B*
17/06109 (2013.01); *A61B 17/06114*
(2013.01); *A61B 17/34* (2013.01); *A61B*
17/06119 (2013.01); *A61B 2017/0023*

Disclosed is a laparoscopic port site closure device. The device is configured such that a cartridge receiving a surgical suture therein is provided at a fore-end of a needle guide for port site closure; the surgical suture is caught in a needle tip that is pierced through a body tissue by being guided by the needle guide; and when the needle is withdrawn, the surgical suture is pulled out along a path through which the needle was pierced into the tissue, and the surgical suture is tied outside a patient's body, thereby being capable of closing a laparoscopic port site.


7 Claims, 14 Drawing Sheets

FIG. 1




FIG. 2a




FIG. 2b




FIG. 3




FIG. 4a




FIG. 4b




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16





FIG. 17



1

LAPAROSCOPIC PORT SITE CLOSURE DEVICE

This application is a national stage application of PCT/KR2015/009109 filed on Aug. 31, 2015, which claims priority of Korean patent application number 10-2014-0163452 filed on Nov. 21, 2014. The disclosure of each of the foregoing applications is incorporated herein by reference in its entirety.

TECHNICAL FIELD

The present invention relates generally to a laparoscopic port site closure device. More particularly, the present invention relates to a laparoscopic port site closure device configured such that a cartridge receiving a surgical suture therein is provided at a fore-end of a needle guide for port site closure; the surgical suture is caught in a needle tip that is pierced through, a body tissue by being guided by the needle guide; and when the needle is withdrawn, the surgical suture is pulled out along a path through which the needle is pierced into the tissue, and the surgical suture is tied outside a patient's body, thereby being capable of closing a laparoscopic port site.

BACKGROUND ART

In general, laparoscopic surgery, unlike conventional open surgical procedures, refers to a surgical technique where four to six incisions about 0.5~1.2 cm in size are made on the patient's abdomen, and trocars, which have a diameter of 0.5~1.2 cm and are 15~16 cm long, are placed through these incisions. A light source, a camera, and surgical instruments are then introduced into the abdomen through the trocars. The surgeon performs the procedure, watching a television monitor on which the camera transmits an image of the organs inside the abdomen.

Laparoscopic surgery is used for cholecystectomy, bile duct stone removal, hepatic duct stone removal, appendectomy, and removal of tumors in a variety of organs. Patients with laparoscopic surgery have much less pain, fewer complications such as enteroplegia, shorter hospital stays, rapid recovery, and less post-operative scarring compared to patients with open surgical procedures.

For laparoscopic surgery, after a plurality of trocars is placed into a patient's abdomen, carbon dioxide gas is used to inflate the abdomen through one of the trocars in order to give the surgeon room to work. The endoscope and surgical instruments are then introduced through other trocars. The surgeon performs a surgery for the affected area, monitoring the surgical site.

After the procedure, in order to close the incisions, a trocar site closure tool is used. The trocar site closure tool is configured such that the incisions are closed by stitching while the needle is held by the forceps that are placed into the abdominal cavity through the trocar. After closing the incisions, in order to prevent the stitches from being untied, opposite ends of the surgical suture are pulled out of the patient's body through the trocar, and the knots are tied outside the patient's body. After tying the knots, the knots are formed into the abdominal cavity by pushing the knots using a compressor.

However, the conventional trocar site closure tool for laparoscopic surgery described above is problematic in that when the surgical suture, which is pulled out through the

2

incision along with the needle, is pulled using the forceps, the surgical suture may be easily cut by the pressure of the forceps.

Further, after stitching the incisions, to prevent the stitches from being untied, the knots are tied. When opposite ends of the surgical suture are pulled out of the patient's body in order to tie the knots, an additional instrument, such as forceps or pincette, is required.

As another related art, a fascial closure device is shown in FIG. 1.

The fascial closure device, which is in a tube shape for being introduced into a port site, includes: a tubular body 1 formed with needle guides 2 that face each other and guide insertion of a needle 3; and a pair of wings 5 being mounted to a lower portion of the tubular body 1, and being opened and closed using cam method, wherein each of the wings 5 is provided with a silicon pad 6 at a location where the needle 3 penetrates through, and the wings 5 are configured to be opened by rotating an operating stick 4 and configured to be closed by reversely rotating the operating stick 4.

The conventional fascial closure device solves a few of the above problems occurring in the related art. However, the fascial closure device is still problematic in the closure process. Reference will be made to the closure process using the conventional, fascial closure device.

As shown in FIGS. 2 and 3, the needle 3 penetrates through a tissue along the guide path 2 by threading the surgical suture 7. Here, the needle 3 is placed on the silicon pad 6 of the wing 5. When the needle 3 is further pushed into the silicon pad 6, a needle tip penetrates therethrough. After that, when the needle 3 is pulled out, the surgical suture 7 remains compressed in the silicon pad 6.

After the surgical suture 7 is compressed in the silicon pad 6 of the wings 5, the needle 3 is removed. The operating stick 4 is then rotated so as to close the wings 5, whereby the compressed surgical suture 7 is concentrated around the axis of the tubular body 1. When the tubular body 1 is withdrawn, the surgical suture 7 is pulled out and tied, whereby the closure is completed.

However, the conventional fascial closure device is problematic in that the suture area is easily infected by the surgical suture that is placed thereon during the recovery because the surgical suture, which penetrates through a tissue around the port site, is pulled out of a patient's body through the port.

Further, the conventional fascial closure device requires cutting the surgical suture into a predetermined length and threading the needle with the surgical suture. Thus, the procedure is inconvenient. The conventional fascial closure device is further problematic in that when the binding force of the silicon pad to the surgical suture becomes weak, it is difficult to pull out the surgical suture, thereby requiring additional work.

Further, in the process of threading the surgical suture in the needle, a surgeon or a nurse may be stuck or infected by the needle. In the process of closing a plurality of ports, the above mentioned problems occur repeatedly, whereby the operation time may be long.

DISCLOSURE

Technical Problem

Accordingly, the present invention has been made keeping in mind the above problems occurring in the related art, and the present invention is intended to propose a laparoscopic port site closure device.

The present invention is configured such that a tubular body of the laparoscopic port site closure device is provided with a detachable cartridge at an end thereof so as to be capable of being repeatedly used by replacing only the cartridge. Thus, the laparoscopic port site closure device according to the present invention is convenient and kept free from spreading infection.

The present invention is configured such that the cartridge includes wings capable of being open enough to fit a location where a needle is inserted; and surgical suture being received therein, the surgical suture temporarily locked to the wings. Thus, the laparoscopic port site closure device according to the present invention does not require tying the surgical suture, whereby it is possible to realize speedy closure.

The present invention is configured such that the surgical suture, which is placed in the abdominal cavity, is simply pulled out of a patient's body in order to close an opening in the tissue. Thus, the laparoscopic port site closure device according to the present invention prevents an incision area, namely an opening port site, from intervention of the surgical suture therein.

The present invention includes a needle for catching and withdrawing the surgical suture that is placed in the abdominal cavity. Thus, the laparoscopic port site closure device according to the present invention prevents the surgical suture from slipping off from the needle.

The present invention is configured such that the surgical suture that is received in the laparoscopic port site closure device is provided with an additional structure at opposite ends thereof so as to be caught and pulled out using the needle. Thus, the laparoscopic port site closure device according to the present invention realizes easy closure.

The present invention is configured such that the cartridge, in which the surgical suture is received, is replaceable. Thus, the laparoscopic port site closure device according to the present invention is capable of being used repeatedly, thereby economical.

Technical Solution

In order to achieve the above object according to one aspect of the present invention, there is provided a laparoscopic port site closure device.

The laparoscopic port site closure device, which is in a tube shape for being introduced into a port site, includes: a tubular body provided with needle guides that face each other and guide insertion of a needle; wings mounted to a lower portion of the tubular body such that the wings are opened and closed through a cam method; and an operating stick penetrating through the tubular body to operate the wings by being rotated to push and open the wings and to pull and close the wings by being rotated reversely. The laparoscopic port site closure device further includes: a replaceable cartridge provided on a lower end of the tubular body to be detachably combined with the operating stick, wherein the cartridge is provided with the wings capable of being opened by operating the operating stick, and provided with a compartment for receiving surgical suture therein, wherein the laparoscopic port site closure device is configured such that opposites ends of the surgical suture in the compartment are threaded through the wings such that the ends of the surgical suture are pulled out of a patient's body by being caught by a suture slot of a needle that is pierced into the patient's body from outside.

The needle may include a suture slot for catching and pulling out a surgical suture by being concavely formed on a needle tip in an opposite direction of pulling the surgical suture.

The surgical suture may be received at a lower end of the cartridge, wherein each end of the surgical suture may be provided with a spiral coil, with a stopper provided at each end of the coil, such that the surgical suture is easily caught in the suture slot. Herein, the surgical suture is folded and received in a case to be easily unfolded toward outside when being pulled out of the case.

Attachment and detachment of the cartridge and operation of the wings that are provided in the cartridge may be dependent on a location of the operating stick. To achieve this, the device may be provided with protrusions and grooves.

Advantageous Effects

According to the present invention having the above-described characteristics, the advantageous effects of the present invention are as follows. The present invention is configured such that a tubular body of the laparoscopic port site closure device is provided with a detachable cartridge at an end thereof so as to be capable of being repeatedly used by replacing only the cartridge. Thus, the present invention is convenient and kept free from transmitting infection. The present invention is further configured such that the cartridge includes wings capable of being open enough to fit a location where a needle is inserted; and surgical suture being received therein, the surgical suture temporarily locked to the wings. Thus, the laparoscopic port site closure device according to the present invention does not require tying the surgical suture, whereby it is possible to realize speedy closure of an incision site. The present invention is further configured such that the surgical suture, which is placed in the abdominal cavity, is simply pulled out of a patient's body in order to close an opening in the tissue. Thus, the laparoscopic port site closure device according to the present invention prevents an incision area, namely an opening port site, from intervention of the surgical suture therein, thereby realizing speedy recovery. The present invention includes a needle for catching and withdrawing the surgical suture that is placed in the abdominal cavity. Thus, the laparoscopic port site closure device according to the present invention prevents the surgical suture from slipping off the needle, thereby realizing a speedy and safe procedure.

The present invention is configured such that the surgical suture that is received in the laparoscopic port site closure device is provided with an additional structure at opposite ends thereof so as to be caught and pulled out using the needle. Thus, the laparoscopic port site closure device according to the present invention realizes easy closure of an incision site. The present invention is configured such that the cartridge, in which the surgical suture is received, is replaceable. Thus, the laparoscopic port site closure device according to the present invention is capable of being used repeatedly and is thereby economical.

DESCRIPTION OF DRAWINGS

FIG. 1 is a view illustrating a conventional laparoscopic port site closure device;

FIGS. 2a and 2b are sectional views of essential portions illustrating a closure process using the device of FIG. 1;

FIG. 3 is a schematic view illustrating a final tie structure of surgical suture in the closure process of FIG. 1;

5

FIG. 4a is a perspective view illustrating an appearance of the present invention;

FIG. 4b is a partial exploded perspective view of FIG. 4a;

FIG. 5 is a perspective view of the present invention illustrating a state where a needle is inserted into a wing by opening the wing;

FIG. 6 is a view illustrating a cartridge according to the present invention;

FIG. 7 is an exploded perspective view illustrating the cartridge according to the present invention;

FIG. 8 is a view illustrating a configuration of an operating stick that operates the cartridge according to the present invention;

FIGS. 9 to 12 are views illustrating operation of the cartridge in response to manipulation of the operating stick according to the present invention;

FIG. 13 is a view of an essential portion illustrating a configuration of the needle according to the present invention;

FIG. 14 is a view illustrating a structure of surgical suture according to the present invention;

FIG. 15 is a schematic view illustrating a closure process using a laparoscopic port site closure device according to the present invention;

FIG. 16 is a schematic view illustrating a state where the surgical suture is caught in the needle according to the present invention; and

FIG. 17 is a schematic view illustrating a state of a port site being finally sutured by the surgical suture according to the present invention.

BEST MODE

Reference will now be made in greater detail to an exemplary embodiment of the present invention, an example of which is illustrated in the accompanying drawings.

As shown in FIGS. 4 to 7, a laparoscopic port site closure device according to the present invention, which is in a tube shape for being introduced into a port site, includes: a tubular body provided with needle guides that lace each other and guide insertion of a needle; wings mounted to a lower portion of the tubular body such that the wings are opened and closed through a cam method; and an operating stick penetrating through the tubular body to operate the wings by being rotated to push and open the wings and to pull and close the wings by being rotated reversely. The laparoscopic port site closure device further includes: a replaceable cartridge 30 provided on a lower end of the tubular body 10 to be detachably combined with the operating stick 20, wherein the cartridge 30 is provided with the wings 33 capable of being opened by operating the operating stick, and provided with a compartment 32 for receiving surgical suture 40 therein, wherein the laparoscopic port site closure device is configured such that opposites ends of the surgical suture 40 in the compartment are threaded through the wings 33 such that the ends of the surgical suture are pulled out of a patient's body by being caught by a suture slot of a needle 50 that is pierced into the patient's body from outside.

The tubular body 10 may be divided into two parts, and may include a cone-shaped handle 11 and a tube that extends from the handle, wherein inner protrusions 12 are provided inside of the tube at a lower portion thereof at positions facing each other; needle guide holes 13 are provided on the handle 11 for guiding introduction and withdrawal of the needle, the needle guide holes ranging from an upper portion of the handle 11 to a side wall of the tube at opposite

6

positions; and a crank-shaped guide groove 14 is provided inside the handle 11 and guides a rotation and forward-backward movement of the operating stick 20 and fixes a location of the operating stick.

The guide groove 14 is provided in each half of the tubular body, wherein the guide groove 14 includes an inward groove and an outward groove 14a and 14b so as to form the crank shaped guide groove 14.

The operating stick 20 may include a handle 21 and a rod that extends from the handle, wherein outer protrusions 22 that are disposed opposite to each other are provided at an end of the rod, and guide protrusions 23 that are disposed opposite to each other are provided below the handle 21 by protruding and serve to mount and demount the cartridge 30 such that the cartridge is combined with the tubular body 10.

The cartridge 30 may include: a first support 300 including a mounting slot 301 provided in the center thereof, and locking channels 302 disposed opposite to each other provided on an outer circumferential surface thereof; a second support 310 provided beneath the first support, the second support being in a planar shape so as to support a surface of each of the wings 33, and including wing protrusions 311 disposed opposite to each other as a pivot of the wings; a third support 320 being in a planar shape rotated at an angle of 90 degrees relative to the second support, having a width to come into close contact with the wings 33 when the wings are closed, and including the compartment 32 that is in a cone shape and is provided at a lowermost end thereof and a cover 322 for covering the compartment; and the wings 33 each including: a wing hole 331 for being engaged with the wing protrusions 311 of the second support 310; an arch-shaped link hole 333 that is provided outside the wing hole 331, the link hole 333 having an opening at an edge thereof with a ridge 334 provided by protruding in the opening; a mounting hole 335 for mounting an end of the surgical suture 40; and a communication slot 336 provided on an outer surface of the wing to communicate with the mounting hole 335, wherein the wings comprise a pair of wings that are disposed opposite to each other.

When the cartridge 30 including the wings 33 is assembled with the tubular body, the cartridge may share the same center point as the tubular body and may have no protruding surfaces.

The compartment 32 may include a notch 337 provided at a portion of an outer surface thereof so as to serve as a suture outlet for the surgical suture that is received therein.

The surgical suture 40 may be received at a lower end of the cartridge 30, wherein each end of the surgical suture 40 may be provided with a spiral coil 42, with a stopper 43 provided at each end of the coil, such that the surgical suture is easily caught in the suture slot. Herein, the surgical-suture is folded and received in a case 45 to be easily unfolded toward outside when being pulled out of the case.

Further, the spiral coil 42 that is combined with the surgical suture may include a silicon tube 46 fitted over a junction between the spiral coil and the surgical suture.

An end of the coil, which is made of metal, may be melted to form a bail-shaped stopper 43.

The spiral coil 42 may be made of a metal wire having a diameter of 0.1~0.15 mm by coiling the wire such that the coil is extended when pulled by an external force.

The needle 50 may be long enough to reach from the needle guide holes 13 to the wings 33 that are opened, and the needle 50 may be provided with a suture slot 52 at a tip thereof by being concavely formed thereon.

In other words, the suture slot **52** of the needle **50** may be concavely formed on the needle tip in an opposite direction of pulling the surgical suture so as to catch and pull out the surgical suture.

Reference numeral **11a** denotes a handle cover of the tubular body for allowing easily recognizing a lock or an unlock state of the operating stick **20**, and reference numeral **10a** denotes a locking clip for assembling the tubular body that is divided into two parts.

Reference will now be made in greater detail to operation of the laparoscopic port site closure device, hereinbelow.

The laparoscopic port site closure device according to the present invention may be configured such that the surgical suture **40**, which is in the case **45**, is received in the compartment **32**, and the coil **42** provided at each end of the surgical suture is inserted into the mounting hole **335** of the wings **33**, wherein the surgical suture is pulled out through the notch **337** of the compartment **32**.

Here, the silicon tube **46** of the surgical suture may be made of a soft material so as to be deformed to help the surgical suture to be caught in the communication slot **336** for temporal fixation. Further, the silicon tube **46** covers and protects the junction between the surgical suture and the spiral coil, wherein the surgical suture is combined with the end of the coil **42**.

When the cartridge **30** that receives the surgical suture is inserted into the tubular body **10**, the inner protrusions **12** at the lower portion of the tubular body are combined with the cartridge **30** by passing the ridge **334** of the wings **33**. Here, the outer protrusions **22** of the operating stick **20** are guided to and mounted to the mounting slot **301** of the first support **300**.

When the laparoscopic port site closure device according to the present invention is used to close the port site, as a manner similar to a conventional operation, after a cone-shaped fore-end of the cartridge **30** is inserted into the patient's body by holding the cone-shaped handle **11** according to the present invention, the link hole **333** is engaged, with, the inner protrusions **12** around the wing protrusions **311** by pulling the handle **21** of the operating stick **20**, wherein the wings **33** are combined with the wing protrusions **311** of the second support **310**. Here, when the operating stick **20** is rotated at an angle of 45 degrees clockwise, the wings **33** are opened along an edge of the arch-shaped link hole **333**.

The opened wings **33** may be perpendicular to the tubular body **10**, and an angle of rotation is dependent on the link hole **333**.

The guide protrusions **23** of the operating stick **20** are engaged with the inward groove **14a** of the guide groove **14** such that, a location of the operating stick **20** is fixed, whereby the opened wings **33** remain open (see FIG. **10**).

The guide groove **14** is crank shaped and includes grooves **14a** and **14b** for guiding a rotation and forward-backward movement of the operating stick **20** and fixing a location of the operating stick.

After the wings **33** is opened and fixed, as shown in FIG. **5**, when the needle **50** is inserted through the guide holes **13**, the needle tip is pierced through a tissue around a port. The needle is then withdrawn after the coil **42** is passed through the wings **33**. Here, the stopper **43** of the coil is caught in the suture slot **52** of the needle, wherein the coil is extended along the needle that is pulled, whereby a tied portion of the surgical suture is safely pulled out of the patient's body (see FIGS. **15** and **16**).

As shown in FIG. **9**, after opposite ends of the surgical suture **40** are pulled out of the patient's body, when the

operating stick **20** is rotated at an angle of 45 degrees counterclockwise, the guide protrusions **23** engaged with the inward groove **14a** of the guide groove **14** are disengaged. When the operating stick **20** is then pushed, the opened wings **33** are closed. When the cone-shaped handle **11** is pulled out, the entire tubular body **10** of the laparoscopic port site closure device comes out of the patient's body. Here, the surgical suture is tied using the conventional suturing method, and the coil is removed (see FIG. **17**).

When the cartridge **30** is replaced after using the laparoscopic port site closure device and the surgical suture therein, as shown in FIG. **11**, the operating stick **20** is further rotated at an angle of 45 degrees counterclockwise. Here, the guide protrusions **23** of the operating stick are locked to the outward groove **14b** of the crank shaped guide groove **14**, and the outer protrusions **22** engaged with the locking channels **302** of the cartridge **30** are moved to an unlock location. Thereby, the cartridge **30** is detached from the operating stick **20** (see FIGS. **11** and **12**).

The cartridge **30** detached from the operating stick **20** is still combined with the tubular body **10** because the inner protrusions **12** provided inside the tubular body **10** at the lower portion thereof are engaged with the link hole **333** and the ridge **334** of the wings **33**. This engagement is configured such that the tubular body **10** is detached from the cartridge **30** by a user's physical force.

A new cartridge **30** is combined with the tubular body **10** in a reverse process so as to reuse the laparoscopic port site closure device.

The needle **50** is configured to catch and pull out the coil **42**. Thus, the suture slot **52** for catching the surgical suture is longitudinally formed on the needle tip so as to pull out the surgical suture.

Further, each end of the surgical suture **40** may be provided with the coil so as to easily pull out the surgical suture using the needle, wherein the coil is made of a harmless metal material and is coiled into a spiral shape so as to be easily threaded through the needle. The coil maintains an original shape thereof using elasticity thereof, and the coil is extended by being caught in the needle. Here, a coil having enough elasticity and rigidity to be extended long may be used for the coil. Each end of the coil may be melted to form the ball-shaped stopper **43**, whereby it is possible to manufacture a stopper having a simple structure through easy processing.

The stopper **43** of the coil prevents the coil from deviating from the suture slot **52** of the needle, and also prevents the surgical suture from being separated from the coil.

The surgical suture **40** is folded and received in the tubular case, and opposite ends of the surgical suture **40** are threaded through the wings **33** in order to use. The surgical suture may be provided in a state where the surgical suture is received in the cartridge.

The spiral coil **42** is capable of being threaded through the needle tip using a gap between spirals even when the tip of the needle **50** is inserted not perfectly in the middle of the coil. Further, the spiral coil **42** is capable of being threaded through the needle tip using the gap between the spirals regardless of a direction where an opening of the suture slot **52** faces when inserted. Once the coil is caught in the suture slot **52** of the inserted needle tip, the stopper **43** of the coil is caught in the suture slot **52** by being pulled by the needle, thereby extending and being pulled outside. Thus, it is possible to prevent failure in removing the surgical suture.

The present invention is capable of clearly removing the surgical suture when closing a port site, thereby helping the recovery of a patient by lowering the possibility of infection

during the recovery. Further, the present invention is capable of realising an easy procedure by having a handle manipulation structure that allows easy closure of the insertion site, thereby helping medical staff. Furthermore, the present invention is simple and economical because the cartridge receiving the surgical suture therein is replaceable.

Description of reference characters of important parts	
10: tubular body	11: cone-shaped handle
21: handle	12: inner protrusions
22: outer protrusions	23: guide protrusions
311: wing protrusions	13: needle guide holes
14: guide groove	20: operating stick
30: cartridge	32: compartment
33: wings	40: surgical suture
42: coil	43: stopper
45: case	46: silicon tube
50: needle	52: suture slot
300: first support	301: mounting slot
302: locking channels	310: second support
320: third support	322: cover
331: wing hole	333: link hole
334: ridge	335: mounting hole
336: communication slot	

The invention claimed is:

1. A laparoscopic port site closure device, which is in a tube shape for being introduced into a port site, comprising: a tubular body provided with needle guides that face each other and guide insertion of a needle; wings mounted to a lower portion of the tubular body such that the wings are opened and closed through a cam method; and an operating stick penetrating through the tubular body to operate the wings by being rotated to push and open the wings and to pull and close the wings by being rotated reversely, the laparoscopic port site closure device further comprising:

a replaceable cartridge provided on a lower end of the tubular body to be detachably combined with the operating stick, wherein the cartridge is provided with the wings capable of being opened by operating the operating stick, and provided with a compartment for receiving surgical suture therein, wherein

the laparoscopic port site closure device is configured such that opposites ends of the surgical suture in the compartment are threaded through the wings such that the ends of the surgical suture are capable of being pulled out of a patient's body after being caught by a suture slot of a needle that is pierced into the patient's body from outside.

2. The device of claim 1, wherein the tubular body is divided into two parts, and includes a cone-shaped handle and a tube that extends from the handle, wherein inner protrusions are provided inside of the tube at a lower portion thereof at positions facing each other;

needle guide holes are provided on the handle for guiding introduction and withdrawal of the needle, the needle guide holes ranging from an upper portion of the handle to a side wall of the tube at opposite positions; and a crank-shaped guide groove is provided inside the handle and guides a rotation and forward-backward movement of the operating stick and fixes a location of the operating stick.

3. The device of claim 1, wherein the operating stick includes a handle and a rod that extends from the handle, with outer protrusions provided at an end of the rod at

opposite positions, and guide protrusions provided below the handle by protruding at opposite positions, the guide protrusions serving to mount and demount the cartridge such that the cartridge is combined with the tubular body.

4. The device of claim 1, wherein the cartridge includes: a first support including a mounting slot provided in a center thereof, and locking channels provided on opposite positions of an outer circumferential surface thereof;

a second support provided beneath the first support, the second support being in a planar shape so as to support a surface of each of the wings, and including wing protrusions disposed opposite to each other as a pivot of the wings;

a third support being in a planar shape rotated at an angle of 90 degrees relative to the second support, having a width to come into close contact with the wings when the wings are closed, and including the compartment that is in a cone shape and is provided at a lowermost end thereof, and a cover for covering the compartment; and

the wings each including: a wing hole for being engaged with the wing protrusions of the second support; an arch-shaped link hole that is provided outside the wing hole, the link hole having an opening at an edge thereof with a ridge provided by protruding in the opening; a mounting hole for mounting an end of the surgical suture; and a communication slot provided on an outer surface of the wing to communicate with the mounting hole, wherein the wings comprise a pair of wings that are disposed opposite to each other.

5. The device of claim 3, wherein when the cartridge including the wings is assembled with the tubular body, the cartridge shares a same center point as the tubular body and has no protruding surfaces.

6. The device of claim 3, wherein the compartment includes a notch provided at a portion of an outer surface thereof so as to serve as a suture outlet for the surgical suture that is received therein.

7. A laparoscopic port site closure device, which is in a tube shape for being introduced into a port site, the device comprising: wings mounted to a lower portion of a tubular body such that the wings are opened and closed through a cam method; and an operating stick penetrating through the tubular body to operate the wings by being rotated to push and open the wings and to pull and close the wings by being rotated reversely, the laparoscopic port site closure device further comprising:

a needle including a suture slot for catching and pulling out surgical suture by being concavely formed on a needle tip in an opposite direction of pulling the surgical suture; and

a replaceable cartridge provided on a lower end of the tubular body to be detachably combined with the operating stick, wherein the cartridge is provided with a compartment for receiving surgical suture therein, and

wherein the tubular body is provided with needle guides that face each other, wherein each needle guide being configured to guide insertion of the needle.

* * * * *

专利名称(译)	腹腔镜端口部位闭合装置		
公开(公告)号	US10307146	公开(公告)日	2019-06-04
申请号	US15/104189	申请日	2015-08-31
[标]申请(专利权)人(译)	金基成		
申请(专利权)人(译)	KIM , KI SEONG		
当前申请(专利权)人(译)	KIM , KI SEONG		
[标]发明人	KIM KI SEONG		
发明人	KIM, KI SEONG		
IPC分类号	A61B17/00 A61B17/34 A61B17/04 A61B17/06		
CPC分类号	A61B17/0057 A61B17/0482 A61B17/06004 A61B17/06109 A61B17/06114 A61B17/34 A61B2017/06042 A61B17/06119 A61B2017/0023 A61B2017/00473 A61B2017/00637 A61B2017/00663 A61B17/0483 A61B17/0485 A61B17/3403 A61B2017/3405 A61B17/04 A61B2017/0461		
优先权	1020140163452 2014-11-21 KR		
其他公开文献	US20170245846A1		
外部链接	Espacenet		

摘要(译)

公开了一种腹腔镜端口部位闭合装置。该装置被配置成使得在其中接收外科缝合线的药筒设置在针引导件的前端处，用于端口部位闭合；手术缝合线被针尖捕获，该针尖通过针引导器刺穿身体组织；当针被抽出时，手术缝合线沿着穿过针刺入组织的路径被拉出，并且手术缝合线被绑在患者体外，从而能够关闭腹腔镜端口部位。

