



US007967748B2

(12) **United States Patent**
Kistler et al.

(10) **Patent No.:** **US 7,967,748 B2**
(45) **Date of Patent:** **Jun. 28, 2011**

(54) **RESILIENTLY SUPPORTED SEAL CAP FOR HAND ASSISTED LAPAROSCOPIC SURGICAL PROCEDURES**

5,171,249 A 12/1992 Stefanchik et al.
5,197,955 A 3/1993 Stephens et al.
5,292,330 A 3/1994 Shutt
5,324,268 A 6/1994 Yoon
5,337,754 A 8/1994 Heaven et al.
5,366,478 A 11/1994 Brinkerhoff et al.
5,385,552 A 1/1995 Haber et al.
5,437,683 A 8/1995 Neumann et al.

(75) Inventors: **Paul H. Kistler**, Cincinnati, OH (US);
Andrew T. Beckman, Cincinnati, OH (US)

(Continued)

(73) Assignee: **Ethicon Endo-Surgery, Inc.**, Cincinnati, OH (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 414 days.

EP 0776180 6/1997

(Continued)

(21) Appl. No.: **11/611,167**

OTHER PUBLICATIONS

(22) Filed: **Dec. 15, 2006**

International Search Report dated May 28, 2008 for PCT/US2007/087372.

(Continued)

(65) **Prior Publication Data**

US 2008/0146883 A1 Jun. 19, 2008

Primary Examiner — Thomas C Barrett

Assistant Examiner — Michael T Schaper

(51) **Int. Cl.**
A61B 17/00 (2006.01)

(74) *Attorney, Agent, or Firm* — Frost Brown Todd LLC

(52) **U.S. Cl.** **600/204**; 606/201; 606/206; 606/207;
606/208; 606/213

(57) **ABSTRACT**

(58) **Field of Classification Search** 600/204,
600/206, 207, 208, 213
See application file for complete search history.


A laparoscopic disk assembly for a Hand Assisted Laparoscopic Surgery (HALS) procedure includes an exteriorly visible laparoscopic disk (seal cap) attached to a retractor skirt. The laparoscopic disk provides an adjustable exterior opening. A downward annular surface is supported by an attached flexible or resilient ("soft") support member that in turn forms an annular contact upon a patient's abdomen wall surrounding an incision to form a sealing connection, to facilitate improved manipulation or degrees of freedom through the laparoscopic disk without loss of insufflation pressure, to minimize, if not eliminate, bruising, to prevent rotation movement of a retractor skirt in the incision, and to reduce fatigue. Versions include a resilient pad, a resilient skirt that adheres to the patient's skin, a skirt with horizontal pleats, and a toroidal bladder that comfortably depresses into the skin.

(56) **References Cited**

U.S. PATENT DOCUMENTS

563,645 A 7/1896 Bitting
564,645 A 7/1896 Queen
2,739,587 A 3/1956 Scholl
3,111,943 A 11/1963 Orndorff
3,332,417 A 7/1967 Blanford et al.
3,347,226 A 10/1967 Harrower
3,347,227 A 10/1967 Harrower
3,397,692 A 8/1968 Creager, Jr. et al.
5,100,420 A 3/1992 Green et al.
5,104,383 A 4/1992 Shichman

14 Claims, 9 Drawing Sheets



U.S. PATENT DOCUMENTS

5,460,170	A	10/1995	Hammerslag	
5,480,410	A	1/1996	Cuschieri et al.	
5,514,133	A	5/1996	Golub et al.	
5,522,791	A	6/1996	Leyva	
5,524,644	A	6/1996	Crook	
5,526,536	A	6/1996	Cartmill	
5,545,179	A	8/1996	Williamson, IV	
5,640,977	A	6/1997	Leahy et al.	
5,649,550	A	7/1997	Crook	
5,653,705	A	8/1997	de la Torre et al.	
5,653,717	A	8/1997	Ko et al.	
5,672,168	A	9/1997	de la Torre et al.	
5,741,298	A	4/1998	MacLeod	
5,803,921	A	9/1998	Bonadio	
5,810,721	A	9/1998	Mueller et al.	
5,813,409	A	9/1998	Leahy et al.	
5,817,062	A	10/1998	Flom et al.	
5,853,395	A	12/1998	Crook et al.	
5,899,208	A	5/1999	Bonadio	
5,906,577	A	5/1999	Beane et al.	
5,925,064	A	7/1999	Meyers et al.	
5,947,922	A	9/1999	MacLeod	
5,957,913	A	9/1999	de la Torre et al.	
6,024,736	A	2/2000	de la Torre et al.	
6,033,426	A	3/2000	Kaji	
6,033,428	A	3/2000	Sardella	
6,048,309	A	4/2000	Flom et al.	
6,077,288	A	6/2000	Shimomura et al.	
6,110,154	A	8/2000	Shimomura et al.	
6,142,935	A	11/2000	Flom et al.	
6,142,936	A	11/2000	Beane et al.	
6,142,946	A	11/2000	Hwang et al.	
6,149,642	A	11/2000	Gerhart et al.	
6,159,200	A	12/2000	Verdura et al.	
6,165,184	A	12/2000	Verdura et al.	
6,228,022	B1	5/2001	Friesem et al.	
6,254,534	B1	7/2001	Butler et al.	
6,315,770	B1	11/2001	de la Torre et al.	
6,319,246	B1	11/2001	de la Torre et al.	
6,382,211	B1	5/2002	Crook	
6,440,063	B1	8/2002	Beane et al.	
6,450,983	B1	9/2002	Rambo	
6,485,467	B1	11/2002	Crook et al.	
6,536,277	B1	3/2003	Chuang	
6,540,983	B1	4/2003	Adjei et al.	
6,578,577	B2	6/2003	Bonadio et al.	
6,582,364	B2	6/2003	Butler et al.	
6,589,167	B1	7/2003	Shimomura et al.	
6,613,952	B2	9/2003	Rambo	
6,623,426	B2	9/2003	Bonadio et al.	
6,676,706	B1	1/2004	Mears et al.	
6,723,044	B2	4/2004	Pulford et al.	
6,808,520	B1	10/2004	Fourkas et al.	
6,814,078	B2	11/2004	Crook	
6,814,700	B1	11/2004	Mueller et al.	
6,846,287	B2	1/2005	Bonadio et al.	
2001/0037053	A1	11/2001	Bonadio et al.	
2001/0047188	A1	11/2001	Bonadio et al.	
2002/0002324	A1	1/2002	McManus	
2002/0010389	A1	1/2002	Butler et al.	
2002/0038077	A1	3/2002	de la Torre et al.	
2002/0068923	A1	6/2002	Caldwell et al.	
2002/0072762	A1	6/2002	Bonadio et al.	
2002/0162559	A1	11/2002	Crook	
2002/0183594	A1*	12/2002	Beane et al.	600/207
2003/0062051	A1	4/2003	Rambo	
2003/0078478	A1	4/2003	Bonadio et al.	
2003/0192553	A1	10/2003	Rambo	
2004/0015185	A1	1/2004	Ewers et al.	
2004/0049099	A1	3/2004	Ewers et al.	
2004/0049100	A1	3/2004	Butler et al.	
2004/0073090	A1	4/2004	Butler et al.	

2004/0092795	A1	5/2004	Bonadio et al.	
2004/0092796	A1	5/2004	Butler et al.	
2004/0093001	A1*	5/2004	Hamada	606/190
2004/0097793	A1	5/2004	Butler et al.	
2004/0127772	A1	7/2004	Ewers et al.	
2004/0154624	A1	8/2004	Bonadio et al.	
2004/0249248	A1	12/2004	Bonadio et al.	
2004/0254426	A1	12/2004	Wenchell	
2004/0260153	A1	12/2004	Pulford et al.	
2004/0267096	A1*	12/2004	Caldwell et al.	600/213
2005/0020884	A1*	1/2005	Hart et al.	600/206
2005/0137460	A1*	6/2005	Bertolero et al.	600/213
2005/0148823	A1*	7/2005	Vaugh et al.	600/206
2005/0192483	A1*	9/2005	Bonadio et al.	600/208
2005/0222582	A1	10/2005	Wenchell	
2005/0241647	A1	11/2005	Nguyen et al.	
2005/0283050	A1	12/2005	Gundlapalli et al.	
2006/0084842	A1	4/2006	Hart et al.	
2006/0135977	A1	6/2006	Thompson et al.	
2006/0247500	A1	11/2006	Voegele et al.	
2008/0009834	A1	1/2008	Mialhe	
2008/0092034	A1	4/2008	Lim et al.	

FOREIGN PATENT DOCUMENTS

EP	0845960	6/1998
EP	0887047	12/1998
EP	0887048	12/1998
EP	0888755	1/1999
EP	1000583	5/2000
EP	1135070	9/2001
EP	1312318	5/2003
EP	1 415 610	5/2004
EP	1442710	8/2004
WO	WO 93/11811	6/1993
WO	WO 95/22289	8/1995
WO	WO 95/24864	9/1995
WO	WO 95/27468	10/1995
WO	WO 96/10963	4/1996
WO	WO 97/07742	3/1997
WO	WO 98/48724	11/1998
WO	WO 99/03416	1/1999
WO	WO 99/25268	5/1999
WO	WO 00/24326	5/2000
WO	WO 00/54677	9/2000
WO	WO 01/08581	2/2001
WO	WO 01/26558	4/2001
WO	WO 01/45568	6/2001
WO	WO 02/34108	5/2002
WO	WO 03/028523	4/2003
WO	WO 03/061480	7/2003
WO	WO 03/077726	9/2003
WO	WO 2004/026153	4/2004
WO	WO 2004/030547	4/2004
WO	WO 2004/054456	7/2004
WO	WO 2004/075730	9/2004
WO	WO 2004/075741	9/2004
WO	WO 2004/096012	11/2004
WO	WO 2004/103161	12/2004
WO	WO 2005/009257	2/2005
WO	WO 2006/061356	6/2006

OTHER PUBLICATIONS

U.S. Appl. No. 11/548,325, filed Oct. 11, 2006, Lim et al.
 Abstract for EP 0845960.
 Abstract for EP 0776180.
 Abstract for EP 1135070.
 International Search Report dated May 28, 2008 for Application No. PCT/US2007/087372.
 International Search Report dated May 19, 2008 for Application No. PCT/US2007/087385.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

RESILIENTLY SUPPORTED SEAL CAP FOR HAND ASSISTED LAPAROSCOPIC SURGICAL PROCEDURES

CROSS REFERENCE TO RELATED APPLICATION

The present application is related to two commonly-owned U.S. Patent Applications filed on even date herewith, the disclosures of which are hereby incorporated by reference in their entirety: (1) U.S. patent application Ser. No. 11/611,215, entitled "Handoscopy Interwoven Layered Seal Laparoscopic Disk"; and (2) U.S. patent application Ser. No. 11/611,193, entitled "Fully Automated Iris Seal for Hand Assisted Laparoscopic Surgical Procedures".

FIELD OF THE INVENTION

The invention generally relates to surgical access systems that facilitate sealed access across a body wall and into a body cavity during a laparoscopic surgical procedure.

BACKGROUND OF THE INVENTION

Abdominal surgery typically involves an incision in the abdominal wall large enough to accommodate a surgeon's hands, multiple instruments, and illumination of the body cavity. While large incisions simplify access to the body cavity during a surgery, it also increases trauma, requires extended recovery time, and can result in unsightly scars. In response to these drawbacks, minimally invasive surgical methods have been developed.

In minimally invasive abdominal surgery, or laparoscopic surgery, several smaller incisions are made into the abdominal wall. One of the openings is used to inflate the abdominal cavity with gas, which lifts the abdominal wall away from underlying organs and provides space to perform the desired surgery. This process is referred to as insufflation of the body cavity. Additional openings may be used to accommodate cannulas or trocars for illuminating and viewing the cavity, as well as instruments involved in actually performing the surgery, e.g., instruments to manipulate, cut, or resect organs and tissue.

Hand Assisted Laparoscopic Surgical (HALS) procedures are gaining increased acceptance as combining advantages of open surgery (e.g., tactile feedback) yet having some of the advantages of reduced scarring, reduced recovery time, and reduced incidence of complications of closed procedures. Laparoscopic disks are often used to provide an adjustable opening that allows insertion of the surgeon's hand to the insufflated body cavity, yet provides significant pneumatic sealing with or without the presence of the surgeon's hand.

While generally-known laparoscopic disks successfully support FIALS procedures, improvements to increase patient and surgeon comfort and to enhance performance are desired.

BRIEF DESCRIPTION OF THE FIGURES

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the invention, and, together with the general description of the invention given above, and the detailed description of the embodiments given below, serve to explain the principles of the present invention.

FIG. 1 is an environmental perspective view of a patient prepared for a Hand Assisted Laparoscopic Surgery (HALS) procedure by the insertion of a laparoscopic disk.

FIG. 2 is a perspective view of a FIALS laparoscopic disk assembly that includes the laparoscopic disk of FIG. 1 and incorporates a flexible or resilient ("soft") support member downwardly and annularly positioned to contact and seal to a patient's abdominal wall around an incision formed for the laparoscopic disk and attached retractor skirt.

FIG. 3 is an exploded perspective view of the HALS laparoscopic disk assembly of FIG. 2.

FIG. 4 is a side view taken in cross section through a left side of the HALS laparoscopic disk assembly of FIG. 2 retracting an incision through an abdominal wall and supported by the soft support member of FIG. 2 comprising a cylindrical corner pad.

FIG. 5 is a side view taken in cross section through a left side of the HALS laparoscopic disk assembly of FIG. 2 retracting an incision through an abdominal wall and supported by an alternative soft support member comprising a horizontally pleated resilient skirt with an annular adhesive surface.

FIG. 6 is a side view taken in cross section through a left side of the HALS laparoscopic disk assembly of FIG. 2 retracting an incision through an abdominal wall and supported by another alternative soft support member comprising an outwardly and downwardly sloped resilient skirt with an annular adhesive surface.

FIG. 7 is a side view taken in cross section through a left side of the HALS laparoscopic disk assembly of FIG. 2 retracting an incision through an abdominal wall and supported by an additional alternative soft support member comprising an annular resilient barrier attached to the downward annular surface formed by the retractor skirt and filled to form an annular bladder that comfortably depresses onto the abdominal wall.

FIG. 8 is a side view taken in cross section through a left side of the HALS laparoscopic disk assembly of FIG. 2 retracting an incision through an abdominal wall and supported by a further alternative soft support member comprising a toroidal (inner tube) bladder attached to the downward annular surface formed by the retractor skirt that comfortably depresses onto the abdominal wall.

FIG. 9 is a side view taken in cross section through a left side of the HALS laparoscopic disk assembly of FIG. 2 retracting an incision through an abdominal wall and supported by a further alternative soft support member comprising a resilient toroidal pad attached to the downward annular surface formed by the retractor skirt that comfortably depresses onto the abdominal wall.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to FIGS. 1-4, the environment for performing an endoscopic surgical procedure within an abdomen is illustrated, herein referred to as Hand Assisted Laparoscopic Surgery (HALS). A surgeon places a hand through a HALS laparoscopic disk assembly 10 that includes an exteriorly visible laparoscopic disk (seal cap) 12 attached to a retractor skirt 14. The laparoscopic disk 12 provides an adjustable exterior opening 16 large enough to admit a surgeon's hand, yet provides sufficient pneumatic seal with or without the presence of the surgeon's hand to maintain an insufflated body cavity for the HALS procedure. An upper opening 17 of the retractor skirt 14 is attached to a lower circumference of the laparoscopic disk 12 with either or both presenting a downward annular surface 18 that is supported by an attached flexible or resilient ("soft") support member 20 consistent with aspects of the present invention. The soft support member 20

forms an annular contact upon an exterior surface **22** of the patient's abdomen wall **24** surrounding an incision **26**.

The soft support member **20** may serve one or more, as well as others, of the following functions: (a) forms a sealing connection with the exterior surface **22** of the abdominal wall **24**; (b) facilitates improved manipulation or degrees of freedom of the surgeon's hand or laparoscopic instrument (not shown) through the laparoscopic disk **12** without loss of insufflation pressure during a HALS procedure; (c) minimizes, if not eliminates altogether, bruising to the patient that would otherwise be the result of the laparoscopic disk **12**; (d) prevents rotation movement of the retractor skirt **14** in the incision **26**; and (e) reduces fatigue for the surgeon by more comfortably guiding the surgeon's hand.

The incision **26** is retracted (i.e., made wider) by a resilient waist **28** of the retractor skirt **14**. A lower opening **30** of the retractor skirt **14** is defined by a flexible ring **32** that forms a lip of the retractor skirt **14** and is wider than the resilient waist **28** thereof to contact an inner surface **34** (FIG. 4) of the abdominal wall **24** around the incision **26**. The flexible ring **32** allows insertion in a deformed state through the incision **26** with subsequent rebounding to the depicted relaxed, circular shape.

In FIGS. 2-4, the adjustable opening **16** of the illustrative version of the laparoscopic disk **12** is formed by a resilient, cylindrical diaphragm **36** depicted in an open, wheel rim shape formed when stretched for attachment to a rigid upper twist ring **38** and to a rigid lower locking ring **40**. In particular, an upper portion **42** of the cylindrical diaphragm **36** extends upwardly through an aperture **44** of the twist ring **38** and outwardly over an upper cylindrical rim **46** of the twist ring **38** and held by an interference fit within a ring groove **48**. A lower portion **50** of the cylindrical diaphragm **36** extends downward through an aperture **52** of the locking ring **40** and is stretched outwardly to be received over a lower cylindrical rim **54** of the locking ring **40**, held by a lower O-ring **56**. An upper edge **59** of the retractor skirt **14** is interposed between the lower O-ring **56** and the lower portion **50** of the cylindrical diaphragm **36**.

An outer, downward cylindrical lip **58** of the twist ring **40** slides downwardly around an inner, upward cylindrical lip **60** of the locking ring **40**. A downward annular surface inward to the outer, downward cylindrical lip **58** of the twist ring **38** presents a downward saw tooth engaging surface **64** that engages a corresponding upward saw tooth engaging surface **66** on the inner, upward cylindrical lip **60** of the locking ring **40**, resisting relative rotation between the rings **38**, **40**. The cylindrical diaphragm **36** is sized to draw engaging surfaces **64**, **66** of the ring **38**, **40** into engagement until manually separated and twisted to close the adjustable opening or thereafter twists in a return direction to open again. Alternate adjustable openings **16** are described in the two cross referenced U.S. patent application Ser. No. 11/611,193, entitled "Fully Automated Iris Seal for Hand Assisted Laparoscopic Surgical Procedures" and Ser. No. 11/611,215, entitled "Handoscopy Interwoven Layered Seal Laparoscopic Disk". The illustrative version includes the downward annular surface **18** that is provided by the retractor skirt **14** whereas these two cross referenced laparoscopic disks provide a lower surface that serves as the downward annular surface **18**.

In FIG. 4, the soft support member **20** comprises a thick annular ring **68** having a top surface **70** contacting the upper edge **59** of the retractor skirt **14** and a downward surface **72** resting upon the exterior surface **22** of the patient's abdominal wall **24**. The soft support member **20** also includes an upward cylindrical portion **74** that is attached and integral to the thick annular ring **68** and that conforms to an outer portion of the

locking ring **40** and lower O-ring **56** to hold the soft support member **20** onto the locking ring **40**, forming a cylindrical corner pad.

In FIG. 5, an alternative soft support member **20a** comprises a horizontally pleated resilient skirt **76** that slopes generally downwardly and outwardly from an upper aperture **78** sized for engagement within an outward cylindrical groove **80** that serves as the downward annular surface of the locking ring **40** and is formed between a top outward cylindrical ridge **82** and an intermediate outward cylindrical ridge **84** that resides above, and constrains upward migration of, the lower O-ring **56**. The soft support member **20a** has a lower contact surface **86** onto which an annular adhesive surface **88** is attached for adhering to the exterior surface **22** of the patient's abdominal wall **24** around the incision **26**. A cylindrical gasket portion **89** of rectangular cross section is formed integral to the lower contact surface **86** for stiffening to present a flat contact surface **86** when adhering to the abdominal wall **24**. Thus, the horizontally pleated resilient skirt **76** that encompasses the locking ring **40** creates a pneumatic seal that captures a volume of air that cushions the laparoscopic disk **12** from the abdominal wall **24**. A bottom annular lip **90** of the resilient skirt **76** extends outwardly and slightly upwardly from the lower contact surface **86** to present a gripping surface for removal of the annular adhesive surface **88** from the abdominal wall **24**.

In FIG. 6, another alternative soft support member **20b** comprises a resilient skirt **96** that slopes downwardly and outwardly from an upper aperture **78** sized for engagement within the outward cylindrical groove **80** of the locking ring **40**. The soft support member **20b** has a lower contact surface **106** onto which an annular adhesive surface **108** is attached for adhering to the exterior surface **22** of the patient's abdominal wall **24** around the incision **26**. A cylindrical gasket portion **109** of the rectangular cross section is formed integral to the lower contact surface **106** for stiffening to present a flat contact surface **106** when adhering to the abdominal wall **24**. Thus the horizontally pleated resilient skirt **96** that encompasses the locking ring **40** creates a pneumatic seal that captures a volume of air that cushions the laparoscopic disk **12** from the abdominal wall **24**. A bottom annular lip **110** of the resilient skirt **96** extends outwardly and slightly upwardly from the lower contact surface **106** to present a gripping surface for removal of the annular adhesive surface **108** from the abdominal wall **24**.

In FIG. 7, an additional alternative soft support member **20c** comprises a resilient annular barrier **120** attached along an outer circumference **122** to the curled, upper edge **59** of the retractor skirt **14** and along an inner circumference **124** also attached to the retractor skirt **14** that forms the downward annular surface **18** and creates an annular, downwardly extending bladder **126** that contains a gaseous, liquid, gel or resilient material **128** that comfortably presses against the exterior surface **22** of the abdominal wall **24** to form a seal and to provide support to the laparoscopic disk **12**.

In FIG. 8, a further alternative soft support member **20d** comprises a resilient toroidal bladder ("inner tube") **130** attached along an upper surface **132** to the upper portion of the retractor skirt **14** that forms the downward annular surface **18**. The toroidal bladder **130** contains a gaseous, liquid, gel or resilient material **134** that comfortably presses against the exterior surface **22** of the abdominal wall **24** to form a seal and to provide support to the laparoscopic disk **12**.

In FIG. 9, yet a further alternative soft support member **20e** comprises a resilient toroidal pad **140** attached along an upper surface **142** to the upper portion of the retractor skirt **14** that forms the downward annular surface **18** that comfortably

5

presses against the exterior surface **22** of the abdominal wall **24** to form a seal and to provide support to the laparoscopic disk **12**.

It should be appreciated that any patent, publication, or other disclosure material, in whole or in part, that is said to be incorporated by reference herein is incorporated herein only to the extent that the incorporated material does not conflict with existing definitions, statements, or other disclosure material set forth in this disclosure. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

While the present invention has been illustrated by description of several embodiments and while the illustrative embodiments have been described in considerable detail, it is not the intention of the applicant to restrict or in any way limit the scope of the appended claims to such detail. Additional advantages and modifications may readily appear to those skilled in the art.

What is claimed is:

1. A device, comprising:

a laparoscopic disk comprising an adjustable opening sized to admit and substantially pneumatically seal to a surgeon's hand, wherein the laparoscopic disk comprises a rigid upper ring, a rigid lower ring, and a cylindrical diaphragm, wherein the cylindrical diaphragm has an engagement portion presenting an upper surface and a lower surface, wherein the cylindrical diaphragm defines the adjustable opening, wherein the upper ring is rotatable relative to the lower ring to adjust the size of the adjustable opening;

a retractor skirt comprising an upper opening attached to the lower ring of the laparoscopic disk, and a waist portion aligned with the adjustable opening for passing through and retracting an incision in an abdominal wall, wherein the retractor skirt presents a downwardly facing annular contact surface, wherein part of the cylindrical diaphragm is sandwiched between the retractor skirt and the lower ring; and

an annular support member having an upper surface that is attached to the downwardly facing annular contact surface of the retractor skirt, wherein a patient contacting lower portion of the annular support member is located below the downwardly facing annular contact surface of the retractor skirt such that the downwardly facing annular contact surface of the retractor skirt is located above the patient contacting lower portion of the annular support member, wherein part of the retractor skirt is apposed between the upper surface of the annular support member and the lower surface of the engagement portion of the cylindrical diaphragm, and such that a portion of the retractor skirt is positioned between the upper surface of the annular support member and a lower surface of the lower ring, wherein a lower surface of the patient contacting lower portion of the annular support member is positioned to contact an exterior surface of the abdominal wall surrounding the incision.

2. The device of claim 1, wherein the annular support member comprises an annular resilient pad.

6

3. The device of claim 2, wherein the annular support member further comprises a cylindrical portion gripping a lower, outer portion of the laparoscopic disk and attached to the annular resilient pad.

4. The device of claim 1, further comprising an annular adhesive surface affixed to a lower surface of the annular support member.

5. The device of claim 4, wherein the lower surface further comprises a circular gasket portion.

6. The device of claim 1, wherein the annular support member comprises a bladder.

7. The device of claim 6, wherein the bladder comprises a toroidal tube.

8. The device of claim 6, wherein the bladder comprises an annular barrier attached along outer and inner circumferences to the downward annular contact surface,

9. The device of claim 6, wherein the bladder further comprises a liquid content.

10. The device of claim 6, wherein the bladder further comprises a gel content.

11. The device of claim 6, wherein the bladder further comprises a gaseous content.

12. A hand seal device, comprising:

a laparoscopic disk assembly, the laparoscopic disk assembly comprising:

an upper ring,

a lower ring, wherein the lower ring has a lower horizontal surface and an outer vertical surface, wherein the lower horizontal surface of the lower ring and the outer vertical surface of the lower ring are joined at an outer lower corner of the lower ring, and

a seal defining an opening, wherein the seal is secured to the upper ring, wherein the seal is configured to substantially pneumatically seal to a surgeon's hand;

a retractor skirt comprising an upper portion, a lower portion, and a waist portion, wherein the upper portion is secured to the lower ring, wherein the lower portion is positionable within a patient's abdomen, wherein the waist portion extends between the upper portion and the lower portion, wherein the waist portion defines an opening aligned with the opening defined by the seal; and

an annular support pad, wherein the annular support pad comprises a soft material, wherein the annular support pad comprises a first portion and a second portion, wherein the first portion is substantially horizontally oriented and extends radially inward below the lower horizontal surface of the lower ring, wherein the second portion is substantially vertically oriented and extends axially upward along the outer vertical surface of the lower ring, wherein the second portion of the annular support pad is positioned adjacent to the upper portion of the retractor skirt, below the lower ring, wherein the first portion of the annular support pad and the second portion of the annular support pad are joined at an inner lower corner of the annular support pad, such that the outer lower corner of the lower ring is nested in the inner lower corner of the annular support pad, with a portion of the retractor skirt and a portion of the seal being oppositely positioned between the outer lower corner of the lower ring and the inner lower corner of the annular support, wherein the annular support pad is configured to engage the exterior of the patient's abdomen.

13. The hand seal device of claim 12, wherein the second portion of the annular support pad is secured to the outer vertical surface of the lower ring.

14. A hand seal device, comprising:
 a laparoscopic disk assembly, the laparoscopic disk assembly comprising:
 an upper ring, wherein the upper ring defines a central axis, 5
 a lower ring, wherein the lower ring has a lower surface, wherein the lower ring defines a central axis aligned with the central axis of the upper ring, and
 a seal defining an opening, wherein the seal is secured to the upper ring, wherein the seal is configured to substantially pneumatically seal to a surgeon's hand; 10
 a retractor skirt comprising an upper portion, a lower portion, and a waist portion, wherein the upper portion is secured to the lower ring, wherein the lower portion is positionable within a patient's abdomen, wherein the waist portion extends between the upper portion and the lower portion, wherein the waist portion defines an opening aligned with the opening defined by the seal; 15
 and
 an annular support member, wherein the annular support member comprises a skirt extending radially outwardly relative to the central axes defined by the upper and lower rings, wherein the skirt comprises a first portion and a cylindrical gasket portion configured to be adhered to the exterior of the patient's abdomen such that the

adhered skirt of the annular support member and the retractor skirt together provide a pneumatically sealed volume of space adjacent to the patient's abdomen to provide an air cushion for the laparoscopic disk assembly, the air cushion being located between the lower surface of the lower ring and the patient's abdomen, wherein the skirt assembly terminates in a radially outwardly extending lip, wherein the radially outwardly extending lip extends radially outwardly relative to the central axes defined by the upper and lower rings, wherein the first portion of the skirt extends outwardly from the lower ring, wherein the gasket portion extends outwardly from the first portion of the skirt, wherein the radially outwardly extending lip extends outwardly from the gasket portion, wherein the radially outwardly extending lip also extends upwardly to present a gripping surface configured to be grasped by an operator when the gasket portion is adhered to the exterior of the patient's abdomen, wherein the radially outwardly extending lip is further operable to be gripped and pulled away from the exterior of the patient's abdomen to disengage the gasket portion from the exterior of the patient's abdomen to break the pneumatic seal provided in part by the adhered skirt.

* * * * *

专利名称(译)	弹性支撑密封盖，用于手助腹腔镜手术		
公开(公告)号	US7967748	公开(公告)日	2011-06-28
申请号	US11/611167	申请日	2006-12-15
[标]申请(专利权)人(译)	KISTLER PAUL ^ h BECKMAN ANDREW†		
申请(专利权)人(译)	KISTLER PAUL ^ h BECKMAN ANDREW†		
当前申请(专利权)人(译)	爱惜康内镜手术，INC.		
[标]发明人	KISTLER PAUL H BECKMAN ANDREW T		
发明人	KISTLER, PAUL H. BECKMAN, ANDREW T.		
IPC分类号	A61B17/00		
CPC分类号	A61B17/3423 A61B17/0293 A61B2017/3419 A61B2017/00265		
其他公开文献	US20080146883A1		
外部链接	Espacenet USPTO		

摘要(译)

用于手辅助腹腔镜手术 (HALS) 手术的腹腔镜盘组件包括附接到牵开器裙部的外部可见腹腔镜盘 (密封帽)。腹腔镜盘提供可调节的外部开口。向下的环形表面由附接的柔性或弹性 (“柔软的”) 支撑构件支撑，该支撑构件又在患者的围绕切口的腹壁上形成环形接触以形成密封连接，以便于通过腹腔镜改善操作或自由度。在不损失吹气压力的情况下，尽量减少 (如果不能消除) 瘀伤，防止牵开器裙部在切口处旋转运动，并减少疲劳。版本包括弹性垫，粘附在患者皮肤上的弹性裙边，带有水平褶皱的裙边，以及舒适地压入皮肤的环形膀胱。

