



US010617439B2

(12) **United States Patent**
Deodhar et al.

(10) **Patent No.:** **US 10,617,439 B2**
(45) **Date of Patent:** ***Apr. 14, 2020**

(54) **COMBINATIONAL SCISSOR-GRASPER
TOOL FOR USE IN LAPAROSCOPY**

(71) Applicant: **Intuitive Surgical Operations, Inc.,**
Sunnyvale, CA (US)

(72) Inventors: **Chinmay Deodhar**, Kothrud (IN);
Asokan Thondiyath, Itt Madras (IN)

(73) Assignee: **Intuitive Surgical Operations, Inc.,**
Sunnyvale, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 282 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **14/499,418**

(22) Filed: **Sep. 29, 2014**

(65) **Prior Publication Data**

US 2016/0089176 A1 Mar. 31, 2016
US 2017/0303951 A9 Oct. 26, 2017

Related U.S. Application Data

(63) Continuation of application No. 13/503,773, filed as
application No. PCT/IB2011/052723 on Jun. 22,
2011, now Pat. No. 8,870,902.

(30) **Foreign Application Priority Data**

Jun. 23, 2010 (IN) 1852/MUM/2010

(51) **Int. Cl.**
A61B 17/295 (2006.01)
A61B 17/3201 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 17/295** (2013.01); **A61B 17/3201**
(2013.01); **A61B 2017/00353** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61B 17/22031; A61B 2017/22034; A61B
2017/22035; A61B 17/28; A61B 17/29;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,336,228 A 8/1994 Cholhan
5,509,923 A 4/1996 Middleman et al.
(Continued)

FOREIGN PATENT DOCUMENTS

EP 2368504 A1 9/2011

OTHER PUBLICATIONS

International Search Report and Written Opinion for Application
No. PCT/IB2011/52723, dated Nov. 23, 2011, 9 pages.

(Continued)


Primary Examiner — Kathleen S Holwerda

Assistant Examiner — Brooke Labranche


(57) **ABSTRACT**


Disclosed is a four-jawed combinational scissor-grasper
surgical tool for use in laparoscopy. Cutting and grasping
functionalities are respectively enabled via movement of a
pair of such specially contoured jaw members sliding
against or splaying apart from the other pair. Also disclosed
are means for achieving selectable interlocking of jaw
members and mechanical linkage for their actuation by
human user.

19 Claims, 11 Drawing Sheets



- (51) **Int. Cl.**
A61B 17/00 (2006.01)
A61B 17/29 (2006.01)
- (52) **U.S. Cl.**
 CPC *A61B 2017/2926* (2013.01); *A61B 2017/2938* (2013.01)
- (58) **Field of Classification Search**
 CPC *A61B 17/2909*; *A61B 17/282*; *A61B 2017/2926*; *A61B 17/30*; *A61B 17/320092*; *A61B 17/2804*; *A61B 2017/2808*; *A61B 17/2812*; *A61B 17/2816*; *A61B 2017/2825*; *A61B 2017/2829*; *A61B 17/2833*; *A61B 2017/2837*; *A61B 17/2841*; *A61B 2017/2845*; *A61B 17/285*; *A61B 2017/2901*; *A61B 2017/2902*; *A61B 2017/2903*; *A61B 2017/2904*; *A61B 2017/2905*; *A61B 2017/2906*; *A61B 2017/2908*; *A61B 2017/291*; *A61B 2017/2912*; *A61B 2017/2913*; *A61B 2017/2915*; *A61B 2017/2916*; *A61B 2017/2917*; *A61B 2017/2918*; *A61B 2017/2919*; *A61B 2017/2925*; *A61B 2017/2927*; *A61B 2017/2929*; *A61B 2017/293*; *A61B 2017/2931*; *A61B 2017/2932*; *A61B 2017/2933*; *A61B 2017/2934*; *A61B 2017/2936*; *A61B 2017/2937*; *A61B 2017/2938*; *A61B 2017/2939*; *A61B 2017/294*; *A61B 2017/2945*; *A61B 2017/2946*; *A61B 2017/2947*; *A61B 2017/2948*; *A61B 17/295*; *A61B 2018/0225*; *A61B 18/085*; *A61B 18/1442*; *A61B 18/1445*; *A61B 17/3201*; *A61B 2017/00353*
- USPC 606/205, 207, 208
 See application file for complete search history.
- (56) **References Cited**
 U.S. PATENT DOCUMENTS
- | | | | |
|-------------------|---------|-------------------|--------------------------------|
| 5,542,949 A | 8/1996 | Yoon | |
| 5,637,111 A * | 6/1997 | Sutcu | <i>A61B 18/1445</i>
606/174 |
| 5,919,206 A | 7/1999 | Gengler et al. | |
| 6,024,744 A | 2/2000 | Kese et al. | |
| 6,030,384 A | 2/2000 | Nezhat | |
| 6,520,960 B2 * | 2/2003 | Blocher | <i>A61B 18/12</i>
606/48 |
| 8,870,902 B2 | 10/2014 | Deodhar et al. | |
| 2003/0055424 A1 | 3/2003 | Ciarrocca | |
| 2005/0072827 A1 | 4/2005 | Mollenauer | |
| 2007/0179525 A1 | 8/2007 | Freckner et al. | |
| 2010/0057085 A1 * | 3/2010 | Holcomb | <i>A61B 18/1445</i>
606/51 |
| 2010/0122419 A1 * | 5/2010 | Zupancic-Albin | <i>A61J 7/0007</i>
7/125 |
| 2011/0238066 A1 * | 9/2011 | Olson | <i>A61B 17/295</i>
606/51 |
| 2012/0029305 A1 * | 2/2012 | La Guardia et al. | <i>A61B 17/2812</i>
606/119 |
- OTHER PUBLICATIONS
- Vertut, Jean and Phillipe Coiffet, Robot Technology: Teleoperation and Robotics Evolution and Development, English translation, Prentice-Hall, Inc., Inglewood Cliffs, NJ, USA 1986, vol. 3A, 332 pages.
 Extended European Search Report for Application No. 11797712.4, dated Jun. 21, 2017, 9 pages.
- * cited by examiner

















Fig. 3










Fig. 7.a




Fig. 7.b




Fig. 7.c




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21

COMBINATIONAL SCISSOR-GRASPER TOOL FOR USE IN LAPAROSCOPY

This United States patent application claims the benefit under 35 U.S.C. §§ 119 and 120 and is a continuation of U.S. patent application Ser. No. 13/503,773 (filed Jun. 22, 2011) (now granted as U.S. Pat. No. 8,870,902), which is the U.S. National Stage Entry of International Application No. PCT/IB2011/052723 (filed Jun. 22, 2011), which claimed priority from Indian Patent Application Number 1852/MUM/2010 (filed on Jun. 23, 2010).

FIELD OF THE INVENTION

The present invention generally relates to art of surgical tools and more specifically to the architecture and operation of a bifunctional scissor-grasper tool capable of being used in minimally invasive surgical procedures such as laparoscopy.

BACKGROUND OF THE INVENTION

Past few decades have seen vast development as to surgical procedures—minimally invasive surgery being one of the prime advances of this era. Minimally invasive surgeries, such as arthroscopic surgery and laparoscopic surgery, recently have become widely practiced surgical procedures. Such procedures have gained rapid popularity and generally are preferable over the traditional open surgery which requires cutting large incisions through the skin, muscles and membranes to open and expose the body cavity, thereby necessitating longer hospitalization stays and prolonged recovery periods. In minimally invasive surgery, small incisions are made into which tubular conduits, such as cannulae and trocars, are inserted and directed to the site of the operable internal organ or tissue. One or more surgical instruments are introduced, each through individual tubular conduits in order to perform the surgical procedure. It would be obvious to the reader that said minimally invasive surgical procedures including arthroscopy, endoscopy and laparoscopy owe their realization to special tools capable of access to intended site of surgery via small incision made to body of patient and operation of which allows precise performance of intended site-specific surgical manipulations.

Cutting, grasping, suturing, cauterization, distension, stapling form commonality of operations in surgery. Minimally invasive surgery tools of art do provide individually for such functions. However, due to the singularity of function accorded by such tools available, the interchange of tools amidst operations and efforts, time required for such becomes unavoidable, besides causing opportunity for complications during repeated insertion and removal of different tools.

In laparoscopic surgery, specialized long thin tools are inserted via air-tight ports fixed on the CO₂ inflated abdomen of the patient. The operation area as seen by the endoscope is displayed on an external display where the surgeon views it. Since only a few thin holes are created for inserting tools, this type of surgery results in fewer injuries to the patient, faster healing periods and less cosmetic damage. This type of surgery requires specialized tools that are characterized by their long shafts (usually around 300 mm) and thin cross sections (usually 5-8 mm dia). These tools come in various end-tips, such as scissors, blades, graspers, etc. Procurement/maintenance costs, sterilization requirements of additional equipment are other problems faced by the medical

fraternity. Thus, development of minimum invasive surgical tools capable of plural functionality, yet maintaining accuracy, precision and ease of use, are pressing needs of art.

There have been some attempts for resolving said needs of art. Various forms of laparoscopy tools, housings for positioning instruments, extendible blades, multifunctional scissor jaw designs and the like find mention in the art. Many devices which are used commonly for grasping or cutting objects have two elements which can be moved towards one another and away from one another. The elements have surfaces which may be blunt or sharp so that an object positioned between them may be either grasped or cut when the elements are moved towards one another. Examples of such devices include tongs, tweezers, forceps, scissors, guillotines, and wire cutters. Such devices can also be adapted to dissect tissue, for example, by placing the elements of the device into or next to an object and then causing the elements to splay apart thereby dissecting the object. However, these designs have been found to suffer from drawbacks critically affecting their intended function.

U.S. Pat. No. 6,024,744 discloses a combined bipolar scissor and grasper. The instrument disclosed in this patent is a combined bipolar electrosurgical cutting and grasping instrument where the grasping surfaces are contained within the shape of a standard surgical scissor. Accuracy of operation is defined by precise positioning of these portions at site of manipulation. However, being contained within same arm, the cutting and grasping portions are invariably in same angle of motion, thus present risk of accidental cuts or clamps. Also, pivoting of the tool while being inserted is not without risk due to exposed cutting edges.

U.S. Pat. No. 5,397,325 discloses a surgical suturing device which has a tubular elongated shaft terminating into a jaw assembly at the distal end and a handle assembly at the proximal end thereof. The jaw assembly includes a first jaw member pivotally connected to a second jaw member. An actuator rod extending longitudinally within the length of said shaft is connected at its proximal end to said handle assembly and is pivotally connected at its distal end to said jaw assembly. The underside of said first jaw member is provided with a cupped recess having a wheel assembly disposed therein. The wheel assembly includes a needle mount for securely retaining a needle and is configured such that the needle lies within the cupped recess when the jaw members are closed and can be deployed in a protracted position away from the first jaw member when the jaw members are in an open position. In operation, the suturing device offers superior control over both the needle and the tissue to be sutured.

The above mentioned invention suffers from drawback of limited degree of operation due to configuration wherein only one jaw is movable and the other fixed. The said single shaft device presented finds utility for function of suturing having adequate needle control, however, does not offer means to grasp and stabilize the tissue, which is slippery by nature thus mandating that the tissue tending to evade needle carrier manipulation must be grasped by a second instrument. As a result, the surgeon encounters difficulty in controlling and positioning both the needle and the tissue simultaneously, and the patient can suffer complications such as frayed tissue, errant punctures, inadequate stitches, extended surgical duration, hemorrhaging, and the like.

U.S. Pat. No. 5,509,923 describes a device for dissecting, grasping and/or cutting an object has at least two elongate elements at least a portion of at least one of the elements is formed from a pseudoelastic material, preferably a pseudoelastic shape memory alloy. End portions of the elements

can be moved away from one another and then toward one another to dissect, grasp and/or cut an object with the elements. In certain embodiments, the device further comprises an actuating means and at least a portion of the elements and/or the actuating means is formed from a pseudoelastic material. The device is intended for applications including dissecting, grasping and/or cutting objects located in difficult to reach areas, within the body during surgery. However, the cutting/grasping members of this tool are pseudoelastic and thus, allow limited degree of choice while deciding on the angle of cut and portion of tissue being grasped. Unintentional nicks and pinches cannot be ruled out are limitations in rotational ability of the tool proposed.

Laparoscopic Scissor Grasper, a product by Interventional and Surgical Innovations LLC is a minimally invasive surgery tool that can both cut and grasp with aid of two jaws having mated via serrations along their inner surfaces. The jaws separate along two axes apart and sideways to provide grasping and cutting functions respectively. However, this design is subject to certain shortcomings as the grasping serrations are invariably exposed while shearing. Also, pivoting of the jaws about their longitudinal axis is not possible. Also, for cutting edge to work, the chamfered edges necessarily need to press against each other. This pressure is enabled by forging a slight curvature in cutting arms being pressed at pivot by means of rivet or other tightening means. Over period of use, this arrangement loses its original construction leading to either loss of pressure of cutting arms or distancing of said cutting arms which ultimately leads to firstly loss of cutting functionality and secondly, presence of two sharpened (chamfered) edges which act as knives and can cut whether intended or not. Such occurrence, is thus compromise to application intended.

U.S. Pat. No. 5,133,727 discloses radial jaw biopsy forceps which feature a multi element head having a fixed blade juxtaposed between two grasper jaws having mated serrations along their internal edges for grip. However, this design too has shortcomings of limited scope for movement and accidental cuts to material in space between the grasping arms while performing delicate functions.

By and large, innovations cited have not been able to overcome the problems of the art. Design of a pluri-functional device for achievement of surgical operations is a pressing need of the art. The present inventor has undertaken specific research and has arrived at novel construction and operability of a device for addressing said problems of art. The following brief description presents one non-limiting embodiment of constructing and performing the present invention.

OBJECTS OF THE PRESENT INVENTION

It is an object of the present invention to provide a single shaft four-jawed laparoscopic instrument with suitable components and linkages that provide for cutting-grasping bi-functionality and construction capable of performing intended bi-functionality in a manner that allows infinite rotational ability about its longitudinal axis.

It is another object of the present invention to provide a single shaft laparoscopic instrument wherein cutting functionality is enabled via shear forces achieved at edges of jaws by their motion against each other thus avoiding open blade design altogether.

It is another object of the present invention to provide a four-jawed single shaft laparoscopic instrument wherein construction of jaws comprise integral mechanical interlock-

ing system that allows for selectable locking of two pairs of jaws each configuration serving the cutting or grasping functionalities.

It is another object of the present invention to provide a bifunctional single shaft laparoscopic instrument which reduces the amount of instrumentation necessary for surgical procedures in which both cutting and grasping is required.

It is another object of the present invention to provide a bifunctional single shaft laparoscopic instrument which reduces the amount of dexterity needed by a surgeon performing a surgical procedure in which both electrosurgical cutting and grasping is required.

It is another object of the present invention to provide a bifunctional single shaft laparoscopic instrument which is easily amenable to common art pre-surgical sterilization techniques.

It is another object of the present invention to provide a bifunctional single shaft laparoscopic instrument which is capable of repeated use thus decreasing the amount of medical waste generated in surgical procedures.

It is yet another object of the present invention to provide for a minimally invasive surgical tool which efficiently combines functions of cutting, grasping and overcomes overall drawbacks of prior art devices.

It is also an object of the present invention to achieve accurate fine cuts or shear-free firm grasp whenever intended.

It is also an object of the present invention to provide grasping and cutting surfaces which are independent of each other.

These and further objects shall present themselves to the reader upon description presented herein below along with accompanying drawings.

SUMMARY OF THE PRESENT INVENTION

In accordance with principles of the present invention, a single shaft laparoscopic instrument is proposed which has cutting/grasping bi-functionality. Said bi-functionality is enabled by achieving two user-selectable configurations of four specially constructed jaw members. Design of these jaw members comprises an integral mechanical interlocking system and linkage which, when operated by the user, results in two movable elements each comprising a pair of jaws. In one configuration where linkage allows for sliding of the movable elements against each other, cutting function is achieved. In other configuration where linkage allows for movement of the movable elements away from and towards each other, the grasping functionality is achieved.

The invention may be more fully understood by reference to the cited figures and details of exemplary embodiments. Alternative embodiments of the invention as claimed, and providing the benefits of the novel concepts of the invention, are contemplated and will be obvious from the explanations hereinafter.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of the preferred embodiment of the present invention showing the jaws in the closed position locked in the scissor configuration.

FIG. 2 is a perspective view of the preferred embodiment of the present invention showing the jaws in the closed position locked in the scissor configuration, but with two of the jaws not visible, so as to show the inner locking mechanism of the instrument.

FIG. 3 is a perspective view of the laparoscopic instrument proposed by the present invention with a magnified view of the four-jawed tip shown in inset.

FIGS. 4 (*a,b,c*) are schematic representation of inter-play between two jaw pairs when in grasping configuration.

FIGS. 5 (*a,b,c*) are schematic representation of inter-play between two jaw pairs when in cutting configuration.

FIGS. 6 (*a,b,c*) are side, front perspective and back perspective views of jaw element **002/004** of the laparoscopic instrument proposed by the present invention.

FIGS. 7 (*a,b,c*) are side, front perspective and back perspective views of identical jaw element **001/003** of the laparoscopic instrument proposed by the present invention.

FIG. 8 illustrates the hinge, described as element **005** in FIGS. 4 and 5

FIG. 9 illustrates the connecting link that enables force to get transmitted to jaw elements **001** and **003**.

FIG. 10 illustrates the inner shaft that connects to the connecting link shown in FIG. 9.

FIG. 11 illustrates the hinge member that resides within the distal end of the inner shaft.

FIG. 12 illustrates the pin that allows the connecting link to hinge with jaws **001** and **003**.

FIG. 13 illustrates the shifter shaft that engages the jaw elements **002** and **004** in order to push them forward or pull them backward in order to respectively convert the tool from the grasper mode to scissor mode or the other way round.

FIG. 14 illustrates the outer holder of the tool that holds all the jaws together on the hinge **005**, and attaches to the outer shaft **009**.

FIG. 15 illustrates the side view of the proposed instrument in the grasper configuration, with the jaws in open position. Outer holder is hidden in this view.

FIG. 16 illustrates the side view of the proposed instrument in the grasper configuration, with the jaws in closed position. Outer holder is hidden in this view.

FIG. 17 illustrates the side view of the proposed instrument in the scissor configuration, with the jaws in closed position. Outer holder is hidden in this view.

FIG. 18 illustrates the side view of the proposed instrument in the scissor configuration, with the jaws in open position. Outer holder is hidden in this view.

FIG. 19 illustrates a close-up perspective view of the inner mechanism of the instrument in the scissor configuration with the jaws in closed position. Outer holder is hidden in this view.

FIG. 20 illustrates a close-up perspective view of the inner mechanism of the instrument in the grasper configuration with the jaws in closed position. Outer holder is hidden in this view.

FIG. 21 illustrates a perspective view of the inner mechanism of the instrument in the grasper configuration, with the jaws in closed position and the connecting links visible. Outer holder and shifter shaft are hidden in this illustration.

The invention may be more fully understood by reference to the cited figures and details of exemplary embodiments. Alternative embodiments of the invention as claimed, and providing the benefits of the novel concepts of the invention, are contemplated and will be obvious from the explanations hereinafter.

DETAILED DESCRIPTION OF THE INVENTION

The laparoscopic procedure generally involves creating small incisions through the navel and through the abdominal wall for viewing and operating on internal areas of the body,

such as the uterus, ovaries, gall bladder and appendix. Typically, a trocar tube is introduced through the navel incision for receiving a camera, magnifying lens or other fiber optic device for viewing the surgery. One or more additional trocar tubes are introduced through incisions in the abdominal wall such that laparoscopic surgical tools can be inserted through the tube(s) for manipulating, cutting and/or suturing an internal organ or tissue. In this manner, while viewing a video monitor via the fiber optic device positioned in the navel trocar, the surgeon can grasp an organ or tissue with one surgical tool and simultaneously cut or suture with another surgical device.

The evolution of minimally invasive surgery has given rise to the need of single-shaft surgical instruments which can be inserted through a trocar and easily manipulated by a surgeon. These instruments are fashioned such that they can be inserted lengthwise through the trocar and comprise hand-held controls on the proximal end thereof to operate the distal, tissue-manipulating end of said instrument. Single shaft devices must have a sufficiently small diameter so that they can be inserted into a trocar tube and guided to the operative tissue site. Typically, such instruments are designed to perform one function, such as grasping and stabilizing tissue, cutting tissue, holding a suturing needle or pulling a suturing needle through tissue, suctioning and irrigating the fluids, cauterizing the tissue, coagulating blood vessels and so on. A major drawback to minimally invasive surgery is that it requires exceptional motor coordination to grasp and stabilize an organ or tissue with one surgical tool and performing a cutting or suturing procedure on said organ or tissue with a second surgical device, all while viewing a two dimensional video monitor. This disadvantage is particularly acute in performing a laparoscopic suturing procedure.

FIG. 1 is a schematic side perspective view of the four jawed tip of the laparoscopic instrument proposed by the present invention. Also, FIG. 2 illustrates elements structurally integral to the jaws of the laparoscopic instrument proposed by the present invention which provide for interlocking action. Explanation as to construction of the laparoscopic tool subject of the present invention is now attempted referring to both these figures. The combinational scissor-grasper tool **000** comprises a bullet nosed end comprising four independent jaw elements **001**, **002**, **003** and **004**. Said jaw elements are in operational association with a single hinge **005** and can lock into one another by positive locking mechanism enabled by mated protrusions and depressions corresponding to protrusion **006** and depression **007** along respective inner surface of each adjacent arm-in-pair. This mechanism ensures that when motion is delivered at the hinge, at all times, a specific combination of arms moves together.

FIG. 3 illustrates magnified view of the four-jawed tip of the laparoscopic instrument proposed by the present invention. As illustrated therein, the four jawed tip **000** is key novel feature of the present invention capable of performance between both cutting and grasping functionalities via actuation of controller **008**.

FIGS. 4 (*a,b,c*) and 5 (*a,b,c*) are schematic representation of inter-play between two jaw pairs when in grasping and cutting configurations respectively. When viewed from its tip with the tool being oriented such that its hinge **005** hosting the jaw elements **001**, **002**, **003** and **004** is parallel to the floor (horizontal), locking of jaw **001** with **004** and jaw **002** with **003** respectively to each other results in grasper configuration of the tool. In same orientation, locking of the

left side jaws **003** and **004** and right side jaws **001** and **002** respectively to each other results in the scissor configuration of the tool **000**.

FIGS. **6** (*a,b,c*) are front, perspective and back views of jaw element **002/004** of the laparoscopic instrument **000**. It may be seen that **010** is a depression into which the extension **021** illustrated later in FIG. **7.a** enters while the instrument is in the scissor configuration. Generally referring to FIGS. **6** to **17**, it may be seen that the shape associated with the depression **010** is intended to mate with shape associated with extension **021** so that the two elements can snugly slide into one another. **011** is an arc section having its geometric centre at point **012** which is geometrically mimicked on the inner arc of extension **021** thus allowing the extension **021** to slide over arc section **011** smoothly. This motion is later described in FIG. **15**. Points **012** and **013** determine the endpoints of slot **027**. The hinge **005** fits into the slot **027**. Along the slot **027** jaws **004** and **002** can slide backward and forward such that either points **012** or **013** align with central axis of hinge **005**, to enable the instrument to function as a grasper or as a scissor, respectively. Jaws **004** or **002** can rotate about hinge **005** either about point **012** or point **013**. Arcs **014** and **015** define a slot **020**. The arc **014** has its geometric centre at point **013**, while the arc **015** has its geometric center at point **012**. Protrusion **038** is positioned within the slot **020**. Arcs **015** and **016** define the handle **028**. The arc **016** has its geometric centre at point **013**. This handle gets positioned into the depression **039**. When the instrument shifts from grasper to scissor position, the shifter shaft **043** moves forward, towards the distal direction. During this forward motion, the proximal vertical surface **046** of the depression **039** pushes against the surface **016**. At the same time, the distal surface **048** pushes against surface **014**. This pushes the jaws **004** and **002** forward, towards the distal direction such that they slide on hinge **005** along their respective slots **027** taking them from being hinged about point **012** to being hinged about point **013**. As a result of this motion, the protrusion **021** in jaws **001** and **003** gets inserted into depression **010** in jaws **002** and **004** respectively, thus locking jaw **001** to **002** and jaw **003** to **004**. During the same motion, the protrusion **006** in jaws **001** and **003** slides out of the depression **007** in jaws **004** and **002** respectively, thus removing the lock between jaws **002** and **003** and between jaws **001** and **004**. This is the scissor configuration. When the instrument shifts back from scissor to the grasper configuration, the shifter shaft **043** moves backwards, towards the proximal end. During this motion, the distal vertical surface **047** of depression **039** engages with the surface **015**. This pulls the jaws **004** and **002** backwards, towards the proximal direction such that they slide on hinge **005** along their respective slots **027** taking them from being hinged about point **013** to being hinged about point **012**. As a result of this motion, the protrusion **021** in jaws **001** and **003** gets removed from depression **010** in jaws **002** and **004** respectively, thus unlocking jaw **001** from **002** and jaw **003** from **004**. During the same motion, the protrusion **006** in jaws **001** and **003** slides into the depression **007** in jaws **004** and **002** respectively, thus engaging the lock between jaws **002** and **003** and between jaws **001** and **004**. This is the grasper configuration. Thus, the protrusion **021** and depression **010** form a male-female pair to lock the device in the scissor configuration. The protrusion **006** and depression **007** form another male-female pair to lock the device in the grasper configuration. This switching mechanism between grasper and scissor

configurations is shown between FIG. **16** to FIG. **17** as a side view and also between FIG. **20** and FIG. **19** as a close-up perspective view.

When the instrument is in the scissor configuration, the jaws **004** and **002** rotate about the point **013** on hinge **005**. In this configuration, the shifter shaft **043** has kept the jaws **004** and **002** pushed in this position. Hence, the surfaces **046** and **048** slide over surfaces **016** and **014** respectively. As the jaws **004** and **002** rotate about point **013**, it is essential that the arcs **014** and **016** have their geometric centers at point **013**. When the instrument is in the grasper configuration, the jaws **004** and **002** rotate about the point **012** on hinge **005**. In this configuration, the shifter shaft **043** has kept the jaws **004** and **002** pulled in this position. Hence, the surface **047** slides over surface **015**. As jaws **004** and **002** rotate about point **012**, it is essential that the arc **015** has its geometric centre at point **012**.

While shifting between scissor and grasper configurations, a single stroke motion engages one lock and disengages the other. The serrated surfaces **017** of jaws **004** or **002** and serrated surfaces **026** of jaws **001** and **003** are used for the grasping action. The distance between each tooth of the serrated surfaces **017** and **026** is greater than or equal to the distance between points **012** and **013**. While the tool jaws are in the closed position and the tool needs to be shifted between scissor and grasper configurations in either direction, this particular distance between the teeth on serrated surfaces **017** and **026** ensures that jaw **004** can slide over jaw **003** and jaw **002** can slide over jaw **001**, without letting the teeth physically interfere with each other.

According to another aspect of the present invention, edge **018** of jaws **004** or **002** is hardened and angled to create a sharp shearing edge. As shown in FIG. **5.b** and FIG. **18**, the edge **018** in jaw **004** moves against the edge **018** of jaw **002** to create the necessary shearing action required for the instrument to function as a scissor.

The serrated surfaces **017** and **026** are physically distinct and independent of the shearing edge **018**. This makes it possible to pick a great variety of grasping serration independently of a variety of scissor edge. Thus, a large number of combinations of different scissor and grasper types are possible to be incorporated in the instrument.

According to another aspect of the present invention, the handle **028** is created with a step **019** such that the depression **039** can be accommodated with the protrusion **038** positioned in the slot **020**.

The protrusion **021** is of a shape comprising an arc with the geometric centre at point **023**. This curvature also matches with the curvature of depression **010**. The depression **022** is of a shape comprising an arc with the geometric centre at point which is offset towards the distal end of the tool from point **023** by a distance that is equal to the distance between points **012** and **013**. This is also the distance by which the shifter shaft **043** moves while switching between the scissor and grasper mechanisms. Point **023** is the position of a hole in jaws **001** or **003** in which the hinge **005** resides. Jaws **001** and **003** always rotate about the axis through point **023**.

The connecting link **034** hinges to the jaws **001** and **003** at the hole **024** using pin **037**. Pin **037** can be in the form of a rivet that joins holes **033** and **024**. A step **025** accommodates the thickness of the connecting link **034**. Inner shaft **045** has a means of connecting with link **034** by a pin **031** at holes **032** and **035**. The pin **031** can be in the form of a rivet.

The entire system of the inner shaft **045** connected to jaws **001** and **003** by means of connecting links **034** hinged respectively at **032** and **033** by pins **031** and **037**, is shown in FIG. **21**. The jaws **001** and **003** are forced to open by a simple parallelogram mechanism when the inner shaft **045** is moved forward in the distal direction. The connecting links **034** and the distance between points **023** to **024** on jaws **001** and **003** form the segments of this parallelogram mechanism. The user's action at element **008** creates this required motion in **045**. When the proposed surgical tool is in the grasper configuration, the protrusion **006** in jaws **001** and **003** locks in with depression **007** in jaws **004** and **002** respectively, thus locking jaws **001** and **004** together on one hand, and jaws **002** and **003** on the other. At this time the protrusion **021** in jaws **001** and **003** and depression **010** in jaws **002** and **004** are no longer engaged. When the jaws **001** and **003** are forced to open up by the parallelogram mechanism movement initiated by the user acting on inner shaft **045**, they also, in turn force jaws **004** and **002** to move along with them respectively. This creates the grasper configuration as shown in FIG. **15** and FIGS. **4.a**, **4.b**, **4.c**.

When the tool is in the scissor configuration, the protrusion **021** in jaws **001** and **003** locks in with depression **010** in jaws **002** and **004** respectively, thus locking jaws **001** and **002** together on one hand, and jaws **004** and **003** on the other. At this time the protrusion **006** in jaws **001** and **003** and depression **007** in jaws **004** and **002** respectively are no longer engaged. When the jaws **001** and **003** are forced to open up by the parallelogram mechanism movement initiated by the user acting on inner shaft **045**, they also, in turn force jaws **002** and **004** to move along with them respectively. This creates the scissor configuration as shown in FIG. **18** and FIGS. **5.a**, **5.b**, **5.c**.

Thus, when the instrument is in the grasper configuration, jaw **004** locks with jaw **001** while jaw **003** locks with jaw **002**. On the other hand, when the instrument is in the scissor configuration, the jaw **004** locks with jaw **003** while jaw **001** locks with jaw **002**.

A step **036** is created at the distal tip of inner shaft **045** in order to accommodate the thickness of connecting link **034**. The combined widths of the section **036** and two instances of link **034** are accommodated by pin **031** within the cut out gap **040** of shifter shaft **043**. This in turn must fit within the cut out gap **041** of outer holder **044**. In this outer holder **044** the hole **042** holds the hinge **005**.

A means to provide for the backward and forward movement of the shifter shaft is created. Any standard method to achieve this in a user-friendly manner would work. Other requirements of a surgical instrument, such as the ability to rotate and fit within a 5 mm diameter, are also fulfilled.

According to another aspect of the present invention, the surfaces involved in grasping and cutting are independent of each other. Hence they may be sharpened, knurled, and formed independently for optimal performance.

Since both scissor and grasper operate about the same common hinge **005**, there is no inherent need for a 90° rotation about the tool's axis for a shift of configuration.

As described hereinabove, the mechanism for interlocking of jaw elements comprises male and female locking elements. Said interlocking elements are completely internal to the jaws themselves and thus do not interfere with the surgical environment.

According to another aspect of the present invention, the mechanism to shift between the grasper and scissor configurations is also contained completely internal to arm of the tool. It has so been designed to allow the tool to be manufactured within a 5 mm diameter. It should be appre-

ciated that the instrument can be provided with a different shape of jaws to perform other actions besides straightforward grasping and cutting. Different types of graspers, scissors can be incorporated to this mechanism. The actuation of the instrument may be carried out by either the means of a regular handle operated by hands or it can be motorized to be applied in a robotic setting. In either case the mechanism of the front tip does not change.

If the jaw members and internal mechanism members are coated with appropriate insulation layers, the function of bipolar cauterization may also be added into the tool. The bipolar cauterization will occur between the jaw elements when the instrument is in the grasper configuration.

According to yet another aspect of the present invention, the mechanism to shift between the grasper and scissor configurations operates with a strictly linear motion along the axis of the tool. Inner and outer shafts of the main shaft body **009** are separable and thus, allow for rotation along the longitudinal axis. This allows for the tool to be rotated infinitely clockwise or anticlockwise about the axis of its main shaft body **009** and thus enable a 360° field of operation.

According to another aspect of the present invention, it is intended by the present inventor to make the device of the present invention amendable to controllers of common art, thus negating design of customized control architecture and/or user interfaces. This also means easy migration between tools for surgeons.

Thus, it would be now evident to the reader that the user interface or controlling means is same for both cutting as well as grasping functions and that the selection of function is enabled via actuation of a switch which controls interlocking of pairs of jaws of the device proposed by the present invention in accordance with functionality required. This switch may be selected among common art easy switching mechanisms such as turning knobs, trigger or toggle levers. Thus, the user has ability to migrate from one mode of operation to other with single stroke of switch and without having to remove/reinsert in body of patient being operated. Further, the scissor grasper combination can be made able to withstand infinite rotation of the tool along its longitudinal axis using a common art thumbwheel. As common art controllers are utilized, the user maintains same tactile feel and dexterity while adapting to use of the proposed tool.

According to other embodiments of the present invention, the inner shafts of the tool are constructed to allow disassembly and reassembly to the main outer shaft by means chosen among press-fit, threading/screw mechanism or key-slot mechanism. This makes it possible to easily autoclave or sterilize the tip of the proposed instrument. It also allows for just the tip to be replaced without having to replace the handle or outer shaft.

According to another embodiment of the present invention, a cleaning port may be introduced in the shaft of the proposed laparoscopic tool for allowing sterilization and multiple use thereafter.

As will be realized, the present invention is capable of various other embodiments and that its several components and related details are capable of various alterations, all without departing from the basic concept of the present invention. Accordingly, descriptions will be regarded as illustrative in nature and not as restrictive in any form whatsoever. Modifications and variations of the system and apparatus described herein will be obvious to those skilled in the art. Such modifications and variations are intended to come within the scope of the appended claims.

We claim:

1. A method for operating a surgical instrument having a shifter shaft, an inner shaft, and first, second, third, and fourth jaw elements, the method comprising:

placing the surgical instrument in a cutting configuration 5
by moving the shifter shaft to a first position along a longitudinal axis to lock the first and second jaw elements relative to each other and the third and fourth jaw elements relative to each other;

while the shifter shaft is fixed in the first position, moving 10
the inner shaft back and forth along the longitudinal axis to slide the locked first and second jaw elements against the locked third and fourth jaw elements to create a shearing action;

placing the surgical instrument in a grasping configuration 15
by moving the shifter shaft to a second position along the longitudinal axis to lock the first and fourth jaw elements relative to each other and the second and third jaw elements relative to each other; and

while the shifter shaft is fixed in the second position, 20
moving the inner shaft back and forth along the longitudinal axis to move the locked first and fourth jaw elements towards the locked second and third jaw elements to create a grasping action.

2. The method of claim 1:

each of the first, second, third, and fourth jaw elements 25
comprising a serrated surface;

the method further comprising, in the cutting configura- 30
tion, engaging the serrated surfaces of the first and second jaw elements with each other, and engaging the serrated surfaces of the third and fourth jaw elements with each other.

3. The method of claim 1:

each of the first, second, third, and fourth jaw elements 35
comprising an extension and a depression;

the placing the surgical instrument in the cutting configura- 40
tion comprising coupling the first and second jaw elements to each other by the depression of the second jaw element receiving the extension of the first jaw element, and coupling the third and fourth jaw elements to each other by the depression of the fourth jaw element receiving the extension of the third jaw element; and

the placing the surgical instrument in the grasping configura- 45
tion comprising coupling the first and fourth jaw elements to each other by the depression of the fourth jaw element receiving the extension of the first jaw element, and coupling the second and third jaw elements to each other by the depression of the second jaw element receiving the extension of the third jaw element.

4. The method of claim 1, further comprising using a 55
controller to translate manual movement by an operator into the moving of the shifter shaft along the longitudinal axis.

5. The method of claim 1, further comprising opening the 60
first and third jaw elements by moving the inner shaft in a distal direction toward the first, second, third, and fourth jaw elements.

6. The method of claim 5: the inner shaft being separated 65
from the shifter shaft; the method further comprising rotating the inner shaft to rotate the first, second, third, and fourth jaw elements about the longitudinal axis.

7. The method of claim 5, further comprising disassembling 70
the inner shaft from the shifter shaft to sterilize the first, second, third, and fourth jaw elements.

8. The method of claim 1:

the placing the surgical instrument in the cutting configura-
tion being in response to a first switch actuation;

the placing the surgical instrument in the grasping configura-
tion being in response to a second switch actuation.

9. An apparatus comprising:

first, second, third, and fourth jaw elements;

an inner shaft; and

a shifter shaft movable along a longitudinal axis between
a first position and a second position, the shifter shaft
in the first position locking the first and second jaw
elements relative to each other and locking the third
and fourth jaw elements relative to each other, and the
shifter shaft in the second position locking the first and
fourth jaw elements relative to each other and locking
the second and third jaw elements relative to each
other;

wherein when the shifter shaft is fixed in the first position,
the first and second jaw elements locked relative to
each other are slidable against the third and fourth jaw
elements locked relative to each other through back and
forth movement of the inner shaft to create a shearing
action; and

wherein when the shifter shaft is fixed in the second
position, the first and fourth jaw elements locked rela-
tive to each other are movable away from and towards
the second and third jaw elements locked relative to
each other through back and forth movement of the
inner shaft to create a grasping action.

10. The apparatus of claim 9, each of the first, second,
third, and fourth jaw elements comprising a serrated surface,
the serrated surfaces of the first and second jaw elements
being configured to engage each other, and the serrated
surfaces of the third and fourth jaw elements being configured
to engage each other.

11. The apparatus of claim 10, each serrated surface
comprising a plurality of adjacent teeth, any two adjacent
teeth on a single serrated surface being separated by a
distance equal to or larger than a distance between the first
position and the second position of the shifter shaft.

12. The apparatus of claim 10, each of the first, second,
third, and fourth jaw elements further comprising a shearing
edge independent of the serrated surface.

13. The apparatus of claim 9:

each of the first, second, third, and jaw elements com-
prising an extension and a depression;

the first and second jaw elements being coupled to each
other by the depression of the second jaw element
receiving the extension of the first jaw element, and the
third and fourth jaw elements being coupled to each
other by the depression of the fourth jaw element
receiving the extension of the third jaw element, when
the shifter shaft is in the first position; and

the first and fourth jaw elements being coupled to each
other by the depression of the first jaw element receiv-
ing the extension of the fourth jaw element, and the
second and third jaw elements being coupled to each
other by the depression of the third jaw element receiv-
ing the extension of the second jaw element, when the
shifter shaft is in the second position.

14. The apparatus of claim 9, the first position being
closer to the first, second, third, and fourth jaw elements
along the longitudinal axis than the second position.

15. The apparatus of claim 9, further comprising a con-
troller coupled to an end of the shifter shaft, the controller

being configured to translate manual movement by an operator into movement of the shifter shaft along the longitudinal axis.

16. The apparatus of claim 9, further comprising a hinge coupled to the first, second, third, and fourth jaw elements, each of the first, second, third, and fourth jaw elements being configured to rotate about the hinge. 5

17. The apparatus of claim 16, each of the second and fourth jaw elements comprising a first slot along which the hinge can move in a direction parallel to the longitudinal axis. 10

18. The apparatus of claim 17, each of the second and fourth jaw elements further comprising a second slot defined by two arcs, an end of the shifter shaft being configured to engage the second slots of the second and fourth jaw elements to shift the second and fourth jaw elements relative to the hinge when the shifter shaft is moved between the first and second positions. 15

19. The apparatus of claim 9, further comprising:
a pair of connecting links each coupled to a distal end of the inner shaft, a first one of the connecting links being coupled to the first jaw element, a second one of the connecting links being coupled to the third jaw element; and
a common pin inserted through a hole in the first jaw element and through a hole in the third jaw element. 20 25

* * * * *

专利名称(译)	腹腔镜检查中使用的组合式剪草器工具		
公开(公告)号	US10617439	公开(公告)日	2020-04-14
申请号	US14/499418	申请日	2014-09-29
[标]申请(专利权)人(译)	直观外科手术操作公司		
申请(专利权)人(译)	Intuitive Surgical公司运营 , INC.		
当前申请(专利权)人(译)	Intuitive Surgical公司运营 , INC.		
[标]发明人	DEODHAR CHINMAY THONDIYATH ASOKAN		
发明人	DEODHAR, CHINMAY THONDIYATH, ASOKAN		
IPC分类号	A61B17/295 A61B17/3201 A61B17/00 A61B17/29		
CPC分类号	A61B17/295 A61B17/3201 A61B2017/2938 A61B2017/00353 A61B2017/2926		
优先权	1852MUM2010 2010-06-23 IN PCT/IB2011/052723 2011-06-22 WO		
其他公开文献	US20170303951A9 US20160089176A1		
外部链接	Espacenet		

摘要(译)

公开了一种用于腹腔镜检查的四爪组合剪刀式抓取手术工具。切割和抓握功能分别通过一对这样的特殊轮廓的钳口构件相对于另一对滑动或张开而移动而实现。还公开了用于实现钳口构件的选择性互锁和用于由人类使用者致动的机械连接的装置。

