



US008608769B2

(12) **United States Patent**
Kahle et al.

(10) **Patent No.:** **US 8,608,769 B2**
(45) **Date of Patent:** **Dec. 17, 2013**

(54) **BLADELESS OPTICAL OBTURATOR**

(75) Inventors: **Henry Kahle**, Rancho Santa Margarita, CA (US); **Arkadiusz A. Strokosz**, Rancho Santa Margarita, CA (US); **Kimball B. McGinley**, Rancho Santa Margarita, CA (US); **Scott V. Taylor**, Rancho Santa Margarita, CA (US); **Gary M. Johnson**, Rancho Santa Margarita, CA (US); **John R. Brustad**, Rancho Santa Margarita, CA (US)

(73) Assignee: **Applied Medical Resources Corporation**, Rancho Santa Margarita, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/565,972**

(22) Filed: **Aug. 3, 2012**

(65) **Prior Publication Data**
US 2012/0316595 A1 Dec. 13, 2012

Related U.S. Application Data

(63) Continuation of application No. 13/085,194, filed on Apr. 12, 2011, now Pat. No. 8,267,952, which is a continuation of application No. 10/956,167, filed on Oct. 1, 2004, now Pat. No. 7,947,058, which is a continuation-in-part of application No. 10/489,403, filed as application No. PCT/US02/06759 on Mar. 4, 2002, now Pat. No. 7,686,823.

(60) Provisional application No. 60/324,613, filed on Sep. 24, 2001, provisional application No. 60/508,390, filed on Oct. 3, 2003.

(51) **Int. Cl.**
A61B 17/00 (2006.01)

(52) **U.S. Cl.**
USPC **606/190; 604/264**

(58) **Field of Classification Search**

USPC 606/159, 167, 185, 190; 604/264; 600/164.12, 564
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

RE682 E 4/1838 Peall
184,573 A 11/1876 Becker

(Continued)

FOREIGN PATENT DOCUMENTS

BE 1 006 811 12/1994
CA 2 170 841 9/1997

(Continued)

OTHER PUBLICATIONS

Co-Pending U.S. Appl. No. 10/489,403, filed Mar. 11, 2004; Title: Bladeless Obturator.

(Continued)


Primary Examiner — Victor Nguyen

(74) *Attorney, Agent, or Firm* — Rimas T. Lukas

(57) **ABSTRACT**

A surgical access device comprising a tissue separating obturator suitable for connection with a cannula is disclosed. The obturator includes an elongate shaft having a transparent distal tip. The elongate shaft extends along a longitudinal axis and defines a lumen. The transparent distal tip has a tapered configuration and includes an inner surface and an outer surface adapted for penetrating tissue. The lumen is sized and configured to receive an optical instrument such as a laparoscope. The surgical access device further includes a scope lock at the proximal end of the shaft portion. The lock includes a multi-fingered collet coaxial with the lumen. The inner diameter of the collet is smaller than an outer diameter of the optical instrument and the fingers of the collet provide frictional engagement with the outer diameter of the optical instrument that is inserted into the lumen of the obturator.

17 Claims, 23 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

224,513 A	2/1880	Burdon	4,803,999 A	2/1989	Liegner
396,754 A	1/1889	Mayfield	4,813,400 A	3/1989	Washizuka et al.
764,322 A	7/1904	Wiegand	4,850,393 A	7/1989	Lashomb
1,147,408 A	7/1915	Kelis	4,895,431 A	1/1990	Tsujluchi et al.
1,672,258 A	6/1928	Hippenmeyer	4,901,142 A	2/1990	Ikuno et al.
1,727,495 A	9/1929	Wappler	4,956,143 A	9/1990	McFarlane
1,845,727 A	2/1932	Slaughter	4,959,067 A	9/1990	Muller
2,102,274 A	12/1937	Larimore	4,972,827 A	11/1990	Kishi et al.
2,189,343 A	2/1940	Fritz	4,978,350 A	12/1990	Wagenknecht
2,301,338 A	11/1942	Smith	5,017,057 A	5/1991	Kruygor
2,434,594 A	1/1948	Schultz	5,030,210 A	7/1991	Alchas
2,441,143 A	5/1948	Gracey	5,041,100 A	8/1991	Rowland et al.
2,646,701 A	7/1953	Lietin	5,057,082 A	10/1991	Burchette, Jr.
2,699,770 A	1/1955	Fourestier et al.	5,066,288 A	11/1991	Deniego et al.
2,764,148 A	9/1956	Sheldon	5,098,379 A	3/1992	Conway
2,764,149 A	9/1956	Sheldon	5,098,388 A	3/1992	Kulkashi et al.
2,769,355 A	11/1956	Henry	5,104,316 A	4/1992	McSpadden
2,877,368 A	3/1959	Sheldon	5,104,388 A	4/1992	Quackenbush
2,932,294 A	4/1960	Fourestier et al.	5,104,389 A	4/1992	Deem et al.
3,005,468 A	10/1961	Erwin et al.	5,114,407 A	5/1992	Burbank
3,021,834 A	2/1962	Sheldon	5,116,547 A	5/1992	Tsukahara et al.
3,033,226 A	5/1962	Allen	5,144,942 A	9/1992	Decarie et al.
3,042,022 A	7/1962	Sheldon	5,147,376 A	9/1992	Pianetti
3,224,320 A	12/1965	Knudsen	5,159,920 A	11/1992	Condon et al.
3,277,922 A	10/1966	Eisel	5,163,941 A	11/1992	Garth et al.
3,357,433 A	12/1967	Fourestier et al.	5,178,186 A	1/1993	Levasseur
3,385,553 A	5/1968	Braun	5,186,972 A	2/1993	Williams et al.
3,417,745 A	12/1968	Sheldon	5,197,955 A	3/1993	Stephens et al.
3,437,747 A	4/1969	Sheldon	5,207,656 A	5/1993	Kranys
3,459,189 A	8/1969	Alley et al.	5,217,441 A	6/1993	Shichman
3,556,085 A	1/1971	Takahashi	5,221,163 A	6/1993	Nishimura
3,613,684 A	10/1971	Sheridan	5,240,397 A	8/1993	Fay et al.
3,653,338 A	4/1972	Sauey	5,246,425 A	9/1993	Hunsberger et al.
3,791,379 A	2/1974	Storz	5,250,068 A	10/1993	Ideguchi et al.
3,817,251 A	6/1974	Hasson	5,256,149 A	10/1993	Banik et al.
3,821,956 A	7/1974	Gordhamer	5,258,003 A	11/1993	Ciaglia
3,870,036 A	3/1975	Fiore	5,269,316 A	12/1993	Spitainy
3,961,621 A	6/1976	Northved	5,271,380 A	12/1993	Riek et al.
3,971,385 A	7/1976	Corbett	5,279,567 A	1/1994	Ciaglia et al.
3,994,287 A	11/1976	Turp	5,288,290 A	2/1994	Brody
3,994,301 A	11/1976	Agris	5,290,276 A	3/1994	Sewell
4,028,987 A	6/1977	Wilson	5,290,585 A	3/1994	Elton
207,932 A	9/1978	Alvord	5,300,033 A	4/1994	Miller
4,112,932 A	9/1978	Chiulli	5,334,150 A	8/1994	Kaali
4,126,291 A	11/1978	Gilbert et al.	5,342,382 A	8/1994	Brinkerhoff
4,150,929 A	4/1979	Brandt	5,350,364 A	9/1994	Stephens et al.
4,168,882 A	9/1979	Hopkins	5,366,446 A	11/1994	Tal et al.
4,180,068 A	12/1979	Jacobsen et al.	5,370,624 A	12/1994	Edwards et al.
4,191,191 A	3/1980	Auburn	5,372,588 A	12/1994	Farley
4,222,375 A	9/1980	Martinez	5,374,253 A	12/1994	Burns, Sr. et al.
4,248,214 A	2/1981	Hannah et al.	5,380,291 A	1/1995	Kaali
4,254,762 A	3/1981	Yoon	5,387,197 A	2/1995	Smith
4,269,192 A	5/1981	Matsuo	5,389,077 A	2/1995	Melinyshin et al.
4,274,771 A	6/1981	Nishimura	5,391,153 A	2/1995	Haber et al.
4,285,618 A	8/1981	Shanley	5,391,248 A	2/1995	Brain
4,299,230 A	11/1981	Kubota	5,392,766 A	2/1995	Masterson et al.
4,311,138 A	1/1982	Sugarman	5,405,328 A	4/1995	Vidal et al.
4,319,563 A	3/1982	Kubota	5,407,427 A	4/1995	Zhu et al.
4,356,826 A	11/1982	Kubota	5,431,151 A	7/1995	Riek et al.
4,386,179 A	5/1983	Sterling	5,441,041 A	8/1995	Sauer et al.
4,414,966 A	11/1983	Stednitz	5,443,484 A	8/1995	Kirsch et al.
4,429,856 A	2/1984	Jackson	5,445,615 A	8/1995	Yoon et al.
4,436,519 A	3/1984	O'Neill	5,454,791 A	10/1995	Tovey et al.
4,493,444 A	1/1985	Deli et al.	5,480,410 A	1/1996	Cuschieri et al.
4,498,902 A	2/1985	Ash et al.	5,510,065 A	4/1996	McFarlane
4,524,805 A	6/1985	Hoffman	5,540,711 A *	7/1996	Kieturakis et al. 606/192
4,535,773 A	8/1985	Yoon	5,542,845 A	8/1996	Jenkins
4,535,808 A	8/1985	Hoffman	5,549,546 A	8/1996	Schneider et al.
4,537,593 A	8/1985	Alchas	5,551,947 A	9/1996	Kaai
4,567,882 A	2/1986	Heller	3,279,460 A	10/1996	Sheldon
4,601,710 A	7/1986	Moll	5,562,695 A	10/1996	Nobles et al.
4,607,619 A	8/1986	Seike et al.	5,562,696 A	10/1996	Nobles et al.
4,750,877 A	6/1988	McFarlane	5,569,291 A	10/1996	Privitera
4,762,130 A	8/1988	Fogarty et al.	5,569,292 A	10/1996	Scwemberger et al.
4,779,613 A	10/1988	Hashiguchi et al.	5,577,993 A	11/1996	Zhu et al.
			5,591,186 A	1/1997	Wurster et al.
			5,591,192 A	1/1997	Privitera et al.
			5,593,402 A	1/1997	Patrick
			5,603,720 A	2/1997	Kieturakis

(56)

References Cited

U.S. PATENT DOCUMENTS

5,609,562 A	3/1997	Kaali	6,468,228 B1	10/2002	Topel et al.
5,609,604 A	3/1997	Schwemberger et al.	6,478,806 B2	11/2002	McFarlane
5,613,954 A	3/1997	Nelson et al.	6,508,759 B1	1/2003	Taylor et al.
5,622,462 A	4/1997	Gakhar et al.	6,520,939 B2	2/2003	Lafontaine
5,630,805 A	5/1997	Ternamian	6,656,160 B1	12/2003	Taylor et al.
5,634,908 A	6/1997	Loomas	6,656,198 B2	12/2003	Tsontou et al.
5,658,236 A	8/1997	Sauer	6,685,630 B2	2/2004	Sauer et al.
5,662,615 A	9/1997	Blake, III	6,764,107 B1	7/2004	Obahi et al.
5,662,673 A	9/1997	Kieturakis	6,770,731 B2	8/2004	Mason et al.
5,676,611 A	10/1997	Foster	6,835,201 B2	12/2004	O'Heeron
5,685,820 A	11/1997	Riek et al.	6,884,253 B1	4/2005	McFarlane
5,695,462 A	12/1997	Sutcu et al.	6,887,194 B2	5/2005	Hart et al.
5,697,947 A	12/1997	Wolf	6,902,541 B2	6/2005	McNally et al.
5,720,730 A	2/1998	Blake, III	6,939,296 B2	9/2005	Ewers et al.
5,720,761 A	2/1998	Kaali	7,008,979 B2	3/2006	Schottman et al.
5,735,867 A	4/1998	Golser et al.	7,037,303 B2	5/2006	Beaufore et al.
5,738,628 A	4/1998	Sierocuk	7,056,294 B2	6/2006	Khairkahan et al.
5,743,881 A	4/1998	Demco	7,056,329 B2	6/2006	Kerr
5,746,734 A	5/1998	Domandy, Jr. et al.	7,070,586 B2	7/2006	Hart et al.
5,752,970 A	5/1998	Yoon et al.	7,182,752 B2	2/2007	Stubbs
5,759,185 A	6/1998	Grinberg	7,344,519 B2	3/2008	Wing et al.
5,779,697 A	7/1998	Glowa et al.	7,370,709 B2	5/2008	Williamson, Jr.
5,785,693 A	7/1998	Halinig	7,470,255 B2	12/2008	Sterns et al.
5,792,112 A	8/1998	Hart et al.	7,563,250 B2	7/2009	Wenchell
5,797,888 A	8/1998	Yoon et al.	7,686,823 B2	3/2010	Pingleton et al.
5,797,944 A	8/1998	Nobles et al.	7,708,713 B2	5/2010	Albrecht et al.
5,817,061 A	10/1998	Goodwin	7,758,603 B2	7/2010	Taylor et al.
5,817,062 A	10/1998	Flom et al.	7,794,644 B2	9/2010	Taylor et al.
5,836,957 A	11/1998	Shulz	7,811,253 B2	10/2010	Hart et al.
5,842,971 A	12/1998	Yoon	7,942,862 B2	5/2011	Hart et al.
5,860,996 A	1/1999	Urban et al.	7,947,058 B2	5/2011	Kahle et al.
5,865,809 A	2/1999	Moening et al.	8,007,477 B2	8/2011	Johnson et al.
5,871,474 A	2/1999	Hermann et al.	8,028,395 B2	10/2011	Taylor et al.
5,876,202 A	3/1999	Berlin	8,075,530 B2	12/2011	Taylor et al.
5,882,340 A	3/1999	Yoon 604/164.12	8,105,285 B2	1/2012	Hart et al.
5,884,639 A	3/1999	Chen	8,128,590 B2	3/2012	Albrecht et al.
5,891,013 A	4/1999	Thompson	8,152,828 B2	4/2012	Taylor et al.
5,893,865 A	4/1999	Swindle	8,267,952 B2	9/2012	Kahle et al.
5,904,699 A	5/1999	Schwemberger et al.	8,282,663 B2	10/2012	Smith
5,913,818 A	6/1999	Co et al.	8,292,853 B2	10/2012	Hart et al.
5,922,351 A	7/1999	Daher	8,317,815 B2	11/2012	Mastri et al.
5,924,452 A	7/1999	Szpapa et al.	8,377,090 B2	2/2013	Taylor et al.
5,941,852 A	8/1999	Dunlap et al.	8,382,663 B2	2/2013	Taylor
5,957,884 A	9/1999	Hooven	2002/0013597 A1	1/2002	McFarlane
5,957,888 A	9/1999	Hinchliffe	2002/0026207 A1	2/2002	Stellon et al.
5,968,060 A	10/1999	Kellogg	2002/0133188 A1	9/2002	O'Heeron et al.
5,976,079 A	11/1999	Volz et al.	2002/0183715 A1	12/2002	Mantell et al.
5,976,168 A	11/1999	Chin	2002/0183775 A1	12/2002	Tsontou et al.
5,980,809 A	11/1999	Crain et al.	2003/0023201 A1	1/2003	Aboul-Hosn
5,984,941 A	11/1999	Wilson	2003/0032755 A1	2/2003	Gomey et al.
6,001,084 A	12/1999	Riek	2003/0059263 A1	3/2003	Chen
6,007,481 A	12/1999	Riek et al.	2003/0187471 A1	10/2003	Cooper
6,007,544 A	12/1999	Kim	2004/0015185 A1	1/2004	Ewers et al.
6,019,776 A	2/2000	Preissman	2004/0082969 A1	4/2004	Kerr
6,024,551 A	2/2000	Yamaguchi	2004/0093000 A1	5/2004	Kerr
6,030,406 A	2/2000	Davis	2004/0093018 A1	5/2004	Johnson et al.
6,043,310 A	3/2000	Liu et al.	2004/0106942 A1	6/2004	Taylor et al.
6,053,194 A	4/2000	Nelson et al.	2004/0108623 A1	6/2004	Deeter et al.
6,068,637 A	5/2000	Popov et al.	2004/0167559 A1	8/2004	Taylor et al.
6,077,481 A	6/2000	Ichida et al.	2004/0199127 A1	10/2004	Jensen et al.
6,092,551 A	7/2000	Bennett	2004/0204671 A1	10/2004	Stubbs et al.
6,168,355 B1	1/2001	Wardell	2004/0230155 A1	11/2004	Blanco et al.
6,179,528 B1	1/2001	Wardell	2004/0230217 A1	11/2004	O'Heeroon
6,203,559 B1	3/2001	Davis	2004/0254517 A1	12/2004	Quiroz-Mercado et al.
6,203,745 B1	3/2001	Wachsmann et al.	2005/0033246 A1	2/2005	Ahlberg et al.
6,221,061 B1	4/2001	Engelson et al.	2005/0038466 A1	2/2005	O'Heeron et al.
6,228,059 B1	5/2001	Astarita	2005/0332237	2/2005	Herrera
6,228,063 B1	5/2001	Aboul-Hosn	2005/0059865 A1	3/2005	Kahle
6,270,484 B1	8/2001	Yoon	2005/0065543 A1	3/2005	Kahle et al.
6,302,873 B1	10/2001	Moening	2005/0107803 A1	5/2005	Guanche
6,319,266 B1	11/2001	Stellon	2005/0107816 A1	5/2005	Pingleton et al.
6,346,074 B1	2/2002	Roth	2005/0113533 A1	5/2005	Shaikh et al.
6,355,014 B1	3/2002	Zadno-Azizi et al.	2005/0149094 A1	7/2005	Kasahara et al.
6,387,043 B1	5/2002	Yoon	2005/0149096 A1	7/2005	Hilal et al.
6,462,111 B1	10/2002	Singh et al.	2005/0159711 A1	7/2005	Kathrani et al.
			2005/0216028 A1	9/2005	Hart et al.
			2005/0227610 A1	10/2005	Zukor et al.
			2005/0273133 A1	12/2005	Schluzas et al.
			2005/0283122 A1	12/2005	Nordgren

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0288622 A1 12/2005 Albrecht et al.
 2006/0030755 A1 2/2006 Ewers et al.
 2006/0030870 A1 2/2006 Staudner
 2006/0041270 A1 2/2006 Lenker et al.
 2006/0047284 A1 3/2006 Gresham
 2006/0058570 A1 3/2006 Rapach et al.
 2006/0074374 A1 4/2006 Gresham
 2006/0118189 A1 6/2006 Tekulve et al.
 2006/0224174 A1 10/2006 Smith et al.
 2006/0264991 A1 11/2006 Johnson
 2007/0027453 A1 2/2007 Hart et al.
 2007/0075465 A1 4/2007 Taylor et al.
 2007/0088277 A1 4/2007 McGinley
 2007/0239108 A1 10/2007 Albrecht et al.
 2008/0065021 A1 3/2008 Jenkins et al.
 2008/0086074 A1 4/2008 Taylor et al.
 2008/0086093 A1 4/2008 Steppe et al.
 2009/0030375 A1 1/2009 Franer et al.
 2009/0137943 A1 5/2009 Steams et al.
 2009/0187079 A1 7/2009 Albrecht et al.
 2009/0281500 A1 11/2009 Acosta et al.
 2010/0025045 A1 2/2010 Lake et al.

FOREIGN PATENT DOCUMENTS

DE 0365049 12/1922
 DE 1616107 4/1971
 DE 2218901 10/1973
 DE 2538758 3/1977
 DE 2929233 1/1980
 DE 2922239 12/1980
 DE 4020956 1/1991
 DE 4133073 4/1992
 DE 4035146 5/1992
 DE 4116648 11/1992
 DE 29503750 4/1995
 DE 29521431 4/1997
 DE 19541041 5/1997
 DE 19718086 11/1998
 DE 19819432 11/1999
 EP 0135364 3/1985
 EP 0312787 4/1989
 EP 0347140 12/1989
 EP 0369936 5/1990
 EP 0369937 5/1990
 EP 0474124 3/1992
 EP 0548612 6/1993
 EP 0556056 8/1993
 EP 0664992 8/1995
 EP 0724864 8/1996
 EP 1074224 2/2001
 EP 1582158 10/2005
 EP 2229897 9/2010
 EP 2233090 9/2010
 FR 1370580 8/1964
 GB 2 124 970 2/1984
 GB 186 005 9/1992
 GB 2 313 316 11/1997
 JP 408127661 5/1996
 JP 2001-137253 5/2001
 SU 0942730 7/1982
 SU 1328658 8/1987
 SU 1329769 8/1987
 WO WO 93/25148 12/1993
 WO WO 94/11040 5/1994
 WO WO 96/01074 A2 1/1996
 WO WO 96/01132 1/1996
 WO WO 96/10361 4/1996
 WO WO 97/40758 11/1997
 WO WO 98/33536 8/1998
 WO WO 99/02089 1/1999
 WO WO 99/15084 4/1999
 WO WO 00/18306 4/2000
 WO WO 00/54648 9/2000

WO WO 01/01847 1/2001
 WO WO 01/01871 1/2001
 WO WO 01/08563 2/2001
 WO WO 02/01998 1/2002
 WO WO 02/34108 5/2002
 WO WO 02/41795 5/2002
 WO WO 03/026512 4/2003
 WO WO 03/032819 4/2003
 WO WO 03/096879 11/2003
 WO WO 2004/037097 5/2004
 WO WO 2004/093699 11/2004
 WO WO 2005/063134 7/2005
 WO WO 2007/093957 8/2007

OTHER PUBLICATIONS

Co-Pending U.S. Appl. No. 10/514,313, filed Nov. 12, 2004; Title: Blunt Tip Obturator.

Co-Pending U.S. Appl. No. 11/170,567, filed Jun. 29, 2005; Title: Insufflating Optical Surgical Instrument.

U.S. Appl. No. 10/745,262, filed Dec. 23, 2003; Title: Catheter With Conduit Traversing Tip.

Co-Pending U.S. Appl. No. 11/868,883, filed Oct. 8, 2007; Title: Visual Insufflation Port.

Co-Pending U.S. Appl. No. 10/346,846, filed Jan. 17, 2003; Title: Surgical Access Apparatus and Method.

Co Pending U.S. Appl. No. 10/805,864, filed Mar. 22, 2004; Title: Surgical Access Port and Method.

The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US04/032346, dated Feb. 24, 2009.

European Patent Office, Supplementary European Search Report, for European Patent Application No. EP 04 79 3965, dated Apr. 16, 2010. International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US04/32346, mailed May 20, 2008.

U.S. Appl. No. 10/745,262, filed Dec. 23, 2003; Title: "Catheter With Conduit Traversing Tip" (abandoned).

Co-Pending U.S. Appl. No. 12/750,372, filed Mar. 30, 2010, title: "Bladeless Obturator".

Co-Pending U.S. Appl. No. 11/549,872, filed Oct. 16, 2006, title: "Surgical Devices, Systems and Methods Thereof Having Gel Material, Gel Coatings, or Gel Lubricants".

Co-Pending U.S. Appl. No. 13/565,972, filed Aug. 3, 2012, title: "Bladeless Optical Obturator".

Co-Pending U.S. Appl. No. 13/356,260, filed Jan. 23, 2012, title: "Insufflating Optical Surgical Instrument".

Co-Pending U.S. Appl. No. 13/078,750, filed Apr. 1, 2011 title "Surgical Access Apparatus and Method".

Co-Pending U.S. Appl. No. 12/569,652, filed Sep. 29, 2009; title "First-Entry Trocar System".

Co-Pending U.S. Appl. No. 12/359,964, filed Jan. 26, 2009, title: "Insufflating Access System".

Co-Pending U.S. Appl. No. 13/462,330, filed May 2, 2012, title: "Low-Profile Surgical Universal Access Port".

Co-Pending U.S. Appl. No. 13/411,244, filed Mar. 2, 2012, title: "Blunt Tip Obturator".

Co-Pending U.S. Appl. No. 13/586,825, filed Aug. 15, 2012, title: "Blunt Tip Obturator".

Co-Pending U.S. Appl. No. 11/868,883; filed Oct. 8, 2007; Title: "Visual Insufflation Port".

International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US04/032346, dated May 20, 2008.

International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2005/022716 mailed Nov. 22, 2005.

International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2006/060013, mailed Apr. 24, 2008.

International Bureau of WIPO, The International Preliminary Report on Patentability for International Application No. PCT/US2009/058792, titled First Entry Trocar System, dated Mar. 29, 2011.

(56)

References Cited

OTHER PUBLICATIONS

International Bureau of WIPO, The International Preliminary Report on Patentability for International Application No. PCT/US2007/080724, titled "Visual Insufflation Port", dated Apr. 7, 2009.

International Bureau of WIPO, The International Preliminary Report on Patentability for International Application No. PCT/US2009/32026, titled "Insufflating Access System", dated Jul. 27, 2010.

International Bureau of WIPO, The International Preliminary Report on Patentability for International Application No. PCT/US2004/000695, titled "Surgical Access Apparatus and Method", dated Jul. 22, 2005.

International Bureau of WIPO, The International Preliminary Report on Patentability for International Application No. PCT/US2004/04883, titled "Surgical Access Apparatus and Method", dated Sep. 9, 2005.

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US2004/000695, titled "Surgical Access Apparatus and Method", mailed Jan. 12, 2005.

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US2004/04883, titled "Surgical Access Apparatus and Method", mailed Mar. 31, 2005.

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US2002/06759, titled "Bladeless Obturator", mailed Jul. 12, 2002.

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US2005/022716, titled "Insufflating Optical Surgical Instrument", mailed Nov. 22, 2005.

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US04/32346, titled "Bladeless Optical Obturator", mailed May 20, 2008.

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US2009/32026, titled "Insufflating Access System", mailed Mar. 23, 2009.

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US2007/080724, titled "Visual Insufflation Port", mailed Apr. 16, 2008.

International Searching Authority/US, International Search Report and The Written Opinion of the International Searching Authority dated May 27, 2009, for International Application No. PCT/US2009/037863, titled "Instrument Seal with Inverting Shroud", mailed May 27, 2009.

The International Searching Authority, The International Search Report and the Written Opinion for International Application No. PCT/US2009/058792, titled "First Entry Trocar System", mailed Dec. 23, 2009.

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US2012/036119, titled "Low-Profile Surgical Universal Access Port", mailed Nov. 7, 2012.

European Patent Office, Supplementary European Search Report for European Patent Application No. EP 04 70 1731 based on International Application No. PCT/US2004/000695, titled "Surgical Access Apparatus and Method", dated Apr. 11, 2007.

European Patent Office, Supplementary European Search Report for European Patent Application No. EP 02706494.8, titled "Bladeless Obturator", dated Jun. 24, 2008.

European Patent Office, Supplementary European Search Report for European Patent Application No. EP 03753017.7, titled "Blunt Tip Obturator", dated Nov. 21, 2008.

European Patent Office, Supplementary European Search Report for European Patent Application No. EP 04712378, titled "Surgical Access Apparatus and Method", dated May 19, 2008.

European Patent Office, Supplementary European Search Report for European Patent Application No. EP 07843973.4, titled "Visual Insufflation Port" dated Oct. 4, 2008.

European Patent Office, Supplementary European Search Report for European Patent Application No. EP 04793965.7, titled "Bladeless Optical Obturator", dated Apr. 16, 2010.

European Patent Office, Supplementary European Search Report for European Patent Application No. EP 11154547.1, titled "Blunt Tip Obturator", dated Mar. 22, 2011.

European Patent Office, European Search Report for European Application No. 11191191.3, titled "Bladeless Obturator" dated Feb. 29, 2012.

European Patent Office, European Search Report for European Application No. 11191179.8, titled "Bladeless Obturator", dated Feb. 21, 2012.

European Patent Office, European Search Report for European Application No. 11191193.9, titled "Bladeless Obturator", dated Mar. 5, 2012.

European Patent Office, European Search Report for European Application No. 11191187.1, titled "Bladeless Obturator", dated Feb. 23, 2012.

European Patent Office, European Search Report for European Application No. 11191184.8, titled "Bladeless Obturator", dated Feb. 23, 2012.

European Patent Office, European Search Report for European Application No. 11191189.7, titled "Bladeless Obturator", dated Feb. 24, 2012.

European Patent Office, European Search Report for European Application No. 11191175.6, titled "Bladeless Obturator", dated Feb. 21, 2012.

European Patent Office, European Search Report for European Application No. 047017314, titled "Surgical Access Apparatus and Method", dated Mar. 30, 2007.

Taut, Inc., Adapt-Asymmetrical Dilating Access Port, Geneva Illinois, Aug. 27, 2001.

Karl Storz, The Karl Storz Ternamian EndoTIP (TM) System, date: Aug. 27, 2001.

Karl Storz, Zerocart Trocar with eccentric tip, Recklinghausen, Germany, date Mar. 7, 2001.

Ethicon Endo-Surgery, Inc., Endopath Minimally Invasive Access, date: 2001.

European Patent Office, Invitation to Pay Additional Fees for International Application No. PCT/US2012/036119, titled "Low-Profile Surgical Universal Access Port", mailed Jul. 13, 2012.

European Patent Office, European Search Report for European Application No. 12187933, titled "Insufflating Optical Surgical Instrument", dated Nov. 20, 2012.

European Patent Office, European Search Report for European Application No. 12187929, titled "Insufflating Optical Surgical Instrument", dated Nov. 20, 2012.

European Patent Office, European Search Report for European Application No. 12186716.2, titled "Bladeless Optical Obturator", dated Mar. 7, 2013.

European Patent Office, European Search Report for European Application No. 12186717.0, titled "Bladeless Optical Obturator", dated Mar. 7, 2013.

European Patent Office, European Search Report for European Application No. 12186712.1, titled "Bladeless Optical Obturator", dated Mar. 7, 2013.

European Patent Office, European Search Report for European Application No. 12186720.4, titled "Bladeless Optical Obturator", dated Mar. 7, 2013.

International Searching Authority, International Search Report and Written Opinion for International Application No. PCT/US2013/023458 titled "Adaptable Obturator for Various Sized Trocars", mailed Mar. 19, 2013.



European Patent Office, European Search Report for European Application No. 12186722.0, titled "Bladeless Optical Obturator", dated Mar. 20, 2013.

European Patent Office, European Search Report for European Application No. 12186721.2, titled "Bladeless Optical Obturator", dated Mar. 22, 2013.

European Patent Office, European Search Report for European Application No. 12186723.8, titled "Bladeless Optical Obturator", dated Mar. 22, 2013.

European Patent Office, European Communication pursuant to Article 94(3) EPC for European Patent Application No. 12186717.0, titled "Bladeless Optical Obturator", dated Mar. 26, 2013.

* cited by examiner






FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6






FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37

BLADELESS OPTICAL OBTURATOR

This application is a continuation of co-pending U.S. patent application Ser. No. 13/085,194 entitled "Bladeless optical obturator" filed on Apr. 12, 2011 which is a continuation of U.S. patent application Ser. No. 10/956,167 entitled "Bladeless optical obturator" filed on Oct. 1, 2004 now U.S. Pat. No. 7,947,058 which is continuation-in-part of U.S. application Ser. No. 10/489,403, filed on Mar. 11, 2004, now U.S. Pat. No. 7,686,823, which is a 371 of International Application No. PCT/US02/06759, filed on Mar. 4, 2002 based on Provisional Application Ser. No. 60/324,613, filed on Sep. 24, 2001, and entitled "Bladeless obturator," all of which are fully incorporated herein by reference in their entirety. U.S. patent application Ser. No. 10/956,167 entitled "Bladeless optical obturator" filed on Oct. 1, 2004 further claims priority to provisional application Ser. No. 60/508,390, filed on Oct. 3, 2003, entitled "Bladeless optical obturator," which is fully incorporated herein by reference in its entirety.

BACKGROUND OF THE INVENTION**1. Field of the Invention**

This invention generally relates to trocar systems including obturators and, more specifically, to blunt tip obturators having hollow shafts for insertion of optical instruments.

2. Discussion of the Prior Art

Trocar systems have been of particular advantage in facilitating less invasive surgery across a body wall and within a body cavity. This is particularly true in abdominal surgery where trocars have provided a working channel across the abdominal wall to facilitate the use of instruments within the abdominal cavity.

The trocar systems of the past typically included a cannula, which provides the working channel, and an obturator which is used to place the cannula across the abdominal wall. The obturator is inserted into the working channel of the cannula and then pushed through the abdominal wall with a penetration force of sufficient magnitude resulting in penetration of the abdominal wall. Once the cannula is in place, the obturator can be removed.

Obturators have been developed with an attempt to reduce the penetration force of the abdominal wall. For example, sharp blades, sharp edges and piercing points have typically been used to enable the obturator to cut or pierce its way through the abdominal wall. While the sharp blades, sharp edges and piercing points have facilitated a reduced penetration force, they have also caused larger trocar site defects. These trocar site defects may have to be sutured closed resulting in increased operating room costs and procedural time. Moreover, once the abdominal wall has been penetrated, the sharp blades, sharp edges and piercing points of the obturator may still cause damage to the vessels and organs that lie within the peritoneal cavity. For example, the blades on the obturators that serve to cut tissue during insertion may also cut vessels or puncture organs that may result in patient injury or surgical complications.

In some cases, shields have been provided with the obturators in order to sense penetration of the abdominal wall and immediately shield the sharp blades, edges or piercing points. These shielding systems are typically complex and require some time to deploy and, as such, many have not been effective in protecting the vessels and organs against the sharp blades, edges or piercing points. Accordingly, there remains a need in the art for an improved bladeless obturator that separates tissue during insertion through a body wall. Moreover,

there is a need for a transparent blunt tip obturator having a hollow shaft to enable insertion of an optical instrument to view the insertion of the obturator through the body wall.

SUMMARY OF THE INVENTION

The invention is directed to a bladeless trocar obturator to separate or divaricate body tissue during insertion through a body wall. The distal tip of the bladeless obturator is constructed of a transparent material to enable visualization of tissue during the insertion of the obturator through the body wall. The bladeless obturator is configured to enable the insertion of a conventional laparoscope which typically includes an imaging element and fiber optic light fibers. During use, the bladeless obturator is first inserted into and through a trocar seal and cannula. A conventional laparoscope is then inserted into the proximal end of the bladeless obturator and advanced to the distal tip of the obturator. An endoscopic video camera is attached to the proximal end of the laparoscope and the bladeless trocar system is then axially advanced by the surgeon through the body wall, the surgeon can visually observe the tissue as it is being separated via a video monitor that is connected to the endoscopic video camera.

In one aspect, the obturator of the invention comprises a shaft extending along an axis between a proximal end and a distal end; and a bladeless tip disposed at the distal end of the shaft and having a generally tapered configuration with an outer surface, the outer surface extending distally to a blunt point with a pair of side sections having a common shape and being separated by at least one intermediate section, wherein each of the side sections extends from the blunt point radially outwardly with progressive positions proximally along the axis, and the shaft is sized and configured to receive an optical instrument having a distal end to receive an image of the body tissue. With this aspect, the tapered configuration facilitates separation or spreading of different layers of the body tissue and provides proper alignment of the tip between the layers. The side sections include a distal portion and a proximal portion, the distal portion of the side sections being twisted radially with respect to the proximal portion of the side sections. The intermediate section includes a distal portion and a proximal portion, the distal portion of the intermediate section being twisted in a first radial direction and the proximal portion of the intermediate section being twisted in a second radial direction opposite the first radial direction.

The bladeless tip can be formed from a transparent material or a translucent material. The bladeless tip can be formed from a plastic material or a glass material. The plastic material can be at least one of polycarbonate, polyphenylsulfone, polyetherimide, acrylic, and polyvinyl chloride. The bladeless obturator can be constructed such that at least one of the shaft and the tip is formed from a reusable or a disposable material. The reusable material can be a metallic material or an autoclavable polymer. The bladeless tip can be generally hollow or substantially solid to receive the distal end of the optical instrument. The bladeless tip can also be solid. The bladeless tip can further comprise at least one portion that is marked differently from the rest of the tip to serve as an indicator, for example, of depth as the tip is being inserted into the body tissue. The bladeless tip can be shaped and configured to receive the distal end of the optical instrument having an angled or non-angled lens. The bladeless tip can further comprise a ledge to provide proper positioning of the distal end of the optical instrument having an angled or non-angled lens. The bladeless tip can further comprise a bulbous section to accommodate the distal end of the angled lens optical instrument. The bladeless tip can be further coated or formed

from a soft elastomeric material. The shaft and the tip can be connected together by adhesive bonding, ultrasonic welding, snap-fitting, with a shrink tube, or by overmolding the tip over the shaft. The bladeless tip can further comprise a cutout section to provide the distal end of the optical instrument with direct vision of the body tissue.

In another aspect of the invention, the bladeless obturator further comprises a lock disposed at the proximal end of the shaft to frictionally lock the optical instrument in an axial position in the shaft. The lock operates to prevent the optical instrument from moving axially relative to the shaft while allowing the optical instrument to rotate freely about the shaft. The lock can be constructed from a plastic material including polycarbonate. The lock can be a multi-finger collet having an inner diameter smaller than an outer diameter of the optical instrument wherein the fingers of the collet spread open during insertion of the optical instrument providing frictional engagement with the outer diameter of the optical instrument. The lock can further comprise a camming member to constrict the optical instrument in the axial position relative to the shaft. The camming member may be a horizontal or vertical camming member. In another aspect, the lock can further comprise a locking collar to rotationally lock the optical instrument. In yet another aspect, the lock can further comprise a locking nut and thread that frictionally engage the optical instrument in the axial position relative to the shaft, or an elastomeric element that facilitates frictional engagement with the optical instrument in the axial position relative to the shaft.

In another aspect of the invention, the bladeless obturator further comprises a cap disposed at the proximal end of the shaft. The cap may further comprise a handle.

In yet another aspect of the invention, a surgical obturator adapted to separate body tissue is disclosed comprising a shaft extending along an axis between a proximal end and a distal end; and a bladeless tip disposed at the distal end of the shaft having a tapered surface forming proximally into an outer surface, the outer surface including a pair of generally opposed sections, wherein the outer surface has a generally geometric shape in progressive radial cross-sections from a distal cross-section to a proximal cross-section, wherein the pair of generally opposed sections of the outer surface appears as a pair of lines in each of the progressive radial cross-sections, wherein at least one of the pair of lines becomes more arcuate in the progressive radial cross-sections, and wherein the shaft is sized and configured to receive an optical instrument having a distal end to receive an image of the body tissue. With this aspect, the area of the geometric shape increases along the progressive radial cross-sections.

In another aspect of the invention, a surgical obturator adapted to separate body tissue is disclosed comprising a shaft having a proximal end and a distal end; and a transparent bladeless tip disposed at the distal end of the shaft having a tapered surface forming proximally into an outer surface, the outer surface extending distally to a blunt point, wherein the shaft is sized and configured to receive an optical instrument having a distal end to receive an image of the body tissue.

In yet another aspect of the invention, an optical separator adapted to receive an image of a body tissue and to separate the body tissue is disclosed comprising an optical instrument having a proximal end and a distal end; and a bladeless tip removably attached at the distal end of the optical instrument and having a generally tapered configuration with an outer surface, the outer surface extending distally to a blunt point.

These and other features of the invention will become more apparent with a discussion of the various embodiments in reference to the associated drawings.

DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included in and constitute a part of this specification, illustrate the embodiments of the invention and, together with the description, explain the features and principles of the invention. In the drawings:

FIGS. 1A and 1B illustrate side views of a trocar system including a cannula with associated valve housing, and an obturator with a blunt tip extending through the working channel of the cannula to facilitate placement across the abdominal wall;

FIG. 2 is a side elevation view of the blunt tip of the obturator of the invention;

FIG. 3 is a side elevation view of the blunt tip taken along line 3-3 of FIG. 2;

FIG. 4 is an end view taken along line 4-4 of FIG. 2;

FIG. 5 is a radial cross-section view taken along line 5-5 of FIG. 2;

FIG. 6 is a radial cross-section view taken along line 6-6 of FIG. 2;

FIG. 7 is a radial cross-section view taken along line 7-7 of FIG. 2;

FIG. 8 is a radial cross-section view taken along line 8-8 of FIG. 2;

FIG. 9 is a radial cross-section view taken along line 9-9 of FIG. 2;

FIG. 10 is a schematic view illustrating each of the FIGS. 4-9 super-imposed to facilitate an understanding of the blunt tip and its twisted configuration;

FIG. 11 illustrates a side view of a bladeless obturator of the invention having a tip formed as a blunt tapered shape;

FIG. 12 illustrates a side view of a bladeless obturator of the invention having a tip formed as a pyramidal shape;

FIG. 13 illustrates a side view of a bladeless obturator of the invention having a fully radiused tip;

FIGS. 14 and 15 illustrate a side view and a cross-section view, respectively, of the trocar system of FIGS. 1A and 1B and further illustrating the insertion of a laparoscope;

FIG. 16 illustrates a side view of a bladeless obturator of the invention having a bulbous tip;

FIG. 17 illustrates a side view of a bladeless obturator of the invention having a tip with a cutout section;

FIG. 18 illustrates a side view of a bladeless obturator of the invention having a shaft with a cutout section;

FIG. 19 illustrates a side view of a bladeless obturator of the invention and a cover for the cutout section of the shaft of FIG. 18;

FIGS. 20 and 21 illustrate side views of a bladeless obturator of the invention having a laparoscope lock;

FIGS. 22 and 23 illustrate side views of a bladeless obturator of the invention including a cap with pistol-grip handle;

FIGS. 24 and 25 illustrate the locking mechanism between the bladeless obturator and the trocar seal of the invention;

FIGS. 26 and 27 illustrate the release mechanism between the bladeless obturator and the trocar seal of the invention;

FIG. 28 illustrates a top view of a laparoscope lock of the invention comprising a multiple-finger collet;

FIG. 29 illustrates an optical instrument having a transparent bladeless tip of the invention;

FIGS. 30 and 31 illustrate a top view and a side view, respectively, of a laparoscope lock of the invention comprising a camming member;

FIGS. 32 and 33 illustrate a top view and a side view, respectively, of a laparoscope lock of the invention comprising a clamping member;

5

FIGS. 34 and 35 illustrate a top view and a side view, respectively, of a laparoscope lock of the invention comprising a locking collar; and

FIGS. 36 and 37 illustrate a top view and a side view, respectively, of a laparoscope lock of the invention comprising a locking nut and thread.

DESCRIPTION OF THE INVENTION

A trocar system is illustrated in FIG. 1 and is designated by reference numeral 10. This system includes a cannula 12, defining a working channel 14, and a valve housing 16. The system 10 also includes an obturator 18 having a shaft 21 extending along an axis 23. A handle 25 is disposed at a proximal end of the shaft 21 while a blunt tip 27 is disposed at a distal end of the shaft 21. The shaft 21 of the obturator 18 is sized and configured for disposition within the working channel 14 of the cannula 12. With this disposition, the obturator 18 can be placed across a body wall such as the abdominal wall to provide the cannula 12 with access across the wall and into a body cavity, such as the peritoneal or abdominal cavity. The blunt tip 27 serves to direct the obturator 18 through the abdominal wall and the peritoneum, and can be removed with the obturator 18 once the cannula 12 is operatively disposed with the working channel 14 extending into the abdominal cavity. The diameter of the shaft 21 can range from about 3 mm to about 20 mm and is designed to fit within a trocar seal and the cannula 12.

In accordance with the present invention, the tip 27 is provided with a blunt tip configuration. The blunt tip 27 of the invention takes into account the anatomical configuration of the abdominal wall with an improved structural design and method of insertion. To fully appreciate these aspects of the invention, it is helpful to initially discuss the anatomy associated with the abdominal wall. The abdominal wall typically includes a skin layer and a series of muscle layers, in addition to fat and fascia. The muscle layers are each defined by muscle fibers that extend generally parallel to each other in a direction that is different for each of the layers. For example, fibers of a first muscle layer and a second muscle layer may extend in directions that are generally 90 degrees off of each other.

Having noted the directional nature of the muscle fibers, it can be appreciated that such a structure may be separated or divaricated by an obturator having a blunt tip. The blunt tip may also include a twisted rectangular configuration to facilitate movement between the muscle fibers and layers. That is, the blunt tip is capable of being moved generally parallel to and between the fibers associated with a particular muscle layer.

As described earlier, the fibers of the muscle layers may be oriented at different angles to each other such that proper alignment of the tip 27 for separation of one layer may not necessarily result in proper alignment for separation of the next layer. For at least this reason, the obturator 18 has a blunt tip 27 to direct the obturator 18 through the different layers and a rectangular configuration that is twisted slightly so that separation of a first layer begins to rotate the distal end of the blunt tip 27 into proper orientation for separation of the next layer.

The twisted configuration of the blunt tip 27 also causes the blunt tip 27 to function, for example, with the mechanical advantage of a screw thread. With this configuration, an exemplary method of placement requires that the user grip the handle 25 of the obturator 18 and twist it about the axis 23. This twisting motion in combination with the screw configuration of the blunt tip 27 converts radial movement into forward

6

ward movement along the axis 23. Thus, the user applies both a forwardly directed force as well as a radial force to move the trocar system 10 in a forward direction.

The twisted configuration of the blunt tip 27 is most apparent in the side elevation views of FIGS. 2 and 3. In this embodiment, the blunt tip 27 comprises generally of eight surfaces: two opposing surfaces 50 and 52, separated by two side surfaces 54 and 56, two end surfaces 58 and 59, a generally tapered surface 60 formed in surfaces 50 and 52 around axis 23 and extending beyond end surfaces 58 and 59, and a blunt surface 62.

The surfaces 50 and 52, side surfaces 54 and 56, and tapered surface 60 generally define the cross-section of the blunt tip 27 from blunt surface 62 to proximal end 61. This configuration can best be appreciated with reference to the cross-section views of FIGS. 4-9. In FIG. 4, the distal end of the blunt tip 27 is shown with a circle 64 having the smallest circular area and a rectangle 63 having the greatest length-to-width ratio. The rectangle 63 has a twisted, S-shaped configuration at end surfaces 58 and 59.

As views are taken along progressive proximal cross-sections, it can be seen that the circle 64 becomes larger and the rectangle 63 becomes less twisted, and the width increases relative to the length of the rectangle 63. The spiral nature of the blunt tip 27 is also apparent as the circle 64 and rectangle 63 move counterclockwise around the axis 23. This is perhaps best appreciated in a comparison of the circle 64, the rectangle 63 and the side surfaces 54 and 56 in FIG. 6 relative to that in FIG. 5. With progressive proximal positions, the circle 64 begins to expand with increasing circular area and the rectangle 63 begins to widen with a reduction in the ratio of length to width. The long sides 63' of the rectangle 63 also tend to become more arcuate as they approach a more rounded configuration most apparent in FIGS. 8 and 9. That is, the circle 64 and the rounded rectangle 63 become more circular with progressive proximal positions. Furthermore, the circle 64 expands at a lesser rate than the rectangle 63, which eventually absorbs the circle 64 as shown in FIGS. 8 and 9. In these figures, it will also be apparent that the rotation of the rectangle 63 reaches a most counterclockwise position and then begins to move clockwise. This is best illustrated in FIGS. 7-9. This back and forth rotation results from the configuration of the side surfaces 54 and 56, which in general are U-shaped as best illustrated in FIGS. 2 and 3.

The ratio of the length to width of the rectangle 63 is dependent on the configuration of the side surfaces 54 and 56, which define the short sides of the rectangle 63 as well as the configuration of the surfaces 50 and 52, which define the long sides of the rectangle 63. Again with reference to FIGS. 2 and 3, it can be seen that the side surfaces 54 and 56 are most narrow at the end surfaces 58 and 59. As the side surfaces 54 and 56 extend proximally, they reach a maximum width near the point of the most counterclockwise rotation, shown generally in FIG. 8, and then reduce in width as they approach the proximal end 61. Along this same distal to proximal path, the surfaces 50 and 52 transition from a generally flat configuration at the end surfaces 58 and 59 to a generally rounded configuration at the proximal end 61.

In the progressive views of FIGS. 5-7, the circle 64 is further designated with a lower case letter a, b or c, respectively; similarly, the rectangle 63 and the side surfaces 54 and 56 are further designated with a lower case letter a, b, c, d or e, respectively, in FIGS. 5-9. In FIG. 10, the circles 64, 64a-64c, the rectangles 63, 63a-63e and the side surfaces 54, 54a-54e and 56, 56a-56e are superimposed on the axis 23 to show their relative sizes, shapes and angular orientations.

With a generally tapered configuration at the distal end and a rectangular configuration at a distal portion of the tip, the tip 27 appears much like a flathead screwdriver having a blunt tip. More particularly, the tip 27 includes a tapered structure extending outward from the end surfaces 58 and 59 that serves to direct the obturator 18 through the tissue fibers.

In one aspect, the lengths of the end surfaces 58 and 59 may be aligned parallel with the fibers of each muscle layer. A simple back and forth twisting motion of the blunt tip 27 tends to separate the fibers along natural lines of separation, opening the muscle layer to accept the larger diameter of the cannula 12. Once the first layer is substantially separated, the tapered and twisted configuration of the blunt tip 27 directs and turns the rectangle 63 more into a parallel alignment with fibers in the next layer. Again, the blunt tip 27 and the twisting or dithering motion facilitates an easy separation of the fibers requiring a significantly reduced insertion force.

The invention facilitates a unique method of separating tissue and can be applied to any object with a blunt tip and generally flat sides. In particular, the device of the invention can be operated by rotating in alternating clockwise and counterclockwise directions while applying a downward force. When rotating in alternating directions, the tissue is moved apart and a larger opening is created for a profile of greater cross-sectional area to follow. This process continues safely as the device enters the peritoneal cavity and moves to its operative position.

When the cannula 12 is ultimately removed, the size of the opening left in the tissue is minimal. Importantly, this opening is left with a small defect that does not require suturing due to a dilating effect caused by the mere separation of fibers. Since there are no sharp blades, sharp edges or piercing points to cut tissue fibers, the healing process is shortened. It is appreciated that in other aspects of the invention, the tip of the bladeless obturator 18 can be formed as a generally tapered shape 27a with a blunt distal end as illustrated in FIG. 11, as a pyramidal shape 27b with a blunt distal end and blunt edges as illustrated in FIG. 12, and as a fully radiused tip 27c for insertion through flaccid tissue or an existing body orifice such as the urethra as illustrated in FIG. 13.

The blunt tip 27 can be formed from a translucent or a transparent material. The blunt tip 27 can be formed from a plastic material or a glass material. In one aspect, the shaft 21 and the tip 27 are formed from a transparent polycarbonate material.

Referring to FIGS. 14 and 15, the bladeless obturator 18 of the invention is designed to accommodate the insertion of a conventional laparoscope 30. In particular, the shaft 21 of the bladeless obturator 18 is hollow to allow for the insertion of the laparoscope 30 at an opening 32. The shaft 21 is sized and configured to allow the laparoscope 30 to slide within proximity of the tip 27 thus providing a viewing area through the tip 27. An endoscopic video camera (not shown) is typically connected to the laparoscope 30 and this combination is connected to a video monitor. By enabling the positioning of the conventional laparoscope 30 within the tip 27 of the bladeless obturator 18, it is possible to visually observe body tissue as it is being separated by the trocar system 10. Visualization of body tissue as it is being separated by the trocar system 10 allows a surgeon to monitor the advancement of the trocar system 10 and to avoid traumatizing vessels or organs. For example, during a laparoscopic cholecystectomy, a trocar is usually placed through the umbilicus of the patient. The placement of this trocar is typically performed in a blind fashion in that the surgeon cannot see where the tip of the trocar is as it is advanced through the abdominal wall and into the abdominal cavity of the patient. This results in a high

degree of risk that the trocar may be inadvertently advanced too far into the abdomen of the patient resulting in trauma to vital organs and/or vessels. By providing a trocar system with visualization properties, this risk is diminished as the surgeon is better able to determine when the trocar has traversed the abdominal wall.

It is appreciated that the tip 27 may be generally hollow or it may be substantially solid to receive the distal end of the laparoscope 30. In another aspect, the tip 27 may be a solid tip. The tip 27 may further comprise at least one portion that is marked differently from the rest of the tip to serve as an indicator, for example, of depth as the tip 27 is being inserted into the body tissue. The at least one portion may be opaque or marked with a different color from the rest of the tip 27.

The shaft 21 and the tip 27 of the bladeless obturator 18 can accommodate a laparoscope with a non-angled lens, also known as a 0° laparoscope. The shaft 21 and the tip 27 can also accommodate a laparoscope with an angled lens such as a 30° laparoscope. The tip 27 is designed such that when either a 0° laparoscope or a 30° laparoscope is inserted therein, the lens of the laparoscope extends beyond a distal edge 36 of the cannula 12 thereby providing a clear and unobstructed view through the tip 27. The tip 27 further includes a ledge 39 that properly engages either the 0° laparoscope or the 30° laparoscope.

It should be noted that conventional trocars with visualization properties typically require a 0° laparoscope for insertion of the trocars and a 30° laparoscope for viewing anatomical structures during the remainder of the laparoscopic procedure. This requires the operating staff to provide two laparoscopes for the laparoscopic procedure, which increases hospital inventory costs and surgical preparation costs relating to cleaning and sterilization of the laparoscopes. In addition, because two laparoscopes are required for the laparoscopic procedure, there is additional operating room time required during the surgical procedure to transfer the endoscopic video camera from the 0° laparoscope to the 30° laparoscope which results in increased operating room costs for the hospital.

The bladeless obturator of the present invention provides a clear unobstructed view of body tissue through either a 0° or a 30° laparoscope, therefore obviating the need for a hospital to carry the additional inventory required to provide two laparoscopes for each laparoscopic surgical procedure, and obviating the need for a hospital to clean and sterilize a second laparoscope for each laparoscopic surgical procedure, and obviating the need to transfer the endoscopic video equipment from one laparoscope to the other laparoscope during each laparoscopic surgical procedure. Referring to FIG. 16, the shaft 21 may include a tip with a bulbous section 27d to better accommodate the distal end of the angled lens laparoscope. By adding the bulbous section 27d, the distal end of the angled lens laparoscope would be closer to the tip of the obturator thereby improving visualization.

In yet another aspect of the invention, the bladeless obturator can include integral fiber optic light fiber elements and an integral imaging element within the shaft and the tip of the obturator. The bladeless obturator with integral imaging means can be formed of reusable or disposable materials.

The bladeless obturator 18 can be constructed as a single component or as multiple components such as the shaft 21 and the tip 27. If the obturator 18 is constructed as a single component, then it can be formed from either disposable or reusable materials. If the obturator 18 is constructed as two or more components, then each component can be formed from either disposable or reusable materials as desired for a particular configuration. In one aspect, the obturator 18 is constructed from a single reusable material such as metal (e.g.,

stainless steel) or an autoclavable polymer to facilitate re-sterilization. In another aspect, the obturator **18** is formed from a transparent steam sterilizable reusable plastic material such as polyphenylsulfone or polyetherimide. The blunt tip **27** can also be coated or otherwise constructed from a soft elastomeric material. In such a case, the material can be a solid elastomer or composite elastomer/polymer.

It is further appreciated that the shaft **21** can be formed so as to be partially or fully flexible. With this configuration, the obturator **18** can be inserted through a passageway containing one or more curves of virtually any shape. A partially or fully flexed obturator **18** can then be used with a flexible cannula **12** allowing greater access to an associated body cavity.

The obturator **18** can include a separately molded tip **27** and a molded or extruded shaft **21** with the two components, as explained above, comprising of the same material or different materials. The tip **27** can then be attached to the shaft **21** by adhesive bonding, ultrasonic welding, snap-fitting, or with a shrink tube. The tip **27** can also be overmolded over the shaft **21** to mechanically lock the two components together. The tip **27** can be formed from a transparent material such as polycarbonate to enable visualization while the shaft **21** can be formed from either an opaque material or a transparent material. The shaft **21** can also be formed from a metal material.

In another aspect, the obturator **18** can include a disposable tip that is releasably attached to a reusable shaft **21**. In this aspect, a new tip **27** can be used for each procedure to provide optimal visualization through the tip **27** of the obturator **18** during each procedure.

Referring to FIG. **17**, there is shown a shaft **18e** in accordance with another aspect of the invention including a cutout section **100e** in the tip portion **27e** that enables direct visualization of the body tissue as the tip **27e** separates tissue fibers. By providing an obturator with cutout sections, the reflection of light from the laparoscope is minimized and the visibility of the tissue through the laparoscope is improved as compared to a design where visualization occurs through a plastic or glass window. It is appreciated that the shaft **21e** can include a single or a plurality of cutouts **100e** in the tip **27e** or along the shaft of the obturator.

Referring to FIG. **18**, there is shown a shaft **21f** in accordance with another aspect of the invention having a cutout portion **100f** along the axial axis of the shaft **21f**. The shaft **21f** has a cross-section of about $\frac{1}{2}$ -circle to about $\frac{3}{4}$ -circle and the cutout portion **100f** has a cross-section of about $\frac{1}{2}$ -circle to about $\frac{1}{4}$ -circle. An advantage of this aspect of the invention is the wall of the shaft **21f** can be a little thicker as a result of the cutout section, which makes injection molding of the shaft easier.

Referring to FIG. **19**, there is shown a cover **102f** that can be attached over the cutout portion **100f** of the $\frac{1}{2}$ -circle shaft **21f** as shown in FIG. **18**. In particular, a polycarbonate cover also with a $\frac{1}{2}$ -circle shaped cross-section can be attached to the shaft to form a tubular cross-section. An advantage of molding the tubular shaft **21f** in two pieces is increased manufacturability of the shaft **21f**. The cover **102f** can be attached to the shaft **21f** with an adhesive bond, an ultrasonic weld, a snap-fit, or with a shrink tube.

In another aspect, the obturator can be formed from two clam-shell components each including one-half of the shaft and tip configuration along the axial axis of the obturator. The two components can then be affixed together using an adhesive bond, an ultrasonic weld, an outer shrink tube, or a snap fit.

Referring to FIGS. **20** and **21**, another feature of the bladeless obturator **18** of the invention is it is designed to frictionally lock the laparoscope **30** in place using a laparoscope lock

40, which can be formed within the handle **25**. More specifically, the laparoscope lock **40** prevents the laparoscope **30** from moving axially relative to the shaft **21** of the obturator **18** during handling within the sterile field and during insertion through a body wall but enables the laparoscope **30** to rotate freely relative to the shaft **21**. This rotation of the lock **40** enables the trocar system **10** to be twisted during insertion into and through the abdominal wall while maintaining the laparoscope **30** in a fixed rotational position that provides for a stable viewing image on the video monitor.

The conventional obturators with visualization properties include means for locking the laparoscope in place but these obturators lock the laparoscope both axially and rotationally. A drawback of the conventional devices is the viewing image on the video monitor is unstable if the trocar is twisted during insertion. More specifically, with prior art obturator laparoscope locks, if the trocar is twisted back and forth in a clockwise and counter-clockwise fashion, the laparoscope also moves clockwise and counter-clockwise with the trocar resulting in an oscillating and disorienting viewing image on the video monitor. The laparoscope lock **40** of the present invention improves visualization and enables a more precise placement of the trocar within the body tissue and across the body wall as compared to obturators of the prior art while preventing inadvertent axial movement of the laparoscope during handling and use.

In another aspect of the invention as illustrated in FIGS. **20** and **21**, the bladeless obturator **18** further comprises a cap **42** that can be snap-fitted onto the proximal end of the obturator shaft **21**, after which the laparoscope lock **40** can be snap-fitted onto the end of the cap **42**. Both the cap **42** and the lock **40** can be formed of a plastic material such as polycarbonate. The obturator cap **42** can be provided with and without a pistol-grip handle. The handled version of the bladeless obturator provides a pistol-grip to ease insertion of the trocar system as illustrated in FIGS. **22** and **23**. The pistol-grip handle is designed to nest into the handle on the trocar seal to prevent excessive flexure of the handle during insertion of the trocar as illustrated in FIG. **23**. More particularly, the handled bladeless obturator includes three components comprising of an obturator shaft **21b**, an obturator cap **42b** having a pistol-grip handle **26b**, and a laparoscope lock **40b**, all of which can be injection molded out of polycarbonate. The pistol-grip handle **26b** can be formed with two components frictionally fitted together with, for example, interference pins. The interference pins can be fitted into holes in the handle **26b** to affect a frictional lock between the two components.

Referring to FIG. **24**, the bladeless obturator **18** is designed to releasably attach to a trocar seal **17** via two cantilever snap-fits **70a**, **70b**. As the obturator **18** is inserted into the trocar seal **17** and cannula **12**, the snap-fits **70a**, **70b** passively engage the trocar seal **17** and serve to axially lock the obturator **18** to the trocar seal **17** and cannula **12** (FIGS. **24** and **25**). To release the obturator **18** from the trocar seal **17** and cannula **12**, outboard tabs **72a**, **72b** on the obturator cap **42** are depressed inwardly and the obturator **18** is then free to be slidably removed as illustrated in FIGS. **26** and **27**. Referring back to FIGS. **20** and **21**, the bladeless obturator **18** includes axial key members **74** at its proximal end which are designed to mate with axial keyways on the trocar seal **17**. As the bladeless obturator **18** is inserted into the trocar seal **17** and cannula **12**, the obturator **18** is rotated slightly to align the axial key members **74** with the axial keyways and then advanced until the snap-fits **70a**, **70b** engage the trocar seal **17**. The axial key members **74** serve to rotationally lock the obturator **18** to the trocar seal **17**.

Referring to FIG. 28, there is shown another embodiment of the laparoscope lock 40c comprising a multiple-finger collet 80c comprising a plurality of fingers 82c. The multiple-finger collet 80c has an inner diameter that is smaller than the outer diameter of the laparoscope. The fingers 82c of the collet 80c spread open during insertion of the laparoscope providing frictional engagement with the outer diameter of the laparoscope. The laparoscope lock 40c is free to rotate on an obturator cap 42c, and allows the laparoscope to freely rotate relative to the shaft of the bladeless obturator.

Referring back to FIGS. 20 and 21, the obturator shaft 21 of the bladeless obturator 18 can be configured with a barb 76 at its proximal end. The barb 76 is vertically slotted to enable the shaft 21 to flex during assembly. The obturator shaft 21 may also include a plurality of keys (not shown) near its proximal end. The obturator cap 42 is configured to axially slide over the barb 76 on the obturator shaft 21 to affect a one-way snap-fit lock between the two components. This snap-fit prevents the removal of the obturator cap 42 from the obturator shaft 21. The obturator cap 42 may further include keyways (not shown) that engage the keys on the obturator shaft 21 to rotationally index the components together. The obturator cap 42 may further include a second barb (not shown) at its proximal end. The laparoscope lock 40 may include a plurality of tabs (not shown) that are designed to spread and axially slide over the second barb on the obturator cap 42 to affect a one-way snap-fit lock between the obturator cap 42 and the laparoscope lock 40. This snap-fit prevents the axial removal of the laparoscope lock 40 from the obturator cap 42. The laparoscope lock 40 is free to rotate relative to the obturator cap 42.

Referring to FIG. 29, there is shown another aspect of the invention of a laparoscope 30a having a tip 33a configured similar to that of the tip 27 of the bladeless obturator 18 described above, the tip 33a being adapted to snap-fit or frictionally engage the end of the laparoscope 30a. With this configuration, the combination of the tip 33a and the laparoscope 30a serve to form an optical obturator having a blunt tip. Once the trocar is inserted and the laparoscope removed from the trocar seal and cannula, the bladeless tip 33a can then be removed from the laparoscope 30a. The bladeless tip 33a can be formed from either a disposable or reusable transparent material. The bladeless tip 33a can be temporarily or permanently affixed to the scope 30a by any of the known methods of attaching the two components together as explained above.

Referring to FIGS. 30 and 31, there is shown a laparoscope lock 40d in accordance with another embodiment of the invention including an active lock comprising a camming member 43d. With this type of lock, the laparoscope would first be inserted into the shaft of the obturator and then the lock 40d would be activated to lock the laparoscope in an axial position relative to the shaft. The lock 40d can either rotate freely to enable the laparoscope to rotate freely relative to the shaft or the lock 40d can be rotationally fixed to prevent the laparoscope from rotating relative to the shaft. In another aspect as illustrated in FIGS. 32 and 33, a lock 40e can include an active lock comprising a clamping member 45e. With this type of lock, the laparoscope would first be inserted into the shaft of the obturator and then the lock would be activated to lock the laparoscope in an axial position relative to the shaft. The lock 40e can either rotate freely to enable the laparoscope to rotate freely relative to the shaft or the lock 40e can be rotationally fixed to prevent the laparoscope from rotating relative to the shaft.

Referring to FIGS. 34 and 35, there is shown a lock 40f in accordance with another embodiment of the invention includ-

ing an active lock comprising a locking collar 46 positioned eccentrically with respect to the axis of the obturator so that as the locking collar 46 is turned, a frictional engagement with the laparoscope is affected. The laparoscope would first be inserted into the locking collar 46 and the shaft of the obturator, the locking collar 46 can then be turned to frictionally engage the laparoscope. The laparoscope lock 40f can either rotate freely to enable the laparoscope to rotate freely relative to the shaft or the laparoscope lock 40f can be rotationally fixed to prevent the laparoscope from rotating relative to the shaft.

In another aspect of the invention as illustrated in FIGS. 36 and 37, there is shown a laparoscope lock 40g including an active lock comprising of a locking nut 48 and a thread. The threaded portion of the lock 40g has flexible elements similar to those on a collet. The laparoscope would first be inserted into the threaded portion of the lock 40g and the nut then rotated clockwise to collapse the flexible elements to frictionally engage the laparoscope. To release the laparoscope, the nut is rotated counter-clockwise.

In another aspect, the laparoscope lock can include a lock that includes an elastomeric element. The addition of the elastomeric element can enhance the frictional engagement with the laparoscope. An example of such an elastomeric element is a silicone O-ring sized with an inside diameter smaller than the outside diameter of the laparoscope. The laparoscope lock can either rotate freely to enable the laparoscope to rotate freely relative to the shaft or the laparoscope lock can be rotationally fixed to prevent the laparoscope from rotating relative to the shaft.

In yet another aspect, the obturator 18 can also be used as an insufflation needle having a passageway and valve to administer carbon dioxide or other insufflation gas to the peritoneal cavity. The obturator 18 can also be used with an insufflation needle cannula in which case removal of the obturator 18 upon entry would allow for rapid insufflation of the peritoneal cavity.

In another aspect of the invention, the bladeless obturator can be formed with a 2-3 mm outer diameter and with a small thru-hole at its distal end. The bladeless obturator can be used in conjunction with a miniaturized laparoscope to provide initial access into a hollow body cavity. Once access is obtained, the laparoscope can be removed from the bladeless obturator and an insufflation gas such as carbon dioxide can be dispensed through the obturator into the hollow body cavity. The bladeless obturator can also include holes in the tip portion to enhance the flow of insufflation gases through the obturator. More particularly, the bladeless obturator can be formed with a 2-3 mm outer diameter and used in conjunction with a miniaturized laparoscope to provide initial access into a hollow body cavity. After access is obtained, the bladeless obturator can be removed from the trocar cannula and an insufflation gas such as carbon dioxide can be dispensed through the cannula and into the hollow body cavity.

It will be understood that many modifications can be made to the disclosed embodiments without departing from the spirit and scope of the invention. For example, various sizes of the surgical device are contemplated as well as various types of constructions and materials. It will also be apparent that many modifications can be made to the configuration of parts as well as their interaction. For these reasons, the above description should not be construed as limiting the invention, but should be interpreted as merely exemplary of preferred embodiments.

The invention claimed is:

1. A surgical access device comprising:
 - a tissue separating obturator comprising:
 - an elongate shaft portion extending along a longitudinal axis and defining a first lumen between an open proximal end and a distal end; and
 - a transparent distal tip portion with an inner surface and an outer surface adapted for penetrating tissue; the distal tip portion disposed at the distal end of the shaft portion; at least part of the tip portion having a generally tapered configuration;
 - wherein the first lumen is sized and configured to receive an optical instrument having a distal end adapted to receive an image and the tip portion being adapted to permit passage of an image; and
 - a lock disposed at the proximal end of the shaft portion; the lock having a multi-fingered collet coaxial with the first lumen; wherein the collet has an inner diameter smaller than an outer diameter of the optical instrument; the fingers of the collet providing frictional engagement with the outer diameter of the optical instrument inserted into the first lumen.
2. The surgical access device of claim 1 wherein the lock is configured to allow the optical instrument to rotate freely inside and relative to the elongate shaft.
3. The surgical access device of claim 2 wherein the lock is configured to frictionally engage with the outer diameter of the optical instrument inserted into the first lumen to minimize movement of the optical instrument in the axial direction relative to the obturator.
4. The surgical access device of claim 1 further including a cannula comprising an elongate shaft extending along a longitudinal axis and defining a second lumen between an open proximal end and an open distal end; the cannula being configured to receive the obturator inside the second lumen and to connect to the obturator such that the obturator does not move axially or rotationally relative to the cannula.
5. The surgical access device of claim 1 wherein the lock is connected to the proximal end of the obturator such that the lock is free to rotate relative to the elongate shaft.
6. The surgical access device of claim 1 wherein the lock is connected to the obturator and configured such that the lock is

free to rotate relative to the elongate shaft and the optical instrument inserted into the first lumen rotates with the lock.

7. The surgical access device of claim 1 further including an obturator cap connected to the proximal end of the obturator.

8. The surgical access device of claim 7 further including a cannula comprising an elongate shaft extending along a longitudinal axis and defining a second lumen between an open proximal end and an open distal end; the cannula configured to receive the obturator inside the second lumen;

wherein the obturator cap is configured to removably connect to the proximal end of the cannula such that the obturator when connected to the cannula does not move axially or rotationally relative to the cannula.

9. The surgical access device of claim 7 wherein the lock is connected to the obturator cap.

10. The surgical access device of claim 1 further including at least one hole in the distal tip portion.

11. The surgical access device of claim 10 wherein the at least one hole in the distal tip portion is configured for delivering insufflation gases through the obturator and out the at least one hole.

12. The surgical access device of claim 1 wherein the transparent distal tip portion has a hollow chamber with the first lumen extending into the hollow chamber.

13. The surgical access device of claim 12 wherein the optical instrument is a laparoscope and the distal end of the laparoscope when inserted extends into the hollow chamber of the tip portion.

14. The surgical access device of claim 1 wherein the lock is configured to allow the shaft portion to rotate freely relative to the inserted optical instrument.

15. The surgical access device of claim 1 wherein the lock is configured to enable the shaft portion to be twisted in a back and forth motion while maintaining the optical instrument in a fixed rotational position to provide for a stable viewing image via the optical instrument.

16. The surgical access device of claim 1 wherein the inner diameter of the collet is smaller than an inner diameter of the first lumen.

17. The surgical access device of claim 1 wherein the lock is made of elastomeric material.

* * * * *

专利名称(译)	无叶光学闭孔器		
公开(公告)号	US8608769	公开(公告)日	2013-12-17
申请号	US13/565972	申请日	2012-08-03
[标]申请(专利权)人(译)	应用医疗资源		
申请(专利权)人(译)	应用医疗资源CORPORATION		
当前申请(专利权)人(译)	应用医疗资源CORPORATION		
[标]发明人	KAHLE HENRY STROKOSZ ARKADIUSZ A MCGINLEY KIMBALL B TAYLOR SCOTT V JOHNSON GARY M BRUSTAD JOHN R		
发明人	KAHLE, HENRY STROKOSZ, ARKADIUSZ A. MCGINLEY, KIMBALL B. TAYLOR, SCOTT V. JOHNSON, GARY M. BRUSTAD, JOHN R.		
IPC分类号	A61B17/00 A61B A61B17/32 A61B17/34 A61B19/00		
CPC分类号	A61B17/3417 A61B17/3496 A61B2017/3464 A61B17/3474 A61B19/5212 A61B2017/0046 A61B2017/00477 A61B2017/00907 A61B2017/320044 A61B2017/346 A61B2017/347 A61B2019/444 A61B2019/5437 A61B17/3478 A61B2017/3456 A61B17/3462 A61B90/361 A61B90/92 A61B2090/3937 A61B1/3132 A61B17/3415 A61B17/3421 A61B17/3423 A61B17/3468 A61B2017/3425 A61B2017/3445		
审查员(译)	NGUYEN , VICTOR		
优先权	10/956167 2011-05-24 US 10/489403 2010-03-30 US PCT/US2002/006759 2002-03-04 WO 60/324613 2001-09-24 US 60/508390 2003-10-03 US		
其他公开文献	US20120316595A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种外科进入装置，其包括适于与套管连接的组织分离填塞器。闭塞器包括具有透明远端尖端的细长轴。细长轴沿纵向轴线延伸并限定内腔。透明远侧末端具有锥形构造并且包括内表面和适于穿透组织的外表面。内腔的尺寸和构造适于容纳诸如腹腔镜的光学仪器。外科进入装置还包括在轴部分的近端处的窥视锁。该锁包括与内腔同轴的多指夹头。夹头的内径小于光学仪器的外径，并且夹头的指状物与插入到闭塞器的内腔中的光学仪器的外径摩擦接合。

